

Objectives

- Explain about conditional rendering in React
- Define element variables
- Explain how to prevent components from rendering

In this hands-on lab, you will learn how to:

- Implement conditional rendering in React applications

Prerequisites

The following is required to complete this hands-on lab:

- Node.js
- NPM
- Visual Studio Code

Notes

Estimated time to complete this lab: **60 minutes.**

Create a React Application named “ticketbookingapp” where the guest user can browse the page where the flight details are displayed whereas the logged in user only can book tickets.

The Login and Logout buttons should accordingly display different pages. Once the user is logged in the User page should be displayed. When the user clicks on Logout, the Guest page should be displayed.



Please sign up.

Login



Welcome back

Logout

Hint:

```
function LoginButton(props) {  
  return (  
    <button onClick={props.onClick}>  
      Login  
    </button>  
  );  
}
```

```
function LogoutButton(props) {  
  return (  
    <button onClick={props.onClick}>  
      Logout  
    </button>  
  );  
}
```

```
function Greeting(props) {  
  const isLoggedIn = props.isLoggedIn;  
  if (isLoggedIn) {  
    return <UserGreeting />;  
  }  
  return <GuestGreeting />;  
}
```

1. Create Project

```
npx create-react-app ticketbookingapp  
cd ticketbookingapp  
code .  
npm start
```

2. Folder Structure

ticketbookingapp

```
{  
  └── src  
      ├── App.js  
      ├── Greeting.js  
      ├── LoginButton.js  
      ├── LogoutButton.js  
      ├── GuestGreeting.js  
      ├── UserGreeting.js  
      └── index.js
```

3. App.js

```
import React, { useState } from "react";  
import Greeting from "../Greeting";  
import LoginButton from "../LoginButton";  
import LogoutButton from "../LogoutButton";  
  
function App() {  
  
  const [isLoggedIn, setIsLoggedIn] = useState(false);  
  
  const login = () => {  
    setIsLoggedIn(true);  
  };  
}
```

```

const logout = () => {
  setIsLoggedIn(false);
};

let button;

if (isLoggedIn) {
  button = <LogoutButton onClick={logout} />;
} else {
  button = <LoginButton onClick={login} />;
}

return (
  <div style={{ margin: "50px" }}>
    <Greeting isLoggedIn={isLoggedIn} />
    <br />
    {button}
  </div>
);
}

export default App;

```

4. Greeting.js

```

import React from "react";
import GuestGreeting from "../GuestGreeting";
import UserGreeting from "../UserGreeting";

function Greeting(props) {

  const isLoggedIn = props.isLoggedIn;

  if (isLoggedIn) {
    return <UserGreeting />;
  }

  return <GuestGreeting />;
}

export default Greeting;

```

5. LoginButton.js

```

import React from "react";

function LoginButton(props) {

  return (
    <button onClick={props.onClick}>
      Login
    </button>
  );
}

```

```
);  
}  
  
export default LoginButton;
```

6. LogoutButton.js

```
import React from "react";  
  
function LogoutButton(props) {  
  
  return (  
    <button onClick={props.onClick}>  
      Logout  
    </button>  
  );  
}  
  
export default LogoutButton;
```

7. GuestGreeting.js

```
import React from "react";  
  
function GuestGreeting() {  
  
  return (  
    <div>  
  
      <h1>Please sign up.</h1>  
  
      <h2>Flight Details</h2>  
  
      <table border="1" cellPadding="8">  
  
        <thead>  
  
          <tr>  
            <th>Flight No</th>  
            <th>Source</th>  
            <th>Destination</th>  
            <th>Fare</th>  
          </tr>  
  
        </thead>  
  
        <tbody>  
  
          <tr>  
            <td>AI101</td>  
            <td>Hyderabad</td>
```

```
        <td>Delhi</td>
        <td>₹4500</td>
      </tr>

      <tr>
        <td>6E202</td>
        <td>Chennai</td>
        <td>Mumbai</td>
        <td>₹5200</td>
      </tr>

    </tbody>

  </table>

</div>
);
}

export default GuestGreeting;
```

8. UserGreeting.js

```
import React from "react";

function UserGreeting() {

  return (
    <div>

      <h1>Welcome back</h1>

      <h2>Book Your Flight</h2>

      <table border="1" cellPadding="8">

        <thead>

          <tr>
            <th>Flight No</th>
            <th>Source</th>
            <th>Destination</th>
            <th>Status</th>
          </tr>

        </thead>

        <tbody>

          <tr>
            <td>AI101</td>
```

```

        <td>Hyderabad</td>
        <td>Delhi</td>
        <td>Available</td>
      </tr>

      <tr>
        <td>6E202</td>
        <td>Chennai</td>
        <td>Mumbai</td>
        <td>Available</td>
      </tr>

    </tbody>

  </table>

  <br />

  <button>Book Ticket</button>

</div>
);
}

export default UserGreeting;

```

9. index.js

```

import React from 'react';
import ReactDOM from 'react-dom/client';
import App from './App';

const root = ReactDOM.createRoot(document.getElementById('root'));

root.render(
  <React.StrictMode>
    <App />
  </React.StrictMode>
);

```

Output

Initially

Please sign up.

Flight Details

Login

Please sign up.

Flight Details

Flight	From	To
AI101	Hyderabad	Delhi
6E202	Chennai	Mumbai

Login

Welcome back

Ticket Booking Page

Flight	Status
AI101	Available
6E202	Available

Book Ticket

Logout