{···}

File ▾   Edit ▾   Insert ▾   Generate Server ▾   Generate Client ▾

DHL Transcomm-Data-Transformer 1.0.0 OAS3

DHL Transcomm Data Transformer Orders API Description

default   ⌃

POST   **/submitOrder**   ⌃

Submit an Order. The request body schemas are found below. For order mode = 'F' (final) or mode = 'B' (basic), we expect an Order schema format. For order mode = 'C' (cancel), we expect a CancelOrder schema format. For order mode = 'R' (return), we expect a ReturnOrder schema format

Parameters   Try it out

No parameters

Request body   application/json

Example Value   Schema

```json
{
  "msgType": "submitOrder",
  "data": {
    "orderNumber": "ORDER-S-68",
    "actionDate": "01/14/2020 10:10:00",
    "ecomBusinessCode": "12345",
    "mode": "F",
    "consigneeName": "ISMA NOOR",
    "consigneeAddress": {
      "addressLine1": "10th Floor, Plaza IBM",
      "addressLine2": "No. 1005, First Avenue",
      "POBox": "54000",
      "city": "54000",
      "country": "PK",
      "phone": "+944413344901",
      "email": "isma.noor@avanzainnovations.com"
    },
    "billTo": "ISMA NOOR",
    "billToAddress": {
      "addressLine1": "10th Floor, Plaza IBM",
      "addressLine2": "No. 1005, First Avenue",
      "POBox": "54000",
```

Responses

Code	Description	Links
200	OK	No links
400	Bad Request	No links

Code	Description	Links
422	Unprocessable Entity (Validation error)	*No links*

Media type

```
application/json
```

Example Value   Schema

```json
{
  "status": "string",
  "message": {
    "keyword": "enum",
    "dataPath": "/consigneeAddress/country",
    "schemaPath": "#/definitions/Country/enum",
    "params": {
      "allowedValues": [
        "AE",
        "BH",
        "DJ",
        "IN",
        "IQ",
        "IR",
        "KW",
        "OM",
        "PK",
        "SA",
        "SD",
        "SO",
        "YE"
      ]
    }
  }
}
```

500	Internal server error	*No links*

POST   `/confirmReturnDelivery`   ⌄

Schemas   ⋀

↵

ValidationError   {
   status   **string**
   message
                                  {

                                  }
                                  example: OrderedMap { "keyword": "enum", "dataPath": "/consigneeAddress/country",
                                  "schemaPath": "#/definitions/Country/enum", "params": OrderedMap {
                                  "allowedValues": List ["AE", "BH", "DJ", "IN", "IQ", "IR", "KW", "OM", "PK",
                                  "SA", "SD", "SO", "YE"] }, "message": "should be equal to one of the allowed
                                  values" }

}

↵

ConfirmReturnDelivery   {
   id   **string**
                                 example: vc-id-1
   msgType   **string**
                                 example: submitOrder
   data
                                  {
     orderNumber   **string**
                                        example: DEMO-ORDER-1
     ecomOrgCode   **string**
                                        example: amazonae
     invoiceNumber   **string**
                                        example: INV-2
     lineItems
                                         [{
                                         lineNo   **integer**($int32)
                                         example: 1292

example: 1292

```
                                        hscode              string
                                                            example: 20059994
                                        skuProductCode      string
                                                            example: sku1020
                                        receivedQuantity    integer($int32)
                                                            example: 1
                                        isExtra             string
                                                            example: N
                                        hsCode              string
                                                            example: 20059994
                                        quantityUOM         string
                                                            example: KG
                                        quantityReturned    integer($int32)
                                                            example: 1
                                        goodsCondition      string
                                                            example: N


                                      }]
          transportDocNo        string
                                example: HAWB38393
          returnRequestNo       string
                                example:
          gatePasses
                                      [     {
                                        gatePassNumber      string
                                                            example: GP2182
                                        gatePassDirection   string
                                                            example: I
                                        ActualMovingInDate  string
                                                            example: 15/1/2020


                                      }]
          dateOfReceivingBackGoods string
                                      example: 15/1/2020


                                    }


                              }
```

ReturnOrder   {

```
msgType        string
               example: submitOrder
data
                   {
  orderNumber      string
                   example: ORDER-S-65
  actionDate       string
                   example: 2021-08-28T17:59:27.453Z
  ecomBusinessCode string
                   example: 1100
  mode             string
                   example: R
  invoices
                       [    {
      mode             string
                       example: R
      invoiceNumber string
                       example: 12902
      exporterCode  string
                       example: AMZ_EXP_22
      returnDetails
                           {
          returnRequestNo        string
                                 example: RET22002
          returnReason           integer($int32)
                                 example: 2
          returnTransportDocNo string
                                 example: TD191022
          returnJustification    string
                                 example: Items for
                                 playground, theatre,
                                 exhibition and like events

                           }
      lineItems
                           [    {
          mode             string
                           example: R
          lineNo           integer($int32)
                           example: 11
          hscode           string
                           example: 20059994
          quantityReturned integer($int32)
                           example: 1
```

```
                                              exemptions
                                                            [     {
                                                            exemptionType  integer($int32)
                                                                           example: 1030
                                                            exemptionRefNo string
                                                                           example:
                                                                           1261202


                                                          }]


                                               }]


                                  }]


                    }


        }
```

                                                                                                                        ↩

CancelOrder   {
```
    msgType              string
                        example: submitOrder

    data
                          {
                        orderNumber         string
                                            example: ORDER-S-67

                        actionDate          string
                                            example: 2021-08-28T17:59:27.453Z
                        ecomBusinessCode    string
                                            example: 1100

                        mode                string
                                            example: C

                        invoices
                                                [...]

                      }

    }
```
                                                                                                                        ↩

Order   {

```
Order      {
    msgType string
            example: submitOrder
    data
           {
           orderNumber      string
                            example: ORDER-S-68
           actionDate       string
                            example: 01/14/2020 10:10:00
           ecomBusinessCode string
                            example: 12345
           mode             string
                            example: F
           consigneeName    string
                            example: ISMA NOOR
           consigneeAddress
                               {
                               addressLine1        string
                                                   example: 10th Floor, Plaza IBM
                               addressLine2        string
                                                   example: No. 1005, First Avenue
                               POBox               string
                                                   example: 54000
                               city                string
                                                   example: 54000
                               country             string
                                                   example: PK
                               phone               string
                                                   example: +944413344901
                               email               string
                                                   example: isma.noor@avanzainnovations.com

                               }
           billTo           string
                            example: ISMA NOOR
           billToAddress
                               {
                               addressLine1        string
                                                   example: 10th Floor, Plaza IBM
                               addressLine2        string
                                                   example: No. 1005, First Avenue
                               POBox               string
                                                   example: 54000
                               city                string
                                                   example: 54000
```

```
                                            example: 54000
                    country              string
                                            example: PK


              }
shipTo        string
              example: ISMA NOOR
shipToAddress
              {
              addressLine1         string
                                      example: 10th Floor, Plaza IBM
              addressLine2         string
                                      example: No. 1005, First Avenue
              POBox                string
                                      example: 54000
              city                 string
                                      example: 54000
              country              string
                                      example: PK


              }
invoices
              [    {
              mode                    string
                                         example: F
              invoiceNumber           string
                                         example: 12902
              invoiceDate             string
                                         example: 08/31/2020
              invoiceType             integer($int32)
                                         example: 2
              incoTerm                string
                                         example: CIF
              totalNoOfInvoicePages   integer($int32)
                                         example: 1
              paymentInstrumentType   integer($int32)
                                         example: 10
              currency                string
                                         example: AED
              totalValue              integer($int32)
                                         example: 2050
              exporterCode            string
                                         example: 12902
              FZCode                  string
```

                                                          example: 1
          warehouseCode   **string**
                                      example:
          cargoOwnership   **string**
                                      example: 1
          associatedEcomCompany **string**
                                      example:
          brokerBusinessCode   **string**
                                      example: DHL
          logisticsSPBusinessCode **string**
                                      example:
          documents
                                      [{
                                      hash   **string**
                                          example:
                                          2bce0b22d7e078f261cbc8b6a0aa37c05ec81a9ffb37ff3
                                      path   **string**
                                          example: /uat/uploadPublic/2020-6-
                                          28/2bce0b22d7e078f264c4df25db56c91b2104e03f725t
                                      name   **string**
                                          example: 44.pdf

                                      }]
          lineItems
                                      [{
                                      mode   **string**
                                          example: F
                                      lineNo   **integer**($int32)
                                          example: 11
                                      hscode   **string**
                                          example: 20059994
                                      goodsCondition   **string**
                                          example: N
                                      returnDays   **integer**($int32)
                                          example: 1
                                      description   **string**
                                          example: Tom Ford Black Faye
                                      quantity   **integer**($int32)
                                          example: 2
                                      quantityUOM   **string**
                                          example: kg
                                      netWeight   **integer**($int32)
                                          example: 2
                                      netWeightUOM   **string**

```
netweightUOM            string
                        example: kg
dutyPaid                string
                        example: N
supplementaryQuantity   string($nullable)
supplementaryQuantityUOM string($nullable)
valueOfGoods            integer($int32)
                        example: 196
countryOfOrigin         string
                        example: IR
prevDeclarationReference string($nullable)
exemptions
                           [    {

                          }]
sku
                            {
                            productCode        strin
                            examp
                            quantityUOM        strin
                            examp

                          }
discount
                            {
                            value              strin
                            percentage         integ
                            examp

                          }
permits
                           [    {

                          }]
originalValueOfItem     integer($int32)
                        example: 200
isFreeOfCost            string
                        example: N

                       }]

                  }]

          }
```

```
}
```