
http://game-review-ms.herokuapp.com/edit_game/61425afce8fd9db270fdde1d





Performance

Metrics			=
First Contentful Paint	0.8 s	Time to Interactive	0.8 s
Speed Index	0.8 s	Total Blocking Time	0 ms
Largest Contentful Paint	0.8 s	Cumulative Layout Shift	0.012

Values are estimated and may vary. The <u>performance score is calculated</u> directly from these metrics. <u>See calculator</u>.







Show audits relevant to: All FCP LCP TBT CLS

Opportunities — These suggestions can help your page load faster. They don't <u>directly affect</u> the Performance score.

Opportunity Estimated Savings

Eliminate render-blocking resources

0.58 s ^

Resources are blocking the first paint of your page. Consider delivering critical JS/CSS inline and deferring all non-critical JS/styles. Learn more. FCP LCP

✓ Show 3rd-party resources (3)

URL	Transfer Size	Potential Savings
css/materialize.min.css (cdnjs.cloudflare.com)	17.4 KiB	270 ms
css/all.css (use.fontawesome.com)	11.8 KiB	650 ms
/icon?family=Material+Icons (fonts.googleapis.com)	0.5 KiB	230 ms

Transfer Potential **URL** Savings Size 5.4 KiB 70 ms ...css/style.css (game-review-ms.herokuapp.com) Diagnostics — More information about the performance of your application. These numbers don't directly affect the Performance score. Ensure text remains visible during webfont load Leverage the font-display CSS feature to ensure text is user-visible while webfonts are loading. Learn more. FCP (LCP) Show 3rd-party resources (3) Potential **URL** Savings 660 ms ...webfonts/fa-solid-900.woff2 (use.fontawesome.com) ...v103/flUhRq6tz....woff2 (fonts.gstatic.com) 70 ms ...webfonts/fa-brands-400.woff2 (use.fontawesome.com) 680 ms Does not use passive listeners to improve scrolling performance Consider marking your touch and wheel event listeners as `passive` to improve your page's scroll performance. Learn more. Show 3rd party resources (3) Source materialize.min.js:6 materialize.min.js:6 materialize.min.js:6 Avoid chaining critical requests — 10 chains found The Critical Request Chains below show you what resources are loaded with a high priority. Consider reducing the length of chains, reducing the download size of resources, or deferring the download of unnecessary resources to improve page load. Learn more. (FCP) (LCP) Maximum critical path latency: 840 ms Initial Navigation /edit_game/61425af... (game-review-ms.herokuapp.com) ...css/materialize.min.css (cdnjs.cloudflare.com) - 40 ms, 17.37 KiB ...css/all.css (use.fontawesome.com) ...webfonts/fa-solid-900.woff2 (use.fontawesome.com) - 660 ms, 78.04 KiB ...webfonts/fa-brands-400.woff2 (use.fontawesome.com) - 680 ms, 73.00 KiB /icon?family=Material+Icons (fonts.googleapis.com) ...v103/flUhRq6tz....woff2 (fonts.gstatic.com) - 70 ms, 108.06 KiB /css2?family=Orbitron&family=Roboto&display=swap (fonts.googleapis.com) ...v17/yMJMMIlzd....woff (fonts.gstatic.com) - 10 ms, 8.48 KiB

...v27/KFOmCnqEu....woff2 (fonts.gstatic.com) - 20 ms, 10.84 KiB

...css/style.css (game-review-ms.herokuapp.com) - 20 ms, 5.38 KiB

/jquery-3.5.1.min.js (code.jquery.com) - 150 ms, 30.41 KiB

...js/materialize.min.js (cdnjs.cloudflare.com) - 30 ms, 36.38 KiB

...js/script.js (game-review-ms.herokuapp.com) - 20 ms, 2.48 KiB

Keep request counts low and transfer sizes small $\,-\,$ 15 requests $\, \cdot \,$ 478 KiB

To set budgets for the quantity and size of page resources, add a budget.json file. Learn more.

Resource Type	Requests	Transfer Size
Total	15	478.3 KiB
Font	5	278.4 KiB
Image	1	86.7 KiB
Script	3	69.3 KiB
Stylesheet	5	35.7 KiB
Document	1	8.2 KiB
Media	0	0.0 KiB
Other	0	0.0 KiB
Third-party	11	375.5 KiB

Largest Contentful Paint element — 1 element found

This is the largest contentful element painted within the viewport. Learn More (LCP)

Element



h3.center-align

Avoid large layout shifts — 5 elements found

These DOM elements contribute most to the CLS of the page. CLS

Element CLS Contribution



div.row

0.005

I	Element CL:	S Contribution			
	h3.center-align				
		0.002			
	span.underline				
		0.000			
		0.002			
	ul.right.hide-on-med-and-down				
		0.001			
	label				
		0.001			
,	Avoid long main-thread tasks — 1 long task found	^			
ı	Lists the longest tasks on the main thread, useful for identifying worst contributors to input delay. <u>Learn more</u> (TB	T			
Show 3rd party red					
ı	URL Start Time	Duration			
	/edit_game/61425af (game-review-ms.herokuapp.com) 212 ms	68 ms			
Pass	sed audits (29)	^			
	Properly size images				
	Serve images that are appropriately-sized to save cellular data and improve load time. <u>Learn more</u> .	^			
	Defer offscreen images	^			
(Consider lazy-loading offscreen and hidden images after all critical resources have finished loading to lower time	e to			
i	interactive. <u>Learn more</u> .				
I	Minify CSS	^			
	Minifying CSS files can reduce network payload sizes. <u>Learn more</u> . <u>FCP</u> <u>LCP</u>				
ı	Minify JavaScript	^			
ı	Minifying JavaScript files can reduce payload sizes and script parse time. <u>Learn more</u> . <u>FCP</u> <u>LCP</u>				
ı	Reduce unused CSS — Potential savings of 28 KiB	^			

Reduce unused rules from stylesheets and defer CSS not used for above-the-fold content to decrease bytes consumed by network activity. Learn more. (FCP) (LCP) Show 3rd party resources (2) Transfer Potential **URL** Size Savings 17.4 KiB 16.1 KiB ...css/materialize.min.css (cdnjs.cloudflare.com) 11.8 KiB 11.7 KiB ...css/all.css (use.fontawesome.com) Reduce unused JavaScript — Potential savings of 27 KiB Reduce unused JavaScript and defer loading scripts until they are required to decrease bytes consumed by network activity. Learn more. (LCP) Show 3rd-party resources (1) Transfer Potential **URL** Size Savings ...js/materialize.min.js (cdnjs.cloudflare.com) 36.4 KiB 27.2 KiB Efficiently encode images Optimized images load faster and consume less cellular data. Learn more. Serve images in next-gen formats — Potential savings of 37 KiB Image formats like WebP and AVIF often provide better compression than PNG or JPEG, which means faster downloads and less data consumption. Learn more. Show 3rd party resources (0) Potential Resource **URL** Size Savings 86.4 KiB 37.2 KiB ...images/bg_img.jpg (game-review-ms.herokuapp.com) Enable text compression — Potential savings of 11 KiB Text-based resources should be served with compression (gzip, deflate or brotli) to minimize total network bytes. Learn more. (FCP) (LCP) Show 3rd-party resources (0) Transfer Potential **URL** Savings Size /edit game/61425af... (game-review-ms.herokuapp.com) 8.0 KiB 5.5 KiB 5.1 KiB 3.6 KiB ...css/style.css (game-review-ms.herokuapp.com) 2.2 KiB 1.4 KiB ...js/script.js (game-review-ms.herokuapp.com)

Consider adding `preconnect` or `dns-prefetch` resource hints to establish early connections to important third-party origins. <u>Learn more</u>. FCP <u>LCP</u>

Preconnect to required origins

Initial server response time was short — Root document took 30 ms	^
Keep the server response time for the main document short because all other requests depend o LCP	n it. <u>Learn more</u> . FCP
	Chow 3rd-party resources (0)
URL	Time Spent
/edit_game/61425af (game-review-ms.herokuapp.com)	30 ms
Avoid multiple page redirects	^
Redirects introduce additional delays before the page can be loaded. <u>Learn more</u> . FCP LCP	
Preload key requests	^
Consider using ` <link rel="preload"/> ` to prioritize fetching resources that are currently requested la more. FCP LCP	ter in page load. <u>Learn</u>
Use HTTP/2	^
HTTP/2 offers many benefits over HTTP/1.1, including binary headers and multiplexing. Learn mo	ore.
Use video formats for animated content	^
Large GIFs are inefficient for delivering animated content. Consider using MPEG4/WebM videos PNG/WebP for static images instead of GIF to save network bytes. <u>Learn more</u> <u>LCP</u>	for animations and
Remove duplicate modules in JavaScript bundles	^
Remove large, duplicate JavaScript modules from bundles to reduce unnecessary bytes consume TBT	ed by network activity.
Avoid serving legacy JavaScript to modern browsers — Potential savings of 0 KiB	^
Polyfills and transforms enable legacy browsers to use new JavaScript features. However, many modern browsers. For your bundled JavaScript, adopt a modern script deployment strategy using detection to reduce the amount of code shipped to modern browsers, while retaining support for I More TBT	module/nomodule feature
	Show 3rd-party resources (1)
URL	Potential Savings
Preload Largest Contentful Paint image	^
Preload the image used by the LCP element in order to improve your LCP time. Learn more. LCF	
Avoids enormous network payloads — Total size was 480 KiB	^
Large network payloads cost users real money and are highly correlated with long load times. Le	arn more. (LCP)
✓ S	Show 3rd-party resources (9)
URL	Transfer Size
v103/flUhRq6tzwoff2 (fonts.gstatic.com)	108.1 KiB
images/bg_img.jpg (game-review-ms.herokuapp.com)	86.7 KiB
webfonts/fa-solid-900.woff2 (use.fontawesome.com)	78.0 KiB

URL			Transfer Size
webfonts/fa-brands-400.woff2 (use.fontawesome.com)			73.0 KiB
js/materialize.min.js (cdnjs.cloudflare.com)			36.4 KiB
/jquery-3.5.1.min.js (code.jquery.com)			30.4 KiB
css/materialize.min.css (cdnjs.cloudflare.com)			17.4 KiB
css/all.css (use.fontawesome.com)			11.8 KiB
v27/KFOmCnqEuwoff2 (fonts.gstatic.com)			10.8 KiB
v17/yMJMMIIzdwoff (fonts.gstatic.com)			8.5 KiB
Jses efficient cache policy on static assets — 0 resources found			^
A long cache lifetime can speed up repeat visits to your page. <u>Learn mo</u>	ore.		
Avoids an excessive DOM size — 122 elements			^
A large DOM will increase memory usage, cause longer <u>style calculation</u> TBT	ns, and produce co	ostly <u>layout reflows</u> . <u>Le</u>	<u>earn more</u> .
Statistic Element			Value
Total DOM Elements			122
Maximum DOM Depth span			11
Maximum Child ul#select-options-da41b9d4-6ff3-08f4-936a- Elements dropdown	-e6347fc7b801.dro	pdown-content.select	- 15
Jser Timing marks and measures			^
Consider instrumenting your app with the User Timing API to measure yexperiences. Learn more.	our app's real-wor	ld performance during	g key user
lavaScript execution time — 0.1 s			^
Consider reducing the time spent parsing, compiling, and executing JS. with this. <u>Learn more</u> . (TBT)	You may find deliv		·
		Show 3rd-party	resources (0)
URL	Total CPU Time	Script Evaluation	Script Parse
/edit_game/61425af (game-review-ms.herokuapp.com)	127 ms	47 ms	16 ms
chrome-extension://fheoggkfdfchfphceeifdbepaooicaho/content.js	56 ms	31 ms	17 ms
Minimizes main-thread work — 0.3 s			^
Consider reducing the time spent parsing, compiling and executing JS. with this. <u>Learn more (TBT)</u>	You may find delive	ering smaller JS paylo	pads helps
Category			Time Spent

Category		Time Spent
Other		85 ms
Script Parsing & Compilation		36 ms
Style & Layout		21 ms
Parse HTML & CSS		21 ms
Rendering		10 ms
Garbage Collection		2 ms
Minimize third-party usage — Third-party code blocked the main the	aroad for 0 ms	
Third-party code can significantly impact load performance. Limit th load third-party code after your page has primarily finished loading.	e number of redundant thir	d-party providers and try to
		Show 3rd-party resources (0)
Third-Party	Transfer Size	Main-Thread Blocking Time
FontAwesome CDN	163 KiB	0 ms
webfonts/fa-solid-900.woff2 (use.fontawesome.com)	78 KiB	0 ms
webfonts/fa-brands-400.woff2 (use.fontawesome.com)	73 KiB	0 ms
css/all.css (use.fontawesome.com)	12 KiB	0 ms
Google Fonts	128 KiB	0 ms
v103/flUhRq6tzwoff2 (fonts.gstatic.com)	108 KiB	0 ms
v27/KFOmCnqEuwoff2 (fonts.gstatic.com)v17/yMJMMIIzdwoff (fonts.gstatic.com)	11 KiB 8 KiB	0 ms
Cloudflare CDN		
	54 KiB	0 ms
js/materialize.min.js (cdnjs.cloudflare.com)css/materialize.min.css (cdnjs.cloudflare.com)	36 KiB 17 KiB	0 ms
jQuery CDN	30 KiB	0 ms
/jquery-3.5.1.min.js (code.jquery.com)	30 KiB	0 ms
Lazy load third-party resources with facades Some third-party embeds can be lazy loaded. Consider replacing the	em with a facade until they	are required. <u>Learn more</u> .
TBT Avoids document.write()		^
For users on slow connections, external scripts dynamically injected seconds. <u>Learn more</u> .	d via `document.write()` car	n delay page load by tens of
Avoid non-composited animations		^
Animations which are not composited can be janky and increase Cl	S. <u>Learn more</u> CLS	
Image elements have explicit width and height		^



Accessibility

These checks highlight opportunities to improve the accessibility of your web app. Only a subset of accessibility issues can be automatically detected so manual testing is also encouraged.

Contrast — These are opportunities to improve the legibility of your content. Background and foreground colors do not have a sufficient contrast ratio. Low-contrast text is difficult or impossible for many users to read. Learn more. Failing Elements span button.col.s8.m8.offset-s2.offset-m2.btn.text-shadow Names and labels — These are opportunities to improve the semantics of the controls in your application. This may enhance the experience for users of assistive technology, like a screen reader. Form elements do not have associated labels Labels ensure that form controls are announced properly by assistive technologies, like screen readers. Learn more. Failing Elements input.select-dropdown.dropdown-trigger textarea#description.materialize-textarea.white-text

	input#img_link
	input#img.file-path.validate
	or images, when used as links) that is discernible, unique, and focusable improves the een reader users. Learn more.
Failing Elements	a
	u de la companya del companya de la companya de la companya del companya de la co
	a
	a
	а
itional items to manually ch	neck (10) — These items address areas which an automated testing tool cannot cover. Lear an accessibility review.
The page has a logical tab or	

	Interactive controls are keyboard focusable	^
	Custom interactive controls are keyboard focusable and display a focus indicator. <u>Learn more</u> .	
	Interactive elements indicate their purpose and state	^
	Interactive elements, such as links and buttons, should indicate their state and be distinguishable from non-interactive elements. <u>Learn more</u> .	
	The user's focus is directed to new content added to the page	^
	If new content, such as a dialog, is added to the page, the user's focus is directed to it. <u>Learn more</u> .	
	User focus is not accidentally trapped in a region	^
	A user can tab into and out of any control or region without accidentally trapping their focus. <u>Learn more</u> .	
	Custom controls have associated labels	^
	Custom interactive controls have associated labels, provided by aria-label or aria-labelledby. <u>Learn more</u> .	
	Custom controls have ARIA roles	^
	Custom interactive controls have appropriate ARIA roles. <u>Learn more</u> .	
	Visual order on the page follows DOM order	^
	DOM order matches the visual order, improving navigation for assistive technology. <u>Learn more</u> .	
	Offscreen content is hidden from assistive technology	^
	Offscreen content is hidden with display: none or aria-hidden=true. <u>Learn more</u> .	
	HTML5 landmark elements are used to improve navigation	^
	Landmark elements (<main>, <nav>, etc.) are used to improve the keyboard navigation of the page for assistive technology. <u>Learn more</u>.</nav></main>	y.
Pa	ssed audits (12)	^
	[aria-hidden="true"] is not present on the document <body></body>	^
	Assistive technologies, like screen readers, work inconsistently when `aria-hidden="true"` is set on the document ` <body>` Learn more.</body>	
	Buttons have an accessible name	^
	When a button doesn't have an accessible name, screen readers announce it as "button", making it unusable for users who rely on screen readers. <u>Learn more</u> .	Э
	The page contains a heading, skip link, or landmark region	^
	Adding ways to bypass repetitive content lets keyboard users navigate the page more efficiently. <u>Learn more</u> .	
	Document has a <title> element</td><td>^</td></tr><tr><td></td><td>The title gives screen reader users an overview of the page, and search engine users rely on it heavily to determine if a page is relevant to their search. <u>Learn more</u>.</td><td></td></tr><tr><td></td><td>[id] attributes on active, focusable elements are unique</td><td>^</td></tr></tbody></table></title>	

All focusable elements must have a unique 'id' to ensure that they're visible to assistive technologies. Learn more.

ARIA IDs are unique

The value of an ARIA ID must be unique to prevent other instances from being overlooked by assistive technologies. <u>Learn more</u>.

Heading elements appear in a sequentially-descending order

Properly ordered headings that do not skip levels convey the semantic structure of the page, making it easier to navigate and understand when using assistive technologies. <u>Learn more</u>.

<html> element has a [lang] attribute

If a page doesn't specify a lang attribute, a screen reader assumes that the page is in the default language that the user chose when setting up the screen reader. If the page isn't actually in the default language, then the screen reader might not announce the page's text correctly. <u>Learn more</u>.

html> element has a valid value for its [lang] attribute

Specifying a valid BCP 47 language helps screen readers announce text properly. Learn more.

Lists contain only elements and script supporting elements (<script> and <template>).

Screen readers have a specific way of announcing lists. Ensuring proper list structure aids screen reader output. <u>Learn more</u>.

List items () are contained within or parent elements

Screen readers require list items (`') to be contained within a parent `' or `' to be announced properly. <u>Learn more</u>.

[user-scalable="no"] is not used in the <meta name="viewport"> element and the [maximum-scale] attribute is not less than 5.

Disabling zooming is problematic for users with low vision who rely on screen magnification to properly see the contents of a web page. <u>Learn more</u>.

Not applicable (29)

[accesskey] values are unique

Access keys let users quickly focus a part of the page. For proper navigation, each access key must be unique. Learn more.

[aria-*] attributes match their roles

Each ARIA `role` supports a specific subset of `aria-*` attributes. Mismatching these invalidates the `aria-*` attributes. <u>Learn more</u>.

button, link, and menuitem elements have accessible names

When an element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. <u>Learn more</u>.

[aria-hidden="true"] elements do not contain focusable descendents

Focusable descendents within an `[aria-hidden="true"]` element prevent those interactive elements from being available to users of assistive technologies like screen readers. <u>Learn more</u>.

ARIA input fields have accessible names When an input field doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. Learn more. ARIA meter elements have accessible names When an element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. Learn more. ARIA progressbar elements have accessible names When a 'progressbar' element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. Learn more. [role]s have all required [aria-*] attributes Some ARIA roles have required attributes that describe the state of the element to screen readers. Learn more. Elements with an ARIA [role] that require children to contain a specific [role] have all required children. Some ARIA parent roles must contain specific child roles to perform their intended accessibility functions. Learn more. [role]s are contained by their required parent element Some ARIA child roles must be contained by specific parent roles to properly perform their intended accessibility functions. Learn more. [role] values are valid ARIA roles must have valid values in order to perform their intended accessibility functions. Learn more. ARIA toggle fields have accessible names When a toggle field doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. Learn more. ARIA tooltip elements have accessible names When an element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. Learn more. ARIA treeitem elements have accessible names When an element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. Learn more. [aria-*] attributes have valid values Assistive technologies, like screen readers, can't interpret ARIA attributes with invalid values. Learn more. [aria-*] attributes are valid and not misspelled Assistive technologies, like screen readers, can't interpret ARIA attributes with invalid names. Learn more. <dl>'s contain only properly-ordered <dt> and <dd> groups, <script>, <template> or <div> elements. When definition lists are not properly marked up, screen readers may produce confusing or inaccurate output. Learn more. Definition list items are wrapped in <dl> elements

Definition list items (`<dt>` and `<dd>`) must be wrapped in a parent `<dl>` element to ensure that screen readers can properly announce them. <u>Learn more</u>.

No form fields have multiple labels

Form fields with multiple labels can be confusingly announced by assistive technologies like screen readers which use either the first, the last, or all of the labels. <u>Learn more</u>.

<frame> or <iframe> elements have a title

Screen reader users rely on frame titles to describe the contents of frames. Learn more.

Image elements have [alt] attributes

Informative elements should aim for short, descriptive alternate text. Decorative elements can be ignored with an empty alt attribute. <u>Learn more</u>.

```
<input type="image"> elements have [alt] text
```

When an image is being used as an `<input>` button, providing alternative text can help screen reader users understand the purpose of the button. <u>Learn more</u>.

The document does not use <meta http-equiv="refresh">

Users do not expect a page to refresh automatically, and doing so will move focus back to the top of the page. This may create a frustrating or confusing experience. <u>Learn more</u>.

<object> elements have [alt] text

Screen readers cannot translate non-text content. Adding alt text to `<object>` elements helps screen readers convey meaning to users. <u>Learn more</u>.

No element has a [tabindex] value greater than 0

A value greater than 0 implies an explicit navigation ordering. Although technically valid, this often creates frustrating experiences for users who rely on assistive technologies. <u>Learn more</u>.

Cells in a element that use the [headers] attribute refer to table cells within the same table.

Screen readers have features to make navigating tables easier. Ensuring `` cells using the `[headers]` attribute only refer to other cells in the same table may improve the experience for screen reader users. <u>Learn more</u>.

elements and elements with [role="columnheader"/"rowheader"] have data cells they describe.

Screen readers have features to make navigating tables easier. Ensuring table headers always refer to some set of cells may improve the experience for screen reader users. <u>Learn more</u>.

[lang] attributes have a valid value

Specifying a valid <u>BCP 47 language</u> on elements helps ensure that text is pronounced correctly by a screen reader. <u>Learn more</u>.

<video> elements contain a <track> element with [kind="captions"]

When a video provides a caption it is easier for deaf and hearing impaired users to access its information. Learn more.



Trust and Safety

A	Does not use HTTPS — 5 insecure requests found	^
	All sites should be protected with HTTPS, even ones that don't handle sensitive da where some resources are loaded over HTTP despite the initial request being serv intruders from tampering with or passively listening in on the communications between prerequisite for HTTP/2 and many new web platform APIs. Learn more.	ed over HTTPS. HTTPS prevents
		Show 3rd-party resources (0)
	Insecure URL	Request Resolution
	/edit_game/61425af (game-review-ms.herokuapp.com)	Allowed
	css/style.css (game-review-ms.herokuapp.com)	Allowed
	js/script.js (game-review-ms.herokuapp.com)	Allowed
	images/bg_img.jpg (game-review-ms.herokuapp.com)	Allowed
	images/favicon.ico (game-review-ms.herokuapp.com)	Allowed
	Failing Anchors a a	

Failing Anchors			
а			
Ensure CSP is effective against XSS attacks			
A strong Content Security Policy (CSP) significantly redu	uces the risk of cross-site script	ting (XSS) attacks. <u>Learn more</u>	
Description	Directive	Severity	
No CSP found in enforcement mode		High	
assed audits (15)			
Avoids requesting the geolocation permission on page lo	oad	,	
Users are mistrustful of or confused by sites that reques action instead. <u>Learn more</u> .	st their location without context.	Consider tying the request to a user	
Avoids requesting the notification permission on page lo	pad	,	
Users are mistrustful of or confused by sites that reques user gestures instead. <u>Learn more</u> .	t to send notifications without c	ontext. Consider tying the request to	
Avoids front-end JavaScript libraries with known security	y vulnerabilities	,	
Some third-party scripts may contain known security vul <u>Learn more</u> .	nerabilities that are easily ident	ified and exploited by attackers.	
Allows users to paste into password fields		,	
Preventing password pasting undermines good security	policy. <u>Learn more</u> .		
Displays images with correct aspect ratio		,	
Image display dimensions should match natural aspect	ratio. <u>Learn more</u> .		
Serves images with appropriate resolution			
Image natural dimensions should be proportional to the more.	display size and the pixel ratio	to maximize image clarity. <u>Learn</u>	
Page has the HTML doctype		/	
Specifying a doctype prevents the browser from switchir	ng to quirks-mode. <u>Learn more</u> .		
Properly defines charset			
A character encoding declaration is required. It can be decontent-Type HTTP response header. <u>Learn more</u> .	lone with a ` <meta/> ` tag in the	first 1024 bytes of the HTML or in the	
Avoids unload event listeners			

The 'unload' event does not fire reliably and listening for it can prevent browser optimizations like the Back-Forward Cache. Consider using the 'pagehide' or 'visibilitychange' events instead. Learn more **Avoids Application Cache** Application Cache is deprecated. Learn more. **Detected JavaScript libraries** All front-end JavaScript libraries detected on the page. Learn more. Name Version 3.5.1 jQuery Avoids deprecated APIs Deprecated APIs will eventually be removed from the browser. Learn more. No browser errors logged to the console Errors logged to the console indicate unresolved problems. They can come from network request failures and other browser concerns. Learn more Page has valid source maps Source maps translate minified code to the original source code. This helps developers debug in production. In addition, Lighthouse is able to provide further insights. Consider deploying source maps to take advantage of these benefits. Learn more. No issues in the Issues panel in Chrome Devtools Issues logged to the 'Issues' panel in Chrome Devtools indicate unresolved problems. They can come from network request failures, insufficient security controls, and other browser concerns. Open up the Issues panel in Chrome DevTools for more details on each issue. Not applicable (1) Fonts with font-display: optional are preloaded Preload 'optional' fonts so first-time visitors may use them. Learn more



SFO

These checks ensure that your page is optimized for search engine results ranking. There are additional factors Lighthouse does not check that may affect your search ranking. <u>Learn more</u>.

Content Best Practices — Format your HTML in a way that enables crawlers to better understand your app's content.

Document does not have a meta description Meta descriptions may be included in search results to concisely summarize page content. Learn more. Additional items to manually check (1) — Run these additional validators on your site to check additional SEO best practices. Structured data is valid Run the Structured Data Testing Tool and the Structured Data Linter to validate structured data. Learn more. Passed audits (8) Has a <meta name="viewport"> tag with width or initial-scale Add a `<meta name="viewport">` tag to optimize your app for mobile screens. Learn more. Document has a <title> element The title gives screen reader users an overview of the page, and search engine users rely on it heavily to determine if a page is relevant to their search. Learn more. Page has successful HTTP status code Pages with unsuccessful HTTP status codes may not be indexed properly. Learn more. Links have descriptive text Descriptive link text helps search engines understand your content. Learn more. Links are crawlable Search engines may use 'href' attributes on links to crawl websites. Ensure that the 'href' attribute of anchor elements links to an appropriate destination, so more pages of the site can be discovered. Learn More Page isn't blocked from indexing Search engines are unable to include your pages in search results if they don't have permission to crawl them. Learn more. Document has a valid hreflang hreflang links tell search engines what version of a page they should list in search results for a given language or region. Learn more. Document avoids plugins Search engines can't index plugin content, and many devices restrict plugins or don't support them. Learn more. Not applicable (5) robots.txt is valid If your robots.txt file is malformed, crawlers may not be able to understand how you want your website to be crawled or indexed. Learn more. Image elements have [alt] attributes

Informative elements should aim for short, descriptive alternate text. Decorative elements can be ignored with an empty alt attribute. <u>Learn more</u>.

Document has a valid rel=canonical

Canonical links suggest which URL to show in search results. Learn more.

Document uses legible font sizes

Font sizes less than 12px are too small to be legible and require mobile visitors to "pinch to zoom" in order to read. Strive to have >60% of page text ≥12px. <u>Learn more</u>.

Tap targets are sized appropriately

Interactive elements like buttons and links should be large enough (48x48px), and have enough space around them, to be easy enough to tap without overlapping onto other elements. <u>Learn more</u>.



Progressive Web App

These checks validate the aspects of a Progressive Web App. Learn more.

Installable

▲ Web app manifest or service worker do not meet the installability requirements — 1 reason

Service worker is the technology that enables your app to use many Progressive Web App features, such as offline, add to homescreen, and push notifications. With proper service worker and manifest implementations, browsers can proactively prompt users to add your app to their homescreen, which can lead to higher engagement. <u>Learn more</u>.

Failure reason

No manifest was fetched

PWA Optimized

▲ Does not register a service worker that controls page and start_url

The service worker is the technology that enables your app to use many Progressive Web App features, such as offline, add to homescreen, and push notifications. <u>Learn more</u>.

Does not redirect HTTP traffic to HTTPS

If you've already set up HTTPS, make sure that you redirect all HTTP traffic to HTTPS in order to enable secure web features for all your users. <u>Learn more</u>.

Is not configured for a custom splash screen Failures: No manifest was fetched.

A themed splash screen ensures a high-quality experience when users launch your app from their homescreens. <u>Learn</u> more.

Each page has a URL

media. <u>Learn more</u>.

Channel

	,,	
A	Does not set a theme color for the address bar. Failures: No manifest was fetched, No ` <meta name="theme-color"/> ` tag found.	^
	The browser address bar can be themed to match your site. <u>Learn more</u> .	
	Content is sized correctly for the viewport	^
	If the width of your app's content doesn't match the width of the viewport, your app might not be optimized for mobile screens. <u>Learn more</u> .	
	Has a <meta name="viewport"/> tag with width or initial-scale	_
	Add a ` <meta name="viewport"/> ` tag to optimize your app for mobile screens. <u>Learn more</u> .	
A	Does not provide a valid apple-touch-icon	^
	For ideal appearance on iOS when users add a progressive web app to the home screen, define an `apple-touch-icon`. It must point to a non-transparent 192px (or 180px) square PNG. <u>Learn More</u> .	
A	Manifest doesn't have a maskable icon No manifest was fetched	^
	A maskable icon ensures that the image fills the entire shape without being letterboxed when installing the app on a device <u>Learn more</u> .	.
	ditional items to manually check (3) — These checks are required by the baseline PWA Checklist but are not tomatically checked by Lighthouse. They do not affect your score but it's important that you verify them manually.	^
	Site works cross-browser	^
	To reach the most number of users, sites should work across every major browser. <u>Learn more</u> .	
	Page transitions don't feel like they block on the network	^
	Transitions should feel snappy as you tap around, even on a slow network. This experience is key to a user's perception of performance. <u>Learn more</u> .	f

Duntimo	Cattings
Runtime	Sellinus

Ensure individual pages are deep linkable via URL and that URLs are unique for the purpose of shareability on social

Runume Settings	
URL	http://game-review-ms.herokuapp.com/edit_game/61425afce8fd9db270fdde1d
Fetch Time	Sep 16, 2021, 3:35 PM GMT+1
Device	Emulated Desktop
Network throttling	40 ms TCP RTT, 10,240 Kbps throughput (Simulated)
CPU throttling	1x slowdown (Simulated)

devtools

User agent (host) Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like

Gecko) Chrome/93.0.4577.82 Safari/537.36

User agent (network) Mozilla/5.0 (Macintosh; Intel Mac OS X 10_14_6) AppleWebKit/537.36 (KHTML,

like Gecko) Chrome/90.0.4420.0 Safari/537.36 Chrome-Lighthouse

CPU/Memory Power 2209

Axe version 4.2.3

Generated by Lighthouse 8.1.0 | File an issue