

# Package ‘filesstrings’

October 20, 2018

**Type** Package

**Title** Handy File and String Manipulation

**Version** 2.7.0

**Maintainer** Rory Nolan <rorynolan@gmail.com>

**Description** This started out as a package for file and string manipulation.

Since then, the 'fs' and 'strex' packages emerged, offering functionality previously given by this package (but slightly better). Those packages have hence almost pushed 'filesstrings' into extinction. However, it still has a small number of unique, handy file manipulation functions which can be seen in the vignette. One example is a function to remove spaces from all file names in a directory.

**License** GPL-3

**Encoding** UTF-8

**LazyData** true

**Imports** magrittr, tools, purrr, checkmate, strex, matrixStats, Rcpp,  
ore, tibble, rlang

**RoxygenNote** 6.1.0

**Suggests** testthat, covr, knitr, rmarkdown, spelling

**Depends** stringr

**URL** <https://www.github.com/rorynolan/filesstrings>

**BugReports** <https://www.github.com/rorynolan/filesstrings/issues>

**VignetteBuilder** knitr

**LinkingTo** Rcpp

**Language** en-US

**NeedsCompilation** yes

**Author** Rory Nolan [aut, cre, cph] (<<https://orcid.org/0000-0002-5239-4043>>),  
Sergi Padilla-Parra [ths] (<<https://orcid.org/0000-0002-8010-9481>>)

**Repository** CRAN

**Date/Publication** 2018-09-03 15:20:02 UTC

## R topics documented:

all_equal . . . . .	2
before_last_dot . . . . .	3
can_be_numeric . . . . .	4
count_matches . . . . .	4
create_dir . . . . .	5
currency . . . . .	5
extend_char_vec . . . . .	6
extract_non_numerics . . . . .	6
extract_numbers . . . . .	7
filesstrings . . . . .	8
filesstrings-defunct . . . . .	8
give_ext . . . . .	8
group_close . . . . .	9
locate_braces . . . . .	9
match_arg . . . . .	10
move_files . . . . .	10
nice_file_nums . . . . .	11
nice_nums . . . . .	12
nth_number_after_mth . . . . .	12
nth_number_before_mth . . . . .	13
put_in_pos . . . . .	15
remove_dir . . . . .	15
remove_filename_spaces . . . . .	16
remove_quoted . . . . .	17
rename_with_nums . . . . .	17
singleize . . . . .	18
str_after_nth . . . . .	18
str_elem . . . . .	19
str_nth_instance_indices . . . . .	19
str_paste_elems . . . . .	20
str_split_by_nums . . . . .	20
str_split_camel_case . . . . .	21
str_to_vec . . . . .	21
str_with_patterns . . . . .	21
trim_anything . . . . .	22
unitize_dirs . . . . .	22

<b>Index</b>	<b>24</b>
--------------	-----------

---

all_equal	<i>A more flexible version of <a href="#">all.equal</a> for vectors.</i>
-----------	--

---

### Description

This function will return TRUE whenever `base::all.equal()` would return TRUE, however it will also return TRUE in some other cases:

- If a is given and b is not, TRUE will be returned if all of the elements of a are the same.
- If a is a scalar and b is a vector or array, TRUE will be returned if every element in b is equal to a.

- If a is a vector or array and b is a scalar, TRUE will be returned if every element in a is equal to b.

When this function does not return TRUE, it returns FALSE (unless it errors). This is unlike `base::all.equal()`.

### Usage

```
all_equal(a, b = NULL)
```

### Arguments

a                      A vector, array or list.  
b                      Either NULL or a vector, array or list of length either 1 or length(a).

### Value

TRUE if "equality of all" is satisfied (as detailed in 'Description' above) and FALSE otherwise.

### Note

- This behaviour is totally different from `base::all.equal()`.
- There's also `dplyr::all_equal()`, which is different again. To avoid confusion, always use the full `filesstrings::all_equal()` and never `library(filesstrings)` followed by just `all_equal()`.

### Examples

```
all_equal(1, rep(1, 3))
all_equal(2, 1:3)
all_equal(1:4, 1:4)
all_equal(1:4, c(1, 2, 3, 3))
all_equal(rep(1, 10))
all_equal(c(1, 88))
all_equal(1:2)
all_equal(list(1:2))
all_equal(1:4, matrix(1:4, nrow = 2)) # note that this gives TRUE
```

---

before_last_dot	<i>Get the part of a string before the last period.</i>
-----------------	---

---

### Description

See `strex::str_before_last_dot()`.

### Usage

```
before_last_dot(string)
```

### Arguments

string                A character vector.

---

can_be_numeric	<i>Check if a string could be considered as numeric.</i>
----------------	--

---

### Description

See `strex::str_can_be_numeric()`.

### Usage

```
can_be_numeric(string)
```

### Arguments

string	A character vector.
--------	---------------------

---

count_matches	<i>Count the number of the matches of a pattern in a string.</i>
---------------	--

---

### Description

Vectorized over string and pattern.

### Usage

```
count_matches(string, pattern)
```

### Arguments

string	A character vector.
pattern	A character vector. Pattern(s) specified like the pattern(s) in the stringr package (e.g. look at <code>stringr::str_locate()</code> ). If this has length >1 its length must be the same as that of string.

### Value

An integer vector giving the number of matches in each string.

---

create\_dir

*Create directories if they don't already exist*


---

### Description

Given the names of (potential) directories, create the ones that do not already exist.

### Usage

```
create_dir(...)
```

### Arguments

...                      The names of the directories, specified via relative or absolute paths. Duplicates are ignored.

### Value

Invisibly, a vector with a TRUE for each time a directory was actually created and a FALSE otherwise. This vector is named with the paths of the directories that were passed to the function.

### Examples

```
## Not run:
create_dir(c("mydir", "yourdir"))
remove_dir(c("mydir", "yourdir"))
## End(Not run)
```

---

currency

*Get the currencies of numbers within a string.*


---

### Description

See [strex::str\\_get\\_currency\(\)](#).

### Usage

```
get_currencies(string)
```

```
get_currency(string)
```

### Arguments

string                      A string for get\_currencies() and a character vector for get\_currency().

---

extend_char_vec	<i>Pad a character vector with empty strings.</i>
-----------------	---

---

### Description

Extend a character vector by appending empty strings at the end.

### Usage

```
extend_char_vec(char_vec, extend_by = NA, length_out = NA)
```

### Arguments

char_vec	A character vector. The thing you wish to expand.
extend_by	A non-negative integer. By how much do you wish to extend the vector?
length_out	A positive integer. How long do you want the output vector to be?

### Value

A character vector.

### Examples

```
extend_char_vec(1:5, extend_by = 2)
extend_char_vec(c("a", "b"), length_out = 10)
```

---

extract_non_numerics	<i>Extract non-numbers from a string.</i>
----------------------	---

---

### Description

See [strex::str\\_extract\\_non\\_numerics\(\)](#)

### Usage

```
extract_non_numerics(string, decimals = FALSE,
  leading_decimals = FALSE, negs = FALSE)

nth_non_numeric(string, n, decimals = FALSE, leading_decimals = FALSE,
  negs = FALSE)

first_non_numeric(string, decimals = FALSE, leading_decimals = FALSE,
  negs = FALSE)

last_non_numeric(string, decimals = FALSE, leading_decimals = FALSE,
  negs = FALSE)
```

**Arguments**

string	A string.
decimals	Do you want to include the possibility of decimal numbers (TRUE) or not (FALSE, the default).
leading_decimals	Do you want to allow a leading decimal point to be the start of a number?
negs	Do you want to allow negative numbers? Note that double negatives are not handled here (see the examples).
n	The index of the number (or non-numeric) that you seek. Negative indexing is allowed i.e. $n = 1$ (the default) will give you the first number (or non-numeric) whereas $n = -1$ will give you the last number (or non-numeric), $n = -2$ will give you the second last number and so on. The function is vectorized over this argument.

---

extract_numbers	<i>Extract numbers from a string.</i>
-----------------	---------------------------------------

---

**Description**

See `strex::str_extract_numbers()`.

**Usage**

```
extract_numbers(string, leave_as_string = FALSE, decimals = FALSE,
  leading_decimals = FALSE, negs = FALSE)
```

```
nth_number(string, n, leave_as_string = FALSE, decimals = FALSE,
  leading_decimals = FALSE, negs = FALSE)
```

```
first_number(string, leave_as_string = FALSE, decimals = FALSE,
  leading_decimals = FALSE, negs = FALSE)
```

```
last_number(string, leave_as_string = FALSE, decimals = FALSE,
  leading_decimals = FALSE, negs = FALSE)
```

**Arguments**

string	A string.
leave_as_string	Do you want to return the number as a string (TRUE) or as numeric (FALSE, the default)?
decimals	Do you want to include the possibility of decimal numbers (TRUE) or not (FALSE, the default).
leading_decimals	Do you want to allow a leading decimal point to be the start of a number?
negs	Do you want to allow negative numbers? Note that double negatives are not handled here (see the examples).

`n` The index of the number (or non-numeric) that you seek. Negative indexing is allowed i.e. `n = 1` (the default) will give you the first number (or non-numeric) whereas `n = -1` will give you the last number (or non-numeric), `n = -2` will give you the second last number and so on. The function is vectorized over this argument.

---

filesstrings      filesstrings: *handy file and string manipulation*

---

### Description

This started out as a package for file and string manipulation. Since then, the `fs` file manipulation package and the `strex` string manipulation package emerged, offering functionality previously given by this package (but slightly better). Those packages have hence almost pushed 'filesstrings' into extinction. However, it still has a small number of unique, handy file manipulation functions which can be seen in the [vignette](#). One example is a function to remove spaces from all file names in a directory.

### References

Rory Nolan and Sergi Padilla-Parra (2017). filesstrings: An R package for file and string manipulation. The Journal of Open Source Software, 2(14). doi: [10.21105/joss.00260](https://doi.org/10.21105/joss.00260).

---

filesstrings-defunct      *Defunct functions*

---

### Description

These functions have been made defunct, mostly because the naming style of the package has been changed. Some have been removed because they were not well-done.

### Arguments

... Defunct function arguments.

---

give\_ext      *Ensure a file name has the intended extension.*

---

### Description

See `strex::str_give_ext()`.

### Usage

```
give_ext(string, ext, replace = FALSE)
```



**Arguments**

string	The intended file name.
ext	The intended file extension (with or without the ".").
replace	If the file has an extension already, replace it (or append the new extension name)?

---

group_close	<i>Group together close adjacent elements of a vector.</i>
-------------	--

---

**Description**

Given a strictly increasing vector (each element is bigger than the last), group together stretches of the vector where *adjacent* elements are separated by at most some specified distance. Hence, each element in each group has at least one other element in that group that is *close* to it. See the examples.

**Usage**

```
group_close(vec_ascending, max_gap = 1)
```

**Arguments**

vec_ascending	A strictly increasing numeric vector.
max_gap	The biggest allowable gap between adjacent elements for them to be considered part of the same <i>group</i> .

**Value**

A where each element is one group, as a numeric vector.

**Examples**

```
group_close(1:10, 1)
group_close(1:10, 0.5)
group_close(c(1, 2, 4, 10, 11, 14, 20, 25, 27), 3)
```

---

locate_braces	<i>Locate the braces in a string.</i>
---------------	---------------------------------------

---

**Description**

See [strex::str\\_locate\\_braces\(\)](#).

**Usage**

```
locate_braces(string)
```

**Arguments**

string	A character vector
--------	--------------------

---

match_arg	<i>Argument Matching</i>
-----------	--------------------------

---

### Description

See `strex::match_arg()`.

### Usage

```
match_arg(arg, choices, index = FALSE, several_ok = FALSE,
  ignore_case = FALSE)
```

### Arguments

arg	A character vector (of length one unless <code>several_ok = TRUE</code> ).
choices	A character vector of candidate values.
index	Return the index of the match rather than the match itself? Default no.
several_ok	Allow arg to have length greater than one to match several arguments at once? Default no.
ignore_case	Ignore case while matching. Default no. If this is TRUE, the returned value is the matched element of choices (with its original casing).

---

move_files	<i>Move files around.</i>
------------	---------------------------

---

### Description

Move specified files into specified directories

### Usage

```
move_files(files, destinations, overwrite = FALSE)

file.move(files, destinations, overwrite = FALSE)
```

### Arguments

files	A character vector of files to move (relative or absolute paths).
destinations	A character vector of the destination directories into which to move the files.
overwrite	Allow overwriting of files? Default no.

### Details

If there are  $n$  files, there must be either 1 or  $n$  directories. If there is one directory, then all  $n$  files are moved there. If there are  $n$  directories, then each file is put into its respective directory. This function also works to move directories.

If you try to move files to a directory that doesn't exist, the directory is first created and then the files are put inside.

**Value**

Invisibly, a logical vector with a TRUE for each time the operation succeeded and a FALSE for every fail.

**Examples**

```
## Not run:
dir.create("dir")
files <- c("1litres_1.txt", "1litres_30.txt", "3litres_5.txt")
file.create(files)
file.move(files, "dir")
## End(Not run)
```

---

nice\_file\_nums

---

*Make file numbers comply with alphabetical order*


---

**Description**

If files are numbered, their numbers may not *comply* with alphabetical order, i.e. "file2.ext" comes after "file10.ext" in alphabetical order. This function renames the files in the specified directory such that they comply with alphabetical order, so here "file2.ext" would be renamed to "file02.ext".

**Usage**

```
nice_file_nums(dir = ".", pattern = NA)
```

**Arguments**

dir	Path (relative or absolute) to the directory in which to do the renaming (default is current working directory).
pattern	A regular expression. If specified, files to be renamed are restricted to ones matching this pattern (in their name).

**Details**

It works on file names with more than one number in them e.g. "file01part3.ext" (a file with 2 numbers). All the file names that it works on must have the same number of numbers, and the non-number bits must be the same. One can limit the renaming to files matching a certain pattern. This function wraps [nice\\_nums\(\)](#), which does the string operations, but not the renaming. To see examples of how this function works, see the examples in that function's documentation.

**Value**

A logical vector with a TRUE for each successful rename (should be all TRUEs) and a FALSE otherwise.

**Examples**

```
## Not run:
dir.create("NiceFileNums_test")
setwd("NiceFileNums_test")
files <- c("1litres_1.txt", "1litres_30.txt", "3litres_5.txt")
file.create(files)
nice_file_nums()
nice_file_nums(pattern = "\\..txt$")
setwd("..")
dir.remove("NiceFileNums_test")
## End(Not run)
```

---

nice_nums	<i>Make string numbers comply with alphabetical order</i>
-----------	---

---

**Description**

See [strex::str\\_alphord\\_nums\(\)](#).

**Usage**

```
nice_nums(strings)
```

**Arguments**

strings            A vector of strings.

---

nth_number_after_mth	<i>Find the nth number after the mth occurrence of a pattern.</i>
----------------------	---

---

**Description**

See [strex::str\\_nth\\_number\\_after\\_mth\(\)](#).

**Usage**

```
nth_number_after_mth(string, pattern, n, m, decimals = FALSE,
  leading_decimals = FALSE, negs = FALSE, leave_as_string = FALSE)

nth_number_after_first(string, pattern, n, decimals = FALSE,
  leading_decimals = FALSE, negs = FALSE, leave_as_string = FALSE)

nth_number_after_last(string, pattern, n, decimals = FALSE,
  leading_decimals = FALSE, negs = FALSE, leave_as_string = FALSE)

first_number_after_mth(string, pattern, m, decimals = FALSE,
  leading_decimals = FALSE, negs = FALSE, leave_as_string = FALSE)

last_number_after_mth(string, pattern, m, decimals = FALSE,
  leading_decimals = FALSE, negs = FALSE, leave_as_string = FALSE)
```

```
first_number_after_first(string, pattern, decimals = FALSE,
  leading_decimals = FALSE, negs = FALSE, leave_as_string = FALSE)
```

```
first_number_after_last(string, pattern, decimals = FALSE,
  leading_decimals = FALSE, negs = FALSE, leave_as_string = FALSE)
```

```
last_number_after_first(string, pattern, decimals = FALSE,
  leading_decimals = FALSE, negs = FALSE, leave_as_string = FALSE)
```

```
last_number_after_last(string, pattern, decimals = FALSE,
  leading_decimals = FALSE, negs = FALSE, leave_as_string = FALSE)
```

### Arguments

string	A character vector.
pattern	A character vector. Pattern(s) specified like the pattern(s) in the stringr package (e.g. look at <code>stringr::str_locate()</code> ). If this has length >1 its length must be the same as that of string.
n	Natural numbers.
m	Natural numbers.
decimals	Do you want to include the possibility of decimal numbers (TRUE) or not (FALSE, the default).
leading_decimals	Do you want to allow a leading decimal point to be the start of a number?
negs	Do you want to allow negative numbers? Note that double negatives are not handled here (see the examples).
leave_as_string	Do you want to return the number as a string (TRUE) or as numeric (FALSE, the default)?

---

`nth_number_before_mth` *Find the nth number before the mth occurrence of a pattern.*

---

### Description

Given a string, a pattern and natural numbers n and m, find the nth number that comes before the mth occurrence of the pattern.

### Usage

```
nth_number_before_mth(string, pattern, n, m, decimals = FALSE,
  leading_decimals = FALSE, negs = FALSE, leave_as_string = FALSE)
```

```
nth_number_before_first(string, pattern, n, decimals = FALSE,
  leading_decimals = FALSE, negs = FALSE, leave_as_string = FALSE)
```

```
nth_number_before_last(string, pattern, n, decimals = FALSE,
  leading_decimals = FALSE, negs = FALSE, leave_as_string = FALSE)
```

```

first_number_before_mth(string, pattern, m, decimals = FALSE,
  leading_decimals = FALSE, negs = FALSE, leave_as_string = FALSE)

last_number_before_mth(string, pattern, m, decimals = FALSE,
  leading_decimals = FALSE, negs = FALSE, leave_as_string = FALSE)

first_number_before_first(string, pattern, decimals = FALSE,
  leading_decimals = FALSE, negs = FALSE, leave_as_string = FALSE)

first_number_before_last(string, pattern, decimals = FALSE,
  leading_decimals = FALSE, negs = FALSE, leave_as_string = FALSE)

last_number_before_first(string, pattern, decimals = FALSE,
  leading_decimals = FALSE, negs = FALSE, leave_as_string = FALSE)

last_number_before_last(string, pattern, decimals = FALSE,
  leading_decimals = FALSE, negs = FALSE, leave_as_string = FALSE)

```

### Arguments

string	A character vector.
pattern	A character vector. Pattern(s) specified like the pattern(s) in the stringr package (e.g. look at <a href="#">stringr::str_locate()</a> ). If this has length >1 its length must be the same as that of string.
n, m	Natural numbers.
decimals	Do you want to include the possibility of decimal numbers (TRUE) or not (FALSE, the default).
leading_decimals	Do you want to allow a leading decimal point to be the start of a number?
negs	Do you want to allow negative numbers? Note that double negatives are not handled here (see the examples).
leave_as_string	Do you want to return the number as a string (TRUE) or as numeric (FALSE, the default)?

### Value

A numeric vector.

### Examples

```

string <- c("abc1abc2abc3abc4def5abc6abc7abc8abc9",
  "abc1def2ghi3abc4def5ghi6abc7def8ghi9")
nth_number_before_mth(string, "def", 1, 1)
nth_number_before_mth(string, "abc", 2, 3)
nth_number_before_first(string, "def", 2)
nth_number_before_last(string, "def", -1)
first_number_before_mth(string, "abc", 2)
last_number_before_mth(string, "def", 1)
first_number_before_first(string, "def")
first_number_before_last(string, "def")

```

```
last_number_before_first(string, "def")
last_number_before_last(string, "def")
```

---

put_in_pos	<i>Put specified strings in specified positions in an otherwise empty character vector.</i>
------------	---

---

### Description

Create a character vector with a set of strings at specified positions in that character vector, with the rest of it taken up by empty strings.

### Usage

```
put_in_pos(strings, positions)
```

### Arguments

strings	A character vector of the strings to put in positions (coerced by <a href="#">as.character</a> if not character already).
positions	The indices of the character vector to be occupied by the elements of strings. Must be the same length as strings or of length 1.

### Value

A character vector.

### Examples

```
put_in_pos(1:3, c(1, 8, 9))
put_in_pos(c("Apple", "Orange", "County"), c(5, 7, 8))
put_in_pos(1:2, 5)
```

---

remove_dir	<i>Remove directories</i>
------------	---------------------------

---

### Description

Delete directories and all of their contents.

### Usage

```
remove_dir(...)

dir.remove(...)
```

### Arguments

...	The names of the directories, specified via relative or absolute paths.
-----	---

**Value**

Invisibly, a logical vector with TRUE for each success and FALSE for failures.

**Examples**

```
## Not run:
sapply(c("mydir1", "mydir2"), dir.create)
remove_dir(c("mydir1", "mydir2"))
## End(Not run)
```

---

```
remove_filename_spaces
```

*Remove spaces in file names*

---

**Description**

Remove spaces in file names in a specified directory, replacing them with whatever you want, default nothing.

**Usage**

```
remove_filename_spaces(dir = ".", pattern = "", replacement = "")
```

**Arguments**

<code>dir</code>	The directory in which to perform the operation.
<code>pattern</code>	A regular expression. If specified, only files matching this pattern will be treated.
<code>replacement</code>	What do you want to replace the spaces with? This defaults to nothing, another sensible choice would be an underscore.

**Value**

A logical vector indicating which operation succeeded for each of the files attempted. Using a missing value for a file or path name will always be regarded as a failure.

**Examples**

```
## Not run:
dir.create("RemoveFileNameSpaces_test")
setwd("RemoveFileNameSpaces_test")
files <- c("1litres 1.txt", "1litres 30.txt", "3litres 5.txt")
file.create(files)
remove_filename_spaces()
list.files()
setwd("..")
dir.remove("RemoveFileNameSpaces_test")
## End(Not run)
```



---

remove_quoted	<i>Remove the quoted parts of a string.</i>
---------------	---

---

**Description**

See `strex::str_remove_quoted()`.

**Usage**

```
remove_quoted(string)
```

**Arguments**

string	A character vector.
--------	---------------------

---

rename_with_nums	<i>Replace file names with numbers</i>
------------------	--

---

**Description**

Rename the files in the directory, replacing file names with numbers only.

**Usage**

```
rename_with_nums(dir = ".", pattern = NULL)
```

**Arguments**

dir	The directory in which to rename the files (relative or absolute path). Defaults to current working directory.
pattern	A regular expression. If specified, only files with names matching this pattern will be treated.

**Value**

A logical vector with a TRUE for each successful renaming and a FALSE otherwise.

**Examples**

```
## Not run:
dir.create("RenameWithNums_test")
setwd("RenameWithNums_test")
files <- c("1litres 1.txt", "1litres 30.txt", "3litres 5.txt")
file.create(files)
rename_with_nums()
list.files()
setwd("../")
dir.remove("RenameWithNums_test")
## End(Not run)
```

---

singleize	<i>Remove back-to-back duplicates of a pattern in a string.</i>
-----------	---

---

**Description**

See [strex::str\\_singleize\(\)](#).

**Usage**

```
singleize(string, pattern)
```

**Arguments**

string	A character vector. The string(s) to be purged of duplicates.
pattern	A character vector. Pattern(s) specified like the pattern(s) in the stringr package (e.g. look at <a href="#">stringr::str_locate()</a> ). If this has length >1 its length must be the same as that of string.

---

str_after_nth	<i>Text before or after nth occurrence of pattern.</i>
---------------	--

---

**Description**

See [strex::str\\_after\\_nth\(\)](#).

**Usage**

```
str_after_nth(strings, pattern, n)
str_after_first(strings, pattern)
str_after_last(strings, pattern)
str_before_nth(strings, pattern, n)
str_before_first(strings, pattern)
str_before_last(strings, pattern)
```

**Arguments**

strings	A character vector.
pattern	A character vector. Pattern(s) specified like the pattern(s) in the stringr package (e.g. look at <a href="#">stringr::str_locate()</a> ). If this has length >1 its length must be the same as that of string.
n	A natural number to identify the <i>n</i> th occurrence (defaults to first ( <i>n</i> = 1)). This can be negatively indexed, so if you wish to select the <i>last</i> occurrence, you need <i>n</i> = -1, for the second-last, you need <i>n</i> = -2 and so on.

---

str_elem	<i>Extract a single character from a string, using its index.</i>
----------	---

---

### Description

See [strex::str\\_elem\(\)](#).

### Usage

```
str_elem(string, index)
```

### Arguments

string	A string.
index	An integer. Negative indexing is allowed as in <a href="#">stringr::str_sub()</a> .

---

str_nth_instance_indices	<i>Get the indices of the <math>n</math>th instance of a pattern.</i>
--------------------------	---

---

### Description

See [strex::str\\_locate\\_nth\(\)](#).

### Usage

```
str_nth_instance_indices(string, pattern, n)

str_first_instance_indices(string, pattern)

str_last_instance_indices(string, pattern)
```

### Arguments

string	A character vector. These functions are vectorized over this argument.
pattern	A character vector. Pattern(s) specified like the pattern(s) in the stringr package (e.g. look at <a href="#">stringr::str_locate()</a> ). If this has length >1 its length must be the same as that of string.
n	Then $n$ for the $n$ th instance of the pattern.

---

str_paste_elems	<i>Extract bits of a string and paste them together</i>
-----------------	---

---

**Description**

See `strex::str_paste_elems()`.

**Usage**

```
str_paste_elems(string, indices)
```

**Arguments**

string	A string.
indices	A numeric vector of positive integers detailing the indices of the characters of string that we wish to paste together.

---

str_split_by_nums	<i>Split a string by its numeric characters.</i>
-------------------	--

---

**Description**

See `strex::str_split_by_nums()`.

**Usage**

```
str_split_by_nums(string, decimals = FALSE, leading_decimals = FALSE,
  negs = FALSE)
```

**Arguments**

string	A string.
decimals	Do you want to include the possibility of decimal numbers (TRUE) or not (FALSE, the default).
leading_decimals	Do you want to allow a leading decimal point to be the start of a number?
negs	Do you want to allow negative numbers? Note that double negatives are not handled here (see the examples).

---

str_split_camel_case	<i>Split a string based on CamelCase</i>
----------------------	--

---

**Description**

See [strex::str\\_split\\_camel\\_case\(\)](#).

**Usage**

```
str_split_camel_case(string, lower = FALSE)
```

**Arguments**

string	A character vector.
lower	Do you want the output to be all lower case (or as is)?

---

str_to_vec	<i>Convert a string to a vector of characters</i>
------------	---

---

**Description**

See [strex::str\\_to\\_vec\(\)](#).

**Usage**

```
str_to_vec(string)
```

**Arguments**

string	A string.
--------	-----------

---

str_with_patterns	<i>Which strings match the patterns?</i>
-------------------	--

---

**Description**

Given a character vector of strings and one of patterns (in regular expression), which of the strings match all (or any) of the patterns.

**Usage**

```
str_with_patterns(strings, patterns, ignore_case = FALSE, any = FALSE)
```

**Arguments**

strings	A character vector.
patterns	Regular expressions.
ignore_case	Do we want to ignore case when matching patterns?
any	Set this to TRUE if you want to see which strings match <i>any</i> of the patterns and not <i>all</i> (all is the default).

**Details**

This function is deprecated. Please use `stringr::str_subset()` instead.

**Value**

A character vector of strings matching the patterns.

---

trim_anything	<i>Trim something other than whitespace</i>
---------------	---

---

**Description**

See `strex::str_trim_anything()`.

**Usage**

```
trim_anything(string, pattern, side = "both")
```

**Arguments**

string	A string.
pattern	A string. The pattern to be trimmed ( <i>not</i> interpreted as regular expression). So to trim a period, use <code>char = "."</code> and not <code>char = "\\."</code> .
side	Which side do you want to trim from? "both" is the default, but you can also have just either "left" or "right" (or optionally the shortened "b", "l" and "r").

---

unitize_dirs	<i>Put files with the same unit measurements into directories</i>
--------------	---

---

**Description**

Say you have a number of files with "5min" in their names, number with "10min" in the names, a number with "15min" in their names and so on, and you'd like to put them into directories named "5min", "10min", "15min" and so on. This function does this, but not just for the unit "min", for any unit.

**Usage**

```
unitize_dirs(unit, pattern = NULL, dir = ".")
```

**Arguments**

unit	The unit upon which to base the categorizing.
pattern	If set, only files with names matching this pattern will be treated.
dir	In which directory do you want to perform this action (defaults to current)?

**Details**

This function takes the number to be the last number (as defined in [nth\\_number\(\)](#)) before the first occurrence of the unit name. There is the option to only treat files matching a certain pattern.

**Value**

Invisibly TRUE if the operation is successful, if not there will be an error.

**Examples**

```
## Not run:
dir.create("UnitDirs_test")
setwd("UnitDirs_test")
files <- c("1litres_1.txt", "1litres_3.txt", "3litres.txt", "5litres_1.txt")
file.create(files)
unitize_dirs("litres", "\\*.txt")
setwd("..")
dir.remove("UnitDirs_test")
## End(Not run)
```

# Index

`all.equal`, [2](#)  
`all_equal`, [2](#)  
`as.character`, [15](#)  
  
`base::all.equal()`, [2](#), [3](#)  
`before_last_dot`, [3](#)  
  
`can_be_numeric`, [4](#)  
`count_matches`, [4](#)  
`create_dir`, [5](#)  
`currency`, [5](#)  
  
`dir.remove(remove_dir)`, [15](#)  
`dplyr::all_equal()`, [3](#)  
  
`extend_char_vec`, [6](#)  
`extract_non_numerics`, [6](#)  
`extract_numbers`, [7](#)  
  
`file.move(move_files)`, [10](#)  
`filesstrings`, [8](#)  
`filesstrings-defunct`, [8](#)  
`filesstrings-package(filesstrings)`, [8](#)  
`first_non_numeric`  
    (`extract_non_numerics`), [6](#)  
`first_number(extract_numbers)`, [7](#)  
`first_number_after_first`  
    (`nth_number_after_mth`), [12](#)  
`first_number_after_last`  
    (`nth_number_after_mth`), [12](#)  
`first_number_after_mth`  
    (`nth_number_after_mth`), [12](#)  
`first_number_before_first`  
    (`nth_number_before_mth`), [13](#)  
`first_number_before_last`  
    (`nth_number_before_mth`), [13](#)  
`first_number_before_mth`  
    (`nth_number_before_mth`), [13](#)  
  
`get_currencies(currency)`, [5](#)  
`get_currency(currency)`, [5](#)  
`give_ext`, [8](#)  
`group_close`, [9](#)  
  
`last_non_numeric`  
    (`extract_non_numerics`), [6](#)  
  
`last_number(extract_numbers)`, [7](#)  
`last_number_after_first`  
    (`nth_number_after_mth`), [12](#)  
`last_number_after_last`  
    (`nth_number_after_mth`), [12](#)  
`last_number_after_mth`  
    (`nth_number_after_mth`), [12](#)  
`last_number_before_first`  
    (`nth_number_before_mth`), [13](#)  
`last_number_before_last`  
    (`nth_number_before_mth`), [13](#)  
`last_number_before_mth`  
    (`nth_number_before_mth`), [13](#)  
`locate_braces`, [9](#)  
  
`match_arg`, [10](#)  
`move_files`, [10](#)  
  
`nice_file_nums`, [11](#)  
`nice_nums`, [12](#)  
`nice_nums()`, [11](#)  
`nth_non_numeric(extract_non_numerics)`,  
    [6](#)  
`nth_number(extract_numbers)`, [7](#)  
`nth_number()`, [23](#)  
`nth_number_after_first`  
    (`nth_number_after_mth`), [12](#)  
`nth_number_after_last`  
    (`nth_number_after_mth`), [12](#)  
`nth_number_after_mth`, [12](#)  
`nth_number_before_first`  
    (`nth_number_before_mth`), [13](#)  
`nth_number_before_last`  
    (`nth_number_before_mth`), [13](#)  
`nth_number_before_mth`, [13](#)  
  
`put_in_pos`, [15](#)  
  
`remove_dir`, [15](#)  
`remove_filename_spaces`, [16](#)  
`remove_quoted`, [17](#)  
`rename_with_nums`, [17](#)  
  
`singleize`, [18](#)  
`str_after_first(str_after_nth)`, [18](#)



`str_after_last(str_after_nth)`, 18  
`str_after_nth`, 18  
`str_before_first(str_after_nth)`, 18  
`str_before_last(str_after_nth)`, 18  
`str_before_nth(str_after_nth)`, 18  
`str_elem`, 19  
`str_first_instance_indices`  
    (`str_nth_instance_indices`), 19  
`str_last_instance_indices`  
    (`str_nth_instance_indices`), 19  
`str_nth_instance_indices`, 19  
`str_paste_elems`, 20  
`str_split_by_nums`, 20  
`str_split_camel_case`, 21  
`str_to_vec`, 21  
`str_with_patterns`, 21  
`strex::match_arg()`, 10  
`strex::str_after_nth()`, 18  
`strex::str_alphord_nums()`, 12  
`strex::str_before_last_dot()`, 3  
`strex::str_can_be_numeric()`, 4  
`strex::str_elem()`, 19  
`strex::str_extract_non_numerics()`, 6  
`strex::str_extract_numbers()`, 7  
`strex::str_get_currency()`, 5  
`strex::str_give_ext()`, 8  
`strex::str_locate_braces()`, 9  
`strex::str_locate_nth()`, 19  
`strex::str_nth_number_after_mth()`, 12  
`strex::str_paste_elems()`, 20  
`strex::str_remove_quoted()`, 17  
`strex::str_singleize()`, 18  
`strex::str_split_by_nums()`, 20  
`strex::str_split_camel_case()`, 21  
`strex::str_to_vec()`, 21  
`strex::str_trim_anything()`, 22  
`stringr::str_locate()`, 4, 13, 14, 18, 19  
`stringr::str_sub()`, 19  
`stringr::str_subset()`, 22  
  
`trim_anything`, 22  
  
`unitize_dirs`, 22