

## LAB – 3

Name: Gandevia Keval Dharmeshbhai

Sem: VII


Roll No: CE046



Subject: Big Data and Analytics


**Aim:** Interfacing to Distributed File System – HDFS commands and Web GUI file system browser usage.

**Q. 1: Create/Delete a directory/file named 'Test' from HDFS web UI in '/user/Hadoop'. It should give error message. Read this message and solve the error.**

- ❖ We cannot create a file/directory on GUI because we as a Hadoop user has not access to that GUI.







❖ Stop the server.

```
hadoop@celab2-ThinkCentre-neo-50s-Gen-3: /opt/hadoop
2022-07-20 08:49:48,248 WARN util.NativeCodeLoader: Unable to load native-hadoop
library for your platform... using builtin-java classes where applicable
hadoop@celab2-ThinkCentre-neo-50s-Gen-3:/opt/hadoop$ jps
8297 SecondaryNameNode
8442 Jps
7899 NameNode
8076 DataNode
hadoop@celab2-ThinkCentre-neo-50s-Gen-3:/opt/hadoop$ stop-dfs.sh
WARNING: HADOOP_PREFIX has been replaced by HADOOP_HOME. Using value of HADOOP_P
REFIX.
Stopping namenodes on [localhost]
WARNING: HADOOP_PREFIX has been replaced by HADOOP_HOME. Using value of HADOOP_P
REFIX.
Stopping datanodes
WARNING: HADOOP_PREFIX has been replaced by HADOOP_HOME. Using value of HADOOP_P
REFIX.
Stopping secondary namenodes [localhost]
WARNING: HADOOP_PREFIX has been replaced by HADOOP_HOME. Using value of HADOOP_P
REFIX.
WARNING: HADOOP_PREFIX has been replaced by HADOOP_HOME. Using value of HADOOP_P
REFIX.
2022-07-20 08:54:34,634 WARN util.NativeCodeLoader: Unable to load native-hadoop
library for your platform... using builtin-java classes where applicable
hadoop@celab2-ThinkCentre-neo-50s-Gen-3:/opt/hadoop$
```

- ❖ We need to edit the core-site.xml and need to add the staticuser with value hadoop.

```
hadoop@celab2-ThinkCentre-neo-50s-Gen-3: /opt/hadoop/etc/h
etc  lib      licenses-binary  NOTICE-binary  sbin
hdfs  libexec  LICENSE.txt      NOTICE.txt     share
hadoop@celab2-ThinkCentre-neo-50s-Gen-3:/opt/hadoop$ cd etc
hadoop@celab2-ThinkCentre-neo-50s-Gen-3:/opt/hadoop/etc$ cd hadoop/
hadoop@celab2-ThinkCentre-neo-50s-Gen-3:/opt/hadoop/etc/hadoop$ ls
capacity-scheduler.xml      kms-log4j.properties
configuration.xml           kms-site.xml
container-executor.cfg      log4j.properties
core-site.xml               mapred-env.cmd
hadoop-env.cmd              mapred-env.sh
hadoop-env.sh               mapred-queues.xml.template
hadoop-metrics2.properties mapred-site.xml
hadoop-policy.xml           shellprofile.d
hadoop-user-functions.sh.example  ssl-client.xml.example
hdfs-rbf-site.xml           ssl-server.xml.example
hdfs-site.xml               user_ec_policies.xml.template
httpfs-env.sh               workers
httpfs-log4j.properties    yarn-env.cmd
httpfs-site.xml             yarn-env.sh
kms-acls.xml                yarnservice-log4j.properties
kms-env.sh                  yarn-site.xml
hadoop@celab2-ThinkCentre-neo-50s-Gen-3:/opt/hadoop/etc/hadoop$ gedit core-site.xml
```

```
hadoop@celab2-ThinkCentre-neo-50s-Gen-3:/opt/hadoop/etc/hadoop$ cat core-site.xml
<?xml version="1.0" encoding="UTF-8"?>
<?xml-stylesheet type="text/xsl" href="configuration.xsl"?>

<configuration>
<property>
  <name>fs.defaultFS</name>
  <value>hdfs://localhost:9000</value>
</property>
<property>
  <name>hadoop.tmp.dir</name>
  <value>/opt/hadoop/tmp</value>
</property>
<property>
  <name>hadoop.http.staticuser.user</name>
  <value>hadoop</value>
</property>
</configuration>
hadoop@celab2-ThinkCentre-neo-50s-Gen-3:/opt/hadoop/etc/hadoop$
```

```
hadoop@celab2-ThinkCentre-neo-50s-Gen-3: /opt/hadoop/etc/hadoop$ start-dfs.sh
WARNING: HADOOP_PREFIX has been replaced by HADOOP_HOME. Using value of HADOOP_P
PREFIX.
Starting namenodes on [localhost]
WARNING: HADOOP_PREFIX has been replaced by HADOOP_HOME. Using value of HADOOP_P
PREFIX.
Starting datanodes
WARNING: HADOOP_PREFIX has been replaced by HADOOP_HOME. Using value of HADOOP_P
PREFIX.
Starting secondary namenodes [localhost]
WARNING: HADOOP_PREFIX has been replaced by HADOOP_HOME. Using value of HADOOP_P
PREFIX.
WARNING: HADOOP_PREFIX has been replaced by HADOOP_HOME. Using value of HADOOP_P
PREFIX.
2022-07-20 08:59:40,191 WARN util.NativeCodeLoader: Unable to load native-hadoop
library for your platform... using builtin-java classes where applicable
hadoop@celab2-ThinkCentre-neo-50s-Gen-3: /opt/hadoop/etc/hadoop$ jps
10481 NameNode
10659 DataNode
10876 SecondaryNameNode
11023 Jps
hadoop@celab2-ThinkCentre-neo-50s-Gen-3: /opt/hadoop/etc/hadoop$
```

Browse Directory

/ Go!

Show 25 entries Search:

Permission	Owner	Group	Size	Last Modified	Replication	Block Size	Name
drwxr-xr-x	hadoop	supergroup	0 B	Jul 20 08:59	0	0 B	Test
drwxr-xr-x	hadoop	supergroup	0 B	Jul 19 11:14	0	0 B	user

Showing 1 to 2 of 2 entries

Previous 1 Next



**Q. 2: Create a text file in local file system and put the same file in HDFS using appropriate command.**

```
hadoop@celab2-ThinkCentre-neo-50s-Gen-3: ~/Desktop/BDA_LAB_3_CE046
hadoop@celab2-ThinkCentre-neo-50s-Gen-3:/opt/hadoop/etc$ cd ..
hadoop@celab2-ThinkCentre-neo-50s-Gen-3:/opt/hadoop$ cd ..
hadoop@celab2-ThinkCentre-neo-50s-Gen-3:/opt$ cd ..
hadoop@celab2-ThinkCentre-neo-50s-Gen-3:/opt$ cd ~/Desktop
hadoop@celab2-ThinkCentre-neo-50s-Gen-3:~/Desktop$ ls
BDA_LAB_3_CE046
hadoop@celab2-ThinkCentre-neo-50s-Gen-3:~/Desktop$ cd BDA_LAB_3_CE046/
hadoop@celab2-ThinkCentre-neo-50s-Gen-3:~/Desktop/BDA_LAB_3_CE046$ cat data.txt
cat: data.txt: No such file or directory
hadoop@celab2-ThinkCentre-neo-50s-Gen-3:~/Desktop/BDA_LAB_3_CE046$ cta > data.txt
Command 'cta' not found, did you mean:
  command 'ctr' from deb containerd (1.5.9-0ubuntu3)
  command 'cba' from deb cba (0.3.6-5build1)
  command 'cat' from deb coreutils (8.32-4.1ubuntu1)
  command 'eta' from deb eta (1.0.1-1)
  command 'sta' from deb opensta (0~20191111gitc018cb2+dfsg-1build1)
Try: apt install <deb name>
hadoop@celab2-ThinkCentre-neo-50s-Gen-3:~/Desktop/BDA_LAB_3_CE046$ cat > data.txt
Hello I am Keval Gandevia.
I am student of computer science engineering at DD University.
hadoop@celab2-ThinkCentre-neo-50s-Gen-3:~/Desktop/BDA_LAB_3_CE046$ cat data.txt
Hello I am Keval Gandevia.
I am student of computer science engineering at DD University.
hadoop@celab2-ThinkCentre-neo-50s-Gen-3:~/Desktop/BDA_LAB_3_CE046$
```

- ❖ We can copy the file from local machine to Hadoop distributed file system using 'put' command.

```
hadoop@celab2-ThinkCentre-neo-50s-Gen-3:~/Desktop/BDA_LAB_3_CE046$ cat > data.txt
Hello I am Keval Gandevia.
I am student of computer science engineering at DD University.
hadoop@celab2-ThinkCentre-neo-50s-Gen-3:~/Desktop/BDA_LAB_3_CE046$ cat data.txt
Hello I am Keval Gandevia.
I am student of computer science engineering at DD University.
hadoop@celab2-ThinkCentre-neo-50s-Gen-3:~/Desktop/BDA_LAB_3_CE046$ hdfs dfs -put data.txt /user/hadoop/test
WARNING: HADOOP_PREFIX has been replaced by HADOOP_HOME. Using value of HADOOP_PREFIX.
2022-07-20 09:13:06,482 WARN util.NativeCodeLoader: Unable to load native-hadoop library for your platform... using builtin-j
ava classes where applicable
hadoop@celab2-ThinkCentre-neo-50s-Gen-3:~/Desktop/BDA_LAB_3_CE046$
```

```

hadoop@celab2-ThinkCentre-neo-50s-Gen-3:/opt/hadoop$ hdfs dfs -ls /user/hadoop/test
WARNING: HADOOP_PREFIX has been replaced by HADOOP_HOME. Using value of HADOOP_PREFIX.
2022-07-20 09:13:38,819 WARN util.NativeCodeLoader: Unable to load native-hadoop library for your platform... using builtin-java classes where applicable
Found 1 items
-rw-r--r-- 3 hadoop supergroup 90 2022-07-20 09:13 /user/hadoop/test/data.txt
hadoop@celab2-ThinkCentre-neo-50s-Gen-3:/opt/hadoop$ hdfs dfs -cat /user/hadoop/test/data.txt
WARNING: HADOOP_PREFIX has been replaced by HADOOP_HOME. Using value of HADOOP_PREFIX.
2022-07-20 09:15:22,687 WARN util.NativeCodeLoader: Unable to load native-hadoop library for your platform... using builtin-java classes where applicable
Hello I am Keval Gandevia.
I am student of computer science engineering at DD University.

```

### **Q. 3: Display the contents of this file of HDFS on terminal.**

```

hadoop@celab2-ThinkCentre-neo-50s-Gen-3:/opt/hadoop$ hdfs dfs -cat /user/hadoop/test/data.txt
WARNING: HADOOP_PREFIX has been replaced by HADOOP_HOME. Using value of HADOOP_PREFIX.
2022-07-20 09:15:22,687 WARN util.NativeCodeLoader: Unable to load native-hadoop library for your platform... using builtin-java classes where applicable
Hello I am Keval Gandevia.
I am student of computer science engineering at DD University.

```

### **Q. 4: Download this file of HDFS on local machine and change its contents. Upload this modified file again on HDFS and verify its contents. Also make sure that this file should be deleted from local machine automatically.**

- ❖ Modified content. For automatic deletion file from local machine we can use 'moveFromLocal' command.

```

hadoop@celab2-ThinkCentre-neo-50s-Gen-3:~/Desktop/BDA_LAB_3_CE046$ cat data.txt
Hello I am Keval Gandevia.
I am student of computer science engineering at DD University.
hadoop@celab2-ThinkCentre-neo-50s-Gen-3:~/Desktop/BDA_LAB_3_CE046$ cat >> data.txt
I am doing IELTS for abroad study.
hadoop@celab2-ThinkCentre-neo-50s-Gen-3:~/Desktop/BDA_LAB_3_CE046$ cat data.txt
Hello I am Keval Gandevia.
I am student of computer science engineering at DD University.
I am doing IELTS for abroad study.
hadoop@celab2-ThinkCentre-neo-50s-Gen-3:~/Desktop/BDA_LAB_3_CE046$

```

```

hadoop@celab2-ThinkCentre-neo-50s-Gen-3:/opt/hadoop$ hdfs dfs -rm /user/hadoop/test/data.txt
WARNING: HADOOP_PREFIX has been replaced by HADOOP_HOME. Using value of HADOOP_PREFIX.
2022-07-20 09:29:26,840 WARN util.NativeCodeLoader: Unable to load native-hadoop library for your platform... using builtin-java classes where applicable
Deleted /user/hadoop/test/data.txt
hadoop@celab2-ThinkCentre-neo-50s-Gen-3:/opt/hadoop$ hdfs dfs -cat /user/hadoop/test/
WARNING: HADOOP_PREFIX has been replaced by HADOOP_HOME. Using value of HADOOP_PREFIX.
2022-07-20 09:29:37,160 WARN util.NativeCodeLoader: Unable to load native-hadoop library for your platform... using builtin-java classes where applicable
cat: '/user/hadoop/test': Is a directory
hadoop@celab2-ThinkCentre-neo-50s-Gen-3:/opt/hadoop$ hdfs dfs -moveFromLocal /home/hadoop/Desktop/BDA_LAB_3_CE046/data.txt /user/hadoop/test
WARNING: HADOOP_PREFIX has been replaced by HADOOP_HOME. Using value of HADOOP_PREFIX.
2022-07-20 09:29:52,094 WARN util.NativeCodeLoader: Unable to load native-hadoop library for your platform... using builtin-java classes where applicable

```

```

hadoop@celab2-ThinkCentre-neo-50s-Gen-3:/opt/hadoop$ hdfs dfs -ls /user/hadoop/test
WARNING: HADOOP_PREFIX has been replaced by HADOOP_HOME. Using value of HADOOP_PREFIX.
2022-07-20 09:31:09,746 WARN util.NativeCodeLoader: Unable to load native-hadoop library for your platform... using builtin-java classes where applicable
Found 1 items
-rw-r--r-- 3 hadoop supergroup 125 2022-07-20 09:29 /user/hadoop/test/data.txt
hadoop@celab2-ThinkCentre-neo-50s-Gen-3:/opt/hadoop$ hdfs dfs -cat /user/hadoop/test/data.txt
WARNING: HADOOP_PREFIX has been replaced by HADOOP_HOME. Using value of HADOOP_PREFIX.
2022-07-20 09:31:15,237 WARN util.NativeCodeLoader: Unable to load native-hadoop library for your platform... using builtin-java classes where applicable
Hello I am Keval Gandevia.
I am student of computer science engineering at DD University.
I am doing IELTS for abroad study.
hadoop@celab2-ThinkCentre-neo-50s-Gen-3:/opt/hadoop$

```

```

hadoop@celab2-ThinkCentre-neo-50s-Gen-3:~/Desktop/BDA_LAB_3_CE046$ ls
screenshots
hadoop@celab2-ThinkCentre-neo-50s-Gen-3:~/Desktop/BDA_LAB_3_CE046$ cat data.txt
cat: data.txt: No such file or directory
hadoop@celab2-ThinkCentre-neo-50s-Gen-3:~/Desktop/BDA_LAB_3_CE046$

```

## Q. 5: Find out CLI way to display all file system commands supported by HDFS. Record the list.

❖ To find out all file system commands we can use 'help' command.



```

hadoop@celab2-ThinkCentre-neo-50s-Gen-3:/opt/hadoop$ hdfs dfs -help
WARNING: HADOOP_PREFIX has been replaced by HADOOP_HOME. Using value of HADOOP_PREFIX.
2022-07-20 09:35:27,604 WARN util.NativeCodeLoader: Unable to load native-hadoop library for your platform... using builtin-java classes where applicable
Usage: hadoop fs [generic options]
    [-appendToFile <localsrc> ... <dst>]
    [-cat [-ignoreCrc] <src> ...]
    [-checksum [-v] <src> ...]
    [-chgrp [-R] GROUP PATH...]
    [-chmod [-R] <MODE[,MODE]... | OCTALMODE> PATH...]
    [-chown [-R] [OWNER][:[GROUP]] PATH...]
    [-concat <target path> <src path> <src path> ...]
    [-copyFromLocal [-f] [-p] [-l] [-d] [-t <thread count>] [-q <thread pool queue size>] <localsrc> ... <dst>]
    [-copyToLocal [-f] [-p] [-crc] [-ignoreCrc] [-t <thread count>] [-q <thread pool queue size>] <src> ... <localdst>]
    [-count [-q] [-h] [-v] [-t <storage type>]] [-u] [-x] [-e] [-s] <path> ...]
    [-cp [-f] [-p | -p[topax]] [-d] [-t <thread count>] [-q <thread pool queue size>] <src> ... <dst>]
    [-createSnapshot <snapshotDir> [<snapshotName>]]
    [-deleteSnapshot <snapshotDir> <snapshotName>]
    [-df [-h] [<path> ...]]
    [-du [-s] [-h] [-v] [-x] <path> ...]
    [-expunge [-immediate] [-fs <path>]]
    [-find <path> ... <expression> ...]
    [-get [-f] [-p] [-crc] [-ignoreCrc] [-t <thread count>] [-q <thread pool queue size>] <src> ... <localdst>]
    [-getfacl [-R] <path>]
    [-getfattr [-R] {-n name | -d} [-e en] <path>]
    [-getmerge [-nl] [-skip-empty-file] <src> <localdst>]
    [-head <file>]
    [-help [cmd ...]]
    [-ls [-C] [-d] [-h] [-q] [-R] [-t] [-S] [-r] [-u] [-e] [<path> ...]]
    [-mkdir [-p] <path> ...]
    [-moveFromLocal [-f] [-p] [-l] [-d] <localsrc> ... <dst>]
    [-moveToLocal <src> <localdst>]
    [-mv <src> ... <dst>]
    [-put [-f] [-p] [-l] [-d] [-t <thread count>] [-q <thread pool queue size>] <localsrc> ... <dst>]
    [-renameSnapshot <snapshotDir> <oldName> <newName>]
    [-rm [-f] [-r|-R] [-skipTrash] [-safely] <src> ...]
    [-rmdir [--ignore-fail-on-non-empty] <dir> ...]
    [-setfacl [-R] [{-b|-k} {-m|-x <acl_spec>} <path>}][--set <acl_spec> <path>]]
    [-setfattr [-R] {-n name [-v value] | -x name} <path>]
    [-setrep [-R] [-w] <rep> <path> ...]
    [-stat [format] <path> ...]
    [-tail [-f] [-s <sleep interval>] <file>]
    [-test [-defswrz] <path>]
    [-text [-ignoreCrc] <src> ...]
    [-touch [-a] [-m] [-t TIMESTAMP (yyyyMMdd:HHmmss) ] [-c] <path> ...]
    [-touchz <path> ...]
    [-truncate [-w] <length> <path> ...]
    [-usage [cmd ...]]

```


```

    [-setfacl [-R] [{-b|-k} {-m|-x <acl_spec>} <path>}][--set <acl_spec> <path>]]
    [-setfattr {-n name [-v value] | -x name} <path>]
    [-setrep [-R] [-w] <rep> <path> ...]
    [-stat [format] <path> ...]
    [-tail [-f] [-s <sleep interval>] <file>]
    [-test [-defswrz] <path>]
    [-text [-ignoreCrc] <src> ...]
    [-touch [-a] [-m] [-t TIMESTAMP (yyyyMMdd:HHmmss) ] [-c] <path> ...]
    [-touchz <path> ...]
    [-truncate [-w] <length> <path> ...]
    [-usage [cmd ...]]


```

## Q. 6: Perform file operations through Web GUI.




- ❖ We can upload file to distributed file system through web GUI.



❖ Successfully uploaded.



❖ We can download the file and also can see the content of the file.



❖ We can delete the file from the distributed file system through GUI.

