




FUDAN SOE SUMMER SCHOOL INTRODUCTION TO AI

Probabilistic Reasoning and Decision Making
Day 10 – EM for Noisy-OR, Hidden Markov Model (HMM)


EM for Learning Noisy-OR model




Problem: From *complete* data $\{(x_1^{(t)}, x_2^{(t)}, \dots, x_n^{(t)}, y^{(t)})\}_{t=1}^T$, estimate $p_i \in [0,1]$.

EM for Learning Noisy-OR: Alternate model

Problem: From (complete) data $\{(x_1^{(t)}, x_n^{(t)}, \dots, x_n^{(t)}, y^{(t)})\}_{t=1}^T$, estimate $p_i \in [0,1]$.



$$P(Y = 1 | x_1, x_2, \dots, x_n) = 1 - \prod_{i=1}^n (1 - p_i)^{x_i}$$



EM for Learning Noisy-OR: Alternate model


Problem: From (complete) data $\{(x_1^{(t)}, x_n^{(t)}, \dots, x_n^{(t)}, y^{(t)})\}_{t=1}^T$, estimate $p_i \in [0,1]$.

$$P(Z_i = 0 | X_i = 0) = 1$$

$$P(Z_i = 1 | X_i = 1) = p_i$$

What is $P(Y = 1 | x_1, x_2, \dots, x_n)$ in this alternate model?

First show that $P(Y = 1 | \vec{x}) = \sum_{\vec{z}} P(Y = 1 | \vec{z}) P(\vec{z} | \vec{x})$



$$P(Y | \vec{z}) = \text{OR}(\vec{z})$$

EM for Learning Noisy-OR: Alternate model


Problem: From (complete) data $\{(x_1^{(t)}, x_n^{(t)}, \dots, x_n^{(t)}, y^{(t)})\}_{t=1}^T$, estimate $p_i \in [0,1]$.

$$P(Z_i = 0 | X_i = 0) = 1$$

$$P(Z_i = 1 | X_i = 1) = p_i$$

What is $P(Y = 1 | x_1, x_2, \dots, x_n)$ in this alternate model?

$$P(Y = 1 | \vec{x}) = \sum_{\vec{z}} \boxed{P(Y = 1 | \vec{z}) P(\vec{z} | \vec{x})}$$



$$P(Y | \vec{z}) = \text{OR}(\vec{z})$$

When is the term in the red box 0?

- A. When at least one z_i is 0
- B. When all z_i s are 0
- C. You can't tell from the information given

EM for Learning Noisy-OR: Alternate model


Problem: From (complete) data $\{(x_1^{(t)}, x_n^{(t)}, \dots, x_n^{(t)}, y^{(t)})\}_{t=1}^T$, estimate $p_i \in [0,1]$.

$$P(Z_i = 0 | X_i = 0) = 1$$

$$P(Z_i = 1 | X_i = 1) = p_i$$

What is $P(Y = 1 | x_1, x_2, \dots, x_n)$ in this alternate model?

$$P(Y = 1 | \vec{x}) = \sum_{\vec{z}} P(Y = 1 | \vec{z}) P(\vec{z} | \vec{x})$$




$$P(Y | \vec{z}) = \text{OR}(\vec{z})$$

EM for Learning Noisy-OR: Alternate model

Problem: From (complete) data $\{(x_1^{(t)}, x_n^{(t)}, \dots, x_n^{(t)}, y^{(t)})\}_{t=1}^T$, estimate $p_i \in [0,1]$.

$$P(Z_i = 0 | X_i = 0) = 1$$

$$P(Z_i = 1 | X_i = 1) = p_i$$



$$P(Y | \vec{Z}) = \text{OR}(\vec{Z})$$

What is $P(Y = 1 | x_1, x_2, \dots, x_n)$ in this alternate model?

$$P(Y = 1 | \vec{x}) = \sum_{\vec{z}} P(Y = 1 | \vec{z}) P(\vec{z} | \vec{x}) = \sum_{\vec{z} \neq 0} P(\vec{z} | \vec{x}) =$$

- A. $P(\vec{z} = 0 | \vec{x})$
- B. $1 - P(\vec{z} = 0 | \vec{x})$
- C. $P(\vec{z} | \vec{x} = 0)$
- D. $1 - P(\vec{z} | \vec{x} = 0)$
- E. None of these

EM for Learning Noisy-OR: Alternate model


Problem: From (complete) data $\{(x_1^{(t)}, x_2^{(t)}, \dots, x_n^{(t)}, y^{(t)})\}_{t=1}^T$, estimate $p_i \in [0,1]$.

$$P(Z_i = 0 | X_i = 0) = 1$$

$$P(Z_i = 1 | X_i = 1) = p_i$$

What is $P(Y = 1 | x_1, x_2, \dots, x_n)$ in this alternate model?

$$P(Y = 1 | \vec{x}) = \sum_{\vec{z}} P(Y = 1 | \vec{z}) P(\vec{z} | \vec{x}) = \sum_{\vec{z} \neq 0} P(\vec{z} | \vec{x}) = 1 - P(\vec{z} = 0 | \vec{x})$$



$$P(Y | \vec{z}) = \text{OR}(\vec{z})$$

Learning $P(Z_i = 1|X_i = 1) = p_i$ using EM

- If we had fully observed data:

Learning $P(Z_i = 1|X_i = 1) = p_i$ using EM


$$\widehat{count}(Z_i = 1, X_i = 1) = \sum_{t=1}^T P(Z_i = 1, X_i = 1 | \vec{x}^{(t)}, y^{(t)})$$

Learning $P(Z_i = 1|X_i = 1) = p_i$ using EM:
 Calculate $P(Z_i = 1|\vec{x}^{(t)}, y^{(t)})$ with current params

$$P(Z_i = 0|X_i = 0) = 1$$

$$P(Z_i = 1|X_i = 1) = p_i$$

$$\widehat{\text{count}}(Z_i = 1, X_i = 1) = \sum_{t=1}^T P(Z_i = 1, X_i = 1|\vec{x}^{(t)}, y^{(t)}) = \sum_{t=1}^T x_i^{(t)} P(Z_i = 1|\vec{x}^{(t)}, y^{(t)})$$



$$P(Y|\vec{Z}) = \text{OR}(\vec{Z})$$

$$P(Z_i = 1|\vec{x}^{(t)}, y^{(t)}) = \frac{P(Y = y^{(t)}|Z_i = 1)P(Z_i = 1|\vec{x}^{(t)})}{P(Y = y^{(t)}|\vec{x}^{(t)})}$$

Which of the following is NOT a true statement?


- A. $P(Y = y^{(t)}|Z_i = 1) = 0$ when $y^{(t)} = 0$
- B. $P(Y = y^{(t)}|Z_i = 1) = 1$ when $y^{(t)} = 1$
- C. $P(Z_i = 1|\vec{x}^{(t)}) = 1$ when $x_i^{(t)} = 1$
- D. $P(Z_i = 1|\vec{x}^{(t)}) = 0$ when $x_i^{(t)} = 0$
- E. More than one of the above is NOT true

Learning $P(Z_i = 1 | X_i = 1) = p_i$ using EM:
 Calculate $P(Z_i = 1 | \vec{x}^{(t)}, y^{(t)})$ with current params

$$P(Z_i = 0 | X_i = 0) = 1$$

$$P(Z_i = 1 | X_i = 1) = p_i$$

$$\widehat{\text{count}}(Z_i = 1, X_i = 1) = \sum_{t=1}^T P(Z_i = 1, X_i = 1 | \vec{x}^{(t)}, y^{(t)}) = \sum_{t=1}^T x_i^{(t)} P(Z_i = 1 | \vec{x}^{(t)}, y^{(t)})$$




$$P(Y | \vec{Z}) = \text{OR}(\vec{Z})$$

$$P(Z_i = 1 | \vec{x}^{(t)}, y^{(t)}) = \frac{P(Y = y^{(t)} | Z_i = 1) P(Z_i = 1 | \vec{x}^{(t)})}{P(Y = y^{(t)} | \vec{x}^{(t)})}$$

Learning $P(Z_i = 1|X_i = 1) = p_i$ using EM: Update rule

$$P(Z_i = 0|X_i = 0) = 1$$

$$P(Z_i = 1|X_i = 1) = p_i$$



$$P(Y|\vec{z}) = \text{OR}(\vec{z})$$



$$\widehat{\text{count}}(Z_i = 1, X_i = 1) = \sum_{t=1}^T \left[\frac{p_i y^{(t)} x_i^{(t)}}{1 - \prod_{i=1}^n (1 - p_i) x_i^{(t)}} \right]$$

$$p_i \leftarrow \frac{\widehat{\text{count}}(Z_i = 1, X_i = 1)}{\widehat{\text{count}}(X_i = 1)} = \frac{p_i}{T_i} \sum_{t=1}^T \left[\frac{y^{(t)} x_i^{(t)}}{1 - \prod_{i=1}^n (1 - p_i) x_i^{(t)}} \right]$$

Markov chains (Bayes Net)

(1st order)

State



Two simplifying assumptions:

1. Finite Context

$$P(S_t | S_1 \dots S_{t-1}) = P(S_t | S_{t-1}) \quad \begin{array}{l} \text{(1st order)} \\ \text{makes CPTs very small} \end{array}$$

2. Position Invariance



$$P(S_{t+1} = j | S_t = i) = P(S_{t+k+1} = j | S_{t+k} = i) \quad \begin{array}{l} \text{(save} \\ \text{a lot of} \\ \text{CPTs)} \end{array}$$

Bayes Net

Hidden Markov Models (HMMs): An extension of Markov chains

True or False: An HMM is a polytree.

- A. True
- B. False



finite context

$$\left[\begin{aligned} P(S_t | S_1 \dots S_{t-1}) &= P(S_t | S_{t-1}) \\ P(O_t | S_1 \dots S_t) &= P(O_t | S_t) \end{aligned} \right]$$

Assumptions


position invariant

$$\left[\begin{aligned} P(S_{t+1} | S_t) &= P(S_{t+k+1} | S_{t+k}) \\ P(O_t | S_t) &= P(O_{t+k} | S_{t+k}) \end{aligned} \right]$$

CPTs are matrices

HMM examples

- HMMs for language: If the hidden states are words, what might the observations be?




- HMMs for Robotics: If the hidden states are the robot's orientation and location, what might the observations be?

- HMMs for biology: if the hidden states are status of genes in DNA, what might the observations be?

State: gene or not

observed: GATC sequence


Conditional Independence in an HMM



Is the statement below true (A) or false (B)?

$$P(S_t|S_{t-1}) = P(S_t|S_{t-1}, O_t)$$



Conditional Independence in an HMM



Is the statement below true (A) or false (B)?

$$P(S_2, S_3, \dots, S_T | S_1) = \prod_{t=2}^T P(S_t | S_{t-1})$$


Parameters of the HMM



Which of the following is NOT a parameter of this model?

- A. $P(s_t | s_{t+1})$
- B. $P(s_1)$
- C. $P(o_t | o_{t-1})$
- D. $P(o_t | s_t)$
- E. More than one of these is NOT a parameter of the model


HMM Key Questions



$$\begin{aligned} a_{ij} &= P(S_t = j | S_{t-1} = i) \\ b_{io_k} &= P(O_t = o_k | S_t = i) \\ \pi_i &= P(S_1 = i) \end{aligned}$$

1. How to compute $P(o_1, o_2, o_3, \dots o_T)$
2. How to compute the most likely state sequence given observations
3. How to update beliefs for real-time monitoring
4. How to learn HMMs from data

How to compute $P(o_1, o_2, o_3, \dots o_T)$




$$\begin{aligned} a_{ij} &= P(S_t = j | S_{t-1} = i) \\ b_{io_k} &= P(O_t = o_k | S_t = i) \\ \pi_i &= P(S_1 = i) \end{aligned}$$

$$P(o_1, o_2, o_3, \dots o_T) = \sum_{\vec{s}} P(s_1 \dots s_T, o_1 \dots o_T)$$

Use the structure of the HMM to factor this joint probability


How to compute $P(o_1, o_2, o_3, \dots o_T)$ efficiently using the "forward algorithm"



$$\begin{aligned} a_{ij} &= P(S_t = j | S_{t-1} = i) \\ b_{io_k} &= P(O_t = o_k | S_t = i) \\ \pi_i &= P(S_1 = i) \end{aligned}$$

Let $\alpha_{it} \leftarrow P(o_1, \dots o_t, s_t = i)$

How to compute $P(o_1, o_2, o_3, \dots o_T)$ efficiently using the "forward algorithm"




$$\begin{aligned} a_{ij} &= P(S_t = j | S_{t-1} = i) \\ b_{io_k} &= P(O_t = o_k | S_t = i) \\ \pi_i &= P(S_1 = i) \end{aligned}$$

Let $\alpha_{it} \leftarrow P(o_1, \dots o_t, s_t = i)$

$P(o_1, o_2, o_3, \dots o_T) =$

How to compute $P(o_1, o_2, o_3, \dots o_T)$ efficiently using the "forward algorithm"




$$\begin{aligned} a_{ij} &= P(S_t = j | S_{t-1} = i) \\ b_{io_k} &= P(O_t = o_k | S_t = i) \\ \pi_i &= P(S_1 = i) \end{aligned}$$

Let $\alpha_{it} \leftarrow P(o_1, \dots o_t, s_t = i)$

$$P(o_1, o_2, o_3, \dots o_T) = \sum_{i=1}^n P(o_1, \dots o_T, s_T = i) = \sum_{i=1}^n \alpha_{iT}$$

$$\alpha_{jt+1} =$$

How to compute $P(o_1, o_2, o_3, \dots o_T)$ efficiently using the "forward algorithm"



$$\begin{aligned} a_{ij} &= P(S_t = j | S_{t-1} = i) \\ b_{io_k} &= P(O_t = o_k | S_t = i) \\ \pi_i &= P(S_1 = i) \end{aligned}$$


Let $\alpha_{it} \leftarrow P(o_1, \dots o_t, s_t = i)$

$$P(o_1, o_2, o_3, \dots o_T) = \sum_{i=1}^n P(o_1, \dots o_T, s_T = i) = \sum_{i=1}^n \alpha_{iT}$$

$$\alpha_{jt+1} = \sum_{i=1}^n \alpha_{it} a_{ij} b_{jo_{t+1}}$$

$$\alpha_{i1} =$$

How to compute $P(o_1, o_2, o_3, \dots o_T)$ efficiently using the "forward algorithm"



$$\begin{aligned} a_{ij} &= P(S_t = j | S_{t-1} = i) \\ b_{io_k} &= P(O_t = o_k | S_t = i) \\ \pi_i &= P(S_1 = i) \end{aligned}$$


Let $\alpha_{it} \leftarrow P(o_1, \dots o_t, s_t = i)$

$$P(o_1, o_2, o_3, \dots o_T) = \sum_{i=1}^n P(o_1, \dots o_T, s_T = i) = \sum_{i=1}^n \alpha_{iT}$$

$$\alpha_{jt+1} = \sum_{i=1}^n \alpha_{it} a_{ij} b_{jo_{t+1}}$$

$$\alpha_{i1} = \pi_i b_{io_1}$$

How to compute $\arg \max_{\vec{s}} (P(s_1 \dots s_T | o_1 \dots o_T))$




$$\begin{aligned} a_{ij} &= P(S_t = j | S_{t-1} = i) \\ b_{io_k} &= P(O_t = o_k | S_t = i) \\ \pi_i &= P(S_1 = i) \end{aligned}$$

Is the following equality true? (and why or why not?) A. Yes B. No

$$\arg \max_{\vec{s}} (P(s_1 \dots s_T | o_1 \dots o_T)) = \arg \max_{\vec{s}} (P(s_1 \dots s_T, o_1 \dots o_T))$$

How to compute $\arg \max_{\vec{s}} (P(s_1 \dots s_T | o_1 \dots o_T))$



$$\begin{aligned} a_{ij} &= P(S_t = j | S_{t-1} = i) \\ b_{io_k} &= P(O_t = o_k | S_t = i) \\ \pi_i &= P(S_1 = i) \end{aligned}$$


$$(s_1^*, s_2^*, \dots, s_T^*) = \arg \max_{\vec{s}} (P(s_1 \dots s_T, o_1 \dots o_T))$$

Define $\ell_{it}^* = \max_{s_1 \dots s_{t-1}} \log P(s_1 \dots s_{t-1}, s_t = i, o_1 \dots o_t)$

What does ℓ_{it}^* mean, in English?

- A. The log probability of the most likely set of states $s_1 \dots s_{t-1}, s_t$ given observations $o_1 \dots o_t$
- B. The state that is most likely at time t
- C. The log probability of the most likely set of states $s_1 \dots s_{t-1}, s_t$ that ends in state $s_t = i$ and explains observations $o_1 \dots o_t$
- D. The log probability of only state $s_t = i$ that explains observations $o_1 \dots o_t$

How to compute $\arg \max_{\vec{s}} (P(s_1 \dots s_T | o_1 \dots o_T))$



$$\begin{aligned} a_{ij} &= P(S_t = j | S_{t-1} = i) \\ b_{io_k} &= P(O_t = o_k | S_t = i) \\ \pi_i &= P(S_1 = i) \end{aligned}$$


$$(s_1^*, s_2^*, \dots, s_T^*) = \arg \max_{\vec{s}} (P(s_1 \dots s_T, o_1 \dots o_T))$$

Define $\ell_{it}^* = \max_{s_1 \dots s_{t-1}} \log P(s_1 \dots s_{t-1}, s_t = i, o_1 \dots o_t)$

Viterbi algorithm:

1. Fill in an $n \times T$ table with the values of ℓ_{it}^* from left to right. Fill in a second table to keep track of best i 's at each time t at the same time.
2. Backtrack through the second table from right to left to determine which state i at time t led to the best outcome at time $t+1$

	1	2	...	t-1	t	t+1	...	T
1								
...								
n								




$$\begin{aligned}
 a_{ij} &= P(S_t = j | S_{t-1} = i) \\
 b_{io_k} &= P(O_t = o_k | S_t = i) \\
 \pi_i &= P(S_1 = i)
 \end{aligned}$$

$$(s_1^*, s_2^*, \dots, s_T^*) = \arg \max_{\vec{s}} (P(s_1 \dots s_T, o_1 \dots o_T))$$

$$\text{Define } \ell_{it}^* = \max_{s_1 \dots s_{t-1}} \log P(s_1 \dots s_{t-1}, s_t = i, o_1 \dots o_t)$$

$$\ell_{j,t+1}^* =$$



$$\begin{aligned}
 a_{ij} &= P(S_t = j | S_{t-1} = i) \\
 b_{io_k} &= P(O_t = o_k | S_t = i) \\
 \pi_i &= P(S_1 = i)
 \end{aligned}$$


$$(s_1^*, s_2^*, \dots, s_T^*) = \arg \max_{\vec{s}} (P(s_1 \dots s_T, o_1 \dots o_T))$$

$$\text{Define } \ell_{it}^* = \max_{s_1 \dots s_{t-1}} \log P(s_1 \dots s_{t-1}, s_t = i, o_1 \dots o_t)$$

$$\ell_{j,t+1}^* = \max_i \{ \ell_{it}^* + \log a_{ij} \} + \log b_{jo_{t+1}}$$

$$\ell_{i1}^*$$

How to compute $\arg \max_{\vec{s}} (P(s_1 \dots s_T | o_1 \dots o_T))$



$$\begin{aligned} a_{ij} &= P(S_t = j | S_{t-1} = i) \\ b_{ik} &= P(O_t = k | S_t = i) \\ \pi_i &= P(S_1 = i) \end{aligned}$$

$$(s_1^*, s_2^*, \dots, s_T^*) = \arg \max_{\vec{s}} (P(s_1 \dots s_T, o_1 \dots o_T))$$


Define $\ell_{it}^* = \max_{s_1 \dots s_{t-1}} \log P(s_1 \dots s_{t-1}, s_t = i, o_1 \dots o_t)$

$$\ell_{i1}^* = \log[\pi_i b_{io_1}]$$

$$\ell_{jt+1}^* = \max_i \{ \ell_{it}^* + \log a_{ij} \} + \log b_{jo_{t+1}}$$

	1	2	...	t-1	t	t+1	...	T
1								
...								
n								

The table represents a dynamic programming table for the HMM. The columns represent time steps from 1 to T, and the rows represent hidden states from 1 to n. A red bracket above the table indicates the time dimension (T), and a red bracket to the right indicates the state dimension (n).



$$\begin{aligned}
 a_{ij} &= P(S_t = j | S_{t-1} = i) \\
 b_{io_k} &= P(O_t = o_k | S_t = i) \\
 \pi_i &= P(S_1 = i)
 \end{aligned}$$


$$(s_1^*, s_2^*, \dots, s_T^*) = \arg \max_{\vec{s}} (P(s_1 \dots s_T, o_1 \dots o_T))$$

$$\text{Define } \ell_{it}^* = \max_{s_1 \dots s_{t-1}} \log P(s_1 \dots s_{t-1}, s_t = i, o_1 \dots o_t)$$

Viterbi algorithm:

1. Fill in an $n \times T$ table with the values of ℓ_{it}^* from left to right. Fill in a second table to keep track of best i 's at each time t at the same time.
2. Backtrack through the second table from right to left to determine which state i at time t led to the best outcome at time $t+1$

	1	2	...	t-1	t	t+1	...	T
1								
...								
n								



$$\begin{aligned}
 a_{ij} &= P(S_t = j | S_{t-1} = i) \\
 b_{io_k} &= P(O_t = o_k | S_t = i) \\
 \pi_i &= P(S_1 = i)
 \end{aligned}$$

$$(s_1^*, s_2^*, \dots, s_T^*) = \arg \max_{\vec{s}} (P(s_1 \dots s_T, o_1 \dots o_T))$$

$$\text{Define } \ell_{it}^* = \max_{s_1 \dots s_{t-1}} \log P(s_1 \dots s_{t-1}, s_t = i, o_1 \dots o_t)$$

Viterbi algorithm:

1. Fill in an $n \times T$ table with the values of ℓ_{it}^* from left to right. Fill in a second table to keep track of best i 's at each time t at the same time.
2. Backtrack through the second table from right to left to determine which state i at time t led to the best outcome at time $t+1$

	1	2	...	t-1	t	t+1	...	T
1								
...								
n								

Viterbi alg. to find $(s_1^*, s_2^*, \dots, s_T^*) = \arg \max_{\vec{s}} (P(s_1 \dots s_T, o_1 \dots o_T))$

Define $\ell_{it}^* = \max_{s_1 \dots s_{t-1}} \log P(s_1 \dots s_{t-1}, s_t = i, o_1 \dots o_t)$

$$\ell_{i1}^* = \log[\pi_i b_{io_1}]$$

$$\ell_{jt+1}^* = \max_i \{ \ell_{it}^* + \log a_{ij} \} + \log b_{jo_{t+1}}$$

$$\arg \max_i \{ \ell_{it}^* + \log a_{ij} \}$$

Consider the value in the shaded box. How does its value depend on the values from the previous column (at time t)?

- A. It is a weighted sum of all of the values from the previous column
- B. It uses only one of the values from the previous column
- C. It does not use any of the values from the previous column

	1	2	...	t-1	t	t+1	...	T
1								
...						ℓ_{jt+1}^*		
n								

	1	2	...	t-1	t	t+1	...	T
1								
...						ℓ_{jt+1}^*		
n								

Viterbi alg. to find $(s_1^*, s_2^*, \dots, s_T^*) = \arg \max_{\vec{s}} (P(s_1 \dots s_T, o_1 \dots o_T))$

Define $\ell_{it}^* = \max_{s_1 \dots s_{t-1}} \log P(s_1 \dots s_{t-1}, s_t = i, o_1 \dots o_t)$

$$\ell_{i1}^* = \log[\pi_i b_{io_1}]$$

$$\ell_{jt+1}^* = \max_i \{ \ell_{it}^* + \log a_{ij} \} + \log b_{jo_{t+1}}$$

$$\Phi_{jt+1} \leftarrow \arg \max_i \{ \ell_{it}^* + \log a_{ij} \}$$

T

	1	2	...	t-1	t	t+1	...	T
1								
...						ℓ_{jt+1}^*		
n								

n

	1	2	...	t-1	t	t+1	...	T
1								
...						Φ_{jt+1}		
n								

Viterbi alg. to find $(s_1^*, s_2^*, \dots, s_T^*) = \arg \max_{\vec{s}} (P(s_1 \dots s_T, o_1 \dots o_T))$

Define $\ell_{it}^* = \max_{s_1 \dots s_{t-1}} \log P(s_1 \dots s_{t-1}, s_t = i, o_1 \dots o_t)$

$$\ell_{i1}^* = \log[\pi_i b_{io_1}]$$

$$\ell_{jt+1}^* = \max_i \{ \ell_{it}^* + \log a_{ij} \} + \log b_{jo_{t+1}}$$

Define $\Phi_{jt+1} = \arg \max_i \{ \ell_{it}^* + \log a_{ij} \}$

	1	2	...	t-1	t	t+1	...	T
1								
...						ℓ_{jt+1}^*		
n								

TWO tables:

1. Table of ℓ_{i1}^* , filled in from left to right
2. Table of $\Phi_{i,t}$, filled in from left to right at the same time (column 1 will be empty)

	1	2	...	t-1	t	t+1	...	T
1								
...						$\Phi_{j,t+1}$		
n								

Viterbi alg. to find $(s_1^*, s_2^*, \dots, s_T^*) = \arg \max_{\vec{s}} (P(s_1 \dots s_T, o_1 \dots o_T))$

Define $\ell_{it}^* = \max_{s_1 \dots s_{t-1}} \log P(s_1 \dots s_{t-1}, s_t = i, o_1 \dots o_t)$

	1	2	...	t-1	t	t+1	...	T
1								
...						ℓ_{jt+1}^*		
n								

Define $\Phi_{j,t+1} = \operatorname{argmax}_i \{\ell_{it}^* + \log a_{ij}\}$

	1	2	...	t-1	t	t+1	...	T
1								
...						$\Phi_{j,t+1}$		
n								

Once both tables are filled in with values, how can you find $(s_1^*, s_2^*, \dots, s_T^*)$?

- Tracing a path from left to right (forward: starting at column 1) in the ℓ_{it}^* table
- Tracing a path from left to right (forward: starting at column 1) in the $\Phi_{j,t}$ table
- Tracing a path from right to left (backward: starting at column T) in the ℓ_{it}^* table
- Tracing a path from right to left (backward: starting at column T) in the $\Phi_{j,t}$ table

Viterbi alg. to find $(s_1^*, s_2^*, \dots, s_T^*) = \arg \max_{\vec{s}} (P(s_1 \dots s_T, o_1 \dots o_T))$

Define $\ell_{it}^* = \max_{s_1 \dots s_{t-1}} \log P(s_1 \dots s_{t-1}, s_t = i, o_1 \dots o_t)$

	1	2	...	t-1	t	t+1	...	T
1								
...						ℓ_{jt+1}^*		
n								

Define $\Phi_{j,t+1} = \operatorname{argmax}_i \{\ell_{it}^* + \log a_{ij}\}$

	1	2	...	t-1	t	t+1	...	T
1								
...						$\Phi_{j,t+1}$		
n								

To recover $(s_1^*, s_2^*, \dots, s_T^*)$:

Viterbi alg. to find $(s_1^*, s_2^*, \dots, s_T^*) = \arg \max_{\vec{s}} (P(s_1 \dots s_T, o_1 \dots o_T))$

Define $\ell_{it}^* = \max_{s_1 \dots s_{t-1}} \log P(s_1 \dots s_{t-1}, s_t = i, o_1 \dots o_t)$

	1	2	...	t-1	t	t+1	...	T
1								
...						ℓ_{jt+1}^*		
n								


Define $\Phi_{j,t+1} = \operatorname{argmax}_i \{\ell_{it}^* + \log a_{ij}\}$

	1	2	...	t-1	t	t+1	...	T
1								
...						$\Phi_{j,t+1}$		
n								

Complete Viterbi algorithm:

1. Create two $n \times T$ tables
2. Fill in both tables from leftmost column ($t=1$) to rightmost column ($t=T$) [using recursive formula for ℓ_{jt+1}^* and $\Phi_{j,t+1}$]
3. Recover path:
 1. Let $s_T^* = \operatorname{argmax}_i \ell_{iT}^*$
 2. For $t=T-1$ to 1 , $s_t^* = \Phi_{s_{t+1}^*, t+1}$

HMM Key Questions




$$\begin{aligned} a_{ij} &= P(S_t = j | S_{t-1} = i) \\ b_{io_k} &= P(O_t = o_k | S_t = i) \\ \pi_i &= P(S_1 = i) \end{aligned}$$

$$\begin{aligned} S_t &\in \{1, 2, \dots, n\} \\ O_t &\in \{1, 2, \dots, m\} \end{aligned}$$

1. How to compute $P(o_1, o_2, o_3, \dots, o_T)$ \leftarrow LAST WEEK (running time?)
2. How to compute the most likely state sequence given observations \leftarrow LAST TIME (running time?)
3. How to update beliefs for real-time monitoring
4. How to learn HMMs from data

Calculating $P(S_t = j | o_1, \dots, o_t)$




$$\begin{aligned} a_{ij} &= P(S_t = j | S_{t-1} = i) \\ b_{io_k} &= P(O_t = o_k | S_t = i) \\ \pi_i &= P(S_1 = i) \end{aligned}$$

$$\begin{aligned} S_t &\in \{1, 2, \dots, n\} \\ O_t &\in \{1, 2, \dots, m\} \end{aligned}$$

True (A) or False (B): $P(S_t = j | o_1, \dots, o_t) = P(S_t = j | o_t)$

Calculating $P(S_t = j | o_1, \dots, o_t)$




$$\begin{aligned} a_{ij} &= P(S_t = j | S_{t-1} = i) \\ b_{io_k} &= P(O_t = o_k | S_t = i) \\ \pi_i &= P(S_1 = i) \end{aligned}$$

$$S_t \in \{1, 2, \dots, n\}$$

$$O_t \in \{1, 2, \dots, m\}$$

$$q_{j,t} = P(S_t = j | o_1, \dots, o_{t-1}, o_t)$$

Calculating $P(S_t = j | o_1, \dots, o_t)$



$$a_{ij} = P(S_t = j | S_{t-1} = i)$$

$$b_{io_k} = P(O_t = o_k | S_t = i)$$

$$\pi_i = P(S_1 = i)$$

$$S_t \in \{1, 2, \dots, n\}$$

$$O_t \in \{1, 2, \dots, m\}$$

$$q_{j,t} = P(S_t = j | o_1, \dots, o_{t-1}, o_t)$$