

Linux command summary

Command	description
• ll	查看当前目录下的所有文件的权限
• ls -al	显示所有（包括隐藏的文件）文件
• date	查看系统时间
• pwd	显示当前目录
• mkdir/rmdir	新建或删除一个新的/空目录
• cd -	返回上一次 cd 的目录
• cat -n filename	查看当前文件内容，顺便输出行号
• mv file1 file2	将文件名 file1 改为 file2
• ctrl+z	暂停目前的命令
• ctrl+c	终止目前的命令
• ctrl+s	暂停屏幕的输出
• ctrl+q	恢复屏幕的输出
• jobs	查看当前有多少 job 在执行
• bg	查看当前后台执行的 job 情况
• fg % id	将后台运行的某个进程放到前台执行
• ps	查看当前执行的进程数
• kill jobid	关闭当前的某个进程
• ssh -X	登陆服务器，加 option X 表示服务器可以可视化
• su user	切换当前账户到 user 这个账户
• who	查看当前服务器登录的用户情况
• who am i	显示当前 local 用户登录信息
• exit	退出当前执行的账户
• xeyes	查看当前服务器是否可视化，如果可以就有 eyes 弹窗显示
• chmod xxx filename	修改文件的 permission（readable，writeable，executable）
• touch filename	当前目录下新建空文件 filename
• rm -rf	强制执行删除一个文件
• double tab	查看当前用户可执行的文件数或者操作数
• vimdiff file1 file2	比较当前两个文件的差异
• echo str	当前目录下查找含有特定字符的文件
• alias command='str'	对可执行文件设置 alias 方便经常执行调用
• more/less	一页一页地显示文件内容，向下翻页查看文件内容
• tail -f file	实时显示文件的状态，特别执行 job 时，查看 log 文件内容
• man command	查看 command 的操作指南，特别是 option 的 usage

About test

- `test -e demo.sh && echo "exist" || echo "not exist" #test the file demo.sh exist or not.`
- `test -z $filename && echo "you must input a filename"&& exit 0`
- `test ! -e $filename && echo "the filename does not exist" && exit 0`
- `test -f $filename && echo filetype="file is a filename"&& exit 0`
- `test -d $filename && echo filetype="file is a directory "&& exit 0`
- `test -r $filename && perm="readable"`
- `test -w $filename && perm="$perm writable"`
- `test -x $filename && perm="$perm executable" 1`

About file types

- Regular file `-frwxrwxrwx`
- ASCII file
- Binary file
- Date file
- Directory `drwxrwxrwx`
- Link `lrwxrwxrwx`
- Device/block file `brwxrwxrwx` /character file `crwxrwxrwx` /sockets file `srwxrwxrwx`
- Sockets
- FIFO, pipe

About vi/vim editors

➤ Regular mode

- `h/j/k/l` turn left/down/up/right
- `n<space>` turn right by n steps
- `G` turn to the bot
- `gg` turn to the top
- `/word` find the word downward
- `n` double find /word
- `N` double find /word reverse
- `?word` find the word upward
- `x, X` delete strings backward or forward
- `dd` delete the whole line
- `ndd` delete n lines downward
- `yy` copy the whole line
- `p, P` paste the copy context after/before this line.

- u rebuilt the last condition
- 0 turn to the head of line
- \$ turn to the end of line
- fa find the 1st string "a" forward
- 3fa fine the 3rd string "a" forward
- Ctrl+z 将当前的 vi,vim editor 放置到后台执行，回来用 fg

➤ Editor mode (insert mode)

- i change from regular to editor mode
- esc change from editor to regular mode
- ctrl+p auto polishing (自动补齐功能)

➤ Command mode

- : wq save change and exit
- : q! don't save change and exit
- : set nu/nonu set row numbers auto

➤ Multiple windows operate

- :sp filename in command mode
- Ctrl+w+(j/k) switch windows
- Ctrl+w+q exit multiple windows operate

About retarget data

- Com1 && com2 如果 com1 正确执行，则开始执行 com2，如果没有，com2 不执行
- Com1 || com2 如果 com1 正确执行，则 com2 不执行，如果没有，com2 执行

About pipe

- cut -d 'splits str' -f fields 查找出用 splits str 分割的变量的第 fields 的区域。
- cut -c fields 排列整齐的信息。
- grep [-acnv] --color=auto 'str' filename 按行查找文件中的指定字符串。
- xargs 由于很多 command 并不支持 pipe，所以加上 xargs 在前面可以读取 stdin.
- awk -F : '{print \$1 \$3 \$5}' 将得到的列表信息的第 1,3,5 列输出。
- > filename 将结果以文件 file 的形式保存，方便查看。

Linux setting usage

➤ Set display row number as default

1. `cp /usr/share/vim/vimrc ~/.vimrc` (if Redhot system, change usr to etc)
2. `vi ~/.vimrc`
3. go into editor mode
4. syntax on
5. set nu

FYI, check a blog link: <http://www.cnblogs.com/yjmyzz/p/4019783.html>

➤ Set open vim editor as default when using vi editor

1. `which vi vim`(display the directory)
2. `rm /bin/vi` or `mv /bin/vi /bin/vi/old`
3. `cp /usr/bin/vim /bin/vi` or `alias vi ='/usr/bin/vim'`

➤ Change strings in files by one time (very useful)

1. `sed -i "s/old str/new str/g" `grep old str -rl dir``

➤ About close process

1. `jobs` and `kill % num`
2. `ps` and `kill jobid`