

# Kennesaw State University

## Parallel and Distributed Computing

### Project - Pthread

S1= 🍈🍉🦉🦉❤️🦉🍎🍒🍎🍷❤️🦉

S2= ❤️🦉

Emoji is popular in today's world. Given two emoji strings s1 and s2. Write a Pthread program to find out the number of subEmojiStrings, in string s1, that is exactly the same as s2.

For example, suppose number\_subEmojiStrings(s1, s2) implements the function, then  
 number\_subEmojiStrings("🍈🍉🍎🍒🦉🍈🍉🍎🍒", "🍈🍉") = 2,  
 number\_subEmojiStrings("🍈🍉🍈🍉🍈🍉", "🍈") = 3,  
 number\_subEmojiStrings("❤️❤️❤️❤️", "❤️❤️") = 0.

The size of s1 and s2 (n1 and n2) as well as their data are input by user file. Assume that  
 n1 mod NUM\_THREADS = 0  
 and  
 n2 < n1/NUM\_THREADS.

The following is a sequential solution of the problem. read\_f() reads the two emoji strings from a file named "emoji.txt and num\_subEmojiString() calculates the number of substrings. Here s1 is a string with thousands of emojis and s2 = "❤️🦉".

<https://github.com/kevinsuo/CS4504/blob/main/project-pthread.c>

```
-----
#include <stdlib.h>
#include <stdio.h>
#include <string.h>

#define MAX 10240

int total = 0;
int n1,n2;
char *s1,*s2;
FILE *fp;

int readf(FILE *fp)
{
    if((fp=fopen("emoji.txt", "r"))==NULL){
```

```

        printf("ERROR: can't open string.txt!\n");
        return 0;
    }
    s1=(char *)malloc(sizeof(char)*MAX);
    if(s1==NULL){
        printf("ERROR: Out of memory!\n");
        return -1;
    }
    s2=(char *)malloc(sizeof(char)*MAX);
    if(s1==NULL){
        printf("ERROR: Out of memory!\n");
        return -1;
    }
    /*read s1 s2 from the file*/
    s1=fgets(s1, MAX, fp);
    s2=fgets(s2, MAX, fp);
    n1=strlen(s1); /*length of s1*/
    n2=strlen(s2); /*length of s2*/
    if(s1==NULL || s2==NULL || n1<n2) /*when error exit*/
        return -1;
}

int num_subEmojiString(void)
{
    int i,j,k;
    int count;

    for (i = 0; i <= (n1-n2); i++){
        count=0;
        for(j = i,k = 0; k < n2; j++,k++){ /*search for the next string of size of n2*/
            if (*(s1+j) != *(s2+k)) {
                break;
            }
            else
                count++;
            if(count==n2)
                total++; /*find a substring in this step*/
        }
        return total;
    }
}

int main(int argc, char *argv[])
{
    int count;

    readf(fp);
    count = num_subEmojiString();
    printf("The number of substrings is: %d\n", count);
    return 1;
}

```

---

You can find an example of the “emoji.txt” here:

<https://raw.githubusercontent.com/kevinsuo/CS4504/main/emoji.txt>

To compile the program with Pthread, use:

`$ gcc project-pthread.c -o project-pthread.o -pthread`

Current output:

```
administrator@CS3502-14 ~/p2> ./project-pthread.o
The number of substrings is: 55
```

(Different text files output is also different. For the strings.txt, the output is 55)

Download the emoji.txt:

\$ wget <https://raw.githubusercontent.com/kevinsuo/CS4504/main/emoji.txt>

Write a parallel program using Pthread based on this sequential solution. Please set the thread number as **20** in your code. You can start with this template code:

<https://github.com/kevinsuo/CS4504/blob/main/parallel-template.c>

To compile the program with Pthread, use:

\$ gcc file.c -o file.o -pthread

Here file refers to your source code name.

Expected output:

```
ksuo@ltkup66583mac ~/Desktop> ./parallel.o
This is thread 0, num of substring 🍷 is █
This is thread 1, num of substring 🍷 is █
This is thread 2, num of substring 🍷 is █
This is thread 3, num of substring 🍷 is █
This is thread 4, num of substring 🍷 is █
This is thread 5, num of substring 🍷 is █
This is thread 6, num of substring 🍷 is █
This is thread 7, num of substring 🍷 is █
This is thread 8, num of substring 🍷 is █
This is thread 9, num of substring 🍷 is █
This is thread 10, num of substring 🍷 is █
This is thread 11, num of substring 🍷 is █
This is thread 12, num of substring 🍷 is █
This is thread 13, num of substring 🍷 is █
This is thread 14, num of substring 🍷 is █
This is thread 15, num of substring 🍷 is █
This is thread 16, num of substring 🍷 is █
This is thread 17, num of substring 🍷 is █
This is thread 18, num of substring 🍷 is █
This is thread 19, num of substring 🍷 is █
The number of substrings is: █
```

HINT: Strings s1 and s2 are stored in a file named “emoji.txt”. String s1 is evenly partitioned for `NUM_THREADS` threads to concurrently search for matching with string s2. After a thread finishes its work and obtains the number of local matchings, this local number is added into a global variable showing the total number of matched substrings in string s1. Finally, this

total number is printed out. Please make sure the number of substrings of parallel program is the same as the serial program.

## Submission

Submit your assignment file through D2L using the appropriate link.

The submission must include the *source code, output screenshot of your parallel code* and *a report describe your code logic.*