

CS 6041

Theory of Computation

Regular language

Kun Suo

Computer Science, Kennesaw State University

<https://kevinsuo.github.io/>

Regular language

- A language is called a regular language if some finite automaton (DFA) recognizes it
- A language is called a regular language if some nondeterministic finite automaton (NFA) recognizes it
- Regular language:
 - $L = L(M)$
 - M is DFA or NFA

Closure under the union

- Theorem: regular language is closed under the union operation.

- Proof idea:

In the past, we prove this by creating a DFA. This time we prove it by creating a NFA.




Closure under the union proved by DFA

- Proof:

Let $L_i = L(M_i)$ is a regular language, $M_i = (Q_i, \Sigma, \delta_i, q_i, F_i)$, $i=1,2$. We need to build a finite automata to recognize $L_1 \cup L_2$

Build $M_3 = (Q_3, \Sigma, \delta_3, q_3, F_3)$.

$Q_3 = Q_1 \times Q_2$;




Closure under the union proved by DFA

- Proof:

Let $L_i = L(M_i)$ is a regular language, $M_i = (Q_i, \Sigma, \delta_i, q_i, F_i)$, $i=1,2$. We need to build a finite automata to recognize $L_1 \cup L_2$

Build $M_3 = (Q_3, \Sigma, \delta_3, q_3, F_3)$.

$\delta_3((r_1, r_2), a) = (\delta_1(r_1, a), \delta_2(r_2, a))$;




Closure under the union proved by DFA

- Proof:

Let $L_i = L(M_i)$ is a regular language, $M_i = (Q_i, \Sigma, \delta_i, q_i, F_i)$, $i=1,2$. We need to build a finite automata to recognize $L_1 \cup L_2$

Build $M_3 = (Q_3, \Sigma, \delta_3, q_3, F_3)$.

$q_3 = (q_1, q_2)$;




Closure under the union proved by DFA

- Proof:

Let $L_i = L(M_i)$ is a regular language, $M_i = (Q_i, \Sigma, \delta_i, q_i, F_i)$, $i=1,2$. We need to build a finite automata to recognize $L_1 \cup L_2$

Build $M_3 = (Q_3, \Sigma, \delta_3, q_3, F_3)$.
 $F_3 = (F_1 \times Q_2) \cup (Q_1 \times F_2)$.

One accept state in M_1 with all states in M_2
One accept state in M_2 with all states in M_1



Closure under the union proved by DFA

- Proof:

Let $L_i = L(M_i)$ is a regular language, $M_i = (Q_i, \Sigma, \delta_i, q_i, F_i)$, $i=1,2$. We need to build a finite automata to recognize $L_1 \cup L_2$

Build $M_3 = (Q_3, \Sigma, \delta_3, q_3, F_3)$.

$Q_3 = Q_1 \times Q_2$;

$\delta_3((r_1, r_2), a) = (\delta_1(r_1, a), \delta_2(r_2, a))$;

$q_3 = (q_1, q_2)$;




$F_3 = (F_1 \times Q_2) \cup (Q_1 \times F_2)$.

$L(M_3) = L_1 \cup L_2$, so $L_1 \cup L_2$ is still regular language



Closure under the union

- Theorem: regular language is closed under the union operation.
- Proof idea:



Closure under the union

- Theorem: regular language is closed under the union operation.

- Proof:

Let NFA $N_i = (Q_i, \Sigma, \delta_i, q_i, F_i)$ recognize A_i , $i=1,2$.


Create NFA

$N = (Q, \Sigma, \delta, q_0, F)$ to recognize $A_1 \cup A_2$

Let $Q = Q_1 \cup Q_2 \cup \{q_0\}$

$F = F_1 \cup F_2$

$$\delta(q, a) = \begin{cases} \delta_1(q, a), & \text{if } q \in Q_1 \\ \delta_2(q, a), & \text{if } q \in Q_2 \\ \{q_1, q_2\}, & \text{if } q = q_0 \text{ and } a = \varepsilon \\ \emptyset, & \text{if } q = q_0 \text{ and } a \neq \varepsilon \end{cases}$$



Closure under the concatenation

- Theorem: regular language is closed under the concatenation operation.

- Proof idea:

In the past, we prove this by creating a DFA. This time we prove it by creating a NFA.




Closure under the concatenation proved by DFA

- Proof:

Let $L_i = L(M_i)$ is a regular language, $M_i = (Q_i, \Sigma, \delta_i, q_i, F_i)$, $i=1,2$. We need to build a finite automata to recognize $L_1 \cap L_2$

Build $M_3 = (Q_3, \Sigma, \delta_3, q_3, F_3)$.

$Q_3 = Q_1 \times Q_2$;





Closure under the concatenation proved by DFA

- Proof:

Let $L_i = L(M_i)$ is a regular language, $M_i = (Q_i, \Sigma, \delta_i, q_i, F_i)$, $i=1,2$. We need to build a finite automata to recognize $L_1 \cap L_2$

Build $M_3 = (Q_3, \Sigma, \delta_3, q_3, F_3)$.

$\delta_3((r_1, r_2), a) = (\delta_1(r_1, a), \delta_2(r_2, a));$




Closure under the concatenation proved by DFA

- Proof:

Let $L_i = L(M_i)$ is a regular language, $M_i = (Q_i, \Sigma, \delta_i, q_i, F_i)$, $i=1,2$. We need to build a finite automata to recognize $L_1 \cap L_2$

Build $M_3 = (Q_3, \Sigma, \delta_3, q_3, F_3)$.

$q_3 = (q_1, q_2)$;



Closure under the concatenation proved by DFA


- Proof:

Let $L_i = L(M_i)$ is a regular language, $M_i = (Q_i, \Sigma, \delta_i, q_i, F_i)$, $i=1,2$. We need to build a finite automata to recognize $L_1 \cap L_2$

Build $M_3 = (Q_3, \Sigma, \delta_3, q_3, F_3)$.

$F_3 = F_1 \times F_2$.

One accept state in M_1 with
One accept state in M_2



Closure under the concatenation proved by DFA

- Proof:

Let $L_i = L(M_i)$ is a regular language, $M_i = (Q_i, \Sigma, \delta_i, q_i, F_i)$, $i=1,2$. We need to build a finite automata to recognize $L_1 \cap L_2$

Build $M_3 = (Q_3, \Sigma, \delta_3, q_3, F_3)$.

$Q_3 = Q_1 \times Q_2$;

$\delta_3((r_1, r_2), a) = (\delta_1(r_1, a), \delta_2(r_2, a))$;

$q_3 = (q_1, q_2)$;


$F_3 = F_1 \times F_2$.

$L(M_3) = L_1 \cap L_2$, so $L_1 \cap L_2$ is still regular language



Closure under the concatenation

- Theorem: regular language is closed under the concatenation operation.



Closure under the concatenation

- Theorem: regular language is closed under the concatenation operation.

- Proof:


Let NFA $N_i = (Q_i, \Sigma, \delta_i, q_i, F_i)$ recognize A_i , $i=1,2$.

Create NFA

$N = (Q, \Sigma, \delta, q_1, F)$ to recognize $A_1 \cap A_2$

Let $Q = Q_1 \cup Q_2$
 $F = F_2$


$$\delta(q, a) = \begin{cases} \delta_1(q, a), & \text{if } q \in Q_1 \text{ and } q \notin F_1 \\ \delta_1(q, a), & \text{if } q \in F_1 \text{ and } a \neq \varepsilon \\ \delta_1(q, a) \cup \{q_2\}, & \text{if } q \in F_1 \text{ and } a = \varepsilon \\ \delta_2(q, a), & \text{if } q \in Q_2 \end{cases}$$



Closure under the star

- Theorem: regular language is closed under the star operation.

$$A^* = A \times A \times \dots \times A$$



Closure under the star

- Theorem: regular language is closed under the star operation.

- Proof:

let $A_1 = L(N_1)$, $A_1^* = L(N)$, NFA $N_1 = (Q_1, \Sigma, \delta_1, q_1, F_1)$.


create NFA $N = (Q, \Sigma, \delta, q_0, F)$.

$$Q = Q_1 \cup \{q_0\};$$

$$F = F_1 \cup \{q_0\};$$

$$\delta(q, a) = \begin{cases} \delta_1(q, a), & \text{if } q \in Q_1 \text{ and } q \notin F_1 \\ \delta_1(q, a), & \text{if } q \in F_1 \text{ and } a \neq \varepsilon \\ \delta_1(q, a) \cup \{q_1\}, & \text{if } q \in F_1 \text{ and } a = \varepsilon \\ \{q_1\}, & \text{if } q = q_0 \text{ and } a = \varepsilon \\ \emptyset, & \text{if } q = q_0 \text{ and } a \neq \varepsilon \end{cases}$$

if $q \in Q_1$ and $q \notin F_1$
if $q \in F_1$ and $a \neq \varepsilon$
if $q \in F_1$ and $a = \varepsilon$
if $q = q_0$ and $a = \varepsilon$
if $q = q_0$ and $a \neq \varepsilon$



Regular operations

	DFA/NFA	PDA	TM
Union	close	?	?
Concatenation	close	?	?
Star	close	?	?
Complement	close	?	?
Boolean operation	close	?	?

