

**David M. Kroenke and David J. Auer**  
**Database Processing:**  
**Fundamentals, Design, and Implementation**



**Chapter Seven:**  
**SQL for Database**  
**Construction**  
**and Application**  
**Processing**

Wireless Access Technologies & Software Engineering

Chapter Objectives



- To create and manage table structures using SQL statements
- To understand how referential integrity actions are implemented in SQL statements
- To create and use SQL constraints
- To understand several uses for SQL views
- To use SQL statements to create and use views
- To understand how SQL is used in an application programming
- To understand SQL/Persistent Stored Modules (SQL/PSM)
- To understand how to create and use functions
- To understand how to create and use triggers
- To understand how to create and use stored procedures

Wireless Access Technologies & Software Engineering

## SQL DML—INSERT I



- The **SQL INSERT** statement:

```
/* *** EXAMPLE CODE - DO NOT RUN *** */
/* *** SQL-INSERT-CH07-01 *** */
INSERT INTO ARTIST
    (LastName, FirstName, Nationality, DateOfBirth, DateDeceased)
VALUES ('Miro', 'Joan', 'Spanish', 1893, 1983);
/* *** EXAMPLE CODE - DO NOT RUN *** */
/* *** SQL-INSERT-CH07-02 *** */
INSERT INTO ARTIST VALUES
    ('Miro', 'Joan', 'Spanish', 1893, 1983);
/* *** EXAMPLE CODE - DO NOT RUN *** */
/* *** SQL-INSERT-CH07-04 *** */
INSERT INTO ARTIST
    (LastName, FirstName, Nationality)
VALUES ('Miro', 'Joan', 'Spanish');
```

Wireless Access Technologies & Software Engineering

## SQL DML—INSERT II



- Bulk INSERT:

```
/* *** EXAMPLE CODE - DO NOT RUN *** */
/* *** SQL-INSERT-CH07-05 *** */
INSERT INTO ARTIST
    (LastName, FirstName, Nationality, DateOfBirth, DateDeceased)
SELECT      LastName, FirstName, Nationality,
            DateOfBirth, DateDeceased
FROM        IMPORTED_ARTIST;
```

Wireless Access Technologies & Software Engineering

## Populating the VRG Tables I



- The VRG database data contain **non-sequential surrogate key values.**

ArtistID	LastName	FirstName	Nationality	DateOfBirth	DateDeceased
1	Miro	Joan	Spanish	1893	1983
2	Kandinsky	Wassily	Russian	1866	1944
3	Klee	Paul	German	1879	1940
4	Matisse	Henri	French	1869	1954
5	Chagall	Marc	French	1887	1985
11	Sargent	John Singer	United States	1856	1925
17	Tobey	Mark	United States	1890	1976
18	Horiuchi	Paul	United States	1906	1999
19	Graves	Morris	United States	1920	2001

Wireless Access Technologies & Software Engineering

## Populating the VRG Tables II



- Cannot** just use SQL INSERT statement by itself.
- See discussions of how to handle this situation:
  - Chapter 10A - Microsoft SQL Server 2014
  - Chapter 10B - Oracle Database
  - Chapter 10C - MySQL 5.6

Wireless Access Technologies & Software Engineering

## SQL DML—UPDATE I



- The **SQL UPDATE** statement:

```

/* *** EXAMPLE CODE - DO NOT RUN *** */
/* *** SQL-UPDATE-CH07-01 *** */
UPDATE      CUSTOMER
      SET      City = 'New York City'
      WHERE      CustomerID = 1000;
/* *** EXAMPLE CODE - DO NOT RUN *** */
/* *** SQL-UPDATE-CH07-02 *** */
UPDATE      CUSTOMER
      SET      City = 'New York City', State = 'NY'
      WHERE      CustomerID = 1000;

```

Wireless Access Technologies & Software Engineering

## SQL DML—UPDATE II



- Bulk **UPDATE**:

```

/* *** EXAMPLE CODE - DO NOT RUN *** */
/* *** SQL-UPDATE-CH07-03 *** */
UPDATE      CUSTOMER
      SET      City = 'New York City';
/* *** EXAMPLE CODE - DO NOT RUN *** */
/* *** SQL-UPDATE-CH07-04 *** */
UPDATE      CUSTOMER
      SET      AreaCode = '303'
      WHERE      City = 'Denver';

```

Wireless Access Technologies & Software Engineering

## SQL DML—UPDATE III



- Using values from other tables:

```
/* *** EXAMPLE CODE - DO NOT RUN *** */
/* *** SQL-UPDATE-CH07-06 *** */

UPDATE      PURCHASE_ORDER
  SET      TaxRate =
            (SELECT  Tax
             From    TAX_TABLE
             WHERE   TAX_TABLE.City = PURCHASE_ORDER.City)
  WHERE    PURCHASE_ORDER.Number = 1000;
```

Wireless Access Technologies & Software Engineering

## SQL DML—MERGE



- The **SQL MERGE** statement:

```
/* *** EXAMPLE CODE - DO NOT RUN *** */
/* *** SQL-MERGE-CH07-01 *** */

MERGE INTO ARTIST AS A USING ARTIST_DATA_RESEARCH AS ADR
  ON   (A.LastName = ADR.LastName
        AND
        A.FirstName = ADR.FirstName)
  WHEN MATCHED THEN
    UPDATE SET
      A.Nationality = ADR.Nationality,
      A.DateOfBirth = ADR.DateOfBirth,
      A.DateDeceased = ADR.DateDeceased
  WHEN NOT MATCHED THEN
    INSERT (LastName, FirstName, Nationality,
           DateOfBirth, DateDeceased);
```

Wireless Access Technologies & Software Engineering

## SQL DML—DELETE



- SQL DELETE statement:

```
/* *** EXAMPLE CODE - DO NOT RUN *** */
/* *** SQL-DELETE-CH07-01 *** */
DELETE      FROM CUSTOMER
WHERE       CustomerID = 1000;
```

- If you omit the WHERE clause, you will delete every row in the table.
- Does *not* reset surrogate key values.

Wireless Access Technologies & Software Engineering

## Using Aliases



- Use of aliases:

```
SELECT      C.Name, A.Name
FROM        CUSTOMER AS C
            JOIN
            CUSTOMER_ARTIST_INT AS CI
ON          C.CustomerID = CI.CustomerID
            JOIN ARTIST AS A
            ON CI.ArtistID = A.ArtistID;
```

- DBMS products differ

CUSTOMER AS C versus CUSTOMER C

Wireless Access Technologies & Software Engineering

## VRG Database Data

### CUSTOMER I

CustomerID	LastName	FirstName	EmailAddress	EncryptedPassword
1000	Janes	Jeffrey	Jeffrey.Janes@somewhere.com	ng76tG9E
1001	Smith	David	David.Smith@somewhere.com	ttr67i23
1015	Twilight	Tiffany	Tiffany.Twilight@somewhere.com	gr44t5uz
1033	Smathers	Fred	Fred.Smathers@somewhere.com	mnF3D00Q
1034	Frederickson	Mary Beth	MaryBeth.Frederickson@somewhere.com	Nd5qr4Tv
1036	Warning	Selma	Selma.Warning@somewhere.com	CAe3Gh98
1037	Wu	Susan	Susan.Wu@somewhere.com	Ues3thQ2
1040	Gray	Donald	Donald.Gray@somewhere.com	NULL
1041	Johnson	Lynda	NULL	NULL
1051	Wilkins	Chris	Chris.Wilkins@somewhere.com	45QZjx59

Wireless Access Technologies & Software Engineering

## VRG Database Data

### CUSTOMER II

CustomerID	LastName	FirstName	Street	City	State	ZIPorPostalCode
1000	Janes	Jeffrey	123 W. Elm St	Renton	WA	98055
1001	Smith	David	813 Tumbleweed Lane	Loveland	CO	81201
1015	Twilight	Tiffany	88 1st Avenue	Langley	WA	98260
1033	Smathers	Fred	10899 88th Ave	Bainbridge Island	WA	98110
1034	Frederickson	Mary Beth	25 South Lafayette	Denver	CO	80201
1036	Warning	Selma	205 Burnaby	Vancouver	BC	V6Z 1W2
1037	Wu	Susan	105 Locust Ave	Atlanta	GA	30322
1040	Gray	Donald	55 Bodega Ave	Bodega Bay	CA	94923
1041	Johnson	Lynda	117 C Street	Washington	DC	20003
1051	Wilkins	Chris	87 Highland Drive	Olympia	WA	98508

Wireless Access Technologies & Software Engineering

## VRG Database Data

### CUSTOMER III

CustomerID	LastName	FirstName	Country	AreaCode	PhoneNumber
1000	Janes	Jeffrey	USA	425	543-2345
1001	Smith	David	USA	970	654-9876
1015	Twilight	Tiffany	USA	360	765-5566
1033	Smathers	Fred	USA	206	876-9911
1034	Frederickson	Mary Beth	USA	303	513-8822
1036	Warning	Selma	Canada	604	988-0512
1037	Wu	Susan	USA	404	653-3465
1040	Gray	Donald	USA	707	568-4839
1041	Johnson	Lynda	USA	202	438-5498
1051	Wilkens	Chris	USA	360	876-8822

Wireless Access Technologies & Software Engineering

## VRG Database Data

### ARTIST

ArtistID	LastName	FirstName	Nationality	DateOfBirth	DateDeceased
1	Miro	Joan	Spanish	1893	1983
2	Kandinsky	Wassily	Russian	1866	1944
3	Klee	Paul	German	1879	1940
4	Matisse	Henri	French	1869	1954
5	Chagall	Marc	French	1887	1985
11	Sargent	John Singer	United States	1856	1925
17	Tobey	Mark	United States	1890	1976
18	Horiuchi	Paul	United States	1906	1999
19	Graves	Morris	United States	1920	2001

Wireless Access Technologies & Software Engineering



## VRG Database Data

### CUSTOMER\_ARTIST\_INT

ArtistID	CustomerID	ArtistID	CustomerID
1	1001	17	1033
1	1034	17	1040
2	1001	17	1051
2	1034	18	1000
4	1001	18	1015
4	1034	18	1033
5	1001	18	1040
5	1034	18	1051
5	1036	19	1000
11	1001	19	1015
11	1015	19	1033
11	1036	19	1036
17	1000	19	1040
17	1015	19	1051

Wireless Access Technologies & Software Engineering

## VRG Database Data

### WORK I

WorkID	Title	Medium	Description	Copy	ArtistID
500	Memories IV	Casein rice paper collage	31 × 24.8 in.	Unique	18
511	Surf and Bird	High Quality Limited Print	Northwest School Expressionist style	142/500	19
521	The Tilled Field	High Quality Limited Print	Early Surrealist style	788/1000	1
522	La Lecon de Ski	High Quality Limited Print	Surrealist style	353/500	1
523	On White II	High Quality Limited Print	Bauhaus style of Kandinsky	435/500	2
524	Woman with a Hat	High Quality Limited Print	A very colorful Impressionist piece	596/750	4
537	The Woven World	Color lithograph	Signed	17/750	17
548	Night Bird	Watercolor on Paper	50 × 72.5 cm.—Signed	Unique	19
551	Der Blaue Reiter	High Quality Limited Print	"The Blue Rider"—Early Pointilism influence	236/1000	2
552	Angelus Novus	High Quality Limited Print	Bauhaus style of Klee	659/750	3
553	The Dance	High Quality Limited Print	An Impressionist masterpiece	734/1000	4
554	I and the Village	High Quality Limited Print	Shows Belarusian folk-life themes and symbology	834/1000	5
555	Claude Monet Painting	High Quality Limited Print	Shows French Impressionist influence of Monet	684/1000	11
561	Sunflower	Watercolor and ink	33.3 × 16.1 cm.—Signed	Unique	19
562	The Fiddler	High Quality Limited Print	Shows Belarusian folk-life themes and symbology	251/1000	5
563	Spanish Dancer	High Quality Limited Print	American realist style—From work in Spain	583/750	11
564	Farmer's Market #2	High Quality Limited Print	Northwest School Abstract Expressionist style	267/500	17

Wireless Access Technologies & Software Engineering

## VRG Database Data

### WORK II

WorkID	Title	Medium	Description	Copy	ArtistID
565	Farmer's Market #2	High Quality Limited Print	Northwest School Abstract Expressionist style	268/500	17
566	Into Time	High Quality Limited Print	Northwest School Abstract Expressionist style	323/500	18
570	Untitled Number 1	Monotype with tempera	4.3 × 6.1 in.—Signed	Unique	17
571	Yellow covers blue	Oil and collage	71 × 78 in.—Signed	Unique	18
578	Mid Century Hibernation	High Quality Limited Print	Northwest School Expressionist style	362/500	19
580	Forms in Progress I	Color aquatint	19.3 × 24.4 in.—Signed	Unique	17
581	Forms in Progress II	Color aquatint	19.3 × 24.4 in.—Signed	Unique	17
585	The Fiddler	High Quality Limited Print	Shows Belarusian folk-life themes and symbology	252/1000	5
586	Spanish Dancer	High Quality Limited Print	American Realist style—From work in Spain	588/750	11
587	Broadway Boggie	High Quality Limited Print	Northwest School Abstract Expressionist style	433/500	17
588	Universal Field	High Quality Limited Print	Northwest School Abstract Expressionist style	114/500	17
589	Color Floating in Time	High Quality Limited Print	Northwest School Abstract Expressionist style	487/500	18
590	Blue Interior	Tempera on card	43.9 × 28 in.	Unique	17
593	Surf and Bird	Gouache	26.5 × 29.75 in.—Signed	Unique	19
594	Surf and Bird	High Quality Limited Print	Northwest School Expressionist style	366/500	19
595	Surf and Bird	High Quality Limited Print	Northwest School Expressionist style	366/500	19
596	Surf and Bird	High Quality Limited Print	Northwest School Expressionist style	366/500	19

Wireless Access Technologies & Software Engineering

## VRG Database Data

### TRANS I

TransactionID	DateAcquired	AcquisitionPrice	AskingPrice	DateSoldID	SalesPrice	CustomerID	WorkID
100	11/4/2011	\$30,000.00	\$45,000.00	12/14/2011	\$42,500.00	1000	500
101	11/7/2011	\$250.00	\$500.00	12/19/2011	\$500.00	1015	511
102	11/17/2011	\$125.00	\$250.00	1/18/2012	\$200.00	1001	521
103	11/17/2011	\$250.00	\$500.00	12/12/2012	\$400.00	1034	522
104	11/17/2011	\$250.00	\$250.00	1/18/2012	\$200.00	1001	523
105	11/17/2011	\$200.00	\$500.00	12/12/2012	\$400.00	1034	524
115	3/3/2012	\$1,500.00	\$3,000.00	6/7/2012	\$2,750.00	1033	537
121	9/21/2012	\$15,000.00	\$30,000.00	11/28/2012	\$27,500.00	1015	548
125	11/21/2012	\$125.00	\$250.00	12/18/2012	\$200.00	1001	551
126	11/21/2012	\$200.00	\$400.00	NULL	NULL	NULL	552
127	11/21/2012	\$125.00	\$500.00	12/22/2012	\$400.00	1034	553
128	11/21/2012	\$125.00	\$250.00	3/16/2013	\$225.00	1036	554
129	11/21/2012	\$125.00	\$250.00	3/16/2013	\$225.00	1036	555
151	5/7/2013	\$10,000.00	\$20,000.00	6/28/2013	\$17,500.00	1036	561
152	5/18/2013	\$125.00	\$250.00	8/15/2013	\$225.00	1001	562
153	5/18/2013	\$200.00	\$400.00	8/15/2013	\$350.00	1001	563
154	5/18/2013	\$250.00	\$500.00	9/28/2013	\$400.00	1040	564
155	5/18/2013	\$250.00	\$500.00	NULL	NULL	NULL	565


Accounting

## VRG Database Data

### TRANS II

TransactionID	DateAcquired	AcquisitionPrice	AskingPrice	DateSoldID	SalesPrice	CustomerID	WorkID
156	5/18/2013	\$250.00	\$500.00	9/27/2013	\$400.00	1040	566
161	6/28/2013	\$7,500.00	\$15,000.00	9/29/2013	\$13,750.00	1033	570
171	8/23/2013	\$35,000.00	\$60,000.00	9/29/2013	\$55,000.00	1000	571
175	9/29/2013	\$40,000.00	\$75,000.00	12/18/2013	\$72,500.00	1036	500
181	10/11/2013	\$250.00	\$500.00	NULL	NULL	NULL	578
201	2/28/2014	\$2,000.00	\$3,500.00	4/26/2014	\$3,250.00	1040	580
202	2/28/2014	\$2,000.00	\$3,500.00	4/26/2014	\$3,250.00	1040	581
225	6/8/2014	\$125.00	\$250.00	9/27/2014	\$225.00	1051	585
226	6/8/2014	\$200.00	\$400.00	NULL	NULL	NULL	586
227	6/8/2014	\$250.00	\$500.00	9/27/2014	\$475.00	1051	587
228	6/8/2014	\$250.00	\$500.00	NULL	NULL	NULL	588
229	6/8/2014	\$250.00	\$500.00	NULL	NULL	NULL	589
241	8/29/2014	\$2,500.00	\$5,000.00	9/27/2014	\$4,750.00	1015	590
251	10/25/2014	\$25,000.00	\$50,000.00	NULL	NULL	NULL	593
252	10/27/2014	\$250.00	\$500.00	NULL	NULL	NULL	594
253	10/27/2014	\$250.00	\$500.00	NULL	NULL	NULL	595
254	10/27/2014	\$250.00	\$500.00	NULL	NULL	NULL	596

## SQL Views I



Wireless Access Technologies & Software Engineering

## SQL Views II



- An **SQL view** is a virtual table that is constructed from other tables or views.
- It has no data of its own, but obtains data from tables or other views.
- SELECT statements are used to define views:
  - A view definition may not include an ORDER BY clause.
- SQL views are a subset of the external views:
  - They can be used only for external views that involve one multivalued path through the schema.

Wireless Access Technologies & Software Engineering

## SQL Views



Uses of SQL Views
Hide columns or rows.
Display results of computations.
Hide complicated SQL syntax.
Layer built-in functions.
Provide level of isolation between table data and users' view of data.
Assign different processing permissions to different views of the same table.
Assign different triggers to different views of the same table.

Wireless Access Technologies & Software Engineering

## SQL CREATE VIEW Statement I

- The **SQL CREATE VIEW** statement:

```
/* *** SQL-CREATE-VIEW-CH07-01 *** */
CREATE VIEW CustomerNameView AS
    SELECT      LastName AS CustomerLastName,
               FirstName AS CustomerFirstName
    FROM        CUSTOMER;
```

- In the SQL standard, views do *not* support the **SQL ORDER BY** clause.
  - Individual DBMS products may support the SQL ORDER BY clause – see documentation.

7-25

Wireless Access Technologies &amp; Software Engineering

## SQL CREATE VIEW Statement II

- To see the results, use an **SQL SELECT** statement with the **view name** as the table name in the FROM clause:

```
/* *** SQL-Query-View-CH07-01 *** */
SELECT      *
FROM        CustomerNameView
ORDER BY    CustomerLastName, CustomerFirstName
```

	CustomerLastName	CustomerFirstName
1	Frederickson	Mary Beth
2	Gray	Donald
3	Janes	Jeffrey
4	Johnson	Lynda
5	Smathers	Fred
6	Smith	David
7	Twilight	Tiffany
8	Waring	Selma
9	Wilkens	Chris
10	Wu	Susan

7-26

Wireless Access Technologies &amp; Software Engineering

## SQL ALTER VIEW Statement I

- The **SQL ALTER VIEW** statement:

```
/* *** EXAMPLE CODE - DO NOT RUN *** */
/* *** SQL-ALTER-VIEW-CH07-01 *** */
ALTER VIEW CustomerNameView AS
    SELECT      FirstName AS CustomerFirstName,
               LastName AS CustomerLastName,
    FROM        CUSTOMER;
```

- In the Oracle Database or MySQL 5.6, use the **SQL CREATE OR REPLACE VIEW** statement.
  - This allows creation and modification of SQL VIEW code.

7-27

Wireless Access Technologies &amp; Software Engineering

## Updateable Views



Updateable Views
View based on a single table with no computed columns and all non-null columns present in the view.
View based on any number of tables, with or without computed columns, and INSTEAD OF trigger defined for the view.
Possibly Updateable Views
Based on a single table, primary key in view, some required columns missing from view, update and delete may be allowed. Insert is not allowed.
Based on multiple tables, updates may be allowed on the most subordinate table in the view if rows of that table can be uniquely identified.

Wireless Access Technologies &amp; Software Engineering

## Embedding SQL in Program Code



- SQL cursors are used to select one row at a time from pseudo-files.
- Problem: assigning SQL table columns with program variables
  - Solution: object-oriented programming, PL/SQL
- Problem: paradigm mismatch between SQL and application programming language:
  - SQL statements return sets of rows; an application works on one row at a time
  - Solution: process the SQL results as **pseudo-files**

Wireless Access Technologies & Software Engineering

## Variables in Program Code



- Oracle Database and MySQL 5.6 style variables:

```
/* *** EXAMPLE CODE - DO NOT RUN *** */
/* *** SQL-Code-Example-CH07-01 *** */
SELECT      Count(*) INTO rowCount
FROM        CUSTOMER;
```

- Microsoft SQL Server 2014 style variables:

```
/* *** EXAMPLE CODE - DO NOT RUN *** */
/* *** SQL-Code-Example-CH07-02 *** */
SELECT      @rowCount = Count(*)
FROM        CUSTOMER;
```

Wireless Access Technologies & Software Engineering



## SQL Cursors in Program Code



- SQL can be embedded in triggers, stored procedures, and program code.

- A typical cursor code pattern is:

```
/* *** EXAMPLE CODE - DO NOT RUN *** */
/* *** SQL-Code-Example-CH07-04 *** */
DECLARE SQLcursor CURSOR FOR (SELECT * FROM CUSTOMER);
/* Opening SQLcursor executes (SELECT * FROM CUSTOMER) */
OPEN SQLcursor;
MOVE SQLcursor to first row of (SELECT * FROM CUSTOMER);
    WHILE (SQLcursor not past the last row) LOOP
        SET CustomerLastName = LastName;
        ...other statements...
    REPEAT LOOP UNTIL DONE;
CLOSE SQLcursor
...other processing...
```

Wireless Access Technologies & Software Engineering

## SQL/Persistent Stored Modules (SSL/PSM)



- **SQL/Persistent Stored Modules (SQL/PSM)** is an ANSI/ISO standard for embedding procedural programming functionality into SQL
- Each DBMS product implements SQL/PSM in a different way, with some closer to the standard than others.
  - Microsoft SQL Server 2014 calls its version **Transact-SQL (T-SQL)**.
  - Oracle Database calls its variant **Procedural Language/SQL (PL/SQL)**.
  - MySQL 5.6 implements SQL/PSM, but has no special name for its variant of SQL.


Wireless Access Technologies & Software Engineering



## User-Defined Functions I



- A **user-defined function (stored function)** is a stored set of SQL statements that:
  - is *called by name* from another SQL statement
  - may have *input parameters* passed to it by the calling SQL statement, and
  - *returns an output value* to the SQL statement that called the function.



Wireless Access Technologies & Software Engineering

## User-Defined Functions II The *NameConcatenation* Function



```

CREATE FUNCTION dbo.NameConcatenation

-- These are the input parameters
(
    @FirstName    CHAR(25),
    @LastName     CHAR(25)
)
RETURNS VARCHAR(60)
AS
BEGIN
    -- This is the variable that will hold the value to be returned
    DECLARE @FullName VARCHAR(60);

    -- SQL statements to concatenate the names in the proper order
    SELECT @FullName = RTRIM(@LastName) + ', ' + RTRIM(@FirstName);

    -- Return the concatenated name
    RETURN @FullName;
END;
  
```

Wireless Access Technologies & Software Engineering

## User-Defined Functions III

### The *NameConcatenation* Function



- Using the NameConcatenation function:

```
/* *** SQL-Query-CH07-02 *** */
SELECT      dbo.NameConcatenation(FirstName, LastName) AS CustomerName,
            AreaCode, PhoneNumber, EmailAddress
FROM        CUSTOMER
ORDER BY    CustomerName;
```

	CustomerName	AreaCode	PhoneNumber	EmailAddress
1	Frederickson, Mary Beth	303	513-8822	MaryBeth.Frederickson@somewhere.com
2	Gray, Donald	707	568-4839	Donald.Gray@somewhere.com
3	Janes, Jeffrey	425	543-2345	Jeffrey.Janes@somewhere.com
4	Johnson, Lynda	202	438-5498	NULL
5	Smathers, Fred	206	876-9911	Fred.Smathers@somewhere.com
6	Smith, David	970	654-9876	David.Smith@somewhere.com
7	Twilight, Tiffany	360	765-5566	Tiffany.Twilight@somewhere.com
8	Waring, Selma	604	988-0512	Selma.Waring@somewhere.com
9	Wilkens, Chris	360	876-8822	Chris.Wilkens@somewhere.com
10	Wu, Susan	404	653-3465	Susan.Wu@somewhere.com

Wireless Access Technologies & Software Engineering

## User-Defined Functions IV

### The *NameConcatenation* Function



```
/* *** SQL-Query-CH07-04 *** */
SELECT      dbo.NameConcatenation(C.FirstName, C.LastName) AS CustomerName,
            dbo.NameConcatenation(A.FirstName, A.LastName) AS ArtistName
FROM        CUSTOMER AS C JOIN CUSTOMER_ARTIST_INT AS CAI
            ON      C.CustomerID = CAI.CustomerID
            JOIN    ARTIST AS A
            ON      CAI.ArtistID = A.ArtistID
ORDER BY    CustomerName, ArtistName;
```

	CustomerName	ArtistName
1	Frederickson, Mary Beth	Chagall, Marc
2	Frederickson, Mary Beth	Kandinsky, Wassily
3	Frederickson, Mary Beth	Matisse, Henri
4	Frederickson, Mary Beth	Miro, Joan
5	Gray, Donald	Graves, Morris
6	Gray, Donald	Horiuchi, Paul
7	Gray, Donald	Tobey, Mark
8	Janes, Jeffrey	Graves, Morris
9	Janes, Jeffrey	Horiuchi, Paul
10	Janes, Jeffrey	Tobey, Mark

Wireless Access Technologies & Software Engineering

## Triggers I



- A **trigger** is a stored program that is executed by the DBMS whenever a specified event occurs on a specified table or view.
- Three trigger types:  
**BEFORE**, **INSTEAD OF**, and **AFTER**
  - Each type can be declared for Insert, Update, and Delete.
  - Resulting in a total of nine trigger types.
- Oracle supports all nine trigger types.
- SQL Server supports six trigger types (INSTEAD OF and AFTER).
- MySQL supports six trigger types (BEFORE and AFTER).

Wireless Access Technologies & Software Engineering

## Triggers II



Trigger Type DML Action	BEFORE	INSTEAD OF	AFTER
INSERT	Oracle Database MySQL	Oracle Database SQL Server	Oracle Database SQL Server MySQL
UPDATE	Oracle Database MySQL	Oracle Database SQL Server	Oracle Database SQL Server MySQL
DELETE	Oracle Database MySQL	Oracle Database SQL Server	Oracle Database SQL Server MySQL

7-38

Wireless Access Technologies & Software Engineering

## Firing Triggers



- When a trigger is fired, the DBMS supplies:
  - Old and new values for the update
  - New values for inserts
  - Old values for deletions
- The way the values are supplied depends on the DBMS product.
- Trigger applications include:
  - Providing default values
  - Enforcing data constraints
  - Updating views
  - Performing referential integrity actions

7-39

Wireless Access Technologies &amp; Software Engineering

```

/* *** EXAMPLE CODE - DO NOT RUN *** */
CREATE TRIGGER TRANS_AskingPriceInitialValue
AFTER INSERT ON TRANS

DECLARE
  rowCount      Int;
  sumNetProfit   Numeric(10,2);
  avgNetProfit   Numeric(10,2);

BEGIN
  /* First find if work has been here before */
  SELECT Count(*) INTO rowCount
  FROM   TRANS AS T
  WHERE  new:WorkID = T.WorkID;

  IF (rowCount = 1)
  THEN
    /* This is first time work has been in gallery */
    new:AskingPrice = 2 * new:AcquisitionPrice;
  ELSE
    IF rowCount > 1
    THEN
      /* Work has been here before */
      SELECT SUM(NetProfit) into sumNetProfit
      FROM   ArtistWorkNetView ANNV
      WHERE  ANNV.WorkID = new.WorkID
      GROUP BY ANNV.WorkID;

      avgNetProfit = sumNetProfit / (rowCount - 1);

      /* Now choose larger value for the new AskingPrice */
      IF ((new:AcquisitionPrice + avgNetProfit)
        > (2 * new:AcquisitionPrice))
      THEN
        new:AskingPrice = (new:AcquisitionPrice + avgNetProfit);
      ELSE
        new:AskingPrice = (2 * new:AcquisitionPrice);
      END IF;
    ELSE
      /* Error, rowCount cannot be less than 1 */
      /* Do something! */
    END IF;
  END IF;
END;

```

7-40

Wireless Access Technologies &amp; Software Engineering

```

/* *** EXAMPLE CODE - DO NOT RUN *** */
CREATE TRIGGER CustomerInterestView_UpdateCustomerLastName
INSTEAD OF UPDATE ON CustomerInterestView

DECLARE
    rowCount      Int;

BEGIN

    SELECT      COUNT(*) into rowCount
    FROM        CUSTOMER
    WHERE       CUSTOMER.LastName = old:LastName

    IF (rowCount = 1)
    THEN
        /* If get here, then only one customer has this last name. */
        /* Make the name change. */

        UPDATE   CUSTOMER
        SET       CUSTOMER.LastName = new:LastName
        WHERE     CUSTOMER.LastName = old:LastName;

    ELSE

        IF (rowCount > 1 )
        THEN
            /* Send a message to the user saying cannot update because */
            /* there are too many customers with this last name. */

        ELSE
            /* Error, if rowcount <= 0 there is an error! */
            /* Do something! */
        END IF;
        END IF;
    END;

```

7-41  
Wireless Access Technologies & Software Engineering

```

/* *** EXAMPLE CODE - DO NOT RUN *** */
CREATE TRIGGER EMPLOYEE_DeleteCheck
INSTEAD OF DELETE ON DeleteEmployeeView

DECLARE
    rowCount      Int;

BEGIN

    /* First determine if this is the last employee in the department */

    SELECT      Count(*) into rowCount
    FROM        EMPLOYEE
    WHERE       EMPLOYEE.EmployeeNumber = old:EmployeeNumber;

    IF (rowCount > 1)
    THEN
        /* Not last employee, allow deletion */

        DELETE   EMPLOYEE
        WHERE     EMPLOYEE.EmployeeNumber = old:EmployeeNumber;

    ELSE

        /* Send a message to user saying that the last employee */
        /* in a department cannot be deleted. */

    END IF;

    END;

```

7-42  
Wireless Access Technologies & Software Engineering

```

/* *** EXAMPLE CODE - DO NOT RUN *** */

CREATE TRIGGER EMPLOYEE_DEPARTMENT_DeleteCheck
  INSTEAD OF DELETE ON DeleteEmployeeDepartmentView
DECLARE
  rowCount      Int;
BEGIN
  /* First determine if this is the last employee in the department */
  SELECT  Count(*) into rowCount
  FROM    EMPLOYEE
  WHERE   EMPLOYEE.EmployeeNumber = old:EmployeeNumber;

  /* Delete Employee row regardless of whether Department is deleted */
  DELETE  EMPLOYEE
  WHERE   EMPLOYEE.EmployeeNumber = old:EmployeeNumber;

  IF (rowCount = 1)
  THEN
    /* Last employee in Department, delete Department */
    DELETE  DEPARTMENT
    WHERE   DEPARTMENT.DepartmentName = old:DepartmentName;
  END IF;
END;

```

7-43  
Wireless Access Technologies & Software Engineering

## Stored Procedures



- A **stored procedure** is a program that is stored within the database and is compiled when used.
  - In Oracle, it can be written in PL/SQL or Java.
  - In SQL Server, it can be written in TRANSACT-SQL.
- Stored procedures can receive input parameters and they can return results.
- Stored procedures can be called from:
  - Programs written in standard languages, e.g., Java, C#.
  - Scripting languages, e.g., JavaScript, VBScript.
  - SQL command prompt, e.g., SQL Plus, Query Analyzer.

7-44  
Wireless Access Technologies & Software Engineering