




tid 1 sinusoidal W=10mm | cut@high-kappa 1.0/1.0 mm | straight-leg ripple p95 0.0 mm | min wall clearance 4.0 mm




tid 2 sinusoidal W=20mm | cut@high-kappa 3.4/3.4 mm | straight-leg ripple p95 0.6 mm | min wall clearance 6.6 mm




tid 3 sinusoidal W=30mm | cut@high-kappa 5.1/5.2 mm | straight-leg ripple p95 1.0 mm | mirror clearance 9.8 mm




tid 4 sinusoidal W=40mm | cut@high-kappa 6.8/6.9 mm | straight-leg ripple p95 1.4 mm | mi range 13.1 mm




tid 5 sinusoidal W=50mm | cut@high-kappa 8.5/8.7 mm | straight-leg ripple p95 1.7 mm | m distance 16.3 mm




tid 6 corner W=10mm | cut@high-kappa 0.5/1.7 mm | straight-leg ripple p95 0.0 mm | min wall clearance 2.8 mm




tid 7 corner W=20mm | cut@high-kappa 1.5/3.6 mm | straight-leg ripple p95 0.0 mm | min wall clearance 5.9 mm




tid 8 corner W=30mm | cut@high-kappa 2.7/5.3 mm | straight-leg ripple p95 0.0 mm | min wall clearance 8.9 mm



tid 9 corner W=40mm | cut@high-kappa 3.9/7.0 mm | straight-leg ripple p95 0.0 mm | min wall clearance 12.1 mm



tid 10 corner W=50mm | cut@high-kappa 2.8/5.1 mm | straight-leg ripple p95 0.0 mm | min distance 16.5 mm



tid 11 straight W=10mm | cut@high-kappa 0.0/0.0 mm | straight-leg ripple p95 0.0 mm | min wall clearance 5.0 mm

$1e-6 + 1.30001e-1$

-0


0.0

0.1

0.2

0.3

0



tid 12 straight W=20mm | cut@high-kappa 0.0/0.0 mm | straight-leg ripple p95 0.0 mm | min wall clearance 10.0 mm

$1e-6 + 1.30001e-1$




0.0

0.1

0.2

0.3



tunnel
centerline
reference path
start
end

tid 13 straight W=30mm | cut@high-kappa 0.0/0.0 mm | straight-leg ripple p95 0.0 mm | min wall clearance 15.0 mm

$1e-6 + 1.30001e-1$

0

0.0


0.1

0.2

0.3

- tunnel
- centerline
- reference path
- start
- end

tid 14 straight W=40mm | cut@high-kappa 0.0/0.0 mm | straight-leg ripple p95 0.0 mm | min wall clearance 20.0 mm



tid 15 straight W=50mm | cut@high-kappa 0.0/0.0 mm | straight-leg ripple p95 0.0 mm | min wall clearance 25.0 mm

$1e-6 + 1.30001e-1$




0.0

0.1


0.2

0.3





tunnel
centerline
reference path
start
end


tid 26 gentle_sinusoidal W=10mm | cut@high-kappa 0.5/0.6 mm | straight-leg ripple p95 0.1 mm | mirror wall clearance 4.4 mm




tid 27 gentle_sinusoidal W=20mm | cut@high-kappa 3.3/3.4 mm | straight-leg ripple p95 0.7 mm | minntr wall clearance 6.6 mm












tid 31 sharp_sinusoidal W=10mm | cut@high-kappa 1.6/1.7 mm | straight-leg ripple p95 0.0 mm | min wall clearance 3.3 mm




tid 32 sharp_sinusoidal W=20mm | cut@high-kappa 3.3/3.5 mm | straight-leg ripple p95 0.0 mm | min wall clearance 6.5 mm



tid 33 sharp_sinusoidal W=30mm | cut@high-kappa 5.1/5.3 mm | straight-leg ripple p95 0.5 mm | min wall clearance 9.7 mm



tid 34 sharp_sinusoidal W=40mm | cut@high-kappa 6.9/7.1 mm | straight-leg ripple p95 0.9 mm | ripple clearance 12.8 mm



tid 35 sharp_sinusoidal W=50mm | cut@high-kappa 8.6/9.0 mm | straight-leg ripple p95 1.2 mm | clearance 16.0 mm

