

Numerical Analysis HW 13

Kevin Ho

April 2025

- 13.1. Consider Example 13.13, p.488. Compute vectors of cosines, for each subspace approximations, i.e., with A_k where $k = 1, 2, \dots, 5$.

Cosine Similarities

For $k = 1$: $[1. \quad 1. \quad 1. \quad 1. \quad 1.]$
For $k = 2$: $[0.7857 \quad 0.8332 \quad 0.967 \quad 0.4873 \quad 0.1819]$
For $k = 3$: $[0.1024 \quad 0.8501 \quad 0.8371 \quad 0.4218 \quad 0.4685]$
For $k = 4$: $[0.054 \quad 0.8476 \quad 0.8291 \quad 0.4165 \quad 0.3918]$
For $k = 5$: $[0. \quad 0.7223 \quad 0.8393 \quad 0.3612 \quad 0.3612]$

- 13.2. Verify equations in Derivation 13.26, p.497, particularly (13.28), (13.29), and (13.30).

We start with equation (13.28):

$$z = \alpha Qy + \beta \frac{e}{n}$$

Left-multiply by the vector of ones, e^T :

$$e^T z = e^T \left(\alpha Qy + \beta \frac{e}{n} \right)$$

Distribute e^T :

$$e^T z = \alpha(e^T Qy) + \beta \left(e^T \frac{e}{n} \right)$$

Evaluate $e^T e$. Since e is a vector of n ones, $e^T e = 1 \cdot 1 + \dots + 1 \cdot 1 = n$:

$$\begin{aligned} e^T z &= \alpha(e^T Qy) + \beta \left(\frac{n}{n} \right) \\ e^T z &= \alpha e^T Qy + \beta \end{aligned}$$

From premise (2), we know $e^T z = \|z\|_1 = 1$. Substitute this value:

$$1 = \alpha e^T Qy + \beta$$

Now, solve for β :

$$\beta = 1 - \alpha e^T Qy$$

This verifies the first equality in (13.30).

To verify the second equality, $\beta = 1 - \|\alpha Qy\|_1$, we need to relate $e^T Qy$ to the L1 norm.

- In PageRank, y represents probabilities/scores, so its entries are non-negative.
- The matrix Q represents transition probabilities (possibly adjusted for dangling nodes), so its entries are also non-negative.
- Therefore, the vector Qy has non-negative entries. Let $v = Qy$, then $v_i \geq 0$.
- The L1 norm of a vector v with non-negative entries is $\|v\|_1 = \sum_i |v_i| = \sum_i v_i$.
- The sum of the elements of a vector v is $e^T v$.
- Thus, for the non-negative vector Qy , we have $\|Qy\|_1 = e^T(Qy)$.

Substituting this into our result for β :

$$\begin{aligned}\beta &= 1 - \alpha(e^T Qy) \\ \beta &= 1 - \alpha(\|Qy\|_1)\end{aligned}$$

Since $\alpha > 0$, we can move it inside the norm:

$$\beta = 1 - \|\alpha Qy\|_1$$

This verifies the second equality in (13.30).

Conclusion: We have successfully shown, starting from equation (13.28) and using property (13.27), that $\beta = 1 - \alpha e^T Qy$ and subsequently that $\beta = 1 - \|\alpha Qy\|_1$. This completes the verification of equation (13.30).

13.3. Consider the link matrix Q in (13.4) and its corresponding link graph in Figure 13.2. Find the pagerank vector r by solving the Google pagerank equation.

- You may initialize the power method with any vector $r^{(0)}$ satisfying $\|r^{(0)}\|_1 = 1$.
- Set $\alpha = 0.85$.
- Let the iteration stop, when residual $< 10^{-4}$.

PageRank Vector: $[0.057922 \quad 0.057922 \quad 0.249026 \quad 0.116522 \quad 0.206839 \quad 0.311769]$

13.4. Now, consider a **modified** link matrix \tilde{Q} , by adding an outlink from page ④ to ⑤ in Figure 13.2. Find the pagerank vector \tilde{r} , by setting parameters and initialization the same way as for the previous problem.

- Compare r with \tilde{r} .
- Compare the number of iterations for convergence.

PageRank Vector: $[0.034884 \quad 0.034884 \quad 0.241867 \quad 0.111357 \quad 0.269946 \quad 0.307063]$

Table 1: Comparison of PageRank Vectors (r vs e_r)

Page	Original r	Modified e_r	Difference ($e_r - r$)
1	0.057 922	0.034 884	−0.023 038
2	0.057 922	0.034 884	−0.023 038
3	0.249 026	0.241 867	−0.007 159
4	0.116 522	0.111 357	−0.005 165
5	0.206 839	0.269 946	0.063 107
6	0.311 769	0.307 063	−0.004 706

Overall the iterations for convergence for r took 11 iterations while the modified link matrix ended 16 for me.

Code for Homework 13

13.1

```
import numpy as np

# Define the term-document matrix A (10x5)
A = np.array([
    [0, 0, 0, 1, 0],
    [0, 0, 0, 0, 1],
    [0, 0, 0, 0, 1],
    [1, 0, 1, 0, 0],
    [1, 0, 0, 0, 0],
    [0, 1, 0, 0, 0],
    [1, 0, 1, 1, 0],
    [0, 1, 1, 0, 0],
    [0, 0, 1, 1, 1],
    [0, 1, 1, 0, 0]
], dtype=float)

# Define the query vector q (10-dimensional)
q = np.array([0, 0, 0, 0, 0, 0, 0, 1, 1, 1], dtype=float)

# Compute the full SVD of A
U, s, Vh = np.linalg.svd(A, full_matrices=False)

L = np.array([0,0,0,1,1,0,1,0,0,0])

print(L @ L.T)

def cosine_similarity(vec1, vec2):
    norm1 = np.linalg.norm(vec1)
    norm2 = np.linalg.norm(vec2)
    if norm1 == 0 or norm2 == 0:
        return 0.0
    return np.dot(vec1, vec2) / (norm1 * norm2)

# Compute cosine similarities for each rank-k approximation
results = {}
for k in range(1, 6):
    print("K = {}".format(k))
    Uk = U[:, :k]
    Sk = np.diag(s[:k])
    Vhk = Vh[:, :k]
    print(f"\nSTEP {np.round(k, 4)} ")
    print(f"Uk = {np.round(Uk, 4)}\n")
    print(f"Sk = {np.round(Sk, 4)}\n")
    print(f"Vhk = {np.round(Vhk, 4)}")

    Dk = Sk @ Vhk
    qb_k = Uk.T @ q
```

```

cosines = []
for j in range(5):
    doc_vec = Dk[:, j]
    cos_sim = cosine_similarity(qb_k, doc_vec)
    cosines.append(cos_sim)
results[k] = np.array(cosines)

for k in range(1, 6):
    print(f"k = {k} cosines: {np.round(results[k], 4)}")

orig_cosines = []
for j in range(5):
    doc_vec = A[:, j]
    cos_sim = cosine_similarity(q, doc_vec)
    orig_cosines.append(cos_sim)
print("\nOriginal cosine similarities (full space):", np.round(orig_cosines,
4))

```

13.3 & 13.4

```

import numpy as np

def calculate_pagerank(Q, alpha=0.85, tolerance=1e-4, max_iterations=100):
    n = Q.shape[0]
    if n == 0:
        return np.array([]), 0
    S = Q.copy()
    column_sums = np.sum(S, axis=0)
    dangling_nodes = np.where(column_sums == 0)[0]
    uniform_prob = 1.0 / n
    for node_idx in dangling_nodes:
        S[:, node_idx] = uniform_prob
    r = np.full(n, uniform_prob)
    p = np.full(n, uniform_prob)
    iterations = 0
    residual = 1.0

    while residual >= tolerance and iterations < max_iterations:
        r_prev = r.copy()
        r = alpha * (S @ r_prev) + (1 - alpha) * p
        r /= np.sum(r)
        residual = np.linalg.norm(r - r_prev, 1)
        iterations += 1

    if iterations == max_iterations:
        print(f"Warning: PageRank did not converge within {max_iterations}
iterations.")
        return None, iterations

```

```

        return r, iterations

# --- Problem 13.3 ---
print("--- Problem 13.3: Original Link Matrix Q ---")

# Define the original link matrix Q from (13.4)
Q = np.array([
    [0, 1 / 3, 0, 0, 0, 0],
    [1 / 3, 0, 0, 0, 0, 0],
    [0, 1 / 3, 0, 0, 1 / 3, 1 / 2],
    [1 / 3, 0, 0, 0, 1 / 3, 0],
    [1 / 3, 1 / 3, 0, 0, 0, 1 / 2],
    [0, 0, 1, 0, 1 / 3, 0]
])

# Set parameters
alpha = 0.85
tolerance = 1e-4

# Calculate PageRank for original Q
r, iterations_r = calculate_pagerank(Q, alpha, tolerance)

if r is not None:
    print(f"Converged in {iterations_r} iterations.")
    print("PageRank vector r:")
    for i, rank in enumerate(r):
        print(f"  Page {i + 1}: {rank:.6f}")

# --- Problem 13.4 ---
print("\n--- Problem 13.4: Modified Link Matrix Qe ---")
Qe = Q.copy()
Qe[:, 3] = 0.0
Qe[4, 3] = 1.0

# Calculate PageRank for modified Qe
er, iterations_er = calculate_pagerank(Qe, alpha, tolerance)

if er is not None:
    print(f"Converged in {iterations_er} iterations.")
    print("PageRank vector er (modified):")
    # Print nicely formatted
    for i, rank in enumerate(er):
        print(f"  Page {i + 1}: {rank:.6f}")

# --- Comparison ---
print("\n--- Comparison ---")
if r is not None and er is not None:
    print(f"Number of iterations (original Q): {iterations_r}")
    print(f"Number of iterations (modified Qe): {iterations_er}")

    print("\nComparison of PageRank Vectors (r vs er):")
    print("Page | Original r | Modified er | Difference (er - r)")
    print("-----")
    for i in range(len(r)):

```

```
diff = er[i] - r[i]
print(f" {i + 1} | {r[i]:.6f} | {er[i]:.6f} | {diff:+.6f}")
```