DualChan-LVIO: Two-Channel, Consistency-Gated LiDAR-Visual-Inertial Odometry with an Added Orientation-Tensor Channel

Kavinkumar S and G. Sivasankar

***Abstract*—LiDAR odometry loses accuracy along directions that the scene does not constrain, such as the axis of a corridor, while visual-inertial odometry (VIO) fails under fast rotation, darkness and poor initialisation. Switching-based systems pick one source when the other is judged degenerate, but a binary decision on the whole pose discards the LiDAR information that remains in the constrained directions. We present DualChan-LVIO, a loosely coupled front end that fuses A-LOAM and VINS-Mono per scan and per direction through two channels plus one added channel. Schur complements split the registration Hessian into a rotation channel and a translation channel. The translation channel sets an information weight along each eigen-direction, and the added channel, an orientation tensor computed from the raw scan geometry, supplies support that the solver under-reports. The VIO is trusted only while its scale agrees with the LiDAR, a guard catches LiDAR blow-ups, and the hand-over between modes is anchored to avoid heading steps. A degeneracy-gated prediction takes the scan-to-map initial guess from the LiDAR unless the scan is degenerate. All constants were fixed on one calibration sequence. On the SubT-MRS Multi Floor and Long Corridor sequences the front end reaches 0.54 m and 2.10 m ATE RMSE against 1.61 m and 2.42 m published for Switch-SLAM, a LiDAR-inertial front end, so the comparison is not like for like. On a Gazebo farm route it reaches 0.29 m against 0.38 m published. On Corridor02, where A-LOAM alone diverged in every run, it reaches 1.99 m, and on Cave02 and the GEODE stairs it leaves 5 to 6 m. One-sided tests separate the fusion from VINS-Mono alone only on GEODE ($p = 0.008$). We report every run, including one divergence of the variant without gated prediction, and discuss how far the small number of runs and the shared development data limit these comparisons.**

***Index Terms*—LiDAR degeneracy, sensor fusion, visual-inertial odometry, SLAM, Schur complement.**

I. Introduction

LIDAR odometry and mapping [1]–[3] is accurate where the geometry constrains all six degrees of freedom, and it degrades where it does not. In a long corridor the translation along the axis is unobservable; on a staircase or in a cave the constraint is weak and changes from scan to scan. Visual-inertial odometry [4] has the opposite profile. It keeps its scale in featureless corridors as long as the camera tracks texture, and it drifts or re-initialises under darkness, fast rotation or a poor start [5], [6].

Tightly coupled LiDAR-visual-inertial systems [7]–[11] fuse both sources in one maximum a posteriori estimate. Lee *et al.* [12] argue that such fusion lets a long failure of one sensor corrupt the whole estimate, and propose Switch-SLAM, which selects the scan-to-map initial guess from LiDAR or VIO with a parameter-free eigenvalue test and remaps the solution along the degenerate directions. A test on the whole Hessian makes one decision for all six directions. In a corridor, the LiDAR still fixes the two lateral translations and all three rotations, and a switch spends that information.

This letter describes a front end that keeps both odometries running and fuses them per direction. Our contributions are:

1) A two-channel weighting with one added channel. Schur complements of the registration Hessian give a rotation block and a translation block in their own units. The translation block sets a per-direction information weight between the LiDAR and VIO increments, and an orientation tensor of the raw scan geometry supplies support that the solver under-reports.
2) A consistency-gated trust of the VIO. A scale-consistency gate, a rotation-consistency check, a LiDAR blow-up guard and an anchored hand-over decide when each source may carry a step. Their constants come from one calibration sequence and were not refitted.
3) A degeneracy-gated prediction that uses the switching rule of [12] only for the scan-to-map initial guess, while the output stays the fused estimate.
4) A live evaluation on five real sequences with ground truth and a simulated farm route, against the published Switch-SLAM results and against our own re-implementation of it in the same pipeline, with every run reported and a one-sided significance test for each comparison.

II. Related Work

A. Detecting and handling LiDAR degeneracy

Gelfand *et al.* [13] related ICP stability to the eigenvalues of the point-to-plane information matrix. Zhang *et al.* [14] thresholded the eigenvalues of the registration Hessian and updated the solution only in the well-conditioned directions (solution remapping), and Hinduja *et al.* [15] carried the same idea into degeneracy-aware factors for pose graphs. Later work replaced the fixed threshold by a localizability analysis of the correspondences (X-ICP [16], LP-ICP [17]), a learned predictor [18], or a probabilistic test [19]. Tuna *et al.* [20] compared these strategies in the field and found that mitigation matters most when no reliable external prior exists. DCReg [21] decouples the Hessian into rotation and translation subspaces with Schur complements before characterising

The authors are with Amrita School of Engineering, Coimbatore, Amrita Vishwa Vidyapeetham, India.

ill-conditioning, the same decomposition we use, but it acts inside the registration solver, while we use it to weight two odometries. NV-LIOM [22] uses normal vectors from range images to detect degeneracy in multi-floor buildings.

B. Combining LiDAR and visual-inertial odometry

LVI-SAM [7] seeds scan matching with VIO, which makes it sensitive to VIO failures [12]. R^{2}LIVE [8], R^{3}LIVE [9] and FAST-LIVO [10] fuse all measurements in an iterated Kalman filter, and Super Odometry [11] centres the estimate on the IMU. RELEAD [23] adds degeneracy-aware constraints to LiDAR odometry. Switch-SLAM [12] is the closest to our setting. It runs both odometries in parallel, chooses the initial guess by a chi-squared bound on the three smallest normalised Hessian eigenvalues, interpolates over a status buffer at the start and end of a degenerate stretch, and remaps the solution. Our system differs in that the output is never switched as a whole: every scan is a per-direction weighted combination, and the switching rule only decides the initial guess.

III. Method

A. Overview and notation

Fig. 1 shows the structure. The fusion splits the work by direction: rotation comes from the VIO, translation from the LiDAR along the directions the scan constrains and from the VIO along the others, and the LiDAR carries the whole step where the VIO is unusable. A-LOAM [24] has no IMU of its own, so inertial information reaches the LiDAR side only through the VIO pose. A-LOAM provides, for every scan k, its scan-to-map pose $(\mathbf{R}_{A,k}, \mathbf{p}_{A,k})$ and the 6×6 Hessian $\mathbf{H}$ of its scan-to-scan registration. VINS-Mono [4] runs unchanged and provides an IMU pose, moved into the LiDAR frame with the extrinsic calibration. From consecutive poses we form the increments $(\Delta\mathbf{R}_L, \Delta\mathbf{t}_L)$ of the LiDAR and $(\Delta\mathbf{R}_V, \Delta\mathbf{t}_V)$ of the VIO, both in the body frame of scan $k-1$. The fused pose is propagated as

$$\Delta\mathbf{t} = \mathbf{W}_t\,\Delta\mathbf{t}_L + (\mathbf{I}-\mathbf{W}_t)\,\Delta\mathbf{t}_V, \tag{1}$$

$$\boldsymbol{\phi} = \mathbf{W}_R\,\mathrm{Log}(\Delta\mathbf{R}_L) + (\mathbf{I}-\mathbf{W}_R)\,\mathrm{Log}(\Delta\mathbf{R}_V), \tag{2}$$

with $\mathbf{R}_k = \mathbf{R}_{k-1}\,\mathrm{Exp}(\boldsymbol{\phi})$ and $\mathbf{p}_k = \mathbf{p}_{k-1} + \mathbf{R}_{k-1}\Delta\mathbf{t}$. The weights $\mathbf{W}_t, \mathbf{W}_R$ are 3×3 matrices, so each direction has its own balance. Algorithm 1 lists the whole per-scan procedure. The node has four modes: a warm-up of 20 s after VIO (re)starts and a failure mode, in both of which the LiDAR carries the step ($\mathbf{W}_t = \mathbf{W}_R = \mathbf{I}$); the fused mode; and an initial mode.

B. Rotation and translation channels

Let $\mathbf{H}$ be expressed in radians and metres and split into 3×3 blocks. The Schur complements

$$\mathbf{S}_{tt} = \mathbf{H}_{tt} - \mathbf{H}_{tR}\mathbf{H}_{RR}^{-1}\mathbf{H}_{Rt}, \qquad \mathbf{S}_{RR} = \mathbf{H}_{RR} - \mathbf{H}_{Rt}\mathbf{H}_{tt}^{-1}\mathbf{H}_{tR} \tag{3}$$

are the translation information left once rotation is free, and the reverse. Each block has one unit, so its eigenvalues can be compared, which is not true of the full Hessian, where rotational and translational eigenvalues mix units. In a corridor $\mathbf{S}_{tt}$ has one small eigenvalue along the axis and two large ones across it.




Fig. 1. Structure of DualChan-LVIO. Both odometries run unchanged and A-LOAM has no IMU. The fusion node weights their increments per direction, gates the VIO by consistency, anchors heading to wall structure and returns a degeneracy-gated initial guess to the scan-to-map matching.

The translation channel treats the LiDAR increment as a measurement with information $c_T\mathbf{S}_{tt}$ and the VIO increment as a prior with information $\gamma\mathbf{I}$:

$$\mathbf{W}_t = (c_T\mathbf{S}'_{tt} + \gamma\mathbf{I})^{-1}c_T\mathbf{S}'_{tt}, \tag{4}$$

where $\mathbf{S}'_{tt}$ is $\mathbf{S}_{tt}$ after the support check of Section III-C. Along an eigenvector with eigenvalue λ the weight is $c_T\lambda/(c_T\lambda+\gamma)$. It is close to one where the scene constrains the motion and close to zero along a degenerate axis, with no switching threshold. The scale $c_T = 0.03$ was chosen once on Multi Floor. The gate value γ is described in Section III-D.

With A-LOAM, the VINS-Mono rotation was better than the LiDAR rotation on most sequences in replay, so in the fused mode $\mathbf{W}_R = \mathbf{0}$ and $\mathbf{S}_{RR}$ is monitored. A rotation-consistency check accumulates $\|\,\mathrm{Log}(\Delta\mathbf{R}_L^\top\Delta\mathbf{R}_V)\|$ over 2 s and 10 s windows. If it exceeds 0.402 rad or 0.585 rad, the largest values seen on 19 Multi Floor recordings, the LiDAR rotation carries the step with $\mathbf{W}_R = (\mathbf{S}_{RR} + 10^{-3}\mathbf{I})^{-1}\mathbf{S}_{RR}$.

C. Orientation-tensor support

The Hessian reflects only the correspondences that A-LOAM accepted in one scan. As a second opinion that uses no correspondence, at every keyframe (1 m or 0.2 rad of motion) we classify each point by the eigenvalues $\mu_1 \le \mu_2 \le \mu_3$ of its 12-neighbour covariance as planar, with normal $\mathbf{n}$, when $(\mu_2-\mu_1)/\mu_3 > 0.5$, or linear, with direction $\mathbf{d}$, when $(\mu_3-\mu_2)/\mu_3 > 0.5$, and form

$$\mathbf{G} = \frac{1}{n_p+n_l}\Big(\sum_{\text{planar}}\mathbf{n}\mathbf{n}^\top + \tfrac{1}{2}\sum_{\text{linear}}(\mathbf{I}-\mathbf{d}\mathbf{d}^\top)\Big). \tag{5}$$

A plane constrains translation along its normal and an edge in the plane perpendicular to it. $\mathbf{G}$ has unit trace and uses no correspondence and no solver state. It is scaled to the solver's total information, $\mathbf{B} = \mathrm{tr}(\mathbf{H}_{tt})\,\mathbf{G}$, rotated into the current frame, and combined with $\mathbf{A} = \mathbf{S}_{tt}$ by the generalised maximum

$$\mathbf{S}'_{tt} = \mathbf{B}^{1/2}\max(\mathbf{M},\mathbf{I})\,\mathbf{B}^{1/2}, \qquad \mathbf{M} = \mathbf{B}^{-1/2}\mathbf{A}\mathbf{B}^{-1/2}, \tag{6}$$

which raises every generalised eigenvalue below one to one, so along each direction the larger of the two supports is kept. This rule is optimistic; the protection against a solver that is confident and wrong comes from the gate below. A tensor of planar normals alone understated the support from door frames and pipes and made the corridor sequences 0.26 to 1.0 m worse in replay.

D. Consistency gate and guards

Within one VIO segment, every scan closes a 10 s window. For windows with at least 1 m of LiDAR motion we form $x = \ln(\|\Delta\mathbf{p}_V\|/\|\Delta\mathbf{p}_L\|)$, and $r = \sqrt{\overline{x^2}}$ over the segment and over the windows that ended in the last 5 s. The VIO is trusted, $\gamma = 1$ in (4), while $r \le 0.157$ and the fast value is ≤ 0.277; otherwise $\gamma = 0$ and $\mathbf{W}_t = \mathbf{I}$. The VIO is trusted at the start of a segment until enough windows exist (200 for the segment test, 25 for the fast one).

Three guards act on single steps. A VIO step above 1 m or 0.5 rad marks a VIO failure and restarts the warm-up. While the VIO is trusted, a LiDAR path that runs more than 4.325 m ahead of the VIO path within 2 s marks the LiDAR step as failed, and the VIO carries it. At every entry into the fused mode the orientation is reset to

$$\mathbf{R}_f = \mathbf{R}_{\text{off}}\,\mathbf{R}_{VL}, \qquad \mathbf{R}_{\text{off}} = \text{mean}_j\left(\mathbf{R}_{A,j}\mathbf{R}_{VL,j}^{\top}\right), \tag{7}$$

where $\mathbf{R}_{VL}$ is the LiDAR orientation predicted by the VIO and the robust chordal mean runs over the warm-up scans. Without this anchor the fused heading jumped by 6 to 7° at the first fused scan of Long Corridor, because the warm-up had already integrated a fast turn that the lagging VIO then added again.

E. Structure-anchored heading

Heading is unobservable for the VIO and dominates the error in long corridors. At each keyframe the near-vertical planar normals are levelled with the VIO gravity direction, and their horizontal directions form an axial histogram $h(\theta)$ with 0.5° bins over 180°. The heading error is the shift, searched over ±15°, that best aligns h with a reference histogram learned in the world frame. It passes a Kalman update and is applied at no more than 0.25° per scan. It switches itself off when the structure is not distinct, using a test against random directions, a unique correlation peak, a chi-squared gate and a drift gate.

F. Degeneracy-gated prediction

A-LOAM starts each scan-to-map registration from a predicted pose. We compose the last fused pose with an increment $\boldsymbol{\delta}$ chosen by the rule of [12]: the three smallest eigenvalues of $\mathbf{H}$ are normalised to unit norm, $\bar{\boldsymbol{\lambda}}$, and the scan is degenerate if any $\bar{\lambda}_i$ lies below $[0.12,\ 0.27,\ 0.48]_i$. A status queue of the last five scans gives

$$\boldsymbol{\delta} = \begin{cases} \boldsymbol{\delta}_L & \text{(a)}, \\ w\,\boldsymbol{\delta}_L \oplus (1-w)\,\boldsymbol{\delta}_V,\ w = \min(1, \sqrt{3}\bar{\lambda}_1) & \text{(b)}, \\ \boldsymbol{\delta}_V & \text{(c)}, \end{cases} \tag{8}$$

where case (a) holds when the scan is not degenerate or the VIO is unusable, (b) when the queue holds both states and (c) when it holds only degenerate scans. Here $\boldsymbol{\delta}_L$ is A-LOAM's scan-to-scan increment, $\boldsymbol{\delta}_V$ the VIO increment, and $\oplus$ combines increments in the tangent space. The VIO is unusable after a failure step or for a step above the 1 m or 0.5 rad limits. Without this rule, the system used the VIO increment whenever it was usable and no motion otherwise; Section V-B compares the two.

Algorithm 1 Fusion node with degeneracy-gated prediction

Input: previous pose $\mathbf{T}_{k-1}$; A-LOAM Hessian $\mathbf{H}$ and increment $\boldsymbol{\delta}_L$; VIO increment $\boldsymbol{\delta}_V$ and status S_{vo}; orientation tensor $\mathbf{G}$; status queue Q_s of size 5; mode
Output: fused pose $\mathbf{T}_k$; initial guess $\mathbf{T}_{k+1}^{\text{init}}$ for A-LOAM

1: $u \leftarrow (S_{vo} = \text{fail}) \ \vee\ \|\boldsymbol{\delta}_V\|$ above 1 m or 0.5 rad ▷ VIO unusable
2: **if** u **then** mode ← failure; restart the 20 s warm-up
3: **end if**
4: **if** mode ∈ {warm-up, failure} **then**
5: $\mathbf{W}_t \leftarrow \mathbf{I},\ \mathbf{W}_R \leftarrow \mathbf{I}$ ▷ the LiDAR carries the step
6: **else**
7: **if** first fused scan of the segment **then**
8: $\mathbf{R}_{k-1} \leftarrow \mathbf{R}_{\text{off}}\mathbf{R}_{VL}$ ▷ anchored hand-over
9: **end if**
10: $\mathbf{S}_{tt}, \mathbf{S}_{RR} \leftarrow$ Schur complements of $\mathbf{H}$
11: $\mathbf{S}'_{tt} \leftarrow$ generalised maximum of $\mathbf{S}_{tt}$ and $\text{tr}(\mathbf{H}_{tt})\mathbf{G}$ ▷ tensor
12: update r and r_{fast}; $\gamma \leftarrow 1$ if $r \le 0.157$ and $r_{\text{fast}} \le 0.277$, else 0
13: $\mathbf{W}_t \leftarrow (c_T\mathbf{S}'_{tt} + \gamma\mathbf{I})^{-1} c_T\mathbf{S}'_{tt}$ ▷ translation channel
14: $\mathbf{W}_R \leftarrow \mathbf{0}$; **if** rotation check above 0.402 rad (2 s) or 0.585 rad (10 s) **then** $\mathbf{W}_R \leftarrow (\mathbf{S}_{RR} + 10^{-3}\mathbf{I})^{-1}\mathbf{S}_{RR}$
15: **if** LiDAR path leads the VIO path by more than 4.325 m within 2 s **then**
16: $\mathbf{W}_t \leftarrow \mathbf{0}$ ▷ LiDAR step failed, the VIO carries it
17: **end if**
18: **end if**
19: $\Delta\mathbf{t} \leftarrow \mathbf{W}_t\Delta\mathbf{t}_L + (\mathbf{I} - \mathbf{W}_t)\Delta\mathbf{t}_V$; $\boldsymbol{\phi} \leftarrow \mathbf{W}_R\text{Log}(\Delta\mathbf{R}_L) + (\mathbf{I} - \mathbf{W}_R)\text{Log}(\Delta\mathbf{R}_V)$
20: $\mathbf{T}_k \leftarrow \mathbf{T}_{k-1} \oplus (\boldsymbol{\phi}, \Delta\mathbf{t})$; apply the heading correction, at most 0.25° per scan
21: $\bar{\boldsymbol{\lambda}} \leftarrow$ three smallest eigenvalues of $\mathbf{H}$, normalised; flag ← $\exists i : \bar{\lambda}_i < \lambda_{t,i}$, with $\boldsymbol{\lambda}_t = [0.12, 0.27, 0.48]$
22: **if** u or no scan in Q_s is degenerate **then**
23: $\boldsymbol{\delta} \leftarrow \boldsymbol{\delta}_L$ ▷ A-LOAM's own increment
24: **else if** Q_s holds both states **then**
25: $w \leftarrow \min(1, \sqrt{3}\bar{\lambda}_1)$; $\boldsymbol{\delta} \leftarrow w\boldsymbol{\delta}_L \oplus (1-w)\boldsymbol{\delta}_V$ ▷ interpolation
26: **else**
27: $\boldsymbol{\delta} \leftarrow \boldsymbol{\delta}_V$ ▷ only degenerate scans
28: **end if**
29: $\mathbf{T}_{k+1}^{\text{init}} \leftarrow \mathbf{T}_k \oplus \boldsymbol{\delta}$; dequeue Q_s and enqueue flag
30: **return** $\mathbf{T}_k,\ \mathbf{T}_{k+1}^{\text{init}}$

G. Per-scan procedure

Algorithm 1 puts the parts together for one scan. Lines 1 to 20 form the fusion of Sections III-B to III-E, and lines 21 to 30 the gated prediction of Section III-F, which returns A-LOAM's initial guess; the source of every constant is given in Table I.

IV. Experimental Setup

A. Sequences

Table II lists the five real sequences. Multi Floor and Long Corridor are the two SubT-MRS [25] sequences on which Switch-SLAM reports results [12]. Corridor02 and Cave02, also from SubT-MRS, add a longer corridor and a dark cave. GEODE stairs alpha [26] is a staircase from a dataset built

TABLE I
FROZEN CONSTANTS

Constant	Value	Source
c_T (translation scale)	0.03	Multi Floor, once
c_R in fused mode	0	Replay (VIO rotation better)
Warm-up	20 s	Design value
VIO step limits	1 m, 0.5 rad	Design value
Rotation check	0.402 rad / 2 s, 0.585 rad / 10 s	19 Multi Floor recordings
Scale gate	0.157 (segment), 0.277 (5 s)	6 Multi Floor replays
LiDAR guard	4.325 m over 2 s	6 Multi Floor replays
Tensor k-NN, shape cut	12, 0.5	Shared with heading
Heading search, step	$\pm 15^\circ$, 0.25°/scan	Long Corridor, Corridor02
Prediction thresholds	$[0.12, 0.27, 0.48]$, queue 5	From [12]

TABLE II
SEQUENCES

Sequence	Path (m)	Time (s)	Main difficulty	Replay
Multi Floor	272.7	417	Stairwells between floors	1.0×
Long Corridor	579.2	279	Long uniform corridor	0.5×
Corridor02	695.2	893	Long corridors, loops	0.33×
Cave02	475.0	954	Dark, irregular cave	0.5×
GEODE stairs	301.1	345	Staircase, weak structure	0.5×

around degenerate scenes. All have ground-truth trajectories. In addition, one live route in a Gazebo farm world (about 80 m, forward RGB camera) is used because Switch-SLAM reports a Farm sequence; it is described with its results.

B. Implementation and metric

A-LOAM [24] is patched to publish the Hessian of its scan-to-scan registration, and its mapping stage takes the predicted pose from the fusion node in place of its own odometry. VINS-Mono runs unchanged in its own container. The fusion node is written in Python. All runs are live: the bag is replayed through the whole pipeline on one laptop (AMD Ryzen 5 5600H), at the rates in Table II, because the pipeline does not keep up at full rate on longer sequences. The metric is the absolute trajectory error of the front end without loop closure: the estimated positions are aligned to the ground truth by the rigid transformation without scale [27] over the full span, and we report the RMSE and the maximum, as [12] does.

C. Protocol

The constants in Table I were fixed on Multi Floor and not changed afterwards. Multi Floor is therefore calibration data, and Long Corridor and Corridor02 were used while designing the heading anchor and the guards. Cave02 and GEODE were first run after the configuration without gated prediction was frozen, but the gated prediction was added after those runs, so for the final system no sequence is strictly held out. The prediction rule adds no fitted constant; its thresholds are those of [12]. Every completed run is reported, failures included.

Significance tests. Following the format of Ganesan *et al.* [28], each comparison tests H_0: the median ATE RMSE of the baseline equals that of DualChan-LVIO, against H_1: the baseline is larger, at the 5 % level. We use the exact one-sided Mann-Whitney test, whose null distribution is enumerated over all arrangements of the pooled runs, so that no normal approximation is needed with so few runs, and add Welch's t-test where both groups have at least two runs. With n baseline runs and m runs of DualChan-LVIO the smallest possible p is $1/\binom{n+m}{m}$, so one DualChan-LVIO run against three baseline runs cannot go below 0.25. The Farm has one run per method and is not tested. The published Switch-SLAM values are single numbers and cannot be tested.

D. Baselines

We report A-LOAM alone and VINS-Mono alone in our pipeline, the published Switch-SLAM results [12] (mean of three runs, real time on an Intel i7-1165G7), and our re-implementation of Switch-SLAM. No code of Switch-SLAM has been released. A-LOAM has no IMU, whereas Switch-SLAM matches each scan to its map with a LiDAR-inertial front end and starts the match from an IMU-propagated guess. Our re-implementation follows its Algorithm 1 and Eqs. (11) to (16) on the same A-LOAM and VINS-Mono, but A-LOAM's scan-to-scan increment replaces the IMU-propagated LiDAR odometry of the original, and the remap is applied to A-LOAM's converged solution instead of inside the solver.

V. RESULTS

A. Accuracy against the baselines

Table III gives the results. On Multi Floor DualChan-LVIO reached 0.54 m RMSE and 1.01 m maximum, against 1.61 / 3.63 m published for Switch-SLAM [12]. On Long Corridor it reached 2.10 / 3.73 m against 2.42 / 5.09 m, and on the Gazebo farm route 0.290 / 0.562 m against 0.38 / 1.10 m (Fig. 2). These comparisons are not like for like: Switch-SLAM matches each scan to its map with a LiDAR-inertial front end, starts from an IMU-propagated guess and switches between the sources, whereas A-LOAM has no IMU and our fusion blends the sources per direction. The published values are means of three runs, ours come from one to four runs, cover the front end only and are scored with the protocol of Section IV. The variant without gated prediction gave 0.72 / 1.30 m and 2.01 / 4.80 m over three runs each, with run-to-run ranges of 0.45 to 1.01 m and 1.75 to 2.15 m, so the comparison with the published numbers does not depend on one favourable run of one variant.

Two facts limit this comparison. First, our VINS-Mono configuration alone reaches 1.28 m on Multi Floor and 5.81 m on Long Corridor, where the Switch-SLAM letter reports 6.30 m and 11.8 m for VINS-Mono; part of the gap therefore lies in the front ends, not in the fusion. Second, our re-implementation of Switch-SLAM in the same pipeline gave 5.24 m and 12.85 m, far from the published values. With its rule the scan was degenerate on only 1.5 % of Multi Floor scans and 4.5 % of Long Corridor scans, so it behaved mostly like A-LOAM, whose guess in our pipeline lacks the IMU propagation of the original. We therefore read the re-implementation as a lower bound on Switch-SLAM in our pipeline, not as a reproduction.

Relative to the two single sources, the fusion was below both on Multi Floor (VINS-Mono 1.28 m, A-LOAM 26.4 m), Long Corridor (5.81 m and 15.8 m) and Corridor02, where A-LOAM alone failed in all four runs and VINS-Mono reached

TABLE III
ATE OF THE FRONT END, RMSE / MAX IN METRES; n = NUMBER OF LIVE RUNS, MEAN OVER RUNS. "–": NOT AVAILABLE OR NOT RECORDED (NOT A FAILED RUN); A RUN WITH ATE ABOVE 10 M COUNTS AS FAILED. BOLD: BEST OF OUR OWN ROWS. FARM: GAZEBO SIMULATION, ROUTE ABOUT 80 M.

Method	Multi Floor	Long Corridor	Corridor02	Cave02	GEODE stairs	Farm
A-LOAM [24], our pipeline	26.4 / 49.4 (n=3)	15.8 / –[c] (n=3)	46.5 to 93.0 (n=4, all failed)	–	7.98 / 22.09[e] (n=1)	0.478 / 0.977 (n=1)
VINS-Mono [4], our configuration[a]	1.28 / 2.47 (n=3)	5.81 / 15.54 (n=3)	4.03 / 6.75 (n=3)	10.2 / – (n=3, failed)	153 to 272 (n=7, failed)	9.39 / 16.76 (n=2)
Switch-SLAM, published [12][d]	1.61 / 3.63	2.42 / 5.09	not reported	not reported	not reported	0.38 / 1.10
Switch-SLAM, our replica (A-LOAM)	5.24 / 10.58 (n=2)	12.85 / 23.50 (n=2)	not run	not run	not run	not run
DualChan-LVIO without gated prediction	0.72 / 1.30 (n=3)	**2.01** / 4.80 (n=3)	**1.38 / 2.60**[b] (n=3)	7.25 / 12.06 (n=3)	7.23 / 18.25 (n=4)	0.472 / 1.068 (n=1)
DualChan-LVIO	**0.54 / 1.01** (n=1)	2.10 / **3.73** (n=1)	1.99 / 3.46 (n=2)	**6.23 / 10.56** (n=1)	**5.04 / 12.38** (n=3)	**0.290 / 0.562** (n=1)

[a] VINS-Mono alone is taken from its own runs on Multi Floor, Long Corridor, Corridor02 and Cave02, and from the logs of the fused runs on GEODE and the farm, which is valid because VINS-Mono takes no input from the fusion; a range is given where it failed. [b] Mean of the two runs that completed normally; the third run diverged at 104.00 / 149.20 m (Section V-B). [c] Earlier batch at 1.0× replay; maximum not recorded. [d] Values copied from Table II of [12] with the order changed to RMSE / max; mean of three runs, real time, LiDAR-inertial scan-to-map front end with an IMU-propagated guess. Not like for like with our rows. The published Farm route is 536 m with fast-rotation and plane-only stretches; ours is about 80 m without them. [e] One run on another machine.

4.03 m. On Corridor02 the fused trajectory follows the ground truth over 695 m (Fig. 5).

B. Effect of the gated prediction

Fig. 4 shows every run of both variants. With gated prediction the mean RMSE was lower on Multi Floor (0.54 against 0.72 m), Cave02 (6.23 against 7.25 m) and GEODE (5.04 against 7.23 m), about the same on Long Corridor (2.10 against 2.01 m), and higher on the two normal Corridor02 runs (1.99 against 1.38 m). On GEODE the three runs with gated prediction (3.26 to 6.36 m) and the four without (6.15 to 9.15 m) barely overlap. An exact Mann-Whitney test gives $U = 1$, one-sided $p = 0.057$, which is suggestive and not significant.

The mechanism is visible in the logs. Without gated prediction, the predicted pose carried no motion whenever the VIO was unusable, which happened on 13.5 % of Cave02 scans (the first 130 s, where 14 to 36 % of the squared error arises) and on 78 % of GEODE scans. A-LOAM then started each registration one scan behind. With the gated rule, A-LOAM's own increment is used in that case, and since the eigenvalue test fires on few scans (0.0 % of Cave02, 10.3 % of GEODE), the guess came from the LiDAR on 100 % and 93.7 % of scans. Comparing the first run of each variant on Cave02 (Fig. 3), the error with gated prediction was lower in every 120 s block, from 12.0 to 9.7 m in the first block and from 4.9 to 5.8 m down to 4.1 to 5.0 m in the later ones.

One run of the variant without gated prediction diverged on Corridor02 (104.00 m). The logs show that A-LOAM turned the wrong way at about 545 s: its trajectory and the VIO's separated from 6 m to 49 m within 7 s. The rotation check closed for about 10 s, which hands the rotation to the LiDAR, the scale gate closed for a single scan, and the fused pose followed A-LOAM. VINS-Mono alone was normal in that run (3.55 m). The two runs with gated prediction on Corridor02 did not diverge; two runs cannot establish a failure rate, so we report this as an observed failure mode of the system, not as an effect of the prediction.

C. Hypothesis tests

Table IV gives the tests of Section IV-C for every baseline that has runs on the same sequence. DualChan-LVIO was lower than the baseline in every pairing of runs against VINS-Mono alone and A-LOAM alone. Only the GEODE comparison with VINS-Mono alone rejects H_0 with the exact test ($p = 0.008$, 21 of 21 pairs; Welch $p = 1.7 \times 10^{-5}$). On Corridor02 the exact test cannot go below 0.10 with three and two runs, and Welch's test rejects against VINS-Mono alone ($p = 0.008$) and A-LOAM alone ($p = 0.022$). On Multi Floor, Long Corridor and Cave02 one run of DualChan-LVIO sets the limit at $p = 0.25$, so the test cannot reject whatever the numbers are.

Against the variant without gated prediction no test rejects. On GEODE DualChan-LVIO was lower in 11 of 12 pairs ($p = 0.057$, Welch $p = 0.065$, and $p = 0.114$ for the maximum error), and on Corridor02 it was higher in four of six pairs, those against the two normal runs of the variant (the diverged run of 104 m accounts for the other two). The tests therefore support one claim, that the fusion is reliably better than VINS-Mono alone where VINS-Mono fails, and none about the gated prediction, which the data show only as a lower mean on three sequences.

TABLE IV
ONE-SIDED TESTS OF H_0: MEDIAN ATE RMSE OF THE BASELINE EQUALS THAT OF DUALCHAN-LVIO, AGAINST H_1: BASELINE LARGER. n: RUNS OF THE BASELINE / OF DUALCHAN-LVIO. EXACT MANN-WHITNEY p FOR THE RMSE AND THE MAXIMUM ERROR, WELCH p FOR THE RMSE. "–": NOT COMPUTED (ONE RUN IN A GROUP, OR MAXIMUM NOT RECORDED).

Baseline	Sequence	n	Lower in	p (RMSE)	p (max)	Welch p	Reject H_0
VINS-Mono alone	Multi Floor	3 / 1	3 of 3	0.25	0.25	–	No
	Long Corridor	3 / 1	3 of 3	0.25	0.25	–	No
	Corridor02	3 / 2	6 of 6	0.10	0.10	0.008	No (Welch yes)
	Cave02	3 / 1	3 of 3	0.25	–	–	No
	GEODE stairs	7 / 3	21 of 21	**0.008**	**0.008**	1.7×10^{-5}	**Yes**
A-LOAM alone	Multi Floor	3 / 1	3 of 3	0.25	0.25	–	No
	Long Corridor	3 / 1	3 of 3	0.25	0.25	–	No
	Corridor02	3 / 2	6 of 6	0.10	0.10	0.022	No (Welch yes)
Without gated prediction	Multi Floor	3 / 1	2 of 3	0.50	0.50	–	No
	Long Corridor	3 / 1	2 of 3	0.50	0.50	–	No
	Corridor02	3 / 2	2 of 6	0.80	0.80	0.21	No
	Cave02	3 / 1	3 of 3	0.25	0.25	–	No
	GEODE stairs	4 / 3	11 of 12	0.057	0.114	0.065	No

D. How often each part acted

Table V reads the logs of the first run of the final system on each sequence. Two observations qualify the description of Section III. The smallest eigenvalue of $\mathbf{W}_t$ never fell below 0.5 in the fused mode on any sequence; its median was 0.69 on Long Corridor and 0.80 to 0.81 on Multi Floor and Corridor02.




Fig. 2. Top-down paths on the three sequences for which Switch-SLAM publishes results. Ground truth, DualChan-LVIO, A-LOAM's output and VINS-Mono alone are from the same run and each is aligned to the ground truth on its own; the legends give ATE RMSE / maximum. Switch-SLAM published values only, no path is available. On the farm the published route is 536 m with fast-rotation and plane-only stretches; ours is about 80 m without them, with one run per version.




Fig. 3. Cave02, first run of each variant: RMSE per 120 s window. The gated prediction lowers every window; the first 240 s dominate both runs.




Fig. 4. ATE RMSE of every live run, logarithmic scale. The diverged Corridor02 run of the variant without gated prediction is the point at 104 m.

The translation channel therefore never handed a direction to the VIO completely on these sequences. It blended the two increments, giving the VIO 19 to 31 % of the weakest direction. The scale gate, in contrast, acted strongly where the VIO was poor: it was closed on 94.4 % of the fused scans of Cave02 and 71.5 % of GEODE, and on at most 1.9 % elsewhere. On GEODE the fused mode covered only 17.0 % of the scans, since warm-up and VIO failures took the rest. The rotation check closed only on GEODE (3.6 %), and the heading anchor acted on the three corridor-type sequences and hardly at all on Cave02 and GEODE, where the wall structure it needs is missing.

TABLE V
HOW OFTEN EACH PART ACTED (FINAL SYSTEM, FIRST RUN PER SEQUENCE; SHARES OF SCANS)

	Multi Floor	Long Corr.	Corridor02	Cave02	GEODE
Warm-up mode	9.8	7.6	11.3	14.5	48.5
VIO-failure mode	0.0	0.0	0.0	1.9	34.5
Fused mode	90.2	92.4	88.7	83.6	17.0
Median min. eigenvalue of $\mathbf{W}_t$	0.81	0.69	0.80	1.00	1.00
Scale gate closed (fused)	0.1	0.0	1.9	94.4	71.5
Rotation check closed (fused)	0.0	0.0	0.0	0.0	3.6
Guess from LiDAR increment	98.5	95.4	97.8	100.0	93.6
Heading correction, total (°)	80.8	37.2	24.4	0.0	1.3

E. Where the error remains

Cave02 and GEODE stay at 5 to 6 m. On Cave02 the error is concentrated in the first 300 s. In the three runs without gated prediction, aligning each segment on its own, the fused error is 0.67 to 0.70 m after 300 s and 2.2 to 2.4 m before it, so most of the 6 to 7 m full-span error is an offset between segments. A-LOAM stalls between 285 and 305 s, and the VIO, whose scale is 22 to 28 % off on this sequence, is rejected by the scale gate, as designed, so nothing replaces the stalled LiDAR. On GEODE VINS-Mono diverged in every run, the fused output is




Fig. 5. Top-down paths on the sequences without a published Switch-SLAM run, first run of DualChan-LVIO. Same conventions as Fig. 2. VINS-Mono alone is off the plot on Cave02 and GEODE.

close to A-LOAM's, and the remaining error is mostly vertical. In both cases the front end is limited by the odometries it fuses. An offline loop-closure back end on the saved keyframes of the variant without gated prediction lowered Corridor02 from 1.47 to 1.11 m with 22 loops but found no loops on GEODE.

On the 80 m route in the Gazebo farm world with a forward 60 Hz RGB camera, DualChan-LVIO reached 0.290 / 0.562 m against 0.472 / 1.068 m without gated prediction and 0.478 / 0.977 m for A-LOAM alone (one run each; VINS-Mono alone 4.31 and 14.47 m in two runs). The route is shorter than the 536 m Farm sequence of [12] and lacks its fast-rotation and plane-only phases, so the numbers are not comparable with the published ones (Fig. 2).

VI. Discussion

The measured weights change how the design should be read. On these sequences the translation channel never declared a direction degenerate: the smallest weight stayed between 0.5 and 1, so the LiDAR always carried at least half of every translation component, and the VIO contributed a smaller share along the weakest axis. The accuracy came from three other places: the gate that withdrew a VIO with the wrong scale (Cave02, GEODE), the heading anchor on the corridor sequences, and the predicted pose. A soft blend is cheap to get wrong in a small way and hard to get wrong in a large way, which suited sequences where the LiDAR was weak but rarely blind. On a sequence where the LiDAR is truly blind along an axis, such as the plane-only scenes of [12], the weight would fall towards zero and the VIO would carry that axis; we have not tested such a sequence.

The gated prediction acted mostly through its first case. Because the eigenvalue test of [12] fired on few scans, the rule usually returned A-LOAM's own increment, and its main effect was to stop the predicted pose from freezing whenever the VIO was unusable. The same observation explains our re-implementation of Switch-SLAM: with the test firing on 1.5 to 4.5 % of scans it seldom switched, so it inherited A-LOAM's weakness on these sequences. A test computed on blocks of one unit, such as $\mathbf{S}_{tt}$, may fire more often; when we evaluated it on the logged Hessians, the rotation block crossed a condition-number threshold of 15.7 on 37 to 82 % of scans on every sequence except Cave02 (4.4 %), which is too often to switch on, and the translation block fell below the information of the VIO on under 8 %. Choosing that threshold for switching remains open.

The two sources also fail in different ways, and the checks have to match them. A VIO with the wrong scale is withdrawn by the gate, and the LiDAR then carries the step, as on Cave02 and GEODE. A LiDAR that turns the wrong way while the VIO is healthy, as in the diverged Corridor02 run, is caught only if the disagreement lasts long enough for the guard or the gate. A stalled LiDAR with a distrusted VIO, as on Cave02, is caught by neither, because no third source is available to tell which one is right.

VII. Limitations

Most cells of Table III rest on one to three runs, and the final system has one run on Multi Floor, Long Corridor and Cave02. Switch-SLAM reports means of three runs, and the run-to-run spread we observed (0.45 to 1.01 m on Multi Floor, 6.15 to 9.15 m on GEODE) is of the same order as some of the differences we discuss, so none of the differences between our two variants is statistically established (Table IV). The constants were set on Multi Floor, which is also one of the two comparison sequences, and the gated prediction was added after the Cave02 and GEODE runs. A confirmation on sequences that played no part in the design, such as the remaining SubT-MRS caves, is needed before any claim of generalisation. The comparison with Switch-SLAM mixes two hardware platforms and two VINS-Mono configurations, and

replay below real time removes the timing pressure that a robot would impose. Finally, the scale gate protects the fusion from a VIO with the wrong scale but cannot replace a LiDAR that stalls, which is the dominant failure on Cave02.

VIII. Conclusion

DualChan-LVIO fuses LiDAR and visual-inertial odometry per direction. Schur complements separate the rotation and translation channels of the registration Hessian, an orientation tensor adds the support of raw geometry, consistency checks decide when the VIO may carry a step, and the switching rule of Switch-SLAM is kept only for the scan-to-map initial guess. In live runs on five real sequences the front end reached 0.54 m on Multi Floor and 2.10 m on Long Corridor, below the published Switch-SLAM values on both (a comparison that is not like for like), stayed bounded on the long Corridor02 sequence where A-LOAM alone diverged, and left 5 to 6 m on Cave02 and GEODE, where the error comes from the odometries themselves. The next steps are repeated runs of the final system on every sequence, a test on held-out caves, and a replacement for the stalled LiDAR on Cave02, where neither source is currently trusted.

References

[1] J. Zhang and S. Singh, "LOAM: Lidar odometry and mapping in real-time," in *Proc. Robot.: Sci. Syst.*, Berkeley, CA, USA, Jul. 2014.

[2] T. Shan, B. Englot, D. Meyers, W. Wang, C. Ratti, and D. Rus, "LIO-SAM: Tightly-coupled lidar inertial odometry via smoothing and mapping," in *Proc. IEEE/RSJ Int. Conf. Intell. Robots Syst.*, Las Vegas, NV, USA, 2020, pp. 5135–5142.

[3] W. Xu, Y. Cai, D. He, J. Lin, and F. Zhang, "FAST-LIO2: Fast direct LiDAR-inertial odometry," *IEEE Trans. Robot.*, vol. 38, no. 4, pp. 2053–2073, Aug. 2022.

[4] T. Qin, P. Li, and S. Shen, "VINS-Mono: A robust and versatile monocular visual-inertial state estimator," *IEEE Trans. Robot.*, vol. 34, no. 4, pp. 1004–1020, Aug. 2018.

[5] C. Cadena, L. Carlone, H. Carrillo, Y. Latif, D. Scaramuzza, J. Neira, I. Reid, and J. J. Leonard, "Past, present, and future of simultaneous localization and mapping: Toward the robust-perception age," *IEEE Trans. Robot.*, vol. 32, no. 6, pp. 1309–1332, Dec. 2016.

[6] K. Ebadi *et al.*, "Present and future of SLAM in extreme environments: The DARPA SubT challenge," *IEEE Trans. Robot.*, vol. 40, pp. 936–959, 2024.

[7] T. Shan, B. Englot, C. Ratti, and D. Rus, "LVI-SAM: Tightly-coupled lidar-visual-inertial odometry via smoothing and mapping," in *Proc. IEEE Int. Conf. Robot. Autom.*, Xi'an, China, May 2021, pp. 5692–5698.

[8] J. Lin, C. Zheng, W. Xu, and F. Zhang, "R^{2}LIVE: A robust, real-time, LiDAR-inertial-visual tightly-coupled state estimator and mapping," *IEEE Robot. Autom. Lett.*, vol. 6, no. 4, pp. 7469–7476, Oct. 2021.

[9] J. Lin and F. Zhang, "R^{3}LIVE: A robust, real-time, RGB-colored, LiDAR-inertial-visual tightly-coupled state estimation and mapping package," in *Proc. IEEE Int. Conf. Robot. Autom.*, 2022, pp. 10 672–10 678.

[10] C. Zheng, Q. Zhu, W. Xu, X. Liu, Q. Guo, and F. Zhang, "FAST-LIVO: Fast and tightly-coupled sparse-direct LiDAR-inertial-visual odometry," in *Proc. IEEE/RSJ Int. Conf. Intell. Robots Syst.*, 2022, pp. 4003–4009.

[11] S. Zhao, H. Zhang, P. Wang, L. Nogueira, and S. Scherer, "Super odometry: IMU-centric LiDAR-visual-inertial estimator for challenging environments," in *Proc. IEEE/RSJ Int. Conf. Intell. Robots Syst.*, 2021, pp. 8729–8736.

[12] J. Lee, R. Komatsu, M. Shinozaki, T. Kitajima, H. Asama, Q. An, and A. Yamashita, "Switch-SLAM: Switching-based LiDAR-inertial-visual SLAM for degenerate environments," *IEEE Robot. Autom. Lett.*, vol. 9, no. 8, pp. 7270–7277, Aug. 2024.

[13] N. Gelfand, L. Ikemoto, S. Rusinkiewicz, and M. Levoy, "Geometrically stable sampling for the ICP algorithm," in *Proc. 4th Int. Conf. 3-D Digit. Imag. Model.*, Banff, AB, Canada, Oct. 2003, pp. 260–267.

[14] J. Zhang, M. Kaess, and S. Singh, "On degeneracy of optimization-based state estimation problems," in *Proc. IEEE Int. Conf. Robot. Autom.*, Stockholm, Sweden, May 2016, pp. 809–816.

[15] A. Hinduja, B.-J. Ho, and M. Kaess, "Degeneracy-aware factors with applications to underwater SLAM," in *Proc. IEEE/RSJ Int. Conf. Intell. Robots Syst.*, Macau, China, Nov. 2019, pp. 1293–1299.

[16] T. Tuna, J. Nubert, Y. Nava, S. Khattak, and M. Hutter, "X-ICP: Localizability-aware LiDAR registration for robust localization in extreme environments," *IEEE Trans. Robot.*, vol. 40, pp. 452–471, 2024.

[17] H. Yue, Q. Xu, F. Chen, J. Pan, and W. Chen, "LP-ICP: General localizability-aware point cloud registration for robust localization in extreme unstructured environments," arXiv:2501.02580, 2025.

[18] J. Nubert, E. Walther, S. Khattak, and M. Hutter, "Learning-based localizability estimation for robust LiDAR localization," in *Proc. IEEE/RSJ Int. Conf. Intell. Robots Syst.*, Kyoto, Japan, Oct. 2022, pp. 17–24.

[19] J. Hatleskog and K. Alexis, "Probabilistic degeneracy detection for point-to-plane error minimization," *IEEE Robot. Autom. Lett.*, vol. 9, no. 12, pp. 11 234–11 241, Dec. 2024.

[20] T. Tuna, J. Nubert, P. Pfreundschuh, C. Cadena, S. Khattak, and M. Hutter, "Informed, constrained, aligned: A field analysis on degeneracy-aware point cloud registration in the wild," *IEEE Trans. Field Robot.*, vol. 2, pp. 485–515, 2025.

[21] X. Hu, X. Chen, M. Jia, J. Wu, P. Tan, and S. L. Waslander, "DCReg: Decoupled characterization for efficient degenerate LiDAR registration," *Int. J. Robot. Res.*, Aug. 2026, early access.

[22] D. Chung and J. Kim, "NV-LIOM: LiDAR-inertial odometry and mapping using normal vectors towards robust SLAM in multifloor environments," *IEEE Robot. Autom. Lett.*, vol. 9, no. 11, pp. 9375–9382, Nov. 2024.

[23] Z. Chen *et al.*, "RELEAD: Resilient localization with enhanced LiDAR odometry in adverse environments," in *Proc. IEEE Int. Conf. Robot. Autom.*, Yokohama, Japan, May 2024, pp. 3999–4005.

[24] T. Qin and S. Cao, "A-LOAM: Advanced implementation of LOAM," GitHub repository. [Online]. Available: https://github.com/HKUST-Aerial-Robotics/A-LOAM, accessed: Oct. 9, 2026.

[25] S. Zhao *et al.*, "SubT-MRS dataset: Pushing SLAM towards all-weather environments," in *Proc. IEEE/CVF Conf. Comput. Vis. Pattern Recognit.*, Seattle, WA, USA, Jun. 2024, pp. 22 647–22 657.

[26] Z. Chen *et al.*, "Heterogeneous LiDAR dataset for benchmarking robust localization in diverse degenerate scenarios," *Int. J. Robot. Res.*, vol. 45, no. 1, pp. 6–22, Jan. 2026.

[27] S. Umeyama, "Least-squares estimation of transformation parameters between two point patterns," *IEEE Trans. Pattern Anal. Mach. Intell.*, vol. 13, no. 4, pp. 376–380, Apr. 1991.

[28] S. Ganesan, B. Ramalingam, and R. E. Mohan, "A hybrid sampling-based RRT* path planning algorithm for autonomous mobile robot navigation," *Expert Systems with Applications*, vol. 258, p. 125206, Dec. 2024.