



University of Cambridge

bruhopen

Isaac Chan, Bosco Wang, Kevin Xie

2026 ICPC Europe Championship

February 8, 2026

1 Contest

2 Mathematics

3 Data structures

4 Numerical

5 Number theory

6 Combinatorial

7 Graph

8 Geometry

9 Strings

10Various

Contest (1)

template.cpp20 lines

```
#include <bits/allocator.h>
#pragma GCC optimize("O3,unroll-loops")
#pragma GCC target("avx2,bmi,bmi2,lzcnt,popcnt")
#include <bits/stdc++.h>
using namespace std;

#define rep(i, a, b) for(int i = a; i < (b); ++i)
#define all(x) begin(x), end(x)
#define sz(x) (int)(x).size()
typedef long long ll;
typedef pair<int, int> pii;
typedef vector<int> vi;

void solve() {

}

int32_t main() {
    cin.tie(0)->sync_with_stdio(0);
    solve();
}
```

compile.sh2 lines

```
#!/usr/bin/bash
g++ "${1}.cpp" -o "${1}" -DBRUH -std=c++20 -Wall -fsanitize=undefined,
    address
```

StressChecker.cpp20 lines

```
#include "bits/stdc++.h"
using namespace std;

vector<string> readAns(ifstream &fin) {
    vector<string> v;
    string r;
    while(getline(fin, r)) v.push_back(r);
    return v;
}

int32_t main(int32_t argc, char* argv[]) {
    ifstream inf("input.txt", ifstream::in);
    ifstream ouf("output.txt", ifstream::in);
    ifstream ans("answer.txt", ifstream::in);

    vector<string> myAnswer = readAns(ouf);
    vector<string> correctAnswer = readAns(ans);
```

```
1 if (myAnswer != correctAnswer) return -1;
2 return 0;
3 }
```

StressScript.sh12 lines

```
3 set -e
4 g++ code.cpp -std=c++17 -o code
5 g++ brute.cpp -std=c++17 -o brute
6 g++ gen.cpp -std=c++17 -o gen
7 g++ checker.cpp -std=c++17 -o checker
8 for((i=1; ; ++i)); do
9     ./gen $i > input.txt
10    ./code < input.txt > output.txt
11    ./brute < input.txt > answer.txt
12    ./checker > checker_log
13    echo "Passed test: " $i
14 done
```

.bashrc3 lines

```
17 alias c='g++ -Wall -Wconversion -Wfatal-errors -g -std=c++17 \
18 -fsanitize=undefined,address'
21 xmodmap -e 'clear lock' -e 'keycode 66=less greater' #caps = ⇐
```

.vimrc6 lines

```
23 set cin aw ai is ts=4 sw=4 tm=50 nu noeB bg=dark ru cul
24 sy on | im jk <esc> | im kj <esc> | no ; :
25 " Select region and then type :Hash to hash your selection.
26 " Useful for verifying that there aren't mistypes.
27 ca Hash w !cpp -dD -P -fpreprocessed \ | tr -d '[:space:]' \
28 \ | md5sum \ | cut -c-6
```

hash.sh3 lines

```
1 # Hashes a file, ignoring all whitespace and comments. Use for
2 # verifying that code was correctly typed.
3 cpp -dD -P -fpreprocessed | tr -d '[:space:]' | md5sum |cut -c-6
```

troubleshoot.txt52 lines

```
Pre-submit:
Write a few simple test cases if sample is not enough.
Are time limits close? If so, generate max cases.
Is the memory usage fine?
Could anything overflow?
Make sure to submit the right file.

Wrong answer:
Print your solution! Print debug output, as well.
Are you clearing all data structures between test cases?
Can your algorithm handle the whole range of input?
Read the full problem statement again.
Do you handle all corner cases correctly?
Have you understood the problem correctly?
Any uninitialized variables?
Any overflows?
Confusing N and M, i and j, etc.?
Are you sure your algorithm works?
What special cases have you not thought of?
Are you sure the STL functions you use work as you think?
Add some assertions, maybe resubmit.
Create some testcases to run your algorithm on.
Go through the algorithm for a simple case.
Go through this list again.
Explain your algorithm to a teammate.
Ask the teammate to look at your code.
Go for a small walk, e.g. to the toilet.
Is your output format correct? (including whitespace)
Rewrite your solution from the start or let a teammate do it.

Runtime error:
Have you tested all corner cases locally?
Any uninitialized variables?
Are you reading or writing outside the range of any vector?
Any assertions that might fail?
Any possible division by 0? (mod 0 for example)
Any possible infinite recursion?
```

Invalidated pointers or iterators?
Are you using too much memory?
Debug with resubmits (e.g. remapped signals, see Various).

Time limit exceeded:
Do you have any possible infinite loops?
What is the complexity of your algorithm?
Are you copying a lot of unnecessary data? (References)
How big is the input and output? (consider scanf)
Avoid vector, map. (use arrays/unordered_map)
What do your teammates think about your algorithm?

Memory limit exceeded:
What is the max amount of memory your algorithm should need?
Are you clearing all data structures between test cases?

Mathematics (2)

2.1 Equations

$$ax^2 + bx + c = 0 \Rightarrow x = \frac{-b \pm \sqrt{b^2 - 4ac}}{2a}$$

The extremum is given by $x = -b/2a$.

$$ax + by = e \Rightarrow x = \frac{ed - bf}{ad - bc}$$
$$cx + dy = f \Rightarrow y = \frac{af - ec}{ad - bc}$$

In general, given an equation $Ax = b$, the solution to a variable x_i is given by

$$x_i = \frac{\det A'_i}{\det A}$$

where A'_i is A with the i 'th column replaced by b .

2.2 Recurrences

If $a_n = c_1a_{n-1} + \dots + c_ka_{n-k}$, and r_1, \dots, r_k are distinct roots of $x^k - c_1x^{k-1} - \dots - c_k$, there are d_1, \dots, d_k s.t.

$$a_n = d_1r_1^n + \dots + d_kr_k^n.$$

Non-distinct roots r become polynomial factors, e.g.

$$a_n = (d_1n + d_2)r^n.$$

2.3 Trigonometry

$$\sin(v + w) = \sin v \cos w + \cos v \sin w$$

$$\cos(v + w) = \cos v \cos w - \sin v \sin w$$

$$\tan(v + w) = \frac{\tan v + \tan w}{1 - \tan v \tan w}$$

$$\sin v + \sin w = 2 \sin \frac{v + w}{2} \cos \frac{v - w}{2}$$

$$\cos v + \cos w = 2 \cos \frac{v + w}{2} \cos \frac{v - w}{2}$$

$$(V + W) \tan(v - w)/2 = (V - W) \tan(v + w)/2$$

where V, W are lengths of sides opposite angles v, w .

$$a \cos x + b \sin x = r \cos(x - \phi)$$

$$a \sin x + b \cos x = r \sin(x + \phi)$$

where $r = \sqrt{a^2 + b^2}, \phi = \operatorname{atan2}(b, a)$.

2.4 Geometry

2.4.1 Triangles and Quadrilaterals

Side lengths: a, b, c

Semiperimeter: $p = \frac{a + b + c}{2}$

Area: $A = \sqrt{p(p - a)(p - b)(p - c)}$

Circumradius: $R = \frac{abc}{4A}$

Inradius: $r = \frac{A}{p}$

Length of median (divides triangle into two equal-area triangles):

$m_a = \frac{1}{2}\sqrt{2b^2 + 2c^2 - a^2}$

Length of bisector (divides angles in two):

$s_a = \sqrt{bc \left[1 - \left(\frac{a}{b + c} \right)^2 \right]}$

Law of sines: $\frac{\sin \alpha}{a} = \frac{\sin \beta}{b} = \frac{\sin \gamma}{c} = \frac{1}{2R}$

Law of cosines: $a^2 = b^2 + c^2 - 2bc \cos \alpha$


Law of tangents: $\frac{a + b}{a - b} = \frac{\tan \frac{\alpha + \beta}{2}}{\tan \frac{\alpha - \beta}{2}}$

With side lengths a, b, c, d , diagonals e, f , diagonals angle θ , area A and magic flux $F = b^2 + d^2 - a^2 - c^2$:

$4A = 2ef \cdot \sin \theta = F \tan \theta = \sqrt{4e^2 f^2 - F^2}$

For cyclic quadrilaterals the sum of opposite angles is 180° , $ef = ac + bd$, and $A = \sqrt{(p - a)(p - b)(p - c)(p - d)}$.

2.4.2 Spherical coordinates



$$\begin{aligned} x &= r \sin \theta \cos \phi & r &= \sqrt{x^2 + y^2 + z^2} \\ y &= r \sin \theta \sin \phi & \theta &= \arccos(z / \sqrt{x^2 + y^2 + z^2}) \\ z &= r \cos \theta & \phi &= \operatorname{atan2}(y, x) \end{aligned}$$

2.5 Derivatives/Integrals

$$\begin{aligned} \frac{d}{dx} \arcsin x &= \frac{1}{\sqrt{1 - x^2}} & \frac{d}{dx} \arccos x &= -\frac{1}{\sqrt{1 - x^2}} \\ \frac{d}{dx} \tan x &= 1 + \tan^2 x & \frac{d}{dx} \arctan x &= \frac{1}{1 + x^2} \\ \int \tan ax \, dx &= -\frac{\ln |\cos ax|}{a} & \int x \sin ax \, dx &= \frac{\sin ax - ax \cos ax}{a^2} \\ \int e^{-x^2} \, dx &= \frac{\sqrt{\pi}}{2} \operatorname{erf}(x) & \int x e^{ax} \, dx &= \frac{e^{ax}}{a^2} (ax - 1) \end{aligned}$$

Integration by parts:

$$\int_a^b f(x)g(x)dx = [F(x)g(x)]_a^b - \int_a^b F(x)g'(x)dx$$

2.6 Sums

Lagrange Interpolation: for $f(x_i) = y_i$, consider $\sum f_i(x)$, where $f_i(x_j) = \delta_{i,j} y_i$. Becomes $O(n)$ with precomputation when $x_i = i$. Useful for k -th power.

$$f(x) = \sum_{i=1}^n f(x_i) \prod_{j=1, i \neq j}^n \frac{x - x_j}{x_i - x_j}$$

$$\begin{aligned} 1^3 + 2^3 + 3^3 + \dots + n^3 &= \frac{n^2(n + 1)^2}{4} \\ 1^4 + 2^4 + 3^4 + \dots + n^4 &= \frac{n(n + 1)(2n + 1)(3n^2 + 3n - 1)}{30} \end{aligned}$$

2.7 Series

$$\begin{aligned} e^x &= 1 + x + \frac{x^2}{2!} + \frac{x^3}{3!} + \dots, \quad (-\infty < x < \infty) \\ \ln(1 + x) &= x - \frac{x^2}{2} + \frac{x^3}{3} - \frac{x^4}{4} + \dots, \quad (-1 < x \leq 1) \\ \sqrt{1 + x} &= 1 + \frac{x}{2} - \frac{x^2}{8} + \frac{2x^3}{32} - \frac{5x^4}{128} + \dots, \quad (-1 \leq x \leq 1) \\ \sin x &= x - \frac{x^3}{3!} + \frac{x^5}{5!} - \frac{x^7}{7!} + \dots, \quad (-\infty < x < \infty) \\ \cos x &= 1 - \frac{x^2}{2!} + \frac{x^4}{4!} - \frac{x^6}{6!} + \dots, \quad (-\infty < x < \infty) \end{aligned}$$

2.8 Probability theory

Let X be a discrete random variable with probability $p_X(x)$ of assuming the value x . It will then have an expected value (mean) $\mu = \mathbb{E}(X) = \sum_x x p_X(x)$ and variance $\sigma^2 = V(X) = \mathbb{E}(X^2) - (\mathbb{E}(X))^2 = \sum_x (x - \mathbb{E}(X))^2 p_X(x)$ where σ is the standard deviation. If X is instead continuous it will have a probability density function $f_X(x)$ and the sums above will instead be integrals with $p_X(x)$ replaced by $f_X(x)$.

Expectation is linear:

$$\mathbb{E}(aX + bY) = a\mathbb{E}(X) + b\mathbb{E}(Y)$$

For independent X and Y ,

$$V(aX + bY) = a^2 V(X) + b^2 V(Y).$$

2.8.1 Discrete distributions

Binomial distribution

The number of successes in n independent yes/no experiments, each which yields success with probability p is $\operatorname{Bin}(n, p)$, $n = 1, 2, \dots$, $0 \leq p \leq 1$.

$$\begin{aligned} p(k) &= \binom{n}{k} p^k (1 - p)^{n - k} \\ \mu &= np, \sigma^2 = np(1 - p) \end{aligned}$$

$\operatorname{Bin}(n, p)$ is approximately $\operatorname{Po}(np)$ for small p .

First success distribution

The number of trials needed to get the first success in independent yes/no experiments, each which yields success with probability p is $\operatorname{Fs}(p)$, $0 \leq p \leq 1$.

$$\begin{aligned} p(k) &= p(1 - p)^{k - 1}, \quad k = 1, 2, \dots \\ \mu &= \frac{1}{p}, \sigma^2 = \frac{1 - p}{p^2} \end{aligned}$$

Poisson distribution

The number of events occurring in a fixed period of time t if these events occur with a known average rate κ and independently of the time since the last event is $\operatorname{Po}(\lambda)$, $\lambda = t\kappa$.

$$\begin{aligned} p(k) &= e^{-\lambda} \frac{\lambda^k}{k!}, \quad k = 0, 1, 2, \dots \\ \mu &= \lambda, \sigma^2 = \lambda \end{aligned}$$

2.8.2 Continuous distributions

Uniform distribution

If the probability density function is constant between a and b and 0 elsewhere it is $\operatorname{U}(a, b)$, $a < b$.

$$\begin{aligned} f(x) &= \begin{cases} \frac{1}{b - a} & a < x < b \\ 0 & \text{otherwise} \end{cases} \\ \mu &= \frac{a + b}{2}, \sigma^2 = \frac{(b - a)^2}{12} \end{aligned}$$

Exponential distribution

The time between events in a Poisson process is $\operatorname{Exp}(\lambda)$, $\lambda > 0$.

$$\begin{aligned} f(x) &= \begin{cases} \lambda e^{-\lambda x} & x \geq 0 \\ 0 & x < 0 \end{cases} \\ \mu &= \frac{1}{\lambda}, \sigma^2 = \frac{1}{\lambda^2} \end{aligned}$$

Normal distribution

Most real random values with mean μ and variance σ^2 are well described by $\mathcal{N}(\mu, \sigma^2)$, $\sigma > 0$.

$$f(x) = \frac{1}{\sqrt{2\pi\sigma^2}} e^{-\frac{(x - \mu)^2}{2\sigma^2}}$$

If $X_1 \sim \mathcal{N}(\mu_1, \sigma_1^2)$ and $X_2 \sim \mathcal{N}(\mu_2, \sigma_2^2)$ then

$$aX_1 + bX_2 + c \sim \mathcal{N}(\mu_1 + \mu_2 + c, a^2\sigma_1^2 + b^2\sigma_2^2)$$

2.9 Markov chains

A *Markov chain* is a discrete random process with the property that the next state depends only on the current state. Let X_1, X_2, \dots be a sequence of random variables generated by the Markov process. Then there is a transition matrix $\mathbf{P} = (p_{ij})$, with $p_{ij} = \operatorname{Pr}(X_n = i | X_{n - 1} = j)$, and $\mathbf{p}^{(n)} = \mathbf{P}^n \mathbf{p}^{(0)}$ is the probability distribution for X_n (i.e., $p_i^{(n)} = \operatorname{Pr}(X_n = i)$), where $\mathbf{p}^{(0)}$ is the initial distribution.

Stationary distribution

π is a stationary distribution if $\pi = \pi \mathbf{P}$. If the Markov chain is *irreducible* (it is possible to get to any state from any state), then $\pi_i = \frac{1}{\mathbb{E}(T_i)}$ where $\mathbb{E}(T_i)$ is the expected time between two visits in state i . π_j/π_i is the expected number of visits in state j between two visits in state i .

For a connected, undirected and non-bipartite graph, where the transition probability is uniform among all neighbors, π_i is proportional to node i 's degree.

Ergodicity

A Markov chain is *ergodic* if the asymptotic distribution is independent of the initial distribution. A finite Markov chain is ergodic iff it is irreducible and *aperiodic* (i.e., the gcd of cycle lengths is 1). $\lim_{k \rightarrow \infty} \mathbf{P}^k = \mathbf{1}\pi$.

Absorption

A Markov chain is an A-chain if the states can be partitioned into two sets **A** and **G**, such that all states in **A** are absorbing ($p_{ii} = 1$), and all states in **G** leads to an absorbing state in **A**. The probability for absorption in state $i \in \mathbf{A}$, when the initial state is j , is $a_{ij} = p_{ij} + \sum_{k \in \mathbf{G}} a_{ik} p_{kj}$. The expected time until absorption, when the initial state is i , is $t_i = 1 + \sum_{k \in \mathbf{G}} p_{ki} t_k$.

Data structures (3)

OrderStatisticTree.h

Description: A set (not multiset!) with support for finding the n'th element, and finding the index of an element. To get a map, change null.type.
Time: $\mathcal{O}(\log N)$

```
#include <bits/extc++.h>
using namespace __gnu_pbds;

template<class T>
using Tree = tree<T, null_type, less<T>, rb_tree_tag,
    tree_order_statistics_node_update>;

void example() {
    Tree<int> t, t2; t.insert(8);
    auto it = t.insert(10).first;
    assert(it == t.lower_bound(9));
    assert(t.order_of_key(10) == 1);
    assert(t.order_of_key(11) == 2);
    assert(*t.find_by_order(0) == 8);
    t.join(t2); // assuming T < T2 or T > T2, merge t2 into t
}
```

HashMap.h

Description: Hash map with mostly the same API as unordered_map, but ~3x faster. Uses 1.5x memory. Initial capacity must be a power of 2 (if provided).

```
#include <bits/extc++.h>
// To use most bits rather than just the lowest ones:
struct chash { // large odd number for C
    const uint64_t C = 11(4e18 * acos(0)) | 71;
    ll operator()(ll x) const { return __builtin_bswap64(x*C); }
};
__gnu_pbds::gp_hash_table<ll,int,chash> h({},{},{},{},{1<16});
```

SegmentTree.h

Description: Zero-indexed max-tree. Bounds are inclusive to the left and exclusive to the right. Can be changed by modifying T, f and unit.
Time: $\mathcal{O}(\log N)$

```
struct Tree {
    typedef int T;
    static constexpr T unit = INT_MIN;
    T f(T a, T b) { return max(a, b); } // (any associative fn)
```

```
vector<T> s; int n;
Tree(int n = 0, T def = unit) : s(2*n, def), n(n) {}
void update(int pos, T val) {
    for (s[pos += n] = val; pos /= 2;)
        s[pos] = f(s[pos * 2], s[pos * 2 + 1]);
}
T query(int b, int e) { // query [b, e)
    T ra = unit, rb = unit;
    for (b += n, e += n; b < e; b /= 2, e /= 2) {
        if (b % 2) ra = f(ra, s[b++]);
        if (e % 2) rb = f(s[--e], rb);
    }
    return f(ra, rb);
}
};
```

LazySegmentTree.h

Description: Segment tree with ability to add or set values of large intervals, and compute max of intervals. Can be changed to other things. Use with a bump allocator for better performance, and SmallPtr or implicit indices to save memory.
Usage: Node* tr = new Node(v, 0, sz(v));
Time: $\mathcal{O}(\log N)$.

```
"/various/BumpAllocator.h"
34cef5, 50 lines

const int inf = 1e9;
struct Node {
    Node *l = 0, *r = 0;
    int lo, hi, mset = inf, madd = 0, val = -inf;
    Node(int lo,int hi):lo(lo),hi(hi){ // Large interval of -inf
    Node(vi& v, int lo, int hi) : lo(lo), hi(hi) {
        if (lo + 1 < hi) {
            int mid = lo + (hi - lo)/2;
            l = new Node(v, lo, mid); r = new Node(v, mid, hi);
            val = max(l->val, r->val);
        }
        else val = v[lo];
    }
    int query(int L, int R) {
        if (R <= lo || hi <= L) return -inf;
        if (L <= lo && hi <= R) return val;
        push();
        return max(l->query(L, R), r->query(L, R));
    }
    void set(int L, int R, int x) {
        if (R <= lo || hi <= L) return;
        if (L <= lo && hi <= R) mset = val = x, madd = 0;
        else {
            push(), l->set(L, R, x), r->set(L, R, x);
            val = max(l->val, r->val);
        }
    }
    void add(int L, int R, int x) {
        if (R <= lo || hi <= L) return;
        if (L <= lo && hi <= R) {
            if (mset != inf) mset += x;
            else madd += x;
            val += x;
        }
        else {
            push(), l->add(L, R, x), r->add(L, R, x);
            val = max(l->val, r->val);
        }
    }
    void push() {
        if (!l) {
            int mid = lo + (hi - lo)/2;
            l = new Node(lo, mid); r = new Node(mid, hi);
        }
        if (mset != inf)
            l->set(lo,hi,mset), r->set(lo,hi,mset), mset = inf;
        else if (madd)
            l->add(lo,hi,madd), r->add(lo,hi,madd), madd = 0;
    }
}
};
```

UnionFind.h

Description: Disjoint-set data structure.
Time: $\mathcal{O}(\alpha(N))$

```
struct UF {
    vi e;
    UF(int n) : e(n, -1) {}
    bool sameSet(int a, int b) { return find(a) == find(b); }
    int size(int x) { return -e[find(x)]; }
    int find(int x) { return e[x] < 0 ? x : e[x] = find(e[x]); }
    bool join(int a, int b) {
        a = find(a), b = find(b);
        if (a == b) return false;
        if (e[a] > e[b]) swap(a, b);
        e[a] += e[b]; e[b] = a;
        return true;
    }
};
```

UnionFindRollback.h

Description: Disjoint-set data structure with undo. If undo is not needed, skip st.time() and rollback().
Usage: int t = uf.time(); ...; uf.rollback(t);
Time: $\mathcal{O}(\log(N))$

```
struct RollbackUF {
    vi e; vector<pii> st;
    RollbackUF(int n) : e(n, -1) {}
    int size(int x) { return -e[find(x)]; }
    int find(int x) { return e[x] < 0 ? x : find(e[x]); }
    int time() { return sz(st); }
    void rollback(int t) {
        for (int i = time(); i --> t;)
            e[st[i].first] = st[i].second;
            st.resize(t);
    }
    bool join(int a, int b) {
        a = find(a), b = find(b);
        if (a == b) return false;
        if (e[a] > e[b]) swap(a, b);
        st.push_back({a, e[a]});
        st.push_back({b, e[b]});
        e[a] += e[b]; e[b] = a;
        return true;
    }
};
```

SubMatrix.h

Description: Calculate submatrix sums quickly, given upper-left and lower-right corners (half-open).
Usage: SubMatrix<int> m(matrix);
m.sum(0, 0, 2, 2); // top left 4 elements
Time: $\mathcal{O}(N^2 + Q)$

```
template<class T>
struct SubMatrix {
    vector<vector<T>>> p;
    SubMatrix(vector<vector<T>>& v) {
        int R = sz(v), C = sz(v[0]);
        p.assign(R+1, vector<T>(C+1));
        rep(r,0,R) rep(c,0,C)
            p[r+1][c+1] = v[r][c] + p[r][c+1] + p[r+1][c] - p[r][c];
    }
    T sum(int u, int l, int d, int r) {
        return p[d][r] - p[d][l] - p[u][r] + p[u][l];
    }
};
```

Matrix.h

Description: Basic operations on square matrices.
Usage: Matrix<int, 3> A;
A.d = {{{{1,2,3}}, {{4,5,6}}, {{7,8,9}}}};
array<int, 3> vec = {1,2,3};
vec = (A^N) * vec;

```
template<class T, int N> struct Matrix {
    typedef Matrix M;
    array<array<T, N>, N> d{};
    M operator*(const M& m) const {
        M a;
        rep(i,0,N) rep(j,0,N)
            rep(k,0,N) a.d[i][k] += d[i][j] * m.d[j][k];
        return a;
    }
};
```

```

}
array<T, N> operator*(const array<T, N>& vec) const {
    array<T, N> ret{};
    rep(i,0,N) rep(j,0,N) ret[i] += d[i][j] * vec[j];
    return ret;
}
M operator^(ll p) const {
    assert(p >= 0);
    M a, b(*this);
    rep(i,0,N) a.d[i][i] = 1;
    while (p) {
        if (p&1) a = a*b;
        b = b*b;
        p >>= 1;
    }
    return a;
}
};
```

LineContainer.h

Description: Container where you can add lines of the form $kx+m$, and query maximum values at points x . Useful for dynamic programming (“convex hull trick”).
Time: $\mathcal{O}(\log N)$

```

struct Line {
    mutable ll k, m, p;
    bool operator<(const Line& o) const { return k < o.k; }
    bool operator<(ll x) const { return p < x; }
};

struct LineContainer : multiset<Line, less<>> {
    // (for doubles, use inf = 1/.0, div(a,b) = a/b)
    static const ll inf = LLONG_MAX;
    ll div(ll a, ll b) { // floored division
        return a / b - ((a ^ b) < 0 && a % b); }
    bool isect(iterator x, iterator y) {
        if (y == end()) return x->p = inf, 0;
        if (x->k == y->k) x->p = x->m > y->m ? inf : -inf;
        else x->p = div(y->m - x->m, x->k - y->k);
        return x->p >= y->p;
    }
    void add(ll k, ll m) {
        auto z = insert({k, m, 0}), y = z++, x = y;
        while (isect(y, z)) z = erase(z);
        if (x != begin() && isect(--x, y)) isect(x, y = erase(y));
        while ((y = x) != begin() && (--x)->p >= y->p)
            isect(x, erase(y));
    }
    ll query(ll x) {
        assert(!empty());
        auto l = *lower_bound(x);
        return l.k * x + l.m;
    }
};
```

Treap.h

Description: A short self-balancing tree. It acts as a sequential container with log-time splits/joins, and is easy to augment with additional data.
Time: $\mathcal{O}(\log N)$

```

struct Node {
    Node *l = 0, *r = 0;
    int val, y, c = 1;
    Node(int val) : val(val), y(rand()) {}
    void recalc();
};

int cnt(Node* n) { return n ? n->c : 0; }
void Node::recalc() { c = cnt(l) + cnt(r) + 1; }

template<class F> void each(Node* n, F f) {
    if (n) { each(n->l, f); f(n->val); each(n->r, f); }
}

pair<Node*, Node*> split(Node* n, int k) {
    if (!n) return {};
    if (cnt(n->l) >= k) { // "n->val >= k" for lower_bound(k)
        auto [L,R] = split(n->l, k);
        n->l = R;
```

```

        n->recalc();
        return {L, n};
    } else {
        auto [L,R] = split(n->r, k - cnt(n->l) - 1); // and just "k"
        n->r = L;
        n->recalc();
        return {n, R};
    }
}

Node* merge(Node* l, Node* r) {
    if (!l) return r;
    if (!r) return l;
    if (l->y > r->y) {
        l->r = merge(l->r, r);
        return l->recalc(), l;
    } else {
        r->l = merge(l, r->l);
        return r->recalc(), r;
    }
}

Node* ins(Node* t, Node* n, int pos) {
    auto [l,r] = split(t, pos);
    return merge(merge(l, n), r);
}
```

```

// Example application: move the range [l, r) to index k
void move(Node&& t, int l, int r, int k) {
    Node *a, *b, *c;
    tie(a,b) = split(t, l); tie(b,c) = split(b, r - l);
    if (k <= l) t = merge(ins(a, b, k), c);
    else t = merge(a, ins(c, b, k - r));
}
```

FenwickTree.h

Description: Computes partial sums $a[0] + a[1] + \dots + a[pos - 1]$, and updates single elements $a[i]$, taking the difference between the old and new value.
Time: Both operations are $\mathcal{O}(\log N)$.

```

struct FT {
    vector<ll> s;
    FT(int n) : s(n) {}
    void update(int pos, ll dif) { // a[pos] += dif
        for (; pos < sz(s); pos |= pos + 1) s[pos] += dif;
    }
    ll query(int pos) { // sum of values in [0, pos)
        ll res = 0;
        for (; pos > 0; pos &= pos - 1) res += s[pos-1];
        return res;
    }
    int lower_bound(ll sum) { // min pos st sum of [0, pos] >= sum
        // Returns n if no sum is >= sum, or -1 if empty sum is.
        if (sum <= 0) return -1;
        int pos = 0;
        for (int pw = 1 << 25; pw; pw >= 1) {
            if (pos + pw <= sz(s) && s[pos + pw-1] < sum)
                pos += pw, sum -= s[pos-1];
        }
        return pos;
    }
};
```

FenwickTree2d.h

Description: Computes sums $a[i,j]$ for all $i < I, j < J$, and increases single elements $a[i,j]$. Requires that the elements to be updated are known in advance (call fake-Update() before init()).
Time: $\mathcal{O}(\log^2 N)$. (Use persistent segment trees for $\mathcal{O}(\log N)$.)

```

"FenwickTree.h"
157f07, 22 lines

struct FT2 {
    vector<vi> ys; vector<FT> ft;
    FT2(int limx) : ys(limx) {}
    void fakeUpdate(int x, int y) {
        for (; x < sz(ys); x |= x + 1) ys[x].push_back(y);
    }
    void init() {
        for (vi& v : ys) sort(all(v)), ft.emplace_back(sz(v));
    }
}
```

```

int ind(int x, int y) {
    return (int)(lower_bound(all(ys[x]), y) - ys[x].begin()); }
void update(int x, int y, ll dif) {
    for (; x < sz(ys); x |= x + 1)
        ft[x].update(ind(x, y), dif);
}
ll query(int x, int y) {
    ll sum = 0;
    for (; x; x &= x - 1)
        sum += ft[x-1].query(ind(x-1, y));
    return sum;
}
};
```

RMQ.h

Description: Range Minimum Queries on an array. Returns $\min(V[a], V[a + 1], \dots V[b - 1])$ in constant time.
Usage: RMQ rmq(values);
rmq.query(inclusive, exclusive);
Time: $\mathcal{O}(|V| \log |V| + Q)$

```

510c32, 16 lines

template<class T>
struct RMQ {
    vector<vector<T>> jmp;
    RMQ(const vector<T>& V) : jmp(1, V) {
        for (int pw = 1, k = 1; pw * 2 <= sz(V); pw *= 2, ++k) {
            jmp.emplace_back(sz(V) - pw * 2 + 1);
            rep(j,0,sz(jmp[k]))
                jmp[k][j] = min(jmp[k - 1][j], jmp[k - 1][j + pw]);
        }
    }
    T query(int a, int b) {
        assert(a < b); // or return inf if a == b
        int dep = 31 - __builtin_clz(b - a);
        return min(jmp[dep][a], jmp[dep][b - (1 << dep)]);
    }
};
```

MoQueries.h

Description: Answer interval or tree path queries by finding an approximate TSP through the queries, and moving from one query to the next by adding/removing points at the ends. If values are on tree edges, change step to add/remove the edge (a, c) and remove the initial add call (but keep in).
Time: $\mathcal{O}(N\sqrt{Q})$

```

a12ef4, 49 lines

void add(int ind, int end) { ... } // add a[ind] (end = 0 or 1)
void del(int ind, int end) { ... } // remove a[ind]
int calc() { ... } // compute current answer

vi mo(vector<pii>& Q) {
    int L = 0, R = 0, blk = 350; // ~N/sqrt(Q)
    vi s(sz(Q)), res = s;
    #define K(x) pii(x.first/blk, x.second ^ -(x.first/blk & 1))
    iota(all(s), 0);
    sort(all(s), [&](int s, int t){ return K(Q[s]) < K(Q[t]); });
    for (int qi : s) {
        pii q = Q[qi];
        while (L > q.first) add(--L, 0);
        while (R < q.second) add(R++, 1);
        while (L < q.first) del(L++, 0);
        while (R > q.second) del(--R, 1);
        res[qi] = calc();
    }
    return res;
}
```

```

vi moTree(vector<array<int, 2>> Q, vector<vi>& ed, int root=0){
    int N = sz(ed), pos[2] = {}, blk = 350; // ~N/sqrt(Q)
    vi s(sz(Q)), res = s, I(N), L(N), R(N), in(N), par(N);
    add(0, 0), in[0] = 1;
    auto dfs = [&](int x, int p, int dep, auto& f) -> void {
        par[x] = p;
        L[x] = N;
        if (dep) I[x] = N++;
        for (int y : ed[x]) if (y != p) f(y, x, !dep, f);
        if (!dep) I[x] = N++;
        R[x] = N;
    };
    dfs(root, -1, 0, dfs);
```

```
#define K(x) pii(I[x[0]] / blk, I[x[1]] ^ -(I[x[0]] / blk & 1))
iota(all(s), 0);
sort(all(s), [&](int s, int t){ return K(Q[s]) < K(Q[t]); });
for (int qi : s) rep(end,0,2) {
    int &a = pos[end], b = Q[qi][end], i = 0;
#define step(c) { if (in[c]) { del(a, end); in[a] = 0; } \
                else { add(c, end); in[c] = 1; } a = c; }
    while (!(L[b] <= L[a] && R[a] <= R[b]))
        I[i++] = b, b = par[b];
    while (a != b) step(par[a]);
    while (i--) step(I[i]);
    if (end) res[qi] = calc();
}
return res;
}
```

WaveletTree.h

Description: Usage is `int a[n+1]`; `tr.init(a+1, a+n+1, x, y)`; where `x, y` are lower and upper bounds of `a[i]` respectively. Do not use 0-based arrays or vectors.
Time: $\mathcal{O}(n \log n)$.

f2187d, 83 lines

```
struct WaveletTree {
    int lo, hi;
    WaveletTree *l, *r;
    int *b, *c, bsz, csz; // c holds the prefix sum of elements

    WaveletTree() {
        lo = 1;
        hi = 0;
        bsz = 0;
        csz = 0, l = NULL;
        r = NULL;
    }

    void init(int *from, int *to, int x, int y) {
        lo = x, hi = y;
        if(from >= to) return;
        int mid = (lo + hi) >> 1;
        auto f = [mid](int x) {
            return x <= mid;
        };
        b = (int*)malloc((to - from + 2) * sizeof(int));
        bsz = 0;
        b[bsz++] = 0;
        c = (int*)malloc((to - from + 2) * sizeof(int));
        csz = 0;
        c[csz++] = 0;
        for(auto it = from; it != to; it++) {
            b[bsz] = (b[bsz - 1] + f(*it));
            c[csz] = (c[csz - 1] + (*it));
            bsz++;
            csz++;
        }
        if(hi == lo) return;
        auto pivot = stable_partition(from, to, f);
        l = new WaveletTree();
        l->init(from, pivot, lo, mid);
        r = new WaveletTree();
        r->init(pivot, to, mid + 1, hi);
    }
    //kth smallest element in [l, r]
    //for array [1,2,1,3,5] 2nd smallest is 1 and 3rd smallest is 2
    int kth(int l, int r, int k) {
        if(l > r) return 0;
        if(lo == hi) return lo;
        int inLeft = b[r] - b[l - 1], lb = b[l - 1], rb = b[r];
        if(k <= inLeft) return this->l->kth(lb + 1, rb, k);
        return this->r->kth(l - lb, r - rb, k - inLeft);
    }
    //count of numbers in [l, r] Less than or equal to k
    int LTE(int l, int r, int k) {
        if(l > r || k < lo) return 0;
        if(hi <= k) return r - l + 1;
        int lb = b[l - 1], rb = b[r];
        return this->l->LTE(lb + 1, rb, k) + this->r->LTE(l - lb, r - rb, k);
    }
    //count of numbers in [l, r] equal to k
    int count(int l, int r, int k) {
```

```
        if(l > r || k < lo || k > hi) return 0;
        if(lo == hi) return r - l + 1;
        int lb = b[l - 1], rb = b[r];
        int mid = (lo + hi) >> 1;
        if(k <= mid) return this->l->count(lb + 1, rb, k);
        return this->r->count(l - lb, r - rb, k);
    }
    //sum of numbers in [l, r] less than or equal to k
    int sum(int l, int r, int k) {
        if(l > r or k < lo) return 0;
        if(hi <= k) return c[r] - c[l - 1];
        int lb = b[l - 1], rb = b[r];
        return this->l->sum(lb + 1, rb, k) + this->r->sum(l - lb, r - rb, k);
    }
    //count max element in [l, r] stricly smaller than k
    int upper_bound(int l, int r, int k) {
        if(l > r) return -1;
        int uwu = LTE(l, r, k - 1);
        if(uwu == 0) return -1;
        return kth(l, r, uwu);
    }
}
~WaveletTree() {
    delete l;
    delete r;
}
```

};

Numerical (4)

4.1 Polynomials and recurrences

Polynomial.h

c9b7b0, 17 lines

```
struct Poly {
    vector<double> a;
    double operator()(double x) const {
        double val = 0;
        for (int i = sz(a); i--;) (val += x) += a[i];
        return val;
    }
    void diff() {
        rep(i,1,sz(a)) a[i-1] = i*a[i];
        a.pop_back();
    }
    void divroot(double x0) {
        double b = a.back(), c; a.back() = 0;
        for(int i=sz(a)-1; i--;) c = a[i], a[i] = a[i+1]*x0+b, b=c;
        a.pop_back();
    }
};
```

PolyRoots.h

Description: Finds the real roots to a polynomial.
Usage: `polyRoots({{2,-3,1}},-1e9,1e9)` // solve $x^2-3x+2 = 0$
Time: $\mathcal{O}(n^2 \log(1/\epsilon))$

"Polynomial.h" b00bfe, 23 lines

```
vector<double> polyRoots(Poly p, double xmin, double xmax) {
    if (sz(p.a) == 2) { return {-p.a[0]/p.a[1]}; }
    vector<double> ret;
    Poly der = p;
    der.diff();
    auto dr = polyRoots(der, xmin, xmax);
    dr.push_back(xmin-1);
    dr.push_back(xmax+1);
    sort(all(dr));
    rep(i,0,sz(dr)-1) {
        double l = dr[i], h = dr[i+1];
        bool sign = p(l) > 0;
        if (sign ^ (p(h) > 0)) {
            rep(it,0,60) { // while (h - l > 1e-8)
                double m = (l + h) / 2, f = p(m);
                if ((f <= 0) ^ sign) l = m;
                else h = m;
            }
            ret.push_back((l + h) / 2);
        }
```

```
    }
}
return ret;
}
```

PolyInterpolate.h

Description: Given n points $(x[i], y[i])$, computes an $n-1$ -degree polynomial p that passes through them: $p(x) = a[0] * x^0 + \dots + a[n-1] * x^{n-1}$. For numerical precision, pick $x[k] = c * \cos(k/(n-1) * \pi), k = 0 \dots n-1$.
Time: $\mathcal{O}(n^2)$

08bf48, 13 lines

```
typedef vector<double> vd;
vd interpolate(vd x, vd y, int n) {
    vd res(n), temp(n);
    rep(k,0,n-1) rep(i,k+1,n)
        y[i] = (y[i] - y[k]) / (x[i] - x[k]);
    double last = 0; temp[0] = 1;
    rep(k,0,n) rep(i,0,n) {
        res[i] += y[k] * temp[i];
        swap(last, temp[i]);
        temp[i] -= last * x[k];
    }
    return res;
}
```

BerlekampMassey.h

Description: Recovers any n -order linear recurrence relation from the first $2n$ terms of the recurrence. Useful for guessing linear recurrences after brute-forcing the first terms. Should work on any field, but numerical stability for floats is not guaranteed. Output will have size $\leq n$.
Usage: `berlekampMassey({0, 1, 1, 3, 5, 11})` // {1, 2}

Time: $\mathcal{O}(N^2)$

"./number-theory/ModPow.h" 96548b, 20 lines

```
vector<ll> berlekampMassey(vector<ll> s) {
    int n = sz(s), L = 0, m = 0;
    vector<ll> C(n), B(n), T;
    C[0] = B[0] = 1;

    ll b = 1;
    rep(i,0,n) { ++m;
        ll d = s[i] % mod;
        rep(j,1,L+1) d = (d + C[j] * s[i - j]) % mod;
        if (!d) continue;
        T = C; ll coef = d * modpow(b, mod-2) % mod;
        rep(j,m,n) C[j] = (C[j] - coef * B[j - m]) % mod;
        if (2 * L > i) continue;
        L = i + 1 - L; B = T; b = d; m = 0;
    }

    C.resize(L + 1); C.erase(C.begin());
    for (ll& x : C) x = (mod - x) % mod;
    return C;
}
```

LinearRecurrence.h

Description: Generates the k 'th term of an n -order linear recurrence $S[i] = \sum_j S[i-j-1]tr[j]$, given $S[0 \dots \geq n-1]$ and $tr[0 \dots n-1]$. Faster than matrix multiplication. Useful together with Berlekamp-Massey.
Usage: `linearRec({0, 1}, {1, 1}, k)` // k 'th Fibonacci number
Time: $\mathcal{O}(n^2 \log k)$

f4e444, 26 lines

```
typedef vector<ll> Poly;
ll linearRec(Poly S, Poly tr, ll k) {
    int n = sz(tr);

    auto combine = [&](Poly a, Poly b) {
        Poly res(n * 2 + 1);
        rep(i,0,n+1) rep(j,0,n+1)
            res[i + j] = (res[i + j] + a[i] * b[j]) % mod;
        for (int i = 2 * n; i > n; --i) rep(j,0,n)
            res[i - 1 - j] = (res[i - 1 - j] + res[i] * tr[j]) % mod;
        res.resize(n + 1);
        return res;
    };

    Poly pol(n + 1), e(pol);
```

```
pol[0] = e[1] = 1;

for (++k; k; k /= 2) {
    if (k % 2) pol = combine(pol, e);
    e = combine(e, e);
}

ll res = 0;
rep(i,0,n) res = (res + pol[i + 1] * S[i]) % mod;
return res;
}
```

4.2 Optimization

GoldenSectionSearch.h

Description: Finds the argument minimizing the function f in the interval $[a,b]$ assuming f is unimodal on the interval, i.e. has only one local minimum and no local maximum. The maximum error in the result is ϵ *eps*. Works equally well for maximization with a small change in the code. See TernarySearch.h in the Various chapter for a discrete version.

Usage: double func(double x) { return 4+x.3*x*x; }
double xmin = gss(-1000,1000,func);
Time: $\mathcal{O}(\log((b-a)/\epsilon))$

31d45b, 14 lines

```
double gss(double a, double b, double (*f)(double)) {
    double r = (sqrt(5)-1)/2, eps = 1e-7;
    double x1 = b - r*(b-a), x2 = a + r*(b-a);
    double f1 = f(x1), f2 = f(x2);
    while (b-a > eps)
        if (f1 < f2) { //change to > to find maximum
            b = x2; x2 = x1; f2 = f1;
            x1 = b - r*(b-a); f1 = f(x1);
        } else {
            a = x1; x1 = x2; f1 = f2;
            x2 = a + r*(b-a); f2 = f(x2);
        }
    return a;
}
```

HillClimbing.h

Description: Poor man's optimization for unimodal functions.

Seeef, 14 lines

typedef array<double, 2> P;

```
template<class F> pair<double, P> hillClimb(P start, F f) {
    pair<double, P> cur(f(start), start);
    for (double jmp = 1e9; jmp > 1e-20; jmp /= 2) {
        rep(j,0,100) rep(dx,-1,2) rep(dy,-1,2) {
            P p = cur.second;
            p[0] += dx*jmp;
            p[1] += dy*jmp;
            cur = min(cur, make_pair(f(p), p));
        }
    }
    return cur;
}
```

Integrate.h

Description: Simple integration of a function over an interval using Simpson's rule. The error should be proportional to h^4 , although in practice you will want to verify that the result is stable to desired precision when epsilon changes.

4756fc, 7 lines

```
template<class F>
double quad(double a, double b, F f, const int n = 1000) {
    double h = (b - a) / 2 / n, v = f(a) + f(b);
    rep(i,1,n*2)
        v += f(a + i*h) * (i&1 ? 4 : 2);
    return v * h / 3;
}
```

IntegrateAdaptive.h

Description: Fast integration using an adaptive Simpson's rule.

Usage: double sphereVolume = quad(-1, 1, [](double x) {
return quad(-1, 1, [&](double y) {
return quad(-1, 1, [&](double z) {
return x*x + y*y + z*z < 1; }));});});

92dd79, 15 lines

typedef double d;
#define S(a,b) (f(a) + 4*f((a+b) / 2) + f(b)) * (b-a) / 6

```
template <class F>
d rec(F& f, d a, d b, d eps, d S) {
    d c = (a + b) / 2;
    d S1 = S(a, c), S2 = S(c, b), T = S1 + S2;
    if (abs(T - S) <= 15 * eps || b - a < 1e-10)
        return T + (T - S) / 15;
    return rec(f, a, c, eps / 2, S1) + rec(f, c, b, eps / 2, S2);
}

template<class F>
d quad(d a, d b, F f, d eps = 1e-8) {
    return rec(f, a, b, eps, S(a, b));
}
```

Simplex.h

Description: Solves a general linear maximization problem: maximize $c^T x$ subject to $Ax \leq b, x \geq 0$. Returns -inf if there is no solution, inf if there are arbitrarily good solutions, or the maximum value of $c^T x$ otherwise. The input vector is set to an optimal x (or in the unbounded case, an arbitrary solution fulfilling the constraints). Numerical stability is not guaranteed. For better performance, define variables such that $x = 0$ is viable.

Usage: vvd A = {{1,-1}, {-1,1}, {-1,-2}};

v d b = {1,1,-4}, c = {-1,-1}, x;

T val = LPSolver(A, b, c).solve(x);

Time: $\mathcal{O}(NM * \#pivots)$, where a pivot may be e.g. an edge relaxation. $\mathcal{O}(2^n)$ in the general case.

aa8530, 68 lines

typedef double T; // long double, Rational, double + mod<P>...

typedef vector<T> vd;

typedef vector<vd> vvd;

const T eps = 1e-8, inf = 1/.0;

#define MP make_pair

#define ltj(X) if(s == -1 || MP(X[j],N[j]) < MP(X[s],N[s])) s=j

struct LPSolver {

int m, n;

vi N, B;

vvd D;

LPSolver(const vvd& A, const vd& b, const vd& c) :
m(sz(b)), n(sz(c)), N(n+1), B(m), D(m+2, vd(n+2)) {
rep(i,0,m) rep(j,0,n) D[i][j] = A[i][j];
rep(i,0,m) { B[i] = n+i; D[i][n] = -1; D[i][n+1] = b[i];}
rep(j,0,n) { N[j] = j; D[m][j] = -c[j]; }
N[n] = -1; D[m+1][n] = 1;

void pivot(int r, int s) {
T *a = D[r].data(), inv = 1 / a[s];
rep(i,0,m+2) if (i != r && abs(D[i][s]) > eps) {
T *b = D[i].data(), inv2 = b[s] * inv;
rep(j,0,n+2) b[j] -= a[j] * inv2;
b[s] = a[s] * inv2;
}
rep(j,0,n+2) if (j != s) D[r][j] *= inv;
rep(i,0,m+2) if (i != r) D[i][s] *= -inv;
D[r][s] = inv;
swap(B[r], N[s]);
}

bool simplex(int phase) {
int x = m + phase - 1;
for (;;) {
int s = -1;
rep(j,0,n+1) if (N[j] != -phase) ltj(D[x]);
if (D[x][s] >= -eps) return true;
int r = -1;
rep(i,0,m) {
if (D[i][s] <= eps) continue;
if (r == -1 || MP(D[i][n+1] / D[i][s], B[i])
< MP(D[r][n+1] / D[r][s], B[r])) r = i;
}
if (r == -1) return false;
pivot(r, s);
}
}

T solve(vd &x) {

```
int r = 0;
rep(i,1,m) if (D[i][n+1] < D[r][n+1]) r = i;
if (D[r][n+1] < -eps) {
    pivot(r, n);
    if (!simplex(2) || D[m+1][n+1] < -eps) return -inf;
    rep(i,0,m) if (B[i] == -1) {
        int s = 0;
        rep(j,1,n+1) ltj(D[i]);
        pivot(i, s);
    }
}
bool ok = simplex(1); x = vd(n);
rep(i,0,m) if (B[i] < n) x[B[i]] = D[i][n+1];
return ok ? D[m][n+1] : inf;
}
};
```

4.3 Matrices

Determinant.h

Description: Calculates determinant of a matrix. Destroys the matrix.

Time: $\mathcal{O}(N^3)$

bd5cec, 15 lines

```
double det(vector<vector<double>>& a) {
    int n = sz(a); double res = 1;
    rep(i,0,n) {
        int b = i;
        rep(j,i+1,n) if (fabs(a[j][i]) > fabs(a[b][i])) b = j;
        if (i != b) swap(a[i], a[b]), res *= -1;
        res *= a[i][i];
        if (res == 0) return 0;
        rep(j,i+1,n) {
            double v = a[j][i] / a[i][i];
            if (v != 0) rep(k,i+1,n) a[j][k] -= v * a[i][k];
        }
    }
    return res;
}
```

IntDeterminant.h

Description: Calculates determinant using modular arithmetics. Modulos can also be removed to get a pure-integer version.

Time: $\mathcal{O}(N^3)$

3313dc, 18 lines

```
const ll mod = 12345;
ll det(vector<vector<ll>>& a) {
    int n = sz(a); ll ans = 1;
    rep(i,0,n) {
        rep(j,i+1,n) {
            while (a[j][i] != 0) { // gcd step
                ll t = a[i][i] / a[j][i];
                if (t) rep(k,i,n)
                    a[i][k] = (a[i][k] - a[j][k] * t) % mod;
                swap(a[i], a[j]);
                ans *= -1;
            }
        }
        ans = ans * a[i][i] % mod;
        if (!ans) return 0;
    }
    return (ans + mod) % mod;
}
```

SolveLinear.h

Description: Solves $A * x = b$. If there are multiple solutions, an arbitrary one is returned. Returns rank, or -1 if no solutions. Data in A and b is lost.

Time: $\mathcal{O}(n^2 m)$

44c9ab, 38 lines

typedef vector<double> vd;
const double eps = 1e-12;

int solveLinear(vector<vd>& A, vd& b, vd& x) {
int n = sz(A), m = sz(x), rank = 0, br, bc;
if (n) assert(sz(A[0]) == m);
vi col(m); iota(all(col), 0);

rep(i,0,n) {
double v, bv = 0;

```
rep(r,i,n) rep(c,i,m)
    if ((v = fabs(A[r][c])) > bv)
        br = r, bc = c, bv = v;
if (bv <= eps) {
    rep(j,i,n) if (fabs(b[j]) > eps) return -1;
    break;
}
swap(A[i], A[br]);
swap(b[i], b[br]);
swap(col[i], col[bc]);
rep(j,0,n) swap(A[j][i], A[j][bc]);
bv = 1/A[i][i];
rep(j,i+1,n) {
    double fac = A[j][i] * bv;
    b[j] -= fac * b[i];
    rep(k,i+1,m) A[j][k] -= fac*A[i][k];
}
rank++;
}

x.assign(m, 0);
for (int i = rank; i--;) {
    b[i] /= A[i][i];
    x[col[i]] = b[i];
    rep(j,0,i) b[j] -= A[j][i] * b[i];
}
return rank; // (multiple solutions if rank < m)
}
```

SolveLinear2.h

Description: To get all uniuely determined values of x back from SolveLinear, make the following changes:

"SolveLinear.h"	08e495, 7 lines
-----------------	-----------------

```
rep(j,0,n) if (j != i) // instead of rep(j,i+1,n)
// ... then at the end:
x.assign(m, undefined);
rep(i,0,rank) {
    rep(j,rank,m) if (fabs(A[i][j]) > eps) goto fail;
    x[col[i]] = b[i] / A[i][i];
fail:; }
```

SolveLinearBinary.h

Description: Solves $Ax = b$ over \mathbb{F}_2 . If there are multiple solutions, one is returned arbitrarily. Returns rank, or -1 if no solutions. Destroys A and b .

Time: $\mathcal{O}\left(n^2m\right)$

typedef bitset<1000> bs;	fa2d7a, 34 lines
--------------------------	------------------

```
int solveLinear(vector<bs>& A, vi& b, bs& x, int m) {
    int n = sz(A), rank = 0, br;
    assert(m <= sz(x));
    vi col(m); iota(all(col), 0);
    rep(i,0,n) {
        for (br=i; br<n; ++br) if (A[br].any()) break;
        if (br == n) {
            rep(j,i,n) if(b[j]) return -1;
            break;
        }
        int bc = (int)A[br]._Find_next(i-1);
        swap(A[i], A[br]);
        swap(b[i], b[br]);
        swap(col[i], col[bc]);
        rep(j,0,n) if (A[j][i] != A[j][bc]) {
            A[j].flip(i); A[j].flip(bc);
        }
        rep(j,i+1,n) if (A[j][i]) {
            b[j] ^= b[i];
            A[j] ^= A[i];
        }
        rank++;
    }

    x = bs();
    for (int i = rank; i--;) {
        if (!b[i]) continue;
        x[col[i]] = 1;
        rep(j,0,i) b[j] ^= A[j][i];
    }
}
```

```
return rank; // (multiple solutions if rank < m)
}
```

MatrixInverse.h

Description: Invert matrix A . Returns rank; result is stored in A unless singular (rank < n). Can easily be extended to prime moduli; for prime powers, repeatedly set $A^{-1} = A^{-1}(2I - AA^{-1}) \pmod{p^k}$ where A^{-1} starts as the inverse of A mod p , and k is doubled in each step.

Time: $\mathcal{O}\left(n^3\right)$

int matInv(vector<vector<double>>& A) { int n = sz(A); vi col(n); vector<vector<double>> tmp(n, vector<double>(n)); rep(i,0,n) tmp[i][i] = 1, col[i] = i; rep(i,0,n) { int r = i, c = i; rep(j,i,n) rep(k,i,n) if (fabs(A[j][k]) > fabs(A[r][c])) r = j, c = k; if (fabs(A[r][c]) < 1e-12) return i; A[i].swap(A[r]); tmp[i].swap(tmp[r]); rep(j,0,n) swap(A[j][i], A[j][c]), swap(tmp[j][i], tmp[j][c]); swap(col[i], col[c]); double v = A[i][i]; rep(j,i+1,n) { double f = A[j][i] / v; A[j][i] = 0; rep(k,i+1,n) A[j][k] -= f*A[i][k]; rep(k,0,n) tmp[j][k] -= f*tmp[i][k]; } rep(j,i+1,n) A[i][j] /= v; rep(j,0,n) tmp[i][j] /= v; A[i][i] = 1; } for (int i = n-1; i > 0; --i) rep(j,0,i) { double v = A[j][i]; rep(k,0,n) tmp[j][k] -= v*tmp[i][k]; } rep(i,0,n) rep(j,0,n) A[col[i]][col[j]] = tmp[i][j]; return n; }
--

MatrixInverse-mod.h

Description: Invert matrix A modulo a prime. Returns rank; result is stored in A unless singular (rank < n). For prime powers, repeatedly set $A^{-1} = A^{-1}(2I - AA^{-1}) \pmod{p^k}$ where A^{-1} starts as the inverse of A mod p , and k is doubled in each step.

Time: $\mathcal{O}\left(n^3\right)$

"../number-theory/ModPow.h"	0b7b13, 37 lines
-----------------------------	------------------

```
int matInv(vector<vector<ll>>& A) {
    int n = sz(A); vi col(n);
    vector<vector<ll>> tmp(n, vector<ll>(n));
    rep(i,0,n) tmp[i][i] = 1, col[i] = i;

    rep(i,0,n) {
        int r = i, c = i;
        rep(j,i,n) rep(k,i,n) if (A[j][k]) {
            r = j; c = k; goto found;
        }
        return i;
    found:
        A[i].swap(A[r]); tmp[i].swap(tmp[r]);
        rep(j,0,n)
            swap(A[j][i], A[j][c]), swap(tmp[j][i], tmp[j][c]);
        swap(col[i], col[c]);
        ll v = modpow(A[i][i], mod - 2);
        rep(j,i+1,n) {
            ll f = A[j][i] * v % mod;
            A[j][i] = 0;
            rep(k,i+1,n) A[j][k] = (A[j][k] - f*A[i][k]) % mod;
            rep(k,0,n) tmp[j][k] = (tmp[j][k] - f*tmp[i][k]) % mod;
        }
        rep(j,i+1,n) A[i][j] = A[i][j] * v % mod;
    }
}
```

```
rep(j,0,n) tmp[i][j] = tmp[i][j] * v % mod;
A[i][i] = 1;
}

for (int i = n-1; i > 0; --i) rep(j,0,i) {
    ll v = A[j][i];
    rep(k,0,n) tmp[j][k] = (tmp[j][k] - v*tmp[i][k]) % mod;
}

rep(i,0,n) rep(j,0,n)
    A[col[i]][col[j]] = tmp[i][j] % mod + (tmp[i][j] < 0)*mod;
return n;
}
```

Tridiagonal.h

Description: $x = \text{tridiagonal}(d, p, q, b)$ solves the equation system

$$\begin{pmatrix} b_0 \\ b_1 \\ b_2 \\ b_3 \\ \vdots \\ b_{n-1} \end{pmatrix} = \begin{pmatrix} d_0 & p_0 & 0 & 0 & \cdots & 0 \\ q_0 & d_1 & p_1 & 0 & \cdots & 0 \\ 0 & q_1 & d_2 & p_2 & \cdots & 0 \\ \vdots & \vdots & \ddots & \ddots & \ddots & \vdots \\ 0 & 0 & \cdots & q_{n-3} & d_{n-2} & p_{n-2} \\ 0 & 0 & \cdots & 0 & q_{n-2} & d_{n-1} \end{pmatrix} \begin{pmatrix} x_0 \\ x_1 \\ x_2 \\ x_3 \\ \vdots \\ x_{n-1} \end{pmatrix}.$$

This is useful for solving problems on the type

$$a_i = b_i a_{i-1} + c_i a_{i+1} + d_i, 1 \leq i \leq n,$$

where a_0, a_{n+1}, b_i, c_i and d_i are known. a can then be obtained from

$$\{a_i\} = \text{tridiagonal}(\{1, -1, -1, \dots, -1, 1\}, \{0, c_1, c_2, \dots, c_n\}, \{b_1, b_2, \dots, b_n, 0\}, \{a_0, d_1, d_2, \dots, d_n, a_{n+1}\}).$$

Fails if the solution is not unique. If $|d_i| > |p_i| + |q_{i-1}|$ for all i , or $|d_i| > |p_{i-1}| + |q_i|$, or the matrix is positive definite, the algorithm is numerically stable and neither tr nor the check for diag[i] == 0 is needed.

Time: $\mathcal{O}(N)$

typedef double T; vector<T> tridiagonal(vector<T> diag, const vector<T>& super, const vector<T>& sub, vector<T> b) { int n = sz(b); vi tr(n); rep(i,0,n-1) { if (abs(diag[i]) < 1e-9 * abs(super[i])) { // diag[i] == 0 b[i+1] -= b[i] * diag[i+1] / super[i]; if (i+2 < n) b[i+2] -= b[i] * sub[i+1] / super[i]; diag[i+1] = sub[i]; tr[++i] = 1; } else { diag[i+1] -= super[i]*sub[i]/diag[i]; b[i+1] -= b[i]*sub[i]/diag[i]; } } for (int i = n; i--;) { if (tr[i]) { swap(b[i], b[i-1]); diag[i-1] = diag[i]; b[i] /= super[i-1]; } else { b[i] /= diag[i]; b[i] /= super[i-1]; if (i) b[i-1] -= b[i]*super[i-1]; } } return b; }
--

4.4 Fourier transforms

FastFourierTransform.h

Description: fft(a) computes $f(k) = \sum_x a[x] \exp(2\pi i \cdot kx/N)$ for all k . N must be a power of 2. Useful for convolution: conv(a, b) = c, where $c[x] = \sum a[i]b[x-i]$. For convolution of complex numbers or more than two vectors: FFT, multiply pointwise, divide by n, reverse(start+1, end), FFT back. Rounding is safe if $(\sum a_i^2 + \sum b_i^2) \log_2 N < 9 \cdot 10^{14}$ (in practice 10^{16} ; higher for random inputs). Otherwise, use NTT/FFTMod.

Time: $\mathcal{O}(N \log N)$ with $N = |A| + |B|$ (~1s for $N = 2^{22}$)

typedef complex<double> C; typedef vector<double> vd; void fft(vector<C>& a) {	00ced6, 35 lines
--	------------------


```
int n = sz(a), L = 31 - __builtin_clz(n);
static vector<complex<long double>> R(2, 1);
static vector<C> rt(2, 1); // (^ 10% faster if double)
for (static int k = 2; k < n; k *= 2) {
    R.resize(n); rt.resize(n);
    auto x = polar(1.0L, acos(-1.0L) / k);
    rep(i,k,2*k) rt[i] = R[i] = i&1 ? R[i/2] * x : R[i/2];
}
vi rev(n);
rep(i,0,n) rev[i] = (rev[i / 2] | (i & 1) << L) / 2;
rep(i,0,n) if (i < rev[i]) swap(a[i], a[rev[i]]);
for (int k = 1; k < n; k *= 2)
    for (int i = 0; i < n; i += 2 * k) rep(j,0,k) {
        C z = rt[j+k] * a[i+j+k]; // (25% faster if hand-rolled)
        a[i + j + k] = a[i + j] - z;
        a[i + j] += z;
    }
}
vd conv(const vd& a, const vd& b) {
    if (a.empty() || b.empty()) return {};
    vd res(sz(a) + sz(b) - 1);
    int L = 32 - __builtin_clz(sz(res)), n = 1 << L;
    vector<C> in(n), out(n);
    copy(all(a), begin(in));
    rep(i,0,sz(b)) in[i].imag(b[i]);
    fft(in);
    for (C& x : in) x *= x;
    rep(i,0,n) out[i] = in[-i & (n - 1)] - conj(in[i]);
    fft(out);
    rep(i,0,sz(res)) res[i] = imag(out[i]) / (4 * n);
    return res;
}
```

FastFourierTransformMod.h

Description: Higher precision FFT, can be used for convolutions modulo arbitrary integers as long as $N \log_2 N \cdot \text{mod} < 8.6 \cdot 10^{14}$ (in practice 10^{16} or higher). Inputs must be in $[0, \text{mod})$.

Time: $\mathcal{O}(N \log N)$, where $N = |A| + |B|$ (twice as slow as NTT or FFT)
"FastFourierTransform.h" b27773, 22 lines

```
typedef vector<ll> vl;
template<int M> vl convMod(const vl &a, const vl &b) {
    if (a.empty() || b.empty()) return {};
    vl res(sz(a) + sz(b) - 1);
    int B=32-__builtin_clz(sz(res)), n=1<<B, cut=int(sqrt(M));
    vector<C> L(n), R(n), outs(n), outl(n);
    rep(i,0,sz(a)) L[i] = C((int)a[i] / cut, (int)a[i] % cut);
    rep(i,0,sz(b)) R[i] = C((int)b[i] / cut, (int)b[i] % cut);
    fft(L), fft(R);
    rep(i,0,n) {
        int j = -i & (n - 1);
        outl[j] = (L[i] + conj(L[j])) * R[i] / (2.0 * n);
        outs[j] = (L[i] - conj(L[j])) * R[i] / (2.0 * n) / 1i;
    }
    fft(outl), fft(outs);
    rep(i,0,sz(res)) {
        ll av = ll(real(outl[i])+.5), cv = ll(imag(outs[i])+.5);
        ll bv = ll(imag(outl[i])+.5) + ll(real(outs[i])+.5);
        res[i] = ((av % M * cut + bv) % M * cut + cv) % M;
    }
    return res;
}
```

NumberTheoreticTransform.h

Description: ntt(a) computes $\hat{f}(k) = \sum_x a[x]g^{xk}$ for all k , where $g = \text{root}^{(\text{mod}-1)/N}$. N must be a power of 2. Useful for convolution modulo specific nice primes of the form 2^ab+1 , where the convolution result has size at most 2^a . For arbitrary modulo, see FFTMod. $\text{conv}(a, b) = c$, where $c[x] = \sum a[i]b[x-i]$. For manual convolution: NTT the inputs, multiply pointwise, divide by n , reverse(start+1, end), NTT back. Inputs must be in $[0, \text{mod})$.

Time: $\mathcal{O}(N \log N)$
"../number-theory/ModPow.h" ced03d, 35 lines

```
const ll mod = (119 << 23) + 1, root = 62; // = 998244353
// For p < 2^30 there is also e.g. 5 << 25, 7 << 26, 479 << 21
// and 483 << 21 (same root). The last two are > 10^9.
typedef vector<ll> vl;
void ntt(vl &a) {
    int n = sz(a), L = 31 - __builtin_clz(n);
```

```
static vl rt(2, 1);
for (static int k = 2, s = 2; k < n; k *= 2, s++) {
    rt.resize(n);
    ll z[] = {1, modpow(root, mod >> s)};
    rep(i,k,2*k) rt[i] = rt[i / 2] * z[i & 1] % mod;
}
vi rev(n);
rep(i,0,n) rev[i] = (rev[i / 2] | (i & 1) << L) / 2;
rep(i,0,n) if (i < rev[i]) swap(a[i], a[rev[i]]);
for (int k = 1; k < n; k *= 2)
    for (int i = 0; i < n; i += 2 * k) rep(j,0,k) {
        ll z = rt[j + k] * a[i + j + k] % mod, &ai = a[i + j];
        a[i + j + k] = ai - z + (z > ai ? mod : 0);
        ai += (ai + z >= mod ? z - mod : z);
    }
}
vl conv(const vl &a, const vl &b) {
    if (a.empty() || b.empty()) return {};;
    int s = sz(a) + sz(b) - 1, B = 32 - __builtin_clz(s),
        n = 1 << B;
    int inv = modpow(n, mod - 2);
    vl L(a), R(b), out(n);
    L.resize(n), R.resize(n);
    ntt(L), ntt(R);
    rep(i,0,n)
        out[-i & (n - 1)] = (ll)L[i] * R[i] % mod * inv % mod;
    ntt(out);
    return {out.begin(), out.begin() + s};
}
```

FastSubsetTransform.h

Description: Transform to a basis with fast convolutions of the form $c[z] = \sum_{z=x\oplus y} a[x] \cdot b[y]$, where \oplus is one of AND, OR, XOR. The size of a must be a power of two.

Time: $\mathcal{O}(N \log N)$ 464cf3, 16 lines

```
void FST(vi& a, bool inv) {
    for (int n = sz(a), step = 1; step < n; step *= 2) {
        for (int i = 0; i < n; i += 2 * step) rep(j,i,step) {
            int &u = a[j], &v = a[j + step]; tie(u, v) =
                inv ? pii(v - u, u) : pii(v, u + v); // AND
                inv ? pii(v, u - v) : pii(u + v, u); // OR
                pii(u + v, u - v); // XOR
        }
        if (inv) for (int& x : a) x /= sz(a); // XOR only
    }
}
vi conv(vi a, vi b) {
    FST(a, 0); FST(b, 0);
    rep(i,0,sz(a)) a[i] *= b[i];
    FST(a, 1); return a;
}
```

4.5 Formal Power Series

Poly.h

Description: polynomial class that supports convolution, derivative, integral, inv, ln, exp, pow and sqrt.

2ac319, 245 lines

```
typedef vector<ll> vl;
struct poly : vl {
    const ll mod = (119 << 23) + 1, root = 62; // = 998244353
    // For p < 2^30 there is also e.g. 5 << 25, 7 << 26, 479 << 21
    // and 483 << 21 (same root). The last two are > 10^9.
    poly(int n) : vl(n) {}
    poly(std::initializer_list<ll> x) : vl(all(x)) {}
    poly(vl v) : vl(all(v)) {}
    poly(int n, int v) : vl(n, v) {}
    poly(const poly &b) {
        this->clear();
        for (auto x : b) this->pb(x);
    }
private:
    ll modpow(ll b, ll e, const ll mod = 998244353) const {
        ll ans = 1;
        for (; e; b = b * b % mod, e /= 2)
            if (e & 1) ans = ans * b % mod;
        return ans;
    }
}
```

```
ll modinv(ll b, const ll mod = 998244353) const {
    return modpow(b, mod - 2, mod);
}
void ntt(vl &a) const {
    int n = sz(a), L = 31 - __builtin_clz(n);
    static vl rt(2, 1);
    for (static int k = 2, s = 2; k < n; k *= 2, s++) {
        rt.resize(n);
        ll z[] = {1, modpow(root, mod >> s)};
        rep(i,k,2*k) rt[i] = rt[i / 2] * z[i & 1] % mod;
    }
    vi rev(n);
    rep(i,0,n) rev[i] = (rev[i / 2] | (i & 1) << L) / 2;
    rep(i,0,n) if (i < rev[i]) ::swap(a[i], a[rev[i]]);
    for (int k = 1; k < n; k *= 2)
        for (int i = 0; i < n; i += 2 * k) rep(j,0,k) {
            ll z = rt[j + k] * a[i + j + k] % mod, &ai = a[i + j];
            a[i + j + k] = ai - z + (z > ai ? mod : 0);
            ai += (ai + z >= mod ? z - mod : z);
        }
}
poly conv(const poly &a, const poly &b) const {
    if (a.empty() || b.empty()) return poly(0);
    int s = sz(a) + sz(b) - 1, B = 32 - __builtin_clz(s),
        n = 1 << B;
    int inv = modpow(n, mod - 2);
    poly L(a), R(b), out(n);
    L.resize(n), R.resize(n);
    ntt(L), ntt(R);
    rep(i,0,n)
        out[-i & (n - 1)] = (ll)L[i] * R[i] % mod * inv % mod;
    ntt(out);
    while (sz(out) > s) out.pop_back();
    return out;
}
public:
poly operator+(const poly &b) const {
    poly res(max(sz(*this), sz(b)), 0);
    rep(i,0,sz(res)) {
        ll av = (i < sz(*this) ? (*this)[i] : 0);
        ll bv = (i < sz(b) ? b[i] : 0);
        res[i] = (av + bv >= mod ? av + bv - mod : av + bv);
    }
    return res;
}
poly operator-(const poly &b) const {
    poly res(max(sz(*this), sz(b)), 0);
    rep(i,0,sz(res)) {
        ll av = (i < sz(*this) ? (*this)[i] : 0);
        ll bv = (i < sz(b) ? b[i] : 0);
        res[i] = (av - bv < 0 ? av - bv + mod : av - bv);
    }
    return res;
}
poly operator*(const poly &b) const {
    return conv(*this, b);
}
poly operator*(const ll &b) const {
    poly res(sz(*this), 0);
    rep(i,0,sz(res)) res[i] = ((*this)[i] * b) % mod;
    return res;
}
poly operator=(const poly &b) {
    this->clear();
    for (auto x : b) this->pb(x);
    return *this;
}
poly operator+=(const poly &b) {
    return *this = *this + b;
}
poly operator-=(const poly &b) {
    return *this = *this - b;
}
poly operator*=(const poly &b) {
    return *this = *this * b;
}
poly modxk(int k) const {
    k = min(k, (int)this->size());
    return poly(vl(this->begin(), this->begin() + k));
}
```

```

}
poly deriv() const {
    if (this->empty()) return poly(0);
    poly res(max(0LL, (ll)this->size() - 1), 0);
    for (int i = 1; i < (int)this->size(); i++)
        res[i - 1] = (*this)[i] * i % mod;
    return res;
}
poly integ() const {
    poly res((int)this->size() + 1, 0);
    for (int i = 0; i < (int)this->size(); i++)
        res[i + 1] = (*this)[i] * modpow(i + 1, mod - 2) % mod;
    return res;
}
poly inv(int n) const { // requires (*this)[0] != 0
    assert(!this->empty() && (*this)[0] % mod != 0);
    poly r(vl{modpow((*this)[0], mod - 2)});
    for (int m = 1; m < n; m <= 1) {
        poly f = this->modxk(m < 1);
        r = (r * (poly(vl{2}) - f * r)).modxk(m < 1);
    }
    return r.modxk(n);
}
poly ln(int n) const { // requires (*this)[0] == 1
    assert(!this->empty() && (*this)[0] % mod == 1);
    poly f = this->modxk(n);
    return (f.deriv() * f.inv(n - 1)).integ().modxk(n);
}
poly exp(int n) const {
    assert(this->empty() || (*this)[0] % mod == 0);
    poly g(vl{1});
    for (int m = 1; m < n; m <= 1) {
        poly cur = this->modxk(m < 1);
        g = (g * (poly(vl{1}) - g.ln(m < 1) + cur)).modxk(m < 1);
    }
    return g.modxk(n);
}
// calculate this^k mod x^n
poly pow(int k, int n) const {
    if (this->empty()) return *this;
    if (k == 0) {
        poly one(n, 0);
        one[0] = 1;
        return one;
    }
    int lead = 0;
    while (lead < (int)this->size() && (*this)[lead] == 0) lead++;
    if (lead == (int)this->size() || (__int128) lead * k >= n)
        return poly(n, 0);
    ll inv = modinv((*this)[lead]);
    poly f((int)this->size() - lead, 0);
    for (int i = 0; i < (int)f.size(); i++)
        f[i] = (*this)[i + lead] * inv % mod;
    poly res = (f.ln(n - lead * k) * (k % mod)).exp(n - lead * k);
    res = res * modpow((*this)[lead], k);
    poly ans(n, 0);
    for (int i = 0; i < (int)res.size(); i++)
        ans[i + lead * k] = res[i];
    return ans;
}
poly sqrt(int n) const { // calculate f(x) where f(x)^2 = (*this) mod x^n
    if (n == 0) return poly(0);
    poly a = *this;
    a.resize(n);
    int k = 0;
    while (k < n && a[k] == 0) k++;
    if (k == n) return poly(n, 0);
    if (k & 1) { // NO SOLUTION
        assert(false && "poly::sqrt: no square root exists (odd valuation)");
    }
    if (k) {
        poly b(n - k);
        for (int i = k; i < n; i++) b[i - k] = a[i];
        poly h = b.sqrt(n - (k / 2));
        poly res(n, 0);
        for (int i = 0; i < (int)h.size() && i + k / 2 < n; i++) res[i + k / 2] = h[i];
    }
}
```

```

    return res;
}
auto mod_sqrt = [&](ll A) -> ll {
    A %= mod;
    if (A < 0) A += mod;
    if (A == 0) return 0;
    if (modpow(A, (mod - 1) / 2) != 1) { // NO SOLUTION
        assert(false && "poly::sqrt: constant term is not a quadratic residue");
    }
    ll q = mod - 1;
    int s = 0;
    while ((q & 1) == 0) q >= 1, s++;
    ll z = 2;
    while (modpow(z, (mod - 1) / 2) != mod - 1) z++;
    ll c = modpow(z, q);
    ll x = modpow(A, (q + 1) / 2);
    ll t = modpow(A, q);
    int m = s;
    while (t != 1) {
        int i = 1;
        ll tt = (t * t) % mod;
        while (i < m && tt != 1) {
            tt = (tt * tt) % mod;
            i++;
        }
        ll b = c;
        for (int e = 0; e < m - i - 1; e++) b = (b * b) % mod;
        x = (x * b) % mod;
        ll b2 = (b * b) % mod;
        t = (t * b2) % mod;
        c = b2;
        m = i;
    }
    return x;
};
ll r0 = mod_sqrt(a[0]);
poly g(1);
g[0] = r0;
const ll inv2 = (mod + 1) / 2;
for (int m = 1; m < n; m <= 1) {
    int m2 = min(n, m < 1);
    poly a_cut = a;
    a_cut.resize(m2);
    poly invg = g.inv(m2);
    poly q = a_cut * invg;
    q.resize(m2);
    poly g_ext = g;
    g_ext.resize(m2);
    for (int i = 0; i < m2; i++) {
        q[i] = ( (g_ext[i] + q[i]) % mod ) * inv2 % mod;
    }
    g = q;
}
g.resize(n);
for (int i = 0; i < n; i++) {
    g[i] = (mod - g[i]) % mod;
}
return g;
}
friend ostream& operator<<(ostream& os, const poly& p) {
    os << "(";
    for (int i=0; i<sz(p); i++) {
        os << p[i];
        if (i+1 < sz(p)) os << "x^" << i;
        if (i+1 < sz(p)) os << " + ";
    }
    os << ")";
    return os;
}
};
```

Number theory (5)

5.1 Modular arithmetic

ModularArithmetic.h

Description: Operators for modular arithmetic. You need to set mod to some number first and then you can use the structure.

"euclid.h"	35bfea, 18 lines
------------	------------------

```

const ll mod = 17; // change to something else
struct Mod {
    ll x;
    Mod(ll xx) : x(xx) {}
    Mod operator+(Mod b) { return Mod((x + b.x) % mod); }
    Mod operator-(Mod b) { return Mod((x - b.x + mod) % mod); }
    Mod operator*(Mod b) { return Mod((x * b.x) % mod); }
    Mod operator/(Mod b) { return *this * invert(b); }
    Mod invert(Mod a) {
        ll x, y, g = euclid(a.x, mod, x, y);
        assert(g == 1); return Mod((x + mod) % mod);
    }
    Mod operator^(ll e) {
        if (!e) return Mod(1);
        Mod r = *this ^ (e / 2); r = r * r;
        return e&1 ? *this * r : r;
    }
};
```

ModInverse.h

Description: Pre-computation of modular inverses. Assumes LIM ≤ mod and that mod is a prime.

6f684f, 3 lines

```

const ll mod = 1000000007, LIM = 200000;
ll* inv = new ll[LIM] - 1; inv[1] = 1;
rep(i,2,LIM) inv[i] = mod - (mod / i) * inv[mod % i] % mod;
```

ModPow.h

b83e45, 8 lines

```

const ll mod = 1000000007; // faster if const

ll modpow(ll b, ll e) {
    ll ans = 1;
    for (; e; b = b * b % mod, e /= 2)
        if (e & 1) ans = ans * b % mod;
    return ans;
}
```

ModLog.h

Description: Returns the smallest $x > 0$ s.t. $a^x = b \pmod m$, or -1 if no such x exists. modLog(a,1,m) can be used to calculate the order of a .

c040b8, 11 lines

```

Time:  $O(\sqrt{m})$ 

ll modLog(ll a, ll b, ll m) {
    ll n = (ll) sqrt(m) + 1, e = 1, f = 1, j = 1;
    unordered_map<ll, ll> A;
    while (j <= n && (e = f * e % m) != b % m)
        A[e * b % m] = j++;
    if (e == b % m) return j;
    if (__gcd(m, e) == __gcd(m, b))
        rep(i,2,n+2) if (A.count(e = e * f % m))
            return n * i - A[e];
    return -1;
}
```

ModSum.h

Description: Sums of mod'ed arithmetic progressions. modsum(to, c, k, m) = $\sum_{i=0}^{to-1} (ki + c) \% m$. divsum is similar but for floored division.

5c5bc5, 16 lines

```

Time: log(m), with a large constant.

typedef unsigned long long ull;
ull sumsq(ull to) { return to / 2 * ((to-1) | 1); }

ull divsum(ull to, ull c, ull k, ull m) {
    ull res = k / m * sumsq(to) + c / m * to;
    k %= m; c %= m;
    if (!k) return res;
    ull to2 = (to * k + c) / m;
    return res + (to - 1) * to2 - divsum(to2, m-1 - c, m, k);
}
```

```

}

ll modsum(ull to, ll c, ll k, ll m) {
    c = ((c % m) + m) % m;
    k = ((k % m) + m) % m;
    return to * c + k * sumsq(to) - m * divsum(to, c, k, m);
}
```

ModMulLL.h

Description: Calculate $a \cdot b \bmod c$ (or $a^b \bmod c$) for $0 \leq a, b \leq c \leq 7.2 \cdot 10^{18}$.
Time: $\mathcal{O}(1)$ for modmul, $\mathcal{O}(\log b)$ for modpow

bbbd8f, 11 lines

```
typedef unsigned long long ull;
ull modmul(ull a, ull b, ull M) {
    ll ret = a * b - M * ull(1.L / M * a * b);
    return ret + M * (ret < 0) - M * (ret >= (1l)M);
}
ull modpow(ull b, ull e, ull mod) {
    ull ans = 1;
    for (; e; b = modmul(b, b, mod), e /= 2)
        if (e & 1) ans = modmul(ans, b, mod);
    return ans;
}
```

ModSqrt.h

Description: Tonelli-Shanks algorithm for modular square roots. Finds x s.t. $x^2 = a \pmod p$ ($-x$ gives the other solution).
Time: $\mathcal{O}(\log^2 p)$ worst case, $\mathcal{O}(\log p)$ for most p

19a793, 24 lines

```
ll sqrt(ll a, ll p) {
    a %= p; if (a < 0) a += p;
    if (a == 0) return 0;
    assert(modpow(a, (p-1)/2, p) == 1); // else no solution
    if (p % 4 == 3) return modpow(a, (p+1)/4, p);
    // a^(n+3)/8 or 2^(n+3)/8 * 2^(n-1)/4 works if p % 8 == 5
    ll s = p - 1, n = 2;
    int r = 0, m;
    while (s % 2 == 0)
        ++r, s /= 2;
    while (modpow(n, (p - 1) / 2, p) != p - 1) ++n;
    ll x = modpow(a, (s + 1) / 2, p);
    ll b = modpow(a, s, p), g = modpow(n, s, p);
    for (; r = m) {
        ll t = b;
        for (m = 0; m < r && t != 1; ++m)
            t = t * t % p;
        if (m == 0) return x;
        ll gs = modpow(g, 1LL << (r - m - 1), p);
        g = gs * gs % p;
        x = x * gs % p;
        b = b * g % p;
    }
}
```

5.2 Primality

FastEratosthenes.h

Description: Prime sieve for generating all primes smaller than LIM.
Time: LIM=1e9 \approx 1.5s

6b2912, 20 lines

```
const int LIM = 1e6;
bitset<LIM> isPrime;
vi eratosthenes() {
    const int S = (int)round(sqrt(LIM)), R = LIM / 2;
    vi pr = {2}, sieve(S+1); pr.reserve((int)(LIM/log(LIM)*1.1));
    vector<pii> cp;
    for (int i = 3; i <= S; i += 2) if (!sieve[i]) {
        cp.push_back({i, i * i / 2});
        for (int j = i * i; j <= S; j += 2 * i) sieve[j] = 1;
    }
    for (int L = 1; L <= R; L += S) {
        array<bool, S> block{};
        for (auto &[p, idx] : cp)
            for (int i=idx; i < S+L; idx = (i+p)) block[i-L] = 1;
        rep(i,0,min(S, R - L))
            if (!block[i]) pr.push_back((L + i) * 2 + 1);
    }
    for (int i : pr) isPrime[i] = 1;
```

```

    return pr;
}
```

MillerRabin.h

Description: Deterministic Miller-Rabin primality test. Guaranteed to work for numbers up to $7 \cdot 10^{18}$; for larger numbers, use Python and extend A randomly.
Time: 7 times the complexity of $a^b \bmod c$.

60dcd1, 12 lines

```
bool isPrime(ull n) {
    if (n < 2 || n % 6 % 4 != 1) return (n | 1) == 3;
    ull A[] = {2, 325, 9375, 28178, 450775, 9780504, 1795265022},
        s = __builtin_ctzll(n-1), d = n >> s;
    for (ull a : A) { // ^count trailing zeroes
        ull p = modpow(a%n, d, n), i = s;
        while (p != 1 && p != n - 1 && a % n && i--)
            p = modmul(p, p, n);
        if (p != n-1 && i != s) return 0;
    }
    return 1;
}
```

Factor.h

Description: Pollard-rho randomized factorization algorithm. Returns prime factors of a number, in arbitrary order (e.g. 2299 -> {11, 19, 11}).
Time: $\mathcal{O}(n^{1/4})$, less for numbers with small factors.

d8d98d, 18 lines

```
"ModMulLL.h", "MillerRabin.h"

ull pollard(ull n) {
    ull x = 0, y = 0, t = 30, prd = 2, i = 1, q;
    auto f = [&](ull x) { return modmul(x, x, n) + i; };
    while (t++ % 40 || __gcd(prd, n) == 1) {
        if (x == y) x = ++i, y = f(x);
        if ((q = modmul(prd, max(x,y) - min(x,y), n)) prd = q;
        x = f(x), y = f(f(y));
    }
    return __gcd(prd, n);
}

vector<ull> factor(ull n) {
    if (n == 1) return {};
    if (isPrime(n)) return {n};
    ull x = pollard(n);
    auto l = factor(x), r = factor(n / x);
    l.insert(l.end(), all(r));
    return l;
}
```

5.3 Divisibility

euclid.h

Description: Finds two integers x and y , such that $ax + by = \gcd(a, b)$. If you just need gcd, use the built in `_gcd` instead. If a and b are coprime, then x is the inverse of $a \pmod b$.

33ba8f, 5 lines

```
ll euclid(ll a, ll b, ll &x, ll &y) {
    if (!b) return x = 1, y = 0, a;
    ll d = euclid(b, a % b, y, x);
    return y -= a/b * x, d;
}
```

CRT.h

Description: Chinese Remainder Theorem.
crt(a, m, b, n) computes x such that $x \equiv a \pmod m, x \equiv b \pmod n$. If $|a| < m$ and $|b| < n$, x will obey $0 \leq x < \text{lcm}(m, n)$. Assumes $mn < 2^{62}$.
Time: $\log(n)$

04d93a, 7 lines

```
"euclid.h"

ll crt(ll a, ll m, ll b, ll n) {
    if (n > m) swap(a, b), swap(m, n);
    ll x, y, g = euclid(m, n, x, y);
    assert((a - b) % g == 0); // else no solution
    x = (b - a) % n * x % n / g * m + a;
    return x < 0 ? x + m*n/g : x;
}
```

5.3.1 Bézout’s identity

For $a \neq, b \neq 0$, then $d = \gcd(a, b)$ is the smallest positive integer for which there are integer solutions to

$$ax + by = d$$

If (x, y) is one solution, then all solutions are given by

$$\left(x + \frac{kb}{\gcd(a,b)}, y - \frac{ka}{\gcd(a,b)}\right), \quad k \in \mathbb{Z}$$

phiFunction.h

Description: Euler’s ϕ function is defined as $\phi(n) := \#$ of positive integers $\leq n$ that are coprime with n . $\phi(1) = 1$, p prime $\Rightarrow \phi(p^k) = (p - 1)p^{k-1}$, m, n coprime $\Rightarrow \phi(mn) = \phi(m)\phi(n)$. If $n = p_1^{k_1} p_2^{k_2} \dots p_r^{k_r}$ then $\phi(n) = (p_1 - 1)p_1^{k_1-1} \dots (p_r - 1)p_r^{k_r-1}$. $\phi(n) = n \cdot \prod_{p|n} (1 - 1/p)$.
 $\sum_{d|n} \phi(d) = n$, $\sum_{1 \leq k \leq n, \gcd(k, n)=1} k = n\phi(n)/2, n > 1$
Euler’s thm: a, n coprime $\Rightarrow a^{\phi(n)} \equiv 1 \pmod n$.
Fermat’s little thm: p prime $\Rightarrow a^{p-1} \equiv 1 \pmod p \ \forall a$.

cf7d6d, 8 lines

```
const int LIM = 5000000;
int phi[LIM];

void calculatePhi() {
    rep(i,0,LIM) phi[i] = i&1 ? i : i/2;
    for (int i = 3; i < LIM; i += 2) if(phi[i] == i)
        for (int j = i; j < LIM; j += i) phi[j] -= phi[j] / i;
}
```

5.4 Fractions

ContinuedFractions.h

Description: Given N and a real number $x \geq 0$, finds the closest rational approximation p/q with $p, q \leq N$. It will obey $|p/q - x| \leq 1/qN$.
For consecutive convergents, $p_{k+1}q_k - q_{k+1}p_k = (-1)^k$. (p_k/q_k alternates between $> x$ and $< x$.) If x is rational, y eventually becomes ∞ ; if x is the root of a degree 2 polynomial the a ’s eventually become cyclic.
Time: $\mathcal{O}(\log N)$

dd6c5e, 21 lines

```
typedef double d; // for N ~ 1e7; long double for N ~ 1e9
pair<ll, ll> approximate(d x, ll N) {
    ll LP = 0, LQ = 1, P = 1, Q = 0, inf = LLONG_MAX; d y = x;
    for (;;) {
        ll lim = min(P ? (N-LP) / P : inf, Q ? (N-LQ) / Q : inf),
            a = (ll)floor(y), b = min(a, lim),
            NP = b*P + LP, NQ = b*Q + LQ;
        if (a > b) {
            // If b > a/2, we have a semi-convergent that gives us a
            // better approximation; if b = a/2, we *may* have one.
            // Return {P, Q} here for a more canonical approximation.
            return (abs(x - (d)NP / (d)NQ) < abs(x - (d)P / (d)Q)) ?
                make_pair(NP, NQ) : make_pair(P, Q);
        }
        if (abs(y - 1/(y - (d)a)) > 3*N) {
            return {NP, NQ};
        }
        LP = P; P = NP;
        LQ = Q; Q = NQ;
    }
}
```

FracBinarySearch.h

Description: Given f and N , finds the smallest fraction $p/q \in [0, 1]$ such that $f(p/q)$ is true, and $p, q \leq N$. You may want to throw an exception from f if it finds an exact solution, in which case N can be removed.
Usage: fracBS([f](Frac f) { return f.p>=3*f.q; }, 10); // {1,3}
Time: $\mathcal{O}(\log(N))$

27ab3e, 25 lines

```
struct Frac { ll p, q; };

template<class F>
Frac fracBS(F f, ll N) {
    bool dir = 1, A = 1, B = 1;
    Frac lo{0, 1}, hi{1, 1}; // Set hi to 1/0 to search {0, N]
```

```
if (f(lo)) return lo;
assert(f(hi));
while (A || B) {
    ll adv = 0, step = 1; // move hi if dir, else lo
    for (int si = 0; step; (step *= 2) >= si) {
        adv += step;
        Frac mid(lo.p * adv + hi.p, lo.q * adv + hi.q);
        if (abs(mid.p) > N || mid.q > N || dir == !f(mid)) {
            adv -= step; si = 2;
        }
    }
    hi.p += lo.p * adv;
    hi.q += lo.q * adv;
    dir = !dir;
    swap(lo, hi);
    A = B; B = !adv;
}
return dir ? hi : lo;
}
```

5.5 Pythagorean Triples

The Pythagorean triples are uniquely generated by

$$a = k \cdot (m^2 - n^2), \; b = k \cdot (2mn), \; c = k \cdot (m^2 + n^2),$$

with $m > n > 0$, $k > 0$, $m \perp n$, and either m or n even.

5.6 Primes

$p = 962592769$ is such that $2^{21} \mid p - 1$, which may be useful. For hashing use 990386237 (31-bit number), 30221775611887 (45-bit), 2920387640151097 (52-bit). There are 78498 primes less than 1 000 000.

Primitive roots exist modulo any prime power p^a , except for $p = 2, a > 2$, and there are $\phi(\phi(p^a))$ many. For $p = 2, a > 2$, the group $\mathbb{Z}_{2^a}^\times$ is instead isomorphic to $\mathbb{Z}_2 \times \mathbb{Z}_{2^{a-2}}$.

5.7 Estimates

$$\sum_{d \mid n} d = O(n \log \log n).$$

5.7.1 Highly Composite numbers

Maximum number of divisors for numbers below n . $d(n)$ is at most around 100 for $n < 5e4$, 500 for $n < 1e7$, 2000 for $n < 1e10$, 200 000 for $n < 1e19$.

$\log_{10} n < \mid$	3	5	6	8	9	12	15	18
$d(n) < \mid$	32	128	240	768	1344	6720	26880	103680

The following numbers are highly composite: 840, 83160, 720720, 73513440, 735134400, 963761198400, 866421317361600, 897612484786617600

5.8 Mobius Function

$$\mu(n) = \begin{cases} 0 & n \text{ is not square free} \\ 1 & n \text{ has even number of prime factors} \\ -1 & n \text{ has odd number of prime factors} \end{cases}$$

Mobius Inversion:

$$g(n) = \sum_{d \mid n} f(d) \Leftrightarrow f(n) = \sum_{d \mid n} \mu(d) g(n/d)$$

Other useful formulas/forms:

$$\sum_{d \mid n} \mu(d) = [n = 1] \text{ (very useful)}$$

$$g(n) = \sum_{n \mid d} f(d) \Leftrightarrow f(n) = \sum_{n \mid d} \mu(d/n) g(d)$$

IntPerm multinomial

$$g(n) = \sum_{1 \leq m \leq n} f(\lfloor \frac{n}{m} \rfloor) \Leftrightarrow f(n) = \sum_{1 \leq m \leq n} \mu(m) g(\lfloor \frac{n}{m} \rfloor)$$

Combinatorial (6)

6.1 Permutations

6.1.1 Factorial

n	1	2	3	4	5	6	7	8	9	10
$n!$	1	2	6	24	120	720	5040	40320	362880	3628800
n	11	12	13	14	15	16	17			
$n!$	4.0e7	4.8e8	6.2e9	8.7e10	1.3e12	2.1e13	3.6e14			
n	20	25	30	40	50	100	150	171		
$n!$	2e18	2e25	3e32	8e47	3e64	9e157	6e262	>DBL-MAX		

IntPerm.h

Description: Permutation -> integer conversion. (Not order preserving.) Integer -> permutation can use a lookup table.

Time: $\mathcal{O}(n)$ 044568, 6 lines

```
int permToInt(vi& v) {
    int use = 0, i = 0, r = 0;
    for(int x:v) r = r * ++i + __builtin_popcount(use & ~(1<<x)),
        use |= 1 << x; // (note: minus, not ~!)
    return r;
}
```

6.1.2 Cycles

Let $g_S(n)$ be the number of n -permutations whose cycle lengths all belong to the set S . Then

$$\sum_{n=0}^\infty g_S(n) \frac{x^n}{n!} = \exp \left(\sum_{n \in S} \frac{x^n}{n} \right)$$

6.1.3 Derangements

Permutations of a set such that none of the elements appear in their original position.

$$D(n) = (n - 1)(D(n - 1) + D(n - 2)) = nD(n - 1) + (-1)^n = \left\lfloor \frac{n!}{e} \right\rfloor$$

6.1.4 Burnside’s lemma

Given a group G of symmetries and a set X , the number of elements of X up to symmetry equals

$$\frac{1}{|G|} \sum_{g \in G} |X^g|,$$

where X^g are the elements fixed by g ($g.x = x$).

If $f(n)$ counts “configurations” (of some sort) of length n , we can ignore rotational symmetry using $G = \mathbb{Z}_n$ to get

$$g(n) = \frac{1}{n} \sum_{k=0}^{n-1} f(\gcd(n, k)) = \frac{1}{n} \sum_{k \mid n} f(k) \phi(n/k).$$

6.2 Partitions and subsets

6.2.1 Partition function

Number of ways of writing n as a sum of positive integers, disregarding the order of the summands.

$$p(0) = 1, \; p(n) = \sum_{k \in \mathbb{Z} \setminus \{0\}} (-1)^{k+1} p(n - k(3k - 1)/2)$$

$$p(n) \sim 0.145/n \cdot \exp(2.56\sqrt{n})$$

n	0	1	2	3	4	5	6	7	8	9	20	50	100
$p(n)$	1	1	2	3	5	7	11	15	22	30	627	~2e5	~2e8

6.2.2 Lucas’ Theorem

Let n, m be non-negative integers and p a prime. Write $n = n_k p^k + \dots + n_1 p + n_0$ and $m = m_k p^k + \dots + m_1 p + m_0$. Then $\binom{n}{m} \equiv \prod_{i=0}^k \binom{n_i}{m_i} \pmod{p}$.

6.2.3 Binomials

multinomial.h

Description: Computes $\binom{k_1 + \dots + k_n}{k_1, k_2, \dots, k_n} = \frac{(\sum k_i)!}{k_1! k_2! \dots k_n!}$. a0a312, 5 lines

```
ll multinomial(vi& v) {
    ll c = 1, m = v.empty() ? 1 : v[0];
    rep(i, 1, sz(v)) rep(j, 0, v[i]) c = c * ++m / (j+1);
    return c;
}
```

6.3 General purpose numbers

6.3.1 Bernoulli numbers

EGF of Bernoulli numbers is $B(t) = \frac{t}{e^t - 1}$ (FFT-able).

$$B[0, \dots] = [1, -\frac{1}{2}, \frac{1}{6}, 0, -\frac{1}{30}, 0, \frac{1}{42}, \dots]$$

Sums of powers:

$$\sum_{i=1}^n n^m = \frac{1}{m+1} \sum_{k=0}^m \binom{m+1}{k} B_k \cdot (n+1)^{m+1-k}$$

Euler-Maclaurin formula for infinite sums:

$$\begin{aligned} \sum_{i=m}^\infty f(i) &= \int_m^\infty f(x) dx - \sum_{k=1}^\infty \frac{B_k}{k!} f^{(k-1)}(m) \\ &\approx \int_m^\infty f(x) dx + \frac{f(m)}{2} - \frac{f'(m)}{12} + \frac{f'''(m)}{720} + O(f^{(5)}(m)) \end{aligned}$$

6.3.2 Stirling numbers of the first kind

Number of permutations on n items with k cycles.

$$c(n, k) = c(n - 1, k - 1) + (n - 1) c(n - 1, k), \; c(0, 0) = 1$$

$$\sum_{k=0}^n c(n, k) x^k = x(x + 1) \dots (x + n - 1)$$

$$c(8, k) = 8, 0, 5040, 13068, 13132, 6769, 1960, 322, 28, 1$$

$$c(n, 2) = 0, 0, 1, 3, 11, 50, 274, 1764, 13068, 109584, \dots$$

6.3.3 Eulerian numbers

Number of permutations $\pi \in S_n$ in which exactly k elements are greater than the previous element. k j :s s.t. $\pi(j) > \pi(j + 1)$, $k + 1$ j :s s.t. $\pi(j) \geq j$, k j :s s.t. $\pi(j) > j$.

$$E(n, k) = (n - k) E(n - 1, k - 1) + (k + 1) E(n - 1, k)$$

$$E(n, 0) = E(n, n - 1) = 1$$

$$E(n, k) = \sum_{j=0}^k (-1)^j \binom{n+1}{j} (k + 1 - j)^n$$

6.3.4 Stirling numbers of the second kind

Partitions of n distinct elements into exactly k groups.

$$S(n,k) = S(n-1,k-1) + kS(n-1,k)$$

$$S(n,1) = S(n,n) = 1$$

$$S(n,k) = \frac{1}{k!} \sum_{j=0}^k (-1)^{k-j} \binom{k}{j} j^n$$

6.3.5 Bell numbers

Total number of partitions of n distinct elements. $B(n) = 1, 1, 2, 5, 15, 52, 203, 877, 4140, 21147, \dots$ For p prime,

$$B(p^m + n) \equiv mB(n) + B(n + 1) \pmod{p}$$

6.3.6 Labeled unrooted trees

on n vertices: n^{n-2}
on k existing trees of size n_i : $n_1n_2 \cdots n_kn^{k-2}$
with degrees d_i : $(n-2)!/((d_1-1)! \cdots (d_n-1)!)$

6.3.7 Catalan numbers

$$C_n = \frac{1}{n+1} \binom{2n}{n} = \binom{2n}{n} - \binom{2n}{n+1} = \frac{(2n)!}{(n+1)!n!}$$

$$C_0 = 1, C_{n+1} = \frac{2(2n+1)}{n+2} C_n, C_{n+1} = \sum C_i C_{n-i}$$

$C_n = 1, 1, 2, 5, 14, 42, 132, 429, 1430, 4862, 16796, 58786, \dots$

- sub-diagonal monotone paths in an $n \times n$ grid.
- strings with n pairs of parenthesis, correctly nested.
- binary trees with with $n + 1$ leaves (0 or 2 children).
- ordered trees with $n + 1$ vertices.
- ways a convex polygon with $n + 2$ sides can be cut into triangles by connecting vertices with straight lines.
- permutations of $[n]$ with no 3-term increasing subseq.

Graph (7)

7.1 Fundamentals

BellmanFord.h

Description: Calculates shortest paths from s in a graph that might have negative edge weights. Unreachable nodes get dist = inf; nodes reachable through negative-weight cycles get dist = -inf. Assumes $V^2 \max |w_i| < \sim 2^{63}$.

Time: $\mathcal{O}(VE)$ 830a8f, 23 lines

```
const ll inf = LLONG_MAX;
struct Ed { int a, b, w, s() { return a < b ? a : -a; }};
struct Node { ll dist = inf; int prev = -1; };
```

```
void bellmanFord(vector<Node>& nodes, vector<Ed>& eds, int s) {
    nodes[s].dist = 0;
    sort(all(eds), [](Ed a, Ed b) { return a.s() < b.s(); });
```

```
    int lim = sz(nodes) / 2 + 2; // /3+100 with shuffled vertices
    rep(i,0,lim) for (Ed ed : eds) {
        Node cur = nodes[ed.a], &dest = nodes[ed.b];
        if (abs(cur.dist) == inf) continue;
        ll d = cur.dist + ed.w;
        if (d < dest.dist) {
            dest.prev = ed.a;
            dest.dist = (i < lim-1 ? d : -inf);
        }
    }
```

```
    rep(i,0,lim) for (Ed e : eds) {
        if (nodes[e.a].dist == -inf)
            nodes[e.b].dist = -inf;
    }
}
```

FloydWarshall.h

Description: Calculates all-pairs shortest path in a directed graph that might have negative edge weights. Input is an distance matrix m , where $m[i][j] = \text{inf}$ if i and j are not adjacent. As output, $m[i][j]$ is set to the shortest distance between i and j , inf if no path, or -inf if the path goes through a negative-weight cycle.

Time: $\mathcal{O}(N^3)$ 531245, 12 lines

```
const ll inf = 1LL << 62;
void floydWarshall(vector<vector<ll>>& m) {
    int n = sz(m);
    rep(i,0,n) m[i][i] = min(m[i][i], 0LL);
    rep(k,0,n) rep(i,0,n) rep(j,0,n)
        if (m[i][k] != inf && m[k][j] != inf) {
            auto newDist = max(m[i][k] + m[k][j], -inf);
            m[i][j] = min(m[i][j], newDist);
        }
    rep(k,0,n) if (m[k][k] < 0) rep(i,0,n) rep(j,0,n)
        if (m[i][k] != inf && m[k][j] != inf) m[i][j] = -inf;
}
```

TopoSort.h

Description: Topological sorting. Given is an oriented graph. Output is an ordering of vertices, such that there are edges only from left to right. If there are cycles, the returned list will have size smaller than n – nodes reachable from cycles will not be returned.

Time: $\mathcal{O}(|V| + |E|)$ d678d8, 8 lines

```
vi topoSort(const vector<vi>& gr) {
    vi indeg(sz(gr)), g;
    for (auto& li : gr) for (int x : li) indeg[x]++;
    rep(i,0,sz(gr)) if (indeg[i] == 0) q.push_back(i);
    rep(j,0,sz(q)) for (int x : gr[q[j]])
        if (--indeg[x] == 0) q.push_back(x);
    return q;
}
```

7.2 Network flow

PushRelabel.h

Description: Push-relabel using the highest label selection rule and the gap heuristic. Quite fast in practice. To obtain the actual flow, look at positive values only.

Time: $\mathcal{O}(V^2\sqrt{E})$ 0ae1d4, 48 lines

```
struct PushRelabel {
    struct Edge {
        int dest, back;
        ll f, c;
    };
    vector<vector<Edge>> g;
    vector<ll> ec;
    vector<Edge>> cur;
    vector<vi> hs; vi H;
    PushRelabel(int n) : g(n), ec(n), cur(n), hs(2*n), H(n) {}

    void addEdge(int s, int t, ll cap, ll rcap=0) {
        if (s == t) return;
        g[s].push_back({t, sz(g[t]), 0, cap});
        g[t].push_back({s, sz(g[s])-1, 0, rcap});
    }

    void addFlow(Edge& e, ll f) {
        Edge &back = g[e.dest][e.back];
        if (!ec[e.dest] && f) hs[H[e.dest]].push_back(e.dest);
        e.f += f; e.c -= f; ec[e.dest] += f;
        back.f -= f; back.c += f; ec[back.dest] -= f;
    }

    ll calc(int s, int t) {
        int v = sz(g); H[s] = v; ec[t] = 1;
        vi co(2*v); co[0] = v-1;
        rep(i,0,v) cur[i] = g[i].data();
        for (Edge& e : g[s]) addFlow(e, e.c);
```

```
    for (int hi = 0;;) {
        while (hs[hi].empty()) if (!hi--) return -ec[s];
        int u = hs[hi].back(); hs[hi].pop_back();
        while (ec[u] > 0) // discharge u
            if (cur[u] == g[u].data() + sz(g[u])) {
                H[u] = 1e9;
                for (Edge& e : g[u]) if (e.c && H[u] > H[e.dest]+1)
                    H[u] = H[e.dest]+1, cur[u] = &e;
                if (++co[H[u]],!--co[hi] && hi < v)
                    rep(i,0,v) if (hi < H[i] && H[i] < v)
                        --co[H[i]], H[i] = v + 1;
                hi = H[u];
            } else if (cur[u]->c && H[u] == H[cur[u]->dest]+1)
                addFlow(*cur[u], min(ec[u], cur[u]->c));
            else ++cur[u];
        }
    }
    bool leftOfMinCut(int a) { return H[a] >= sz(g); }
};
```

MinCostMaxFlow.h

Description: Min-cost max-flow. If costs can be negative, call setpi before maxflow, but note that negative cost cycles are not supported. To obtain the actual flow, look at positive values only.

Time: $\mathcal{O}(FE \log(V))$ where F is max flow. $\mathcal{O}(VE)$ for setpi. 58385b, 79 lines

```
#include <bits/extc++.h>

const ll INF = numeric_limits<ll>::max() / 4;

struct MCMF {
    struct edge {
        int from, to, rev;
        ll cap, cost, flow;
    };
    int N;
    vector<vector<edge>> ed;
    vi seen;
    vector<ll> dist, pi;
    vector<edge*> par;

    MCMF(int N) : N(N), ed(N), seen(N), dist(N), pi(N), par(N) {}

    void addEdge(int from, int to, ll cap, ll cost) {
        if (from == to) return;
        ed[from].push_back(edge{ from,to,sz(ed[to]),cap,cost,0 });
        ed[to].push_back(edge{ to,from,sz(ed[from])-1,0,-cost,0 });
    }

    void path(int s) {
        fill(all(seen), 0);
        fill(all(dist), INF);
        dist[s] = 0; ll di;

        __gnu_pbds::priority_queue<pair<ll, int>> q;
        vector<decltype(q)::point_iterator> its(N);
        q.push({ 0, s });

        while (!q.empty()) {
            s = q.top().second; q.pop();
            seen[s] = 1; di = dist[s] + pi[s];
            for (edge& e : ed[s]) if (!seen[e.to]) {
                ll val = di - pi[e.to] + e.cost;
                if (e.cap - e.flow > 0 && val < dist[e.to]) {
                    dist[e.to] = val;
                    par[e.to] = &e;
                    if (its[e.to] == q.end())
                        its[e.to] = q.push({ -dist[e.to], e.to });
                    else
                        q.modify(its[e.to], { -dist[e.to], e.to });
                }
            }
            rep(i,0,N) pi[i] = min(pi[i] + dist[i], INF);
        }

        pair<ll, ll> maxflow(int s, int t) {
            ll totflow = 0, totcost = 0;
            while (path(s), seen[t]) {
```

```
ll fl = INF;
for (edge* x = par[t]; x; x = par[x->from])
    fl = min(fl, x->cap - x->flow);

totflow += fl;
for (edge* x = par[t]; x; x = par[x->from]) {
    x->flow += fl;
    ed[x->to][x->rev].flow -= fl;
}
}
rep(i,0,N) for(edge& e : ed[i]) totcost += e.cost * e.flow;
return {totflow, totcost/2};
}

// If some costs can be negative, call this before maxflow:
void setpi(int s) { // (otherwise, leave this out)
    fill(all(pi), INF); pi[s] = 0;
    int it = N, ch = 1; ll v;
    while (ch-- && it--)
        rep(i,0,N) if (pi[i] != INF)
            for (edge& e : ed[i]) if (e.cap)
                if ((v = pi[i] + e.cost) < pi[e.to])
                    pi[e.to] = v, ch = 1;
    assert(it >= 0); // negative cost cycle
}
};
```

EdmondsKarp.h

Description: Flow algorithm with guaranteed complexity $O(VE^2)$. To get edge flow values, compare capacities before and after, and take the positive values only.

```
template<class T> T edmondsKarp(vector<unordered_map<int, T>&&
    graph, int source, int sink) {
    assert(source != sink);
    T flow = 0;
    vi par(sz(graph)), q = par;

    for (;;) {
        fill(all(par), -1);
        par[source] = 0;
        int ptr = 1;
        q[0] = source;

        rep(i,0,ptr) {
            int x = q[i];
            for (auto e : graph[x]) {
                if (par[e.first] == -1 && e.second > 0) {
                    par[e.first] = x;
                    q[ptr++] = e.first;
                    if (e.first == sink) goto out;
                }
            }
        }
        return flow;
    out:
        T inc = numeric_limits<T>::max();
        for (int y = sink; y != source; y = par[y])
            inc = min(inc, graph[par[y]][y]);

        flow += inc;
        for (int y = sink; y != source; y = par[y]) {
            int p = par[y];
            if ((graph[p][y] -= inc) <= 0) graph[p].erase(y);
            graph[y][p] += inc;
        }
    }
}
```

Dinic.h

Description: Flow algorithm with complexity $O(VE \log U)$ where $U = \max |cap|$. $O(\min(E^{1/2}, V^{2/3})E)$ if $U = 1$; $O(\sqrt{VE})$ for bipartite matching.

```
struct Dinic {
    struct Edge {
        int to, rev;
        ll c, oc;
        ll flow() { return max(oc - c, 0LL); } // if you need flows
    };
    vi lvl, ptr, q;
```

```
vector<vector<Edge>> adj;
Dinic(int n) : lvl(n), ptr(n), q(n), adj(n) {}
void addEdge(int a, int b, ll c, ll rcap = 0) {
    adj[a].push_back({b, sz(adj[b]), c, c});
    adj[b].push_back({a, sz(adj[a]) - 1, rcap, rcap});
}

ll dfs(int v, int t, ll f) {
    if (v == t || !f) return f;
    for (int& i = ptr[v]; i < sz(adj[v]); i++) {
        Edge& e = adj[v][i];
        if (lvl[e.to] == lvl[v] + 1)
            if (ll p = dfs(e.to, t, min(f, e.c))) {
                e.c -= p, adj[e.to][e.rev].c += p;
                return p;
            }
    }
    return 0;
}

ll calc(int s, int t) {
    ll flow = 0; q[0] = s;
    rep(L,0,31) do { // 'int L=30' maybe faster for random data
        lvl = ptr = vi(sz(q));
        int qi = 0, qe = lvl[s] = 1;
        while (qi < qe && !lvl[t]) {
            int v = q[qi++];
            for (Edge e : adj[v])
                if (!lvl[e.to] && e.c >> (30 - L))
                    q[qe++] = e.to, lvl[e.to] = lvl[v] + 1;
        }
        while (ll p = dfs(s, t, LLONG_MAX)) flow += p;
    } while (lvl[t]);
    return flow;
}

bool leftOfMinCut(int a) { return lvl[a] != 0; }
};
```

MinCut.h

Description: After running max-flow, the left side of a min-cut from s to t is given by all vertices reachable from s , only traversing edges with positive residual capacity.

GlobalMinCut.h

Description: Find a global minimum cut in an undirected graph, as represented by an adjacency matrix.

```
Time:  $\mathcal{O}(V^3)$ 
8b0e19, 21 lines

pair<int, vi> globalMinCut(vector<vi> mat) {
    pair<int, vi> best = {INT_MAX, {}};
    int n = sz(mat);
    vector<vi> co(n);
    rep(i,0,n) co[i] = {i};
    rep(ph,1,n) {
        vi w = mat[0];
        size_t s = 0, t = 0;
        rep(it,0,n-ph) { //  $O(V^2) \rightarrow O(E \log V)$  with prio. queue
            w[t] = INT_MIN;
            s = t, t = max_element(all(w)) - w.begin();
            rep(i,0,n) w[i] += mat[t][i];
        }
        best = min(best, {w[t] - mat[t][t], co[t]});
        co[s].insert(co[s].end(), all(co[t]));
        rep(i,0,n) mat[s][i] += mat[t][i];
        rep(i,0,n) mat[i][s] = mat[s][i];
        mat[0][t] = INT_MIN;
    }
    return best;
}
```

GomoryHu.h

Description: Given a list of edges representing an undirected flow graph, returns edges of the Gomory-Hu tree. The max flow between any pair of vertices is given by minimum edge weight along the Gomory-Hu tree path.

```
Time:  $\mathcal{O}(V)$  Flow Computations
"PushRelabel.h"
0418b3, 13 lines

typedef array<ll, 3> Edge;
vector<Edge> gomoryHu(int N, vector<Edge> ed) {
    vector<Edge> tree;
```

```
vi par(N);
rep(i,1,N) {
    PushRelabel D(N); // Dinic also works
    for (Edge t : ed) D.addEdge(t[0], t[1], t[2], t[2]);
    tree.push_back({i, par[i], D.calc(i, par[i])});
    rep(j,i+1,N)
        if (par[j] == par[i] && D.leftOfMinCut(j)) par[j] = i;
}
return tree;
}
```

FlowWithDemands.h

Description: addEdge(u, v, l, r) adds a directed edge from node u to node v with demand l and capacity r. It is also possible to add edges normally using addEdge(u, v, c). Supersource node is node n-2, supersource node is node n-1 as seen inside the template, and nodes n and n+1 respectively seen outside the template. calcMax() returns either the maximum flow satisfying all constraints from s to t, or -1 if a valid flow cannot be found. To find a minimum flow satisfying all constraints, binary search on the parameter X passed to calcMax(s, t, X) to find the smallest X such that calcMax(s, t, X) is not -1.

```
4aebb9, 73 lines

struct FlowWithDemands {
    struct Edge {
        int to, rev;
        ll c, oc;
        ll flow() { return max(oc - c, 0LL); } // if you need flows
    };
    vi lvl, ptr, q;
    vector<vector<Edge>> adj, adjcpy;
    int n;
    ll sumDemands = 0;
    FlowWithDemands(int n_) {
        n_ += 2;
        n = n_;
        lvl.resize(n);
        ptr.resize(n);
        q.resize(n);
        adj.resize(n);
        adjcpy.resize(n);
    }

    void addEdge_(int a, int b, ll c, ll rcap = 0) {
        adj[a].push_back({b, sz(adj[b]), c, c});
        adj[b].push_back({a, sz(adj[a]) - 1, rcap, rcap});
        adjcpy[a].push_back({b, sz(adj[b]), c, c});
        adjcpy[b].push_back({a, sz(adj[a]) - 1, rcap, rcap});
    }

    void addEdge(int a, int b, ll lc, ll rc, ll rcap = 0) {
        addEdge_(a, b, rc - lc);
        addEdge_(n-2, b, lc);
        addEdge_(a, n-1, lc);
        sumDemands += lc;
    }

    void reset() {
        // Resets entire adjacency list to state before any flow calculations
        adj = adjcpy;
    }

    ll dfs(int v, int t, ll f) {
        if (v == t || !f) return f;
        for (int& i = ptr[v]; i < sz(adj[v]); i++) {
            Edge& e = adj[v][i];
            if (lvl[e.to] == lvl[v] + 1)
                if (ll p = dfs(e.to, t, min(f, e.c))) {
                    e.c -= p, adj[e.to][e.rev].c += p;
                    return p;
                }
        }
    }

    }
    return 0;
}

ll calc_(int s, int t) {
    ll flow = 0; q[0] = s;
    rep(L,0,31) do { // 'int L=30' maybe faster for random data
        lvl = ptr = vi(sz(q));
        int qi = 0, qe = lvl[s] = 1;
        while (qi < qe && !lvl[t]) {
            int v = q[qi++];
            for (Edge e : adj[v])
                if (!lvl[e.to] && e.c >> (30 - L))
                    q[qe++] = e.to, lvl[e.to] = lvl[v] + 1;
        }
    }
}
```

```
        while (ll p = dfs(s, t, LLONG_MAX)) flow += p;
    } while (lvl[t]);
    return flow;
}

ll calcMax(int s, int t, ll X = 1e15) {
    // finds MAXIMUM flow satisfying the constraints
    addEdge(t, s, 0, X);
    ll fi = calc_(n-2, n-1);
    adj[t].pop_back();
    adj[s].pop_back();
    if (fi != sumDemands) return -1;
    return calc_(s, t);
}

bool leftOfMinCut(int a) { return lvl[a] != 0; }
};
```

7.3 Matching

HopcroftKarp.h

Description: Fast bipartite matching algorithm. Graph g should be a list of neighbors of the left partition, and r should be a vector full of -1 's of the same size as the right partition. Returns the size of the matching. $r[i]$ will be the match for vertex i on the right side, or -1 if it's not matched.

Time: $\mathcal{O}\left(E\sqrt{V}\right)$ 731cfb, 20 lines

```
int hopcroftKarp(vector<vi>& g, vi& r) {
    int n = sz(g), res = 0;
    vi l(n, -1), q(n), d(n);
    auto dfs = [&](auto f, int u) -> bool {
        int t = exchange(d[u], 0) + 1;
        for (int v : g[u])
            if (r[v] == -1 || (d[r[v]] == t && f(f, r[v])))
                return l[u] = v, r[v] = u, 1;
        return 0;
    };
    for (int t = 0, f = 0;; t = f = 0, d.assign(n, 0)) {
        rep(i, 0, n) if (l[i] == -1) q[t++] = i, d[i] = 1;
        rep(i, 0, t) for (int v : g[q[i]]) {
            if (r[v] == -1) f = 1;
            else if (!d[r[v]]) d[r[v]] = d[q[i]] + 1, q[t++] = r[v];
        }
        if (!f) return res;
        rep(i, 0, n) if (l[i] == -1) res += dfs(dfs, i);
    }
}
```

DFSMatching.h

Description: Simple bipartite matching algorithm. Graph g should be a list of neighbors of the left partition, and $btoa$ should be a vector full of -1 's of the same size as the right partition. Returns the size of the matching. $btoa[i]$ will be the match for vertex i on the right side, or -1 if it's not matched.

Usage: vi btoa(m, -1); dfsMatching(g, btoa);
Time: $\mathcal{O}(VE)$ 522b98, 22 lines

```
bool find(int j, vector<vi>& g, vi& btoa, vi& vis) {
    if (btoa[j] == -1) return 1;
    vis[j] = 1; int di = btoa[j];
    for (int e : g[di])
        if (!vis[e] && find(e, g, btoa, vis)) {
            btoa[e] = di;
            return 1;
        }
    return 0;
}

int dfsMatching(vector<vi>& g, vi& btoa) {
    vi vis;
    rep(i, 0, sz(g)) {
        vis.assign(sz(btoa), 0);
        for (int j : g[i])
            if (find(j, g, btoa, vis)) {
                btoa[j] = i;
                break;
            }
    }
    return sz(btoa) - (int)count(all(btoa), -1);
}
```

MinimumVertexCover.h

Description: Finds a minimum vertex cover in a bipartite graph. The size is the same as the size of a maximum matching, and the complement is a maximum independent set.

"DFSMatching.h" da4196, 20 lines

```
vi cover(vector<vi>& g, int n, int m) {
    vi match(m, -1);
    int res = dfsMatching(g, match);
    vector<bool> lfound(n, true), seen(m);
    for (int it : match) if (it != -1) lfound[it] = false;
    vi q, cover;
    rep(i, 0, n) if (lfound[i]) q.push_back(i);
    while (!q.empty()) {
        int i = q.back(); q.pop_back();
        lfound[i] = 1;
        for (int e : g[i]) if (!seen[e] && match[e] != -1) {
            seen[e] = true;
            q.push_back(match[e]);
        }
    }
    rep(i, 0, n) if (!lfound[i]) cover.push_back(i);
    rep(i, 0, m) if (seen[i]) cover.push_back(n+i);
    assert(sz(cover) == res);
    return cover;
}
```

WeightedMatching.h

Description: Given a weighted bipartite graph, matches every node on the left with a node on the right such that no nodes are in two matchings and the sum of the edge weights is minimal. Takes $cost[N][M]$, where $cost[i][j]$ = cost for $L[i]$ to be matched with $R[j]$ and returns (min cost, match), where $L[i]$ is matched with $R[match[i]]$. Negate costs for max cost. Requires $N \leq M$.

Time: $\mathcal{O}\left(N^2M\right)$ 1e0fe9, 31 lines

```
pair<int, vi> hungarian(const vector<vi> &a) {
    if (a.empty()) return {0, {}};
    int n = sz(a) + 1, m = sz(a[0]) + 1;
    vi u(n), v(m), p(m), ans(n - 1);
    rep(i, 1, n) {
        p[0] = i;
        int j0 = 0; // add "dummy" worker 0
        vi dist(m, INT_MAX), pre(m, -1);
        vector<bool> done(m + 1);
        do { // dijkstra
            done[j0] = true;
            int i0 = p[j0], j1, delta = INT_MAX;
            rep(j, 1, m) if (!done[j]) {
                auto cur = a[i0 - 1][j - 1] - u[i0] - v[j];
                if (cur < dist[j]) dist[j] = cur, pre[j] = j0;
                if (dist[j] < delta) delta = dist[j], j1 = j;
            }
            rep(j, 0, m) {
                if (done[j]) u[p[j]] += delta, v[j] -= delta;
                else dist[j] -= delta;
            }
            j0 = j1;
        } while (p[j0]);
        while (j0) { // update alternating path
            int j1 = pre[j0];
            p[j0] = p[j1], j0 = j1;
        }
    }
    rep(j, 1, m) if (p[j]) ans[p[j] - 1] = j - 1;
    return {-v[0], ans}; // min cost
}
```

GeneralMatching.h

Description: Matching for general graphs. Fails with probability N/m .

Time: $\mathcal{O}\left(N^3\right)$ "numerical/MatrixInverse-mod.h" cb1912, 40 lines

```
vector<pii> generalMatching(int N, vector<pii>& ed) {
    vector<vector<ll>> mat(N, vector<ll>(N)), A;
    for (pii pa : ed) {
        int a = pa.first, b = pa.second, r = rand() % mod;
        mat[a][b] = r, mat[b][a] = (mod - r) % mod;
    }
}
```

```
int r = matInv(A = mat), M = 2*N - r, fi, fj;
assert(r % 2 == 0);
```

```
if (M != N) do {
    mat.resize(M, vector<ll>(M));
    rep(i, 0, N) {
        mat[i].resize(M);
        rep(j, N, M) {
            int r = rand() % mod;
            mat[i][j] = r, mat[j][i] = (mod - r) % mod;
        }
    }
} while (matInv(A = mat) != M);

vi has(M, 1); vector<pii> ret;
rep(it, 0, M/2) {
    rep(i, 0, M) if (has[i])
        rep(j, i+1, M) if (A[i][j] && mat[i][j]) {
            fi = i; fj = j; goto done;
        }
    assert(0); done:
    if (fj < N) ret.emplace_back(fi, fj);
    has[fi] = has[fj] = 0;
    rep(sw, 0, 2) {
        ll a = modpow(A[fi][fj], mod-2);
        rep(i, 0, M) if (has[i] && A[i][fj]) {
            ll b = A[i][fj] * a % mod;
            rep(j, 0, M) A[i][j] = (A[i][j] - A[fi][j] * b) % mod;
        }
        swap(fi, fj);
    }
}
return ret;
}
```

7.4 DFS algorithms

SCC.h

Description: Finds strongly connected components in a directed graph. If vertices u, v belong to the same component, we can reach u from v and vice versa.

Usage: scc(graph, [&](vi& v) { ... }) visits all components in reverse topological order. comp[i] holds the component index of a node (a component only has edges to components with lower index). ncomps will contain the number of components.

Time: $\mathcal{O}(E+V)$ 76b5c9, 24 lines

```
vi val, comp, z, cont;
int Time, ncomps;
template<class G, class F> int dfs(int j, G& g, F& f) {
    int low = val[j] = ++Time, x; z.push_back(j);
    for (auto e : g[j]) if (comp[e] < 0)
        low = min(low, val[e] ?: dfs(e, g, f));

    if (low == val[j]) {
        do {
            x = z.back(); z.pop_back();
            comp[x] = ncomps;
            cont.push_back(x);
        } while (x != j);
        f(cont); cont.clear();
        ncomps++;
    }
    return val[j] = low;
}

template<class G, class F> void scc(G& g, F f) {
    int n = sz(g);
    val.assign(n, 0); comp.assign(n, -1);
    Time = ncomps = 0;
    rep(i, 0, n) if (comp[i] < 0) dfs(i, g, f);
}
```

BiconnectedComponents.h

Description: Finds all biconnected components in an undirected graph, and runs a callback for the edges in each. In a biconnected component there are at least two internally disjoint paths between any two nodes (a cycle exists through them). Note that a node can be in several components. An edge which is not in a component is a bridge, i.e., not part of any cycle.

```
Usage: int eid = 0; ed.resize(N);
for each edge (a,b) {
ed[a].emplace_back(b, eid);
ed[b].emplace_back(a, eid++); }
bicomps [&] (const vi& edgelist) {...});
Time:  $\mathcal{O}(E + V)$ 
```

c6b7c7, 32 lines

```
vi num, st;
vector<vector<pii>> ed;
int Time;
template<class F>
int dfs(int at, int par, F& f) {
    int me = num[at] = ++Time, top = me;
    for (auto [y, e] : ed[at]) if (e != par) {
        if (num[y]) {
            top = min(top, num[y]);
            if (num[y] < me)
                st.push_back(e);
        } else {
            int si = sz(st);
            int up = dfs(y, e, f);
            top = min(top, up);
            if (up == me) {
                st.push_back(e);
                f(vi(st.begin() + si, st.end()));
                st.resize(si);
            }
            else if (up < me) st.push_back(e);
            else { /* e is a bridge */ }
        }
    }
    return top;
}
```

```
template<class F>
void bicomps(F f) {
    num.assign(sz(ed), 0);
    rep(i,0,sz(ed)) if (!num[i]) dfs(i, -1, f);
}
```

2sat.h

Description: Calculates a valid assignment to boolean variables a, b, c,... to a 2-SAT problem, so that an expression of the type $(a||b)\&\&(!a||c)\&\&(d||b)\&\&...$ becomes true, or reports that it is unsatisfiable. Negated variables are represented by bit-inversions (~x).

Usage: TwoSat ts(number of boolean variables);
ts.either(0, ~3); // Var 0 is true or var 3 is false
ts.setValue(2); // Var 2 is true
ts.atMostOne({0,~1,2}); // <= 1 of vars 0, ~1 and 2 are true
ts.solve(); // Returns true iff it is solvable
ts.values[0..N-1] holds the assigned values to the vars

Time: $\mathcal{O}(N + E)$, where N is the number of boolean variables, and E is the number of clauses.

5f9706, 56 lines

```
struct TwoSat {
    int N;
    vector<vi> gr;
    vi values; // 0 = false, 1 = true
```

```
TwoSat(int n = 0) : N(n), gr(2*n) {}
```

```
int addVar() { // (optional)
    gr.emplace_back();
    gr.emplace_back();
    return N++;
}
```

```
void either(int f, int j) {
    f = max(2*f, -1-2*f);
    j = max(2*j, -1-2*j);
    gr[f].push_back(j^1);
    gr[j].push_back(f^1);
}

void setValue(int x) { either(x, x); }
```

```
void atMostOne(const vi& li) { // (optional)
    if (sz(li) <= 1) return;
    int cur = ~li[0];
    rep(i,2,sz(li)) {
```

```
        int next = addVar();
        either(cur, ~li[i]);
        either(cur, next);
        either(~li[i], next);
        cur = ~next;
    }
    either(cur, ~li[1]);
}
```

```
vi val, comp, z; int time = 0;
int dfs(int i) {
    int low = val[i] = ++time, x; z.push_back(i);
    for(int e : gr[i]) if (!comp[e])
        low = min(low, val[e] ?: dfs(e));
    if (low == val[i]) do {
        x = z.back(); z.pop_back();
        comp[x] = low;
        if (values[x]>>1 == -1)
            values[x]>>1 = x&1;
    } while (x != i);
    return val[i] = low;
}
```

```
bool solve() {
    values.assign(N, -1);
    val.assign(2*N, 0); comp = val;
    rep(i,0,2*N) if (!comp[i]) dfs(i);
    rep(i,0,N) if (comp[2*i] == comp[2*i+1]) return 0;
    return 1;
}
```

EulerWalk.h

Description: Eulerian undirected/directed path/cycle algorithm. Input should be a vector of (dest, global edge index), where for undirected graphs, forward/backward edges have the same index. Returns a list of nodes in the Eulerian path/cycle with src at both start and end, or empty list if no cycle/path exists. To get edge indices back, add .second to s and ret.

Time: $\mathcal{O}(V + E)$

780b64, 15 lines

```
vi eulerWalk(vector<vector<pii>>& gr, int nedges, int src=0) {
    int n = sz(gr);
    vi D(n), its(n), eu(nedges), ret, s = {src};
    D[src]++; // to allow Euler paths, not just cycles
    while (!s.empty()) {
        int x = s.back(), y, e, &it = its[x], end = sz(gr[x]);
        if (it == end){ ret.push_back(x); s.pop_back(); continue; }
        tie(y, e) = gr[x][it++];
        if (!eu[e]) {
            D[x]--, D[y]++;
            eu[e] = 1; s.push_back(y);
        }
    }
    for (int x : D) if (x < 0 || sz(ret) != nedges+1) return {};
    return {ret.rbegin(), ret.rend()};
}
```

7.5 Coloring

EdgeColoring.h

Description: Given a simple, undirected graph with max degree D , computes a $(D + 1)$ -coloring of the edges such that no neighboring edges share a color. (D -coloring is NP-hard, but can be done for bipartite graphs by repeated matchings of max-degree nodes.)

Time: $\mathcal{O}(NM)$

e210e2, 31 lines

```
vi edgeColoring(int N, vector<pii> eds) {
    vi cc(N + 1), ret(sz(eds)), fan(N), free(N), loc;
    for (pii e : eds) ++cc[e.first], ++cc[e.second];
    int u, v, ncols = *max_element(all(cc)) + 1;
    vector<vi> adj(N, vi(ncols, -1));
    for (pii e : eds) {
        tie(u, v) = e;
        fan[0] = v;
        loc.assign(ncols, 0);
        int at = u, end = u, d, c = free[u], ind = 0, i = 0;
        while (d = free[v], !loc[d] && (v = adj[u][d]) != -1)
            loc[d] = ++ind, cc[ind] = d, fan[ind] = v;
        cc[loc[d]] = c;
        for (int cd = d; at != -1; cd ^= c ^ d, at = adj[at][cd])
```

```
        swap(adj[at][cd], adj[end = at][cd ^ c ^ d]);
        while (adj[fan[i]][d] != -1) {
            int left = fan[i], right = fan[++i], e = cc[i];
            adj[u][e] = left;
            adj[left][e] = u;
            adj[right][e] = -1;
            free[right] = e;
        }
        adj[u][d] = fan[i];
        adj[fan[i]][d] = u;
        for (int y : {fan[0], u, end})
            for (int& z = free[y] = 0; adj[y][z] != -1; z++);
    }
    rep(i,0,sz(eds))
        for (tie(u, v) = eds[i]; adj[u][ret[i]] != v;) ++ret[i];
    return ret;
}
```

7.6 Heuristics

MaximalCliques.h

Description: Runs a callback for all maximal cliques in a graph (given as a symmetric bitset matrix; self-edges not allowed). Callback is given a bitset representing the maximal clique.

Time: $\mathcal{O}\left(3^{n/3}\right)$, much faster for sparse graphs

b0d5b1, 12 lines

```
typedef bitset<128> B;
template<class F>
void cliques(vector<B>& eds, F f, B P = ~B(), B X={}, B R={}) {
    if (!P.any()) { if (!X.any()) f(R); return; }
    auto q = (P | X)._Find_first();
    auto cands = P & ~eds[q];
    rep(i,0,sz(eds)) if (cands[i]) {
        R[i] = 1;
        cliques(eds, f, P & eds[i], X & eds[i], R);
        R[i] = P[i] = 0; X[i] = 1;
    }
}
```

MaximumClique.h

Description: Quickly finds a maximum clique of a graph (given as symmetric bit-set matrix; self-edges not allowed). Can be used to find a maximum independent set by finding a clique of the complement graph.

Time: Runs in about 1s for n=155 and worst case random graphs (p=.90). Runs faster for sparse graphs.

f7c0bc, 49 lines

```
typedef vector<bitset<200>> vb;
struct Maxclique {
    double limit=0.025, pk=0;
    struct Vertex { int i, d=0; };
    typedef vector<Vertex> vv;
    vb e;
    vv V;
    vector<vi> C;
    vi qmax, q, S, old;
    void init(vv& r) {
        for (auto& v : r) v.d = 0;
        for (auto& v : r) for (auto j : r) v.d += e[v.i][j.i];
        sort(all(r), [](auto a, auto b) { return a.d > b.d; });
        int mxD = r[0].d;
        rep(i,0,sz(r)) r[i].d = min(i, mxD) + 1;
    }
    void expand(vv& R, int lev = 1) {
        S[lev] += S[lev - 1] - old[lev];
        old[lev] = S[lev - 1];
        while (sz(R)) {
            if (sz(q) + R.back().d <= sz(qmax)) return;
            q.push_back(R.back().i);
            vv T;
            for(auto v:R) if (e[R.back().i][v.i]) T.push_back({v.i});
            if (sz(T)) {
                if (S[lev]++ / ++pk < limit) init(T);
                int j = 0, mxk = 1, mnk = max(sz(qmax) - sz(q) + 1, 1);
                C[1].clear(), C[2].clear();
                for (auto v : T) {
                    int k = 1;
                    auto f = [&] (int i) { return e[v.i][i]; };
                    while (any_of(all(C[k]), f)) k++;
                    if (k > mxk) mxk = k, C[mxk + 1].clear();
```



```
        if (k < mnk) T[j++].i = v.i;
        C[k].push_back(v.i);
    }
    if (j > 0) T[j - 1].d = 0;
    rep(k, mnk, mxk + 1) for (int i : C[k])
        T[j].i = i, T[j++].d = k;
    expand(T, lev + 1);
} else if (sz(q) > sz(qmax)) qmax = q;
q.pop_back(), R.pop_back();
}
}
vi maxClique() { init(V), expand(V); return qmax; }
MaxClique(vb conn) : e(conn), C(sz(e)+1), S(sz(C)), old(S) {
    rep(i, 0, sz(e)) V.push_back({i});
}
};
```

MaximumIndependentSet.h

Description: To obtain a maximum independent set of a graph, find a max clique and LCAs. Assumes the root node points to itself.

Time: construction $\mathcal{O}(N \log N)$, queries $\mathcal{O}(\log N)$

```
vector<vi> treeJump(vi& P) {
    int on = 1, d = 1;
    while (on < sz(P)) on *= 2, d++;
    vector<vi> jmp(d, P);
    rep(i, 1, d) rep(j, 0, sz(P))
        jmp[i][j] = jmp[i-1][jmp[i-1][j]];
    return jmp;
}

int jmp(vector<vi>& tbl, int nod, int steps) {
    rep(i, 0, sz(tbl))
        if (steps & (1<<i)) nod = tbl[i][nod];
    return nod;
}
```

```
int lca(vector<vi>& tbl, vi& depth, int a, int b) {
    if (depth[a] < depth[b]) swap(a, b);
    a = jmp(tbl, a, depth[a] - depth[b]);
    if (a == b) return a;
    for (int i = sz(tbl); i--;) {
        int c = tbl[i][a], d = tbl[i][b];
        if (c != d) a = c, b = d;
    }
    return tbl[0][a];
}
```

```
vector<vi> treeJump(vi& P) {
    int on = 1, d = 1;
    while (on < sz(P)) on *= 2, d++;
    vector<vi> jmp(d, P);
    rep(i, 1, d) rep(j, 0, sz(P))
        jmp[i][j] = jmp[i-1][jmp[i-1][j]];
    return jmp;
}

int jmp(vector<vi>& tbl, int nod, int steps) {
    rep(i, 0, sz(tbl))
        if (steps & (1<<i)) nod = tbl[i][nod];
    return nod;
}
```

LCA.h

Description: Data structure for computing lowest common ancestors in a tree (with 0 as root). C should be an adjacency list of the tree, either directed or undirected.

Time: $\mathcal{O}(N \log N + Q)$

"/../data-structures/RMQ.h"

```
struct LCA {
    int T = 0;
    vi time, path, ret;
    RMQ<int> rmq;

    LCA(vector<vi>& C) : time(sz(C)), rmq((dfs(C, 0, -1), ret)) {}
    void dfs(vector<vi>& C, int v, int par) {
        time[v] = T++;
        for (int y : C[v]) if (y != par) {
            path.push_back(v), ret.push_back(time[v]);
            dfs(C, y, v);
        }
    }

    int lca(int a, int b) {
        if (a == b) return a;
        tie(a, b) = minmax(time[a], time[b]);
    }
};
```

```
return path[rmq.query(a, b)];
}
//dist(a,b){return depth[a] + depth[b] - 2*depth[lca(a,b)];}
};
```

CompressTree.h

Description: Given a rooted tree and a subset S of nodes, compute the minimal subtree that contains all the nodes by adding all (at most $|S| - 1$) pairwise LCA's and compressing edges. Returns a list of (par, orig_index) representing a tree rooted at 0. The root points to itself.

Time: $\mathcal{O}(|S| \log |S|)$

"LCA.h"

```
typedef vector<pair<int, int>> vpi;
vpi compressTree(LCA& lca, const vi& subset) {
    static vi rev; rev.resize(sz(lca.time));
    vi li = subset, &T = lca.time;
    auto cmp = [&](int a, int b) { return T[a] < T[b]; };
    sort(all(li), cmp);
    int m = sz(li)-1;
    rep(i, 0, m) {
        int a = li[i], b = li[i+1];
        li.push_back(lca.lca(a, b));
    }
    sort(all(li), cmp);
    li.erase(unique(all(li)), li.end());
    rep(i, 0, sz(li)) rev[li[i]] = i;
    vpi ret = {pii(0, li[0])};
    rep(i, 0, sz(li)-1) {
        int a = li[i], b = li[i+1];
        ret.emplace_back(rev[lca.lca(a, b)], b);
    }
    return ret;
}
};
```

HLD.h

Description: Decomposes a tree into vertex disjoint heavy paths and light edges such that the path from any leaf to the root contains at most $\log(n)$ light edges. Code does additive modifications and max queries, but can support commutative segtree modifications/queries on paths and subtrees. Takes as input the full adjacency list. VALS.EDGES being true means that values are stored in the edges, as opposed to the nodes. All values initialized to the segtree default. Root must be 0.

Time: $\mathcal{O}((\log N)^2)$

"/../data-structures/LazySegmentTree.h"

```
template <bool VALS_EDGES> struct HLD {
    int N, tim = 0;
    vector<vi> adj;
    vi par, siz, rt, pos;
    Node *tree;
    HLD(vector<vi> adj_)
        : N(sz(adj_)), adj(adj_), par(N, -1), siz(N, 1),
          rt(N), pos(N), tree(new Node(0, N)) { dfsSz(0); dfsHld(0); }
    void dfsSz(int v) {
        for (int& u : adj[v]) {
            adj[u].erase(find(all(adj[u]), v));
            par[u] = v;
            dfsSz(u);
            siz[v] += siz[u];
            if (siz[u] > siz[adj[v][0]]) swap(u, adj[v][0]);
        }
    }
    void dfsHld(int v) {
        pos[v] = tim++;
        for (int u : adj[v]) {
            rt[u] = (u == adj[v][0] ? rt[v] : u);
            dfsHld(u);
        }
    }
    template <class B> void process(int u, int v, B op) {
        for (; v = par[rt[v]]; ) {
            if (pos[u] > pos[v]) swap(u, v);
            if (rt[u] == rt[v]) break;
            op(pos[rt[v]], pos[v] + 1);
        }
        op(pos[u] + VALS_EDGES, pos[v] + 1);
    }
    void modifyPath(int u, int v, int val) {
        process(u, v, [&](int l, int r) { tree->add(l, r, val); });
    }
};
```

```
}
int queryPath(int u, int v) { // Modify depending on problem
    int res = -1e9;
    process(u, v, [&](int l, int r) {
        res = max(res, tree->query(l, r));
    });
    return res;
}
int querySubtree(int v) { // modifySubtree is similar
    return tree->query(pos[v] + VALS_EDGES, pos[v] + siz[v]);
}
};
```

LinkCutTree.h

Description: Represents a forest of unrooted trees. You can add and remove edges (as long as the result is still a forest), and check whether two nodes are in the same tree.

Time: All operations take amortized $\mathcal{O}(\log N)$.

```
struct Node { // Splay tree. Root's pp contains tree's parent.
    Node *p = 0, *pp = 0, *c[2];
    bool flip = 0;
    Node() { c[0] = c[1] = 0; fix(); }
    void fix() {
        if (c[0]) c[0]->p = this;
        if (c[1]) c[1]->p = this;
        // (+ update sum of subtree elements etc. if wanted)
    }
    void pushFlip() {
        if (!flip) return;
        flip = 0; swap(c[0], c[1]);
        if (c[0]) c[0]->flip ^= 1;
        if (c[1]) c[1]->flip ^= 1;
    }
    int up() { return p ? p->c[1] == this : -1; }
    void rot(int i, int b) {
        int h = i ^ b;
        Node *x = c[i], *y = b == 2 ? x : x->c[h], *z = b ? y : x;
        if ((y->p = p)) p->c[up()] = y;
        c[i] = z->c[i ^ 1];
        if (b < 2) {
            x->c[h] = y->c[h ^ 1];
            y->c[h ^ 1] = x;
        }
        z->c[i ^ 1] = this;
        fix(); x->fix(); y->fix();
        if (p) p->fix();
        swap(pp, y->pp);
    }
    void splay() {
        for (pushFlip(); p; ) {
            if (p->p) p->p->pushFlip();
            p->pushFlip(); pushFlip();
            int c1 = up(), c2 = p->up();
            if (c2 == -1) p->rot(c1, 2);
            else p->p->rot(c2, c1 != c2);
        }
    }
    Node* first() {
        pushFlip();
        return c[0] ? c[0]->first() : (splay(), this);
    }
};
```

```
struct LinkCut {
    vector<Node> node;
    LinkCut(int N) : node(N) {}

    void link(int u, int v) { // add an edge (u, v)
        assert(!connected(u, v));
        makeRoot(&node[u]);
        node[u].pp = &node[v];
    }
    void cut(int u, int v) { // remove an edge (u, v)
        Node *x = &node[u], *top = &node[v];
        makeRoot(top); x->splay();
        assert(top == (x->pp ? x->c[0]));
        if (x->pp) x->pp = 0;
        else {}
    }
};
```

```
x->c[0] = top->p = 0;
x->fix();
}
}
bool connected(int u, int v) { // are u, v in the same tree?
Node* nu = access(&node[u])->first();
return nu == access(&node[v])->first();
}
void makeRoot(Node* u) {
access(u);
u->splay();
if(u->c[0]) {
u->c[0]->p = 0;
u->c[0]->flip ^= 1;
u->c[0]->pp = u;
u->c[0] = 0;
u->fix();
}
}
Node* access(Node* u) {
u->splay();
while (Node* pp = u->pp) {
pp->splay(); u->pp = 0;
if (pp->c[1]) {
pp->c[1]->p = 0; pp->c[1]->pp = pp; }
pp->c[1] = u; pp->fix(); u = pp;
}
return u;
}
};
```

DirectedMST.h

Description: Finds a minimum spanning tree/arborescence of a directed graph, given a root node. If no MST exists, returns -1.

Time: $\mathcal{O}(E \log V)$

../data-structures/UnionFindRollback.h"	39e620, 60 lines
---	------------------

```
struct Edge { int a, b; ll w; };
struct Node {
Edge key;
Node *l, *r;
ll delta;
void prop() {
key.w += delta;
if (l) l->delta += delta;
if (r) r->delta += delta;
delta = 0;
}
Edge top() { prop(); return key; }
};
Node *merge(Node *a, Node *b) {
if (!a || !b) return a ? b;
a->prop(), b->prop();
if (a->key.w > b->key.w) swap(a, b);
swap(a->l, (a->r = merge(b, a->r)));
return a;
}
void pop(Node*& a) { a->prop(); a = merge(a->l, a->r); }
```

```
pair<ll, vi> dmst(int n, int r, vector<Edge>& g) {
RollbackUF uf(n);
vector<Node*> heap(n);
for (Edge e : g) heap[e.b] = merge(heap[e.b], new Node(e));
ll res = 0;
vi seen(n, -1), path(n), par(n);
seen[r] = r;
vector<Edge> Q(n), in(n, {-1,-1}), comp;
deque<tuple<int, int, vector<Edge>>> cycs;
rep(s,0,n) {
int u = s, qi = 0, w;
while (seen[u] < 0) {
if (!heap[u]) return {-1,{} };
Edge e = heap[u]->top();
heap[u]->delta -= e.w, pop(heap[u]);
Q[qi] = e, path[qi++] = u, seen[u] = s;
res += e.w, u = uf.find(e.a);
if (seen[u] == s) {
Node* cyc = 0;
int end = qi, time = uf.time();
```

```
do cyc = merge(cyc, heap[w = path[--qi]]);
while (uf.join(u, w));
u = uf.find(u), heap[u] = cyc, seen[u] = -1;
cycs.push_front({u, time, {&Q[qi], &Q[end]}));
}
}
rep(i,0,qi) in[uf.find(Q[i].b)] = Q[i];
}
for (auto& [u,t,comp] : cycs) { // restore sol (optional)
uf.rollback(t);
Edge inEdge = in[u];
for (auto& e : comp) in[uf.find(e.b)] = e;
in[uf.find(inEdge.b)] = inEdge;
}
rep(i,0,n) par[i] = in[i].a;
return {res, par};
}
```

7.8 Math

7.8.1 Number of Spanning Trees

Create an $N \times N$ matrix mat , and for each edge $a \rightarrow b \in G$, do $mat[a][b]--$, $mat[b][b]++$ (and $mat[b][a]--$, $mat[a][a]++$ if G is undirected). Remove the i th row and column and take the determinant; this yields the number of directed spanning trees rooted at i (if G is undirected, remove any row/column).

7.8.2 Erdős–Gallai theorem

A simple graph with node degrees $d_1 \geq \dots \geq d_n$ exists iff $d_1 + \dots + d_n$ is even and for every $k = 1 \dots n$,

$$\sum_{i=1}^k d_i \leq k(k-1) + \sum_{i=k+1}^n \min(d_i, k).$$

Geometry (8)

8.1 Geometric primitives

Point.h

Description: Class to handle points in the plane. T can be e.g. double or long long. (Avoid int.)


47ec0a, 28 lines

```
template <class T> int sgn(T x) { return (x > 0) - (x < 0); }
template<class T>
struct Point {
typedef Point P;
T x, y;
explicit Point(T x=0, T y=0) : x(x), y(y) {}
bool operator<(P p) const { return tie(x,y) < tie(p.x,p.y); }
bool operator==(P p) const { return tie(x,y)==tie(p.x,p.y); }
P operator+(P p) const { return P(x+p.x, y+p.y); }
P operator-(P p) const { return P(x-p.x, y-p.y); }
P operator*(T d) const { return P(x*d, y*d); }
P operator/(T d) const { return P(x/d, y/d); }
T dot(P p) const { return x*p.x + y*p.y; }
T cross(P p) const { return x*p.y - y*p.x; }
T cross(P a, P b) const { return (a->this->cross(b->this)); }
T dist2() const { return x*x + y*y; }
double dist() const { return sqrt((double)dist2()); }
// angle to x-axis in interval [-pi, pi]
double angle() const { return atan2(y, x); }
P unit() const { return *this/dist(); } // makes dist()==1
P perp() const { return P(-y, x); } // rotates +90 degrees
P normal() const { return perp().unit(); }
// returns point rotated 'a' radians ccw around the origin
P rotate(double a) const {
return P(x*cos(a)-y*sin(a),x*sin(a)+y*cos(a)); }
friend ostream& operator<<(ostream& os, P p) {
return os << "(" << p.x << ", " << p.y << ")"; }
};
```

lineDistance.h

Description:

Returns the signed distance between point p and the line containing points a and b . Positive value on left side and negative on right as seen from a towards b . $a==b$ gives nan. P is supposed to be `Point<T>` or `Point3D<T>` where T is e.g. double or long long. It uses products in intermediate steps so watch out for overflow if using int or long long. Using `Point3D` will always give a non-negative distance. For `Point3D`, call `.dist` on the result of the cross product.




```
template<class P>
double lineDist(const P& a, const P& b, const P& p) {
return (double) (b-a).cross(p-a) / (b-a).dist();
}
```

SegmentDistance.h

Description:

Returns the shortest distance between point p and the line segment from point s to e .
Usage: `Point<double> a, b(2,2), p(1,1);`
`bool onSegment = segDist(a,b,p) < 1e-10;`




```
typedef Point<double> P;
double segDist(P& s, P& e, P& p) {
if (s==e) return (p-s).dist();
auto d = (e-s).dist2(), t = min(d,max(.0, (p-s).dot(e-s)));
return ((p-s)*d-(e-s)*t).dist()/d;
}
```

SegmentIntersection.h

Description:

If a unique intersection point between the line segments going from $s1$ to $e1$ and from $s2$ to $e2$ exists then it is returned. If no intersection point exists an empty vector is returned. If infinitely many exist a vector with 2 elements is returned, containing the endpoints of the common line segment. The wrong position will be returned if P is `Point<ll>` and the intersection point does not have integer coordinates. Products of three coordinates are used in intermediate steps so watch out for overflow if using int or long long.
Usage: `vector<P> inter = segInter(s1,e1,s2,e2);`
if `(sz(inter)==1)`
`cout << "segments intersect at " << inter[0] << endl;`
if `(sz(inter)==1)`
`"Point.h", "OnSegment.h"`




```
template<class P> vector<P> segInter(P a, P b, P c, P d) {
auto oa = c.cross(d, a), ob = c.cross(d, b),
oc = a.cross(b, c), od = a.cross(b, d);
// Checks if intersection is single non-endpoint point.
if (sgn(oa) * sgn(ob) < 0 && sgn(oc) * sgn(od) < 0)
return {(a * ob - b * oa) / (ob - oa)};
set<P> s;
if (onSegment(c, d, a)) s.insert(a);
if (onSegment(c, d, b)) s.insert(b);
if (onSegment(a, b, c)) s.insert(c);
if (onSegment(a, b, d)) s.insert(d);
return {all(s)};
}
```

lineIntersection.h

Description:

If a unique intersection point of the lines going through $s1,e1$ and $s2,e2$ exists $\{1, point\}$ is returned. If no intersection point exists $\{0, (0,0)\}$ is returned and if infinitely many exists $\{-1, (0,0)\}$ is returned. The wrong position will be returned if P is `Point<ll>` and the intersection point does not have integer coordinates. Products of three coordinates are used in intermediate steps so watch out for overflow if using int or ll.
Usage: `auto res = lineInter(s1,e1,s2,e2);`
if `(res.first == 1)`
`cout << "intersection point at " << res.second << endl;`
if `(res.first == 1)`
`"Point.h"`



```
template<class P>
pair<int, P> lineInter(P s1, P e1, P s2, P e2) {
auto d = (e1 - s1).cross(e2 - s2);
if (d == 0) // if parallel
return {-(s1.cross(e1, s2) == 0), P(0, 0)};
auto p = s2.cross(e1, e2), q = s2.cross(e2, s1);
return {1, (s1 * p + e1 * q) / d};
}
```

}

sideOf.h

Description: Returns where p is as seen from s towards e . $1/0/-1 \Leftrightarrow$ left/on line/right. If the optional argument eps is given 0 is returned if p is within distance eps from the line. P is supposed to be `Point<T>` where T is e.g. double or long long. It uses products in intermediate steps so watch out for overflow if using int or long long.

Usage: `bool left = sideOf(p1,p2,q)==1;`

"Point.h" 3af81c, 9 lines

```
template<class P>
int sideOf(P s, P e, P p) { return sgn(s.cross(e, p)); }
```

```
template<class P>
int sideOf(const P& s, const P& e, const P& p, double eps) {
    auto a = (e-s).cross(p-s);
    double l = (e-s).dist()*eps;
    return (a > l) - (a < -l);
}
```

OnSegment.h

Description: Returns true iff p lies on the line segment from s to e . Use `(segDist(s,e,p)<=epsilon)` instead when using `Point<double>`.

"Point.h" c597e8, 3 lines

```
template<class P> bool onSegment(P s, P e, P p) {
    return p.cross(s, e) == 0 && (s - p).dot(e - p) <= 0;
}
```

linearTransformation.h

Description:

Apply the linear transformation (translation, rotation and scaling) which takes line $p0-p1$ to line $q0-q1$ to point r .

"Point.h" 03a306, 6 lines

```
typedef Point<double> P;
P linearTransformation(const P& p0, const P& p1,
    const P& q0, const P& q1, const P& r) {
    P dp = p1-p0, dq = q1-q0, num(dp.cross(dq), dp.dot(dq));
    return q0 + P((r-p0).cross(num), (r-p0).dot(num))/dp.dist2();
}
```

LineProjectionReflection.h

Description: Projects point p onto line ab . Set `refl=true` to get reflection of point p across line ab instead. The wrong point will be returned if P is an integer point and the desired point doesn't have integer coordinates. Products of three coordinates are used in intermediate steps so watch out for overflow.

"Point.h" b5562d, 5 lines

```
template<class P>
P lineProj(P a, P b, P p, bool refl=false) {
    P v = b - a;
    return p - v.perp()*(1+refl)*v.cross(p-a)/v.dist2();
}
```

Angle.h

Description: A class for ordering angles (as represented by int points and a number of rotations around the origin). Useful for rotational sweeping. Sometimes also represents points or vectors.

Usage: `vector<Angle> v = {w[0], w[0].t360() ...}; // sorted`

`int j = 0; rep(i,0,n) { while (v[j] < v[i].t180()) ++j; }`

// sweeps j such that $(j-i)$ represents the number of positively oriented triangles with vertices at 0 and i

"Point.h" 0f0602, 35 lines

```
struct Angle {
    int x, y;
    int t;
    Angle(int x, int y, int t=0) : x(x), y(y), t(t) {}
    Angle operator-(Angle b) const { return {x-b.x, y-b.y, t}; }
    int half() const {
        assert(x || y);
        return y < 0 || (y == 0 && x < 0);
    }
    Angle t90() const { return {-y, x, t + (half() && x >= 0)}; }
    Angle t180() const { return {-x, -y, t + half()}; }
    Angle t360() const { return {x, y, t + 1}; }
};
bool operator<(Angle a, Angle b) {
```

// add $a.dist2()$ and $b.dist2()$ to also compare distances

```
return make_tuple(a.t, a.half(), a.y * (ll)b.x) <
    make_tuple(b.t, b.half(), a.x * (ll)b.y);
}
```

// Given two points, this calculates the smallest angle between them, i.e., the angle that covers the defined line segment.

```
pair<Angle, Angle> segmentAngles(Angle a, Angle b) {
    if (b < a) swap(a, b);
    return (b < a.t180() ?
        make_pair(a, b) : make_pair(b, a.t360()));
}
```

Angle operator+(Angle a, Angle b) { // point $a + vector b$

Angle $r(a.x + b.x, a.y + b.y, a.t);$

if $(a.t180() < r)$ $r.t--;$

return $r.t180() < a$? $r.t360() : r;$

}

Angle angleDiff(Angle a, Angle b) { // angle $b - angle a$

int $tu = b.t - a.t; a.t = b.t;$

return $\{a.x*b.x + a.y*b.y, a.x*b.y - a.y*b.x, tu - (b < a)\};$

}

8.2 Circles

CircleIntersection.h

Description: Computes the pair of points at which two circles intersect. Returns false in case of no intersection.

"Point.h" 84d6d3, 11 lines

```
typedef Point<double> P;
bool circleInter(P a,P b,double r1,double r2,pair<P, P>* out) {
    if (a == b) { assert(r1 != r2); return false; }
    P vec = b - a;
    double d2 = vec.dist2(), sum = r1+r2, dif = r1-r2,
        p = (d2 + r1*r1 - r2*r2)/(d2*2), h2 = r1*r1 - p*p*d2;
    if (sum*sum < d2 || dif*dif > d2) return false;
    P mid = a + vec*p, per = vec.perp() * sqrt(fmax(0, h2) / d2);
    *out = {mid + per, mid - per};
    return true;
}
```

CircleTangents.h

Description: Finds the external tangents of two circles, or internal if $r2$ is negated. Can return 0, 1, or 2 tangents - 0 if one circle contains the other (or overlaps it, in the internal case, or if the circles are the same); 1 if the circles are tangent to each other (in which case `.first = .second` and the tangent line is perpendicular to the line between the centers). `.first` and `.second` give the tangency points at circle 1 and 2 respectively. To find the tangents of a circle with a point set $r2$ to 0.

"Point.h" b0153d, 13 lines

```
template<class P>
vector<pair<P, P>> tangents(P c1, double r1, P c2, double r2) {
    P d = c2 - c1;
    double dr = r1 - r2, d2 = d.dist2(), h2 = d2 - dr * dr;
    if (d2 == 0 || h2 < 0) return {};
    vector<pair<P, P>> out;
    for (double sign : {-1, 1}) {
        P v = (d * dr + d.perp() * sqrt(h2) * sign) / d2;
        out.push_back({c1 + v * r1, c2 + v * r2});
    }
    if (h2 == 0) out.pop_back();
    return out;
}
```

CircleLine.h

Description: Finds the intersection between a circle and a line. Returns a vector of either 0, 1, or 2 intersection points. P is intended to be `Point<double>`.

"Point.h" e0cfba, 9 lines

```
template<class P>
vector<P> circleLine(P c, double r, P a, P b) {
    P ab = b - a, p = a + ab * (c-a).dot(ab) / ab.dist2();
    double s = a.cross(b, c), h2 = r*r - s*s / ab.dist2();
    if (h2 < 0) return {};
    if (h2 == 0) return {p};
    P h = ab.unit() * sqrt(h2);
    return {p - h, p + h};
}
```

CirclePolygonIntersection.h

Description: Returns the area of the intersection of a circle with a ccw polygon.

Time: $O(n)$


"../content/geometry/Point.h" 19add1, 19 lines

```
typedef Point<double> P;
#define arg(p, q) atan2(p.cross(q), p.dot(q))
double circlePoly(P c, double r, vector<P> ps) {
    auto tri = [&](P p, P q) {
        auto r2 = r * r / 2;
        P d = q - p;
        auto a = d.dot(p)/d.dist2(), b = (p.dist2()-r*r)/d.dist2();
        auto det = a * a - b;
        if (det <= 0) return arg(p, q) * r2;
        auto s = max(0., -a-sqrt(det)), t = min(1., -a+sqrt(det));
        if (t < 0 || 1 <= s) return arg(p, q) * r2;
        P u = p + d * s, v = q + d * (t-1);
        return arg(p,u) * r2 + u.cross(v)/2 + arg(v,q) * r2;
    };
    auto sum = 0.0;
    rep(i,0,sz(ps))
        sum += tri(ps[i] - c, ps[(i + 1) % sz(ps)] - c);
    return sum;
}
```

circumcircle.h

Description:

The circumcircle of a triangle is the circle intersecting all three vertices. `ccRadius` returns the radius of the circle going through points A , B and C and `ccCenter` returns the center of the same circle.



"Point.h" 1caa3a, 9 lines

```
typedef Point<double> P;
double ccRadius(const P& A, const P& B, const P& C) {
    return (B-A).dist()*(C-B).dist()*(A-C).dist()/
        abs((B-A).cross(C-A))/2;
}
P ccCenter(const P& A, const P& B, const P& C) {
    P b = C-A, c = B-A;
    return A + (b*c.dist2()-c*b.dist2()).perp()/b.cross(c)/2;
}
```

MinimumEnclosingCircle.h

Description: Computes the minimum circle that encloses a set of points.

Time: expected $O(n)$

"circumcircle.h" 09dd0a, 17 lines

```
pair<P, double> mec(vector<P> ps) {
    shuffle(all(ps), mt19937(time(0)));
    P o = ps[0];
    double r = 0, EPS = 1 + 1e-8;
    rep(i,0,sz(ps)) if ((o - ps[i]).dist() > r * EPS) {
        o = ps[i], r = 0;
        rep(j,0,i) if ((o - ps[j]).dist() > r * EPS) {
            o = (ps[i] + ps[j]) / 2;
            r = (o - ps[i]).dist();
            rep(k,0,j) if ((o - ps[k]).dist() > r * EPS) {
                o = ccCenter(ps[i], ps[j], ps[k]);
                r = (o - ps[i]).dist();
            }
        }
    }
    return {o, r};
}
```

8.3 Polygons

InsidePolygon.h

Description: Returns true if p lies within the polygon. If strict is true, it returns false for points on the boundary. The algorithm uses products in intermediate steps so watch out for overflow.

Usage: `vector<P> v = {P{4,4}, P{1,2}, P{2,1}};`

`bool in = inPolygon(v, P{3, 3}, false);`

Time: $O(n)$

"Point.h", "OnSegment.h", "SegmentDistance.h" 2bf504, 11 lines

```
template<class P>
bool inPolygon(vector<P> &p, P a, bool strict = true) {
    int cnt = 0, n = sz(p);
```

```
rep(i,0,n) {
    P q = p[(i + 1) % n];
    if (onSegment(p[i], q, a)) return !strict;
    //or: if (segDist(p[i], q, a) <= eps) return !strict;
    cnt ^= ((a.y<p[i].y) - (a.y<q.y)) * a.cross(p[i], q) > 0;
}
return cnt;
}
```

PolygonArea.h

Description: Returns twice the signed area of a polygon. Clockwise enumeration gives negative area. Watch out for overflow if using int as T!

"Point.h"	f12300, 6 lines
template<class T>	
T polygonArea2(vector<Point<T>&& v) {	
T a = v.back().cross(v[0]);	
rep(i,0,sz(v)-1) a += v[i].cross(v[i+1]);	
return a;	
}	

PolygonCenter.h

Description: Returns the center of mass for a polygon.

Time: $\mathcal{O}(n)$

"Point.h"	9706dc, 9 lines
typedef Point<double> P;	
P polygonCenter(const vector<P>& v) {	
P res(0, 0); double A = 0;	
for (int i = 0, j = sz(v) - 1; i < sz(v); j = i++) {	
res = res + (v[i] + v[j]) * v[j].cross(v[i]);	
A += v[j].cross(v[i]);	
}	
return res / A / 3;	
}	

PolygonCut.h

Description:

Returns a vector with the vertices of a polygon with everything to the left of the line going from s to e cut away.

Usage: vector<P> p = ...;
p = polygonCut(p, P(0,0), P(1,0));

"Point.h"	d07181, 13 lines
typedef Point<double> P;	
vector<P> polygonCut(const vector<P>& poly, P s, P e) {	
vector<P> res;	
rep(i,0,sz(poly)) {	
P cur = poly[i], prev = i ? poly[i-1] : poly.back();	
auto a = s.cross(e, cur), b = s.cross(e, prev);	
if ((a < 0) != (b < 0))	
res.push_back(cur + (prev - cur) * (a / (a - b)));	
if (a < 0)	
res.push_back(cur);	
}	
return res;	
}	

PolygonUnion.h

Description: Calculates the area of the union of n polygons (not necessarily convex). The points within each polygon must be given in CCW order. (Epsilon checks may optionally be added to sideOf/sgn, but shouldn't be needed.)

Time: $\mathcal{O}(N^2)$, where N is the total number of points

"Point.h", "sideOf.h"	3931c6, 33 lines
typedef Point<double> P;	
double rat(P a, P b) { return sgn(b.x) ? a.x/b.x : a.y/b.y; }	
double polyUnion(vector<vector<P>&& poly) {	
double ret = 0;	
rep(i,0,sz(poly)) rep(v,0,sz(poly[i])) {	
P A = poly[i][v], B = poly[i][(v + 1) % sz(poly[i])];	
vector<pair<double, int>> segs = {{0, 0}, {1, 0}};	
rep(j,0,sz(poly)) if (i != j) {	
rep(u,0,sz(poly[j])) {	
P C = poly[j][u], D = poly[j][(u + 1) % sz(poly[j])];	
int sc = sideOf(A, B, C), sd = sideOf(A, B, D);	
if (sc != sd) {	
double sa = C.cross(D, A), sb = C.cross(D, B);	
if (min(sc, sd) < 0)	

```
segs.emplace_back(sa / (sa - sb), sgn(sc - sd));
} else if (!sc && !sd && j<i && sgn((B-A).dot(D-C))>0) {
    segs.emplace_back(rat(C - A, B - A), 1);
    segs.emplace_back(rat(D - A, B - A), -1);
}
}
}
sort(all(segs));
for (auto& s : segs) s.first = min(max(s.first, 0.0), 1.0);
double sum = 0;
int cnt = segs[0].second;
rep(j,1,sz(segs)) {
    if (!cnt) sum += segs[j].first - segs[j - 1].first;
    cnt += segs[j].second;
}
ret += A.cross(B) * sum;
}
return ret / 2;
}
```

ConvexHull.h

Description:

Returns a vector of the points of the convex hull in counter-clockwise order. Points on the edge of the hull between two other points are not considered part of the hull.

Time: $\mathcal{O}(n \log n)$

"Point.h"	310954, 13 lines
typedef Point<ll> P;	
vector<P> convexHull(vector<P> pts) {	
if (sz(pts) <= 1) return pts;	
sort(all(pts));	
vector<P> h(sz(pts)+1);	
int s = 0, t = 0;	
for (int it = 2; it--; s = --t, reverse(all(pts)))	
for (P p : pts) {	
while (t >= s + 2 && h[t-2].cross(h[t-1], p) <= 0) t--;	
h[t++] = p;	
}	
return {h.begin(), h.begin() + t - (t == 2 && h[0] == h[1])};	
}	



HullDiameter.h

Description: Returns the two points with max distance on a convex hull (ccw, no duplicate/collinear points).

Time: $\mathcal{O}(n)$

"Point.h"	c571b8, 12 lines
typedef Point<ll> P;	
array<P, 2> hullDiameter(vector<P> S) {	
int n = sz(S), j = n < 2 ? 0 : 1;	
pair<ll, array<P, 2>> res{{0, {S[0], S[0]}}};	
rep(i,0,j)	
for (; j = (j + 1) % n) {	
res = max(res, {{S[i] - S[j]}.dist2(), {S[i], S[j]}});	
if ({S[(j + 1) % n] - S[j]}.cross(S[i + 1] - S[i]) >= 0)	
break;	
}	
return res.second;	
}	

PointInsideHull.h

Description: Determine whether a point t lies inside a convex hull (CCW order, with no collinear points). Returns true if point lies within the hull. If strict is true, points on the boundary aren't included.

Time: $\mathcal{O}(\log N)$

"Point.h", "sideOf.h", "OnSegment.h"	71446b, 14 lines
typedef Point<ll> P;	
bool inHull(const vector<P>& l, P p, bool strict = true) {	
int a = 1, b = sz(l) - 1, r = !strict;	
if (sz(l) < 3) return r && onSegment(l[0], l.back(), p);	
if (sideOf(l[0], l[a], l[b]) > 0) swap(a, b);	
if (sideOf(l[0], l[a], p) >= r sideOf(l[0], l[b], p) <= -r)	
return false;	
while (abs(a - b) > 1) {	
int c = (a + b) / 2;	
(sideOf(l[0], l[c], p) > 0 ? b : a) = c;	
}	

```
return sgn(l[a].cross(l[b], p)) < r;
}
}
```

LineHullIntersection.h

Description: Line-convex polygon intersection. The polygon must be ccw and have no collinear points. lineHull(line, poly) returns a pair describing the intersection of a line with the polygon: $\bullet (-1, -1)$ if no collision, $\bullet (i, -1)$ if touching the corner i , $\bullet (i, i)$ if along side $(i, i + 1)$, $\bullet (i, j)$ if crossing sides $(i, i + 1)$ and $(j, j + 1)$. In the last case, if a corner i is crossed, this is treated as happening on side $(i, i + 1)$. The points are returned in the same order as the line hits the polygon. extrVertex returns the point of a hull with the max projection onto a line.

Time: $\mathcal{O}(\log n)$

"Point.h"	7cf45b, 39 lines
#define cmp(i,j) sgn(dir.perp().cross(poly[(i)%n]-poly[(j)%n]))	
#define extr(i) cmp(i + 1, i) >= 0 && cmp(i, i - 1 + n) < 0	
template <class P> int extrVertex(vector<P>& poly, P dir) {	
int n = sz(poly), lo = 0, hi = n;	
if (extr(0)) return 0;	
while (lo + 1 < hi) {	
int m = (lo + hi) / 2;	
if (extr(m)) return m;	
int ls = cmp(lo + 1, lo), ms = cmp(m + 1, m);	
(ls < ms (ls == ms && ls == cmp(lo, m)) ? hi : lo) = m;	
}	
return lo;	
}	

```
#define cmpL(i) sgn(a.cross(poly[i], b))
template <class P>
array<int, 2> lineHull(P a, P b, vector<P>& poly) {
    int endA = extrVertex(poly, (a - b).perp());
    int endB = extrVertex(poly, (b - a).perp());
    if (cmpL(endA) < 0 || cmpL(endB) > 0)
        return {-1, -1};
    array<int, 2> res;
    rep(i,0,2) {
        int lo = endB, hi = endA, n = sz(poly);
        while ((lo + 1) % n != hi) {
            int m = ((lo + hi + (lo < hi ? 0 : n)) / 2) % n;
            (cmpL(m) == cmpL(endB) ? lo : hi) = m;
        }
        res[i] = (lo + !cmpL(hi)) % n;
        swap(endA, endB);
    }
    if (res[0] == res[1]) return {res[0], -1};
    if (!cmpL(res[0]) && !cmpL(res[1]))
        switch ((res[0] - res[1] + sz(poly) + 1) % sz(poly)) {
            case 0: return {res[0], res[0]};
            case 2: return {res[1], res[1]};
        }
    return res;
}
```

8.4 Misc. Point Set Problems

ClosestPair.h

Description: Finds the closest pair of points.

Time: $\mathcal{O}(n \log n)$

"Point.h"	ac41a6, 17 lines
typedef Point<ll> P;	
pair<P, P> closest(vector<P> v) {	
assert(sz(v) > 1);	
set<P> S;	
sort(all(v), [](P a, P b) { return a.y < b.y; });	
pair<ll, pair<P, P>> ret{LLONG_MAX, {P(), P()}};	
int j = 0;	
for (P p : v) {	
P d(1 + (ll)sqrt(ret.first), 0);	
while (v[j].y <= p.y - d.x) S.erase(v[j++]);	
auto lo = S.lower_bound(p - d), hi = S.upper_bound(p + d);	
for (; lo != hi; ++lo)	
ret = min(ret, {(lo - p).dist2(), {lo, p}});	
S.insert(p);	
}	
return ret.second;	
}	

ManhattanMST.h

Description: Given N points, returns up to 4*N edges, which are guaranteed to contain a minimum spanning tree for the graph with edge weights $w(p, q) = |p.x - q.x| + |p.y - q.y|$. Edges are in the form (distance, src, dst). Use a standard MST algorithm on the result to find the final MST.

Time: $\mathcal{O}(N \log N)$
"Point.h" df6f59, 23 lines

```
typedef Point<int> P;
vector<array<int, 3>> manhattanMST(vector<P> ps) {
    vi id(sz(ps));
    iota(all(id), 0);
    vector<array<int, 3>> edges;
    rep(k,0,4) {
        sort(all(id), [&](int i, int j) {
            return (ps[i]-ps[j]).x < (ps[j]-ps[i]).y;});
        map<int, int> sweep;
        for (int i : id) {
            for (auto it = sweep.lower_bound(-ps[i].y);
                it != sweep.end(); sweep.erase(it++)) {
                int j = it->second;
                P d = ps[i] - ps[j];
                if (d.y > d.x) break;
                edges.push_back({d.y + d.x, i, j});
            }
            sweep[-ps[i].y] = i;
        }
        for (P& p : ps) if ((k & 1) p.x == -p.x; else swap(p.x, p.y));
    }
    return edges;
}
```

kdTree.h

Description: KD-tree (2d, can be extended to 3d)
"Point.h" bac5b0, 63 lines

```
typedef long long T;
typedef Point<T> P;
const T INF = numeric_limits<T>::max();
```

```
bool on_x(const P& a, const P& b) { return a.x < b.x; }
bool on_y(const P& a, const P& b) { return a.y < b.y; }
```

```
struct Node {
    P pt; // if this is a leaf, the single point in it
    T x0 = INF, x1 = -INF, y0 = INF, y1 = -INF; // bounds
    Node *first = 0, *second = 0;
```

```
    T distance(const P& p) { // min squared distance to a point
        T x = (p.x < x0 ? x0 : p.x > x1 ? x1 : p.x);
        T y = (p.y < y0 ? y0 : p.y > y1 ? y1 : p.y);
        return (P(x,y) - p).dist2();
    }
```

```
    Node(vector<P>&& vp) : pt(vp[0]) {
        for (P p : vp) {
            x0 = min(x0, p.x); x1 = max(x1, p.x);
            y0 = min(y0, p.y); y1 = max(y1, p.y);
        }
        if (vp.size() > 1) {
            // split on x if width >= height (not ideal...)
            sort(all(vp), x1 - x0 >= y1 - y0 ? on_x : on_y);
            // divide by taking half the array for each child (not
            // best performance with many duplicates in the middle)
            int half = sz(vp)/2;
            first = new Node({vp.begin(), vp.begin() + half});
            second = new Node({vp.begin() + half, vp.end()});
        }
    }
};
```

```
struct KDTree {
    Node* root;
    KDTree(const vector<P>& vp) : root(new Node({all(vp)})) {}

    pair<T, P> search(Node *node, const P& p) {
        if (!node->first) {
            // uncomment if we should not find the point itself:
            // if (p == node->pt) return {INF, P()};
            return make_pair((p - node->pt).dist2(), node->pt);
        }
```

```
    }

    Node *f = node->first, *s = node->second;
    T bfirst = f->distance(p), bsec = s->distance(p);
    if (bfirst > bsec) swap(bsec, bfirst), swap(f, s);

    // search closest side first, other side if needed
    auto best = search(f, p);
    if (bsec < best.first)
        best = min(best, search(s, p));
    return best;
}
```

```
// find nearest point to a point, and its squared distance
// (requires an arbitrary operator< for Point)
pair<T, P> nearest(const P& p) {
    return search(root, p);
}
```

DelaunayTriangulation.h

Description: Computes the Delaunay triangulation of a set of points. Each circumcircle contains none of the input points. If any three points are collinear or any four are on the same circle, behavior is undefined.

Time: $\mathcal{O}(n^2)$
"Point.h", "3dHull.h" c0e7bc, 10 lines

```
template<class P, class F>
void delaunay(vector<P>& ps, F trifun) {
    if (sz(ps) == 3) { int d = (ps[0].cross(ps[1], ps[2]) < 0);
        trifun(0,1+d,2-d); }
    vector<P3> p3;
    for (P p : ps) p3.emplace_back(p.x, p.y, p.dist2());
    if (sz(p3) > 3) for(auto t:hull3d(p3)) if ((p3[t.b]-p3[t.a]).
        cross(p3[t.c]-p3[t.a]).dot(P3(0,0,1)) < 0)
        trifun(t.a, t.c, t.b);
}
```

FastDelaunay.h

Description: Fast Delaunay triangulation. Each circumcircle contains none of the input points. There must be no duplicate points. If all points are on a line, no triangles will be returned. Should work for doubles as well, though there may be precision issues in 'circ'. Returns triangles in order {t[0][0], t[0][1], t[0][2], t[1][0], ...}, all counter-clockwise.

Time: $\mathcal{O}(n \log n)$
"Point.h" eefdf5, 88 lines

```
typedef Point<ll> P;
typedef struct Quad* Q;
typedef __int128_t l1l; // (can be ll if coords are < 2e4)
P arb(LLONG_MAX,LLONG_MAX); // not equal to any other point
```

```
struct Quad {
    Q rot, o; P p = arb; bool mark;
    P& F() { return r()->p; }
    Q& r() { return rot->rot; }
    Q prev() { return rot->o->rot; }
    Q next() { return r()->prev(); }
} *H;
```

```
bool circ(P p, P a, P b, P c) { // is p in the circumcircle?
    l1l p2 = p.dist2(), A = a.dist2()-p2,
        B = b.dist2()-p2, C = c.dist2()-p2;
    return p.cross(a,b)*C + p.cross(b,c)*A + p.cross(c,a)*B > 0;
}
Q makeEdge(P orig, P dest) {
    Q r = H ? H : new Quad{new Quad{new Quad{new Quad{0}}}};
    H = r->o; r->r()->r() = r;
    rep(i,0,4) r = r->rot, r->p = arb, r->o = i & 1 ? r : r->r();
    r->p = orig; r->F() = dest;
    return r;
}
void splice(Q a, Q b) {
    swap(a->o->rot->o, b->o->rot->o); swap(a->o, b->o);
}
Q connect(Q a, Q b) {
    Q q = makeEdge(a->F(), b->p);
    splice(q, a->next());
    splice(q->r(), b);
}
```

```
    return q;
}

pair<Q,Q> rec(const vector<P>& s) {
    if (sz(s) <= 3) {
        Q a = makeEdge(s[0], s[1]), b = makeEdge(s[1], s.back());
        if (sz(s) == 2) return { a, a->r() };
        splice(a->r(), b);
        auto side = s[0].cross(s[1], s[2]);
        Q c = side ? connect(b, a) : 0;
        return {side < 0 ? c->r() : a, side < 0 ? c : b->r() };
    }
```

```
#define H(e) e->F(), e->p
#define valid(e) (e->F().cross(H(base)) > 0)
Q A, B, ra, rb;
int half = sz(s) / 2;
tie(ra, A) = rec({all(s) - half});
tie(B, rb) = rec({sz(s) - half + all(s)});
while ((B->p.cross(H(A)) < 0 && (A = A->next()) ||
        (A->p.cross(H(B)) > 0 && (B = B->r()->o)));
Q base = connect(B->r(), A);
if (A->p == ra->p) ra = base->r();
if (B->p == rb->p) rb = base;
```

```
#define DEL(e, init, dir) Q e = init->dir; if (valid(e)) \
    while (circ(e->dir->F(), H(base), e->F())) { \
        Q t = e->dir; \
        splice(e, e->prev()); \
        splice(e->r(), e->r()->prev()); \
        e->o = H; H = e; e = t; \
    }
for (;;) {
    DEL(LC, base->r(), o); DEL(RC, base, prev());
    if (!valid(LC) && !valid(RC)) break;
    if (!valid(LC) || (valid(RC) && circ(H(RC), H(LC))))
        base = connect(RC, base->r());
    else
        base = connect(base->r(), LC->r());
}
return { ra, rb };
}
```

```
vector<P> triangulate(vector<P> pts) {
    sort(all(pts)); assert(unique(all(pts)) == pts.end());
    if (sz(pts) < 2) return {};
    Q e = rec(pts).first;
    vector<Q> q = {e};
    int qi = 0;
    while (e->o->F().cross(e->F(), e->p) < 0) e = e->o;
#define ADD { Q c = e; do { c->mark = 1; pts.push_back(c->p); \
    q.push_back(c->r()); c = c->next(); } while (c != e); }
    ADD; pts.clear();
    while (qi < sz(q)) if (!(e = q[qi++])->mark) ADD;
    return pts;
}
```

8.5 3D

PolyhedronVolume.h

Description: Magic formula for the volume of a polyhedron. Faces should point outwards.

```
template<class V, class L>
double signedPolyVolume(const V& p, const L& trilst) {
    double v = 0;
    for (auto i : trilst) v += p[i.a].cross(p[i.b]).dot(p[i.c]);
    return v / 6;
}
```

Point3D.h

Description: Class to handle points in 3D space. T can be e.g. double or long long.

```
template<class T> struct Point3D {
    typedef Point3D P;
    typedef const P& R;
    T x, y, z;
    explicit Point3D(T x=0, T y=0, T z=0) : x(x), y(y), z(z) {}
}
```

```
bool operator<(R p) const {
    return tie(x, y, z) < tie(p.x, p.y, p.z); }
bool operator==(R p) const {
    return tie(x, y, z) == tie(p.x, p.y, p.z); }
P operator+(R p) const { return P(x+p.x, y+p.y, z+p.z); }
P operator-(R p) const { return P(x-p.x, y-p.y, z-p.z); }
P operator*(T d) const { return P(x*d, y*d, z*d); }
P operator/(T d) const { return P(x/d, y/d, z/d); }
T dot(R p) const { return x*p.x + y*p.y + z*p.z; }
P cross(R p) const {
    return P(y*p.z - z*p.y, z*p.x - x*p.z, x*p.y - y*p.x);
}
T dist2() const { return x*x + y*y + z*z; }
double dist() const { return sqrt((double)dist2()); }
//Azimuthal angle (longitude) to x-axis in interval [-pi, pi]
double phi() const { return atan2(y, x); }
//Zenith angle (latitude) to the z-axis in interval [0, pi]
double theta() const { return atan2(sqrt(x*x+y*y),z); }
P unit() const { return *this/(T)dist(); } //makes dist()==1
//returns unit vector normal to *this and p
P normal(P p) const { return cross(p).unit(); }
//returns point rotated 'angle' radians ccw around axis
P rotate(double angle, P axis) const {
    double s = sin(angle), c = cos(angle); P u = axis.unit();
    return u*dot(u)*(1-c) + (*this)*c - cross(u)*s;
}
};
```

3dHull.h

Description: Computes all faces of the 3-dimension hull of a point set. *No four points must be coplanar*, or else random results will be returned. All faces will point outwards.

Time: $\mathcal{O}(n^2)$
"Point3D.h" 5b45fc, 49 lines

typedef Point3D<double> P3;

```
struct PR {
    void ins(int x) { (a == -1 ? a : b) = x; }
    void rem(int x) { (a == x ? a : b) = -1; }
    int cnt() { return (a != -1) + (b != -1); }
    int a, b;
};
```

struct F { P3 q; int a, b, c; };

```
vector<F> hull3d(const vector<P3>& A) {
    assert(sz(A) >= 4);
    vector<vector<PR>> E(sz(A), vector<PR>(sz(A), {-1, -1}));
```

```
#define E(x,y) E[f.x][f.y]
vector<F> FS;
auto mf = [&](int i, int j, int k, int l) {
    P3 q = (A[j] - A[i]).cross((A[k] - A[i]));
    if (q.dot(A[l]) > q.dot(A[i]))
        q = q * -1;
    F f{q, i, j, k};
    E(a,b).ins(k); E(a,c).ins(j); E(b,c).ins(i);
    FS.push_back(f);
};
```

```
rep(i,0,4) rep(j,i+1,4) rep(k,j+1,4)
    mf(i, j, k, 6 - i - j - k);
```

```
rep(i,4,sz(A)) {
    rep(j,0,sz(FS)) {
        F f = FS[j];
        if(f.q.dot(A[i]) > f.q.dot(A[f.a])) {
            E(a,b).rem(f.c);
            E(a,c).rem(f.b);
            E(b,c).rem(f.a);
            swap(FS[j--], FS.back());
            FS.pop_back();
        }
    }
    int nw = sz(FS);
    rep(j,0,nw) {
        F f = FS[j];
#define C(a, b, c) if (E(a,b).cnt() != 2) mf(f.a, f.b, i, f.c);
        C(a, b, c); C(a, c, b); C(b, c, a);
    }
}
```

```
}
for (F& it : FS) if ((A[it.b] - A[it.a]).cross(
    A[it.c] - A[it.a]).dot(it.q) <= 0) swap(it.c, it.b);
return FS;
};
```

sphericalDistance.h

Description: Returns the shortest distance on the sphere with radius radius between the points with azimuthal angles (longitude) f1 (ϕ_1) and f2 (ϕ_2) from x axis and zenith angles (latitude) t1 (θ_1) and t2 (θ_2) from z axis (0 = north pole). All angles measured in radians. The algorithm starts by converting the spherical co-ordinates to cartesian coordinates so if that is what you have you can use only the two last rows. dx*radius is then the difference between the two points in the x direction and d*radius is the total distance between the points. 611f07, 8 lines

```
double sphericalDistance(double f1, double t1,
    double f2, double t2, double radius) {
    double dx = sin(t2)*cos(f2) - sin(t1)*cos(f1);
    double dy = sin(t2)*sin(f2) - sin(t1)*sin(f1);
    double dz = cos(t2) - cos(t1);
    double d = sqrt(dx*dx + dy*dy + dz*dz);
    return radius*2*asin(d/2);
}
```

Strings (9)

Trie.h

Description: This trie has the regular trie features but also an additional walk id that you can use to walk on the trie. You can treat it as a text editor; use the operations append(c) and backspace() to walk on the trie, or directly edit the walk id variable (dangerous). 25939c, 88 lines

```
struct trie_basic {
    const static int ALPHA = 94;
    int f(int x) { // function that converts character to id
        return x - 33;
    }
    struct node {
        int contains_as_prefix = 0;
        int contains_as_word = 0;
        vector<int> child = vector<int>(ALPHA, -1);
        int parent = -1;
        int len = 0;
    } emptynode;
    int walk_id = 0;
    vector<node> v = {emptynode};
    int new_node(int parent_id) { // Creates a new node and returns its id
        int id = v.size();
        v.push_back(emptynode);
        v[id].parent = parent_id;
        v[id].len = v[parent_id].len + 1;
        return id;
    }
    void insert(string str) {
        vector<int> seq;
        for (char c: str) seq.push_back(f(c));
        int cur = 0;
        v[cur].contains_as_prefix++;
        for (int x: seq) {
            if (v[cur].child[x] == -1) {
                v[cur].child[x] = new_node(cur);
            }
            cur = v[cur].child[x];
            v[cur].contains_as_prefix++;
        }
        v[cur].contains_as_word++;
    }
    void erase(string str) {
        vector<int> seq;
        for (char c: str) seq.push_back(f(c));
        int cur = 0;
        v[cur].contains_as_prefix--;
        for (int x: seq) {
            if (v[cur].child[x] == -1) {
                v[cur].child[x] = new_node(cur);
            }
        }
    }
}
```

```
cur = v[cur].child[x];
v[cur].contains_as_prefix--;
}
v[cur].contains_as_word--;
}
void append(char c) {
    if (v[walk_id].child[f(c)] == -1) {
        v[walk_id].child[f(c)] = new_node(walk_id);
    }
    walk_id = v[walk_id].child[f(c)];
}
bool backspace() {
    if (walk_id == 0) return 0;
    walk_id = v[walk_id].parent;
    return 1;
}
int query_asPrefix(string str) { // str is a prefix of how many strings in the trie?
    int save = walk_id;
    walk_id = 0;
    for (char c: str) append(c);
    int ans = v[walk_id].contains_as_prefix;
    walk_id = save;
    return ans;
}
int query_asSuffix(string str) { // str is a suffix of how many strings in the trie?
    int save = walk_id;
    walk_id = 0;
    int ans = v[walk_id].contains_as_word;
    for (char c: str) {
        append(c);
        ans += v[walk_id].contains_as_word;
    }
    walk_id = save;
    return ans;
}
int query_count(string str) {
    int save = walk_id;
    walk_id = 0;
    for (char c: str) append(c);
    int ans = v[walk_id].contains_as_word;
    walk_id = save;
    return ans;
}
};
```

KMP.h

Description: pi[x] computes the length of the longest prefix of s that ends at x, other than s[0...x] itself (abacaba -> 0010123). Can be used to find all occurrences of a string.

Time: $\mathcal{O}(n)$ d4375c, 16 lines

```
vi pi(const string& s) {
    vi p(sz(s));
    rep(i,1,sz(s)) {
        int g = p[i-1];
        while (g && s[i] != s[g]) g = p[g-1];
        p[i] = g + (s[i] == s[g]);
    }
    return p;
}
```

```
vi match(const string& s, const string& pat) {
    vi p = pi(pat + '\0' + s), res;
    rep(i,sz(p)-sz(s),sz(p))
        if (p[i] == sz(pat)) res.push_back(i - 2 * sz(pat));
    return res;
}
```

Zfunc.h

Description: z[i] computes the length of the longest common prefix of s[i:] and s, except z[0] = 0. (abacaba -> 0010301)

Time: $\mathcal{O}(n)$ ee09e2, 12 lines

```
vi Z(const string& S) {
    vi z(sz(S));
    int l = -1, r = -1;
    rep(i,1,sz(S)) {
```

```
z[i] = i >= r ? 0 : min(r - i, z[i - 1]);
while (i + z[i] < sz(S) && S[i + z[i]] == S[z[i]])
    z[i]++;
if (i + z[i] > r)
    l = i, r = i + z[i];
}
return z;
}
```

Manacher.h

Description: For each position in a string, computes p[0][i] = half length of longest even palindrome around pos i, p[1][i] = longest odd (half rounded down).
Time: $\mathcal{O}(N)$

```
array<vi, 2> manacher(const string& s) {
    int n = sz(s);
    array<vi,2> p = {vi(n+1), vi(n)};
    rep(z,0,2) for (int i=0,l=0,r=0; i < n; i++) {
        int t = r-i+!z;
        if (i<r) p[z][i] = min(t, p[z][l+t]);
        int L = i-p[z][i], R = i+p[z][i]-!z;
        while (L>=1 && R+1<n && s[L-1] == s[R+1])
            p[z][i]++, L--, R++;
        if (R>r) l=L, r=R;
    }
    return p;
}
```

MinRotation.h

Description: Finds the lexicographically smallest rotation of a string.
Usage: rotate(v.begin(), v.begin()+minRotation(v), v.end());
Time: $\mathcal{O}(N)$

```
int minRotation(string s) {
    int a=0, N=sz(s); s += s;
    rep(b,0,N) rep(k,0,N) {
        if (a+k == b || s[a+k] < s[b+k]) {b += max(0, k-1); break;}
        if (s[a+k] > s[b+k]) { a = b; break; }
    }
    return a;
}
```

SuffixArray.h

Description: Builds suffix array for a string. sa[i] is the starting index of the suffix which is i'th in the sorted suffix array. The returned vector is of size n + 1, and sa[0] = n. The lcp array contains longest common prefixes for neighbouring strings in the suffix array: lcp[i] = lcp(sa[i], sa[i-1]), lcp[0] = 0. The input string must not contain any nul chars.
Time: $\mathcal{O}(n \log n)$

```
struct SuffixArray {
    vi sa, lcp;
    SuffixArray(string s, int lim=256) { // or vector<int>
        s.push_back(0); int n = sz(s), k = 0, a, b;
        vi x(all(s)), y(n), ws(max(n, lim));
        sa = lcp = y, iota(all(sa), 0);
        for (int j = 0, p = 0; p < n; j = max(1, j * 2), lim = p) {
            p = j, iota(all(y), n - j);
            rep(i,0,n) if (sa[i] >= j) y[p++] = sa[i] - j;
            fill(all(ws), 0);
            rep(i,0,n) ws[x[i]]++;
            rep(i,1,lim) ws[i] += ws[i - 1];
            for (int i = n; i--;) sa[--ws[x[y[i]]]] = y[i];
            swap(x, y), p = 1, x[sa[0]] = 0;
            rep(i,1,n) a = sa[i - 1], b = sa[i], x[b] =
                (y[a] == y[b] && y[a + j] == y[b + j]) ? p - 1 : p++;
        }
        for (int i = 0, j; i < n - 1; lcp[x[i+]] = k)
            for (k && k--, j = sa[x[i] - 1];
                s[i + k] == s[j + k]; k++);
    }
};
```

SuffixTree.h

Description: Ukkonen's algorithm for online suffix tree construction. Each node contains indices [l, r] into the string, and a list of child nodes. Suffixes are given by traversals of this tree, joining [l, r] substrings. The root is 0 (has l = -1, r = 0), non-existent children are -1. To get a complete tree, append a dummy symbol – otherwise it may contain an incomplete path (still useful for substring matching, though).
Time: $\mathcal{O}(26N)$

```
struct SuffixTree {
    enum { N = 200010, ALPHA = 26 }; // N ~ 2*maxlen+10
    int toi(char c) { return c - 'a'; }
    string a; // v = cur node, q = cur position
    int t[N][ALPHA], l[N], r[N], p[N], s[N], v=0, q=0, m=2;

    void ukkadd(int i, int c) { suff:
        if (r[v]<=q) {
            if (t[v][c]==-1) { t[v][c]=m; l[m]=i;
                p[m+]=v; v=s[v]; q=r[v]; goto suff; }
            v=t[v][c]; q=l[v];
        }
        if (q==-1 || c==toi(a[q])) q++; else {
            l[m+1]=i; p[m+1]=m; l[m]=l[v]; r[m]=q;
            p[m]=p[v]; t[m][c]=m+1; t[m][toi(a[q])]=v;
            l[v]=q; p[v]=m; t[p[m]][toi(a[l[m]])]=m;
            v=s[p[m]]; q=l[m];
            while (q<r[m]) { v=t[v][toi(a[q])]; q+=r[v]-l[v]; }
            if (q==r[m]) s[m]=v; else s[m]=m+2;
            q=r[v]-(q-r[m]); m+=2; goto suff;
        }
    }

    SuffixTree(string a) : a(a) {
        fill(r,r+N,sz(a));
        memset(s, 0, sizeof s);
        memset(t, -1, sizeof t);
        fill(t[1],t[1]+ALPHA,0);
        s[0] = 1; l[0] = l[1] = -1; r[0] = r[1] = p[0] = p[1] = 0;
        rep(i,0,sz(a)) ukkadd(i, toi(a[i]));
    }

    // example: find longest common substring (uses ALPHA = 28)
    pii best;
    int lcs(int node, int i1, int i2, int olen) {
        if (l[node] <= i1 && i1 < r[node]) return 1;
        if (l[node] <= i2 && i2 < r[node]) return 2;
        int mask = 0, len = node ? olen + (r[node] - l[node]) : 0;
        rep(c,0,ALPHA) if (t[node][c] != -1)
            mask |= lcs(t[node][c], i1, i2, len);
        if (mask == 3)
            best = max(best, {len, r[node] - len});
        return mask;
    }

    static pii LCS(string s, string t) {
        SuffixTree st(s + (char)('z' + 1) + t + (char)('z' + 2));
        st.lcs(0, sz(s), sz(s) + 1 + sz(t), 0);
        return st.best;
    }
};
```

SuffixAutomaton.h

Description: Suffix Automaton data structure.
Time: $\mathcal{O}(n \log k)$, where k = size of alphabet.

```
struct SuffixAutomaton {
    struct state {
        int len, link;
        map<char, int> next;
    };
    vector<state> st;
    int n, sz = 0, last = 0; // Use sz for number of characters added
    SuffixAutomaton(int n) {
        this->n = n;
        st.resize(2 * n + 6);
        st[0].len = 0;
        st[0].link = -1;
        sz++;
        last = 0;
    }
    void extend(char c) {
```

```
int cur = sz++;
st[cur].len = st[last].len + 1;
int p = last;
while (p != -1 && !st[p].next.count(c)) {
    st[p].next[c] = cur;
    p = st[p].link;
}
if (p == -1) {
    st[cur].link = 0;
} else {
    int q = st[p].next[c];
    if (st[p].len + 1 == st[q].len) {
        st[cur].link = q;
    } else {
        int clone = sz++;
        st[clone].len = st[p].len + 1;
        st[clone].next = st[q].next;
        st[clone].link = st[q].link;
        while (p != -1 && st[p].next[c] == q) {
            st[p].next[c] = clone;
            p = st[p].link;
        }
        st[q].link = st[cur].link = clone;
    }
    last = cur;
}
SuffixAutomaton(string s) {
    *this = SuffixAutomaton(sz(s));
    for (char c: s) extend(c);
}
};
```

Hashing.h

Description: Self-explanatory methods for string hashing. 2d2a67, 44 lines

// Arithmetic mod $2^{64}-1$. 2x slower than mod 2^{64} and more
// code, but works on evil test data (e.g. Thue–Morse, where
// ABBA... and BAAB... of length 2^{10} hash the same mod 2^{64}).
// "typedef ull H;" instead if you think test data is random,
// or work mod 10^9+7 if the Birthday paradox is not a problem.
typedef uint64_t ull;
struct H {
 ull x; H(ull x=0) : x(x) {}
 H operator+(H o) { return x + o.x + (x + o.x < x); }
 H operator-(H o) { return *this + ~o.x; }
 H operator*(H o) { auto m = (__uint128_t)x * o.x;
 return H((ull)m) + (ull)(m >> 64); }
 ull get() const { return x + !~x; }
 bool operator==(H o) const { return get() == o.get(); }
 bool operator<(H o) const { return get() < o.get(); }
};
static const H C = (1ll)1e11+3; // (order ~ 3e9; random also ok)

```
struct HashInterval {
    vector<H> ha, pw;
    HashInterval(string& str) : ha(sz(str)+1), pw(ha) {
        pw[0] = 1;
        rep(i,0,sz(str))
            ha[i+1] = ha[i] * C + str[i],
            pw[i+1] = pw[i] * C;
    }
    H hashInterval(int a, int b) { // hash [a, b)
        return ha[b] - ha[a] * pw[b - a];
    }
};

vector<H> getHashes(string& str, int length) {
    if (sz(str) < length) return {};  
    H h = 0, pw = 1;  
    rep(i,0,length)  
        h = h * C + str[i], pw = pw * C;  
    vector<H> ret = {h};  
    rep(i,length,sz(str)) {  
        ret.push_back(h = h * C + str[i] - pw * str[i-length]);  
    }  
    return ret;
}
```



```
H hashString(string& s){H h{}; for(char c:s) h=h*C+C;return h;}
```

HashString.h

Description: String (multi-)hashing. init(s) if you want to use single hashing; init(s, k) if you want to use k-hashing, for k at most 5.

Time: $\mathcal{O}(kn)$. 029c02, 43 lines

```
struct HashString {
    // all indices are ZERO-BASED
    const int fac[5] = {2017, 211, 269, 397, 691};
    const int MOD[5] = {1734232211, 1000000009, 874803863, 909739993,
        1388999387};
    vector<int> pau[5], ps[5];
    int n, k_;
    void init(string s, int k = 1) {
        k_ = k;
        n = s.size();
        for (int it=0; it<k; it++) {
            pau[it].push_back(1);
            for(int i=1; i<=n; i++) {
                pau[it].push_back((pau[it][i-1] * fac[it]) % MOD[it]);
            }
            ps[it].push_back(s[0]);
            for(int i=1; i<n; i++) {
                ps[it].push_back((ps[it][i-1] * fac[it] + s[i]) % MOD[it]
                    ));
            }
        }
    }
    int eval(int l, int r) {
        int ans = 0;
        for (int i=0; i<k_; i++) {
            int val = (ps[i][r] - (l == 0 ? 0 : (ps[i][l-1] * pau[i][r-l
                +1]) % MOD[i]) + MOD[i]) % MOD[i];
            ans ^= (val * (i + 1));
        }
        return ans;
    }
    vector<int> fulleval(int l, int r) {
        vector<int> v;
        for (int i=0; i<k_; i++) {
            int val = (ps[i][r] - (l == 0 ? 0 : (ps[i][l-1] * pau[i][r-l
                +1]) % MOD[i]) + MOD[i]) % MOD[i];
            v.push_back(val);
        }
        return v;
    }
    int get_hash() {
        return eval(0, n - 1);
    }
    vector<int> get_fullhash() {
        return fulleval(0, n-1);
    }
};
```

AhoCorasick.h

Description: Aho-Corasick automaton, used for multiple pattern matching. Initialize with AhoCorasick ac(patterns); the automaton start node will be at index 0. find(word) returns for each position the index of the longest word that ends there, or -1 if none. findAll(−, word) finds all words (up to $N\sqrt{N}$ many if no duplicate patterns) that start at each position (shortest first). Duplicate patterns are allowed; empty patterns are not. To find the longest words that start at each position, reverse all input. For large alphabets, split each symbol into chunks, with sentinel bits for symbol boundaries.

Time: construction takes $\mathcal{O}(26N)$, where N = sum of length of patterns. find(x) is $\mathcal{O}(N)$, where N = length of x. findAll is $\mathcal{O}(NM)$. f35677, 66 lines

```
struct AhoCorasick {
    enum {alpha = 26, first = 'A'}; // change this!
    struct Node {
        // (nmatches is optional)
        int back, next[alpha], start = -1, end = -1, nmatches = 0;
        Node(int v) { memset(next, v, sizeof(next)); }
    };
    vector<Node> N;
    vi backp;
    void insert(string& s, int j) {
        assert(!s.empty());
        int n = 0;
```

```
for (char c : s) {
    int& m = N[n].next[c - first];
    if (m == -1) { n = m = sz(N); N.emplace_back(-1); }
    else n = m;
}
if (N[n].end == -1) N[n].start = j;
backp.push_back(N[n].end);
N[n].end = j;
N[n].nmatches++;
}
AhoCorasick(vector<string>& pat) : N(1, -1) {
    rep(i,0,sz(pat)) insert(pat[i], i);
    N[0].back = sz(N);
    N.emplace_back(0);

    queue<int> q;
    for (q.push(0); !q.empty(); q.pop()) {
        int n = q.front(), prev = N[n].back;
        rep(i,0,alpha) {
            int &ed = N[n].next[i], y = N[prev].next[i];
            if (ed == -1) ed = y;
            else {
                N[ed].back = y;
                N[ed].end == -1 ? N[ed].end : backp[N[ed].start]
                    = N[y].end;
                N[ed].nmatches += N[y].nmatches;
                q.push(ed);
            }
        }
    }
}
vi find(string word) {
    int n = 0;
    vi res; // ll count = 0;
    for (char c : word) {
        n = N[n].next[c - first];
        res.push_back(N[n].end);
        // count += N[n].nmatches;
    }
    return res;
}
vector<vi> findAll(vector<string>& pat, string word) {
    vi r = find(word);
    vector<vi> res(sz(word));
    rep(i,0,sz(word)) {
        int ind = r[i];
        while (ind != -1) {
            res[i - sz(pat[ind]) + 1].push_back(ind);
            ind = backp[ind];
        }
    }
    return res;
}
};
```

Various (10)

10.1 Intervals

IntervalContainer.h

Description: Add and remove intervals from a set of disjoint intervals. Will merge the added interval with any overlapping intervals in the set when adding. Intervals are [inclusive, exclusive).

Time: $\mathcal{O}(\log N)$ edce47, 23 lines

```
set<pii>::iterator addInterval(set<pii>& is, int L, int R) {
    if (L == R) return is.end();
    auto it = is.lower_bound({L, R}), before = it;
    while (it != is.end() && it->first <= R) {
        R = max(R, it->second);
        before = it = is.erase(it);
    }
    if (it != is.begin() && (--it)->second >= L) {
        L = min(L, it->first);
        R = max(R, it->second);
        is.erase(it);
    }
}
```

```
return is.insert(before, {L,R});
}
```

```
void removeInterval(set<pii>& is, int L, int R) {
    if (L == R) return;
    auto it = addInterval(is, L, R);
    auto r2 = it->second;
    if (it->first == L) is.erase(it);
    else (int&)it->second = L;
    if (R != r2) is.emplace(R, r2);
}
```

IntervalCover.h

Description: Compute indices of smallest set of intervals covering another interval. Intervals should be [inclusive, exclusive). To support [inclusive, inclusive], change (A) to add || R.empty(). Returns empty set on failure (or if G is empty).

Time: $\mathcal{O}(N \log N)$ 9e9d8d, 19 lines

```
template<class T>
vi cover(pair<T, T> G, vector<pair<T, T>> I) {
    vi S(sz(I)), R;
    iota(all(S), 0);
    sort(all(S), [&](int a, int b) { return I[a] < I[b]; });
    T cur = G.first;
    int at = 0;
    while (cur < G.second) { // (A)
        pair<T, int> mx = make_pair(cur, -1);
        while (at < sz(I) && I[S[at]].first <= cur) {
            mx = max(mx, make_pair(I[S[at]].second, S[at]));
            at++;
        }
        if (mx.second == -1) return {};
        cur = mx.first;
        R.push_back(mx.second);
    }
    return R;
}
```

ConstantIntervals.h

Description: Split a monotone function on [from, to) into a minimal set of half-open intervals on which it has the same value. Runs a callback g for each such interval.

Usage: constantIntervals(0, sz(v), [&](int x){return v[x];}, [&](int lo, int hi, T val){...});

Time: $\mathcal{O}\left(k \log \frac{n}{k}\right)$ 753a4c, 19 lines

```
template<class F, class G, class T>
void rec(int from, int to, F& f, G& g, int& i, T& p, T q) {
    if (p == q) return;
    if (from == to) {
        g(i, to, p);
        i = to; p = q;
    } else {
        int mid = (from + to) >> 1;
        rec(from, mid, f, g, i, p, f(mid));
        rec(mid+1, to, f, g, i, p, q);
    }
}
template<class F, class G>
void constantIntervals(int from, int to, F f, G g) {
    if (to <= from) return;
    int i = from; auto p = f(i), q = f(to-1);
    rec(from, to-1, f, g, i, p, q);
    g(i, to, q);
}
```

10.2 Misc. algorithms

TernarySearch.h

Description: Find the smallest i in $[a, b]$ that maximizes $f(i)$, assuming that $f(a) < \dots < f(i) \geq \dots \geq f(b)$. To reverse which of the sides allows non-strict inequalities, change the < marked with (A) to <=, and reverse the loop at (B). To minimize f, change it to >, also at (B).

Usage: int ind = ternSearch(0,n-1,[&](int i){return a[i];});

Time: $\mathcal{O}(\log(b - a))$ 9155b4, 11 lines

```
template<class F>
int ternSearch(int a, int b, F f) {
    assert(a <= b);
```



```
while (b - a >= 5) {
    int mid = (a + b) / 2;
    if (f(mid) < f(mid+1)) a = mid; // (A)
    else b = mid+1;
}
rep(i,a+1,b+1) if (f(a) < f(i)) a = i; // (B)
return a;
}
```

LIS.h
Description: Compute indices for the longest increasing subsequence.
Time: $\mathcal{O}(N \log N)$ 2932a0, 17 lines

```
template<class I> vi lis(const vector<I>& S) {
    if (S.empty()) return {};
    vi prev(sz(S));
    typedef pair<I, int> p;
    vector<p> res;
    rep(i,0,sz(S)) {
        // change 0 → i for longest non-decreasing subsequence
        auto it = lower_bound(all(res), p{S[i], 0});
        if (it == res.end()) res.emplace_back(), it = res.end()-1;
        *it = {S[i], i};
        prev[i] = it == res.begin() ? 0 : (it-1)->second;
    }
    int L = sz(res), cur = res.back().second;
    vi ans(L);
    while (L--) ans[L] = cur, cur = prev[cur];
    return ans;
}
```

FastKnapsack.h
Description: Given N non-negative integer weights w and a non-negative target t, computes the maximum S ≤ t such that S is the sum of some subset of the weights.
Time: $\mathcal{O}(N \max(w_i))$ b20ccc, 16 lines

```
int knapsack(vi w, int t) {
    int a = 0, b = 0, x;
    while (b < sz(w) && a + w[b] <= t) a += w[b++];
    if (b == sz(w)) return a;
    int m = *max_element(all(w));
    vi u, v(2*m, -1);
    v[a+m-t] = b;
    rep(i,b,sz(w)) {
        u = v;
        rep(x,0,m) v[x+w[i]] = max(v[x+w[i]], u[x]);
        for (x = 2*m; --x > m;) rep(j, max(0,u[x]), v[x])
            v[x-w[j]] = max(v[x-w[j]], j);
    }
    for (a = t; v[a+m-t] < 0; a--) ;
    return a;
}
```

UnkBitSequence.h
Description: There is an unknown sequence of n bits In one query you can specify a subset, the return value will be the sum of this subset Deterministically finds the sequence using around 2.67n / log₂(n) queries
Time: $\mathcal{O}(n^2 / \log(n))$. 0e8655, 115 lines

```
struct UnkBitSequence {
    // O(N / log(N)) sum queries → N bits
    // https://codeforces.com/blog/entry/105188
    int qcnt = 0;
    int M; // N in the problem
    vector<int> filtered(vector<int> vt) { // don't include elements > N
        in the query!
        vector<int> res;
        for(int x: vt) {
            if(x < M) res.push_back(x);
        }
        return res;
    }
    int query_sum(vector<int> vt) {
        vt = filtered(vt);
        if(vt.empty()) return 0;
        qcnt++;
        // TO EDIT: Ask a query that is equivalent to asking sum
```

```
}
int query_count() {
    return qcnt;
}
vector<int> get_range(int l, int r) {
    vector<int> ww;
    for(int i=l; i<=r; i++) ww.push_back(i);
    return ww;
}
vector<int> set_union(vector<int> a, vector<int> b) {
    vector<int> c;
    set<int> s;
    for(int x: a) s.insert(x);
    for(int x: b) s.insert(x);
    for(int x: s) c.push_back(x);
    return c;
}
vector<int> set_exclude(vector<int> a, vector<int> b) { // a but not
    b
    set<int> s;
    for(int x: a) s.insert(x);
    for(int x: b) if(s.count(x)) s.erase(x);
    vector<int> c;
    for(int x: s) c.push_back(x);
    return c;
}
unordered_map<int, vector<vector<int>>> mp[21];
vector<vector<int>>> queries(int K, int L, int R) {
    if(K == 0) {
        return {{L}};
    }
    int ff = ((R-L+1) - (1<<(K-1)) + 1) / 2;
    vector<vector<int>>> ql = queries(K-1, L, L+ff-1);
    vector<vector<int>>> qr = queries(K-1, L+ff, L+2*ff-1);
    vector<vector<int>>> new_queries;
    new_queries.push_back(get_range(L+ff, L+2*ff-1));
    for(int i=0; i+l<ql.size(); i++) {
        new_queries.push_back(set_union(ql[i], qr[i]));
        new_queries.push_back(set_union(set_union(ql[i], set_exclude(
            get_range(L+ff, L+2*ff-1), qr[i])), {L+2*ff+i}));
    }
    new_queries.push_back(get_range(L, R));
    mp[K][L] = new_queries;
    return new_queries;
}
vector<bool> answer;
void recur(int K, int L, int R, vector<int> qres) {
    assert(qres.size() == (1ll << K));
    if(K == 0) {
        answer[L] = qres[0];
        return;
    }
    vector<vector<int>>> query_list = mp[K][L]; // 2^K queries
    int ff = ((R-L+1) - (1<<(K-1)) + 1) / 2;
    // [L, L+ff)
    // [L+ff, L+2*ff)
    // [L+2*ff, R]
    int rem = 0;
    vector<int> lans, rans;
    for(int i=1; i<=(1ll<<(K-1))-1; i++) {
        // queries 2*i-1, 2*i
        lans.push_back((qres[2*i-1] + qres[2*i] - qres[0]) / 2);
        rans.push_back((qres[2*i-1] - qres[2*i] + qres[0] + 1) / 2);
        answer[L+2*ff+i-1] = (qres[2*i-1] + qres[2*i] - qres[0]) % 2;
        rem += answer[L+2*ff+i-1];
    }
    lans.push_back(qres[(1ll << K)-1] - rem - qres[0]);
    rans.push_back(qres[0]);
    recur(K-1, L, L+ff-1, lans);
    recur(K-1, L+ff, L+2*ff-1, rans);
}
public:
vector<bool> find_bit_sequence(int N) {
    M = N;
    int f[N+10];
    f[0] = 1;
    int K = 0;
    for(int i=1; i<N; i++) {
        f[i] = (f[i-1] << 1) + (1ll << (i-1)) - 1;
```

```
        if(f[i] >= N) {
            N = f[i];
            K = i;
            break;
        }
    }
    answer.resize(N);
    for(int i=0; i<N; i++) answer[i] = false;
    vector<vector<int>>> qq = queries(K, 0, N - 1);
    vector<int> values;
    for(vector<int> x: qq) {
        values.push_back(query_sum(x));
    }
    recur(K, 0, N - 1, values);
    vector<bool> ret(M);
    for(int i=0; i<M; i++) ret[i] = answer[i];
    return ret;
}

};
```

10.3 Dynamic programming
KnuthDP.h
Description: When doing DP on intervals: $a[i][j] = \min_{i < k < j} (a[i][k] + a[k][j]) + f(i, j)$, where the (minimal) optimal k increases with both i and j, one can solve intervals in increasing order of length, and search $k = p[i][j]$ for $a[i][j]$ only between $p[i][j-1]$ and $p[i+1][j]$. This is known as Knuth DP. Sufficient criteria for this are if $f(b, c) \leq f(a, d)$ and $f(a, c) + f(b, d) \leq f(a, d) + f(b, c)$ for all $a \leq b \leq c \leq d$. Consider also: LineContainer (ch. Data structures), monotone queues, ternary search.
Time: $\mathcal{O}(N^2)$

DivideAndConquerDP.h
Description: Given $a[i] = \min_{lo(i) \leq k < hi(i)} (f(i, k))$ where the (minimal) optimal k increases with i, computes $a[i]$ for $i = L..R - 1$.
Time: $\mathcal{O}((N + (hi - lo)) \log N)$ d38d2b, 18 lines

```
struct DP { // Modify at will:
    int lo(int ind) { return 0; }
    int hi(int ind) { return ind; }
    ll f(int ind, int k) { return dp[ind][k]; }
    void store(int ind, int k, ll v) { res[ind] = pii(k, v); }

    void rec(int L, int R, int LO, int HI) {
        if (L >= R) return;
        int mid = (L + R) >> 1;
        pair<ll, int> best(LLONG_MAX, LO);
        rep(k, max(LO, lo(mid)), min(HI, hi(mid)))
            best = min(best, make_pair(f(mid, k), k));
        store(mid, best.second, best.first);
        rec(L, mid, LO, best.second+1);
        rec(mid+1, R, best.second, HI);
    }
    void solve(int L, int R) { rec(L, R, INT_MIN, INT_MAX); }
};
```

10.4 Debugging tricks

- signal(SIGSEGV, [](int) { _Exit(0); }); converts segfaults into Wrong Answers. Similarly one can catch SIGABRT (assertion failures) and SIGFPE (zero divisions). _GLIBCXX_DEBUG failures generate SIGABRT (or SIGSEGV on gcc 5.4.0 apparently).
- feenableexcept(29); kills the program on NaNs (1), 0-divs (4), infinities (8) and denormals (16).

10.5 Optimization tricks
__builtin_ia32_ldmxcsr(40896); disables denormals (which make floats 20x slower near their minimum value).

10.5.1 Bit hacks

- x & -x is the least bit in x.

- for (int x = m; x;) { --x &= m; ... } loops over all subset masks of m (except m itself).
- c = x&-x, r = x+c; (((r^x) >> 2)/c) | r is the next number after x with the same number of bits set.
- rep(b,0,K) rep(i,0,(1 << K))
if (i & 1 << b) D[i] += D[i^(1 << b)]; computes all sums of subsets.

10.5.2 Pragmas

- #pragma GCC optimize ("trapv") kills the program on integer overflows (but is really slow).

FastMod.h

Description: Compute $a\%b$ about 5 times faster than usual, where b is constant but not known at compile time. Returns a value congruent to $a \pmod b$ in the range $[0, 2b)$.

```
751a02, 8 lines
typedef unsigned long long ull;
struct FastMod {
    ull b, m;
    FastMod(ull b) : b(b), m(-1ULL / b) {}
    ull reduce(ull a) { // a % b + (0 or b)
        return a - (ull)((__uint128_t(m) * a) >> 64) * b;
    }
};
```

FastInput.h

Description: Read an integer from stdin. Usage requires your program to pipe in input from file.
Usage: ./a.out < input.txt
Time: About 5x as fast as cin/scanf.

```
7b3c70, 17 lines
inline char gc() { // like getchar()
    static char buf[1 << 16];
    static size_t bc, be;
    if (bc >= be) {
        buf[0] = 0, bc = 0;
        be = fread(buf, 1, sizeof(buf), stdin);
    }
    return buf[bc++]; // returns 0 on EOF
}

int readInt() {
    int a, c;
    while ((a = gc()) < 40);
    if (a == '-') return -readInt();
    while ((c = gc()) >= 48) a = a * 10 + c - 480;
    return a - 48;
}
```

BumpAllocator.h

Description: When you need to dynamically allocate many objects and don't care about freeing them. "new X" otherwise has an overhead of something like 0.05us + 16 bytes per allocation.

```
745db2, 8 lines
// Either globally or in a single class:
static char buf[450 << 20];
void* operator new(size_t s) {
    static size_t i = sizeof buf;
    assert(s < i);
    return (void*)&buf[i -= s];
}
void operator delete(void*) {}
```

SmallPtr.h

Description: A 32-bit pointer that points into BumpAllocator memory.
"BumpAllocator.h"

```
2dd6c9, 10 lines
template<class T> struct ptr {
    unsigned ind;
    ptr(T* p = 0) : ind(p ? unsigned((char*)p - buf) : 0) {
        assert(ind < sizeof buf);
    }
    T& operator*() const { return *(T*)(buf + ind); }
    T* operator->() const { return &*this; }
```

```
T& operator[](int a) const { return (&*this)[a]; }
explicit operator bool() const { return ind; }
};
```

BumpAllocatorSTL.h

Description: BumpAllocator for STL containers.
Usage: vector<vector<int, small<int>>>> ed(N);

```
bb66d4, 14 lines
char buf[450 << 20] alignas(16);
size_t buf_ind = sizeof buf;

template<class T> struct small {
    typedef T value_type;
    small() {}
    template<class U> small(const U&) {}
    T* allocate(size_t n) {
        buf_ind -= n * sizeof(T);
        buf_ind &= 0 - alignof(T);
        return (T*)(buf + buf_ind);
    }
    void deallocate(T*, size_t) {}
};
```

Unrolling.h

```
520e76, 5 lines
#define F {...; ++i;}
int i = from;
while (i&3 && i < to) F // for alignment, if needed
while (i + 4 <= to) { F F F F }
while (i < to) F
```