```
No.     Time          Source              Destination         Protocol Length Info
    112 5.622973      128.119.245.12      10.136.66.167       HTTP     293    HTTP/1.1 304 Not Modified
Frame 112: 293 bytes on wire (2344 bits), 293 bytes captured (2344 bits) on interface \Device\NPF_{93FDA14B-ED7C-403D-8615-5B858D35BEDE}, id 0
Ethernet II, Src: AristaNe_eb:12:27 (94:8e:d3:eb:12:27), Dst: IntelCor_05:e5:01 (4c:34:88:05:e5:01)
    Destination: IntelCor_05:e5:01 (4c:34:88:05:e5:01)
        Address: IntelCor_05:e5:01 (4c:34:88:05:e5:01)
        .... ..0. .... .... .... .... = LG bit: Globally unique address (factory default)
        .... ...0 .... .... .... .... = IG bit: Individual address (unicast)
    Source: AristaNe_eb:12:27 (94:8e:d3:eb:12:27)
        Address: AristaNe_eb:12:27 (94:8e:d3:eb:12:27)
        .... ..0. .... .... .... .... = LG bit: Globally unique address (factory default)
        .... ...0 .... .... .... .... = IG bit: Individual address (unicast)
    Type: IPv4 (0x0800)
Internet Protocol Version 4, Src: 128.119.245.12, Dst: 10.136.66.167
Transmission Control Protocol, Src Port: 80, Dst Port: 65316, Seq: 1, Ack: 585, Len: 239
Hypertext Transfer Protocol
```