



Engineering Master

GX33

© Fisher Controls Intl. LLC, 2017

Confidential / Do Not Reproduce

Revised: November 22, 2017

Page 1 of 19

Revision AL

Design GX Valve Body and Actuator Assembly, Size NPS 3 / DN80

CONFIDENTIAL, This document, including the information it bears, is the property of Fisher Controls and must be held in strict confidence and properly safeguarded at all times by the recipient. It may not be copied, reproduced or provided or revealed to any other party, except with the prior written authorization of Fisher Controls, any authorized copy or reproduction must include this legend. This document may be used only for the purpose for which Fisher Controls has provided it to the recipient and must be returned to Fisher Controls, along with all copies and reproductions, upon request. By accepting this document, the recipient agrees to the forgoing. This document's original controlled version resides in the Engineering Document Control System (EDOCS), accessible on the Fisher FishWeb. Copies of this document are uncontrolled. Engineering Standard DS40 controls the creation and maintenance of this document.

Pneumatic Spring & Actuator GX33 - A B C D E F G H J K L M N P Q R S T U V 9A 9C 9D 9E 9F 9G 9K 9H 9N

Electric Actuator GX33 - A B C E F G H J K L M N Q R 9C 9D 9E 9F 9G 9J 9K 9N

Temperatures per ASME B31.3, EN1092-1, EN13445-2, PS59.1:021(C), ES161, EN1515-1, PE0
CWP per ASME B16.34, EN1092-1, PS59.1:021(C), ES161, EN12516-1, JIS B2220



Engineering Master

GX33

© Fisher Controls Intl. LLC, 2017

Confidential / Do Not Reproduce

Revised: November 22, 2017

Page 2 of 19

Revision AL

Design GX Valve Body and Actuator Assembly, Size NPS 3 / DN80

Item	Parts contained in Item	Find Number
A	Valve Body	1
B	Plug/Stem, Equal Percent	3
C	Seat Ring or Seat Ring Assembly	2
D	Backup or Seal Ring	38
	Lubricant	80
	Piston Ring	100
E	Bonnet	4
F	Packing Nut	29
	Packing Set	33, 42 & 43
	Belleville Spring	34
	Anti-extrusion Washer	32
	Packing Washer	44
G	Packing Spacer	30
	Packing Box Ring	31
H	Gasket	5, 47 & 50
	Packing Washer	120
J	Stud Bolt, Continuous Thread	6
	Hex Nut	7
K	Yoke/Casing Assembly	8
L	Upper Casing Assembly	9
	Diaphragm	10
	Diaphragm Plate Assembly	11
	Actuator Spacer	13
	Screw Cap, Hex Head	14, 16 & 17
	Diaphragm Washer	15
	Hex Nut	18
	Actuator Rod	22
	Non-Threaded Cap	72
	Travel Indicator Scale	74
	O-Ring	109
	Rod Adaptor	110
	Stud	111
	Nut	112
	Electric Actuator Spacer	114
M	Hex Nut	28
	Stem Connector, Lower	27
N	Yoke Bushing	19
	O-Ring	20
	Vent	21
	Stem Connector Nut	23
	Stem Connector Bolt	24
	Screw Cap, Hex Head	25
	Travel Indicator	26
	Warning Label	36
	Lubricant, Grease	70
	Lubricant, Anti-Seize/Lub-3	71
	Pipe Plug	78
P	Spring	12
Q	Nameplate	35
	Drive Screw	113
	Wire	115

Item	Parts contained in Item	Find Number
R	Bushing Assembly	41
	Insert	48
	Stem/Bellows Assembly	49
	Nut	51
	Pipe Plug	52
	Warning Tag	73
	Sealant	79
	Bushing	93
	Thrust Ring	94
	Liner	95
	Washer	98
S	Drive Screw	56
	Handwheel	76
T	Handjack Body	53
	Handjack Lever	54
	Operating Nut	55
	Washer, Drive Screw	57
	Retaining Ring, Extension	58 & 62
	Thrust Bearing	59
	Pin Pivot	60
	Bushing	61
	Lever Spacer	63
	Screw Cap, Hex Head	64 & 66
	Stud Bolt, Continuous Thread	68
	Lubricant, Grease	70
	Lubricant Fitting, Straight	75
	Hex Nut, Lock	77
U	Travel Stop Assembly	99
	Hex Nut	28
	Hex Nut	69
	Lubricant, Grease	70
	Bracket	85
	Lever	86
	Shaft	87
	Retainer Ring	88
	Cap Screw	89
	Stud	92
	Travel Stop Warning Tag	101
V	Protection Plate	91
	Cap Screw	96
	Warning Label	97



Engineering Master

GX33

© Fisher Controls Intl. LLC, 2017

Confidential / Do Not Reproduce

Revised: November 22, 2017

Page 3 of 19

Revision AL

Design GX Valve Body and Actuator Assembly, Size NPS 3 / DN80

Item	Parts contained in Item
9A	Actuator Diaphragm Operating Pressure Air Supply Opens or Closes Valve
9C	Hydro Test per FGS 4L1
9D	Seat Leak Test per FGS 4L5
9E	Plug & Trim Style (Characteristic)
9F	Flow Cv/Kv
9G	Remove Lower Portion of Warning Tag GF00483
9H	Travel Stop Style
9J	Maximum Allowable Thrust
9K	Side Mounted Handwheel Orientation Position per Drawing GE52353
9N	NACE Service Indicator



Design GX Valve Body and Actuator Assembly, Size NPS 3 / DN80

Item 9N – NACE Service Indicator

NACE Service Metallurgical Requirements Indicator	NACE Indicator	9N
Non-NACE	N/A	N
NACE MR0175-2002	1	1
NACE MR0103	2	2
NACE MR0175-2003	3	3
NACE MR0175/ISO 15156	4	4

Item A – Valve Body

Standard Face to Face Dimension

Body Material	End Connection Face to Face	Process Temperature		Rating	CWP		NACE Indicator	A
		°F	°C		PSI	BAR		
WCC & 1.0619	RF (ASME B16.5) ANSI/ISA-75.08.01	-20+800	-29+427	Class 150	290	20	1,2,3,4	1
				Class 300	750	51.7	1,2,3,4	2
	RTJ (ASME B16.5)	-20+800	-29+427	Class 150	290	20	1,2,3,4	32
				Class 300	750	51.7	1,2,3,4	33
	JPI (ASME B16.5) ANSI/ISA-75.08.01	-20+800	-29+427	Class 150	290	20	1,2,3,4	34
				Class 300	750	51.7	1,2,3,4	35
	RF(EN1092-1/21 B) EN558	-20+752	-29+400	PN10-40	N/A	40	1,2,3,4	3
	Groove (EN1092-1/21 D) EN558	-20+752	-29+400	PN10-40	N/A	40	1,2,3,4	4
	Spigot (EN1092-1/21 E) EN558	-20+752	-29+400	PN10-40	N/A	40	1,2,3,4	5
	Recess (EN1092-1/21 F) EN558	-20+752	-29+400	PN10-40	N/A	40	1,2,3,4	44
LCC	JIS (JIS B2220) JIS B2002	-20+572	-29+300	JIS 10K	203	14	1,2,3,4	36
		-20+797	-29+425	JIS 20K	493	34	1,2,3,4	37
	RF (ASME B16.5) ANSI/ISA-75.08.01	-50+650	-46+343	Class 150	290	20	1,2,3,4	6
				Class 300	750	51.7	1,2,3,4	7
	RF(EN1092-1/21 B) EN558	-50+650	-46+343	PN10-40	N/A	40	1,2,3,4	8
	Groove (EN1092-1/21 D) EN558	-50+650	-46+343	PN10-40	N/A	40	1,2,3,4	9
	Spigot (EN1092-1/21 E) EN558	-50+650	-46+343	PN10-40	N/A	40	1,2,3,4	10
	Recess (EN1092-1/21 F) EN558	-50+650	-46+343	PN10-40	N/A	40	1,2,3,4	45
	RF (ASME B16.5) ANSI/ISA-75.08.01	-425+850	-254+454	Class 150	275	18.9	1,2,3,4	11
				Class 300	720	49.6	1,2,3,4	12
CF3M & 1.4409	RTJ (ASME B16.5)	-425+850	-254+454	Class 150	275	18.9	1,2,3,4	38
				Class 300	720	49.6	1,2,3,4	39
	JPI (ASME B16.5) ANSI/ISA-75.08.01	-425+850	-254+454	Class 150	275	18.9	1,2,3,4	40
				Class 300	720	49.6	1,2,3,4	41
	RF(EN1092-1/21 B) EN558	-321+932	-196+500	PN10-40	N/A	40	1,2,3,4	13
	Groove (EN1092-1/21 D) EN558	-321+932	-196+500	PN10-40	N/A	40	1,2,3,4	14
	Spigot (EN1092-1/21 E) EN558	-321+932	-196+500	PN10-40	N/A	40	1,2,3,4	15
	Recess (EN1092-1/21 F) EN558	-321+932	-196+500	PN10-40	N/A	40	1,2,3,4	46
	JIS (JIS B2220) JIS B2002	-50.8+572	-46+300	JIS 10K	203	14	1,2,3,4	42
		-50.8+797	-46+425	JIS 20K	493	34	1,2,3,4	43
CD3MN (Duplex SST)	RF (ASME B16.5) ANSI/ISA-75.08.01	-60+600	-51+316	Class 150	290	20	N/A	16
				Class 300	750	51.7	N/A	17
	RF(EN1092-1/21 B) EN558	+14+600	-10+316	PN10-40	N/A	40	N/A	18
CF3 (304L SST)	RF (ASME B16.5) ANSI/ISA-75.08.01	-425+800	-254+427	Class 150	275	18.6	1,2,3	19
				Class 300	720	49.6	1,2,3	20
	RF(EN1092-1/21 B) EN558	+14+800	-10+427	PN10-40	N/A	36.8	1,2,3	21
CN7M & CN3MCU (Alloy 20)	RF (ASME B16.5) ANSI/ISA-75.08.01	-325+600	-198+316	Class 150	230	15.8	1,2	22
				Class 300	600	41.4	1,2	23
	RF(EN1092-1/21 B) EN558	+14+600	-10+316	PN10-40	N/A	32.7	1,2	24
CW2M (Hast C)	RF (ASME B16.5) ANSI/ISA-75.08.01	-325+1000	-198+538	Class 150	290	20	1,2,3,4	25
				Class 300	750	51.7	1,2,3,4	26
	RF(EN1092-1/21 B) EN558	+14+1000	-10+538	PN10-40	N/A	40	1,2,3,4	27



Design GX Valve Body and Actuator Assembly, Size NPS 3 / DN80

Item A – Valve Body (Continued)

Standard Face to Face Dimension

Body Material	End Connection Face to Face	Process Temperature		Rating	CWP		NACE Indicator	A
		°F	°C		PSI	BAR		
M35-2(Monel)	RF (ASME B16.5) ANSI/ISA-75.08.01	-325+800	-198+427	Class 150	270	18.6	1,2	28
				Class 300	700	48.2	1,2	29
N7M (Hast B2)	RF (ASME B16.5) ANSI/ISA-75.08.01	-325+1000	-198+538	Class 150	290	20	N/A	30
				Class 300	750	51.7	N/A	31

Item B – Valve Plug/Stem

Item C – Seat Ring

Item 9E – Plug and Trim Style

Item 9J – Maximum Allowable Thrust

Plain Bonnet

LCC, WCC/1.0619 & CF3M/1.4409 Body Material

Process temperature limits for PTFE Seat rings: -73+204 °C (-100+400 °F), other construction: N/A

Port	Plug Style	Travel	Valve Plug	Stem	Max Allow Thrust	Seat Ring	Characteristic	NACE Ind	B	C	9E	9J
36mm	Unbal	20mm	CF3M	316L SST	20000 N	CF3M	Equal Percent Linear	N/A	1	1	1	1
						CF3M/PTFE Seat	Equal Percent Linear	N/A	2	1	2	1
			CF3M/HF Seat	S20910	20000 N	CF3M/HF Seat/Guide	Equal Percent Linear	1,2,3,4	3	3	1	1
							Equal Percent Linear	1,2,3,4	4	3	2	1
			CF3M Ion-Nitride	316L SST	20000 N	CF3M	Equal Percent Linear	N/A	5	1	1	1
							Equal Percent Linear	N/A	6	1	2	1
						CF3M/PTFE Seat	Equal Percent Linear	N/A	5	2	1	1
							Equal Percent Linear	N/A	6	2	2	1
			CF3M/HF Seat/Guide			CF3M/HF Seat/Guide	Equal Percent Linear	N/A	5	3	1	1
							Equal Percent Linear	N/A	6	3	2	1
			CW2M	N06022	20000 N	CW2M	Equal Percent Linear	1,2,3,4	7	4	1	1
							Equal Percent Linear	1,2,3,4	8	4	2	1
46mm	Unbal	20mm	CF3M	316L SST	20000 N	CF3M	Equal Percent Linear	N/A	9	6	1	1
							Equal Percent Linear	N/A	10	6	2	1
			CF3M/PTFE Seat			CF3M/PTFE Seat	Equal Percent Linear	N/A	9	7	1	1
							Equal Percent Linear	N/A	10	7	2	1
			CF3M/HF Seat	S20910	20000 N	CF3M/HF Seat/Guide	Equal Percent Linear	1,2,3,4	11	8	1	1
							Equal Percent Linear	1,2,3,4	12	8	2	1
			CF3M Ion-Nitride	316L SST	20000 N	CF3M	Equal Percent Linear	N/A	13	6	1	1
							Equal Percent Linear	N/A	14	6	2	1
						CF3M/PTFE Seat	Equal Percent Linear	N/A	13	7	1	1
							Equal Percent Linear	N/A	14	7	2	1
			CF3M/HF Seat/Guide			CF3M/HF Seat/Guide	Equal Percent Linear	N/A	13	8	1	1
							Equal Percent Linear	N/A	14	8	2	1
			CW2M	N06022	20000 N	CW2M	Equal Percent Linear	1,2,3,4	15	9	1	1
							Equal Percent Linear	1,2,3,4	16	9	2	1
			CW2M/PTFE Seat			CW2M/PTFE Seat	Equal Percent Linear	N/A	15	10	1	1
							Equal Percent Linear	N/A	16	10	2	1



Engineering Master

GX33

© Fisher Controls Intl. LLC, 2017

Confidential / Do Not Reproduce

Revised: November 22, 2017

Page 6 of 19

Revision AL

Design GX Valve Body and Actuator Assembly, Size NPS 3 / DN80

Item B – Valve Plug/Stem (Continued)
Item C – Seat Ring (Continued)
Item 9E – Plug and Trim Style (Continued)
Item 9J – Maximum Allowable Thrust (Continued)

Plain Bonnet

LCC, WCC/1.0619 & CF3M/1.4409 Body Material

Process temperature limits for PTFE Seat rings: -73+204 °C (-100+400 °F), other construction: N/A

Port	Plug Style	Travel	Valve Plug	Stem	Max Allow Thrust	Seat Ring	Characteristic	NACE Ind	B	C	9E	9J
70mm	Unbal	40mm	CF3M	316L SST	20000 N	CF3M	Equal Percent Linear	N/A	17	11	1	1
								N/A	18	11	2	1
						CF3M/PTFE Seat	Equal Percent Linear	N/A	17	12	1	1
			CF3M/HF Seat	S20910	20000 N	CF3M/HF Seat/Guide	Equal Percent Linear	1,2,3,4	19	13	1	1
								1,2,3,4	20	13	2	1
								1,2,3,4	21	13	3	1
			CF3M Ion-Nitride	316L SST	20000 N	CF3M	Equal Percent Linear	N/A	22	11	1	1
								N/A	23	11	2	1
						CF3M/PTFE Seat	Equal Percent Linear	N/A	22	12	1	1
								N/A	23	12	2	1
			CF3M/HF Seat/Guide				Equal Percent Linear	N/A	22	13	1	1
								N/A	23	13	2	1
			CW2M	N06022	20000 N	CW2M	Equal Percent Linear	1,2,3,4	24	14	1	1
								1,2,3,4	25	14	2	1
						CW2M/PTFE Seat	Equal Percent Linear	N/A	24	15	1	1
								N/A	25	15	2	1
	Bal	20mm	S31603	316L SST	20000 N	CF3M	Equal Percent Linear	N/A	26	11	4	1
								N/A	27	11	5	1
			S31603/HF Seat	S20910	20000 N	CF3M/HF Seat/Guide	Equal Percent Linear	1,2,3,4	28	13	4	1
								1,2,3,4	29	13	5	1
			N06022	N06022	20000 N	CW2M	Equal Percent Linear	1,2,3,4	30	14	4	1
								1,2,3,4	31	14	5	1



Engineering Master

GX33

© Fisher Controls Intl. LLC, 2017

Confidential / Do Not Reproduce

Revised: November 22, 2017

Page 7 of 19

Revision AL

Design GX Valve Body and Actuator Assembly, Size NPS 3 / DN80

Item B – Valve Plug/Stem (Continued)**Item C – Seat Ring** (Continued)**Item 9E – Plug and Trim Style** (Continued)**Item 9J – Maximum Allowable Thrust** (Continued)

Plain Bonnet

Process temperature limits for PTFE Seat rings: -73+204 °C (-100+400 °F), other construction: N/A

Body	Port	Plug Style	Travel	Valve Plug	Stem	Max Allow Thrust	Seat Ring	Characteristic	NACE Ind	B	C	9E	9J
CD3MN	36mm	Unbal	20mm	CD3MN	S31803	20000 N	CD3MN	Equal Percent Linear	N/A	32	16	1	1
									N/A	33	16	2	1
							CD3MN/PTFE Seat	Equal Percent Linear	N/A	32	17	1	1
	46mm	Unbal	20mm	CD3MN	S31803	20000 N			N/A	33	17	2	1
							CD3MN	Equal Percent Linear	N/A	34	18	1	1
									N/A	35	18	2	1
	70mm	Unbal	40mm	CD3MN	S31803	20000 N	CD3MN/PTFE Seat	Equal Percent Linear	N/A	34	19	1	1
									N/A	35	19	2	1
							CD3MN	Equal Percent Linear	N/A	36	20	1	1
		Bal	20mm	S31803	S31803	20000 N			N/A	37	20	2	1
							CD3MN/PTFE Seat	Equal Percent Linear	N/A	36	21	1	1
CF3	36mm	Unbal	20mm	CF3	S31803	20000 N			N/A	37	21	2	1
							CD3MN	Equal Percent Linear	N/A	38	20	4	1
									N/A	39	20	5	1
	46mm	Unbal	20mm	CF3	S31803	20000 N	304L	Equal Percent Linear	1	40	22	1	1
									1	41	22	2	1
							304L/PTFE Seat	Equal Percent Linear	N/A	40	23	1	1
	70mm	Unbal	40mm	CF3	S31803	20000 N			N/A	41	23	2	1
							304L	Equal Percent Linear	1	42	24	1	1
									1	43	24	2	1
		Bal	20mm	S30403	S31803	20000 N	304L/PTFE Seat	Equal Percent Linear	N/A	42	25	1	1
									N/A	43	25	2	1
	70mm	Unbal	40mm	CF3	S31803	20000 N	304L	Equal Percent Linear	1	44	26	1	1
									1	45	26	2	1
							304L/PTFE Seat	Equal Percent Linear	N/A	44	27	1	1
									N/A	45	27	2	1
	70mm	Bal	20mm	S30403	S31803	20000 N	304L	Equal Percent Linear	1	46	26	4	1
									1	47	26	5	1



Engineering Master

GX33

© Fisher Controls Intl. LLC, 2017

Confidential / Do Not Reproduce

Revised: November 22, 2017

Page 8 of 19

Revision AL

Design GX Valve Body and Actuator Assembly, Size NPS 3 / DN80

Item B – Valve Plug/Stem (Continued)
Item C – Seat Ring (Continued)
Item 9E – Plug and Trim Style (Continued)
Item 9J – Maximum Allowable Thrust (Continued)

Plain Bonnet (continued)

Process temperature limits for PTFE Seat rings: -73+204 °C (-100+400 °F), other construction: N/A

Body	Port	Plug Style	Travel	Valve Plug	Stem	Max Allow Thrust	Seat Ring	Characteristic	NACE Ind	B	C	9E	9J
CN7M & CN3MCU, CW2M	36mm	Unbal	20mm	CW2M	N06022	20000 N	CW2M	Equal Percent Linear	1,2,3,4 1,2,3,4	7 8	4 4	1 2	1 1
							CW2M/PTFE Seat	Equal Percent Linear	N/A N/A	7 8	5 5	1 2	1 1
	46mm	Unbal	20mm	CW2M	N06022	20000 N	CW2M	Equal Percent Linear	1,2,3,4 1,2,3,4	15 16	9 9	1 2	1 1
							CW2M/PTFE Seat	Equal Percent Linear	N/A N/A	15 16	10 10	1 2	1 1
	70mm	Unbal	40mm	CW2M	N06022	20000 N	CW2M	Equal Percent Linear	1,2,3,4 1,2,3,4	24 25	14 14	1 2	1 1
							CW2M/PTFE Seat	Equal Percent Linear	N/A N/A	24 25	15 15	1 2	1 1
		Bal	20mm	N06022	N06022	20000 N	CW2M	Equal Percent Linear	1,2,3,4 1,2,3,4	30 31	14 14	4 5	1 1
M35-2	36mm	Unbal	20mm	N05500	N05500	20000 N	N05500	Equal Percent	1	48	28	1	1
	46mm	Unbal	20mm	N05500	N05500	20000 N	N05500	Equal Percent	1	49	29	1	1
	70mm	Unbal	40mm	N05500	N05500	20000 N	N05500	Equal Percent	1	50	30	1	1
N7M	36mm	Unbal	20mm	N7M	N10675	20000 N	N7M	Equal Percent	N/A	51	31	1	1
	46mm	Unbal	20mm	N7M	N10675	20000 N	N7M	Equal Percent	N/A	52	32	1	1
	70mm	Unbal	40mm	N7M	N10675	20000 N	N7M	Equal Percent	N/A	53	33	1	1

Extension Bonnet

LCC, WCC/1.0619 & CF3M/1.4409 Body Material

Port	Plug Style	Travel	Valve Plug	Stem	Max Allow Thrust	Seat Ring	Characteristic	NACE Ind	B	C	9E	9J
36mm	Unbal	20mm	CF3M	316L SST	20000 N	CF3M/HF Seat/Guide	Equal Percent Linear	N/A N/A	1 2	3 3	1 2	1 1
			CF3M/HF Seat	S20910	20000 N	CF3M/HF Seat/Guide	Equal Percent Linear	1,2,3,4 1,2,3,4	3 4	3 3	1 2	1 1
			CF3M	316L SST	20000 N	CF3M/HF Seat/Guide	Equal Percent Linear	N/A N/A	9 10	8 8	1 2	1 1
46mm	Unbal	20mm	CF3M	316L SST	20000 N	CF3M/HF Seat/Guide	Equal Percent Linear	1,2,3,4 1,2,3,4	11 12	8 8	1 2	1 1
			CF3M/HF Seat	S20910	20000 N	CF3M/HF Seat/Guide	Equal Percent Linear	1,2,3,4 1,2,3,4	11 12	8 8	1 2	1 1
			CF3M	316L SST	20000 N	CF3M/HF Seat/Guide	Equal Percent Linear	N/A N/A	17 18	13 13	1 2	1 1
70mm	Unbal	40mm	CF3M	316L SST	20000 N	CF3M/HF Seat/Guide	Equal Percent Linear	1,2,3,4 1,2,3,4	19 20	13 13	1 2	1 1
			CF3M/HF Seat	S20910	20000 N	CF3M/HF Seat/Guide	Equal Percent Linear	1,2,3,4 1,2,3,4	19 20	13 13	1 2	1 1
			CF3M/HF Seat	S20910	20000 N	CF3M/HF Seat/Guide	Whisper III	1,2,3,4	21	13	3	1



Design GX Valve Body and Actuator Assembly, Size NPS 3 / DN80

Item B – Valve Plug/Stem (Continued)
Item C – Seat Ring (Continued)
Item 9E – Plug and Trim Style (Continued)
Item 9J – Maximum Allowable Thrust (Continued)

Bellows Bonnet

Process temperature limits for PTFE Seat rings: -73+204 °C (-100+400 °F), other construction: N/A

LCC, WCC/1.0619 & CF3M/1.4409 Body Material

Port	Plug Style	Travel	Valve Plug	Stem	Max Allow Thrust	Seat Ring	Characteristic	NACE Ind	B	C	9E	9J
36mm	Unbal	20mm	CF3M	316L SST	20000 N	CF3M/HF Seat/Guide	Equal Percent Linear	N/A N/A	1 2	3 3	1 2	1 1
						CF3M/PTFE Seat	Equal Percent Linear	N/A N/A	1 2	2 2	1 2	1 1
			CF3M/HF Seat	S20910	20000 N	CF3M/HF Seat/Guide	Equal Percent Linear	1,2,3,4 1,2,3,4	3 4	3 3	1 2	1 1
			CW2M	N06022	14500 N	CW2M	Equal Percent Linear	1,2,3,4 1,2,3,4	7 8	4 4	1 2	2 2
						CW2M/PTFE Seat	Equal Percent Linear	N/A N/A	7 8	5 5	1 2	2 2
			46mm	Unbal	20mm	CF3M	316L SST	20000 N	CF3M/HF Seat/Guide	Equal Percent Linear	N/A N/A	9 10
CF3M/PTFE Seat	Equal Percent Linear	N/A N/A							9 10	7 7	1 2	1 1
CF3M/HF Seat	S20910	20000 N				CF3M/HF Seat/Guide	Equal Percent Linear	1,2,3,4 1,2,3,4	11 12	8 8	1 2	1 1
CW2M	N06022	14500 N				CW2M	Equal Percent Linear	1,2,3,4 1,2,3,4	15 16	9 9	1 2	2 2
						CW2M/PTFE Seat	Equal Percent Linear	N/A N/A	15 16	10 10	1 2	2 2
70mm	Bal	20mm				S31603	316L SST	20000 N	CF3M	Equal Percent Linear	N/A N/A	26 27
			S31603/HF Seat	S20910	20000 N	CF3M/HF Seat/Guide	Equal Percent Linear	1,2,3,4 1,2,3,4	28 29	13 13	4 5	1 1
			N06022	N06022	14500 N	CW2M	Equal Percent Linear	1,2,3,4 1,2,3,4	30 31	14 14	4 5	2 2

CW2M Body Material

Port	Plug Style	Travel	Valve Plug	Stem	Max Allow Thrust	Seat Ring	Characteristic	NACE Ind	B	C	9E	9J
36mm	Unbal	20mm	CW2M	N06022	14500 N	CW2M	Equal Percent Linear	1,2,3,4	7	4	1	2
							Linear	1,2,3,4	8	4	2	2
						CW2M/PTFE Seat	Equal Percent Linear	N/A	7	5	1	2
46mm	Unbal	20mm	CW2M	N06022	14500 N	CW2M	Equal Percent Linear	1,2,3,4	15	9	1	2
							Linear	1,2,3,4	16	9	2	2
						CW2M/PTFE Seat	Equal Percent Linear	N/A	15	10	1	2
70mm	Bal	20mm	N06022	N06022	14500 N	CW2M	Equal Percent Linear	N/A	16	10	2	2
							Linear	1,2,3,4	30	14	4	2
								1,2,3,4	31	14	5	2



Design GX Valve Body and Actuator Assembly, Size NPS 3 / DN80

Item D – Valve Plug Seal and Backup Rings (NACE Standards not applicable)

Balanced Valve Plugs with a Graphite Piston Ring must use a Class II Seat Leak
Process temperature limits for Seal/Backup Rings

Valve Plug	Port	Seal or Piston Ring	Backup Ring	Process Temperature		D
				°F	°C	
Unbalanced	36, 46 & 70mm	N/A	N/A	N/A	N/A	N
Balanced	70mm	Carbon Filled PTFE	Nitrile	-50+180	-46+82	1
			Ethylene Propylene	-50+450	-46+232	2
			FKM (Fluoroelastomer)	0+400	-18+204	3
		Graphite	N/A	-324+1100	-198+593	4

Item E – Bonnet

Bonnet Style	Valve Plug Style	Body Material	NACE Indicator	E
Plain	Unbalanced	WCC/1.0619	1,2,3,4	1
		LCC	1,2,3,4	2
		CF3M/1.4409	1,2,3,4	3
		CD3MN	N/A	4
		CN7M & CN3MCU	1,2	5
		CF3	1,2,3	6
		CW2M	1,2,3,4	7
		N04400	1,2,3,4	8
		N7M	N/A	9
	Balanced	WCC/1.0619	1,2,3,4	10
		LCC	1,2,3,4	11
		CF3M/1.4409	1,2,3,4	12
		CD3MN	N/A	13
		CN7M & CN3MCU	1,2	14
		CF3	1,2,3	15
		CW2M	1,2,3,4	16
Bellows	Unbalanced	WCC/1.0619	1,2,3,4	17
		LCC	1,2,3,4	18
		CF3M/1.4409	1,2,3,4	19
		CW2M	1,2,3,4	20
	Balanced	WCC/1.0619	N/A	21
		CF3M/1.4409	1,2,3,4	22
		CW2M	1,2,3,4	23
		LCC	N/A	27
Extension	Unbalanced	WCC/1.0619	1,2,3,4	24
		LCC	1,2,3,4	25
		CF3M/1.4409	1,2,3,4	26



Design GX Valve Body and Actuator Assembly, Size NPS 3 / DN80

Item F – Packing and Packing Parts

* Consult PS Sheet 51.1.GX(K) Low Temperature GX Application Guidelines

Live Load Packing	Bonnet Style	Process Temperature Limits for Packing		NACE Indicator	F
		°F	°C		
PTFE (NACE not Exposed)	Plain	-50+450	-46+232	1,2,3,4	1
	Bellows & Extension	-50+800	-46+427	1,2,3,4	1
	Cryogenic Extension	*	*	1,2,3,4	1
PTFE/Glass Oxygen (NACE not Exposed)	Plain	-50+450	-46+232	1,2,3,4	2
Graphite ULF (NACE not Exposed)	Plain	-325+700	-198+371	1,2,3,4	3
	Bellows & Extension	-325+1050	-198+566	1,2,3,4	3
	Cryogenic Extension	-325+1050	-198+566	1,2,3,4	3
ISO-Seal PTFE (NACE not exposed)	Plain	-325+450	-198+232	1,2,3,4	4
	Bellows & Extension	-325+800	-198+427	1,2,3,4	4
	Cryogenic Extension	-325+800	-198+427	1,2,3,4	4

Item G – Packing Box Ring and Spacer

Bonnet Style	Live Load Packing	Stem Material	NACE Indicator	G
Plain	PTFE	316L SST & S20910	1,2,3,4	1
		S31803	1	2
		N06022	1,2,3,4	3
		N05500	1,2,3,4	4
		N10675	N/A	5
	Graphite ULF	316L SST & S20910	1,2,3,4	6
		N06022	1,2,3,4	7
	ISO-Seal PTFE	316L SST & S20910	1,2,3,4	6
		N06022	1,2,3,4	7
Bellows	PTFE	316L SST & S20910	1,2,3,4	1
		N06022	1,2,3,4	3
	Graphite ULF	316L SST & S20910	1,2,3,4	6
		N06022	1,2,3,4	7
	ISO-Seal PTFE	316L SST & S20910	1,2,3,4	6
		N06022	1,2,3,4	7
Extension	PTFE	316L SST & S20910	1,2,3,4	1
	Graphite ULF	316L SST & S20910	1,2,3,4	6
	ISO-Seal PTFE	316L SST & S20910	1,2,3,4	6

Item H – Body/Bonnet Gasket

Process temperature limits:

Graphite: Upper limit: 454 °C (850 °F) No Lower limit

PTFE coated: -40+232 °C (-100+500 °F)

Bonnet Style	Gasket	NACE Indicator	H
Plain	Standard Service	Graphite FMS 17F28	1
		PTFE Coated N10276	2
		PTFE Coated S30403	3
	Oxygen Service	PTFE Coated N04400	4
Bellows	Graphite FMS 17F28	1,2,3,4	5
	PTFE Coated N10276	1,2,3,4	9
Extension	Graphite FMS 17F28	1,2,3,4	7



Design GX Valve Body and Actuator Assembly, Size NPS 3 / DN80

Item J – Body/Bonnet Bolting

Studs	Nuts	Bonnet Style	Body Material	Bolt Temp		NACE Indicator		J
				°F	°C	Non Exposed	Exposed	
B7 NCF2	2H NCF2	Plain	WCC/1.0619, CF3M/1.4409 & LCC	-54+800	-48+427	1,2,3,4	N/A	1
		Extension & Bellows	WCC/1.0619 & LCC	-54+800	-48+427	1,2,3,4	N/A	2
S20910 Hot Rolled	S20910 Hot Rolled	Plain	CW2M, CF3, CD3MN, CN7M & CN3MCU, N7M & M35-2 WCC/1.0619 & CF3M/1.4409, LCC	-325+1100	-198+593	1,2,3,4	1,2,3,4	7
		Extension & Bellows	CW2M	-325+500	-198+260	1,2,3,4	1,2,3,4	8
		Cryogenic Extension	CF3M/1.4409	-325+1100	-198+593	1,2,3,4	1,2,3,4	8

Item K – Yoke (NACE Standards not applicable)

Process temperature limits for Actuator:

Bonnet Style	Yoke material	Process Temperature	
		°F	°C
Plain	LCC	-50+450	-46+232
	CF3M	-76+450	-60+232
Extension or Bellows	LCC	-50+800	-46+427
	CF3M	-76+800	-60+427
Cryogenic Extension	LCC & CF3M	*	*

* Consult PS sheet 51.1.GX(K) Low Temperature GX Application Guidelines

Pneumatic Spring & Diaphragm Actuator

Bonnet Style	Valve Plug Style	Port Diameter	Actuator Size	Travel	SST	Steel
					K	K
All	All	All	750	All	1	2

Electric Actuator

ISO 5210 Mtg	Yoke Material	Travel	K
F7	LCC	All	3



Design GX Valve Body and Actuator Assembly, Size NPS 3 / DN80

Item L – Actuator Parts (NACE standards not applicable)

Pneumatic Spring & Diaphragm Actuator

Actuator	Travel (mm)	L
750	20	1
750	40	2

Electric Actuator

Electric Actuator	ISO 5210 Mtg	Travel	L
Rotork	F7	20 mm	3
		40 mm	4

Item M – Stem Connector Parts (NACE standards not applicable)**M**

1

Item N – Actuator Common Parts (NACE standards not applicable)

Actuator	Type	Ambient Temperature		N
		°F	°C	
Pneumatic Spring & Diaphragm	N/A	-50 +180	-46 +82	1
Electric	Rotork	N/A	N/A	2
Pneumatic S & D – PSA service	N/A	-50 +180	-46 +82	3
Pneumatic Spring & Diaphragm	N/A	-76 +180	-60 +82	4



Engineering Master

GX33

© Fisher Controls Intl. LLC, 2017

Confidential / Do Not Reproduce

Revised: November 22, 2017

Page 14 of 19

Revision AL

Design GX Valve Body and Actuator Assembly, Size NPS 3 / DN80

Item P – Actuator Spring (Use only with Pneumatic Spring & Diaphragm Actuator) (NACE Standards not applicable)
(NACE standards not applicable)

Actuator	Travel (mm)	Stem Material	Air Action	Actuator Construction	Spring Assy per GG00398	P
750	20	316L SST, S20910, or N05500	Air to Open	4 Bar	View B6	1
				3 Bar	View B6	1
				2 Bar	View B4	2
			Air to Close	4 Bar	View B4	2
				3 Bar	View B4	2
				2 Bar	View B4	2
		N06022, S31803, or N10675	Air to Open	4 Bar	View B4	2
				3 Bar	View B4	2
				2 Bar	View B4	2
			Air to Close	4 Bar	View B4	2
				3 Bar	View B4	2
				2 Bar	View B4	2
40	40	316L SST, , S20910 or N05500	Air to Open	4 Bar	View C12	3
				3 Bar	View C8	4
				2 Bar	View C4	5
			Air to Close	4 Bar	View C6	6
				3 Bar	View C3	7
				2 Bar	View C3	7
		N06022, S31803, or N10675	Air to Open	4 Bar	View C8	4
				3 Bar	View C8	4
				2 Bar	View C4	5
			Air to Close	4 Bar	View C6	6
				3 Bar	View C3	7
				2 Bar	View C3	7



Engineering Master

GX33

© Fisher Controls Intl. LLC, 2017

Confidential / Do Not Reproduce

Revised: November 22, 2017

Page 15 of 19

Revision AL

Design GX Valve Body and Actuator Assembly, Size NPS 3 / DN80

Item Q – Nameplate (NACE standards not applicable)

Actuator	Characteristic	Flow	Valve Action	Q
Pneumatic Spring & Diaphragm	Linear & Equal Percent	Up	PDTC	1
Electric	Linear & Equal Percent	Up	PDTC	2
Electric w/o Actuator (Bare Stem)	Linear & Equal Percent	Up	PDTC	3

Item R – Bellows and Extension Stem**Item 9G- Remove Lower Portion of Warning Tag GF00483**

Bonnet Style	Body	Bellows	Extension Stem	Bushing	NACE Indicator	R	9G
Plain	All	N/A	N/A	N/A	N/A	N	N
Extension	LCC , WCC/1.0619 & CF3M/1.4409	N/A	S20910	S31600/Ultimet	N/A	1	N
Cryogenic Extension	CF3M/1.4409	N/A	S20910	S31600/Ultimet	N/A	2	N
Bellows	LCC, WCC/1.0619 & CF3M/1.4409	1.4571 (316TI)	S31603	S31600/Ultimet	N/A	3	N
				S31600/PTFE Carbon	N/A	4	N
		N10276	S31603	S31600/Ultimet	N/A	5	1
				S31600/PTFE Carbon	N/A	6	1
			N06022	N10276/Ultimet	N/A	7	1
				N10276/PTFE Carbon	N/A	8	1
	CW2M	N10276	N06022	N10276/Ultimet	N/A	7	1
			N10276/PTFE Carbon	N/A	8	1	

Item S – Handwheel (When Specified) (NACE standards not applicable)**Item T – Handwheel Common Parts** (When Specified) (NACE standards not applicable)

Note: Handwheel cannot be combined with Travel Stop Assembly if positioner or other yoke mounted accessory is used.

Actuator Size	Travel (mm)	S	T
750	20	1	1
	40	-	-

Item U – Travel Stop Assembly (When Specified) (NACE standards not applicable)**Item 9H – Travel Stop Style** (Up Stop or Down Stop)

Note: Cannot be combined with Handwheel if positioner or other yoke mounted accessory is used.

Actuator Size	Travel (mm)	Handwheel	Air Action	Travel Stop	U	9H
750	20	Yes	ATO	Up Stop	1	1
				Down Stop	N	N
			ATC	Up Stop	N	N
				Down Stop	1	2
		No	ATC/ATO	Up Stop	1	1
				Down Stop	1	2
40	40	No			N	N



Design GX Valve Body and Actuator Assembly, Size NPS 3 / DN80

Item V – Travel Stop Protection Plate (When Specified) (NACE standards not applicable)

Note: Only specify when Travel Stop Assembly is used alone with no positioner, Handwheel, or other yoke mounted accessory.

V
1

Item 9A – Maximum/Minimum Actuator Diaphragm Operating Pressure (Use only with Pneumatic Spring & Diaphragm Actuator)

Actuator Size	Bonnet Style	Stem Material	Air Action	Actuator Construction	Operating Pressure (Bar)		9A
					Minimum	Maximum	
750 (20mm travel)	Plain	316L SST or S20910	Air to Close	4 Bar	4	6	17
				3 Bar	3	6	18
				2 Bar	2	6	19
		N06022, S31803 or N10675	Air to Open	4 Bar	4	6	20
				3 Bar	3	6	21
				2 Bar	2	6	22
	Extension	316L SST or S20910	Air to Close	4 Bar	3	3.9	23
				3 Bar	3	3.9	23
				2 Bar	2	3.9	24
		N06022, S31803 or N10675	Air to Open	4 Bar	4	6	20
				3 Bar	3	6	21
				2 Bar	2	6	22
	Bellows	316L SST or S20910	Air to Close	4 Bar	3	3.9	23
				3 Bar	3	3.9	23
		N06022, S31803 or N10675	Air to Open	4 Bar	4	6	20
				3 Bar	3	6	21
		316L SST or S20910	Air to Close	4 Bar	3	3.1	25
				3 Bar	3	3.1	25
		N06022, S31803 or N10675	Air to Open	4 Bar	4	6	20
				3 Bar	3	6	21



Design GX Valve Body and Actuator Assembly, Size NPS 3 / DN80

Item 9A – Maximum/Minimum Actuator Diaphragm Operating Pressure and Spring Action (Use only with Pneumatic Spring & Diaphragm Actuator) (Continued)

Actuator Size	Bonnet Style	Stem Material	Air Action	Actuator Construction	Operating Pressure (Bar)		9A
					Minimum	Maximum	
750 (40mm travel)	Plain	316L SST or S20910	Air to Close	4 Bar	4	6	17
				3 Bar	3	6	18
				2 Bar	2	6	19
			Air to Open	4 Bar	4	6	20
				3 Bar	3	6	21
				2 Bar	2	6	22
	Extension	N06022, S31803 or N10675	Air to Close	4 Bar	4	4.2	27
				3 Bar	3	3.3	28
				2 Bar	2	3.3	29
			Air to Open	4 Bar	4	6	20
				3 Bar	3	6	21
				2 Bar	2	6	22
	Extension	316L SST or S20910	Air to Close	4 Bar	4	4.3	30
				3 Bar	3	3.4	28
				2 Bar	2	3.4	29
			Air to Open	4 Bar	4	6	20
				3 Bar	3	6	21
				2 Bar	2	6	22

Item 9C – Hydro Test per FGS 4L1

BAR test pressure converted from PSI units for Class 150 & 300

Body Material	Rating	Hydro/Min		9C
		PSI	BAR	
WCC/1.0619, LCC, CF3M/1.4409, CF3, CD3MN, N7M & CW2M	Class 150	450/2	31/2	1
	Class 300	1125/2	77.6/2	2
	PN10/16/25/40	875/2	60/2	3
CN7M & CN3MCU	Class 150	350/2	24/2	4
	Class 300	900/2	62/2	5
	PN10/16/25/40	875/2	60/2	6
M35-2(Monel)	Class 150	425/2	29/2	7
	Class 300	1050/2	72/2	8



Design GX Valve Body and Actuator Assembly, Size NPS 3 / DN80

Item 9D – Seat Leak Test per FGS 4L5

Balanced Valve Plugs with a Graphite Piston Ring must use a Class II Seat Leak.

Seat Type	Seat Leak Class	Plug Style	Port	Travel	Characteristic	Seat leakage	9D
Metal	II	Balanced	70mm	20mm	Equal Percent	803.91 SCFH/379364 mL/min	1
					Linear	1060.70 SCFH/500545 mL/min	2
	IV	Unbalanced	36mm	20mm	Equal Percent	6.79 SCFH/3203 mL/min	3
					Linear	7.98 SCFH/3764 mL/min	4
			46mm	20mm	Equal Percent	10.55 SCFH/4979 mL/min	5
					Linear	12.64 SCFH/5965 mL/min	6
		Whisper III	70mm	40mm	Equal Percent	21.84 SCFH/10305 mL/min	7
					Linear	26.48 SCFH/12494 mL/min	8
			70mm	20mm	Equal Percent	16.08 SCFH/7587 mL/min	10
		Balanced	70mm	20mm	Linear	21.21 SCFH/10011 mL/min	11
	V	Unbalanced	36mm	20mm	N/A	6.7 mL/min	12
			46mm	20mm	N/A	8.5 mL/min	13
			70mm	40mm	N/A	13.0 mL/min	14
Composition	VI	Unbalanced	36mm	20mm	N/A	0.30 mL/min	15
			46mm	20mm	N/A	0.45 mL/min	16
			70mm	40mm	N/A	0.9 mL/min	17

Item 9F – Flow Cv/Kv

Port	Plug Style	Travel	Characteristic	Flow		9F
				Cv	Kv	
36mm	Unbalanced	20mm	Equal Percent	28.6	24.7	1
			Linear	33.3	28.8	2
46mm	Unbalanced	20mm	Equal Percent	43.7	37.8	3
			Linear	51.8	44.8	4
70mm	Unbalanced	40mm	Equal Percent	95.1	82.3	5
			Linear	117	101	6
	Whisper III	40mm	Linear	85.5	73.9	7
	Balanced	20mm	Equal Percent	75.7	65.5	8
			Linear	102	88	9

Item 9K - Side Mounted Handwheel Orientation Position per Drawing GE52353 (When Specified) (Factory Mounted Unit Only)

Side Mounted Handwheel	Side Mounted Handwheel Orientation Position	9K
With	Position 3 (Standard)	1
	Position 1	2
W/O	None	N



Engineering Master

GX33

© Fisher Controls Intl. LLC, 2017

Confidential / Do Not Reproduce

Revised: November 22, 2017

Page 19 of 19

Revision AL

Design GX Valve Body and Actuator Assembly, Size NPS 3 / DN80

Description		Assembly Drawing
Valve & Pneumatic Actuator Assembly	Air to Open (Fail Closed)	GE39500
	Air to Closed (Fail Open)	GE39505
Port Guided Balanced Trim		GE07153
		GE07161
Extension Bonnet Assembly	DN80	GF00339
Bellows Bonnet Assembly	DN80	GF00340
Handwheel Assembly	Air to Close, Spring to Open	GE05810
	Air to Open, Spring to Close	GE05809
Packing Assembly	PTFE Packing	GE28943
	ULF Packing	GE28944
	ISO-Seal Packing	GF11007
Travel Stop Assembly	750 (20mm travel only)	GE24017
	750 (20mm travel only kit)	GE26229
Valve & Electric Actuator Assembly	Actuator Mounting	GG12175

Revision Change Record

The date recorded on this document reflects the effective date of this revision.

ECRN: 20171974

Matrix Section:

On page 2, in the find number table added 120 Packing Washer for the Item H.

Item	Module	Change
H	9	New – PTFE Coated N10276 Gasket for Bellows Bonnet with 1,2,3,4 NACE Indicator.