

### **Robotics 1**

## Position and orientation of rigid bodies

Prof. Alessandro De Luca


DIPARTIMENTO DI INGEGNERIA INFORMATICA AUTOMATICA E GESTIONALE ANTONIO RUBERTI



Robotics 1



### Position and orientation



- $x_A y_A z_A (x_B y_B z_B)$  are axis vectors (of unitary norm) of frame  $RF_A (RF_B)$
- components in  ${}^A\!R_B$  are the direction cosines of the axes of  $RF_B$  with respect to (w.r.t.)  $RF_A$


# STONE SERVICE STONE SERVICE SE

## Position of a rigid body

- for position representation, use of other coordinates than the Cartesian ones is possible, e.g., cylindrical or spherical
- direct transformation from cylindrical to Cartesian

$$x = r \cos \theta$$
$$y = r \sin \theta$$
$$z = h$$

is always well defined (with 
$$r > 0$$
 or  $r \geq 0$ )



inverse transformation from Cartesian to cylindrical

assuming +
$$(r > 0 \text{ only})$$

$$r = \sqrt{x^2 + y^2}$$

$$\frac{y}{x} = \tan \theta$$


$$\Rightarrow \qquad \theta = \text{atan2}\{y, x\}$$

$$h = z$$
with a singularity for  $x = y = 0$ 


four-quadrant arc tangent




### Orientation of a rigid body



$${}^{B}R_{A} = \begin{pmatrix} 0 & 1 & 0 \\ -1 & 0 & 0 \\ 0 & 0 & 1 \end{pmatrix} = {}^{A}R_{B}^{T}$$







$${}^{A}R_{B} = \begin{pmatrix} 0 & -1 & 0 \\ 1 & 0 & 0 \\ 0 & 0 & 1 \end{pmatrix}$$

$${}^{A}R_{A} = {}^{A}R_{B} {}^{B}R_{A} = I$$

$${}^{B}R_{C} = \begin{pmatrix} 0 & 0 & 1 \\ -1 & 0 & 0 \\ 0 & -1 & 0 \end{pmatrix} = {}^{B}R_{A} {}^{A}R_{C} = {}^{A}R_{B}^{T} {}^{A}R_{C}$$

$$\mathbf{z}_{C} \qquad {}^{A}R_{C} = \begin{pmatrix} 1 & 0 & 0 \\ 0 & 0 & 1 \\ 0 & -1 & 0 \end{pmatrix} \qquad \mathbf{z}_{2}$$







### **Rotation matrix**

$$egin{aligned} oldsymbol{x}_A^T oldsymbol{x}_B & oldsymbol{x}_A^T oldsymbol{x}_B & oldsymbol{x}_A^T oldsymbol{x}_B & oldsymbol{x}_A^T oldsymbol{x}_B & oldsymbol{y}_A^T oldsymbol{y}_B & oldsymbol{y}_A^T oldsymbol{z}_B & oldsymbol{y}_A^T oldsymbol{z}_B & oldsymbol{z}_A^T oldsymbol{z}_A & oldsymbol{z}_A & oldsymbol{z}_A & oldsymbol{z}_A & oldsymbol{z}_A & oldsymbol{z}$$


direction cosine of  $\boldsymbol{z}_B$  w.r.t.  $\boldsymbol{x}_A$ 

$$\mathbf{x}_A^T \mathbf{z}_B = \|\mathbf{x}_A\| \|\mathbf{z}_B\| \cos \beta$$
$$= \cos \beta$$

algebraic structure of a group SO(3): neutral element = I, inverse element =  $R^T$ 

orientation of  $RF_j$  w.r.t.  $RF_k$ 


### chain rule property



NOTE: in general, the product of rotation matrices does **not** commute!



### Change of coordinates





## Change of coordinates


$$^{1}\boldsymbol{p} = \begin{pmatrix} 1 \\ 1 \\ 1 \end{pmatrix}$$

$${}^{0}R_{1} = \begin{pmatrix} 1/\sqrt{3} & 1/\sqrt{3} & 1/\sqrt{3} \\ 1/\sqrt{6} & -2/\sqrt{6} & 1/\sqrt{6} \\ 1/\sqrt{2} & 0 & -1/\sqrt{2} \end{pmatrix}$$

$${}^{0}\boldsymbol{p} = {}^{0}R_{1} {}^{1}\boldsymbol{p} = \begin{pmatrix} \sqrt{3} \\ 0 \\ 0 \end{pmatrix}$$

$$\| \boldsymbol{p} \| = \| {}^{0}\boldsymbol{p} \| = \| {}^{1}\boldsymbol{p} \| = \sqrt{3}$$

... and where is  $RF_0$ ?




- $x_0$  is aligned with  $p = \overrightarrow{OP}$
- $\mathbf{z}_0$  is orthogonal to  $\mathbf{y}_1$  ( $\mathbf{z}_0^T \mathbf{y}_1 = 0$ ) and is positive on  $\mathbf{x}_1$  ( $\mathbf{z}_0^T \mathbf{x}_1 = 1/\sqrt{2}$ )
- y<sub>0</sub> completes a right-handed frame

### Orientation of frames in a plane



(elementary rotation around z-axis)



similarly:


$$R_{x}(\theta) = \begin{bmatrix} 1 & 0 & 0 \\ 0 & \cos \theta & -\sin \theta \\ 0 & \sin \theta & \cos \theta \end{bmatrix} \quad R_{y}(\theta) = \begin{bmatrix} \cos \theta & 0 & \sin \theta \\ 0 & 1 & 0 \\ -\sin \theta & 0 & \cos \theta \end{bmatrix}$$

$$R_z(-\theta) = R_z^T(\theta)$$

$$R_{y}(\theta) = \begin{bmatrix} \cos \theta & 0 & \sin \theta \\ 0 & 1 & 0 \\ -\sin \theta & 0 & \cos \theta \end{bmatrix}$$

### Rotation of a vector around z





$$x = \|\boldsymbol{v}\| \cos \alpha$$
$$y = \|\boldsymbol{v}\| \sin \alpha$$

$$x' = \|\mathbf{v}\| \cos (\alpha + \theta) = \|\mathbf{v}\| (\cos \alpha \cos \theta - \sin \alpha \sin \theta)$$

$$= x \cos \theta - y \sin \theta$$

$$y' = \|\mathbf{v}\| \sin (\alpha + \theta) = \|\mathbf{v}\| (\sin \alpha \cos \theta + \cos \alpha \sin \theta)$$

$$= x \sin \theta + y \cos \theta$$

$$z' = z$$


or...


$$\begin{bmatrix} x' \\ y' \\ z' \end{bmatrix} = \begin{bmatrix} \cos \theta & -\sin \theta & 0 \\ \sin \theta & \cos \theta & 0 \\ 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} x \\ y \\ z \end{bmatrix} = R_z(\theta) \begin{bmatrix} x \\ y \\ z \end{bmatrix} \quad \dots \text{ same as before!}$$


## Equivalent interpretations of a rotation matrix



the same rotation matrix (e.g.,  $R_z(\theta)$ ) may represent








the orientation of a rigid body with respect to a reference frame  $RF_0$ e.g.,  $[{}^0\boldsymbol{x}_c {}^0\boldsymbol{y}_c {}^0\boldsymbol{z}_c] = R_z(\theta)$  the change of coordinates from  $RF_C$  to  $RF_0$ e.g.,  ${}^0\boldsymbol{p} = R_z(\theta) \, {}^C\boldsymbol{p}$ 

the rotation operator on vectors e.g.,  $\mathbf{v}' = R_z(\theta) \ \mathbf{v}$ 

the rotation matrix  ${}^{0}R_{\mathcal{C}}$  is an operator superposing frame  $RF_{\mathcal{C}}$  to frame  $RF_{\mathcal{C}}$ 




## Composition of rotations



## Axis/angle representation





### **DATA**

- axis r (unit vector in  $\mathbb{R}^3$ , ||r|| = 1)
- angle θ, positive counterclockwise
   (as seen from an "observer" oriented like r with the head placed on the arrow, looking down to her/his feet)

### **DIRECT PROBLEM**

parametrized by the given data!

find a rotation matrix  $R(\theta, r)$ 


$$R(\theta, \mathbf{r}) = \begin{bmatrix} {}^{0}\mathbf{x}_{1} {}^{0}\mathbf{y}_{1} {}^{0}\mathbf{z}_{1} \end{bmatrix}$$

such that

$${}^{0}\boldsymbol{p} = R(\theta, \boldsymbol{r}) {}^{1}\boldsymbol{p} \quad {}^{0}\boldsymbol{v}' = R(\theta, \boldsymbol{r}) {}^{0}\boldsymbol{v}$$

# STORYM VE

### Axis/angle: Direct problem



$$R(\theta, \mathbf{r}) = C R_z(\theta) C^T$$

sequence of three rotations (one of which is elementary)

$$C = \begin{bmatrix} \mathbf{n} & \mathbf{s} & \mathbf{r} \\ \uparrow & \uparrow - \end{bmatrix}$$

after the first rotation the z-axis coincides with r

n and s are orthogonal unit vectors such that

$$n \times s = r$$

### Skew-symmetric matrices

# STATE OF THE PROPERTY OF THE P

whiteboard...

- properties of a skew-symmetric matrix
  - a square matrix S is skew-symmetric iff  $S^T = -S$  $\Leftrightarrow s_{ij} = -s_{ji} \Rightarrow s_{ii} = 0$  (zeros on the diagonal)
  - any square matrix A can be decomposed into its symmetric and skew-symmetric parts  $A = \frac{A+A^T}{2} + \frac{A-A^T}{2} = A_{symm} + A_{skew}$
  - in quadratic forms the skew-symmetric part vanishes (only the symmetric part matters)

$$x^{T}A x = \frac{1}{2}[x^{T}A x + (x^{T}A x)^{T}] = \frac{1}{2}[x^{T}A x + x^{T}A^{T}x] = x^{T}\frac{A + A^{T}}{2}x = x^{T}A_{symm} x$$

canonical form of a 3 × 3 skew-symmetric matrix

$$\boldsymbol{v} = \begin{bmatrix} x \\ y \\ z \end{bmatrix} \implies S(\boldsymbol{v}) = \begin{bmatrix} 0 & -z & y \\ z & 0 & -x \\ -y & x & 0 \end{bmatrix} \qquad S = \begin{bmatrix} 0 & -v_z & v_y \\ v_z & 0 & -v_x \\ -v_y & v_x & 0 \end{bmatrix} \implies \boldsymbol{v} = \begin{bmatrix} v_x \\ v_y \\ v_z \end{bmatrix}$$

also called vee map v

expression of the vector product between two vectors  $\in \mathbb{R}^3$  Sarrus rule for  $\begin{bmatrix} n_x & n_y & n_z \\ s_x & s_y & s_z \\ \hline n_z & n_z \end{bmatrix}$  and  $\mathbf{r} = \begin{bmatrix} n_x \\ n_y \\ n_z \end{bmatrix}$ ,  $\mathbf{r} = \begin{bmatrix} s_x \\ s_y \\ s_z \end{bmatrix}$   $\Rightarrow \mathbf{r} = \begin{bmatrix} r_x \\ r_y \\ r_z \end{bmatrix} = \mathbf{n} \times \mathbf{s} = \begin{bmatrix} n_y s_z - s_y n_z \\ n_z s_x - s_z n_x \\ n_x s_y - x n_y \end{bmatrix} = \mathbf{s} \cdot \mathbf{s} \cdot \mathbf{s} \cdot \mathbf{s} \cdot \mathbf{s}$ 

$$v_1 \times v_2 = S(v_1)v_2 = -v_2 \times v_1 = -S(v_2)v_1 = S^T(v_2)v_1$$

### Inner and outer products



whiteboard...

• (inner) row by column products between two 3×3 matrices

$$C^{T}C = \begin{bmatrix} \mathbf{n}^{T} \\ \mathbf{s}^{T} \\ \mathbf{r}^{T} \end{bmatrix} \begin{bmatrix} \mathbf{n} & \mathbf{s} & \mathbf{r} \end{bmatrix} = \begin{bmatrix} 1 & 0 & 0 \\ 0 & 1 & 0 \\ 0 & 0 & 1 \end{bmatrix} = I$$

• dyadic expansion of a  $n \times n$  matrix

$$\mathbf{e}_i = [0 \quad \dots \quad 1 \quad \dots \quad 0]^T, \qquad i = 1, \dots, n \quad \Rightarrow \quad A = \sum_{i,j=1}^n a_{ij} \mathbf{e}_i \mathbf{e}_j^T$$

• product of three  $n \times n$  matrices using dyadic form

$$B = \begin{bmatrix} \boldsymbol{b}_1 & \boldsymbol{b}_1 \dots & \boldsymbol{b}_{n-1} & \boldsymbol{b}_n \end{bmatrix} \implies B A B^T = \sum_{i,j=1}^n a_{ij} \boldsymbol{b}_i \boldsymbol{b}_j^T$$

(outer) column by row products between two 3×3 matrices

$$CC^{T} = I \implies CC^{T} = \begin{bmatrix} \mathbf{n} & \mathbf{s} & \mathbf{r} \end{bmatrix} \begin{bmatrix} \mathbf{n}^{T} \\ \mathbf{s}^{T} \\ \mathbf{r}^{T} \end{bmatrix} = \begin{bmatrix} \mathbf{n} & \mathbf{s} & \mathbf{r} \end{bmatrix} \begin{bmatrix} 1 & 0 & 0 \\ 0 & 1 & 0 \\ 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} \mathbf{n}^{T} \\ \mathbf{s}^{T} \\ \mathbf{r}^{T} \end{bmatrix}$$
$$= \mathbf{n}\mathbf{n}^{T} + \mathbf{s}\mathbf{s}^{T} + \mathbf{r}\mathbf{r}^{T} = I$$

### Axis/angle: Direct problem

solution

$$R(\theta, \mathbf{r}) = C R_z(\theta) C^T$$

$$R(\theta, \mathbf{r}) = \begin{bmatrix} \mathbf{n} & \mathbf{s} & \mathbf{r} \end{bmatrix} \begin{bmatrix} c\theta & -s\theta & 0 \\ s\theta & c\theta & 0 \\ 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} \mathbf{n}^T \\ \mathbf{s}^T \\ \mathbf{r}^T \end{bmatrix}$$
$$= \mathbf{r}\mathbf{r}^T + (\mathbf{n}\mathbf{n}^T + \mathbf{s}\mathbf{s}^T)^T c\theta + (\mathbf{s}\mathbf{n}^T - \mathbf{n}\mathbf{s}^T) s\theta$$

taking into account

$$CC^{T} = \boldsymbol{n}\boldsymbol{n}^{T} + \boldsymbol{s}\boldsymbol{s}^{T} + \boldsymbol{r}\boldsymbol{r}^{T} = I$$

$$\boldsymbol{s}\boldsymbol{n}^{T} - \boldsymbol{n}\boldsymbol{s}^{T} = \begin{bmatrix} 0 & -r_{z} & r_{y} \\ r_{z} & 0 & -r_{x} \\ -r_{y} & r_{x} & 0 \end{bmatrix} = S(\boldsymbol{r})$$

depends only on 
$$r$$
 and  $\theta$  !

depends only on 
$$r$$
 and  $\theta$ !  $\rightarrow R(\theta, r) = rr^T + (I - rr^T) c\theta + S(r) s\theta$ 



## Final expression of $R(\theta, \mathbf{r})$

### developing computations...

$$R(\theta, r) =$$

$$\begin{bmatrix} r_x^2(1-\cos\theta)+\cos\theta & r_xr_y(1-\cos\theta)-r_z\sin\theta & r_xr_z(1-\cos\theta)+r_y\sin\theta \\ r_xr_y(1-\cos\theta)+r_z\sin\theta & r_y^2(1-\cos\theta)+\cos\theta & r_yr_z(1-\cos\theta)-r_x\sin\theta \\ r_xr_z(1-\cos\theta)-r_y\sin\theta & r_yr_z(1-\cos\theta)+r_x\sin\theta & r_z^2(1-\cos\theta)+\cos\theta \end{bmatrix}$$

### note that

trace 
$$R(\theta, \mathbf{r}) = 1 + 2 \cos \theta$$
  
 $R(\theta, \mathbf{r}) = R(-\theta, -\mathbf{r}) = R^{T}(-\theta, \mathbf{r})$ 



## Axis/angle: a simple example

$$R(\theta, \mathbf{r}) = \mathbf{r}\mathbf{r}^T + (I - \mathbf{r}\mathbf{r}^T) c\theta + S(\mathbf{r}) s\theta$$

$$r = \begin{bmatrix} 0 \\ 0 \\ 1 \end{bmatrix} = \mathbf{z}_0$$

$$R(\theta, \mathbf{r}) = \begin{bmatrix} 0 & 0 & 0 \\ 0 & 0 & 0 \\ 0 & 0 & 1 \end{bmatrix} + \begin{bmatrix} 1 & 0 & 0 \\ 0 & 1 & 0 \\ 0 & 0 & 0 \end{bmatrix} c\theta + \begin{bmatrix} 0 & -1 & 0 \\ 1 & 0 & 0 \\ 0 & 0 & 0 \end{bmatrix} s\theta$$
$$= \begin{bmatrix} c\theta & -s\theta & 0 \\ s\theta & c\theta & 0 \\ 0 & 0 & 1 \end{bmatrix} = R_z(\theta)$$

Robotics 1



### Axis/angle: Rodriguez formula

$$\boldsymbol{v}' = R(\theta, \boldsymbol{r})\boldsymbol{v}$$

$$\mathbf{v}' = \mathbf{v}\cos\theta + (\mathbf{r}\times\mathbf{v})\sin\theta + (1-\cos\theta)(\mathbf{r}^T\mathbf{v})\mathbf{r}$$

proof

$$R(\theta, \mathbf{r})\mathbf{v} = (\mathbf{r}\mathbf{r}^T + (I - \mathbf{r}\mathbf{r}^T)\cos\theta + S(\mathbf{r})\sin\theta)\mathbf{v}$$
$$= \mathbf{r}\mathbf{r}^T\mathbf{v}(1 - \cos\theta) + \mathbf{v}\cos\theta + (\mathbf{r}\times\mathbf{v})\sin\theta$$


q.e.d.

## Properties of $R(\theta, r)$

- 1.  $R(\theta, r)r = r(r)$  is the invariant axis in this rotation)
- 2. when r is one of the coordinate axes, R boils down to one of the known elementary rotation matrices
- 3.  $(\theta, r) \to R$  is not an injective map:  $R(\theta, r) = R(-\theta, -r)$
- 4.  $det(R) = +1 = \prod_i \lambda_i$  (eigenvalues)
- 5.  $\operatorname{tr}(R) = \operatorname{tr}(rr^T) + (I r r^T)c\theta = 1 + 2c\theta = \sum_i \lambda_i$  in green hold for
  - $1. \Rightarrow \lambda_1 = 1$

4. & 5. 
$$\Rightarrow \lambda_2 + \lambda_3 = 2 c\theta \Rightarrow \lambda^2 - 2 c\theta \lambda + 1 = 0$$
  
 $\Rightarrow \lambda_{2,3} = c\theta \pm \sqrt{c^2\theta - 1} = c\theta \pm i s\theta = e^{\pm i\theta}$ 

all eigenvalues  $\lambda$  have unitary module ( $\Leftarrow R$  orthonormal)





### Axis/angle: Inverse problem

GIVEN a rotation matrix R, FIND a unit vector r and an angle  $\theta$  such that

$$R = rr^{T} + (I - rr^{T})\cos\theta + S(r)\sin\theta = R(\theta, r)$$

note first that  $tr(R) = R_{11} + R_{22} + R_{33} = 1 + 2 \cos \theta$ ; so, one could solve

$$\theta = \arccos \frac{R_{11} + R_{22} + R_{33} - 1}{2}$$

### but

- this formula provides only values in  $[0,\pi]$  (thus, never negative angles  $\theta$ )
- loss of numerical accuracy for  $\theta \to 0$  (sensitivity of  $\cos \theta$  is low around 0)

Robotics 1

### Axis/angle: Inverse problem



solution

from the data

from  $R(\theta, \mathbf{r})$ 

$$R - R^T = \begin{bmatrix} 0 & R_{12} - R_{21} & R_{13} - R_{31} \\ R_{21} - R_{12} & 0 & R_{23} - R_{32} \\ R_{31} - R_{13} & R_{32} - R_{23} & 0 \end{bmatrix} = 2 \sin \theta \begin{bmatrix} 0 & -r_z & r_y \\ r_z & 0 & -r_x \\ -r_y & r_x & 0 \end{bmatrix}$$

it follows

$$\|\boldsymbol{r}\| = 1 \implies \sin \theta = \pm \frac{1}{2} \sqrt{(R_{12} - R_{21})^2 + (R_{13} - R_{31})^2 + (R_{23} - R_{32})^2}$$
 (\*)

thus

$$\theta = \operatorname{atan2} \left\{ \pm \sqrt{(R_{12} - R_{21})^2 + (R_{13} - R_{31})^2 + (R_{23} - R_{32})^2}, R_{11} + R_{22} + R_{33} - 1 \right\}$$

see next slide

$$r = \begin{bmatrix} r_x \\ r_y \\ r_z \end{bmatrix} = \frac{1}{2 \sin \theta} \begin{bmatrix} R_{32} - R_{23} \\ R_{13} - R_{31} \\ R_{21} - R_{12} \end{bmatrix}$$
 can be used or test is made on

can be used only if

test is made on (\*) using the data  $\{R_{ii}\}$ 



### atan2 function

- arctangent with output values "in the four quadrants"
  - two input arguments
  - takes values in  $[-\pi, +\pi]$
  - undefined only for (0,0)
- uses the sign of both arguments to define the output quadrant
- based on arctan function with output values in  $[-\pi/2, +\pi/2]$
- available in main languages (C++, Matlab, ...)

$$\operatorname{atan2}(y,x) = \begin{cases} \arctan(\frac{y}{x}) & x > 0 \\ \pi + \arctan(\frac{y}{x}) & y \geq 0, x < 0 \\ -\pi + \arctan(\frac{y}{x}) & y < 0, x < 0 \\ \frac{\pi}{2} & y > 0, x = 0 \\ -\frac{\pi}{2} & y < 0, x = 0 \\ \operatorname{undefined} & y = 0, x = 0 \end{cases}$$

Robotics 1

### Singular cases

(use when  $\sin \theta = 0$ )



- if  $\theta = 0$  from (\*\*), there is no solution for r (rotation axis undefined)
- if  $\theta = \pm \pi$  from (\*\*), then set  $\sin \theta = 0$ ,  $\cos \theta = -1$  and solve

$$\Rightarrow R = 2rr^T - I$$

$$r = \begin{bmatrix} r_x \\ r_y \\ r_z \end{bmatrix} = \begin{bmatrix} \pm \sqrt{(R_{11} + 1)/2} \\ \pm \sqrt{(R_{22} + 1)/2} \\ \pm \sqrt{(R_{33} + 1)/2} \end{bmatrix} \text{ with } \begin{bmatrix} r_x r_y = R_{12}/2 \\ r_x r_z = R_{13}/2 \\ r_y r_z = R_{23}/2 \end{bmatrix} \Leftrightarrow \text{ used to resolve sign ambiguities } \Rightarrow \text{ two solutions of opposite sign}$$

$$r_x r_y = R_{12}/2$$
  
 $r_x r_z = R_{13}/2$   
 $r_y r_z = R_{23}/2$ 

used to resolve of opposite sign

homework: write a code that determines the two solutions  $(\theta, r)$ 

for 
$$R = \begin{bmatrix} -1 & 0 & 0 \\ 0 & -\frac{1}{\sqrt{2}} & -\frac{1}{\sqrt{2}} \\ 0 & -\frac{1}{\sqrt{2}} & \frac{1}{\sqrt{2}} \end{bmatrix}$$



### Unit quaternion

• to eliminate non-uniqueness and singular cases of the axis/angle  $(\theta, r)$  representation, the unit quaternion can be used

$$Q = \{\eta, \epsilon\} = \{\cos(\theta/2), \sin(\theta/2) r\}$$
 a scalar 3-dim vector

- $\eta^2 + ||\epsilon||^2 = 1$  (thus, "unit ...")
- $(\theta, r)$  and  $(-\theta, -r)$  are associated to the same quaternion Q
- the rotation matrix R associated to a given quaternion Q is

$$R(\eta, \epsilon) = \begin{bmatrix} 2(\eta^2 + \epsilon_x^2) - 1 & 2(\epsilon_x \epsilon_y - \eta \epsilon_z) & 2(\epsilon_x \epsilon_z + \eta \epsilon_y) \\ 2(\epsilon_x \epsilon_y + \eta \epsilon_z) & 2(\eta^2 + \epsilon_y^2) - 1 & 2(\epsilon_y \epsilon_z - \eta \epsilon_x) \\ 2(\epsilon_x \epsilon_z - \eta \epsilon_y) & 2(\epsilon_y \epsilon_z + \eta \epsilon_x) & 2(\eta^2 + \epsilon_z^2) - 1 \end{bmatrix}$$

- no rotation is  $Q = \{1, 0\}$ , while the inverse rotation is  $Q = \{\eta, -\epsilon\}$
- unit quaternions are composed with special rules

$$Q_1 * Q_2 = \{\eta_1 \eta_2 - \boldsymbol{\epsilon}_1^T \boldsymbol{\epsilon}_2, \eta_1 \boldsymbol{\epsilon}_2 + \eta_2 \boldsymbol{\epsilon}_1 + \boldsymbol{\epsilon}_1 \times \boldsymbol{\epsilon}_2\}$$