Experiment Report

Start of automated test report 2023-03-12 07:37:33
Author=luke@workstation obo Luke Vassallo

Machine Information

sysname=Linux
nodename=workstation
release=5.4.0-144-generic
version=#161~18.04.1-Ubuntu SMP Fri Feb 10 15:55:22 UTC 2023
machine=x86_64

CPU arch : X86_64
CPU bits : 64
CPU brand : Intel(R) Core(TM) i7-10700K CPU @ 3.80GHz
CPU cores : 16
CPU base clock : 3.8000 GHz
CPU boost clock : 4.2000 GHz
System Memory : 62.64GB
Nvidia driver version : 470.161.03
Device 0 : NVIDIA GeForce GTX 1080
Device 0 : 7.93GB

Library Information

python : 3.8.13
torch : 1.11.0+cu102
optuna : 3.1.0
numpy : 1.23.3
pandas : 1.5.3
matplotlib : 3.7.0
seaborn : 0.12.2

pcb library: generation of .pcb files.
Library version : 0.0.12
Library built with : C++14
Library built on : Mar 3 2023 23:10:31

netlist_graph: Graph pre-processing library for PCB component placement.
Library version : 0.1.16
Library built with : C++14
Library built on : Mar 3 2023 23:10:32

training_sac_cuda_622:1678569499_0

Steps per trial = 200

Euclidean wirelength (w) = 6

Half perimeter wirelength (hpwl) = 2.0

Overlap (o) = 2.0

Estimated Wirelength (HPWL)

Mean over all trials in run //home/luke/work/rl_pcb/tests/04_training_sac_cuda/work/eval_testing_set/1678569499_0

pcb name	run	0% overlap (#)[1]	10% overlap (#)[1]	20% overlap (#)[1]
voltage_datalogger_adc0	1678569499_0	nan ± nan (0)	32.18 ± 0.0 (1)	32.18 ± 0.0 (1)
voltage_datalogger_adc2	1678569499_0	19.3 ± 0.0 (1)	14.02 ± 1.84 (2)	13.14 ± 1.36 (2)
voltage_datalogger_afe	1678569499_0	nan ± nan (0)	nan ± nan (0)	51.01 ± 9.45 (2)

[1] # indicates the number of layouts over which the mean ± std was computed

Routed Wirelength

Mean over all trials in run //home/luke/work/rl_pcb/tests/04_training_sac_cuda/work/eval_testing_set/1678569499_0

pcb name	run	0% overlap (#)[1]	10% overlap (#)[1]	20% overlap (#)[1]
voltage_datalogger_adc0	1678569499_0	nan ± nan (0)	33.34 ± 0.0 (1)	33.34 ± 0.0 (1)
voltage_datalogger_adc2	1678569499_0	15.5 ± 0.0 (1)	17.63 ± 3.9 (2)	13.8 ± 0.03 (2)
voltage_datalogger_afe	1678569499_0	nan ± nan (0)	nan ± nan (0)	61.8 ± 17.95 (2)

[1] # indicates the number of layouts over which the mean ± std was computed

training_sac_cuda_622:1678569499_1

Steps per trial = 200

Euclidean wirelength (w) = 6

Half perimeter wirelength (hpwl) = 2.0

Overlap (o) = 2.0

Estimated Wirelength (HPWL)

Mean over all trials in run //home/luke/work/rl_pcb/tests/04_training_sac_cuda/work/eval_testing_set/1678569499_1

pcb name	run	0% overlap (#)[1]	10% overlap (#)[1]	20% overlap (#)[1]
voltage_datalogger_adc0	1678569499_1	nan ± nan (0)	30.97 ± 0.0 (1)	30.97 ± 0.0 (1)
voltage_datalogger_adc2	1678569499_1	18.73 ± 4.3 (2)	13.84 ± 0.97 (2)	13.04 ± 1.15 (2)
voltage_datalogger_afe	1678569499_1	nan ± nan (0)	46.76 ± 0.0 (1)	46.76 ± 0.0 (1)

[1] # indicates the number of layouts over which the mean ± std was computed

Routed Wirelength

Mean over all trials in run //home/luke/work/rl_pcb/tests/04_training_sac_cuda/work/eval_testing_set/1678569499_1

pcb name	run	0% overlap (#)[1]	10% overlap (#)[1]	20% overlap (#)[1]
voltage_datalogger_adc0	1678569499_1	nan ± nan (0)	36.04 ± 0.0 (1)	36.04 ± 0.0 (1)
voltage_datalogger_adc2	1678569499_1	15.86 ± 2.54 (2)	12.52 ± 0.17 (2)	11.51 ± 0.88 (2)
voltage_datalogger_afe	1678569499_1	nan ± nan (0)	51.93 ± 0.0 (1)	51.93 ± 0.0 (1)

[1] # indicates the number of layouts over which the mean ± std was computed