

For Review Purposes Only

Sun OpenSSO Enterprise 8.0 C API Reference for Application and Web Agent Development

Beta



Sun Microsystems, Inc.
4150 Network Circle
Santa Clara, CA 95054
U.S.A.

Part No: 820-3738-07
October 2008

Copyright 2008 Sun Microsystems, Inc. 4150 Network Circle, Santa Clara, CA 95054 U.S.A. All rights reserved.

Sun Microsystems, Inc. has intellectual property rights relating to technology embodied in the product that is described in this document. In particular, and without limitation, these intellectual property rights may include one or more U.S. patents or pending patent applications in the U.S. and in other countries.

U.S. Government Rights – Commercial software. Government users are subject to the Sun Microsystems, Inc. standard license agreement and applicable provisions of the FAR and its supplements.

This distribution may include materials developed by third parties.

Parts of the product may be derived from Berkeley BSD systems, licensed from the University of California. UNIX is a registered trademark in the U.S. and other countries, exclusively licensed through X/Open Company, Ltd.

Sun, Sun Microsystems, the Sun logo, the Solaris logo, the Java Coffee Cup logo, docs.sun.com, Java, and Solaris are trademarks or registered trademarks of Sun Microsystems, Inc. or its subsidiaries in the U.S. and other countries. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. in the U.S. and other countries. Products bearing SPARC trademarks are based upon an architecture developed by Sun Microsystems, Inc.

The OPEN LOOK and SunTM Graphical User Interface was developed by Sun Microsystems, Inc. for its users and licensees. Sun acknowledges the pioneering efforts of Xerox in researching and developing the concept of visual or graphical user interfaces for the computer industry. Sun holds a non-exclusive license from Xerox to the Xerox Graphical User Interface, which license also covers Sun's licensees who implement OPEN LOOK GUIs and otherwise comply with Sun's written license agreements.

Products covered by and information contained in this publication are controlled by U.S. Export Control laws and may be subject to the export or import laws in other countries. Nuclear, missile, chemical or biological weapons or nuclear maritime end uses or end users, whether direct or indirect, are strictly prohibited. Export or reexport to countries subject to U.S. embargo or to entities identified on U.S. export exclusion lists, including, but not limited to, the denied persons and specially designated nationals lists is strictly prohibited.

DOCUMENTATION IS PROVIDED "AS IS" AND ALL EXPRESS OR IMPLIED CONDITIONS, REPRESENTATIONS AND WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT, ARE DISCLAIMED, EXCEPT TO THE EXTENT THAT SUCH DISCLAIMERS ARE HELD TO BE LEGALLY INVALID.

Copyright 2008 Sun Microsystems, Inc. 4150 Network Circle, Santa Clara, CA 95054 U.S.A. Tous droits réservés.

Sun Microsystems, Inc. détient les droits de propriété intellectuelle relatifs à la technologie incorporée dans le produit qui est décrit dans ce document. En particulier, et ce sans limitation, ces droits de propriété intellectuelle peuvent inclure un ou plusieurs brevets américains ou des applications de brevet en attente aux Etats-Unis et dans d'autres pays.

Cette distribution peut comprendre des composants développés par des tierces personnes.

Certains composants de ce produit peuvent être dérivées du logiciel Berkeley BSD, licenciés par l'Université de Californie. UNIX est une marque déposée aux Etats-Unis et dans d'autres pays; elle est licenciée exclusivement par X/Open Company, Ltd.

Sun, Sun Microsystems, le logo Sun, le logo Solaris, le logo Java Coffee Cup, docs.sun.com, Java et Solaris sont des marques de fabrique ou des marques déposées de Sun Microsystems, Inc., ou ses filiales, aux Etats-Unis et dans d'autres pays. Toutes les marques SPARC sont utilisées sous licence et sont des marques de fabrique ou des marques déposées de SPARC International, Inc. aux Etats-Unis et dans d'autres pays. Les produits portant les marques SPARC sont basés sur une architecture développée par Sun Microsystems, Inc.

L'interface d'utilisation graphique OPEN LOOK et Sun a été développée par Sun Microsystems, Inc. pour ses utilisateurs et licenciés. Sun reconnaît les efforts de pionniers de Xerox pour la recherche et le développement du concept des interfaces d'utilisation visuelle ou graphique pour l'industrie de l'informatique. Sun détient une licence non exclusive de Xerox sur l'interface d'utilisation graphique Xerox, cette licence couvrant également les licenciés de Sun qui mettent en place l'interface d'utilisation graphique OPEN LOOK et qui, en outre, se conforment aux licences écrites de Sun.

Les produits qui font l'objet de cette publication et les informations qu'il contient sont régis par la législation américaine en matière de contrôle des exportations et peuvent être soumis au droit d'autres pays dans le domaine des exportations et importations. Les utilisations finales, ou utilisateurs finaux, pour des armes nucléaires, des missiles, des armes chimiques ou biologiques ou pour le nucléaire maritime, directement ou indirectement, sont strictement interdites. Les exportations ou réexportations vers des pays sous embargo des Etats-Unis, ou vers des entités figurant sur les listes d'exclusion d'exportation américaines, y compris, mais de manière non exclusive, la liste de personnes qui font objet d'un ordre de ne pas participer, d'une façon directe ou indirecte, aux exportations des produits ou des services qui sont régis par la législation américaine en matière de contrôle des exportations et la liste de ressortissants spécifiquement désignés, sont rigoureusement interdites.

LA DOCUMENTATION EST FOURNIE "EN L'ETAT" ET TOUTES AUTRES CONDITIONS, DECLARATIONS ET GARANTIES EXPRESSES OU TACITES SONT FORMELLEMENT EXCLUES, DANS LA MESURE AUTORISEE PAR LA LOI APPLICABLE, Y COMPRIS NOTAMMENT TOUTE GARANTIE IMPLICITE RELATIVE A LA QUALITE MARCHANDE, A L'APTITUDE A UNE UTILISATION PARTICULIERE OU A L'ABSENCE DE CONTREFACON.

List of Remarks

Contents

Preface	15
1 The C SDK Application Programming Interfaces	19
Where is the C SDK?	19
What is Included in the C SDK?	20
Header Files	20
Code Samples	21
Developing Web Policy Agents	22
Required C Libraries	22
Solaris Operating System	22
Linux Application Environment	23
Microsoft Windows	23
2 Authentication Data Types and Functions	25
The Authentication API for C	25
Authentication Call Sequence	25
Authentication Properties	26
Authentication Data Types	27
am_auth_context_t	27
am_auth_callback_t	28
am_auth_locale_t	29
Authentication Callback Data Types	30
am_auth_choice_callback_t	30
am_auth_confirmation_callback_t	31
am_auth_language_callback_t	32
am_auth_name_callback_t	33
am_auth_password_callback_t	34

am_auth_text_input_callback_t	35
am_auth_text_output_callback_t	35
Authentication Functions	36
am_auth_abort()	37
am_auth_create_auth_context()	37
am_auth_destroy_auth_context()	38
am_auth_get_callback()	39
am_auth_get_module_instance_names()	39
am_auth_get_organization_name()	40
am_auth_get_sso_token_id()	41
am_auth_get_status()	42
am_auth_has_more_requirements()	43
am_auth_init()	43
am_auth_login()	44
am_auth_logout()	45
am_auth_num_callbacks()	46
am_auth_submit_requirements()	46
3 Policy Data Types and Functions	49
The Policy API for C	49
Resources Strings	50
Resource Traits	50
Policy Evaluation	50
Policy Data Types	51
am_policy_result_t	51
am_policy_t	53
am_resource_traits_t	53
Policy Functions	56
am_policy_compare_urls()	56
am_policy_destroy()	58
am_policy_evaluate()	58
am_policy_evaluate_ignore_url_notenforced()	60
am_policy_get_url_resource_root()	62
am_policy_init()	63
am_policy_invalidate_session()	64

am_policy_is_notification_enabled()	65
am_policy_notify()	65
am_policy_resource_canonicalize()	66
am_policy_resource_has_patterns()	67
am_policy_result_destroy()	67
am_policy_service_init()	68
 4 Single Sign-On Data Types and Functions	 71
The Single Sign-on API for C	71
Single Sign-on Properties	71
Single Sign-on Calls	73
Non-Web Applications	78
Single Sign-on Data Types	79
am_sso_token_handle_t	79
am_sso_token_listener_func_t	79
Single Sign-on Functions	80
am_sso_add_listener()	81
am_sso_add_sso_token_listener()	82
am_sso_create_sso_token_handle()	84
am_sso_destroy_sso_token_handle()	85
am_sso_get_auth_level()	86
am_sso_get_auth_type()	86
am_sso_get_host()	87
am_sso_get_idle_time	87
am_sso_get_max_idle_time()	88
am_sso_get_max_session_time()	88
am_sso_get_principal()	89
am_sso_get_principal_set()	89
am_sso_get_property()	89
am_sso_get_sso_token_id()	90
am_sso_get_time_left()	91
am_sso_init()	91
am_sso_invalidate_token()	92
am_sso_is_valid_token()	93
am_sso_refresh_token()	94

am_sso_remove_listener()	95
am_sso_remove_sso_token_listener()	95
am_sso_set_property()	96
am_sso_validate_token()	97
5 Logging Data Types and Functions	99
The Logging API for C	99
Logging Data Types	100
am_log_record_t	100
am_log_module_id_t	100
Logging Functions	101
am_log_add_module()	101
am_log_flush_remote_log()	103
am_log_init()	103
am_log_is_level_enabled()	104
am_log_log()	105
am_log_log_record()	106
am_log_record_add_logininfo()	107
am_log_record_create()	108
am_log_record_destroy()	109
am_log_record_populate()	110
am_log_record_set_log_level()	110
am_log_record_set_log_message()	111
am_log_record_set_logininfo_props()	112
am_log_set_levels_from_string()	113
am_log_set_log_file()	113
am_log_set_module_level()	114
am_log_set_remote_info()	115
am_log_vlog()	116
6 Mapping Data Types and Functions	119
The Mapping API for C	119
Mapping Data Types	119
am_map_t	119
am_map_entry_iter_t	120

am_map_value_iter_t	120
Mapping Functions	121
am_map_clear()	121
am_map_copy()	122
am_map_create()	123
am_map_destroy()	123
am_map_entry_iter_destroy()	124
am_map_entry_iter_get_first_value()	124
am_map_entry_iter_get_key()	125
am_map_entry_iter_get_values()	126
am_map_entry_iter_is_entry_valid()	127
am_map_entry_iter_next()	127
am_map_erase()	128
am_map_find()	129
am_map_find_first_value()	129
am_map_for_each()	130
am_map_get_entries()	131
am_map_insert()	132
am_map_size()	133
am_map_value_iter_destroy()	134
am_map_value_iter_get()	134
am_map_value_iter_is_value_valid()	135
am_map_value_iter_next()	135
 7 Property Data Types and Functions	137
The Property API for C	137
Property Data Types	137
am_properties_t	137
am_properties_iter_t	138
Property Functions	138
am_properties_copy()	139
am_properties_create()	140
am_properties_destroy()	140
am_properties_get()	141
am_properties_get_boolean()	142

am_properties_get_boolean_with_default()	143
am_properties_get_entries()	143
am_properties_get_positive_number()	144
am_properties_get_signed()	145
am_properties_get_signed_with_default()	146
am_properties_get_unsigned()	146
am_properties_get_unsigned_with_default()	147
am_properties_get_with_default()	148
am_properties_is_set()	149
am_properties_iter_destroy()	150
am_properties_iter_get_key()	150
am_properties_iter_get_value()	151
am_properties_load()	151
am_properties_set()	152
am_properties_store()	153
8 Web Agent Data Types and Functions	155
Web Agent API for C	155
Web Agent Data Types	156
am_web_add_header_in_response_t	156
am_web_free_post_data_t	156
am_web_get_post_data_t	157
am_web_postcache_data_t	158
am_web_render_result_t	158
am_web_request_func_t	159
am_web_request_params_t	159
am_web_set_header_in_request_t	161
am_web_set_method_t	161
am_web_set_user_t	162
post_urls_t	162
Web Agent Function Pointers	163
am_web_add_header_in_response_func_t	163
am_web_free_post_data_func_t	164
am_web_get_cookie_sync_func_t	165
am_web_get_post_data_func_t	166

am_web_render_result_func_t	166
am_web_result_set_header_func_t	167
am_web_result_set_header_attr_in_request_func_t	168
am_web_result_set_header_attr_in_response_func_t	169
am_web_set_header_in_request_func_t	170
am_web_set_method_func_t	171
am_web_set_user_func_t	172
Web Agent Functions	173
am_agent_init()	174
am_web_build_advice_response()	175
am_web_check_cookie_in_post()	176
am_web_check_cookie_in_query()	177
am_web_clean_post_urls()	178
am_web_cleanup()	179
am_web_clear_attributes_map()	179
am_web_create_post_page()	180
am_web_create_post_preserve_urls()	180
am_web_delete_agent_configuration()	181
am_web_do_cookie_domain_set()	181
am_web_do_cookies_reset()	182
am_web_free_memory()	183
am_web_get_agent_server_host()	184
am_web_get_agent_configuration()	184
am_web_get_agent_server_port()	185
am_web_get_authType()	185
am_web_get_cookie_name()	186
am_web_get_notification_url()	186
am_web_get_parameter_value()	187
am_web_get_request_url()	188
am_web_get_token_from_assertion()	189
am_web_get_url_to_redirect()	190
am_web_get_user_id_param()	191
am_web_handle_notification()	192
am_web_http_decode()	192
am_web_init() for Agents 3.0	193
am_web_is_access_allowed()	194

am_web_is_cdsso_enabled()	195
am_web_is_cookie_present()	196
am_web_is_debug_on()	197
am_web_is_in_not_enforced_ip_list()	197
am_web_is_in_not_enforced_list()	198
am_web_is_logout_url()	199
am_web_is_max_debug_on()	199
am_web_is_notification()	200
am_web_is_owa_enabled()	201
am_web_is_owa_enabled_change_protocol()	201
am_web_is_owa_enabled_session_timeout_url()	202
am_web_is_postpreserve_enabled()	203
am_web_is_proxy_override_host_port_set()	203
am_web_is_valid_fqdn_url()	204
am_web_log_always()	204
am_web_log_auth()	205
am_web_log_debug()	206
am_web_log_error()	206
am_web_log_info()	207
am_web_log_max_debug()	207
am_web_log_warning()	207
am_web_logout_cookies_reset()	208
am_web_method_num_to_str()	209
am_web_method_str_to_num()	210
am_web_postcache_data_cleanup()	210
am_web_postcache_insert()	211
am_web_postcache_lookup()	212
am_web_postcache_remove()	212
am_web_process_request()	213
am_web_remove_authnrequest()	214
am_web_remove_parameter_from_query()	215
am_web_result_attr_map_set()	215
am_web_result_num_to_str()	217
am_web_set_cookie()	217

9 Additional Data Types and Functions	219
<am.h>	219
am_cleanup() Syntax	219
am_cleanup() Parameters	220
am_cleanup() Returns	220
<am_notify.h>	220
am_notify() Syntax	220
am_notify() Parameters	220
am_notify() Returns	221
<am_string_set.h>	221
String Data Types	221
String Functions	222
<am_types.h>	223
boolean_t	223
bool_t	223
am_status_t	223
am_status_to_string()	224
<am_utils.h>	226
am_http_cookie_encode()	226
am_http_cookie_decode()	227

Preface

The *Sun OpenSSO Enterprise 8.0 C API Reference* provides a listing of application programming interfaces (API) you can use to enable C applications to access the Sun OpenSSO Enterprise components. The *C API Reference* includes function descriptions and syntax.

Who Should Use This Book

The *C API Reference* is intended for use by IT professionals, network administrators and software developers who implement a network access platform using Sun servers and software. It is recommended that readers of this guide are familiar with the following technologies:

- C Programming
- Security Assertion Markup Language (SAML) Specifications
- eXtensible Markup Language (XML)
- Lightweight Directory Access Protocol (LDAP)
- HyperText Transfer Protocol (HTTP)
- HyperText Markup Language (HTML)

Related Documentation

Related documentation is available as follows:

- [“OpenSSO Enterprise 8.0 Core Documentation” on page 15](#)
- [“Adjunct Product Documentation” on page 17](#)

OpenSSO Enterprise 8.0 Core Documentation

The OpenSSO Enterprise 8.0 core documentation set contains the following titles:

- The *Sun Federated Access Manager 8.0 Early Access (EA) Release Notes* will be available online after the product is released. It gathers an assortment of last-minute information, including a description of what is new in this current release, known problems and limitations, installation notes, and how to report issues with the software or the documentation.

- The *Sun OpenSSO Enterprise 8.0 Technical Overview* provides high level explanations of how OpenSSO Enterprise components work together to protect enterprise assets and web-based applications. It also explains basic concepts and terminology.
- The *Sun OpenSSO Enterprise 8.0 Deployment Planning Guide* provides planning and deployment solutions for OpenSSO Enterprise based on the solution life cycle
- The *Sun OpenSSO Enterprise 8.0 Deployment 1: Single Sign-On with Load Balancing and Failover* provides instructions for building an OpenSSO solution incorporating authentication, authorization and access control. Procedures for load balancing and session failover are also included.
- The *Sun OpenSSO Enterprise 8.0 Deployment 2: Federation Using SAMLv2* provides instructions for building an OpenSSO solution incorporating SAML v2 federation. Installation and configuration procedures are included.
- The *Sun OpenSSO Enterprise 8.0 Installation and Configuration Guide* provides information for installing and configuring OpenSSO Enterprise.
- The *Sun OpenSSO Enterprise 8.0 Performance Tuning and Troubleshooting Guide* provides information on how to tune OpenSSO Enterprise and its related components for optimal performance.
- The *Sun OpenSSO Enterprise 8.0 Administration Guide* describes administrative tasks such as *how to create a realm* and *how to configure a policy*. Most of the tasks described can be performed using the administration console as well as the `famadm` command line utilities.
- The *Sun OpenSSO Enterprise 8.0 Administration Reference* is a guide containing information about the command line interfaces, configuration attributes, internal files, and error codes. This information is specifically formatted for easy searching.
- The *Sun OpenSSO Enterprise 8.0 Developer's Guide* offers information on how to customize OpenSSO Enterprise and integrate its functionality into an organization's current technical infrastructure. It also contains details about the programmatic aspects of the product and its API.
- The *Sun OpenSSO Enterprise 8.0 C API Reference for Application and Web Agent Development* (this guide) provides summaries of data types, structures, and functions that make up the public OpenSSO Enterprise C SDK for application and web agent development.
- The *Federated Access Manager 8.0 Java API Reference* provides information about the implementation of Java packages in OpenSSO Enterprise.
- The *Sun OpenSSO Enterprise Policy Agent 3.0 User's Guide for J2EE Agents* provides an overview of the policy functionality and the policy agents available for OpenSSO Enterprise.

Updates to the *Release Notes* and links to modifications of the core documentation can be found on the OpenSSO Enterprise page at docs.sun.com. Updated documents will be marked with a revision date.

Adjunct Product Documentation

Useful information can be found in the documentation for the following products:

- [Sun Java System Directory Server Enterprise Edition 6.0](#)
- [Sun Java System Web Server 7.0](#)
- [Sun Java System Application Server Platform Edition 9.0](#)

Typographic Conventions

The following table describes the typographic conventions that are used in this book.

TABLE P-1 Typographic Conventions

Typeface	Meaning	Example
AaBbCc123	The names of commands, files, and directories, and onscreen computer output	Edit your <code>.login</code> file. Use <code>ls -a</code> to list all files. <code>machine_name%</code> you have mail.
AaBbCc123	What you type, contrasted with onscreen computer output	<code>machine_name%</code> su Password:
<i>aabbcc123</i>	Placeholder: replace with a real name or value	The command to remove a file is <i>rm filename</i> .
<i>AaBbCc123</i>	Book titles, new terms, and terms to be emphasized	Read Chapter 6 in the <i>User's Guide</i> . A <i>cache</i> is a copy that is stored locally. Do <i>not</i> save the file. Note: Some emphasized items appear bold online.

Shell Prompts in Command Examples

The following table shows the default UNIX® system prompt and superuser prompt for the C shell, Bourne shell, and Korn shell.

TABLE P-2 Shell Prompts

Shell	Prompt
C shell	machine_name%
C shell for superuser	machine_name#
Bourne shell and Korn shell	\$
Bourne shell and Korn shell for superuser	#

◆ ◆ ◆ 1 CHAPTER 1

The C SDK Application Programming Interfaces

Sun OpenSSO Enterprise provides C application programming interfaces (API) and related information to form a software development kit (SDK) that can be used to enable external C applications to participate in OpenSSO Enterprise authentication, authorization, single sign-on (SSO), and logging operations. Additionally, the C SDK is a development kit for web agents — allowing developers to create web agents for containers that have not yet been provided for OpenSSO Enterprise. This chapter covers the following topics:

- “Where is the C SDK?” on page 19
- “What is Included in the C SDK?” on page 20
- “Developing Web Policy Agents” on page 22
- “Required C Libraries” on page 22

Where is the C SDK?

The OpenSSO Enterprise C SDK can be found in the `opensso` directory created on the machine to which OpenSSO Enterprise is deployed. From inside the top-level `opensso` directory, change into the `libraries/native/agent-csdk` directory where you will find `agent-csdk.zip` and a `README`. Within `agent-csdk.zip` are the following 32-bit and 64-bit libraries:

- `agent-csdk-solaris-sparc-32.tar.gz` is the C SDK for the Solaris SPARC 32-bit platform.
- `agent-csdk-solaris-sparc-64.tar.gz` is the C SDK for the Solaris SPARC 64-bit platform.
- `agent-csdk-solaris-x86.tar.gz` is the C SDK for the Solaris x86 32-bit platform.
- `agent-csdk-solaris-x86.tar.gz` is the C SDK for the Solaris x86 64-bit platform.
- `agent-csdk-linux-32.tar.gz` is the C SDK for the Linux 32-bit platform.
- `agent-csdk-linux-64.tar.gz` is the C SDK for the Linux 64-bit platform.
- `agent-csdk-windows-32.zip` is the C SDK for the Windows 32-bit platform.
- `agent-csdk-windows-64.zip` is the C SDK for the Windows 64-bit platform.

What is Included in the C SDK?

Each library contains header files, samples, and README files containing information on how to implement the C SDK. More information is in the following sections.

- “Header Files” on page 20
- “Code Samples” on page 21

Header Files

A *header file* is a text file that contains pieces of code written in the C programming language. The name of a header file, by convention, ends with the `.h` extension. It is inserted inside a program by coding the `#include` preprocessor directive. The OpenSSO Enterprise C header files are:

<code><am.h></code>	General utility routines provided by the OpenSSO Enterprise library.
<code><am_auth.h></code>	Data types and functions for developing custom authentication modules.
<code><am_log.h></code>	Data types and functions for logging on the local system or the OpenSSO Enterprise host.
<code><am_map.h></code>	Data types and functions for creating, destroying, and manipulating the map objects used by OpenSSO Enterprise.
<code><am_notify.h></code>	Data types and functions for implementing notifications.
<code><am_policy.h></code>	Data types and functions for using OpenSSO Enterprise policy objects.
<code><am_properties.h></code>	Data types and functions for property maps used by clients of the OpenSSO Enterprise client API.
<code><am_sso.h></code>	Data types and functions for implementing SSO.
<code><am_string_set.h></code>	Data types and functions for manipulating strings.
<code><am_types.h></code>	Common types and macros provided by OpenSSO Enterprise.
<code><am_utils.h></code>	This is an unsupported, early access version of utility functions. Functions and data structures may change without backward compatibility.
<code><am_web.h></code>	Data types and functions intended for use by OpenSSO Enterprise web agents.

Code Samples

OpenSSO Enterprise provides code samples that demonstrate how you can use the API to connect C applications to the OpenSSO Enterprise framework. The code samples are:

<code>am_auth_test.c</code>	Demonstrates the basic usage of the authentication API used to login to an instance of OpenSSO Enterprise.
<code>am_log_test.c</code>	Demonstrates the basic usage of the logging API used to write a message to the OpenSSO Enterprise logs.
<code>am_policy_test.c</code>	Demonstrates the basic usage of the policy API to evaluate access for specified resources.

Note – Before running the sample, be sure the password defined as the value of the property `com.sun.am.policy.am.password` in `AMAgent.properties` is in clear text as the sample does not decrypt it. Since `am_policy_test.c` is only a sample, this poses no security risk. For example:

```
com.sun.am.policy.am.username = UrlAccessAgent
com.sun.am.policy.am.password = clear-text-password
```

<code>am_sso_test.c</code>	Demonstrates the basic usage of the SSO API to perform session operations.
<code>apache_agent.c</code>	Demonstrates how to use the policy API to build a web agent for the Apache Web Server.



Caution – This is a sample web agent and is not intended to serve as a web agent in a real deployment.

<code>Makefile</code>	Makefile for building the sample agent.
<code>README.TXT</code>	Provides detailed instructions for building and executing sample programs.

Note – `am_web_agent_test.c`, referred to in this file, is no longer used.

Developing Web Policy Agents

The C SDK can be used to develop web policy agents. Web agents that are currently available for OpenSSO Enterprise can be downloaded from [the agents download page](#). Web agents that are not yet available can be developed using the C API and the included sample source files as a blueprint. See README.TXT in the `samples` directory for more information on using this *web policy agent development toolkit*.

Required C Libraries

The sample programs are run by launching a generated executable on the command line. The following sections contain instructions for the supported platforms. Be sure to set the library path appropriately for the platform you are using.

- “Solaris Operating System” on page 22
- “Linux Application Environment” on page 23
- “Microsoft Windows” on page 23

Solaris Operating System

For the Solaris™ operating System, set the `LD_LIBRARY_PATH` environment variable to include:

```
/usr/lib/mps:opensso-base/is_csdk/lib:/usr/lib:/usr/ucblib
```

Note – The `/usr/lib` directory is included before the `/usr/ucblib` directory so that common programs (such as editors) will continue to function.

These directories contain the following shared libraries:

- `libamsdk.so`
- `libxml2.so`
- `libssl3.so`
- `libnss3.so`
- `libplc4.so`
- `libplds4.so`
- `libnspr4.so`
- `libucb.so`

Linux Application Environment

For the Linux application environment, set the `LD_LIBRARY_PATH` environment variable to include:

```
/usr/lib/mps:opensso-base/is_csdk/lib:/usr/lib:/usr/ucblib
```

This directory contains the following shared libraries:

- libamsdk.so
- libxml2.so
- libssl3.so
- libnss3.so
- libplc4.so
- libplds4.so
- libnspr4.so

Microsoft Windows

When using Microsoft® Windows, you must have the `\\opensso-base\is_csdk\bin` directory in your path before launching the samples. Alternatively, you can run the `run.bat` script to launch the samples. The script will set your path appropriately.

◆ ◆ ◆ CHAPTER 2

Authentication Data Types and Functions

Sun OpenSSO Enterprise contains public data types and functions you can use in developing custom authentication modules. This chapter provides information and a reference guide to the authentication application programming interfaces (API). Reference summaries include a short description, syntax, parameters and returns. Prototypes are contained in the `<am_auth.h>` header file located in the `XXXXX` directory. The sample source `am_auth_test.c` demonstrates the basic usage of the API to login to an instance of OpenSSO Enterprise. This chapter contains the following sections:

- [“The Authentication API for C” on page 25](#)
- [“Authentication Data Types” on page 27](#)
- [“Authentication Callback Data Types” on page 30](#)
- [“Authentication Functions” on page 36](#)

The Authentication API for C

C applications can authenticate users with the OpenSSO Enterprise Authentication Service by using the authentication API for C. The C application contacts the Authentication Service to initiate the authentication process, and the Authentication Service responds with a set of requirements. The application then submits authentication credentials back to the Authentication Service and receives further authentication requirements back until there are no more to fulfill. After all requirements have been sent, the client makes one final call to determine if authentication has been successful or has failed.

Authentication Call Sequence

The sequence of calls necessary to authenticate to OpenSSO Enterprise begins with the function call `am_auth_create_auth_context()`. This call returns an `am_auth_context` structure that is then used for the rest of the authentication calls. Once the structure has been initialized, the `am_auth_login()` function is called. This indicates to the Authentication Service that an

authentication is desired. Depending on the parameters passed when creating the `am_auth_context` structure and making the `am_auth_login()` function call, the Authentication Service will determine the login requirements with which to respond. For example, if the requested authentication is to an organization configured for Lightweight Directory Access Protocol (LDAP) authentication with no authentication module chaining involved, the server will respond with a request for a user name and password. The client loops the function call `am_auth_has_more_requirements()`, fills in the needed information and submits this back to the server using the function call `am_auth_submit_requirements()`. (When the requirements are a user name and password, this will happen twice.) The final step is to make the function call `am_auth_get_status()` to determine if the authentication was successful or not.

Note – The `remote-auth.dtd` is the template used to format XML authentication requests sent to OpenSSO Enterprise and to parse XML authentication responses received by the external application. The attributes in the requests/responses correspond to elements in the `remote-auth.dtd`. In the example, user name corresponds to the `NameCallback` element and password to the `PasswordCallback` element in the `remote-auth.dtd`. More information on `remote-auth.dtd` can be found in [Chapter 2, “Using the Authentication Interfaces,” in *Sun OpenSSO Enterprise 8.0 Developer’s Guide*](#).

Authentication Properties

With the newly developed policy agents 3.0, `AMAgent.properties` has been replaced with `OpenSSOAgentBootstrap.properties` and `OpenSSOAgentConfiguration.properties`. Properties in `OpenSSOAgentBootstrap.properties` are mandatory for any C API to work. Properties in `OpenSSOAgentConfiguration.properties` will only be used if the repository type of the agent user is `local`. If the repository type is `centralized`, any required properties not in `OpenSSOAgentBootstrap.properties` will be retrieved from the OpenSSO Enterprise server.

Note – See [“Centralized Agent Configuration” in *Sun OpenSSO Enterprise 8.0 Technical Overview*](#) for more information.

The following table lists the mandatory properties in `OpenSSOAgentBootstrap.properties`.

TABLE 2-1 Policy Agent 3.0 Properties Needed by the Authentication API for C

Property	Definition
<code>com.sun.identity.agents.config.naming.url</code>	URL of the OpenSSO Enterprise Naming Service in the format: <code>http://server.domain:port/opensso/namingservice</code>

TABLE 2-1 Policy Agent 3.0 Properties Needed by the Authentication API for C (Continued)

Property	Definition
<code>com.sun.identity.agents.config.local.logfile</code>	The logging directory in the format: <i>path-to-directory/logs/auth-log</i> Note – This property may be added to <code>FAMAgentBootstrap.properties</code> .
<code>com.sun.identity.agents.config.debug.level</code>	The level at which logs are written in the format: all:# where # is the level 5 being the highest, 3 medium and 1 the lowest.
<code>com.sun.identity.agents.config.sslcert.dir</code>	Path to the directory containing the certificate and key databases for Secure Sockets Layer (SSL).
<code>com.sun.identity.agents.config.certdb.prefix</code>	Set this property if the certificate databases in the directory specified by <code>com.sun.am.sslcert.dir</code> has a prefix.
<code>com.sun.identity.agents.config.certdb.password</code>	The password to the key3.db file. Note – This property may be added to <code>OpenSSOAgentBootstrap.properties</code> .
<code>com.sun.identity.agents.config.trust.server.certs</code>	Defines whether or not to trust SSL certificates not defined in the certificate database. Takes a value of true or false where true enables trust.
<code>com.sun.identity.agents.config.certificate.alias</code>	The nick name of the client certificate in the cert7.db. Note – This property may be added to <code>OpenSSOAgentBootstrap.properties</code> .

Authentication Data Types

The authentication types defined in `<am_auth.h>` are:

- [“am_auth_context_t” on page 27](#)
- [“am_auth_callback_t” on page 28](#)
- [“am_auth_locale_t” on page 29](#)

am_auth_context_t

Pointer to the authentication context object representing the details of an authentication action.

Syntax

```
#include "am_auth.h"
typedef struct am_auth_context *am_auth_context_t;
```

Members

`am_auth_context` is an opaque structure with no accessible members.

Memory Concerns

The implementation takes care of creating memory.

`am_auth_callback_t`

Primary callback type for authentication.

Details

`am_auth_callback_t` interacts with the calling application, allowing for the retrieval of specific authentication data (such as user name and password), or the display of error, warning or informational messages. It does not technically retrieve or display the information but provides the means to pass requests between an application and the OpenSSO Enterprise Authentication Service. `struct am_auth_callback` is a C implementation of the Java `javax.security.auth.callback` package. The Java API Reference for this package can be found at <http://java.sun.com/j2se/1.5.0/docs/api/>.

Syntax

```
#include "am_auth.h"
typedef struct am_auth_callback {
    am_auth_callback_type_t callback_type;
    union am_auth_callback_info {
        am_auth_choice_callback_t choice_callback;
        am_auth_confirmation_callback_t confirmation_callback;
        am_auth_language_callback_t language_callback;
        am_auth_name_callback_t name_callback;
        am_auth_password_callback_t password_callback;
        am_auth_text_input_callback_t text_input_callback;
        am_auth_text_output_callback_t text_output_callback;
    } callback_info;
} am_auth_callback_t;
```

Members

<code>callback_type</code>	Indicates the kind of callback that will be used. Each <code>callback_type</code> has a defined structure with a response field to submit authentication credentials. The value of <code>callback_type</code> determines the member of the union defined for the <code>callback_info</code> member. The possible values are defined in the enumeration:
----------------------------	---

```
typedef enum am_auth_callback_type {
    ChoiceCallback = 0,
    ConfirmationCallback,
    LanguageCallback,
    NameCallback,
    PasswordCallback,
    TextInputCallback,
    TextOutputCallback
} am_auth_callback_type_t;
```

Note – Each `callback_type` corresponds to the callback class of the same name in the Java `javax.security.auth.callback` package. The Java API Reference for this package can be found at <http://java.sun.com/j2se/1.5.0/docs/api/>.

`callback_info` Represents the defined `callback_type`. More information on the specific callbacks can be found in “[Authentication Callback Data Types](#)” on [page 30](#).

Memory Concerns

Memory for the callback members is allocated in the `am_auth_login()` call, and freed in the `am_auth_destroy_auth_context()` call. Memory for the response field, though, must be allocated and freed by the caller.

am_auth_locale_t

Data type that holds the attributes that define the locale retrieved in `am_auth_language_callback_t`.

Details

For more information, see “[am_auth_language_callback_t](#)” on [page 32](#).

Syntax

```
#include "am_auth.h"
typedef struct am_auth_locale {
    const char *language;
    const char *country;
    const char *variant;
} am_auth_locale_t;
```

Members

language	Pointer to a valid lower case, two-character ISO—639 language code as defined at http://www.ics.uci.edu/pub/ietf/http/related/iso639.txt .
country	Pointer to a valid upper case, two-character ISO—3166 country code as defined at http://www.chemie.fu-berlin.de/diverse/doc/ISO_3166.html .
variant	Pointer to a vendor or browser-specific character code. For example, WIN for Windows, MAC for Macintosh, and POSIX for POSIX.

Authentication Callback Data Types

This section contains further details on the callback types as discussed in “`am_auth_callback_t`” on page 28. They are:

- “`am_auth_choice_callback_t`” on page 30
- “`am_auth_confirmation_callback_t`” on page 31
- “`am_auth_language_callback_t`” on page 32
- “`am_auth_name_callback_t`” on page 33
- “`am_auth_password_callback_t`” on page 34
- “`am_auth_text_input_callback_t`” on page 35
- “`am_auth_text_output_callback_t`” on page 35

Note – Each type corresponds to the callback class of the same name in the Java `javax.security.auth.callback` package. The Java API Reference for this package can be found at <http://java.sun.com/j2se/1.5.0/docs/api/>.

`am_auth_choice_callback_t`

Displays a list of choices and submits the selection back to the OpenSSO Enterprise Authentication Service.

Details

`am_auth_choice_callback_t` is a C implementation of the Java `javax.security.auth.callback.ChoiceCallback` class.

Syntax

```
#include "am_auth.h"
typedef struct am_auth_choice_callback {
    const char *prompt;
```

```

    boolean_t allow_multiple_selections;
    const char **choices;
    size_t choices_size;
    size_t default_choice;
    const char **response; /* selected indexes */
    size_t response_size;
} am_auth_choice_callback_t;

```

Members

<code>prompt</code>	Pointer to the user's prompt.
<code>allow_multiple_selections</code>	Takes a value based on the <code>boolean_t</code> defined in the <code><am_types.h></code> header file. Set to <code>B_TRUE</code> if multiple selections can be made.
<code>choices</code>	Pointer to a pointer to the strings for the different choices.
<code>choices_size</code>	Value based on the <code>size_t</code> defined in the standard <code><stddef.h></code> header file that reflects the number of choices in the list.
<code>default_choice</code>	Takes a value based on the <code>size_t</code> defined in the standard <code><stddef.h></code> header file that reflects the choice selected by default when the list is displayed.
<code>response</code>	Pointer to a pointer to the choice(s) returned to OpenSSO Enterprise.
<code>response_size</code>	Takes a value based on the <code>size_t</code> defined in the standard <code><stddef.h></code> header file that reflects the number of selected choices in the response.

Memory Concerns

Memory for the choices list is allocated by `am_auth_login()`, and freed by calling `am_auth_destroy_auth_context()`. Memory for the response must be allocated and freed by the caller.

`am_auth_confirmation_callback_t`

Requests YES/NO, OK/CANCEL, YES/NO/CANCEL or similar confirmations.

Details

`am_auth_confirmation_callback_t` is a C implementation of the Java `javax.security.auth.callback.ConfirmationCallback` class.

Syntax

```
#include "am_auth.h"
typedef struct am_auth_confirmation_callback_info {
    const char *prompt;
    const char *message_type;
    const char *option_type;
    const char **options;
    size_t options_size;
    const char *default_option;
    const char *response; /* selected index */
} am_auth_confirmation_callback_t;
```

Members

<code>prompt</code>	Pointer to the user's prompt.
<code>message_type</code>	Pointer to the message type defined as <code>INFORMATION</code> , <code>WARNING</code> or <code>ERROR</code> .
<code>option_type</code>	Pointer to the option type defined as <code>YES_NO_OPTION</code> , <code>YES_NO_CANCEL_OPTION</code> , <code>OK_CANCEL_OPTION</code> , or <code>UNSPECIFIED</code> .
<code>options</code>	Pointer to a pointer to a list of confirmation options, or <code>NULL</code> if the callback was instantiated with an <code>option_type</code> .
<code>options_size</code>	Takes a value based on the <code>size_t</code> defined in the standard <code><stddef.h></code> header file that reflects the number of options in the list.
<code>default_option</code>	Pointer to the option selected by default when the list is displayed.
<code>response</code>	Pointer to the choice returned to OpenSSO Enterprise.

Memory Concerns

Memory is allocated by `am_auth_login()`, and freed by calling `am_auth_destroy_auth_context()`. Memory for the response must be allocated and freed by the caller.

`am_auth_language_callback_t`

Retrieves the locale for localizing text.

Details

`am_auth_language_callback_t` is a C implementation of the Java `javax.security.auth.callback.LanguageCallback` class.

Note – See “[am_auth_locale_t](#)” on page 29 for the individual components.

Syntax

```
#include "am_auth.h"
typedef struct am_auth_language_callback_info {
    am_auth_locale_t *locale;
    am_auth_locale_t *response; /* locale */
} am_auth_language_callback_t;
```

Members

<code>locale</code>	Pointer to the <code>am_auth_locale_t</code> object defining the locale.
<code>response</code>	Pointer to the <code>am_auth_locale_t</code> object being submitted back to OpenSSO Enterprise.

Memory Concerns

Memory is allocated by `am_auth_login()`, and freed by calling `am_auth_destroy_auth_context()`. Memory for the response must be allocated and freed by the caller.

`am_auth_name_callback_t`

Retrieves user name information.

Details

`am_auth_name_callback_t` is a C implementation of the Java `javax.security.auth.callback.NameCallback` class.

Syntax

```
#include "am_auth.h"
typedef struct am_auth_name_callback_info {
    const char *prompt;
    const char *default_name;
```

```
    const char *response; /* name */
} am_auth_name_callback_t;
```

Members

prompt	Pointer to the user's prompt.
default_name	Pointer to the default name displayed with the user prompt, if any.
response	Pointer to the name submitted back to OpenSSO Enterprise.

Memory Concerns

Memory is allocated by `am_auth_login()`, and freed by calling `am_auth_destroy_auth_context()`. Memory for the response must be allocated and freed by the caller.

am_auth_password_callback_t

Retrieves user password information.

Details

`am_auth_password_callback_t` is a C implementation of the Java `javax.security.auth.callback.PasswordCallback` class.

Syntax

```
#include "am_auth.h"
typedef struct am_auth_password_callback_info {
    const char *prompt;
    boolean_t echo_on;
    const char *response; /* password */
} am_auth_password_callback_t;
```

Members

prompt	Pointer to the user's prompt.
echo_on	Takes a value based on the <code>boolean_t</code> defined in the <code><am_types.h></code> header file. Set to <code>B_TRUE</code> to display the password as it is typed.
response	Pointer to the password submitted back to OpenSSO Enterprise.

Memory Concerns

Memory is allocated by `am_auth_login()`, and freed by calling `am_auth_destroy_auth_context()`. Memory for the response must be allocated and freed by the caller.

`am_auth_text_input_callback_t`

Retrieves generic textual information.

Details

`am_auth_text_input_callback_t` is a C implementation of the Java `javax.security.auth.callback.TextInputCallback` class.

Syntax

```
#include "am_auth.h"
typedef struct am_auth_text_input_callback_info {
    const char *prompt;
    const char *default_text;
    const char *response; /* text */
} am_auth_text_input_callback_t;
```

Members

<code>prompt</code>	Pointer to the user's prompt.
<code>default_text</code>	Pointer to the default text to be displayed with the user prompt.
<code>response</code>	Pointer to the text submitted back to OpenSSO Enterprise.

Memory Concerns

Memory is allocated by `am_auth_login()`, and freed by calling `am_auth_destroy_auth_context()`. Memory for the response must be allocated and freed by the caller.

`am_auth_text_output_callback_t`

Displays information messages, warning messages, and error messages.

Details

`am_auth_text_output_callback_t` is a C implementation of the Java `javax.security.auth.callback.TextOutputCallback` class.

Syntax

```
#include "am_auth.h"
typedef struct am_auth_text_output_callback_info {
    const char *message;
    const char *message_type;
} am_auth_text_output_callback_t;
```

Members

`message` Pointer to the message to be displayed.

`message_type` Pointer to the message type: INFORMATION, WARNING, or ERROR.

Memory Concerns

Memory is allocated by `am_auth_login()`, and freed by calling `am_auth_destroy_auth_context()`.

Authentication Functions

The authentication functions defined in `<am_auth.h>` are:

- `"am_auth_abort()"` on page 37
- `"am_auth_create_auth_context()"` on page 37
- `"am_auth_destroy_auth_context()"` on page 38
- `"am_auth_get_callback()"` on page 39
- `"am_auth_get_module_instance_names()"` on page 39
- `"am_auth_get_organization_name()"` on page 40
- `"am_auth_get_sso_token_id()"` on page 41
- `"am_auth_get_status()"` on page 42
- `"am_auth_has_more_requirements()"` on page 43
- `"am_auth_init()"` on page 43
- `"am_auth_login()"` on page 44
- `"am_auth_logout()"` on page 45
- `"am_auth_num_callbacks()"` on page 46
- `"am_auth_submit_requirements()"` on page 46

am_auth_abort()

Aborts an authentication process that has not been completed.

Syntax

```
#include "am_auth.h"
AM_EXPORT am_status_t
am_auth_abort(am_auth_context_t auth_ctx);
```

Parameters

This function takes the following parameter:

`auth_ctx` The `am_auth_context_t` type.

Note – See “[am_auth_context_t](#)” on page 27 for information.

Returns

This function returns one of the following values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file):

<code>AM_SUCCESS</code>	If the process was successfully stopped.
<code>AM_INVALID_ARGUMENT</code>	If the <code>auth_ctx</code> parameter is <code>NULL</code> .

am_auth_create_auth_context()

Creates the context for the authentication and a pointer to it.

Syntax

```
#include "am_auth.h"
AM_EXPORT am_status_t
am_auth_create_auth_context(am_auth_context_t *auth_ctx,
                           const char *org_name,
                           const char *cert_nick_name,
                           const char *url);
```

Parameters

This function takes the following parameters:

`auth_ctx` Pointer to the `am_auth_context_t` type.

Note – See “[am_auth_context_t](#)” on page 27 for information.

<code>org_name</code>	Pointer to the name of the organization for which the authentication context is being initialized. May be NULL to use the value defined in the <code>AMAgent.properties</code> file.
<code>cert_nick_name</code>	Pointer to the alias of the certificate being used if the application will connect securely to OpenSSO Enterprise. May be NULL if the connection is not secure.
<code>url</code>	Pointer to the OpenSSO Enterprise Naming Service URL. May be NULL to use the Naming Service URL defined in the <code>AMAgent.properties</code> file.

Returns

This function returns a pointer to the authentication context object and one of the following values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file):

<code>AM_SUCCESS</code>	If the authentication context was successfully created.
<code>AM_NO_MEMORY</code>	If unable to allocate memory for the handle.
<code>AM_INVALID_ARGUMENT</code>	If the <code>auth_ctx</code> parameter is NULL.
<code>AM_AUTH_CTX_INIT_FAILURE</code>	If the authentication initialization failed.

am_auth_destroy_auth_context()

Eliminates the specified authentication context.

Syntax

```
#include "am_auth.h"
AM_EXPORT am_status_t
am_auth_destroy_auth_context(am_auth_context_t auth_ctx);
```

Parameters

This function takes the following parameter:

`auth_ctx` The `am_auth_context_t` type.

Note – See “[am_auth_context_t](#)” on page 27 for information.

Returns

This function returns one of the following values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file):

<code>AM_SUCCESS</code>	If the pointer was successfully destroyed.
<code>AM_INVALID_ARGUMENT</code>	If the <code>auth_ctx</code> parameter is <code>NULL</code> .

`am_auth_get_callback()`

Retrieves the appropriate callback structure to populate with authentication requirements.

Syntax

```
#include "am_auth.h"
AM_EXPORT am_auth_callback_t *
am_auth_get_callback(am_auth_context_t auth_ctx,
                    size_t index);
```

Parameters

This function takes the following parameters:

`auth_ctx` The `am_auth_context_t` type.

Note – See “[am_auth_context_t](#)” on [page 27](#) for information.

`index` Takes a value based on `size_t` defined in the standard `<stddef.h>` header file that initializes the index into the callback array.

Returns

This function returns a pointer to the `am_auth_callback_t` type. See “[am_auth_callback_t](#)” on [page 28](#) for more information.

`am_auth_get_module_instance_names()`

Retrieves the authentication module plug-in instances configured for the organization (or sub-organization) defined in the `am_auth_context_t` type.

Details

Module instance names are retrieved in pointer to a pointer to a `am_string_set_t` type (as defined in the `<am_string_set.h>` header file).

Syntax

```
#include "am_auth.h"
AM_EXPORT am_status_t
am_auth_get_module_instance_names(am_auth_context_t auth_ctx,
                                  am_string_set_t** module_inst_names_ptr);
```

Parameters

This function takes the following parameters:

`auth_ctx` The `am_auth_context_t` type.

Note – See “[am_auth_context_t](#)” on [page 27](#) for information.

`module_inst_names_ptr` Pointer to a pointer to the `am_string_set_t` type.

Returns

This function returns a pointer to a pointer with the list of module instance names (or NULL if the number of configured modules is zero) and one of the following values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file):

- | | |
|---|--|
| <code>AM_SUCCESS</code> | If the submitted requirements were processed successfully. |
| <code>AM_AUTH_FAILURE</code> | If the authentication process failed. |
| <code>AM_INVALID_ARGUMENT</code> | If the <code>auth_ctx</code> parameter is NULL. |
| <code>AM_SERVICE_NOT_INITIALIZED</code> | If the OpenSSO Enterprise Authentication Service is not initialized. |

Memory Concerns

The implementation takes care of allocating memory for the `module_inst_names_ptr`.

`am_auth_get_organization_name()`

Retrieves the organization to which the user is authenticated.

Syntax

```
#include "am_auth.h"
AM_EXPORT const char *
am_auth_get_organization_name(am_auth_context_t auth_ctx);
```

Parameters

This function takes the following parameter:

`auth_ctx` The `am_auth_context_t` type.

Note – See [“`am_auth_context_t`” on page 27](#) for information.

Returns

This function returns a pointer with one of the following values:

Zero-terminated string representing the organization.

After the user successfully logs in.

NULL

If there was an error or the user has not successfully logged in.

`am_auth_get_sso_token_id()`

Retrieves the session identifier for the authenticated user.

Details

The *SSTokenID* is a randomly-generated string that represents an authenticated user. See [“Single Sign-on Token Handles” on page 74](#) for more information.

Syntax

```
#include "am_auth.h"
AM_EXPORT const char *
am_auth_get_sso_token_id(am_auth_context_t auth_ctx);
```

Parameters

This function takes the following parameter:

`auth_ctx` The `am_auth_context_t` type.

Note – See “[am_auth_context_t](#)” on page 27 for information.

Returns

This function returns a pointer with one of the following values:

Zero-terminated string representing the session token.

After the user successfully logs in.

NULL

If there was an error or the user has not successfully logged in.

am_auth_get_status()

Retrieves the state of the authentication process.

Syntax

```
#include "am_auth.h"
AM_EXPORT am_auth_status_t
am_auth_get_status(am_auth_context_t auth_ctx);
```

Parameters

This function takes the following parameter:

`auth_ctx` The `am_auth_context_t` type.

Note – See “[am_auth_context_t](#)” on page 27 for information.

Returns

This function returns one of the following values of the `am_auth_status_t` enumeration as defined:

```
typedef enum am_auth_status {
    AM_AUTH_STATUS_SUCCESS = 0,
    AM_AUTH_STATUS_FAILED,
    AM_AUTH_STATUS_NOT_STARTED,
    AM_AUTH_STATUS_IN_PROGRESS,
    AM_AUTH_STATUS_COMPLETED
} am_auth_status_t;
```

`AM_AUTH_STATUS_FAILED` The login process has failed.

`AM_AUTH_STATUS_NOT_STARTED` The login process has not started.

AM_AUTH_STATUS_IN_PROGRESS	The login is in progress.
AM_AUTH_STATUS_COMPLETED	The user has been logged out.
AM_AUTH_STATUS_SUCCESS	The user has logged in.

am_auth_has_more_requirements()

Checks to see if there are additional requirements needed to complete the login process.

Details

`am_auth_has_more_requirements()` is invoked after the `am_auth_login()` call. If there are requirements to be supplied, the caller retrieves and submits the requirements in the form of callbacks.

Syntax

```
#include "am_auth.h"
AM_EXPORT boolean_t
am_auth_has_more_requirements(am_auth_context_t auth_ctx);
```

Parameters

This function takes the following parameter:

`auth_ctx` The `am_auth_context_t` type.

Note – See “[am_auth_context_t](#)” on page 27 for information.

Returns

This function returns one of the following values of the `boolean_t` enumeration (defined in the `<am_types.h>` header file):

`B_TRUE` If there are more requirements.
`B_FALSE` If there are no more requirements.

am_auth_init()

Initializes the authentication module using the pointer returned by `am_auth_create_auth_context()`.

Syntax

```
#include "am_auth.h"
AM_EXPORT am_status_t
am_auth_init(const am_properties_t auth_init_params);
```

Parameters

This function takes the following parameter:

auth_init_params	The am_properties_t type which contains the module initialization properties.
------------------	---

Note – See “[am_properties_t](#)” on page 137 for information.

Returns

This function returns one of the following values of the am_status_t enumeration (defined in the <am_types.h> header file):

AM_SUCCESS	If the initialization of the library is successful.
AM_NO_MEMORY	If unable to allocate memory during initialization.
AM_INVALID_ARGUMENT	If auth_init_params is NULL.
Others	See “ am_status_t ” on page 223.

am_auth_login()

Begins the login process given the index type and its value.

Syntax

```
#include "am_auth.h"
AM_EXPORT am_status_t
am_auth_login(am_auth_context_t auth_ctx,
              am_auth_index_t auth_idx,
              const char *value);
```

Parameters

This function takes the following parameters:

auth_ctx	The am_auth_context_t type.
----------	-----------------------------

Note – See “[am_auth_context_t](#)” on page 27 for information.

auth_idx Defines the resource for which the authentication is being performed. Based on the `am_auth_index_t` enumeration used to initiate the login process:

```
typedef enum am_auth_idx {
    AM_AUTH_INDEX_AUTH_LEVEL = 0,
    AM_AUTH_INDEX_ROLE,
    AM_AUTH_INDEX_USER,
    AM_AUTH_INDEX_MODULE_INSTANCE,
    AM_AUTH_INDEX_SERVICE
} am_auth_index_t;
```

value Pointer to the authentication module being used.

Note – See “[Authentication Modules](#)” in *Sun OpenSSO Enterprise 8.0 Administration Guide* for more information.

Returns

This function returns one of the following values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file):

<code>AM_SUCCESS</code>	If the login process was successfully completed.
<code>AM_INVALID_ARGUMENT</code>	If the <code>auth_ctx</code> or <code>value</code> parameter is <code>NULL</code> .
<code>AM_FEATURE_UNSUPPORTED</code>	If the <code>auth_idx</code> parameter is invalid.

am_auth_logout()

Logs out the user.

Syntax

```
#include "am_auth.h"
AM_EXPORT am_status_t
am_auth_logout(am_auth_context_t auth_ctx);
```

Parameters

This function takes the following parameter:

auth_ctx The `am_auth_context_t` type.

Note – See “[am_auth_context_t](#)” on page 27 for information.

Returns

This function returns one of the following values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file):

<code>AM_SUCCESS</code>	If the logout process was successfully completed.
<code>AM_INVALID_ARGUMENT</code>	If the <code>auth_ctx</code> parameter is <code>NULL</code> .

am_auth_num_callbacks()

Retrieves the number of callbacks.

Syntax

```
#include "am_auth.h"
AM_EXPORT size_t
am_auth_num_callbacks(am_auth_context_t auth_ctx);
```

Parameters

This function takes the following parameters:

<code>auth_ctx</code>	The <code>am_auth_context_t</code> type.
-----------------------	--

Note – See “[am_auth_context_t](#)” on page 27 for information.

Returns

This function returns a value based on the `size_t` defined in the standard `<stddef.h>` header file that reflects the number of callbacks.

am_auth_submit_requirements()

Passes the responses populated in the callbacks to the Authentication Service.

Syntax

```
#include "am_auth.h"
AM_EXPORT am_status_t
```

```
am_auth_submit_requirements(am_auth_context_t auth_ctx);
```

Parameters

This function takes the following parameter:

`auth_ctx` The `am_auth_context_t` type.

Note – See “[am_auth_context_t](#)” on [page 27](#) for information.

Returns

This function returns one of the following values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file):

<code>AM_SUCCESS</code>	If the submitted requirements were processed successfully.
<code>AM_AUTH_FAILURE</code>	If the authentication process failed.
<code>AM_INVALID_ARGUMENT</code>	If the <code>auth_ctx</code> parameter is <code>NULL</code> .

◆ ◆ ◆ CHAPTER 3

Policy Data Types and Functions

Sun OpenSSO Enterprise contains public data types and functions you can use to communicate with the Policy Service. Reference summaries include a short description, syntax, parameters and returns. The code is contained in the `<am_policy.h>` header file. The sample source `am_policy_test.c` demonstrates the basic usage of the policy API. This chapter contains the following sections:

- [“The Policy API for C” on page 49](#)
- [“Policy Data Types” on page 51](#)
- [“Policy Functions” on page 56](#)

The Policy API for C

OpenSSO Enterprise provides policy API for use by developers to integrate a resource authorization functionality within their external C applications. The policy API for C determines if a user has been given permission by a recognized authority to access a particular protected resource. The result of the policy evaluation is called an *action value* and may be boolean or binary.

- A *boolean action value* might be allow/deny or yes/no.
- A *binary action value* might be, for example, a mailbox quota. Assuming John Smith can only hold 100 MB of email in his mailbox, the value 100 would be the action value.

Tip – As policy evaluation results in string values only, the policy evaluation returned is 100 numeric and not 100 MB. It is up to the application developer to define the appropriate metric for the values.

Resources Strings

The Policy API for C mandates that any resource be represented in a string format. Thus, resources on a web server must be represented as URLs. The Policy Service is then able to compare the resource string to the policy string and determine a *relative relationship* between the two. This relationship will be defined as one of the following:

- exact match
- no match
- subordinate match
- superior match
- exact pattern match

Note – Exact pattern match is a special case where resources may be represented collectively as patterns. The information is abstracted from the Policy Service and the comparison operation must take a boolean parameter to trigger a pattern matched comparison. During the caching of policy information, the policy engine does not care about patterns, whereas during policy evaluation, the comparisons are pattern sensitive.

Resource Traits

The set of characteristics needed to define a resource is called a *resource trait*. Resource traits are taken as a parameter during service initialization in the “[am_resource_traits_t](#)” on page 53. Using the resource traits, the Policy Service constructs a resource graph for policy evaluation in which the relation between all resources in the system spans out like a tree from the root of the given resource. Thus, the service developer must provide the means to extract the root of the given resource. In a URL, the *protocol://OpenSSO Enterprise-host.domain:port* portion represents the root.

Policy Evaluation

The two typedef structures that are used for information exchange to and from the policy evaluation interfaces are:

- `am_map_t` provides a key to multiple key/value mapping. If the evaluation requires certain environment parameters like the IP address of the requester, it may be passed using this structure. See “[am_map_t](#)” on page 119 for more information.
- `am_properties_t` provides a key to single value mapping. `am_properties_t` provides the additional functionality of loading a configuration file and getting values of specific data types. See “[am_properties_t](#)” on page 137 for more information.

Policy Data Types

The types defined in `<am_policy.h>` are:

- [“am_policy_result_t” on page 51](#)
- [“am_policy_t” on page 53](#)
- [“am_resource_traits_t” on page 53](#)

am_policy_result_t

Carries the evaluation results from the Policy Service.

Details

`am_policy_result_t` unifies various components of a policy evaluation including information regarding the user attempting to perform an action on the resource, *advice messages* as recommended during policy evaluation, if any, and attribute response maps providing specific key/values as set in policy definition or user entries.

Syntax

```
#include "am_policy.h"
typedef struct am_policy_result {
    const char *remote_user;
    const char *remote_user_passwd;
    const char *remote_IP;
    am_map_t advice_map;
    am_map_t attr_profile_map;
    am_map_t attr_session_map;
    am_map_t attr_response_map;
    const char *advice_string;
} am_policy_result_t;
```

Members

<code>remote_user</code>	Pointer to the user attempting access.
<code>remote_user_passwd</code>	Pointer to the password for the remote user.
<code>remote_IP</code>	Pointer to the IP address of the resource the user is attempting to access.
<code>advice_map</code>	Takes a value based on the <code>am_map_t</code> defined in the <code><am_map.h></code> header file that represents any <i>advice messages</i> that might have resulted from the policy evaluation.

Note – For information on advices, see “[Policy Advices](#)” in *Sun OpenSSO Enterprise 8.0 Administration Guide*.

<code>attr_profile_map</code>	<p>Takes a value based on the <code>am_map_t</code> (defined in the <code><am_map.h></code> header file) that represents one or more user profile attributes and a corresponding value. This member is enabled when the following two properties in <code>AMAgent.properties</code> are configured:</p> <ul style="list-style-type: none"> ▪ <code>com.sun.am.policy.agents.config.profile.attribute.fetch.mode</code> takes a value of <code>HTTP_HEADER</code> or <code>HTTP_COOKIE</code>. ▪ <code>com.sun.am.policy.agents.config.profile.attribute.map</code> takes a list of LDAP attributes and their mapped values in the format <code>attribute_name value</code>.
<code>attr_session_map</code>	<p>Takes a value based on the <code>am_map_t</code> (defined in the <code><am_map.h></code> header file) that represents one or more session attributes and a corresponding value. This member is enabled when the following two properties in <code>AMAgent.properties</code> are configured:</p> <ul style="list-style-type: none"> ▪ <code>com.sun.am.policy.agents.config.session.attribute.fetch.mode</code> takes a value of <code>HTTP_HEADER</code> or <code>HTTP_COOKIE</code>. ▪ <code>com.sun.am.policy.agents.config.session.attribute.map</code> takes a list of session attributes and their mapped values in the format <code>attribute_name value</code>.
<code>attr_response_map</code>	<p>Takes a value based on the <code>am_map_t</code> (defined in the <code><am_map.h></code> header file) that represents one or more response attributes and a corresponding value. This member is enabled when the following two properties in <code>AMAgent.properties</code> are configured:</p> <ul style="list-style-type: none"> ▪ <code>com.sun.am.policy.agents.config.response.attribute.fetch.mode</code> takes a value of <code>HTTP_HEADER</code> or <code>HTTP_COOKIE</code>. ▪ <code>com.sun.am.policy.agents.config.response.attribute.map</code> takes a list of response names and their mapped values in the format <code>attribute_name value</code>.
<code>advice_string</code>	<p>Pointer to a string that defines a value for further authentication if dictated by the policy condition. If no condition is specified, the advice string will have an empty value.</p>

Memory Concerns

Memory for `am_policy_result_t` is allocated by `am_policy_evaluate()` and freed by `am_policy_result_destroy()`.

am_policy_t

Declares an unsigned integer as a type for a policy object.

Syntax

```
#include "am_policy.h"
typedef unsigned int am_policy_t;
```

Members

am_policy_t has no members.

am_resource_traits_t

Contains the functions to return resource traits that will be used to compare with a user's defined policy and evaluate the access request.

Syntax

```
#include "am_policy.h"
typedef struct am_resource_traits {
    am_resource_match_t (*cmp_func_ptr)(const struct am_resource_traits *rsrc_traits,
                                        const char *policy_res_name,
                                        const char *resource_name,
                                        boolean_t use_patterns);

    boolean_t (*has_patterns)(const char *resource_name);
    boolean_t (*get_resource_root)(const char *resource_name,
                                   char *root_resource_name,
                                   size_t buflen);

    boolean_t ignore_case;
    char separator;
    void (*canonicalize)(const char *resource, char **c_resource);
    void (*str_free)(void *resource_str);
} am_resource_traits_t;
```

Members

cmp_func_ptr

Pointer to a function that compares policy_res_name and resource_name to return one of the following values of the am_resource_match_t enumeration (defined in the <am_policy.h> header file):

```
typedef enum am_resource_match {
    AM_SUB_RESOURCE_MATCH,
```

```
    AM_EXACT_MATCH,  
    AM_SUPER_RESOURCE_MATCH,  
    AM_NO_MATCH,  
    AM_EXACT_PATTERN_MATCH  
} am_resource_match_t;
```

Tip – `cmp_func_ptr` can point to `am_policy_compare_urls()` to evaluate URL resources.

<code>rsrc_traits</code>	Pointer to the resource traits structure containing data regarding a policy.
<code>policy_res_name</code>	Pointer to the name of the resource being protected.
<code>resource_name</code>	Pointer to the name of the resource being requested.
<code>use_patterns</code>	Based on the <code>boolean_t</code> defined in the <code><am_types.h></code> header file, <code>B_TRUE</code> indicates that the function will use or recognize patterns when comparing resources.

`has_patterns`
Pointer to a function that determines whether a resource has patterns and returns one of the following values of the `boolean_t` enumeration defined in the `<am_types.h>` header file:

- `B_TRUE` If `resource_name` has patterns.
- `B_FALSE` Otherwise.

Tip – `has_patterns` can point to `am_policy_resource_has_patterns()` for URL resources.

<code>resource_name</code>	Pointer to the name of the resource being requested.
----------------------------	--

`get_resource_root`
Pointer to a function that extracts the root of the specified resource and returns one of the following values of the `boolean_t` enumeration defined in the `<am_types.h>` header file:

- `B_TRUE` If the resource root was successfully inserted into the specified `root_resource_name` buffer.
- `B_FALSE` Otherwise.

Tip – `get_resource_root` can point to `am_policy_get_url_resource_root()` for URL resources.

<code>resource_name</code>	Pointer to the name of the resource being requested.
----------------------------	--

`root_resource_name` Buffer to hold the resource root.

`buflength` Value based on the `size_t` defined in the standard `<stddef.h>` header file that reflects the length of the `root_resource_name` buffer.

`ignore_case`

Value that takes one of the following values of the `boolean_t` enumeration defined in the `<am_types.h>` header file:

`B_TRUE` Ignore case for all functions in this structure.

`B_FALSE` Otherwise.

`separator`

Defines the resource separator. For URLs / should be used.

`canonicalize`

Pointer to a function that converts the specified resource name into a standard representation for comparative purposes.

`resource` Pointer to a resource name. This could be the resource being requested or the resource defined in the policy.

`c_resource` Output of the canonical resource name.

Note – Memory for the canonical name must be allocated by the caller. A function to free the allocated memory must be set in `str_free`.

`str_free`

Pointer to a function to free a `c_resource` string after the results have been evaluated by `am_policy_evaluate()`. This field cannot be set to `NULL`.

Note – `free()` should be used if `canonicalize` is set to the `am_policy_resource_canonicalize()` function.

`resource_str` Pointer to the string returned in the `canonicalize` function.

Policy Functions

The functions defined in `<am_policy.h>` are:

- `“am_policy_compare_urls()”` on page 56
- `“am_policy_destroy()”` on page 58
- `“am_policy_evaluate()”` on page 58
- `“am_policy_evaluate_ignore_url_notenforced()”` on page 60
- `“am_policy_get_url_resource_root()”` on page 62
- `“am_policy_init()”` on page 63
- `“am_policy_invalidate_session()”` on page 64
- `“am_policy_is_notification_enabled()”` on page 65
- `“am_policy_notify()”` on page 65
- `“am_policy_resource_canonicalize()”` on page 66
- `“am_policy_resource_has_patterns()”` on page 67
- `“am_policy_result_destroy()”` on page 67
- `“am_policy_service_init()”` on page 68

am_policy_compare_urls()

Compares the URLs of two resources, and returns the appropriate result.

Syntax

```
#include "am_policy.h"
AM_EXPORT am_resource_match_t
am_policy_compare_urls(const am_resource_traits_t *rsrc_traits,
                      const char *policy_resource_name,
                      const char *resource_name,
                      boolean_t use_patterns);
```

Parameters

This function takes the following parameter:

rsrc_traits	Pointer to a <code>am_resource_traits_t</code> type containing data regarding a policy.
-------------	---

Note – See `“am_resource_traits_t”` on page 53 for more information.

policy_resource_name	Pointer to the name of the resource being protected.
----------------------	--

resource_name	Pointer to the name of the resource being requested.
use_patterns	Based on the <code>boolean_t</code> defined in the <code><am_types.h></code> header file, <code>B_TRUE</code> indicates that the function will consider occurrences of <code>*</code> in <code>policy_resource_name</code> as wild cards. If <code>B_FALSE</code> , occurrences of <code>*</code> are taken as a literal characters.

Note – In cases of `SUB_RESOURCE_MATCH` and `SUPER_RESOURCE_MATCH` when `usePatterns` is `B_TRUE`, the patterns are sub or super matching patterns, respectively.

Returns

This function returns one of the following values of the `am_resource_match_t` enumeration as defined:

```
#include "am_policy.h"
typedef enum am_resource_match {
    AM_SUB_RESOURCE_MATCH,
    AM_EXACT_MATCH,
    AM_SUPER_RESOURCE_MATCH,
    AM_NO_MATCH,
    AM_EXACT_PATTERN_MATCH
} am_resource_match_t;
```

AM_EXACT_MATCH	If both URLs match exactly as in, for example, if the URL for the resource is <code>http://example.sun.com:90/index.html</code> and the URL in the policy is <code>http://example.sun.com:90/index.html</code> .
AM_EXACT_PATTERN_MATCH	This result is returned if the URL to which the policy applies matches the URL to which access is requested as in, for example, if the URL for the resource is <code>http://example.sun.com:90/index.html</code> and the URL in the policy is <code>http://example.sun.com:90/*</code> . Distinction is not made between an <code>EXACT_MATCH</code> or a pattern match.
AM_NO_MATCH	If the URLs do not match.
AM_SUB_RESOURCE_MATCH	If the requested URL is found to be a sub-resource of the URL defined in the policy.
AM_SUPER_RESOURCE_MATCH	If the requested URL is found to be a parent of the URL defined in the policy.

am_policy_destroy()

Destroys an initialized instance of a policy evaluator object.

Details

An instance is initialized for each policy request.

Note – The caller must ensure that the same instance is not destroyed more than once.

Syntax

```
#include "am_policy.h"
AM_EXPORT am_status_t
am_policy_destroy(am_policy_t policy);
```

Parameters

This function takes the following parameter:

`policy` Integer specifying the object being destroyed.

Returns

This function returns one of the following values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file):

`AM_SUCCESS` If the call was successful.

`AM_*` If any error occurs, the type of error indicated by the status value.

am_policy_evaluate()

Evaluates a policy for a given request and returns a non-boolean result.

Note – `am_policy_evaluate()` has been deprecated. See [“`am_policy_evaluate_ignore_url_notenforced\(\)`” on page 60](#).

Details

`am_policy_evaluate()` was used to evaluate policy for URLs on the not-enforced list and those not on the not-enforced list. Since there is not a need to evaluate URLs on the not-enforced list,

`am_policy_evaluate()` has been deprecated. Although it can still be used, the SDK invokes `am_policy_evaluate_ignore_url_notenforced()`.

Syntax

```
#include "am_policy.h"
AM_EXPORT am_status_t
am_policy_evaluate(am_policy_t policy_handle,
                  const char *sso_token,
                  const char *resource_name,
                  const char *action_name,
                  const am_map_t env_parameter_map,
                  am_map_t policy_response_map_ptr,
                  am_policy_result_t *policy_result);
```

Parameters

This function takes the following parameters:

<code>policy_handle</code>	Integer specifying the object being evaluated.
<code>sso_token</code>	Pointer to the session token (SSOTokenID) of the authenticated user.

Note – The OpenSSO Enterprise Session Service creates a session data structure (also known as an SSOToken) that stores information such as login time, authentication scheme, and authentication level. It also generates a session token (also known as an SSOTokenID, a randomly-generated string that identifies an instance of an SSOToken).

<code>resource_name</code>	Pointer to the name of the resource being requested.
<code>action_name</code>	Pointer to the action requested.

Note – An *action* is the operation to be performed on the resource. Web server actions are POST and GET. An allowable action for a human resources service, for example, can change a home telephone number.

<code>env_parameter_map</code>	Map object which contains environment variables (IP address, host name, etc.) used for evaluation by the Policy Service.
--------------------------------	--

Note – See “[am_map_t](#)” on page 119 for more information.

`policy_response_map_ptr` Pointer to a map object which contains all the profile, session and response attributes fetched.

Note – This must be enabled in `AMAgent.properties`. See “[am_policy_result_t](#)” on page 51 for information on how this is done. See “[am_map_t](#)” on page 119 for more information on map objects.

`policy_result` Pointer to the `am_policy_result_t` type to store the result.

Note – See “[am_policy_result_t](#)” on page 51 for more information.

Returns

This function returns one of the following values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file):

`AM_SUCCESS` If the call was successful.

`AM_*` If any error occurs, the type of error indicated by the status value.

Memory Concerns

After using the results the caller must call `am_policy_result_destroy()` on `policy_result` to cleanup the allocated memory. Also, `am_map_destroy()` must be called on `policy_response_map_ptr` and `env_parameter_map` after their respective usage.

`am_policy_evaluate_ignore_url_notenforced()`

Evaluates a policy for a given request and returns a non-boolean result.

Details

`am_policy_evaluate_ignore_url_notenforced()` will evaluate a policy for the specified URL only if the URL does not appear on the not-enforced list defined in `AMAgent.properties`.

Note – See *Sun Java System Access Manager Policy Agent 2.2 User's Guide* for more information.

Syntax

```
#include "am_policy.h"
AM_EXPORT am_status_t
am_policy_evaluate_ignore_url_notenforced(am_policy_t policy_handle,
                                          const char *sso_token,
                                          const char *resource_name,
                                          const char *action_name,
                                          const am_map_t env_parameter_map,
                                          am_map_t policy_response_map_ptr,
                                          am_policy_result_t *policy_result,
                                          am_bool_t ignorePolicyResult),
                                          char **am_revision_number;
```

Parameters

This function takes the following parameters:

<code>policy_handle</code>	Integer specifying the object being evaluated.
<code>sso_token</code>	Pointer to the session token (SSOTokenID) of the authenticated user.

Note – The OpenSSO Enterprise Session Service creates a session data structure (also known as an SSOToken) that stores information such as login time, authentication scheme, and authentication level. It also generates a session token (also known as an SSOTokenID, a randomly-generated string that identifies an instance of an SSOToken).

<code>resource_name</code>	Pointer to the name of the resource being requested.
<code>action_name</code>	Pointer to the action requested.

Note – An *action* is the operation to be performed on the resource. Web server actions are POST and GET. An allowable action for a human resources service, for example, can change a home telephone number.

env_parameter_map	Map object which contains environment variables (IP address, host name, etc.) used for evaluation by the Policy Service.
<hr/> Note – See “ am_map_t ” on page 119 for more information. <hr/>	
policy_response_map_ptr	Pointer to a map object which contains all the profile, session and response attributes fetched.
<hr/> Note – This must be enabled in <code>AMAgent.properties</code> . See “ am_policy_result_t ” on page 51 for information on how this is done. See “ am_map_t ” on page 119 for more information on map objects. <hr/>	
policy_result	Pointer to the <code>am_policy_result_t</code> type to store the result.
<hr/> Note – See “ am_policy_result_t ” on page 51 for more information. <hr/>	
ignorePolicyResult	Based on the <code>am_bool_t</code> defined in the <code><am_types.h></code> header file, <code>AM_TRUE</code> indicates that policy evaluation will not be done for the URL.

Returns

This function returns one of the following values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file):

- `AM_SUCCESS` If the call was successful.
- `AM_*` If any error occurs, the type of error indicated by the status value.

Memory Concerns

After using the results the caller must call `am_policy_result_destroy()` on `policy_result` to cleanup the allocated memory. Also, `am_map_destroy()` must be called on `policy_response_map_ptr` and `env_parameter_map` after their respective usage.

am_policy_get_url_resource_root()

Extracts the root of a given URL.

Details

`am_policy_get_url_resource_root()` populates the `resource_root` pointer with the extracted information. For example, `http://www.sun.com/index.html` will return `http://www.sun.com/` and `http://www.sun.com:8080/index.html` will return `http://www.sun.com:8080/`.

Syntax

```
#include "am_policy.h"
AM_EXPORT boolean_t
am_policy_get_url_resource_root(const char *resource_name,
                               char *resource_root,
                               size_t length);
```

Parameters

This function takes the following parameters:

<code>resource_name</code>	Pointer to the protected resource URL.
<code>resource_root</code>	Pointer to the location where the resource root will be written.
<code>length</code>	Value based on the <code>size_t</code> defined in the standard <code><stddef.h></code> header file that reflects the size of the <code>resource_root</code> buffer.

Note – When using resources other than URLs, the developer implementing this function must make accurate judgement about the minimum size of `resource_root`.

Returns

This function returns one of the following values of the `boolean_t` enumeration (defined in the `<am_types.h>` header file):

<code>B_TRUE</code>	If the root was successfully extracted.
<code>B_FALSE</code>	If not.

`am_policy_init()`

Initializes the OpenSSO Enterprise Policy Service.

Syntax

```
#include "am_policy.h"
AM_EXPORT am_status_t
am_policy_init(am_properties_t policy_config_properties);
```

Parameters

This function takes the following parameter:

`policy_config_properties` Pointer to the properties used to initialize the Policy Service.

Note – See “[am_properties_t](#)” on page 137 for more information.

Returns

This function returns one of the following values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file):

`AM_SUCCESS` If the call was successful.

`AM_*` If any error occurs, the type of error indicated by the status value.

Memory Concerns

The caller must call `am_policy_destroy()` to free the memory.

`am_policy_invalidate_session()`

Cancels the specified session.

Syntax

```
#include "am_policy.h"
AM_EXPORT am_status_t
am_policy_invalidate_session(am_policy_t policy_handle,
                           const char *ssoTokenId);
```

Parameters

This function takes the following parameters:

`policy_handle` Integer specifying the object being evaluated.

`ssoTokenId` Pointer to the session token of the authentication user.

Note – The *session token* is a randomly-generated string that represents an authenticated user.

Returns

This function returns one of the following values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file):

`AM_SUCCESS` If the call was successful.
`AM_*` If any error occurs, the type of error indicated by the status value.

`am_policy_is_notification_enabled()`

Checks whether the notification functionality is enabled.

Syntax

```
#include "am_policy.h"
AM_EXPORT boolean_t
am_policy_is_notification_enabled(am_policy_t policy_handle);
```

Parameters

This function takes the following parameter:

`policy_handle` Integer specifying the object being evaluated.

Returns

This function returns the standard `boolean_t` with one of the following values:

`0` If notification is disabled.
`non-zero` If notification is enabled.

`am_policy_notify()`

Refreshes the policy cache when a policy notification is received by the client.

Syntax

```
#include "am_policy.h"
AM_EXPORT am_status_t
```

```
am_policy_notify(am_policy_t policy_handle,
                 const char *notification_data,
                 size_t notification_data_len);
```

Parameters

This function takes the following parameters:

<code>policy_handle</code>	Integer specifying the object being evaluated.
<code>notification_data</code>	Pointer to the notification message as an XML string.
<code>notification_data_len</code>	Value based on the <code>size_t</code> defined in the standard <code><stddef.h></code> header file that reflects the size of the <code>notification_data</code> string.

Returns

This function returns one of the following values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file):

<code>AM_SUCCESS</code>	If the call was successful.
<code>AM_*</code>	If any error occurs, the type of error indicated by the status value.

am_policy_resource_canonicalize()

Converts the specified resource name into a standard representation for comparison purposes.

Syntax

```
#include "am_policy.h"
AM_EXPORT void
am_policy_resource_canonicalize(const char *resource,
                               char **c_resource);
```

Parameters

This function takes the following parameters:

<code>resource</code>	Pointer to the name of the resource to be converted.
<code>c_resource</code>	Pointer to a pointer to the location where the converted string will be placed.

Returns

This function does not return a value.

am_policy_resource_has_patterns()

Checks whether the specified resource name has patterns (such as the wildcard *).

Syntax

```
#include "am_policy.h"
AM_EXPORT boolean_t
am_policy_resource_has_patterns(const char *resource_name);
```

Parameters

This function takes the following parameter:

`resource_name` Pointer to the resource being evaluated.

Returns

This function returns one of the following values of the `boolean_t` enumeration (defined in the `<am_types.h>` header file):

`B_TRUE` If the resource has patterns.

`B_FALSE` Otherwise.

am_policy_result_destroy()

Destroys the specified `am_policy_result_t` structure type.

Note – See “[am_policy_result_t](#)” on page 51 for more information.

Syntax

```
#include "am_policy.h"
AM_EXPORT void
am_policy_result_destroy(am_policy_result_t *result);
```

Parameters

This function takes the following parameter:

`result` Pointer to the `am_policy_result_t` structure type being destroyed.

Returns

This function does not return a value.

am_policy_service_init()

Initializes one instance of the OpenSSO Enterprise Policy Service for policy evaluation.

Syntax

```
#include "am_policy.h"
AM_EXPORT am_status_t
am_policy_service_init(const char *service_name,
                      const char *instance_name,
                      am_resource_traits_t rsrc_traits,
                      am_properties_t service_config_properties,
                      am_policy_t *policy_handle_ptr);
```

Parameters

This function takes the following parameters:

service_name	Pointer to the name for the Policy Service.
instance_name	Pointer to the name of the instance being initialized.
rsrc_traits	Pointer to a <code>am_resource_traits_t</code> structure type.

Note – See “[am_resource_traits_t](#)” on page 53 for more information.

service_config_properties	Pointer to the properties used to initialize the Policy Service instance.
---------------------------	---

Note – See “[am_properties_t](#)” on page 137 for more information.

policy_handle_ptr	Pointer to the integer specifying the object being evaluated.
-------------------	---

Returns

This function returns one of the following values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file):

AM_SUCCESS	If the call was successful.
AM_*	If any error occurs, the type of error indicated by the status value.

4

◆ ◆ ◆ CHAPTER 4

Single Sign-On Data Types and Functions

Sun OpenSSO Enterprise contains public data types and functions you can use to communicate with the Session Service for single sign-on. Reference summaries include a short description, syntax, parameters and returns. The code is contained in the `<am_sso.h>` header file. The sample source `am_sso_test.c` demonstrates the basic usage of the single sign-on API. This chapter contains the following sections:

- “The Single Sign-on API for C” on page 71
- “Single Sign-on Data Types” on page 79
- “Single Sign-on Functions” on page 80

The Single Sign-on API for C

The Single Sign-on API for C are provided in the `SUNWamcom` package which comes with OpenSSO Enterprise or any of its downloadable policy agents. The package includes header files, libraries and samples. The header files are:

- `<am_sso.h>` which must be included for any single sign-on routines.
- `<am_notify.h>` which must be included for parsing notification messages from the server and calling single sign-on listeners.

Single Sign-on Properties

Certain properties must be read and passed to `am_sso_init()` in order to initialize the Session Service. Thus, `am_sso_init()` must be called before any other single sign-on interface. By default, the properties file used for initializing the Session Service is `AMAgent.properties`. This file is created during the process for installing a web agent. Before using the API be sure the properties in the following table are set in `AMAgent.properties`.

Note – See *Sun Java System Access Manager Policy Agent 2.2 User's Guide* for more information.

TABLE 4–1 Single Sign-on Properties in `AMAgent.properties`

Property	Definition
<code>com.sun.am.naming.url</code>	<p>Specifies the URL for the Naming Service which, in turn, finds the URL of the Session Service. This property must be set as:</p> <p><code>com.sun.am.naming.url = protocol://OpenSSOEnterprise-host.domain:port/amserver/namingservice</code></p>
<code>com.sun.am.notification.enable</code>	<p>Specifies whether the Notification Service will be used to update the cache. If enabled, a URL where notification messages from OpenSSO Enterprise are sent must be specified. This property is set as:</p> <p><code>com.sun.am.notification.enable = true false</code></p> <p>Note – If <code>com.sun.am.notification.enable</code> is not found in the properties file, the default value is <code>false</code>.</p>
<code>com.sun.am.notification.url</code>	<p>If <code>com.sun.am.notification.enable</code> is set to <code>true</code>, the value of this property specifies a URL where notification messages from OpenSSO Enterprise are sent. This property is set as:</p> <p><code>com.sun.am.notification.url = protocol://OpenSSOEnterprise-host.domain:port/notification_URL</code></p>
<code>com.sun.am.sso.polling.period</code>	<p>Specifies how often, in minutes, the cache should be checked for entries that have reached the cache entry life time. This property must be set as:</p> <p><code>com.sun.am.sso.checkCacheInterval=#</code></p> <p>Note – By default, this property is not in <code>AMAgent.properties</code> but can be added when needed.</p>
<code>com.sun.am.sso.max_threads</code>	<p>Specifies the maximum number of threads the single sign-on API for C should invoke for handling notifications. The API maintains a thread pool and invokes a thread for each notification. If the maximum number of threads has been reached, the notification will wait until a thread is available. This property must be set as:</p> <p><code>com.sun.am.sso.maxThreads=#</code></p> <p>If not specified the default maximum number of threads is 10.</p> <p>Note – By default, this property is not in <code>AMAgent.properties</code> but can be added when needed.</p>

For more information, see the *Sun Java System Access Manager Policy Agent 2.2 User's Guide*.

Single Sign-on Calls

The following sections contain information and code samples for some of the single sign-on calls.

- “Initialization and Cleanup” on page 73
- “Single Sign-on Token Handles” on page 74
- “Retrieving and Setting Properties” on page 75
- “Listening and Notification” on page 77

Initialization and Cleanup

When implementing single sign-on, `am_sso_init()` must be called before any other `am_sso_*` functions to initialize the internal data structures. At the end of all single sign-on routines, `am_cleanup()` should be called for cleanup. Following is a code sample using these functions.

Note – For more information on `am_cleanup()`, see [Chapter 9, “Additional Data Types and Functions.”](#)

```
#include <am_sso.h>

int main() {
    am_properties_t *properties;
    am_status_t status;

    /* create a properties handle */
    status = am_properties_create(&properties);
    if (status != AM_SUCCESS) {
        printf("am_properties_create failed.\n");
        exit(1);
    }

    /* load properties from a properties file */
    status = am_properties_load(properties, "./myPropertiesFile");
    if (status != AM_SUCCESS) {
        printf("am_properties_load failed.\n");
        exit(1);
    }

    /* initialize SSO module */
    status = am_sso_init(properties);
    if (status != AM_SUCCESS) {
        printf("am_sso_init failed.\n");
        return 1;
    }
}
```

```

        /* login through auth module, and do auth functions.
        * ...
        */

    /* do sso functions
    * ...
    */

    /* done - cleanup. */
    status = am_cleanup();
    if (status != AM_SUCCESS) {
        printf("am_cleanup failed!\\n");
        return 1;
    }
    /* free memory for properties */
    status = am_properties_destroy(properties);
    if (status != AM_SUCCESS) {
        printf("Failed to free properties.\\n");
        return 1;
    }

    /* exit program successfully. */
    return 0;
}

```

Single Sign-on Token Handles

When a user attempts to access a protected resource, the Session Service creates a new, empty session data structure (also known as an SSOToken) that will store information (such as login time, authentication scheme, authentication level, maximum time out limits and caching time limits) after the user is successfully authenticated. Additionally, the Session Service generates a session identifier (also known as an SSOTokenID) which is a randomly-generated string that identifies the user and corresponding session structure. Technically, the SSOTokenID identifies an instance of an SSOToken.

After a user has been successfully authenticated, the SSOToken is activated and the relevant session information is stored in the structure. Additionally, the state of the SSOTokenID is changed from invalid to valid. When using the single sign-on API for C, a *single sign-on token handle* contains this valid SSOTokenID and allows for operations based on the SSOToken.

- [“Creating Single Sign-on Token Handles” on page 74](#)
- [“Validating Single Sign-on Token Handles” on page 75](#)
- [“Destroying Session Token Handles” on page 75](#)

Creating Single Sign-on Token Handles

Once activated, an SSOToken can be obtained and inserted into a single sign-on token handle by passing the SSOTokenID to `am_sso_create_sso_token_handle()`. This function then checks to

see if the identifier is in its local cache and, if not, retrieves the session information associated with the SSOTokenID from OpenSSO Enterprise and caches it. A single sign-on token handle is then assigned to it.

Validating Single Sign-on Token Handles

The caller can check if the session is valid using `am_sso_is_valid_token()`. If not valid, `am_sso_validate_token()` will flush the old session information from the local cache (if any) and fetch the latest session information from OpenSSO Enterprise.

Note – `am_sso_refresh_token()` duplicates the functionality of `am_sso_validate_token()`. In addition, it will reset the idle time of the session on the server.

Destroying Session Token Handles

When the caller is finished with a token handle, it must be freed to prevent memory leak by calling `am_sso_destroy_sso_token_handle()`. The session associated with the token handle can be invalidated or ended with `am_sso_invalidate_token()`.

Tip – Although this ends the session for the user, the proper way to log out is by using `am_auth_logout()` as described in “[am_auth_logout\(\)](#)” on page 45. Not using `am_auth_logout()` will result in authentication resources associated with the session remaining on the server unnecessarily until the session has timed out.

Retrieving and Setting Properties

The following code sample shows how you might use the `am_sso_get_property()` and `am_sso_set_property()` functions. For additional information, see “[am_sso_get_property\(\)](#)” on page 89 and “[am_sso_set_property\(\)](#)” on page 96.

```
/* initialize sso as in previous sample */

am_status_t status = NULL;
am_sso_token_handle_t sso_handle = NULL;
char *session_status = NULL;
am_string_set_t principal_set = NULL;

/* create sso token handle */
status = am_sso_create_sso_token_handle(&sso_handle, sso_token_id, false);
if (status != AM_SUCCESS) {
    printf("Failed getting sso token handle for sso token id %s.
          \\n", sso_token_id);
    return 1;
}
```

```

/* check if session is valid */
session_status = am_sso_is_valid_token(sso_handle) ? "Valid" : "Invalid";
printf("Session state is %s\\n", session_status);

/* check if session is valid using validate. This also updates the handle with
   /*info from the server */
status = am_sso_validate_token(sso_handle);
if (status == AM_SUCCESS) {
    printf("Session state is valid.\\n");
} else if (status == AM_INVALID_SESSION) {
    printf("Session status is invalid.\\n");
} else {
    printf("Error validating sso token.\\n");
    return 1;
}

/* get info on the session */
printf("SSO Token ID is %s.\\n", am_sso_get_sso_token_id(sso_handle));
printf("Auth type is %s.\\n", am_sso_get_auth_type(sso_handle));
printf("Auth level is %d.\\n", am_sso_get_auth_level(sso_handle));
printf("Idle time is %d.\\n", am_sso_get_idle_time(sso_handle));
printf("Max Idle time is %d.\\n", am_sso_get_max_idle_time(sso_handle));
printf("Time left is %d.\\n", am_sso_get_time_left(sso_handle));
printf("Max session time is %d.\\n", am_sso_get_max_session_time(sso_handle));
printf("Principal is %s.\\n", am_sso_get_principal(sso_handle));
printf("Host is %s.\\n", am_sso_get_host(sso_handle));
principal_set = am_sso_get_principal_set(sso_handle);
if (principal_set == NULL) {
    printf("ERROR: Principal set is NULL!\\n");
} else {
    printf("Principal set size %d.\\n", principal_set->size);
    for (i = 0; i < principal_set->size; i++) {
        printf("Principal[%d] = %s.\\n", i, principal_set->strings[i]);
    }
    am_string_set_destroy(principal_set);
}

/* get "HOST" property on the session. Same as am_sso_get_host(). */
printf("Host is %s.\\n", am_sso_get_property(sso_handle, "HOST"));

/* set a application defined property and get it back */
status = am_sso_set_property(sso_handle, "AppPropName", "AppPropValue");
if (status != AM_SUCCESS) {
    printf("Error setting property.\\n");
    return 1;
}
printf("AppPropName value is %s.\\n", am_sso_get_property

```

```

        (sso_handle, "AppPropName");

    /* refresh token, idle time should be 0 after refresh */
    status = am_sso_refresh_token(sso_handle);
    if (status != AM_SUCCESS) {
        printf("Error refreshing token !\n");
        return 1;
    }
    printf("After refresh, idle time is %d.\n", am_sso_get_idle_time(sso_handle));

    /* end this session abruptly. am_auth_logout() is the right way
       /* to end session */
    status = am_sso_invalidate_token(sso_handle);
    if (status != AM_SUCCESS) {
        printf("Error invalidating token.\n");
        return 1;
    }

    /* we are done with sso token handle. free memory for sso handle. */
    status = am_sso_destroy_sso_token_handle(sso_handle);
    if (status != AM_SUCCESS) {
        printf("Failed to free sso token handle.\n");
        return 1;
    }

    /* call am_cleanup, and other cleanup routines as in previous sample */

```

Listening and Notification

A session may become invalid because it has been idle over a time limit, it has reached the maximum session time, or it has been terminated by an administrator. An application can be notified of this by implementing a listener function. Additionally, notification must be enabled for the application to receive change notifications when `am_sso_init()` is initialized. Notification is enabled by setting the `com.sun.am.notification.enable` property in `AMAgent.properties` to true, and by providing the `com.sun.am.notification.url` property a URL which will receive HTTP notification messages from OpenSSO Enterprise. Notification messages are in XML and should be passed as a string (`const char *`) to `am_notify()` which will parse the message and invoke the appropriate session or policy listener. Following is a code sample that illustrates this.

Note – For more information, see [“Single Sign-on Properties” on page 71](#) and [“<am_notify.h>” on page 220](#).

```

void sample_listener_func(
    am_sso_token_handle_t sso_token_handle,
    const am_sso_token_event_type_t event_type,

```

```

        const time_t event_time,
        void *opaque)
{
    if (sso_token_handle != NULL) {
        const char *sso_token_id = am_sso_get_sso_token_id(sso_token_handle);
        boolean_t is_valid = am_sso_is_valid_token(sso_token_handle);
        printf("sso token id is %s.\n",
               sso_token_id==NULL?"NULL":sso_token_id);
        printf("session state is %s.\n",
               is_valid == B_TRUE ? "valid":"invalid");
        printf("event type %d.\n", event_type);
        printf("event time %d.\n", event_time);
    }
    else {
        printf("Error: sso token handle is null!");
    }
    if (opaque)
        *(int *)opaque = 1;
    return;
}

int main(int argc, char *argv[]) {

    am_status_t status;
    char *sso_token_id = argv[1];
    int listener_func_done = 0;

    /* initialize sso as in previous samples */

    /* get sso token handle */
    status = am_sso_create_sso_token_handle(&sso_handle, sso_token_id, false);

    /* register listener function. notification must be enabled, if not,
    /* status AM_NOTIF_NOT_ENABLED will be returned. */
    status = am_sso_add_sso_token_listener(sso_handle, sample_listener_func,
        &listener_func_done, B_TRUE);
    if (status != AM_SUCCESS) {
        printf("Failed to register sample listener function.\n");
        return 1;
    }
}

```

Non-Web Applications

OpenSSO Enterprise provides the single sign-on API for C to be used primarily with web-based applications. It can though be extended to non-web applications with limitations. You can use the API with non-web applications in either of the following ways:

- The application has to obtain the OpenSSO Enterprise cookie value and pass it to the single sign-on client methods to retrieve the SSOToken. The method used for this process is application-specific.
- Command line applications, such as `amadmin`, can be used. Session tokens can be created to access Directory Server directly. No session is created, making OpenSSO Enterprise access valid only within that process or virtual machine.

Single Sign-on Data Types

The single sign-on data types defined in `<am_sso.h>` are:

- [“`am_sso_token_handle_t`” on page 79](#)
- [“`am_sso_token_listener_func_t`” on page 79](#)

`am_sso_token_handle_t`

A pointer to the session information object.

Syntax

```
#include "am_sso.h"
typedef struct am_sso_token_handle *am_sso_token_handle_t;
```

Members

`am_sso_token_handle` is an opaque structure with no accessible members.

`am_sso_token_listener_func_t`

Listener function declaration.

Syntax

```
#include "am_sso.h"
typedef void (*am_sso_token_listener_func_t)(
    const am_sso_token_handle_t sso_token_handle,
    const am_sso_token_event_type_t event_type,
    const time_t event_time,
    void *args);
```

Members

`am_sso_token_listener_func_t` has the following members:

<code>sso_token_handle</code>	Pointer to the session information object.
<code>event_type</code>	Takes one of the following values from the <code>am_sso_token_event_type_t</code> enumeration (defined in the <code><am_sso.h></code> header file): <pre>typedef enum { AM_SSO_TOKEN_EVENT_TYPE_UNKNOWN = 0, AM_SSO_TOKEN_EVENT_TYPE_IDLE_TIMEOUT = 1, AM_SSO_TOKEN_EVENT_TYPE_MAX_TIMEOUT = 2, AM_SSO_TOKEN_EVENT_TYPE_LOGOUT = 3, AM_SSO_TOKEN_EVENT_TYPE_DESTROY = 5 } am_sso_token_event_type_t;</pre>
<code>event_time</code>	Takes a value based on the standard <code>time_t</code> data type that represents the time at which the change event occurred.
<code>*args</code>	Pointer to application-defined parameters.

Single Sign-on Functions

The single sign-on functions defined in `<am_sso.h>` are:

- `“am_sso_add_listener()”` on page 81
- `“am_sso_add_sso_token_listener()”` on page 82
- `“am_sso_create_sso_token_handle()”` on page 84
- `“am_sso_destroy_sso_token_handle()”` on page 85
- `“am_sso_get_auth_level()”` on page 86
- `“am_sso_get_auth_type()”` on page 86
- `“am_sso_get_host()”` on page 87
- `“am_sso_get_idle_time”` on page 87
- `“am_sso_get_max_idle_time()”` on page 88
- `“am_sso_get_max_session_time()”` on page 88
- `“am_sso_get_principal()”` on page 89
- `“am_sso_get_principal_set()”` on page 89
- `“am_sso_get_property()”` on page 89
- `“am_sso_get_sso_token_id()”` on page 90
- `“am_sso_get_time_left()”` on page 91
- `“am_sso_init()”` on page 91
- `“am_sso_invalidate_token()”` on page 92
- `“am_sso_is_valid_token()”` on page 93
- `“am_sso_refresh_token()”` on page 94
- `“am_sso_remove_listener()”` on page 95
- `“am_sso_remove_sso_token_listener()”` on page 95
- `“am_sso_set_property()”` on page 96

- [“am_sso_validate_token\(\)” on page 97](#)

am_sso_add_listener()

Add a listener for any and all event changes related to the referenced single sign-on token handle.

Note – `am_sso_add_listener()` will not be removed after it is called once like [“am_sso_add_sso_token_listener\(\)” on page 82](#).

Details

The caller must do one of the following:

- Provide a URL to this function.
- Enable notification and provide a valid notification URL in the `AMAgent.properties` file passed to `am_sso_init()`.

See [“Listening and Notification” on page 77](#) for more information.

Syntax

```
#include "am_sso.h"
AM_EXPORT am_status_t
am_sso_add_listener(const am_sso_token_listener_func_t listener,
                  void *args,
                  boolean_t dispatch_to_sep_thread);
```

Parameters

This function takes the following parameters:

listener	The listener as described in “am_sso_token_listener_func_t” on page 79 .
----------	--

Note – When the listener is called, updated session information from OpenSSO Enterprise is passed in a temporary `sso_token_handle`.

args	Pointer to application-defined arguments to pass to the listener.
dispatch_to_sep_thread	Takes one of the values based on the <code>boolean_t</code> (defined in the <code><am_types.h></code> header file) that indicates whether the listener

function should be called in the calling thread or dispatched to a thread from the internal thread pool managed by the C SDK.

Note – Calling the listener in a thread from an internal thread pool allows `am_notify()` to return immediately upon parsing the notification message rather than waiting for the listener functions to finish before returning.

Returns

This function returns one of the following values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file):

<code>AM_SUCCESS</code>	If the listener was successfully added.
<code>AM_INVALID_ARGUMENT</code>	If <code>sso_token_handle</code> or <code>listener</code> is invalid, or the notification URL is not set and none is provided in the properties file.
<code>AM_NOTIF_NOT_ENABLED</code>	If notification is not enabled and the notification URL parameter is invalid.
<code>AM_FAILURE</code>	If any other error occurred.

`am_sso_add_sso_token_listener()`

Adds a listener for any and all event changes related to the referenced single sign-on token handle.

Note – `am_sso_add_sso_token_listener()` is removed from memory after it is called once, differentiating its functionality from “[am_sso_add_listener\(\)](#)” on page 81.

Details

The caller must do one of the following:

- Provide a URL to this function.
- Enable notification and provider a valid notification URL in the `AMAgent.properties` file passed to `am_sso_init()`.

See “[Listening and Notification](#)” on page 77 for more information.

Syntax

```
#include "am_sso.h"
AM_EXPORT am_status_t
am_sso_add_sso_token_listener(am_sso_token_handle_t sso_token_handle,
                             const am_sso_token_listener_func_t listener,
                             void *args,
                             boolean_t dispatch_to_sep_thread);
```

Parameters

This function takes the following parameters:

sso_token_handle	Pointer to the session information object containing the session token to which the listener corresponds. The handle will be filled with the session information from the notification message, overwriting any existing contents.
<hr/>	
	Note – The session token is a randomly-generated string that represents an authenticated user.
<hr/>	
listener	The listener as described in “ am_sso_token_listener_func_t ” on page 79.
<hr/>	
	Note – When the listener is called, updated session information from OpenSSO Enterprise is passed in a temporary sso_token_handle.
<hr/>	
args	Arguments to pass to the listener.
dispatch_to_sep_thread	Takes one of the values based on the boolean_t (defined in the <am_types.h> header file) that indicates whether the listener function should be called in the calling thread or dispatched to a thread from the internal thread pool managed by the C SDK.
<hr/>	
	Note – Calling the listener in a thread from an internal thread pool allows am_notify() to return immediately upon parsing the notification message rather than waiting for the listener functions to finish before returning.
<hr/>	

Returns

This function returns one of the following values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file):

<code>AM_SUCCESS</code>	If the listener was successfully added.
<code>AM_INVALID_ARGUMENT</code>	If <code>sso_token_handle</code> or listener is invalid, or the notification URL is not set and none is provided in the properties file.
<code>AM_NOTIF_NOT_ENABLED</code>	If notification is not enabled and the notification URL parameter is invalid.
<code>AM_FAILURE</code>	If any other error occurred.

`am_sso_create_sso_token_handle()`

Creates a single sign-on token handle as a container for a valid SSOTokenID.

Details

For more information, see [“Single Sign-on Token Handles” on page 74](#).

Syntax

```
#include "am_sso.h"
AM_EXPORT am_status_t
am_sso_create_sso_token_handle(am_sso_token_handle_t *sso_token_handle_ptr,
                              const char *sso_token_id,
                              boolean_t reset_idle_timer);
```

Parameters

This function takes the following parameters:

<code>sso_token_handle</code>	Pointer to a <code>am_sso_token_handle_t</code> type which will be assigned if the session validation is successful.
<code>sso_token_id</code>	Pointer to the SSOTokenID to which the handle will be associated.
<code>reset_idle_timer</code>	Takes one of the values based on the <code>boolean_t</code> (defined in the <code><am_types.h></code> header file) that specifies that the idle time of the SSOTokenID on the server will be refreshed when querying for session information.

Returns

This function returns one of the following values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file):

<code>AM_SUCCESS</code>	If session validation was successful and a single sign-on token handle was successfully created.
<code>AM_SERVICE_NOT_INITIALIZED</code>	If the Session Service was not initialized.
<code>AM_INVALID_ARGUMENT</code>	If the <code>session_token_handle_ptr</code> parameter is <code>NULL</code> .
<code>AM_NO_MEMORY</code>	If there was a memory allocation problem.
<code>AM_FAILURE</code>	If any other error occurred.

`am_sso_destroy_sso_token_handle()`

Destroys the specified single sign-on token handle.

Details

`am_sso_destroy_sso_token_handle()` does not log out the user or invalidate the session. For more information, see [“Single Sign-on Token Handles” on page 74](#).

Syntax

```
#include "am_sso.h"
AM_EXPORT am_status_t
am_sso_destroy_sso_token_handle(am_sso_token_handle_t sso_token_handle);
```

Parameters

This function takes the following parameter:

`sso_token_handle` Pointer to a `am_sso_token_handle_t` type which will be destroyed.

Returns

This function returns one of the following values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file):

<code>AM_SUCCESS</code>	If the memory release process was successful.
<code>AM_INVALID_ARGUMENT</code>	If the <code>sso_token_handle</code> parameter is <code>NULL</code> .
<code>AM_FAILURE</code>	If any other error occurred.

am_sso_get_auth_level()

Retrieves the authentication level associated with the specified single sign-on token handle.

Syntax

```
#include "am_sso.h"
AM_EXPORT unsigned long
am_sso_get_auth_level(const am_sso_token_handle_t sso_token);
```

Parameters

This function takes the following parameter:

sso_token Pointer to a `am_sso_token_handle_t` type.

Returns

This function returns the authentication level of the specified handle, or `ULONG_MAX` if an error occurred.

am_sso_get_auth_type()

Retrieves the authentication type associated with the specified single sign-on token handle.

Syntax

```
#include "am_sso.h"
AM_EXPORT const char *
am_sso_get_auth_type(const am_sso_token_handle_t sso_token);
```

Parameters

This function takes the following parameter:

sso_token Pointer to a `am_sso_token_handle_t` type.

Returns

This function returns the authentication type of the specified handle, or `NULL` if an error occurred.

am_sso_get_host()

Retrieves the name of the host associated with the specified single sign-on token handle.

Syntax

```
#include "am_sso.h"
AM_EXPORT const char *
am_sso_get_host(const am_sso_token_handle_t sso_token);
```

Parameters

This function takes the following parameter:

`sso_token` Pointer to a `am_sso_token_handle_t` type.

Returns

This function returns the host name as defined in the `Host` property, or `NULL` if the `Host` property is not set or does not have a value.

am_sso_get_idle_time

Retrieves the idle time associated with the specified single sign-on token handle.

Syntax

```
#include "am_sso.h"
AM_EXPORT time_t
am_sso_get_idle_time(const am_sso_token_handle_t sso_token_handle);
```

Parameters

This function takes the following parameter:

`sso_token_handle` Pointer to a `am_sso_token_handle_t` type.

Returns

This function returns the idle time for this session in seconds, or the standard `time_t` data structure in the form `(time_t) -1` if the token is invalid or some type of error occurs. Detailed error information is logged.

am_sso_get_max_idle_time()

Retrieves the maximum idle time associated with the specified single sign-on token handle.

Syntax

```
#include "am_sso.h"
AM_EXPORT time_t
am_sso_get_max_idle_time(const am_sso_token_handle_t sso_token);
```

Parameters

This function takes the following parameters:

sso_token Pointer to a `am_sso_token_handle_t` type.

Returns

This function returns the maximum idle time for this session in seconds, or the standard `time_t` data structure in the form `(time_t) - 1` if some type of error occurs.

am_sso_get_max_session_time()

Retrieves the maximum session time associated with the specified single sign-on token handle.

Syntax

```
#include "am_sso.h"
AM_EXPORT time_t
am_sso_get_max_session_time(const am_sso_token_handle_t sso_token);
```

Parameters

This function takes the following parameter:

sso_token Pointer to a `am_sso_token_handle_t` type.

Returns

This function returns the maximum session time for this session in seconds, or the standard `time_t` data structure in the form `(time_t) - 1` if some type of error occurs.

am_sso_get_principal()

Retrieves the principal (user) associated with the specified single sign-on token handle.

Syntax

```
#include "am_sso.h"
AM_EXPORT const char *
am_sso_get_principal(const am_sso_token_handle_t sso_token);
```

This function takes the following parameter:

`sso_token` Pointer to a `am_sso_token_handle_t` type.

Returns

This function returns the principal (user) of the specified session, or `NULL` if the handle is invalid or any other error occurred.

am_sso_get_principal_set()

Retrieves a set of principals associated with the specified single sign-on token handle.

Syntax

```
#include "am_sso.h"
AM_EXPORT am_string_set_t *
am_sso_get_principal_set(const am_sso_token_handle_t sso_token);
```

Parameters

This function takes the following parameter:

`sso_token` Pointer to a `am_sso_token_handle_t` type.

Returns

This function returns the `am_string_set_t` type (defined in the `<am_string_set.h>` header file) that points to the set of principals associated with the specified single sign-on token handle. It returns `NULL` if the applicable property is not set or has no value.

am_sso_get_property()

Retrieves the value of a property associated with the specified single sign-on token handle.

Syntax

```
#include "am_sso.h"
AM_EXPORT const char *
am_sso_get_property(const am_sso_token_handle_t sso_token,
                   const char *property_key,
                   boolean_t check_if_session_valid);
```

Parameters

This function takes the following parameters:

<code>sso_token</code>	Pointer to a <code>am_sso_token_handle_t</code> type.
<code>property_key</code>	Pointer to the name of the desired property.
<code>check_if_session_valid</code>	Takes a value based on the <code>boolean_t</code> (defined in the <code><am_types.h></code> header file) that specifies if the function should check first if the session is valid. If the session is invalid, <code>NULL</code> will always be returned.

Returns

This function returns a pointer to the value of the property, or `NULL` if the property is not set or does not have a value.

`am_sso_get_sso_token_id()`

Retrieves the `SSOTokenID` associated with the specified single sign-on token handle.

Syntax

```
#include "am_sso.h"
AM_EXPORT const char *
am_sso_get_sso_token_id(const am_sso_token_handle_t sso_token_handle);
```

Parameters

This function takes the following parameters:

<code>sso_token_handle</code>	Pointer to a <code>am_sso_token_handle_t</code> type.
-------------------------------	---

Returns

This function returns a pointer to the `SSOTokenID`, or `NULL` if `sso_token_handle` is invalid or any other error occurred.

am_sso_get_time_left()

Retrieves the time left in the session associated with the specified single sign-on token handle.

Syntax

```
#include "am_sso.h"
AM_EXPORT time_t
am_sso_get_time_left(const am_sso_token_handle_t sso_token_handle);
```

Parameters

This function takes the following parameters:

`sso_token_handle` Pointer to a `am_sso_token_handle_t` type.

Returns

This function returns the time left on this session in seconds, or the standard `time_t` data structure in the form `(time_t) - 1` if the token is invalid or some other type of error occurs. Detailed error information is logged.

am_sso_init()

Initializes the data structures, allowing communication with the Session Service.

Details

`am_sso_init()` takes as input a properties file that contains name/value pairs, and returns status on the success or failure of the initialization. This call must be made before calling any other `am_sso_*` functions. See [“Single Sign-on Properties” on page 71](#) for more information.

Syntax

```
#include "am_sso.h"
AM_EXPORT am_status_t
am_sso_init(am_properties_t property_map);
```

Parameters

This function takes the following parameter:

`property_map` Pointer to the `am_properties_t` structure used to initialize the Session Service.

Note – See “[am_properties_t](#)” on page 137 for more information.

Returns

This function returns one of the following values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file):

- `AM_SUCCESS` If the initialization was successful.
- `AM_*` If any error occurs, the type of error indicated by the status value.

am_sso_invalidate_token()

Invalidates or destroys the session on OpenSSO Enterprise associated with the single sign-on token handle.

Details

`am_sso_invalidate_token()` does not free the `sso_token_handle` parameter. You must call `am_sso_destroy_sso_token_handle()` to free the memory for the handle itself.

Syntax

```
#include "am_sso.h"
AM_EXPORT am_status_t
am_sso_invalidate_token(const am_sso_token_handle_t sso_token_handle);
```

Parameters

This function takes the following parameter:

- `sso_token_handle` Pointer to a `am_sso_token_handle_t` type.

Note – If successful, the single sign-on token handle will have an invalid state after this call.

Returns

This function returns one of the following values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file):

- `AM_SUCCESS` If session was successfully invalidated.
- `AM_INVALID_ARGUMENT` If the `sso_token_handle` parameter is NULL.

AM_SERVICE_NOT_INITIALIZED	If the Session Service was not initialized with <code>am_sso_init()</code> .
AM_SERVICE_NOT_AVAILABLE	If server returned service not available.
AM_HTTP_ERROR	If an HTTP error was encountered while communicating with OpenSSO Enterprise.
AM_ERROR_PARSING_XML	If an error occurred while parsing XML from OpenSSO Enterprise.
AM_ACCESS_DENIED	If access was denied while communicating with OpenSSO Enterprise.
AM_FAILURE	If any other error occurred.

`am_sso_is_valid_token()`

Checks if the SSOToken associated with the specified single sign-on token handle is valid.

Details

`am_sso_is_valid_token()` looks in the passed `sso_token_handle` to check for validity. It does *not* go to OpenSSO Enterprise.

Syntax

```
#include "am_sso.h"
AM_EXPORT boolean_t
am_sso_is_valid_token(const am_sso_token_handle_t sso_token_handle);
```

Parameters

This function takes the following parameter:

`sso_token_handle` Pointer to a `am_sso_token_handle_t` type.

Returns

This function returns one of the following values of the `boolean_t` enumeration (defined in the `<am_types.h>` header file):

- | | |
|---------|---|
| B_TRUE | If the single sign-on token is valid. |
| B_FALSE | If the single sign-on token is invalid or any other error occurred. |

am_sso_refresh_token()

Refreshes the session information in the SSOToken associated with the specified single sign-on token handle.

Details

`am_sso_refresh_token()` goes to OpenSSO Enterprise to retrieve the latest session information with which to update the SSOToken. This is similar in functionality to `am_sso_validate_token()` however, `am_sso_refresh_token()` also refreshes the last access time of the session.

Syntax

```
#include "am_sso.h"
AM_EXPORT am_status_t
am_sso_refresh_token(const am_sso_token_handle_t sso_token_handle);
```

Parameters

This function takes the following parameter:

`sso_token_handle` Pointer to a `am_sso_token_handle_t` type.

Returns

This function returns one of the following values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file):

<code>AM_SUCCESS</code>	If the token was refreshed with no errors.
<code>AM_INVALID_ARGUMENT</code>	If the <code>sso_token_handle</code> parameter is invalid.
<code>AM_SERVICE_NOT_INITIALIZED</code>	If the Session Service was not initialized with <code>am_sso_init()</code> .
<code>AM_SERVICE_NOT_AVAILABLE</code>	If server returned service not available.
<code>AM_HTTP_ERROR</code>	If an HTTP error was encountered while communicating with OpenSSO Enterprise.
<code>AM_ERROR_PARSING_XML</code>	If an error occurred while parsing XML from OpenSSO Enterprise.
<code>AM_ACCESS_DENIED</code>	If access was denied while communicating with OpenSSO Enterprise.
<code>AM_SESSION_FAILURE</code>	If the session validation failed.

AM_FAILURE

If any other error occurred.

am_sso_remove_listener()

Removes a single sign-on token listener.

Details

If `am_sso_add_listener()` was called more than once for the same listener function, all instances of the listener function will be removed.

Syntax

```
#include "am_sso.h"
AM_EXPORT am_status_t
am_sso_remove_listener(const am_sso_token_listener_func_t listener);
```

Parameters

This function takes the following parameter:

`listener` The listener as described in “[am_sso_token_listener_func_t](#)” on page 79.

Returns

This function returns one of the following values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file):

AM_SUCCESS	If the listener was successfully removed.
AM_INVALID_ARGUMENT	If the listener is NULL.
AM_NOT_FOUND	If listener was not found.
AM_FAILURE	If any other error occurred.

am_sso_remove_sso_token_listener()

Removes a single sign-on token listener associated with the specified single sign-on token handle.

Details

If `am_sso_add_listener()` was called more than once for the same listener function, all instances of the listener function will be removed.

Syntax

```
#include "am_sso.h"
AM_EXPORT am_status_t
am_sso_remove_sso_token_listener(const am_sso_token_handle_t sso_token_handle,
                                const am_sso_token_listener_func_t listener);
```

Parameters

This function takes the following parameters:

sso_token_handle	Pointer to a <code>am_sso_token_handle_t</code> type.
listener	The listener as described in “am_sso_token_listener_func_t” on page 79 .

Returns

This function returns one of the following values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file):

AM_SUCCESS	If the listener was successfully removed.
AM_INVALID_ARGUMENT	If the listener is NULL.
AM_NOT_FOUND	If listener was not found.
AM_FAILURE	If any other error occurred.

am_sso_set_property()

Sets a property and its value in the SSOToken associated with the specified single sign-on token handle.

Details

The single sign-on token handle for this SSOToken was obtained before this call and thus will not include the new property. You must call `am_sso_validate_token()` to update the handle.

Syntax

```
#include "am_sso.h"
AM_EXPORT am_status_t
am_sso_set_property(am_sso_token_handle_t sso_token_handle,
                   const char *name,
                   const char *value);
```


Parameters

This function takes the following parameters:

<code>sso_token_handle</code>	Pointer to a <code>am_sso_token_handle_t</code> type.
<code>name</code>	Pointer to the name of the property.



Caution – If the specified property is protected by OpenSSO Enterprise, `am_sso_set_property()` will return success, but the value given will not be set.

<code>value</code>	Pointer to the value for the specified property.
--------------------	--

Returns

This function returns one of the following values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file):

<code>AM_SUCCESS</code>	If the property was successfully set.
<code>AM_INVALID_ARGUMENT</code>	If the <code>sso_token_handle</code> is invalid.
<code>AM_FAILURE</code>	If any other error occurred.

`am_sso_validate_token()`

Updates the session information in the SSOToken associated with the specified single sign-on token handle.

Details

This call will go to OpenSSO Enterprise to retrieve the latest session information. The `sso_token_handle` is updated if the return status is either `AM_SUCCESS` or `AM_INVALID_SESSION`. This is different from `am_sso_refresh_token()` in that it does *not* update the last access time on the server.

Syntax

```
#include "am_sso.h"
AM_EXPORT am_status_t
am_sso_validate_token(const am_sso_token_handle_t sso_token_handle);
```

Parameters

This function takes the following parameter:

`sso_token_handle` Pointer to a `am_sso_token_handle_t` type.

Returns

This function returns one of the following values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file):

<code>AM_SUCCESS</code>	If single sign-on token is valid. The information is updated.
<code>AM_INVALID_SESSION</code>	If the session is invalid. The information is updated.
<code>AM_INVALID_ARGUMENT</code>	If the input parameter is invalid.
<code>AM_SERVICE_NOT_INITIALIZED</code>	If Session Service is not initialized.
<code>AM_SERVICE_NOT_AVAILABLE</code>	If OpenSSO Enterprise returned service not available.
<code>AM_HTTP_ERROR</code>	If HTTP error encountered while communicating with OpenSSO Enterprise.
<code>AM_ERROR_PARSING_XML</code>	If error parsing XML from OpenSSO Enterprise.
<code>AM_ACCESS_DENIED</code>	If access is denied while communicating with OpenSSO Enterprise.
<code>AM_FAILURE</code>	If any other error occurred.

◆ ◆ ◆ 5 CHAPTER 5

Logging Data Types and Functions

Sun OpenSSO Enterprise contains public data types and functions you can use for logging on the local system or on Sun OpenSSO Enterprise. Reference summaries include a short description, syntax, parameters and returns. The code is contained in the `<am_log.h>` header file. The sample source `am_log_test.c` demonstrates the basic usage of the logging API to record information such as user activity, traffic patterns and authorization violations. This chapter contains the following sections:

- [“The Logging API for C” on page 99](#)
- [“Logging Data Types” on page 100](#)
- [“Logging Functions” on page 101](#)

The Logging API for C

The logging API is designed to allow C applications to produce messages of interest and write them to the OpenSSO Enterprise logs. When some type of event occurs in an external application, the application code first determines if the *logging module* (a file created for messages usually relevant to a specific function or feature) to which the event is relevant has a level high enough to log the event. (A *level* specifies importance and defines the amount of detail that will be logged.) If the determination is affirmative, a log message is generated and a *log record* created in the relevant logging module. Information in the log record can be updated as necessary. The following notes regard the logging API for C functionality:

- The `am_log_init()` function by the application must be called before using any other `am_log_*` interfaces. If either the SSO, authentication, or policy initialization functions (`am_sso_init()`, `am_auth_init()`, or `am_policy_init()`) are called, `am_log_init()` does not need to be called as each of the three aforementioned functions call `am_log_init()` internally.
- The `am_log_record_*` interfaces can be used to set or update information in the log record. They include:
 - [“`am_log_record_add_loginfo\(\)`” on page 107](#)

- [“am_log_record_create\(\)” on page 108](#)
- [“am_log_record_destroy\(\)” on page 109](#)
- [“am_log_record_populate\(\)” on page 110](#)
- [“am_log_record_set_log_level\(\)” on page 110](#)
- [“am_log_record_set_log_message\(\)” on page 111](#)
- [“am_log_record_set_loginfo_props\(\)” on page 112](#)
- The following are convenience functions that provide simplified access to existing log records. They include:
 - [“am_log_record_set_log_level\(\)” on page 110](#)
 - [“am_log_record_set_log_message\(\)” on page 111](#)

Logging Data Types

The logging data types defined in `<am_log.h>` are:

- [“am_log_record_t” on page 100](#)
- [“am_log_module_id_t” on page 100](#)

am_log_record_t

Represents the information and message values to be recorded.

Note – See [Chapter 15, “Recording Events with the Logging Service,” in *Sun OpenSSO Enterprise 8.0 Technical Overview*](#) for information regarding events that are logged and the log fields to which they are written.

Syntax

```
#include "am_log.h"
typedef struct am_log_record *am_log_record_t;
```

Members

`am_log_record` is an opaque structure with no accessible members.

am_log_module_id_t

Represents the identifier for a logging module.

Note – See “[am_log_add_module\(\)](#)” on page 101 for information on logging modules.

Syntax

```
#include "am_log.h"
typedef unsigned int am_log_module_id_t;
```

Members

`am_log_module_id_t` has no members.

Logging Functions

The logging functions defined in `<am_log.h>` are:

- “[am_log_add_module\(\)](#)” on page 101
- “[am_log_flush_remote_log\(\)](#)” on page 103
- “[am_log_init\(\)](#)” on page 103
- “[am_log_is_level_enabled\(\)](#)” on page 104
- “[am_log_log\(\)](#)” on page 105
- “[am_log_log_record\(\)](#)” on page 106
- “[am_log_record_add_loginfo\(\)](#)” on page 107
- “[am_log_record_create\(\)](#)” on page 108
- “[am_log_record_destroy\(\)](#)” on page 109
- “[am_log_record_populate\(\)](#)” on page 110
- “[am_log_record_set_log_level\(\)](#)” on page 110
- “[am_log_record_set_log_message\(\)](#)” on page 111
- “[am_log_record_set_loginfo_props\(\)](#)” on page 112
- “[am_log_set_levels_from_string\(\)](#)” on page 113
- “[am_log_set_log_file\(\)](#)” on page 113
- “[am_log_set_module_level\(\)](#)” on page 114
- “[am_log_set_remote_info\(\)](#)” on page 115
- “[am_log_vlog\(\)](#)” on page 116

`am_log_add_module()`

Adds a new logging file (for a specific function or feature) to the OpenSSO Enterprise Logging Service.

Details

The currently used *module* file names are:

- AuthService
- NamingService
- PolicyService
- SessionService
- PolicyEngine
- ServiceEngine
- Notification
- PolicyAgent
- RemoteLog
- all

Syntax

```
#include "am_log.h"
AM_EXPORT am_status_t
am_log_add_module(const char *name,
                  am_log_module_id_t *id_ptr);
```

Parameters

This function takes the following parameters:

- name Pointer to the name associated with the new module.
- id_ptr Pointer to the location where the identifier for the logging module is stored.

Returns

This function returns one of the following values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file):

Note – If a module of the same name already exists, the module identifier of the existing module is returned.

AM_SUCCESS	If the addition was successful.
AM_INVALID_ARGUMENT	If name or id_ptr is NULL.
AM_NSPR_ERROR	If unable to initialize the logging framework.
AM_NO_MEMORY	If unable to allocate memory for the new module.
AM_FAILURE	If any other error is detected.

am_log_flush_remote_log()

Flushes all the log records in the OpenSSO Enterprise log buffer.

Syntax

```
#include "am_log.h"
AM_EXPORT am_status_t
am_log_flush_remote_log();
```

Parameters

This function takes no parameters:

Returns

This function returns one of the following values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file):

<code>AM_SUCCESS</code>	If the flush was successful.
<code>AM_*</code>	The appropriate code based on the error.

am_log_init()

Initializes the Logging Service.

Details

`am_log_init()` writes events to the logs on the OpenSSO Enterprise server.

Syntax

```
#include "am_log.h"
AM_EXPORT am_status_t
am_log_init(const am_properties_t log_init_params);
```

Parameters

This function takes the following parameter:

<code>log_init_params</code>	Properties used to initialize the Logging Service.
------------------------------	--

Note – See “[am_properties_t](#)” on page 137 for more information.

Returns

This function returns one of the following values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file):

- `AM_SUCCESS` If log initialization is successful.
- `AM_*` If any error occurs, the type of error indicated by the status value.

am_log_is_level_enabled()

Checks whether an event at the specified level intended for the specified logging module should generate a logging message.

Details

If the level of the event is not equal to or higher than the level of the logging module, a logging message will not be generated.

Syntax

```
#include "am_log.h"
AM_EXPORT boolean_t
am_log_is_level_enabled(am_log_module_id_t moduleID,
                       am_log_level_t level);
```

Parameters

This function takes the following parameters:

- `moduleID` The identifier of the logging module.
- `level` The level of the event. Possible values are defined in the following `am_log_level_t` enumeration. The default value is `AM_LOG_INFO`.

```
typedef enum am_log_level {
    AM_LOG_ALWAYS = -1, /* always logged */
    AM_LOG_NONE,      /* never logged, typically used to turn off a module */
    AM_LOG_ERROR,      /* used for error messages */
    AM_LOG_WARNING,    /* used for warning messages */
    AM_LOG_INFO,       /* used for informational messages */
    AM_LOG_DEBUG,      /* used for debug messages */
    AM_LOG_MAX_DEBUG,  /* used for more detailed debug messages */
    AM_LOG_AUTH_REMOTE = 128, /* logged deny and/or allow */
    AM_LOG_AUTH_LOCAL = 256
} am_log_level_t;
```


Returns

This function returns one of the following values of the `boolean_t` enumeration (defined in the standard `<types.h>` header file):

Note – The code used is dependent on the server operating system.

- `!0` If a message will be generated.
- `0` If a message will not be generated.

am_log_log()

Produces a logging message from the specified event string.

Details

When using `am_log_log()`, consider the following:

- The message is produced only if the level defined for the specified module is greater than or equal to the level defined for the message. See [“`am_log_is_level_enabled\(\)`” on page 104](#).
- `am_log_log()` directly enumerates arguments for the format string. See [“`am_log_vlog\(\)`” on page 116](#) for another method.

Syntax

```
#include "am_log.h"
AM_EXPORT boolean_t
am_log_log(am_log_module_id_t moduleID,
           am_log_level_t level,
           const char *format, ...);
```

Parameters

This function takes the following parameters:

- | | |
|-----------------------|---|
| <code>moduleID</code> | The identifier of the OpenSSO Enterprise logging module to which the message is relevant. |
| <code>level</code> | The level of the message. Each message has an associated level that defines the amount of detail that will be logged. Possible values are defined in the <code>am_log_level_t</code> enumeration. The default value is <code>AM_LOG_INFO</code> . |

```
typedef enum am_log_level {
    AM_LOG_ALWAYS = -1, /* always logged */
    AM_LOG_NONE,      /* never logged, typically used to turn off a module */
    AM_LOG_ERROR,      /* used for error messages */
    AM_LOG_WARNING,    /* used for warning messages */
    AM_LOG_INFO,       /* used for informational messages */
    AM_LOG_DEBUG,      /* used for debug messages */
    AM_LOG_MAX_DEBUG,  /* used for more detailed debug messages */
    AM_LOG_AUTH_REMOTE = 128, /* logged deny and/or allow */
    AM_LOG_AUTH_LOCAL = 256
} am_log_level_t;
```

format Pointer to a printf-style character string detailing the event.

Note – The set of additional arguments needed by format are either enumerated directly or passed using the standard `va_list` mechanism as appropriate to the call. See “[am_log_vlog\(\)](#)” on page 116.

Returns

This function returns one of the values of the `boolean_t` enumeration (defined in the standard `<types.h>` header file):

Note – The code used is dependent on the server operating system.

`!0` If the message is logged.

`0` If the message will not be logged.

am_log_log_record()

Writes the given log record to the specified logging module.

Syntax

```
#include "am_log.h"
AM_EXPORT am_status_t
am_log_log_record(am_log_record_t record,
                  const char *log_name,
                  const char *logged_by_token_id);
```

Parameters

This function takes the following parameters:

<code>record</code>	The log record pointer.
<code>log_name</code>	Pointer to the name of the logging module to which the log record will be written.
<code>logged_by_token_id</code>	Pointer to a valid SSOTokenID identifying the user to whom the log record applies.

Note – This is required to access the Logging Service on OpenSSO Enterprise.

Returns

This function returns one of the following values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file):

<code>AM_SUCCESS</code>	If log record is written.
<code>AM_*</code>	If any error occurs, the type of error indicated by the status value.

`am_log_record_add_loginfo()`

Updates a log record with additional information.

Syntax

```
#include "am_log.h"
AM_EXPORT am_status_t
am_log_record_add_loginfo(am_log_record_t record,
                          const char *key,
                          const char *value);
```

Parameters

This function takes the following parameters:

<code>record</code>	A log record pointer.
<code>key</code>	Pointer to the log field being updated.

Note – See [Chapter 15, “Recording Events with the Logging Service,”](#) in *Sun OpenSSO Enterprise 8.0 Technical Overview* for information regarding events that are logged and the log fields to which they are written.

value Pointer to the value with which the log field will be modified.

Returns

This function returns one of the values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file).

am_log_record_create()

Instantiates a log record, initializing it with a message and the message's corresponding level.

Syntax

```
#include "am_log.h"
AM_EXPORT am_status_t
am_log_record_create(am_log_record_t *record_ptr,
                    am_log_record_log_level_t log_level,
                    const char *message);
```

Parameters

This function takes the following parameters:

record_ptr Pointer to a log record pointer.

log_level The level with which the log record will be instantiated. Each log record has an associated level that defines its relative importance and urgency. Possible values are defined in the `am_log_record_log_level_t` enumeration.

```
typedef enum am_log_record_log_level {

    /* Log Level as defined by JDK 1.4 */

    AM_LOG_LEVEL_SEVERE = 1000,
    AM_LOG_LEVEL_WARNING = 900,
    AM_LOG_LEVEL_INFORMATION = 800,
    AM_LOG_LEVEL_CONFIG = 700,
    AM_LOG_LEVEL_FINE = 500,
    AM_LOG_LEVEL_FINER = 400,
```

```
        AM_LOG_LEVEL_FINEST = 300,

        /* Log Levels defined by Access Manager */

        AM_LOG_LEVEL_SECURITY = 950,
        AM_LOG_LEVEL_CATASTROPHE = 850,
        AM_LOG_LEVEL_MISCONF = 750,
        AM_LOG_LEVEL_FAILURE = 650,
        AM_LOG_LEVEL_WARN = 550,
        AM_LOG_LEVEL_INFO = 450,
        AM_LOG_LEVEL_DEBUG = 350,
        AM_LOG_LEVEL_ALL = 250

    } am_log_record_log_level_t;

message    Pointer to the log message to be written to the log record.
```

Returns

This function returns one of the values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file).

am_log_record_destroy()

Destroys the specified log record.

Syntax

```
#include "am_log.h"
AM_EXPORT am_status_t
am_log_record_destroy(am_log_record_t record);
```

Parameters

This function takes the following parameter:

`record` A log record pointer.

Returns

This function returns one of the values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file).

am_log_record_populate()

Updates a log record with the user's session identifier (also known as an SSOTokenID).

Details

See [“Single Sign-on Token Handles” on page 74](#) for more information.

Syntax

```
#include "am_log.h"
AM_EXPORT am_status_t
am_log_record_populate(am_log_record_t record,
                      const char *user_token_id);
```

Parameters

This function takes the following parameters:

record	A log record pointer.
user_token_id	Pointer to a valid session identifier (also known as an SSOTokenID).

Returns

This function returns one of the values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file).

am_log_record_set_log_level()

Sets the level for the specified log record.

Syntax

```
#include "am_log.h"
AM_EXPORT am_status_t
am_log_record_set_log_level(am_log_record_t record,
                           am_log_record_log_level_t log_level);
```

Parameters

This function takes the following parameters:

record	A log record pointer.
--------	-----------------------

`log_level` The level to which the log record will be set. Each log record has an associated level that defines its relative importance and urgency. Possible values are defined in the `am_log_record_log_level_t` enumeration.

```
typedef enum am_log_record_log_level {

    /* Log Level as defined by JDK 1.4 */

    AM_LOG_LEVEL_SEVERE = 1000,
    AM_LOG_LEVEL_WARNING = 900,
    AM_LOG_LEVEL_INFORMATION = 800,
    AM_LOG_LEVEL_CONFIG = 700,
    AM_LOG_LEVEL_FINE = 500,
    AM_LOG_LEVEL_FINER = 400,
    AM_LOG_LEVEL_FINEST = 300,

    /* Log Levels defined by Access Manager */

    AM_LOG_LEVEL_SECURITY = 950,
    AM_LOG_LEVEL_CATASTROPHE = 850,
    AM_LOG_LEVEL_MISCONF = 750,
    AM_LOG_LEVEL_FAILURE = 650,
    AM_LOG_LEVEL_WARN = 550,
    AM_LOG_LEVEL_INFO = 450,
    AM_LOG_LEVEL_DEBUG = 350,
    AM_LOG_LEVEL_ALL = 250

} am_log_record_log_level_t;
```

Returns

This function returns one of the values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file).

`am_log_record_set_log_message()`

Sets the log message to the log record before localization and formatting.

Syntax

```
#include "am_log.h"
AM_EXPORT am_status_t
am_log_record_set_log_message(am_log_record_t record,
                             const char *message);
```

Parameters

This function takes the following parameters:

- record** A log record pointer.
- message** Pointer to the log message to be written to the log record.

Returns

This function returns one of the values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file).

`am_log_record_set_loginfo_props()`

Updates the specified log record with additional information.

Details

`log_info` is expected to have the information formatted as key/value pairs in a properties map. Delete the `am_properties_t` pointer only when finished with the SDK. See [“`am_properties_t`” on page 137](#) for more information.

Syntax

```
#include "am_log.h"
AM_EXPORT am_status_t
am_log_record_set_loginfo_props(am_log_record_t record,
                               am_properties_t log_info);
```

Parameters

This function takes the following parameters:

- record** A log record pointer.
- log_info** Pointer to the properties that contain the information to be set in the log record.

Returns

This function returns one of the values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file).

am_log_set_levels_from_string()

Sets the level for the logging modules listed in a specified string.

Details

The format of the string must be:

*ModuleName[:Level][,ModuleName[:Level]]**

Optional spaces may occur before and after any commas. The comma, brackets and asterisk in the second term signifies that it can occur 0 or more times.

Syntax

```
#include "am_log.h"
AM_EXPORT am_status_t
am_log_set_levels_from_string(const char *module_level_string);
```

Parameters

This function takes the following parameter:

<code>module_level_string</code>	Pointer to the string containing the list of modules and the respective levels.
----------------------------------	---

Returns

This function returns one of the following values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file):

<code>AM_SUCCESS</code>	If the levels were successfully set.
<code>AM_INVALID_ARGUMENT</code>	If <code>module_level_string</code> is <code>NULL</code> .
<code>AM_FAILURE</code>	If any other error is detected.

am_log_set_log_file()

Sets the name of the file to use for logging.

Syntax

```
#include "am_log.h"
AM_EXPORT am_status_t
am_log_set_log_file(const char *name);
```

Parameters

This function takes the following parameter:

name Pointer to the name of the file to which log records are recorded.

Note – If NULL or empty, logging messages are sent to the `stderr` stream.

Returns

This function returns one of the following values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file):

AM_SUCCESS If the logging file is successfully set.
AM_NO_MEMORY If unable to allocate memory for internal data structures.
AM_FAILURE If an error of any type occurs.

`am_log_set_module_level()`

Sets the level for the specified logging module.

Syntax

```
#include "am_log.h"
AM_EXPORT am_log_level_t
am_log_set_module_level(am_log_module_id_t moduleID,
                       am_log_level_t level);
```

Parameters

This function takes the following parameters:

moduleID The identifier of the logging module.
level The level to which the logging module will be set. Each module has an associated level that defines the amount of detail that will be logged. Possible values are defined in the following enumeration. The default value is `AM_LOG_INFO`.

```
typedef enum am_log_level {
    AM_LOG_ALWAYS = -1, /* always logged */
    AM_LOG_NONE,      /* never logged, typically used to turn off a module */
    AM_LOG_ERROR,      /* used for error messages */
    AM_LOG_WARNING,    /* used for warning messages */
    AM_LOG_INFO,       /* used for informational messages */
}
```

```
AM_LOG_DEBUG,    /* used for debug messages */
AM_LOG_MAX_DEBUG, /* used for more detailed debug messages */
AM_LOG_AUTH_REMOTE = 128, /* logged deny and/or allow */
AM_LOG_AUTH_LOCAL = 256
} am_log_level_t;
```

Returns

This function returns `am_log_level_t` with one of the following values:

The previous logging level of the module. If the logging level is set properly.

LOG_NONE If the specified module is invalid.

am_log_set_remote_info()

Initializes the remote log service.

Details

This must be called before `am_log_log()` with `AM_LOG_REMOTE_MODULE` as the log module. Initialization is done only once. Subsequently, only remote logging calls are done.

Syntax

```
#include "am_log.h"
AM_EXPORT am_status_t
am_log_set_remote_info(const char *rem_log_url,
                      const char *sso_token_id,
                      const char *rem_log_name,
                      const am_properties_t log_props);
```

Parameters

This function takes the following parameters:

<code>rem_log_url</code>	Pointer to the URL of the OpenSSO Enterprise Logging Service being used for the remote logging.
<code>sso_token_id</code>	Pointer to a valid SSOTokenID identifying the user to whom the log record applies.
<code>rem_log_name</code>	Pointer to the logging module (file) to which log records are written.
<code>log_props</code>	Pointer to the properties that contain the information to initialize the OpenSSO Enterprise Logging Service.

Note – `log_props` is expected to have the information formatted as a properties map in key/value pairs. Delete the `am_properties_t` pointer only when finished with the SDK. See “[am_properties_t](#)” on page 137 for more information.

Returns

This function returns one of the values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file).

am_log_vlog()

Logs a message for the specified module at the given level.

Details

When using `am_log_vlog()`, consider the following:

- The message is produced only if the level defined for the specified module is greater than or equal to the level defined for the message. See “[am_log_is_level_enabled\(\)](#)” on page 104.
- `am_log_vlog()` passes the standard `va_list` as an argument for the format string. See “[am_log_log\(\)](#)” on page 105 for another method.

Syntax

```
#include "am_log.h"
AM_EXPORT boolean_t
am_log_vlog(am_log_module_id_t moduleID,
            am_log_level_t level,
            const char *format,
            va_list args);
```

Parameters

This function takes the following parameters:

- | | |
|-----------------------|---|
| <code>moduleID</code> | The identifier of the OpenSSO Enterprise logging module to which the message is relevant. |
| <code>level</code> | The level of the message. Each message has an associated level that defines the amount of detail that will be logged. Possible values are defined in the <code>am_log_level_t</code> enumeration. The default value is <code>AM_LOG_INFO</code> . |

```
typedef enum am_log_level {
    AM_LOG_ALWAYS = -1, /* always logged */
    AM_LOG_NONE,      /* never logged, typically used to turn off a module */
    AM_LOG_ERROR,      /* used for error messages */
    AM_LOG_WARNING,    /* used for warning messages */
    AM_LOG_INFO,       /* used for informational messages */
    AM_LOG_DEBUG,      /* used for debug messages */
    AM_LOG_MAX_DEBUG,  /* used for more detailed debug messages */
    AM_LOG_AUTH_REMOTE = 128, /* logged deny and/or allow */
    AM_LOG_AUTH_LOCAL = 256
} am_log_level_t;
```

format Pointer to a printf-style character string.

Note – The set of addition arguments needed by format are either enumerated directly or passed using the standard `va_list` mechanism as appropriate to the call.

va_list A void pointer interpreted as an argument list. `va_list` is the type of the void pointer passed to a function that accepts a pointer to a list of arguments.

Note – The set of additional arguments needed by format are either enumerated directly or passed using the standard `va_list` mechanism as appropriate to the call. See “[am_log_log\(\)](#)” on page 105.

Returns

This function returns one of the values of the `boolean_t` enumeration (defined in the standard `<types.h>` header file):

Note – The code used is dependent on the server operating system. See `<am_types.h>` for more details.

!0 If the message can be logged.

0 If the message will not be logged.

CHAPTER 6

Mapping Data Types and Functions

Sun OpenSSO Enterprise contains public data types and functions you can use for creating, destroying, and manipulating map objects. Reference summaries include a short description, syntax, parameters and returns. The code is contained in the `<am_map.h>` header file. The sample source `am_policy_test.c` demonstrates the basic usage of some of the basic mapping functions. This chapter contains the following sections:

- [“The Mapping API for C” on page 119](#)
- [“Mapping Data Types” on page 119](#)
- [“Mapping Functions” on page 121](#)

The Mapping API for C

A *map* is an object that associates a *key* to a *value*. One key/value pair is an *entry* in the map. Maps are used by the policy API for C to return policy decision results from the Policy Service. They are also used to pass any environment variables to the Policy Service for evaluation.

Mapping Data Types

The mapping types defined in `<am_map.h>` are:

- [“`am_map_t`” on page 119](#)
- [“`am_map_entry_iter_t`” on page 120](#)
- [“`am_map_value_iter_t`” on page 120](#)

`am_map_t`

Pointer to a map object consisting of key/value entry mappings.

Syntax

```
#include "am_map.h"
typedef struct am_map *am_map_t;
```

Members

`am_map` is an opaque structure with no accessible members.

Memory Concerns

Free the allocated structure by calling `am_map_destroy()`. See [“`am_map_destroy\(\)`” on page 123](#).

`am_map_entry_iter_t`

Pointer to an iterator for the entries in a map object.

Syntax

```
#include "am_map.h"
typedef struct am_map_entry_iter *am_map_entry_iter_t;
```

Members

`am_map_entry_iter` is an opaque structure with no accessible members.

`am_map_value_iter_t`

Pointer to an iterator for the values in a map object associated with a specified key.

Syntax

```
#include "am_map.h"
typedef struct am_map_value_iter *am_map_value_iter_t;
```

Members

`am_map_value_iter` is an opaque structure with no accessible members.

Mapping Functions

The mapping functions defined in `<am_map.h>` are:

- `“am_map_clear()”` on page 121
- `“am_map_copy()”` on page 122
- `“am_map_create()”` on page 123
- `“am_map_destroy()”` on page 123
- `“am_map_entry_iter_destroy()”` on page 124
- `“am_map_entry_iter_get_first_value()”` on page 124
- `“am_map_entry_iter_get_key()”` on page 125
- `“am_map_entry_iter_get_values()”` on page 126
- `“am_map_entry_iter_is_entry_valid()”` on page 127
- `“am_map_entry_iter_next()”` on page 127
- `“am_map_erase()”` on page 128
- `“am_map_find()”` on page 129
- `“am_map_find_first_value()”` on page 129
- `“am_map_for_each()”` on page 130
- `“am_map_get_entries()”` on page 131
- `“am_map_insert()”` on page 132
- `“am_map_size()”` on page 133
- `“am_map_value_iter_destroy()”` on page 134
- `“am_map_value_iter_get()”` on page 134
- `“am_map_value_iter_is_value_valid()”` on page 135
- `“am_map_value_iter_next()”` on page 135

am_map_clear()

Erases all of the entries in the specified map object.

Syntax

```
#include "am_map.h"
AM_EXPORT am_status_t
am_map_clear(am_map_t map);
```

Parameters

This function takes the following parameter:

`map` The map object.

Returns

This function returns one of the following values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file):

AM_SUCCESS	If the entries were successfully erased.
AM_INVALID_ARGUMENT	If the map argument is NULL.

am_map_copy()

Makes a copy of the specified map object.

Details

`am_map_copy()` creates a new instance of a `am_map_t`, copies all the elements from the specified `source_map` into it, and assigns to the new instance a pointer. It does not alter the contents of the original map object.

Syntax

```
#include "am_map.h"
AM_EXPORT am_status_t
am_map_copy(am_map_t source_map,
            am_map_t *map_ptr);
```

Parameters

This function takes the following parameters:

<code>source_map</code>	The specified map object. It may be NULL.
<code>map_ptr</code>	Pointer to the location of the new map object copy.



Caution – Be sure not to pass `map_ptr` as a valid `am_map` structure as the reference will be lost.

Returns

This function returns one of the following values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file):

AM_SUCCESS	If the map object was successfully copied.
AM_NO_MEMORY	If unable to allocate memory for the new map object.
AM_INVALID_ARGUMENT	If the <code>source_map</code> or <code>map_ptr</code> argument is NULL.

Memory Concerns

The caller must destroy `map_ptr` after usage by calling `am_map_destroy()`.

am_map_create()

Creates a new, empty map object.

Details

`am_map_create()` creates an instance of a `am_map_t` and returns a pointer back to the caller.

Syntax

```
#include "am_map.h"
AM_EXPORT am_status_t
am_map_create(am_map_t *map_ptr);
```

Parameters

This function takes the following parameter:

`map_ptr` Pointer specifying the location of the new map object.



Caution – Be sure not to pass `map_ptr` as a valid `am_map` structure as the reference will be lost.

Returns

This function returns one of the following values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file):

<code>AM_SUCCESS</code>	If the map object was successfully created.
<code>AM_NO_MEMORY</code>	If unable to allocate memory for the new map object.
<code>AM_INVALID_ARGUMENT</code>	If the <code>map_ptr</code> argument is <code>NULL</code> .

am_map_destroy()

Destroys the specified map object.

Syntax

```
#include "am_map.h"
AM_EXPORT void
am_map_destroy(am_map_t map);
```

Parameters

This function takes the following parameter:

`map` The specified map object. It may be `NULL`.



Caution – Be sure not to pass `map` as a valid `am_map` structure as the reference will be lost.

Returns

This function does not return a value.

Memory Concerns

The pointer to the specified map object can not be freed before calling `am_map_destroy()`. This includes erroneously calling the system `free(void *)` function.

`am_map_entry_iter_destroy()`

Destroys the specified entry iterator.

Syntax

```
#include "am_map.h"
AM_EXPORT void
am_map_entry_iter_destroy(am_map_entry_iter_t entry_iter);
```

Parameters

This function takes the following parameter:

`entry_iter` The specified entry iterator. It may be `NULL`.

Returns

This function does not return a value.

`am_map_entry_iter_get_first_value()`

Returns the first value assigned to the entry currently being referenced by the specified entry iterator.

Syntax

```
#include "am_map.h"
AM_EXPORT const char *
am_map_entry_iter_get_first_value(am_map_entry_iter_t entry_iter);
```

Parameters

This function takes the following parameter:

`entry_iter` The specified entry iterator. It may be `NULL`.

Returns

This function returns one of the following:

- `char *` Returns the first associated value of the specified key. The order of insertion into the map does not guarantee the value returned.
- `NULL` If the specified iterator is `NULL`, does not reference a valid entry, or the entry does not have any associated values.

Memory Concerns

`am_map_entry_iter_get_first_value()` destroys the `am_map_entry_iter_t` passed to it. Because of this, don't call this function more than once on the same `am_map_entry_iter_t`.

`am_map_entry_iter_get_key()`

Returns the key assigned to the entry currently being referenced by the specified entry iterator.

Syntax

```
#include "am_map.h"
AM_EXPORT const char *
am_map_entry_iter_get_key(am_map_entry_iter_t entry_iter);
```

Parameters

This function takes the following parameters:

`entry_iter` The specified entry iterator.

Returns

This function returns one of the following values:

char * Returns the key.

Note – Caller must not modify or free the return value.

NULL If the specified key iterator is NULL or does not reference a valid entry.

am_map_entry_iter_get_values()

Returns a value iterator that can be used to sequence through the values assigned to the entry currently being referenced by the specified entry iterator.

Syntax

```
#include "am_map.h"
AM_EXPORT am_status_t
am_map_entry_iter_get_values(am_map_entry_iter_t entry_iter,
                           am_map_value_iter_t *value_iter_ptr);
```

Parameters

This function takes the following parameters:

entry_iter The specified entry iterator.

value_iter_ptr Pointer specifying the location of the value iterator.

Returns

This function returns one of the following values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file):

AM_SUCCESS If no error was detected.

AM_NO_MEMORY If unable to allocate memory for the key iterator.

AM_INVALID_ARGUMENT If the `value_iter_ptr` argument is NULL.

Note – If `value_iter_ptr` is not NULL and an error is returned, the location that it references will be set to NULL.

AM_NOT_FOUND If the `entry_iter` argument is NULL or does not reference a valid entry.

Memory Concerns

After using `am_map_value_iter_t`, the caller must call `am_map_value_iter_destroy()`.

`am_map_entry_iter_is_entry_valid()`

Determines if the entry currently being referenced by the specified entry iterator is valid.

Syntax

```
#include "am_map.h"
AM_EXPORT boolean_t
am_map_entry_iter_is_entry_valid(am_map_entry_iter_t entry_iter);
```

Parameters

This function takes the following parameter:

`entry_iter` The specified entry iterator.

Returns

This function returns one of the following values of the `boolean_t` enumeration (defined in the standard `<types.h>` header file):

Note – The code used is dependent on the server operating system.

`!0` If the entry is valid.

`0` If the specified iterator is NULL or does not reference a valid entry.

`am_map_entry_iter_next()`

Advances the specified entry iterator to the next entry in the map specified when the iterator was first created.

Syntax

```
#include "am_map.h"
AM_EXPORT boolean_t
am_map_entry_iter_next(am_map_entry_iter_t entry_iter);
```

Parameters

This function takes the following parameter:

`entry_iter` The specified event iterator.

Returns

This function returns one of the following values of the `boolean_t` enumeration (defined in the standard `<types.h>` header file):

Note – The code used is dependent on the server operating system.

`!0` If the entry is valid.

`0` If the specified iterator is NULL or does not reference a valid entry after being updated.

`am_map_erase()`

Erases the entry, associated with the specified key, from the specified map object.

Syntax

```
#include "am_map.h"
AM_EXPORT am_status_t
am_map_erase(am_map_t map,
             const char *key);
```

Parameters

This function takes the following parameters:

`map` The specified map object.

`key` Pointer to the key of the entry to be erased.

Returns

This function returns one of the following values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file):

`AM_SUCCESS` If the entry was successfully erased.

`AM_INVALID_ARGUMENT` If either the map or key argument is NULL.

`AM_NOT_FOUND` If the specified key is not in the map.

am_map_find()

Returns a value iterator that can sequence through all values associated with the specified key in the specified map object.

Syntax

```
#include "am_map.h"
AM_EXPORT am_status_t
am_map_find(am_map_t map,
            const char *key,
            am_map_value_iter_t *value_iter_ptr);
```

Parameters

This function takes the following parameters:

map	The specified map object.
key	Pointer to a key.
value_iter_ptr	Pointer specifying the location of the returned value iterator.

Note – If `value_iter_ptr` is not NULL, the location that it references will be set to NULL if an error is returned.

Returns

This function returns one of the following values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file):

AM_SUCCESS	If no error was detected.
AM_NO_MEMORY	If unable to allocate memory for the key iterator.
AM_INVALID_ARGUMENT	If the <code>value_iter_ptr</code> argument is NULL.
AM_NOT_FOUND	If the specified key is not found in the map.

Memory Concerns

After using `value_iter_ptr`, the caller must call `am_map_value_iter_destroy()`.

am_map_find_first_value()

Returns the first value associated with the specified key in the specified map object.

Details

`am_map_find_first_value()` takes a key and returns the first value associated with that key.

Syntax

```
#include "am_map.h"
AM_EXPORT const char *
am_map_find_first_value(am_map_t map,
                       const char *key);
```

Parameters

This function takes the following parameters:

`map` The specified map object.

`key` Pointer to a key.

Returns

This function returns one of the following values:

`char *` Returns the first value associated with the specified key.

Note – Caller must not modify or free the return value.

`NULL` If the specified key could not be found in the map or had no associated values.

`am_map_for_each()`

Returns a map iterator on a function pointer for the specified map object.

Details

`am_map_for_each()` will iterate over the list of key/value pairs and call each one. For every key in the map, a function can be invoked via the function pointer.

Syntax

```
#include "am_map.h"
AM_EXPORT am_status_t
am_map_for_each(am_map_t,
               am_status_t (*func)(const char *key,
                                   const char *value,
```

```
void **args),  
void **args);
```

Parameters

This function takes the following parameters:

<code>am_map_t</code>	The specified map object.
<code>key</code>	Pointer to a key in an entry.
<code>args</code>	Pointer to application-defined parameters.

Returns

This function returns one of the following values:

Other codes	If the function returns any code other than <code>AM_SUCCESS</code> , the iteration will terminate and the same status code will be returned to the user.
<code>AM_INVALID_ARGUMENT</code>	If the parameters are invalid.

`am_map_get_entries()`

Returns an entry iterator object that can be used to enumerate all entries in the specified map.

Details

`am_map_get_entries()` returns a pointer to an entry iterator that can be used on the key/value pairs stored in the specified map object.

Syntax

```
#include "am_map.h"  
AM_EXPORT am_status_t  
am_map_get_entries(am_map_t map,  
                   am_map_entry_iter_t *entry_iter_ptr);
```

Parameters

This function takes the following parameters:

<code>map</code>	The specified map object.
<code>entry_iter_ptr</code>	Pointer specifying the location of the entry iterator.

Note – If `entry_iter_ptr` is not `NULL`, the location it refers to will be set to `NULL` if an error is returned.

Returns

This function returns one of the following values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file):

<code>AM_SUCCESS</code>	If no error is detected.
<code>AM_NO_MEMORY</code>	If unable to allocate memory for the entry iterator object.
<code>AM_INVALID_ARGUMENT</code>	If <code>entry_iter_ptr</code> is <code>NULL</code> .
<code>AM_NOT_FOUND</code>	If the specified map object contains no keys.

Memory Concerns

The pointer to the iterator must have only one iterator assigned.

`am_map_entry_iter_destroy()` must be called when finished to destroy the iterator instance.

`am_map_insert()`

Inserts a new key/value pair into the specified map.

Details

The map does not retain any references to the provided key or value parameters. It makes copies of any strings it needs to store.

Syntax

```
#include "am_map.h"
AM_EXPORT am_status_t
am_map_insert(am_map_t map,
              const char *key,
              const char *value,
              int replace);
```

Parameters

This function takes the following parameters:

`map` The specified map object.

key	Pointer to the key for the entry.
-----	-----------------------------------

Note – If an entry with the same key already exists, the existing value is replaced by the new value.

value	Pointer to the [new] value to be associated with the key.
-------	---

replace	If not zero, the specified value replaces all existing values. Otherwise, the specified value is added to the list of values already associated with the specified key.
---------	---

Returns

This function returns one of the following values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file):

<code>AM_SUCCESS</code>	If the entry was successfully inserted into the map object.
<code>AM_NO_MEMORY</code>	If unable to allocate memory for the value and, if necessary, the key.
<code>AM_INVALID_ARGUMENT</code>	If either the map, key, or value argument is <code>NULL</code> .

`am_map_size()`

Returns the number of entries in the specified map object.

Syntax

```
#include "am_map.h"
AM_EXPORT size_t
am_map_size(const am_map_t map);
```

Parameters

This function takes the following parameter:

map	The specified map object.
-----	---------------------------

Returns

This function returns a value based on `size_t` defined in the standard `<stddef.h>` header file. The value reflects the number of entries in the specified map object.

am_map_value_iter_destroy()

Destroys the specified value iterator.

Details

`am_map_value_iter_destroy()` destroys the `am_map_value_iter_t` passed to it. The caller must be sure that this function is not called multiple times on the same `am_map_value_iter_t`.

Syntax

```
#include "am_map.h"
AM_EXPORT void
am_map_value_iter_destroy(am_map_value_iter_t iter);
```

Parameters

This function takes the following parameter:

`iter` The specified value iterator.

Returns

This function does not return a value.

am_map_value_iter_get()

Returns the value currently referenced by the specified value iterator.

Syntax

```
#include "am_map.h"
AM_EXPORT const char *
am_map_value_iter_get(am_map_value_iter_t iter);
```

Parameters

This function takes the following parameter:

`iter` The specified value iterator.

Returns

This function returns one of the following values:

`char *` The value.

`NULL` If the specified iterator is `NULL` or does not reference a valid value.

`am_map_value_iter_is_value_valid()`

Determines if the specified value iterator references a valid value.

Syntax

```
#include "am_map.h"
AM_EXPORT boolean_t
am_map_value_iter_is_value_valid(am_map_value_iter_t iter);
```

Parameters

This function takes the following parameter:

`iter` The specified value iterator.

Returns

This function returns one of the following values of the `boolean_t` enumeration (defined in the standard `<types.h>` header file):

Note – The code used is dependent on the server operating system.

`!0` If the value is valid.

`0` If the specified iterator is `NULL` or does not reference a valid value.

`am_map_value_iter_next()`

Advances the specified value iterator to the next value associated with the key that was specified when the iterator was created.

Syntax

```
#include "am_map.h"
AM_EXPORT boolean_t
am_map_value_iter_next(am_map_value_iter_t iter);
```

Parameters

This function takes the following parameter:

`iter` The specified value iterator.

Returns

This function returns one of the following values of the `boolean_t` enumeration (defined in the standard `<types.h>` header file):

Note – The code used is dependent on the server operating system.

`!0` If successful.

`0` If the specified iterator is NULL or does not reference a valid value after being updated.

7

◆ ◆ ◆ CHAPTER 7

Property Data Types and Functions

Sun OpenSSO Enterprise contains public data types and functions you can use to associate properties between an external application and OpenSSO Enterprise itself. Reference summaries include a short description, syntax, parameters and returns. Prototypes for the types and functions are contained in the `<am_properties.h>` header file. This chapter contains the following sections:

- “Property Data Types” on page 137
- “Property Functions” on page 138

The Property API for C

The property API for C are used to manipulate configuration data read from a standard Java™ properties file. A properties file is a text file that contains a list of key/value pairs. More information on properties files can be found at [http://java.sun.com/j2se/1.4.2/docs/api/java/util/Properties.html#load\(java.io.InputStream\)](http://java.sun.com/j2se/1.4.2/docs/api/java/util/Properties.html#load(java.io.InputStream)).

Property Data Types

The property data types defined in `<am_properties.h>` are:

- “`am_properties_t`” on page 137
- “`am_properties_iter_t`” on page 138

`am_properties_t`

Pointer to a properties object.

Details

`am_properties_t` provides a key to single value mapping. It provides the additional functionality of loading a configuration file and getting values of specific data types.

Syntax

```
#include "am_properties.h"
typedef struct am_properties *am_properties_t;
```

Members

`am_properties` is an opaque structure with no accessible members.

`am_properties_iter_t`

Pointer to the iterator for a properties object.

Syntax

```
#include "am_properties.h"
typedef struct am_properties_iter *am_properties_iter_t;
```

Members

`am_properties_iter` is an opaque structure with no accessible members.

Property Functions

The property functions defined in `<am_properties.h>` are:

- `“am_properties_copy()”` on page 139
- `“am_properties_create()”` on page 140
- `“am_properties_destroy()”` on page 140
- `“am_properties_get()”` on page 141
- `“am_properties_get_boolean()”` on page 142
- `“am_properties_get_boolean_with_default()”` on page 143
- `“am_properties_get_entries()”` on page 143
- `“am_properties_get_positive_number()”` on page 144
- `“am_properties_get_signed()”` on page 145
- `“am_properties_get_signed_with_default()”` on page 146
- `“am_properties_get_unsigned()”` on page 146
- `“am_properties_get_unsigned_with_default()”` on page 147
- `“am_properties_get_with_default()”` on page 148

- “am_properties_is_set()” on page 149
- “am_properties_iter_destroy()” on page 150
- “am_properties_iter_get_key()” on page 150
- “am_properties_iter_get_value()” on page 151
- “am_properties_load()” on page 151
- “am_properties_set()” on page 152
- “am_properties_store()” on page 153

am_properties_copy()

Duplicates a specified properties object.

Details

am_properties_copy() copies all the elements in the specified properties object, creates a duplicate instance, and assigns a pointer to it. The original object is not affected during the operation. The removal of any item in either structures does not affect the other.

Syntax

```
#include "am_properties.h"
AM_EXPORT am_status_t
am_properties_copy(am_properties_t source_properties,
                  am_properties_t *properties_ptr);
```

Parameters

This function takes the following parameters:

source_properties	The specified properties object.
properties_ptr	Pointer to the location of the copy of the specified properties object.

Returns

This function returns one of the following values of the am_status_t enumeration (defined in the <am_types.h> header file):

AM_SUCCESS	If the specified properties object was successfully copied.
AM_NO_MEMORY	If unable to allocate memory for the new properties object.
AM_INVALID_ARGUMENT	If the source_properties or properties_ptr argument is NULL.

Memory Concerns

After using the properties_ptr, call am_properties_destroy() to clean up the allocated memory.

am_properties_create()

Creates an empty properties object.

Syntax

```
#include "am_properties.h"
AM_EXPORT am_status_t
am_properties_create(am_properties_t *properties_ptr);
```

Parameters

This function takes the following parameters:

`properties_ptr` Pointer to the location of the new properties object.

Returns

This function returns one of the following values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file):

<code>AM_SUCCESS</code>	If a properties object was successfully created.
<code>AM_NO_MEMORY</code>	If unable to allocate memory for the properties object.
<code>AM_INVALID_ARGUMENT</code>	If the <code>properties_ptr</code> argument is <code>NULL</code> .

Memory Concerns

After using the `properties_ptr`, call `am_properties_destroy()` to clean up the allocated memory.

am_properties_destroy()

Destroys the specified properties object.

Details

Be sure not to pass the same instance of `am_properties_t` to `am_properties_destroy()` more than once. After calling this function, it is advised to initialize properties to `NULL`.

Syntax

```
#include "am_properties.h"
AM_EXPORT void
am_properties_destroy(am_properties_t properties);
```

Parameters

This function takes the following parameter:

properties Pointer to the specified properties object.

Returns

This function returns no values.

am_properties_get()

Retrieves the value associated with the specified key from the specified properties object.

Details

`am_properties_get()` checks for the presence of the specified key and returns its value, if present.

Syntax

```
#include "am_properties.h"
AM_EXPORT am_status_t
am_properties_get(am_properties_t properties,
                 const char *key,
                 const char **value_ptr);
```

Parameters

This function takes the following parameters:

properties Pointer to the specified properties object.

key Pointer to the specified key in the specified properties object.

value_ptr Pointer to a pointer to the location where the value associated with the specified key will be stored.

Returns

One of the following values as well as `value_ptr` containing an unparsed string with the address of the location of the value.

AM_SUCCESS If no error is detected.

AM_INVALID_ARGUMENT If the `properties`, `key`, or `value_ptr` argument is `NULL`.

AM_NOT_FOUND	If the specified key has no associated value and a default value is not provided.
AM_INVALID_VALUE	If the value associated with the specified key cannot be parsed as required by the particular accessor function.
AM_NO_MEMORY	If insufficient memory is available to look up the key.

Memory Concerns

Do not modify `value_ptr` or free the memory.

am_properties_get_boolean()

Retrieves boolean type values associated with the specified key from the specified properties object.

Syntax

```
#include "am_properties.h"
AM_EXPORT am_status_t
am_properties_get_boolean(am_properties_t properties,
                        const char *key,
                        int *value_ptr);
```

Parameters

This function takes the following parameters:

<code>properties</code>	The specified properties object.
<code>key</code>	Pointer to the specified key in the specified properties object.
<code>value_ptr</code>	Pointer to the location where the boolean associated with the specified key will be stored.

Returns

One of the following values stored in `value_ptr`:

- `!0` If the value associated with the specified key is true, on, or yes.
- `0` If the value associated with the specified key is false, off, or no.

If the associated value does not match any of these recognized boolean values, `AM_INVALID_VALUE` will be returned.

am_properties_get_boolean_with_default()

Retrieves boolean type values from the specified properties object.

Details

`am_properties_get_boolean_with_default()` will return a defined default value if no other value is present, contrary to the behavior of `am_properties_get_boolean()`.

Syntax

```
#include "am_properties.h"
am_properties_get_boolean_with_default(am_properties_t properties,
                                     const char *key,
                                     int default_value,
                                     int *value_ptr);
```

Parameters

This function takes the following parameters:

<code>properties</code>	The specified properties object.
<code>key</code>	Pointer to the specified key in the specified properties object.
<code>default_value</code>	Value to return if none is defined for the specified key.
<code>value_ptr</code>	Pointer to the location where the boolean associated with the specified key will be stored.

Returns

One of the following values stored in `value_ptr`:

`!0` If the value associated with the specified key is true, on, or yes.

`0` If the value associated with the specified key is false, off, or no.

If the associated value does not match any of the recognized boolean values, `AM_INVALID_VALUE` will be returned.

am_properties_get_entries()

Returns an iterator object that can be used to sequence through the entries in the specified properties object.

Syntax

```
#include "am_properties.h"
AM_EXPORT am_status_t
am_properties_get_entries(am_properties_t properties,
                        am_properties_iter_t *properties_iter_ptr);
```

Parameters

This function takes the following parameters:

<code>properties</code>	The specified properties object.
<code>properties_iter_ptr</code>	Pointer to the location of the new properties iterator object.

Returns

This function returns one of the following values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file):

<code>AM_SUCCESS</code>	If no error was detected.
<code>AM_NO_MEMORY</code>	If unable to allocate memory for the iterator object.
<code>AM_INVALID_ARGUMENT</code>	If <code>properties_iter_ptr</code> is NULL. If <code>properties_iter_ptr</code> is not NULL and an error is returned, the location that it refers to will be set to NULL.
<code>AM_NOT_FOUND</code>	If the specified properties object contains no entries.

`am_properties_get_positive_number()`

Retrieves a positive integer value associated with a specified key from the specified properties object.

Syntax

```
#include "am_properties.h"
AM_EXPORT am_status_t
am_properties_get_unsigned(am_properties_t properties,
                        const char *key,
                        unsigned long default_value,
                        unsigned long *value_ptr);
```

Parameters

This function takes the following parameters:

<code>properties</code>	Pointer to a properties object.
<code>key</code>	Pointer to the key in the properties object.
<code>default_value</code>	Value to return if none is defined for the specified key.
<code>value_ptr</code>	Pointer to the location where the returned integer will be stored.

Returns

This function returns the unsigned integer value associated with the specified key.

`am_properties_get_signed()`

Retrieves a signed integer value associated with the specified key from the specified properties object.

Syntax

```
#include "am_properties.h"
AM_EXPORT am_status_t
am_properties_get_signed(am_properties_t properties,
                        const char *key,
                        long *value_ptr);
```

Parameters

This function takes the following parameters:

<code>properties</code>	The specified properties object.
<code>key</code>	Pointer to the specified key in the specified properties object.
<code>value_ptr</code>	Pointer to the location where the signed integer associated with the specified key will be stored.

Returns

This function returns a signed integer value associated with the specified key. If the associated value cannot be parsed as an integer or cannot be represented in the range `LONG_MIN` to `LONG_MAX`, `AM_INVALID_VALUE` will be returned.

am_properties_get_signed_with_default()

Retrieves a signed integer value associated with a specified key from the specified properties object.

Details

`am_properties_get_signed_with_default()` will return a defined default value if no other value is present, contrary to the behavior of `am_properties_get_signed()`.

Syntax

```
#include "am_properties.h"
AM_EXPORT am_status_t
am_properties_get_signed_with_default(am_properties_t properties,
                                     const char *key,
                                     long default_value,
                                     long *value_ptr);
```

Parameters

This function takes the following parameters:

<code>properties</code>	The specified properties object.
<code>key</code>	Pointer to the specified key in the specified properties object.
<code>default_value</code>	Value to return if none is defined for the specified key.
<code>value_ptr</code>	Pointer to the location where the signed integer associated with the specified key will be stored.

Returns

This function returns a signed integer value associated with the specified key. If the associated value cannot be parsed as an integer or cannot be represented in the range `LONG_MIN` to `LONG_MAX`, `AM_INVALID_VALUE` will be returned.

am_properties_get_unsigned()

Retrieves an unsigned integer value associated with a specified key from the specified properties object.

Syntax

```
#include "am_properties.h"
AM_EXPORT am_status_t
am_properties_get_unsigned(am_properties_t properties,
                          const char *key,
                          unsigned long *value_ptr);
```

Parameters

This function takes the following parameters:

<code>properties</code>	Pointer to a properties object.
<code>key</code>	Pointer to the key in the properties object.
<code>value_ptr</code>	Pointer to the location where the integer associated with the specified key will be stored.

Returns

This function returns the unsigned integer value associated with the specified key.

`am_properties_get_unsigned_with_default()`

Retrieves an unsigned integer value associated with a specified key from the specified properties object.

Details

`am_properties_get_unsigned_with_default()` will return a defined default value if no other value is present, contrary to the behavior of `am_properties_get_unsigned()`.

Syntax

```
#include "am_properties.h"
AM_EXPORT am_status_t
am_properties_get_unsigned_with_default(am_properties_t properties,
                                       const char *key,
                                       unsigned long default_value,
                                       unsigned long *value_ptr);
```

Parameters

This function takes the following parameters:

<code>properties</code>	The specified properties object.
-------------------------	----------------------------------

<code>key</code>	Pointer to the specified key in the specified properties object.
<code>default_value</code>	Value to return if none is defined for the specified key.
<code>value_ptr</code>	Pointer to the location where the integer associated with the specified key will be stored.

Returns

This function returns the unsigned integer value associated with the specified key.

`am_properties_get_with_default()`

Retrieves the value (or the specified default) associated with the specified key from the specified properties object.

Details

`am_properties_get_with_default()` checks for the presence of the specified key and returns its value, if present. Contrary to `am_properties_get()`, if no value is present, it returns the specified default value.

Syntax

```
#include "am_properties.h"
AM_EXPORT am_status_t
am_properties_get_with_default(am_properties_t properties,
                             const char *key,
                             const char *default_value,
                             const char **value_ptr);
```

Parameters

This function takes the following parameters:

<code>properties</code>	The specified properties object.
<code>key</code>	Pointer to the specified key in the specified properties object.
<code>default_value</code>	Pointer to the value to be returned in case of no associated value.
<code>value_ptr</code>	Pointer to a pointer to the location where the returned value will be stored.

Returns

One of the following values as well as `value_ptr` containing an unparsed string with the address of the location of the value.

AM_SUCCESS	If no error is detected.
AM_INVALID_ARGUMENT	If the properties, key, or value_ptr argument is NULL.
AM_NOT_FOUND	If the specified key has no associated value and a default value is not provided.
AM_INVALID_VALUE	If the value associated with the specified key is cannot be parsed as required by the particular accessor function.
AM_NO_MEMORY	If insufficient memory is available to look up the key.

Memory Concerns

Do not modify value_ptr or free the memory.

am_properties_is_set()

Determines whether the specified key of the specified properties object contains a value.

Details

am_properties_is_set() does not return the value.

Syntax

```
#include "am_properties.h"
AM_EXPORT boolean_t
am_properties_is_set(am_properties_t properties,
                    const char *key);
```

Parameters

This function takes the following parameters:

properties	The specified properties object.
key	Pointer to the name of a key.

Returns

This function returns one of the following values of the boolean_t enumeration (defined in the standard <types.h> header file):

!0	If the property has a value.
0	Otherwise

am_properties_iter_destroy()

Destroys the specified iterator object.

Syntax

```
#include "am_properties.h"
AM_EXPORT void
am_properties_iter_destroy(am_properties_iter_t properties_iter);
```

Parameters

This function takes the following parameter:

`properties_iter` The specified iterator object. It may be NULL.

Returns

This function returns no value.

am_properties_iter_get_key()

Returns the key of the entry currently referenced by the specified iterator object.

Syntax

```
#include "am_properties.h"
AM_EXPORT const char *
am_properties_iter_get_key (am_properties_iter_t properties_iter);
```

Parameters

This function takes the following parameter:

`properties_iter` The specified iterator object.

Returns

This function returns one of the following values:

NULL If the specified iterator is NULL or does not reference a valid entry.

char * The key.

am_properties_iter_get_value()

Returns the value of the key currently referenced by the specified iterator object.

Syntax

```
#include "am_properties.h"
AM_EXPORT const char *
am_properties_iter_get_value (am_properties_iter_t properties_iter);
```

Parameters

This function takes the following parameters:

`properties_iter` The specified iterator object.

Returns

This function returns one of the following values:

`NULL` If the specified iterator is `NULL` or does not reference a valid entry.

`char *` Value associated with the key.

am_properties_load()

Loads information from the specified properties file into the specified properties object.

Details

The file is assumed to follow the syntax of a standard Java properties file.

Syntax

```
#include "am_properties.h"
AM_EXPORT am_status_t
am_properties_load(am_properties_t properties,
                  const char *file_name);
```

Parameters

This function takes the following parameters:

`properties` The specified properties object.

`file_name` Pointer to a properties file.

Returns

This function returns one of the following values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file):

<code>AM_SUCCESS</code>	If no error has occurred.
<code>AM_NOT_FOUND</code>	If the specified file does not exist.
<code>AM_NSPPR_ERROR</code>	If there is a problem accessing the file.
<code>AM_INVALID_ARGUMENT</code>	If properties or <code>file_name</code> is <code>NULL</code> or <code>file_name</code> points to an empty string.
<code>AM_NO_MEMORY</code>	If unable to allocate memory to store the property information.

`am_properties_set()`

Sets a value for the specified key in the specified properties object.

Details

The specified value will replace any existing value.

Syntax

```
#include "am_properties.h"
AM_EXPORT am_status_t
am_properties_set(am_properties_t properties,
                 const char *key,
                 const char *value);
```

Parameters

This function takes the following parameters:

<code>properties</code>	The specified properties object.
<code>key</code>	Pointer to the key being modified.
<code>value</code>	Pointer to the value to associate with the specified key.

Returns

This function returns one of the following values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file):

<code>AM_SUCCESS</code>	If no error is detected.
-------------------------	--------------------------

AM_INVALID_ARGUMENT	If the properties, key, or value argument is NULL.
AM_NO_MEMORY	If unable to allocate memory to store the new key/value.

am_properties_store()

Retrieves key/value information from the specified properties object and stores it in the specified file.

Syntax

```
#include "am_properties.h"
AM_EXPORT am_status_t
am_properties_store(am_properties_t properties,
                  const char *file_name);
```

Parameters

This function takes the following parameters:

properties	The specified properties object.
file_name	Pointer to the file in which the property information will be stored.

Returns

This function returns one of the following values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file):

AM_SUCCESS	If no error is detected.
AM_NSPR_ERROR	If there is a problem writing to the file.
AM_INVALID_ARGUMENT	If properties or file_name is NULL or file_name points to an empty string.

CHAPTER 8

Web Agent Data Types and Functions

Sun OpenSSO Enterprise contains public data types and functions intended for use by Sun web agents. They can also be used to develop proprietary web agents. Reference summaries include a short description, syntax, parameters and returns. Prototypes for the types and functions are contained in the `<am_web.h>` header file. This chapter contains the following sections:

- “Web Agent API for C” on page 155
- “Web Agent Data Types” on page 156
- “Web Agent Function Pointers” on page 163
- “Web Agent Functions” on page 173

Web Agent API for C

The web agent application programming interface (API) for C are used by web agents to interact with OpenSSO Enterprise services such as the Authentication Service, the Session Service, the Policy Service, and the Logging Service. In order to use the data types and functions described herein, you should be familiar with web agents in general and how they work. The following books provide information for this purpose:

- *Sun OpenSSO Enterprise 8.0 Technical Overview*
- *Sun OpenSSO Enterprise Policy Agent 3.0 User's Guide for Web Agents*
- *Sun OpenSSO Enterprise Policy Agent 3.0 Guide for Sun Java System Web Server 7.0*
- *Sun Java System Access Manager Policy Agent 2.2 User's Guide*
- *Sun Java System Access Manager Policy Agent 2.2 Guide for Sun Java System Web Server 6.1*

Web Agent Data Types

The web agent data types defined in `<am_web.h>` are:

- [“am_web_add_header_in_response_t” on page 156](#)
- [“am_web_free_post_data_t” on page 156](#)
- [“am_web_get_post_data_t” on page 157](#)
- [“am_web_postcache_data_t” on page 158](#)
- [“am_web_render_result_t” on page 158](#)
- [“am_web_request_func_t” on page 159](#)
- [“am_web_request_params_t” on page 159](#)
- [“am_web_set_header_in_request_t” on page 161](#)
- [“am_web_set_method_t” on page 161](#)
- [“am_web_set_user_t” on page 162](#)
- [“post_urls_t” on page 162](#)

am_web_add_header_in_response_t

Defines a data type for the `am_web_add_header_in_response_func_t` function pointer.

Details

See also [“am_web_add_header_in_response_func_t” on page 163](#).

Syntax

```
#include "am_web.h"
typedef struct {
    am_web_add_header_in_response_func_t func;
    void **args;
} am_web_add_header_in_response_t;
```

Members

The structure has the following components:

- `func` Pointer to `am_web_add_header_in_response_func_t` function.
- `args` Pointer to a pointer to agent defined parameters.

am_web_free_post_data_t

Defines a data type for the `am_web_free_post_data_t` function pointer.

Details

See also [“am_web_free_post_data_func_t” on page 164](#).

Syntax

```
#include "am_web.h"
typedef struct {
    am_web_free_post_data_func_t func;
    void **args;
} am_web_free_post_data_t;
```

Members

am_web_free_post_data_t has the following components:

func Pointer to am_web_free_post_data_func_t function.

args Pointer to a pointer to agent defined parameters.

am_web_get_post_data_t

Defines a data type for the am_web_get_post_data_t function pointer.

Details

See also [“am_web_get_post_data_func_t” on page 166](#).

Syntax

```
#include "am_web.h"
typedef struct {
    am_web_get_post_data_func_t func;
    void **args;
} am_web_get_post_data_t;
```

Members

am_web_get_post_data_t has the following components:

func Pointer to am_web_get_post_data_func_t function.

args Pointer to a pointer to agent defined parameters.

am_web_postcache_data_t

Data type for temporarily storing POST data sent by the web agent to the OpenSSO Enterprise Session Service.

Details

Policy agents use the POST method to communicate with the Session Service. For information, see [“Session Validation” in *Sun OpenSSO Enterprise 8.0 Technical Overview*](#).

Syntax

```
#include "am_web.h"
typedef struct am_web_postcache_data {
    char *value;
    char *url;
} am_web_postcache_data_t;
```

Members

am_web_postcache_data_t has the following components:

value Pointer to the string value of the POST data.
url Pointer to the destination URL of the POST.

am_web_render_result_t

Defines a data type for the am_web_render_result_func_t function pointer.

Details

See also [“am_web_render_result_func_t” on page 166](#).

Syntax

```
#include "am_web.h"
typedef struct {
    am_web_render_result_func_t func;
    void **args;
} am_web_render_result_t;
```

Members

am_web_render_result_t has the following components:

func Pointer to the `am_web_render_result_func_t` function.
args Pointer to a pointer to agent defined parameters.

`am_web_request_func_t`

Defines an all-inclusive data type for the function pointers used by the web agent.

Syntax

```
#include "am_web.h"
typedef struct {
    am_web_get_post_data_t get_post_data;
    am_web_free_post_data_t free_post_data;
    am_web_set_user_t set_user;
    am_web_set_method_t set_method;
    am_web_set_header_in_request_t set_header_in_request;
    am_web_add_header_in_response_t add_header_in_response;
    am_web_render_result_t render_result;
} am_web_request_func_t;
```

Members

`am_web_request_func_t` has the following components:

<code>get_post_data</code>	See “ am_web_get_post_data_t ” on page 157.
<code>free_post_data</code>	See “ am_web_free_post_data_t ” on page 156.
<code>set_user</code>	See “ am_web_set_user_t ” on page 162.
<code>set_method</code>	See “ am_web_set_method_t ” on page 161.
<code>set_header_in_request</code>	See “ am_web_set_header_in_request_t ” on page 161.
<code>add_header_in_response</code>	See “ am_web_add_header_in_response_t ” on page 156.
<code>render_result</code>	See “ am_web_render_result_t ” on page 158.

`am_web_request_params_t`

Represents the parameters of an HTTP request passed to a web server from a client browser.

Details

This structure represents the parameters of the HTTP request and includes `am_web_req_method_t` which defines the action to be performed on the resource (GET, POST, DELETE, etc.).

Syntax

```
#include "am_web.h"
typedef struct {
    char *url;                /* The full request URL */
    char *query;              /* query string if any */
    am_web_req_method_t method; /* request method */
    char *path_info;          /* path info if any */
    char *client_ip;          /* client IP if any */
    char *cookie_header_val;  /* the cookie header value if any */
    void *reserved;           /* reserved - do not set this */
} am_web_request_params_t;
```

Members

`am_web_request_params_t` has the following components:

<code>url</code>	Pointer to the URL of the resource.
<code>query</code>	The query string appended to the request URL, if any. For example, if the URL is <code>http://www.example.com?a=b&c=d</code> , the value of this parameter would be <code>a=b&c=d</code> .
<code>method</code>	One of the following values of the <code>am_web_req_method_t</code> enumeration as defined:

```
#include "am_web.h"
typedef enum {
    AM_WEB_REQUEST_UNKNOWN,
    AM_WEB_REQUEST_GET,
    AM_WEB_REQUEST_POST,
    AM_WEB_REQUEST_HEAD,
    AM_WEB_REQUEST_PUT,
    AM_WEB_REQUEST_DELETE,
    AM_WEB_REQUEST_TRACE,
    AM_WEB_REQUEST_OPTIONS
} am_web_req_method_t;
```

More information on these request methods can be found in <http://www.faqs.org/rfcs/rfc2068.html>.

<code>path_info</code>	The path information in the request URL, if any.
------------------------	--

<code>client_ip</code>	Pointer to the IP address from which the request was sent.
<code>cookie_header_val</code>	Pointer to the cookie header.
<code>reserved</code>	Do not set this.

`am_web_set_header_in_request_t`

Defines a data type for the `am_web_render_result_func_t` function pointer.

Details

See also [“`am_web_render_result_func_t`” on page 166](#).

Syntax

```
#include "am_web.h"
typedef struct {
    am_web_set_header_in_request_func_t func;
    void **args;
} am_web_set_header_in_request_t;
```

Members

`am_web_set_header_in_request_t` has the following components:

<code>func</code>	Pointer to <code>am_web_set_header_in_request_func_t</code> function.
<code>args</code>	Pointer to a pointer to agent defined parameters.

`am_web_set_method_t`

Defines a data type for the `am_web_set_method_func_t` function pointer.

Details

See also [“`am_web_set_method_func_t`” on page 171](#).

Syntax

```
#include "am_web.h"
typedef struct {
    am_web_set_method_func_t func;
    void **args;
} am_web_set_method_t;
```

Members

`am_web_set_method_t` has the following components:

`func` Pointer to the `am_web_set_method_func_t` function.

`args` Pointer to a pointer to agent defined parameters.

`am_web_set_user_t`

Defines a data type for the `am_web_set_user_func_t` function pointer.

Details

See also [“`am_web_set_user_func_t`” on page 172](#).

Syntax

```
#include "am_web.h"
typedef struct {
    am_web_set_user_func_t func;
    void **args;
} am_web_set_user_t;
```

Members

`am_web_set_user_t` has the following components:

`func` Pointer to `am_web_set_user_func_t` function.

`args` Pointer to a pointer to agent defined parameters.

`post_urls_t`

A session information object defining the URLs used by the web agent to communicate with OpenSSO Enterprise.

Syntax

```
#include "am_web.h"
typedef struct post_urls {
    char *dummy_url;
    char *action_url;
    char *post_time_key;
} post_urls_t;
```

Members

`post_urls_t` has the following components:

`dummy_url` Pointer to a dummy URL to redirect for POST data preservation.

Note – *POST data preservation* is supported only on Policy Agent 2.2 for Sun Java System Web Server 6.1. The feature allows for submitted POST data to be preserved. See [“Preserving POST Data on Sun Java System Web Server 7.0 Only” in Sun Java System Access Manager Policy Agent 2.2 Guide for Sun Java System Web Server 6.1](#) for more information.

`action_url` Pointer to destination URL for a POST request.

`post_time_key` Pointer to a unique key used to tag a POST data entry.

Web Agent Function Pointers

The web agent function pointers must be written before calling the `am_web_process_request()` function to process a request. The function pointers defined in `<am_web.h>` are:

- [“`am_web_add_header_in_response_func_t`” on page 163](#)
- [“`am_web_free_post_data_func_t`” on page 164](#)
- [“`am_web_get_cookie_sync_func_t`” on page 165](#)
- [“`am_web_get_post_data_func_t`” on page 166](#)
- [“`am_web_render_result_func_t`” on page 166](#)
- [“`am_web_result_set_header_func_t`” on page 167](#)
- [“`am_web_result_set_header_attr_in_request_func_t`” on page 168](#)
- [“`am_web_result_set_header_attr_in_response_func_t`” on page 169](#)
- [“`am_web_set_header_in_request_func_t`” on page 170](#)
- [“`am_web_set_method_func_t`” on page 171](#)
- [“`am_web_set_user_func_t`” on page 172](#)

`am_web_add_header_in_response_func_t`

Adds (or sets) an HTTP header in a response.

Details

If a header of the same name already exists, it should be replaced with this header.

Syntax

```
#include "am_web.h"
typedef am_status_t (*am_web_add_header_in_response_func_t)
                    (void **args,
                     const char *name,
                     const char *val);
```

Parameters

This function takes the following parameter:

args Pointer to a pointer to agent defined parameters.

name Pointer to the name of the header.

val Pointer to the value of the header.

Returns

This function returns one of the following values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file):

<code>AM_SUCCESS</code>	If the header was successfully added.
Appropriate <code>am_status_t</code> code	Otherwise.

am_web_free_post_data_func_t

Frees the data retrieved by `am_web_get_post_data_func_t`.

Details

The POST data can be `NULL` if it is not needed.

Syntax

```
#include "am_web.h"
typedef am_status_t (*am_web_free_post_data_func_t)
                    (void **args,
                     char *data);
```

Parameters

This function takes the following parameter:

args Pointer to a pointer to agent defined parameters.

`data` Pointer to the data.

Returns

This function returns one of the following values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file):

`AM_SUCCESS` If the data was successfully freed.

`Warning` If not successfully freed, the status will be logged as a warning but ignored.

`am_web_get_cookie_sync_func_t`

Synchronizes two cookies.

Details

Currently, this is a dummy function. Do not use.

Syntax

```
#include "am_web.h"
typedef am_status_t (*am_web_get_cookie_sync_func_t)(
    const char *cookieName,
    char **dproCookie,
    void **args);
```

Parameters

This function takes the following parameter:

`cookieName` Pointer to the cookie with which the OpenSSO Enterprise cookie will be synchronized.

`dproCookie` Pointer to a pointer to the OpenSSO Enterprise cookie.

`args` Pointer to a pointer to agent defined parameters.

Returns

This function returns one of the following values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file):

`AM_SUCCESS` If the data was successfully freed.

`Warning` If not successfully freed, the status will be logged as a warning but ignored.

am_web_get_post_data_func_t

Retrieves post data.

Details

The returned POST data must be NULL terminated and will be freed by calling `am_web_free_post_data_func_t`.

Syntax

```
#include "am_web.h"
typedef am_status_t (*am_web_get_post_data_func_t)
                    (void **args,
                     char **data);
```

Parameters

This function takes the following parameter:

`args` Pointer to a pointer to agent defined parameters.

`data` Pointer to a pointer to the data.

Returns

This function returns one of the following values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file):

`AM_SUCCESS` If the data was successfully retrieved.

HTTP internal error Otherwise

am_web_render_result_func_t

Renders an HTML page based on the result of a web agent's enforcement.

Syntax

```
#include "am_web.h"
typedef am_status_t (*am_web_render_result_func_t)
                    (void **args,
                     am_web_result_t http_result,
                     char *data);
```

Parameters

This function takes the following parameter:

<code>args</code>	Pointer to a pointer to agent defined parameters.
<code>http_result</code>	One of the following values of the <code>am_web_result_t</code> enumeration as defined:

```
#include "am_web.h"
typedef enum {
    AM_WEB_RESULT_OK,           /* access check was OK */
    AM_WEB_RESULT_OK_DONE,     /* OK and handled (for ex. notification) */
    AM_WEB_RESULT_FORBIDDEN,   /* access forbidden */
    AM_WEB_RESULT_REDIRECT,    /* redirected */
    AM_WEB_RESULT_ERROR        /* internal error */
} am_web_result_t;
```

For `AM_WEB_RESULT_OK_DONE`, the web agent should return an HTTP status code 200 OK and the body of the HTTP response should be set to the string in the data parameter. For `AM_WEB_RESULT_REDIRECT`, the web agent should return an HTTP status code 302 and the Location header should be set to the redirect URL in the data argument. More information on these request methods can be found in <http://www.faqs.org/rfcs/rfc2068.html>.

<code>data</code>	Pointer to a string defining user data, a URL, or other data.
-------------------	---

Returns

This function returns one of the following values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file):

<code>AM_SUCCESS</code>	If page was successfully rendered.
Warning	If not successfully freed, the status will be logged as a warning but ignored.

`am_web_result_set_header_func_t`

Sets LDAP attributes in an HTTP header.

Details

This function will be called when `com.sun.am.policy.agents.config.profile.attribute.fetch.mode` in `AMAgent.properties` is set to `HTTP_HEADER`. This property specifies if additional user profile attributes should be introduced into the request. Possible values are:

- NONE

- HTTP_HEADER
- HTTP_COOKIE

Syntax

```
#include "am_web.h"
typedef am_status_t (*am_web_result_set_header_func_t)(
    const char *key,
    const char *attrValues,
    void **args);
```

Parameters

This function takes the following parameter:

key	Pointer to the key to which the value will be set.
attrValues	Pointer to a string representing the values to be set.
args	Pointer to a pointer to agent defined parameters.

Returns

This function returns one of the values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file) including:

`AM_SUCCESS` If the header was successfully set.

`am_web_result_set_header_attr_in_request_func_t`

Sets LDAP attributes defined in the request's HTTP cookie header.

Details

This function will be called when

`com.sun.am.policy.agents.config.profile.attribute.fetch.mode` in `AMAgent.properties` is set to `HTTP_COOKIE`. This property specifies if additional user profile attributes should be introduced into the request. Possible values are:

- NONE
- HTTP_HEADER
- HTTP_COOKIE

Syntax

```
#include "am_web.h"
typedef am_status_t (*am_web_result_set_header_attr_in_request_func_t)(
    const char *cookieValues,
    void **args);
```

Parameters

This function takes the following parameter:

cookieValues	Pointer to string representing the values in the cookie.
args	Pointer to a pointer to agent defined parameters.

Returns

This function returns one of the values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file) including:

AM_SUCCESS	If the header was successfully set.
------------	-------------------------------------

am_web_result_set_header_attr_in_response_func_t

Sets LDAP attributes defined in the response's HTTP cookie header.

Details

This function will be called when `com.sun.am.policy.agents.config.profile.attribute.fetch.mode` in `AMAgent.properties` is set to `HTTP_COOKIE`. This property specifies if additional user profile attributes should be introduced into the request. Possible values are:

- NONE
- HTTP_HEADER
- HTTP_COOKIE

Syntax

```
#include "am_web.h"
typedef am_status_t (*am_web_result_set_header_attr_in_response_func_t)(
    const char *cookieValues,
    void **args);
```

Parameters

This function takes the following parameter:

cookieValues	Pointer to string representing the values in the cookie.
args	Pointer to a pointer to agent defined parameters.

Returns

This function returns one of the values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file) including:

AM_SUCCESS	If the header was successfully set.
------------	-------------------------------------

am_web_set_header_in_request_func_t

Sets an HTTP header in a request.

Details

If a header of the same name already exists it should be replaced with this header.

Syntax

```
#include "am_web.h"
typedef am_status_t (*am_web_set_header_in_request_func_t)(
    void **args,
    const char *name,
    const char *val);
```

Parameters

This function takes the following parameter:

args	Pointer to a pointer to agent defined parameters.
name	Pointer to the name of the header.
val	Pointer to the value of the header.

Returns

This function returns one of the following values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file):

AM_SUCCESS	If header was successfully added.
------------	-----------------------------------

Warning If not successfully freed, the status will be logged as a warning but ignored.

am_web_set_method_func_t

Sets the request method to be used by a web agent during cross domain single sign-on (CDSSO).

Details

In cases of CDSSO actions between OpenSSO Enterprise and web agents, the POST request method is used by the web agent. `am_web_set_method_func_t` is required to change the request method to POST, if necessary, from the method defined in the original HTTP request. See “Cross-Domain Single Sign-On Session” in *Sun OpenSSO Enterprise 8.0 Technical Overview* for additional information.

Syntax

```
#include "am_web.h"
typedef am_status_t (*am_web_set_method_func_t)(
    void **args,
    am_web_req_method_t method);
```

Parameters

This function takes the following parameter:

args Pointer to a pointer to agent defined parameters.

method One of the following values of the `am_web_req_method_t` enumeration as defined:

```
#include "am_web.h"
typedef enum {
    AM_WEB_REQUEST_UNKNOWN,
    AM_WEB_REQUEST_GET,
    AM_WEB_REQUEST_POST,
    AM_WEB_REQUEST_HEAD,
    AM_WEB_REQUEST_PUT,
    AM_WEB_REQUEST_DELETE,
    AM_WEB_REQUEST_TRACE,
    AM_WEB_REQUEST_OPTIONS
} am_web_req_method_t;
```

More information on these request methods can be found in <http://www.faqs.org/rfcs/rfc2068.html>.

Returns

This function returns one of the following values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file):

<code>AM_SUCCESS</code>	If the method was successfully set.
HTTP forbidden result	Otherwise.

`am_web_set_user_func_t`

Sets the user.

Details

The implementation code sets the user.

Syntax

```
#include "am_web.h"
typedef am_status_t (*am_web_set_user_func_t)(
    void **args,
    const char *user);
```

Parameters

This function takes the following parameter:

<code>args</code>	Pointer to a pointer to agent defined parameters.
<code>user</code>	Pointer to the user login.

Returns

This function returns one of the following values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file):

<code>AM_SUCCESS</code>	If user was successfully set.
HTTP forbidden result	Otherwise.

Web Agent Functions

The web agent functions defined in `<am_web.h>` are:

- `“am_agent_init()”` on page 174
- `“am_web_build_advice_response()”` on page 175
- `“am_web_check_cookie_in_post()”` on page 176
- `“am_web_check_cookie_in_query()”` on page 177
- `“am_web_clean_post_urls()”` on page 178
- `“am_web_cleanup()”` on page 179
- `“am_web_clear_attributes_map()”` on page 179
- `“am_web_create_post_page()”` on page 180
- `“am_web_create_post_preserve_urls()”` on page 180
- `“am_web_delete_agent_configuration()”` on page 181
- `“am_web_do_cookie_domain_set()”` on page 181
- `“am_web_do_cookies_reset()”` on page 182
- `“am_web_free_memory()”` on page 183
- `“am_web_get_agent_server_host()”` on page 184
- `“am_web_get_agent_configuration()”` on page 184
- `“am_web_get_agent_server_port()”` on page 185
- `“am_web_get_authType()”` on page 185
- `“am_web_get_cookie_name()”` on page 186
- `“am_web_get_notification_url()”` on page 186
- `“am_web_get_parameter_value()”` on page 187
- `“am_web_get_request_url()”` on page 188
- `“am_web_get_token_from_assertion()”` on page 189
- `“am_web_get_url_to_redirect()”` on page 190
- `“am_web_get_token_from_assertion()”` on page 189
- `“am_web_handle_notification()”` on page 192
- `“am_web_http_decode()”` on page 192
- `“am_web_init() for Agents 3.0”` on page 193
- `“am_web_is_access_allowed()”` on page 194
- `“am_web_is_cdsso_enabled()”` on page 195
- `“am_web_is_cookie_present()”` on page 196
- `“am_web_is_debug_on()”` on page 197
- `“am_web_is_in_not_enforced_ip_list()”` on page 197
- `“am_web_is_in_not_enforced_list()”` on page 198
- `“am_web_is_logout_url()”` on page 199
- `“am_web_is_max_debug_on()”` on page 199
- `“am_web_is_notification()”` on page 200
- `“am_web_is_owa_enabled()”` on page 201
- `“am_web_is_owa_enabled_change_protocol()”` on page 201
- `“am_web_is_owa_enabled_session_timeout_url()”` on page 202
- `“am_web_is_postpreserve_enabled()”` on page 203

- “am_web_is_proxy_override_host_port_set()” on page 203
- “am_web_is_valid_fqdn_url()” on page 204
- “am_web_log_always()” on page 204
- “am_web_log_auth()” on page 205
- “am_web_log_debug()” on page 206
- “am_web_log_error()” on page 206
- “am_web_log_info()” on page 207
- “am_web_log_max_debug()” on page 207
- “am_web_log_warning()” on page 207
- “am_web_logout_cookies_reset()” on page 208
- “am_web_method_num_to_str()” on page 209
- “am_web_method_str_to_num()” on page 210
- “am_web_postcache_data_cleanup()” on page 210
- “am_web_postcache_insert()” on page 211
- “am_web_postcache_lookup()” on page 212
- “am_web_postcache_remove()” on page 212
- “am_web_process_request()” on page 213
- “am_web_remove_authnrequest()” on page 214
- “am_web_remove_parameter_from_query()” on page 215
- “am_web_result_attr_map_set()” on page 215
- “am_web_result_num_to_str()” on page 217
- “am_web_set_cookie()” on page 217

am_agent_init()

Initializes an agent by creating the agent profile object and performing agent authentication to receive the initial agent configuration data from either OpenSSO Enterprise or the local configuration file.

Syntax

```
#include "am_web.h"
AM_WEB_EXPORT am_status_t
am_agent_init(boolean_t *pAgentAuthenticated);
```

Parameters

This function takes the following parameter:

`pAgentAuthenticated` is the agent authenticated.

Returns

This function returns one of the following values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file):

`AM_SUCCESS` If the query parameter was found in the URL.
`AM_*` If any other error occurred.

`am_web_build_advice_response()`

Builds an advice response.

Syntax

```
#include "am_web.h"
AM_WEB_EXPORT am_status_t
am_web_build_advice_response(const am_policy_result_t *policy_result,
                             const char *redirect_url,
                             char **advice_response);
```

Parameters

This function takes the following parameter:

`policy_result` Pointer to an `am_policy_result_t` data type.

Note – See “[am_policy_result_t](#)” on page 51 for information.

`redirect_url` Pointer to a redirect URL.

`advice_response` Pointer to a pointer to the location of the advice response.

Returns

This function returns one of the following values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file):

`AM_SUCCESS` If the query parameter was found in the URL.
`AM_*` If any other error occurred.

am_web_check_cookie_in_post()

Retrieves a user's SSOToken.

Details

In cases of cross domain single sign-on, OpenSSO Enterprise sends out a user's SSOToken using POST. This method uses POST to retrieve the SSOToken and set it in the foreign domain.

Syntax

```
#include "am_web.h"
M_WEB_EXPORT am_status_t
am_web_check_cookie_in_post(void ** args,
                           char ** dpro_cookie,
                           char ** request_url,
                           char **orig_req,
                           char *method,
                           char *response,
                           boolean_t responseIsCookie,
                           am_status_t (*set_cookie)(const char *, void **),
                           void (*set_method)(void **, char *),
                           void* agent_config
);
```

Parameters

This function takes the following parameter:

args	Pointer to a pointer to agent defined parameters.				
dpro_cookie	Pointer to a pointer to the OpenSSO Enterprise cookie.				
request_url	Pointer to a pointer to the CDSSO URL.				
orig_req	Pointer to a pointer to the original request method.				
method	Pointer to the changed method name.				
response	Pointer to the response which will hold the POST data.				
responseIsCookie	Returns one of the following values of the <code>boolean_t</code> enumeration (defined in the <code><am_types.h></code> header file): <table data-bbox="535 1388 1163 1475"> <tr> <td>B_TRUE</td><td>If using Liberty Alliance Project specifications.</td></tr> <tr> <td>B_FALSE</td><td>If OpenSSO Enterprise POST data.</td></tr> </table>	B_TRUE	If using Liberty Alliance Project specifications.	B_FALSE	If OpenSSO Enterprise POST data.
B_TRUE	If using Liberty Alliance Project specifications.				
B_FALSE	If OpenSSO Enterprise POST data.				
set_cookie	Function pointer used to set the cookie in the foreign domain.				

<code>set_method</code>	Function pointer used to reset the original method in the request.
<code>agent_config</code>	An agent configuration instance returned by <code>am_web_get_agent_configuration()</code> . This parameter may not be NULL.

Returns

This function returns one of the following values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file):

<code>AM_SUCCESS</code>	If the query parameter was found in the URL.
<code>AM_*</code>	If any other error occurred.

am_web_check_cookie_in_query()

Retrieves the cookie from a query string.

Details

In older versions of this product, when performing CDSSO, the cookie was part of the query string.

Syntax

```
AM_WEB_EXPORT am_status_t
am_web_check_cookie_in_query(void **args,
                             char **dpro_cookie,
                             const char *query,
                             char **request_url,
                             char ** orig_req,
                             char *method,
                             am_status_t (*set_cookie)(const char *, void **),
                             void (*set_method)(void **, char *),
                             void* agent_config
);
```

Parameters

This function takes the following parameter:

<code>args</code>	Pointer to a pointer to agent defined parameters.
<code>dpro_cookie</code>	Pointer to a pointer to the OpenSSO Enterprise cookie.
<code>query</code>	Pointer to the query.

<code>request_url</code>	Pointer to a pointer to the CDSSO URL.
<code>orig_req</code>	Pointer to a pointer to the original request method.
<code>method</code>	Pointer to a pointer to the changed method name.
<code>set_cookie</code>	Function pointer used to set the cookie in the foreign domain.
<code>set_method</code>	Function pointer used to reset the original method in the request.
<code>agent_config</code>	An agent configuration instance returned by <code>am_web_get_agent_configuration()</code> . This parameter may not be NULL.

Returns

This function returns one of the following values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file):

<code>AM_SUCCESS</code>	If the query parameter was found in the URL.
<code>AM_*</code>	If any other error occurred.

`am_web_clean_post_urls()`

Cleans up a `post_urls_t` data type.

Details

See “[post_urls_t](#)” on [page 162](#) for more information.

Syntax

```
#include "am_web.h"
AM_WEB_EXPORT void
am_web_clean_post_urls(post_urls_t *posturl_struct);
```

Parameters

This function takes the following parameter:

<code>posturl_struct</code>	Pointer to <code>post_urls_t</code> data type.
-----------------------------	--

Returns

This function returns no values.

am_web_cleanup()

Cleans up any memory called by the `am_web_*` functions.

Details

This should be called before a web agent exits.

Syntax

```
#include "am_web.h"
AM_WEB_EXPORT am_status_t
am_web_cleanup();
```

Parameters

This function does not take any parameters.

Returns

This function returns one of the following values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file):

<code>AM_SUCCESS</code>	If the cleanup was successful.
<code>AM_*</code>	If any error occurs, the type of error indicated by the status value.

am_web_clear_attributes_map()

Clears the profile, session and response attributes maps.

Syntax

```
#include "am_web.h"
AM_WEB_EXPORT void am_web_clear_attributes_map(am_policy_result_t *result);
```

Parameters

This function takes the following parameter:

<code>result</code>	Pointer to the <code>am_policy_result_t</code>
---------------------	--

Returns

This function returns no values.

am_web_create_post_page()

Creates an HTML form that submits the POST data with invisible name/value pairs.

Syntax

```
#include "am_web.h"
AM_WEB_EXPORT char *
am_web_create_post_page(const char *key,
                        const char *postdata,
                        const char *actionurl,
                        void* agent_config);
```

Parameters

This function takes the following parameters:

key	Pointer to the unique key identifying a POST data entry. It is used to remove post data once the page is re-posted.
postdata	Pointer to a browser encoded string representing the POST data entry.
actionurl	Pointer to the POST destination URL.
agent_config	An agent configuration instance returned by <code>am_web_get_agent_configuration()</code> . This parameter may not be NULL.

Returns

This function returns `char *` as the POST form to be submitted.

am_web_create_post_preserve_urls()

Constructs a `post_urls_t` data type during preservation of POST data.

Details

A `post_urls_t` data type contains a dummy POST URL, an action URL and a unique key. The dummy URL is filtered by the Server Application Function (SAF) to identify POST preservation redirects from general redirects. All three of these variables are required for POST preservation.

Syntax

```
#include "am_web.h"
AM_WEB_EXPORT post_urls_t *
am_web_create_post_preserve_urls(const char *request_url,
```

```
void* agent_config);
```

Parameters

This function takes the following parameter:

<code>request_url</code>	Pointer to the request URL for POST in the HTTP request.
<code>agent_config</code>	An agent configuration instance returned by <code>am_web_get_agent_configuration()</code> . This parameter may not be NULL.

Returns

This function returns a `post_urls_t` data type. See [“post_urls_t” on page 162](#) for information.

`am_web_delete_agent_configuration()`

Deletes the referenced object from the agent configuration data stored in the agent configuration cache.

Syntax

```
#include "am_web.h"
AM_WEB_EXPORT void
am_web_delete_agent_configuration(void*);
```

Parameters

This function takes no parameters.

Returns

This function deletes the latest configuration data, referenced by an object for a particular agent, from the agent configuration cache.

`am_web_do_cookie_domain_set()`

Sets the OpenSSO Enterprise cookie (called `iPlanetDirectoryPro`) for each domain configured in the `com.sun.am.policy.agents.config.cookie.domain.list` property in `AMAgent.properties`.

Details

`am_web_do_cookie_domain_set()` builds the set-cookie header for each domain, and calls the callback function declared in `setFunc` to set the cookie. In CDSSO, the callback function is called by `am_web_check_cookie_in_query()` and `am_web_check_cookie_in_post()` to set the cookie in the response.

Syntax

```
#include "am_web.h"
AM_WEB_EXPORT am_status_t
am_web_do_cookie_domain_set(am_status_t (*setFunc)(
    const char *,
    void **),
    void **args,
    const char *cookie
    void* agent_config);
```

Parameters

This function takes the following parameters:

<code>setFunc</code>	Function pointer with which the user can define their own function for setting the cookie in the foreign domain. The implementation defines the parameters.
<code>args</code>	Pointer to a pointer to agent defined parameters.
<code>cookie</code>	Pointer to the cookie.
<code>agent_config</code>	An agent configuration instance returned by <code>am_web_get_agent_configuration()</code> . This parameter may not be NULL.

Returns

This function returns a value of the `am_status_t` enumeration (defined in the `<am_types.h>` header file).

`am_web_do_cookies_reset()`

Resets the cookies in a response before redirecting it for authentication to the OpenSSO Enterprise login page.

Details

This function resets the cookies specified in `AMAgent.properties` and invokes the set action that the agent passes in for each of them. It is enabled by setting the following properties:

- `com.sun.am.policy.agents.config.cookie.reset.enable`: This property must be set to `true` if the web agent needs to reset cookies in the response before redirecting them to OpenSSO Enterprise for authentication. By default it is set to `false`.
- `com.sun.am.policy.agents.config.cookie.reset.list`: This property (used only if `com.sun.am.policy.agents.config.cookie.reset.enable` is enabled) contains a comma-separated list of cookies that need to be included in the response redirected to OpenSSO Enterprise.

See the `AMAgent.properties` file for more information.

Syntax

```
#include "am_web.h"
AM_WEB_EXPORT am_status_t
am_web_do_cookies_reset(am_status_t (*setFunc)(
    const char *,
    void **),
    void **args,
    void* agent_config);
```

Parameters

This function takes the following parameters:

<code>setFunc</code>	Function pointer with which the user can define their own function for setting the cookie in the foreign domain. The implementation defines the parameters.
<code>args</code>	Pointer to a pointer to agent defined parameters.
<code>agent_config</code>	An agent configuration instance returned by <code>am_web_get_agent_configuration()</code> . This parameter may not be <code>NULL</code> .

Returns

This function returns a value of the `am_status_t` enumeration (defined in the `<am_types.h>` header file).

`am_web_free_memory()`

Frees memory previously allocated by a `am_web_*` routine.

Syntax

```
#include "am_web.h"
AM_WEB_EXPORT void
am_web_free_memory(void *memory);
```

Parameters

This function takes the following parameter:

`memory` Pointer to the memory.

Returns

This function returns no value.

`am_web_get_agent_server_host()`

Retrieves the name of the server host for the agent.

Syntax

```
#include "am_web.h"
AM_WEB_EXPORT const char *
am_web_get_agent_server_host(void* agent_config);
```

Parameters

`agent_config` An agent configuration instance returned by
 `am_web_get_agent_configuration()`. This parameter may not be NULL.

Returns

This function returns then name of the server host.

`am_web_get_agent_configuration()`

Retrieves the latest configuration data from the agent configuration cache. The returned instance gets used to serve requests.

Syntax

```
#include "am_web.h"
AM_WEB_EXPORT void*
am_web_get_agent_configuration();
```

Parameters

This function takes no parameters.

Returns

This function returns the latest configuration data, for a particular agent, from the agent configuration cache.

am_web_get_agent_server_port()

Retrieves the port used by the agent on the server host.

Syntax

```
#include "am_web.h"
AM_WEB_EXPORT int
am_web_get_agent_server_port(void* agent_config);
```

Parameters

agent_config An agent configuration instance returned by
 am_web_get_agent_configuration(). This parameter may not be NULL.

Returns

This function returns a port number.

am_web_get_authType()

Determines if the auth-type value DSAME should be replaced by Basic in the Policy Agent 2.2 for Microsoft IIS 6.0.

Details

The Policy Agent 2.2 for Microsoft IIS 6.0 is defined in <am_web.h> as having auth-type value equal to DSAME.

```
#define      AM_WEB_AUTH_TYPE_VALUE      "DSAME"
```

DSAME is a hard-coded value representing all OpenSSO Enterprise authentication types other than Basic.

Syntax

```
#include "am_web.h"  
AM_WEB_EXPORT const char *  
am_web_get_authType(void* agent_config);
```

Parameters

`agent_config` An agent configuration instance returned by `am_web_get_agent_configuration()`. This parameter may not be NULL.

Returns

This function returns either DSAME or Basic.

am_web_get_cookie_name()

Retrieves the name of the OpenSSO Enterprise cookie.

Syntax

```
#include "am_web.h"  
AM_WEB_EXPORT const char *  
am_web_get_cookie_name(void* agent_config);
```

Parameters

`agent_config` An agent configuration instance returned by `am_web_get_agent_configuration()`. This parameter may not be NULL.

Returns

This function returns the name of the OpenSSO Enterprise cookie.

am_web_get_notification_url()

Retrieves the URL of the OpenSSO Enterprise Notification Service.

Syntax

```
#include "am_web.h"
AM_WEB_EXPORT const char *
am_web_get_notification_url(void* agent_config);
```

Parameters

agent_config An agent configuration instance returned by `am_web_get_agent_configuration()`. This parameter may not be NULL.

Returns

This function returns the URL of the OpenSSO Enterprise Notification Service.

am_web_get_parameter_value()

Gets the value of the specified parameter from the specified request URL.

Syntax

```
#include "am_web.h"
AM_WEB_EXPORT am_status_t
am_web_get_parameter_value(const char *inpQuery,
                           const char *param_name,
                           char **param_value);
```

Parameters

This function takes the following parameters:

inpQuery	Pointer to the request URL that holds the parameter.
param_name	Pointer to the name of the parameter.
param_value	Pointer to a pointer to be filled with the value of the <code>param_name</code> parameter, if found.

Returns

This function also returns one of the following values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file):

AM_SUCCESS	If the query parameter was found in the URL.
AM_*	If any other error occurred.

Memory Concerns

The returned parameter value should be freed by the caller using `am_web_free()`.

`am_web_get_request_url()`

Parses the host request header field for a server host name, port, protocol, query parameter, and URI to return the requested URL to the web agent.

Syntax

```
#include "am_web.h"
AM_WEB_EXPORT am_status_t
am_web_get_request_url(const char *host_hdr,
                      const char *protocol,
                      const char *hostname,
                      size_t port,
                      const char *uri,
                      const char *query,
                      char **req_url,
                      void* agent_config);
```

Parameters

This function takes the following parameters:

<code>host_hdr</code>	Pointer to the host header string of the HTTP request as passed from the browser.
<code>protocol</code>	Pointer to the protocol used by the web container of the resource being requested.
<code>hostname</code>	Pointer to the name of the host on which the resource being requested.
<code>port</code>	Value based on the <code>size_t</code> defined in the standard <code><stddef.h></code> header file that reflects the port number of the resource being requested.
<code>uri</code>	Pointer to the URI of the HTTP request.

Note – Most URLs have this basic form: *protocol://server:port/request-URI*. The *request-URI* portion of the URL is used by the web server to identify the document.

<code>query</code>	The query string appended to the request URL, if any. For example, if the URL is <code>http://www.example.com?a=b&c=d</code> , the value of this parameter would be <code>a=b&c=d</code> .
<code>req_url</code>	Pointer to a pointer to the OUT parameter to be populated with the value of the URL string to be used by the agent.
<code>agent_config</code>	An agent configuration instance returned by <code>am_web_get_agent_configuration()</code> . This parameter may not be NULL.

Returns

This function returns one of the following values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file):

<code>AM_SUCCESS</code>	If the query parameter was found in the URL.
<code>AM_*</code>	If any other error occurred.

`am_web_get_token_from_assertion()`

Returns the single sign-on token from the specified Security Assertion Markup Language (SAML) assertion.

Details

`am_web_get_token_from_assertion()` is used to retrieve the cookie sent by OpenSSO Enterprise in a SAML assertion.

Syntax

```
#include "am_web.h"
AM_WEB_EXPORT am_status_t
am_web_get_token_from_assertion(char *assertion,
                                char **token,
                                void* agent_config);
```

Parameters

This function takes the following parameters:

<code>assertion</code>	Pointer to the SAML assertion as an XML string.
<code>token</code>	Pointer to a pointer containing the single sign-on token identifier.
<code>agent_config</code>	An agent configuration instance returned by <code>am_web_get_agent_configuration()</code> . This parameter may not be NULL.

Returns

This function returns one of the following values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file):

`AM_SUCCESS` If successful.

`AM_*` Otherwise.

Memory Concerns

The returned identifier should be freed using `am_web_free()`.

`am_web_get_url_to_redirect()`

Returns a string representing a login URL or access denied URL to which the web agent should redirect.



Caution – `am_web_get_redirect_url()` has been deprecated and must not be used. It is supported for backward compatibility only.

Details

`am_web_get_url_to_redirect()` may redirect the user to the login URL or the access denied URL. The URL is appropriate to the provided status code and advice map returned by the Policy SDK. If redirecting to the login URL, the URL will include existing information specified in the URL from the configuration file (for example, the organization name) as well as the specified goto parameter value which will be used by OpenSSO Enterprise after the user has successfully authenticated. The last parameter reserved must be passed with `NULL`.

Note – If the URL returned is not `NULL`, the caller of this function must call `am_web_free_memory(void *)` to free the pointer.

Syntax

```
#include "am_web.h"
AM_WEB_EXPORT am_status_t
am_web_get_url_to_redirect(am_status_t status,
                           const am_map_t advice_map,
                           const char *goto_url,
                           const char* method,
                           void *reserved,
                           char ** redirect_url,
```

```
void* agent_config);
```

Parameters

This function takes the following parameters:

status The status from `am_web_is_access_allowed()`.

Note – See “`am_web_is_access_allowed()`” on page 194.

advice_map Any advice map from policy evaluation results.

goto_url Pointer to the original URL which the user attempted to access.

method Pointer to the original HTTP method: GET or POST.

reserved This parameter is not currently used.

redirect_url Pointer to a pointer containing the resulting OpenSSO Enterprise redirect URL.

agent_config An agent configuration instance returned by `am_web_get_agent_configuration()`. This parameter may not be NULL.

Returns

This function returns one of the following values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file):

AM_SUCCESS If successful.

AM_* Otherwise.

`am_web_get_user_id_param()`

Returns the value of the logged-in user.

Syntax

```
#include "am_web.h"
AM_WEB_EXPORT char * am_web_get_user_id_param(void* agent_config);
```

Parameters

This function takes the following parameters:

`agent_config` An agent configuration instance returned by `am_web_get_agent_configuration()`. This parameter may not be NULL.

Returns

This function returns the value of the logged-in user.

am_web_handle_notification()

Handles notification data received by a web agent.

Details

`am_web_handle_notification()` generates logging messages for the event and any error that may occur during the processing of the notification.

Syntax

```
#include "am_web.h"
AM_WEB_EXPORT void
am_web_handle_notification(const char *data,
                           size_t data_length,
                           void* agent_config);
```

Parameters

This function takes the following parameters:

<code>data</code>	Pointer to the notification message as an XML string.
<code>data_length</code>	Value based on the <code>size_t</code> defined in the standard <code><stddef.h></code> header file that reflects the length of the notification message.
<code>agent_config</code>	An agent configuration instance returned by <code>am_web_get_agent_configuration()</code> . This parameter may not be NULL.

Returns

This function returns no value.

am_web_http_decode()

URL decodes the specified URL encoded string.

Syntax

```
#include "am_web.h"
AM_WEB_EXPORT char *
am_web_http_decode(const char *string,
                   size_t len);
```

Parameters

This function takes the following parameters:

<code>string</code>	Pointer to the URL encoded string.
<code>len</code>	Value based on the <code>size_t</code> defined in the standard <code><stddef.h></code> header file that reflects the length of the string.

Returns

This function returns the URL decoded value of the URL encoded string, or NULL if an error occurred.

Memory Concerns

The returned value should be freed by calling `am_web_free()`.

`am_web_init()` for Agents 3.0

Initializes the 3.0 web agent by loading the bootstrap properties file.

Syntax

```
#include "am_web.h"
AM_WEB_EXPORT am_status_t
am_web_init(const char *agent_bootstrap_file
           const char *agent_config_file);
```

Parameters

This function takes the following parameter:

<code>agent_bootstrap_file</code>	Pointer to the agent bootstrap file which resides on the machine local to the agent.
<code>agent_config_file</code>	Pointer to the agent configuration file which resides on the same machine as OpenSSO Enterprise.

Returns

This function returns one of the following values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file):

<code>AM_SUCCESS</code>	If the call was successful.
<code>AM_*</code>	If any error occurs, the type of error indicated by the status value.

`am_web_is_access_allowed()`

Evaluates the access control policies for a specified web resource and action against those for a specified user.

Syntax

```
#include "am_web.h"
AM_WEB_EXPORT am_status_t
am_web_is_access_allowed(const char *sso_token,
                        const char *url,
                        const char *path_info,
                        const char *action_name,
                        const char *client_ip,
                        const am_map_t env_parameter_map,
                        am_policy_result_t *result,
                        void* agent_config);
```

Parameters

This function takes the following parameters:

<code>sso_token</code>	Pointer to the session token from the OpenSSO Enterprise cookie. This parameter may be NULL if there is no cookie present.
<code>url</code>	Pointer to the web resource URL. This parameter may not be NULL.
<code>path_info</code>	Pointer to the path information in the web resource URL, if any.
<code>action_name</code>	Pointer to the action (GET, POST, etc.) being performed on the specified resource URL. This parameter may not be NULL.
<code>client_ip</code>	Pointer to the IP address of the client attempting to access the specified resource URL. If client IP validation is turned on, this parameter may not be NULL.
<code>env_parameter_map</code>	A map object containing additional information about the user attempting to access the specified resource URL. This parameter may not be NULL.

<code>advices_map_ptr</code>	An output parameter where the <code>am_map_t</code> can be stored if the policy evaluation produces any advice information. This parameter may not be NULL. See “ am_map_t ” on page 119 for more information.
<code>result</code>	Pointer to a policy result object.
<code>agent_config</code>	An agent configuration instance returned by <code>am_web_get_agent_configuration()</code> . This parameter may not be NULL.

Returns

This function returns one of the following values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file):

<code>AM_SUCCESS</code>	If the evaluation was performed successfully and access is allowed.
<code>AM_NO_MEMORY</code>	If the evaluation was not successfully completed due to insufficient memory being available.
<code>AM_INVALID_ARGUMENT</code>	If any of the <code>url</code> , <code>action_name</code> , <code>env_parameter_map</code> , or <code>advices_map_ptr</code> parameters is NULL or if client IP validation is enabled and the <code>client_ip</code> parameter is NULL.
<code>AM_INVALID_SESSION</code>	If the specified session token does not refer to a currently valid session
<code>AM_ACCESS_DENIED</code>	If the policy information indicates that the user does not have permission to access the specified resource or any error is detected other than the ones listed above.

`am_web_is_cdsso_enabled()`

Returns a boolean specifying whether cross domain single sign-on is enabled in the agent’s configuration file.

Syntax

```
#include "am_web.h"
AM_WEB_EXPORT boolean_t
am_web_is_cdsso_enabled(void* agent_config);
```

Parameters

<code>agent_config</code>	An agent configuration instance returned by <code>am_web_get_agent_configuration()</code> . This parameter may not be NULL.
---------------------------	---

Returns

This function returns one of the following values of the `boolean_t` enumeration (defined in the `<am_types.h>` header file):

`B_TRUE` If cross domain single sign-on is enabled.

`B_FALSE` Otherwise.

`am_web_is_cookie_present()`

Detects whether a cookie is present.

Details

This function will most probably be invoked in a loop. A cookie name and value is passed and the implementation checks whether the cookie is already listed. If not, the new cookie name and value are appended. If present, the value of the cookie name is updated.

Syntax

```
#include "am_web.h"
AM_WEB_EXPORT int
am_web_is_cookie_present(const char *cookie,
                        const char *value,
                        char **new_cookie);
```

Parameters

This function takes the following parameters:

`cookie` Pointer to a cookie.

`value` Pointer to a value.

`new_cookie` Pointer to a pointer to the location of the new cookie.

Returns

This function returns one of the following integers as defined in `<am_web.h>`:

```
#define AM_WEB_COOKIE_EXIST            2
#define AM_WEB_COOKIE_MODIFIED        1
#define AM_WEB_COOKIE_ABSENT          0
#define AM_WEB_COOKIE_ERROR          -1
```

am_web_is_debug_on()

Returns a boolean specifying whether debug is enabled.

Details

`am_web_is_debug_on()` specifies whether the log level is set to anything greater than 0.

Syntax

```
#include "am_web.h"
AM_WEB_EXPORT boolean_t
am_web_is_debug_on();
```

Parameters

This function takes no parameters.

Returns

This function returns one of the following values of the `boolean_t` enumeration (defined in the `<am_types.h>` header file):

`B_TRUE` If the log level is set to anything greater than 0.
`B_FALSE` Otherwise.

am_web_is_in_not_enforced_ip_list()

Returns a boolean specifying whether the given IP address is defined as one where no authentication or authorization is required.

Details

IP addresses that are not enforced are defined in the `com.sun.am.policy.agents.config.notenforced_client_ip_list` property in `AMAgent.properties`. If the IP address from where the request was issued is not enforced, the request goes through without authentication or authorization.

Syntax

```
#include "am_web.h"
AM_WEB_EXPORT boolean_t
am_web_is_in_not_enforced_ip_list(const char *ip,
                                  void* agent_config);
```

Parameters

This function takes the following parameter:

<code>ip</code>	Pointer to the IP address.
<code>agent_config</code>	An agent configuration instance returned by <code>am_web_get_agent_configuration()</code> . This parameter may not be NULL.

Returns

This function returns one of the following values of the `boolean_t` enumeration (defined in the `<am_types.h>` header file):

<code>B_TRUE</code>	If the IP is in the not enforced IP address list.
<code>B_FALSE</code>	Otherwise.

`am_web_is_in_not_enforced_list()`

Returns a boolean specifying whether the URL being accessed by the user is in the not enforced list.

Details

URLs that are not enforced are defined in the `com.sun.am.policy.agents.config.notenforced_list` property in `AMAgent.properties`. If the URL is not enforced, the request goes through without authentication or authorization.

Syntax

```
#include "am_web.h"
AM_WEB_EXPORT boolean_t
am_web_is_in_not_enforced_list(const char *url,
                               const char *path_info,
                               void* agent_config);
```

Parameters

This function takes the following parameters:

<code>url</code>	Pointer to the URL being accessed.
<code>path_info</code>	Pointer to the path information in the URL being accessed, if any.
<code>agent_config</code>	An agent configuration instance returned by <code>am_web_get_agent_configuration()</code> . This parameter may not be NULL.

Returns

This function returns one of the following values of the `boolean_t` enumeration (defined in the `<am_types.h>` header file):

- `B_TRUE` If the URL is in the not enforced list.
- `B_FALSE` Otherwise.

`am_web_is_logout_url()`

Returns a boolean specifying whether the specified URL is a logout URL.

Syntax

```
#include "am_web.h"
AM_WEB_EXPORT boolean_t
am_web_is_logout_url(const char *url,
                    void* agent_config);
```

Parameters

This function takes the following parameter:

- `url` Pointer to a URL.
- `agent_config` An agent configuration instance returned by `am_web_get_agent_configuration()`. This parameter may not be `NULL`.

Returns

This function returns one of the following values of the `boolean_t` enumeration (defined in the `<am_types.h>` header file):

- `B_TRUE` If the specified URL is a logout URL.
- `B_FALSE` Otherwise.

`am_web_is_max_debug_on()`

Returns a boolean specifying whether the log level is set to 5.

Syntax

```
#include "am_web.h"
AM_WEB_EXPORT boolean_t
am_web_is_max_debug_on();
```

Parameters

This function takes no parameters.

Returns

This function returns one of the following values of the `boolean_t` enumeration (defined in the `<am_types.h>` header file):

`B_TRUE` If the log level is set to 5.

`B_FALSE` Otherwise.

`am_web_is_notification()`

Returns a boolean specifying whether the given URL is the Notification Service URL for the web agent as configured in `AMAgent.properties`.

Syntax

```
#include "am_web.h"
AM_WEB_EXPORT boolean_t
am_web_is_notification(const char *request_url
                      void* agent_config);
```

Parameters

This function takes the following parameter:

`request_url` Pointer to the Notification Service URL

`agent_config` An agent configuration instance returned by
`am_web_get_agent_configuration()`. This parameter may not be `NULL`.

Returns

This function returns one of the following values of the `boolean_t` enumeration (defined in the `<am_types.h>` header file):

`B_TRUE` If the URL is the Notification Service URL of the agent as set in
`AMAgent.properties`.

B_FALSE Otherwise.

am_web_is_owa_enabled()

Returns the value of the `com.sun.identity.agents.config.iis.owa.enable` property.

Note – Outlook Web Access (OWA) is a web mail service installed on Microsoft Internet Information Services 6.0. OWA interacts with the Exchange server to retrieve e-mail, calendar contacts, and the like. A policy agent can be used to provide SSO for OWA.

Syntax

```
#include "am_web.h"
AM_WEB_EXPORT boolean_t
am_web_is_owa_enabled(void* agent_config);
```

Parameters

`agent_config` An agent configuration instance returned by
 `am_web_get_agent_configuration()`. This parameter may not be NULL.

Returns

This function returns one of the following values of the `boolean_t` enumeration (defined in the `<am_types.h>` header file):

B_TRUE If OWA is enabled.
B_FALSE Otherwise.

am_web_is_owa_enabled_change_protocol()

Used to convert incoming http and https protocol to https. Returns the value of the `com.sun.identity.agents.config.iis.owa.enable.change.protocol` property. The property can have a value of either true or false; the default value is false.

Note – Outlook Web Access (OWA) is a web mail service installed on Microsoft Internet Information Services 6.0. OWA interacts with the Exchange server to retrieve email, calendar contacts, and the like. A policy agent can be used to provide SSO for OWA.

Syntax

```
#include "am_web.h"
AM_WEB_EXPORT boolean_t
am_web_is_owa_enabled_change_protocol(void* agent_config);
```

Parameters

agent_config An agent configuration instance returned by `am_web_get_agent_configuration()`. This parameter may not be NULL.

Returns

This function returns one of the following values of the `boolean_t` enumeration (defined in the `<am_types.h>` header file):

B_TRUE If the protocol was changed.

B_FALSE Otherwise.

`am_web_is_owa_enabled_session_timeout_url()`

Returns the value of the `com.sun.identity.agents.config.iis.owa.enable.session_timeout_url` property, used to redirect to a custom session timeout page

Note – Outlook Web Access (OWA) is a web mail service installed on Microsoft Internet Information Services 6.0. OWA interacts with the Exchange server to retrieve email, calendar contacts, and the like. A policy agent can be used to provide SSO for OWA.

Syntax

```
#include "am_web.h"
AM_WEB_EXPORT char *
am_web_is_owa_enabled_session_timeout_url(void* agent_config);
```

Parameters

agent_config An agent configuration instance returned by `am_web_get_agent_configuration()`. This parameter may not be NULL.

Returns

This function returns the URL of the custom session timeout page.

am_web_is_postpreserve_enabled()

Returns a boolean specifying whether POST data preservation is enabled for clients in `AMAgent.Properties`.

Syntax

```
#include "am_web.h"
AM_WEB_EXPORT boolean_t
am_web_is_postpreserve_enabled(void* agent_config);
```

Parameters

`agent_config` An agent configuration instance returned by `am_web_get_agent_configuration()`. This parameter may not be `NULL`.

Returns

This function returns one of the following values of the `boolean_t` enumeration (defined in the `<am_types.h>` header file):

`B_TRUE` If POST data preservation is on.

`B_FALSE` If POST data preservation is off.

am_web_is_proxy_override_host_port_set()

Determines if the `com.sun.am.policy.agents.config.override_host` and the `com.sun.am.policy.agents.config.override_port` properties are set for the proxy agent.

Details

These properties are defined in `AMAgent.properties`.

Syntax

```
#include "am_web.h"
AM_WEB_EXPORT boolean_t am_web_is_proxy_override_host_port_set(void* agent_config);
```

Parameters

`agent_config` An agent configuration instance returned by `am_web_get_agent_configuration()`. This parameter may not be `NULL`.

Returns

This function returns one of the following values of the `boolean_t` enumeration (defined in the `<am_types.h>` header file):

- `B_TRUE` If set.
- `B_FALSE` Otherwise.

`am_web_is_valid_fqdn_url()`

Returns a boolean specifying whether the requested URL is a valid fully qualified domain name (FQDN) resource as configured in `AMAgent.properties`. For example, `myhost.mydomain.com`.

Syntax

```
#include "am_web.h"
AM_WEB_EXPORT boolean_t
am_web_is_valid_fqdn_url(const char *url,
                        void* agent_config);
```

Parameters

- `url` Pointer to a URL.
- `agent_config` An agent configuration instance returned by `am_web_get_agent_configuration()`. This parameter may not be `NULL`.

Returns

This function returns one of the following values of the `boolean_t` enumeration (defined in the `<am_types.h>` header file):

- `B_TRUE` If the URL is using a fully qualified domain name.
- `B_FALSE` Otherwise.

`am_web_log_always()`

Log the given message regardless of the log level set in `AMAgent.properties`.

Syntax

```
#include "am_web.h"
AM_WEB_EXPORT void
am_web_log_always(const char *fmt, ...);
```

Parameters

This function takes the following parameter:

fmt Pointer to a formatted string message as in `printf`.

Returns

This function returns no values.

`am_web_log_auth()`

Log the given access allowed or denied message to the OpenSSO Enterprise logs.

Syntax

```
#include "am_web.h"
AM_WEB_EXPORT boolean_t
am_web_log_auth(am_web_access_t access_type,
                const char *fmt, ...
                void* agent_config);
```

Parameters

This function takes the following parameters:

access_type One of the following values of the `am_web_access_t` enumeration as defined:

```
#include "am_web.h"
typedef enum {
    AM_ACCESS_DENY = 0,
    AM_ACCESS_ALLOW
} am_web_access_t;
```

fmt Pointer to a formatted string message as in `printf`.

agent_config An agent configuration instance returned by `am_web_get_agent_configuration()`. This parameter may not be `NULL`.

Returns

This function returns one of the following values of the `boolean_t` enumeration (defined in the `<am_types.h>` header file):

B_TRUE If the call was successful.

B_FALSE Otherwise.

am_web_log_debug()

Log the given message at the debug level.

Syntax

```
#include "am_web.h"
AM_WEB_EXPORT void
am_web_log_debug(const char *fmt, ...);
```

Parameters

This function takes the following parameter:

fmt Pointer to a formatted string message as in `printf`.

Returns

This function returns no values.

am_web_log_error()

Log the given message at the debug log level.

Syntax

```
#include "am_web.h"
AM_WEB_EXPORT void
am_web_log_error(const char *fmt, ...);
```

Parameters

This function takes the following parameter:

fmt Pointer to a formatted string message as in `printf`.

Returns

This function returns no values.

am_web_log_info()

Log the given message at the info log level.

Syntax

```
#include "am_web.h"
AM_WEB_EXPORT void
am_web_log_info(const char *fmt, ...);
```

Parameters

This function takes the following parameter:

fmt Pointer to a formatted string message as in `printf`.

Returns

This function returns no values.

am_web_log_max_debug()

Log the given message at maximum debug level.

Syntax

```
#include "am_web.h"
AM_WEB_EXPORT void
am_web_log_max_debug(const char *fmt, ...);
```

Parameters

This function takes the following parameters:

fmt Pointer to a formatted string message as in `printf`.

Returns

This function returns no values.

am_web_log_warning()

Log the given message at the warning log level.

Syntax

```
#include "am_web.h"
AM_WEB_EXPORT void
am_web_log_warning(const char *fmt, ...);
```

Parameters

This function takes the following parameters:

fmt Pointer to a formatted string message as in `printf`.

Returns

This function returns no values.

am_web_logout_cookies_reset()

Resets cookie configured for reset on user logout.

Details

The reset function passed in is called for each cookie configured for reset. If the function failed for any cookie, the last failed status is returned.

Syntax

```
#include "am_web.h"
AM_WEB_EXPORT am_status_t
am_web_logout_cookies_reset(am_status_t (*setFunc)(
    const char *,
    void **),
    void **args,
    void* agent_config);
```

Parameters

This function takes the following parameters:

setFunc	Function pointer with which the user can define their own function for setting the cookie in the foreign domain. The implementation defines the parameters.
args	Pointer to a pointer to agent defined parameters.
agent_config	An agent configuration instance returned by <code>am_web_get_agent_configuration()</code> . This parameter may not be NULL.

Returns

This function returns no values.

am_web_method_num_to_str()

Converts a `am_web_req_method_t` number to a string.

Details

This function is used for logging the method in the local debug logs. It takes in a method name and returns a string value (such as GET, or POST).

Syntax

```
#include "am_web.h"
AM_WEB_EXPORT const char *
am_web_method_num_to_str(am_web_req_method_t method);
```

Parameters

This function takes the following parameter:

`method` One of the following values of the `am_web_req_method_t` enumeration as defined:

```
#include "am_web.h"
typedef enum {
    AM_WEB_REQUEST_UNKNOWN,
    AM_WEB_REQUEST_GET,
    AM_WEB_REQUEST_POST,
    AM_WEB_REQUEST_HEAD,
    AM_WEB_REQUEST_PUT,
    AM_WEB_REQUEST_DELETE,
    AM_WEB_REQUEST_TRACE,
    AM_WEB_REQUEST_OPTIONS
} am_web_req_method_t;
```

More information on these request methods can be found in <http://www.faqs.org/rfcs/rfc2068.html>.

Returns

This function returns a pointer to the string. If the number passed is not recognized, UNKNOWN is returned.

am_web_method_str_to_num()

Converts a `am_web_req_method_t` string to a number.

Details

This function does the opposite of the previously defined `am_web_method_num_to_str()`. See “[am_web_method_num_to_str\(\)](#)” on page 209 for details.

Syntax

```
#include "am_web.h"
AM_WEB_EXPORT const char *
am_web_method_num_to_str(am_web_req_method_t method);
```

Parameters

This function takes the following parameter:

`method` One of the following values of the `am_web_req_method_t` enumeration as defined:

```
#include "am_web.h"
typedef enum {
    AM_WEB_REQUEST_UNKNOWN,
    AM_WEB_REQUEST_GET,
    AM_WEB_REQUEST_POST,
    AM_WEB_REQUEST_HEAD,
    AM_WEB_REQUEST_PUT,
    AM_WEB_REQUEST_DELETE,
    AM_WEB_REQUEST_TRACE,
    AM_WEB_REQUEST_OPTIONS
} am_web_req_method_t;
```

More information on these request methods can be found in <http://www.faqs.org/rfcs/rfc2068.html>.

Returns

This function returns a pointer to the number. If the string is not recognized, `AM_WEB_REQUEST_UNKNOWN` is returned.

am_web_postcache_data_cleanup()

Cleans up `am_web_postcache_data_t` data type.

Syntax

```
#include "am_web.h"
AM_WEB_EXPORT void
am_web_postcache_data_cleanup(am_web_postcache_data_t * const postentry_struct);
```

Parameters

This function takes the following parameter:

`postentry_struct` Pointer to `am_web_postcache_data_t` data type.

Returns

This function returns no value.

`am_web_postcache_insert()`

Inserts POST data entry in the POST cache.

Syntax

```
#include "am_web.h"
AM_WEB_EXPORT boolean_t
am_web_postcache_insert(const char *key,
                        const am_web_postcache_data_t *value,
                        void* agent_config);
```

Parameters

This function takes the following parameters:

<code>key</code>	Pointer to the POST data preservation key for every entry.
<code>value</code>	Pointer to the <code>am_web_postcache_data_t</code> data type.
<code>agent_config</code>	An agent configuration instance returned by <code>am_web_get_agent_configuration()</code> . This parameter may not be NULL.

Returns

This function returns one of the following values of the `boolean_t` enumeration (defined in the `<am_types.h>` header file):

<code>B_TRUE</code>	If the insertion was successful.
<code>B_FALSE</code>	Otherwise.

am_web_postcache_lookup()

Looks up data in the POST cache.

Syntax

```
#include "am_web.h"
AM_WEB_EXPORT boolean_t
am_web_postcache_lookup(const char *key,
                        am_web_postcache_data_t *postdata_entry,
                        void* agent_config);
```

Parameters

This function takes the following parameters:

key	Pointer to the key to search POST data entry in POST data structure.
postdata_entry	Pointer to the am_web_postcache_data_t data type storing the POST data.
agent_config	An agent configuration instance returned by am_web_get_agent_configuration(). This parameter may not be NULL.

Returns

This function returns one of the following values of the boolean_t enumeration (defined in the <am_types.h> header file):

B_TRUE	If the search was successful.
B_FALSE	Otherwise.

am_web_postcache_remove()

Removes data from the POST cache.

Syntax

```
#include "am_web.h"
AM_WEB_EXPORT void
am_web_postcache_remove(const char *key,
                        void* agent_config);
```

Parameters

This function takes the following parameter:

key	Pointer to the key of the entry to be removed.
agent_config	An agent configuration instance returned by <code>am_web_get_agent_configuration()</code> . This parameter may not be NULL.

Returns

This function returns no value.

am_web_process_request()

Processes a request access check and returns a HTTP result to be rendered by the agent.

Details

The render status is returned in the `render_sts` argument.

Syntax

```
#include "am_web.h"
AM_WEB_EXPORT am_web_result_t
am_web_process_request(am_web_request_params_t *req_params,
                      am_web_request_func_t *req_func,
                      am_status_t *render_sts,
                      void* agent_config);
```

Parameters

This function takes the following parameters:

req_params	Pointer to a <code>am_web_request_params_t</code> data type.
req_func	Pointer to a <code>am_web_request_func_t</code> data type.
render_sts	Pointer to one of the values of the <code>am_status_t</code> enumeration as defined in the <code><am_types.h></code> header file.
agent_config	An agent configuration instance returned by <code>am_web_get_agent_configuration()</code> . This parameter may not be NULL.

Returns

One of the following values of the `am_web_result_t` enumeration as defined:

```
#include "am_web.h"
typedef enum {
    AM_WEB_RESULT_OK,                /* access check was OK */
    AM_WEB_RESULT_OK_DONE,           /* OK and handled (for ex. notification) */
    AM_WEB_RESULT_FORBIDDEN,         /* access forbidden */
    AM_WEB_RESULT_REDIRECT,          /* redirected */
    AM_WEB_RESULT_ERROR              /* internal error */
} am_web_result_t;
```

am_web_remove_authnrequest()

Removes those extra parameters from an authenticated request.

Details

When a user returns from CDSSO authentication, the request contains a list of parameters that were added when the user was authenticated. `am_web_remove_authnrequest()` removes these extra parameters so the request is forwarded to applications as it originally came from the browser.

Syntax

```
#include "am_web.h"
AM_WEB_EXPORT am_status_t
am_web_remove_authnrequest(char* inpString,
                           char **outString );
```

Parameters

This function takes the following parameters:

- `inpString` Pointer to the URL received after CDSSO authentication.
- `outString` Pointer to a pointer to the location of the new URL without the parameters.

Returns

This function returns one of the following values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file):

- `AM_SUCCESS` If successful.
- `AM_*` The type of error indicated by the status value.

Memory Concerns

The value returned should be freed using `am_web_free()`.

`am_web_remove_parameter_from_query()`

Removes the given query parameter from the URL, if present.

Syntax

```
#include "am_web.h"
AM_WEB_EXPORT am_status_t
am_web_remove_parameter_from_query(const char* inpString,
                                   const char *remove_str,
                                   char **outString );
```

Parameters

This function takes the following parameters:

<code>inpString</code>	Pointer to the original URL.
<code>remove_str</code>	Pointer to the query parameter to be removed
<code>outString</code>	Pointer to a pointer to the location of the new URL without the query parameter.

Returns

This function returns one of the following values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file):

<code>AM_SUCCESS</code>	If the call was successful.
<code>AM_*</code>	If any error occurs, the type of error indicated by the status value.

Memory Concerns

The value returned should be freed using `am_web_free()`.

`am_web_result_attr_map_set()`

Processes `attr_response_map` from a `am_policy_result_t` data type and performs the set action.

Details

This function replaces `am_web_do_result_attr_map_set()` which is deprecated. It needs to be explicitly declare to use it. See `<am_web.h>` for more information.

Syntax

```
#include "am_web.h"
AM_WEB_EXPORT am_status_t
am_web_result_attr_map_set(am_policy_result_t *result,
                           am_web_result_set_header_func_t setHeaderFunc,
                           am_web_result_set_header_attr_in_response_func_t setCookieRespFunc,
                           am_web_result_set_header_attr_in_request_func_t setCookieReqFunc,
                           am_web_get_cookie_sync_func_t getCookieSyncFunc,
                           void **args, void* agent_config);
```

Parameters

This function takes the following parameters:

`result` Pointer to the `am_policy_result_t`.

Note – See “[am_policy_result_t](#)” on page 51 for more information.

<code>setHeaderFunc</code>	Pointer to the <code>am_web_result_set_header_func_t</code> .
<code>setCookieRespFunc</code>	Pointer to the <code>am_web_result_set_header_attr_in_response_func_t</code> .
<code>setCookieReqFunc</code>	Pointer to the <code>am_web_result_set_header_attr_in_request_func_t</code> .
<code>getCookieSyncFunc</code>	Pointer to the <code>am_web_get_cookie_sync_func_t</code> .
<code>args</code>	Pointer to a pointer to agent defined parameters.
<code>agent_config</code>	An agent configuration instance returned by <code>am_web_get_agent_configuration()</code> . This parameter may not be NULL.

Returns

This function returns one of the following values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file):

- | | |
|-------------------------|---|
| <code>AM_SUCCESS</code> | If the call was successful. |
| <code>AM_*</code> | If any error occurs, the type of error indicated by the status value. |

Memory Concerns

The value returned should be freed using `am_web_free()`.

`am_web_result_num_to_str()`

Returns the name of a `am_web_result_t` as a string.

Syntax

```
#include "am_web.h"
AM_WEB_EXPORT const char *
am_web_result_num_to_str(am_web_result_t result);
```

Parameters

This function takes the following parameter:

`result` One of the following values of the `am_web_result_t` enumeration as defined:

```
#include "am_web.h"
typedef enum {
    AM_WEB_RESULT_OK,                /* access check was OK */
    AM_WEB_RESULT_OK_DONE,           /* OK and handled (for ex. notification) */
    AM_WEB_RESULT_FORBIDDEN,         /* access forbidden */
    AM_WEB_RESULT_REDIRECT,          /* redirected */
    AM_WEB_RESULT_ERROR              /* internal error */
} am_web_result_t;
```

Returns

This function returns a pointer to the string. For example, `AM_WEB_RESULT_OK` returns `AM_WEB_RESULT_OK`. If the result code passed is not recognized, Unknown result code is returned.

`am_web_set_cookie()`

Sets the specified cookie in the cookie header of the request.

Syntax

```
#include "am_web.h"
AM_WEB_EXPORT am_status_t
am_web_set_cookie(char *cookie_header,
```

```
const char *set_cookie_value,  
char **new_cookie_header);
```

Parameters

This function takes the following parameters:

<code>cookie_header</code>	Pointer to the cookie header.
<code>set_cookie_value</code>	Pointer to the cookie name and value in the <i>set-cookie response header</i> form. This value should be the same as that of the <code>cookieValues</code> parameter of the <code>am_web_result_set_header_attr_in_request_func_t</code> function.
<code>new_cookie_header</code>	Pointer to a pointer to the original cookie header, or a new cookie header value which needs to be freed by the caller. This value can be <code>NULL</code> .

Returns

This function returns one of the following values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file):

<code>AM_SUCCESS</code>	If successful.
<code>AM_*</code>	The type of error indicated by the status value.

◆ ◆ ◆ 9 CHAPTER 9

Additional Data Types and Functions

This chapter provides information and a reference guide to the data types and functions not documented elsewhere. This includes those described in the `<am.h>`, `<am_notify.h>`, `<am_string_set.h>`, `<am_types.h>`, and `<am_util.h>` header files. Reference summaries include a short description, syntax, parameters and returns. This chapter contains the following sections:

- “`<am.h>`” on page 219
- “`<am_notify.h>`” on page 220
- “`<am_string_set.h>`” on page 221
- “`<am_types.h>`” on page 223
- “`<am_utils.h>`” on page 226

`<am.h>`

`<am.h>` contains the `am_cleanup()` function which cleans up all internal data structures created by `am_sso_init()`, `am_auth_init()`, or `am_policy_init()`. It needs to be called only once at the end of any calls. After cleanup, the relevant initialize function must be called again before using any of its interfaces.

Note – Any properties passed to the initialization functions `am_sso_init()`, `am_auth_init()`, or `am_policy_init()` should be destroyed only after `am_cleanup()` is called.

`am_cleanup()` Syntax

```
#include "am.h"
AM_EXPORT am_status_t
am_cleanup(void);
```

am_cleanup() Parameters

This function takes no parameters.

am_cleanup() Returns

This function returns one of the following values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file):

<code>AM_SUCCESS</code>	If successfully cleaned up.
<code>AM_NSPR_ERROR</code>	Netscape Portable Runtime (NSPR) error.
<code>AM_FAILURE</code>	If any other error occurred.

<am_notify.h>

`<am_notify.h>` contains the `am_notify()` function which parses and processes a session or policy notification message as an XML string. If the message is a session notification, any token handle listeners registered using `am_sso_add_listener()` will be called. If the message is a policy notification, the internal policy cache maintained by the policy module in the C SDK will be updated with the notification information only if the policy module has been initialized (using `am_policy_init()` and `am_policy_service_init()`).

am_notify() Syntax

```
#include "am_notify.h"
AM_EXPORT am_status_t
am_notify(const char *xmlmsg,
          am_policy_t policy_handle);
```

am_notify() Parameters

This function takes the following parameters:

<code>xmlmsg</code>	Pointer to the XML message containing the notification.
<code>policy_handle</code>	Reference to the policy evaluation object.

am_notify() Returns

This function returns one of the following values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file):

<code>AM_SUCCESS</code>	If the XML was successfully parsed and processed.
<code>AM_INVALID_ARGUMENT</code>	If any input parameter is invalid.
<code>AM_ERROR_PARSING_XML</code>	If an error occurred parsing the XML.
<code>AM_ERROR_DISPATCH_LISTENER</code>	If an error occurred dispatching the listener.
<code>AM_FAILURE</code>	If any other error occurred.

<am_string_set.h>

`<am_string_set.h>` contains public data types and functions intended to manipulate strings. The sample sources demonstrate basic usage of the string set API. This section contains the following sub sections:

- [“String Data Types” on page 221](#)
- [“String Functions” on page 222](#)

String Data Types

The string data type defined in `<am_string_set.h>` is `am_string_set_t`. The type holds a set of strings.

Details

`am_string_set_allocate()` and `am_string_set_destroy()` are used to allocate and free space for this type.

Syntax

```
#include "am_string_set.h"
typedef struct {
    int size;
    char **strings;
} am_string_set_t;
```

Members

`am_string_set_t` has the following members:

size Number of strings

strings Pointer to a pointer to a list of strings.

String Functions

The string functions defined in <am_string_set.h> are:

- [“am_string_set_allocate\(\)” on page 222](#)
- [“am_string_set_destroy\(\)” on page 222](#)

am_string_set_allocate()

Allocates memory and initializes the string set size.

Syntax

```
#include "am_string_set.h"
AM_EXPORT am_string_set_t *
am_string_set_allocate(int size);
```

Parameters

This function takes the following parameter:

size Number of strings in the set.

Returns

This function returns the allocated `am_string_set_t`, or `NULL` if size is less than zero.

am_string_set_destroy()

Releases memory in the specified string set object by freeing each string in the set, then freeing the associated pointers, and finally, the structure itself.

Syntax

```
#include "am_string_set.h"
AM_EXPORT void
am_string_set_destroy(am_string_set_t *string_set);
```

Parameters

This function takes the following parameter:

`string_set` Pointer to the specified string set object.

Returns

This function returns no values.

<am_types.h>

<am_types.h> contains defined types and corresponding functions. They are:

- [“boolean_t” on page 223](#)
- [“bool_t” on page 223](#)
- [“am_status_t” on page 223](#)
- [“am_status_to_string\(\)” on page 224](#)

boolean_t

Defines true or false boolean with the syntax:

```
#include "am_types.h"
typedef enum {
    B_FALSE,
    B_TRUE
} boolean_t;
```

bool_t

Defines true or false boolean with the syntax:

```
#include "am_types.h"
typedef enum {
    AM_FALSE = 0,
    AM_TRUE
} am_bool_t;
```

am_status_t

Defines error codes with the syntax:

```

#include "am_types.h"
typedef enum {
    AM_SUCCESS = 0,
    AM_FAILURE,
    AM_INIT_FAILURE,
    AM_AUTH_FAILURE,
    AM_NAMING_FAILURE,
    AM_SESSION_FAILURE,
    AM_POLICY_FAILURE,
    AM_NO_POLICY,
    AM_INVALID_ARGUMENT,
    AM_INVALID_VALUE,
    AM_NOT_FOUND,
    AM_NO_MEMORY,
    AM_NSPR_ERROR,
    AM_END_OF_FILE,
    AM_BUFFER_TOO_SMALL,
    AM_NO_SUCH_SERVICE_TYPE,
    AM_SERVICE_NOT_AVAILABLE,
    AM_ERROR_PARSING_XML,
    AM_INVALID_SESSION,
    AM_INVALID_ACTION_TYPE,
    AM_ACCESS_DENIED,
    AM_HTTP_ERROR,
    AM_INVALID_FQDN_ACCESS,
    AM_FEATURE_UNSUPPORTED,
    AM_AUTH_CTX_INIT_FAILURE,
    AM_SERVICE_NOT_INITIALIZED,
    AM_INVALID_RESOURCE_FORMAT,
    AM_NOTIF_NOT_ENABLED,
    AM_ERROR_DISPATCH_LISTENER,
    AM_REMOTE_LOG_FAILURE,
    AM_LOG_FAILURE,
    AM_REMOTE_LOG_NOT_INITIALIZED,
    AM_NUM_ERROR_CODES    /* This should always be the last. */
} am_status_t;

```

am_status_to_string()

Returns a message for the given error code.

Syntax

```

#include "am_types.h"
AM_EXPORT const char *am_status_to_string(am_status_t status);

```


Parameters

This function takes the following parameter:

`status` Given error code

Returns

This function returns the appropriate message for the status code as a const char *

<code>AM_SUCCESS</code>	Success.
<code>AM_FAILURE</code>	Failure.
<code>AM_INIT_FAILURE</code>	Initialization failure.
<code>AM_AUTH_FAILURE</code>	OpenSSO Enterprise Authentication Service failure.
<code>AM_NAMING_FAILURE</code>	OpenSSO Enterprise Naming Service failure.
<code>AM_SESSION_FAILURE</code>	OpenSSO Enterprise Session Service failure.
<code>AM_POLICY_FAILURE</code>	OpenSSO Enterprise Policy Service failure.
<code>AM_NO_POLICY</code>	No policy found.
<code>AM_INVALID_ARGUMENT</code>	Invalid argument.
<code>AM_INVALID_VALUE</code>	Invalid value.
<code>AM_NOT_FOUND</code>	OpenSSO Enterprise not found.
<code>AM_NO_MEMORY</code>	No memory.
<code>AM_NSPR_ERROR</code>	NSPR error.
<code>AM_END_OF_FILE</code>	Reached end of file.
<code>AM_BUFFER_TOO_SMALL</code>	If the defined size of the buffer is smaller than the encoded value.
<code>AM_NO_SUCH_SERVICE_TYPE</code>	No such service type found.
<code>AM_SERVICE_NOT_AVAILABLE</code>	Service is not available.
<code>AM_ERROR_PARSING_XML</code>	Error found during XML parsing.
<code>XML_AM_INVALID_SESSION</code>	Invalid session.
<code>AM_END_OF_FILE</code>	Reached end of file.
<code>AM_INVALID_ACTION_TYPE</code>	Invalid action type.
<code>AM_ACCESS_DENIED</code>	Access denied.
<code>AM_HTTP_ERROR</code>	HTTP error.

AM_INVALID_FQDN_ACCESS	Invalid fully qualified domain name (FQDN) access.
AM_FEATURE_UNSUPPORTED	The feature or configuration is unsupported.
AM_AUTH_CTX_INIT_FAILURE	Authentication context initialization failed.
AM_SERVICE_NOT_INITIALIZED	Specified service was not initialized.
AM_INVALID_RESOURCE_FORMAT	Specified resource name does not follow the format required by the service.
AM_NOTIF_NOT_ENABLED	Notification Service is not enabled or no notification URL is set.
AM_ERROR_DISPATCH_LISTENER	Error occurred dispatching single sign-on (SSO) listener.
AM_REMOTE_LOG_FAILURE	Remote Logging Service encountered an error.
AM_LOG_FAILURE	Log encountered an error.
AM_REMOTE_LOG_NOT_INITIALIZED	Remote Logging Service is not initialized.

<am_utils.h>

<am_utils.h> contains functions to encode and decode cookies. The functions are:

- [“am_http_cookie_encode\(\)” on page 226](#)
- [“am_http_cookie_decode\(\)” on page 227](#)

am_http_cookie_encode()

Encodes an HTTP cookie.

Syntax

```
#include "am.h"
AM_EXPORT am_status_t
am_http_cookie_encode(const char *cookie,
                     char *buf,
                     int len);
```

Parameters

This function takes the following parameters:

cookie Pointer to the cookie.

buf Pointer to the buffer where the encoded cookie will be stored.

len The size of the buffer.

Returns

This function returns one of the following values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file):

<code>AM_SUCCESS</code>	If the cookie was successfully encoded and stored.
<code>AM_INVALID_ARGUMENT</code>	If the cookie or buffer is NULL..
<code>AM_BUFFER_TOO_SMALL</code>	If the defined size is smaller than the encoded value.
<code>AM_FAILURE</code>	If any other error occurred.

am_http_cookie_decode()

Decodes an HTTP cookie.

Syntax

```
#include "am.h"
AM_EXPORT am_status_t
am_http_cookie_decode(const char *cookie,
                     char *buf,
                     int len);
```

Parameters

This function takes the following parameters:

cookie Pointer to the cookie.

buf Pointer to the buffer where the encoded cookie will be stored.

len The size of the buffer.

Returns

This function returns one of the following values of the `am_status_t` enumeration (defined in the `<am_types.h>` header file):

<code>AM_SUCCESS</code>	If the cookie was successfully decoded and copied.
<code>AM_INVALID_ARGUMENT</code>	If the cookie or buffer is NULL..
<code>AM_BUFFER_TOO_SMALL</code>	If the defined size is smaller than the decoded value.

AM_FAILURE	If any other error occurred.
------------	------------------------------