

Owner setup checklist

For Keyan FEILI | Private personal GitHub repository | Local Codex desktop sessions

Target experience: colleagues install once, trust the update hook, then receive automatic BTO update checks at session startup or resume. A package update can require a new chat; a changed hook can require trust review again.

1. Confirm the release

The D.P.-only Word generator is retained. Release 3.1.0 adds a Python SessionStart updater and the maintainer rule. It updates only `bto-cv@bto-cv-marketplace`, with a daily interval and a one-hour retry interval after failure. It does not upload CVs or candidate data.

Before sending this guide: confirm 3.1.0 or later is on main, the plugin is enabled, and the real update check returns current or updated. The separate-account pilot and each colleague's hook trust remain to be completed.

2. Prepare people and access

Collect each colleague's GitHub username. In [BTO-CV](#), open Settings > Collaborators and send an invitation. Ask them to accept and verify they can see the repository. Keep it private. No GitHub organisation is required.

Collaborators on this personal private repository have write access. The maintainer rule asks them to contact Keyan for shared-plugin changes; it is guidance, not an enforced permission boundary. Keep a record of invitees and remove access when no longer needed.

3. Agree the supported environment

Use local Codex desktop chats. Ask IT or the first tester to confirm the Python, Git and Codex CLI tools listed in the team guide work in the hook environment. Do not assume that signing in to GitHub in a browser also signs in Git.

For document fidelity, confirm Microsoft Word and the Century Gothic and Tw Cen MT fonts. Use a fictional CV first. Confirm the company permits the intended candidate documents in the chosen ChatGPT account.

4. Send the team guide

Send `BTO_CV_Team_Setup.pdf` with your usual work contact details. Start with one colleague, then roll out after the checks on page 2 pass.

Pilot and acceptance checks

Complete on a colleague's separate account before wider rollout

One-time setup check

Confirm they can read the private repository, register the Git-backed marketplace on main, install the plugin, and see version 3.1.0 or later enabled. Confirm only one active BTO installation. Retire any old standalone copy only after the plugin works.

Hook trust and a real session test

Have the colleague review the hook with `/hooks` in Codex CLI, or the desktop hook-review control if available. Never bypass trust. Start or resume a local Codex session. Verify the BTO update hook ran and the `update-state.json` in its `PLUGIN_DATA` directory records `ok: true`.

A direct `--force --check` run tests the updater script; it does not prove a trusted `SessionStart` hook fired. Verify both. If the hook is missing, check the app version, hook support, plugin enablement and interpreter paths.

Publish one harmless test update

Increment `plugin.json` to the next unused version, without changing the D.P. format. Commit and push to main. On the colleague's computer, wait until the daily interval has elapsed, then start/resume a session. For a faster script test, use `--force --check`. Confirm the installed version changes and a new-chat message appears.

Open a new chat and generate the fictional sample from `examples/sample-cv.txt`. Confirm editable text, the D.P. banner and square bullets. In Word, press Enter at the end of a bullet; another list item should appear. Check all supplied facts and every page.

Failure and recovery check

Test without network access: the updater should report a failed verification without uninstalling the plugin. Restore access, run a forced check, and confirm recovery. The CV skill separately requests the latest template; if that retrieval fails it asks before using the bundled snapshot.

Rollout gate: access works, one plugin is enabled, hook is trusted, real `SessionStart` execution is confirmed, a version upgrade succeeds, and the sample DOCX passes review. Owner-machine tests do not replace this separate-account check.

Release and support routine

Keep the source central; keep local installations easy to diagnose

When you change the plugin

Edit the repository, not the installed cache. Preserve the D.P. master and its required slots. Run the tests, generate and inspect a sample for formatting changes, increment plugin.json, then commit and push. Increment the version for every package change so the updater can detect it.

```
python -m unittest discover -s tests
```

The hook checks once per 24 hours at startup/resume; it is not a background timer while the app is closed. A failed check becomes eligible again after one hour. Credentials must remain valid. Existing CV files remain unchanged.

Manual recovery if a colleague is behind

Ask their local Codex agent to refresh only this marketplace, inspect the installed version, update BTO if needed and verify it. The corresponding commands are:

```
codex plugin marketplace upgrade bto-cv-marketplace
codex plugin add bto-cv@bto-cv-marketplace
codex plugin list --marketplace bto-cv-marketplace --json
```

Start a new chat after an update. If the updater itself is broken, use this recovery path. Do not delete credential stores, disable hook trust or install another BTO copy as a workaround.

What remains your responsibility

Invite colleagues, complete the pilot, handle access/sign-in problems, and publish tested versioned releases. A trusted hook is our update mechanism; it is not a claim that all personal marketplaces have built-in automatic sync. No workspace-admin role is needed for this local hook.

References and evidence

The release includes regression tests for Word generation and update behaviour. Live script checks use the actual private marketplace. Per-user hook trust and lifecycle execution must be checked at onboarding.

[OpenAI: plugin packaging and marketplaces](#)

[OpenAI: hook events and trust review](#)

[OpenAI: Codex CLI installation](#)

[GitHub: browser sign-in with GitHub CLI](#)

[GitHub: configure Git credentials](#)

[GitHub: personal repository permission levels](#)