Kathego kgone

SQL Exercise 2 Fundamentals

(1) SELECT COUNT(ID) AS number_of_employees
FROM employees;

Number_of_employees
10

(2) SELECT department,
Sum(salary) AS total_salary
FROM employees
WHERE department = 'IT'

department	total_salary
IT	22000

(3) SELECT department,
AVG(Salary) AS Average_salary
FROM employees
WHERE department = 'HR';

department	Average_salary
HR	49500

(4) SELECT MAX(salary) AS Highest_salary,
MIN(salary) AS lowest_salary
FROM employees;

Highest_salary	Lowest_salary
62000	48000

(5) SELECT department,
SUM(salary) AS total salary
FROM employees
GROUP BY department;

department	total_salary
IT	22000
HR	99000
Finance	119000
Marketing	105000

(6) SELECT city,
COUNT(*) AS employee_count
FROM employees
GROUP BY city;

city	employee_count
New yorl	2
Chicago	3
Los Angeles	2
San Francisco	2
Houston	1

(7)
```
SELECT department,
       AVG(salary) AS Average_salary
FROM employees
GROUP BY department
ORDER BY average_salary DESC;
```

department	Average_salary
Finance	59500
IT	55000
Marketing	52500
HR	49500

(8)
```
SELECT department,
       Sum(Salary) AS total_salary
FROM employees
GROUP BY department
HAVING SUM(salary) > 100000;
```

department	total_salary
IT	220 000
finance	119 000
Marketing	105 000

(9)
```
SELECT city
       COUNT(ID) AS employee-count
FROM employee
GROUP BY city
HAVING COUNT(ID) >1
ORDER BY employee-count DESC;
```

City	employee_count
Chicago	3
New York	2
Los Angeles	2
San Francisco	2

(10)
```
SELECT department,
       AVG(salary) AS Average_salary
FROM employees
GROUP BY department
ORDER BY Average_salary DESC
LIMIT 1;
```

department	Average_salary
Finance	59500