

PlenorHub Commerce API Guide

For: External ecosystem application developers who need to display products and support ordering.

Version: 2.5

Updated: July 31, 2026

1) Base URLs

- `PLENORHUB_API_BASE_URL = https://api.plenorhub.com/api/v1/`
- `PLENORHUB_SERVER_URL = https://api.plenorhub.com`
- `KCC_ID_BASE_URL = https://auth.bigkpay.com`

All endpoint paths below are relative to `PLENORHUB_API_BASE_URL` unless stated otherwise.

2) API Families

PlenorHub exposes multiple API families, each serving a different type of client.

2.1 Channel Catalog for Display-Only Integrations

These endpoints support product, merchant, and category browsing for ecosystem apps (BigK, Kincore, Shuyi, NumForLife, and future apps).

Catalog membership is **channel-scoped**. Merchants can opt products into extra apps; **BigK always receives new products by default**. Your app only receives products **published** to your channel.

- `/integration/products`
- `/integration/products/{productId}`
- `/integration/merchants`
- `/integration/merchants/{merchantId}`
- `/integration/categories`

Use a use the deployment guide for keys and usage.

2.2 Wallet-Authenticated Commerce APIs

These endpoints support signed-in user flows for wishlist, cart, delivery addresses, checkout, and order history.

- `/app/wishlist/*`
- `/app/cart/*`

- /app/address/delivery/*
- /app/*
- /checkout/*
- /kmall/merchant/access

Guest browse under /app/products and /app/merchants does **not** require a user token. Those browse endpoints return the **BigK** catalog.

2.3 Currency & System Utility APIs

These endpoints support dynamic currency conversion, exchange rate lookup, app version checks, and legal terms retrieval.

- /currencies
- /exchange-rates
- /exchange-rates/convert
- /currencies/price
- /profile/currency
- /app/config
- /legal

2.4 Merchant APIs

Merchant portal APIs (product management, orders, payouts, staff, channel selection) are separate and not the primary focus of this guide.

3) Authentication

3.1 When Authentication is Required

Surface	Auth type	Purpose
/integration/*	Channel API key (not a user JWT)	Identifies your app/channel; scopes catalog to products published for you
/app/products, /app/merchants, /app/categories, /currencies/*,/legal, /app/config	None (guest OK)	Public catalog, currency rates, legal text, app version checks
/app/wishlist/*, /app/cart/*, /app/address/delivery/*, /app/orders,/checkout/*, /profile/currency	User JWT from KCC ID	Commerce actions and user profile preferences for a signed-in wallet user

3.2 Bearer Token Headers

For **user** authenticated requests (wallet), send:

- Authorization: Bearer <access_token>
- Accept: application/json
- Content-Type: application/json

For **channel** catalog requests (/integration/*), send:

- Authorization: Bearer <channel_api_key>
- Accept: application/json

Optional alias: X-Channel-API-Key: <channel_api_key>.

Do not send a KCC ID user JWT to /integration/*.

3.3 Token Issuer

Tokens are issued by KCC ID.

These are the KCC ID endpoints currently used in production:

- POST {KCC_ID_BASE_URL}/kccid/v1/authorize
- POST {KCC_ID_BASE_URL}/kccid/v1/token
- POST {KCC_ID_BASE_URL}/kccid/v1/login

3.3a Login Request Body (/kccid/v1/login)

The password-based login endpoint requires the following JSON body:

```
{
  "identifier": "user@example.com",
  "password": "example-password",
  "client_id": "bigk_wallet",
  "scope": "commerce wallet"
}
```

Field	Type	Required	Notes
identifier	string	yes	The user's email address
password	string	yes	The user's password
client_id	string	yes	OAuth client identifier — see table below
scope	string	recommended	Space-delimited scope string

client_id values:

Client	client_id	Typical scope
Wallet / app users (BigK consumer app)	bigk_wallet	commerce wallet
Merchant portal users	bigk_merchant	openid profile email

The login response includes access_token, id_token, refresh_token, token_type, expires_in, and scope.

3.4 Token Type, Expiry, and Refresh

- Tokens issued by KCC ID are JWT access tokens.
- The token should be treated as opaque in client code; business meaning should not be inferred from claims.
- Access tokens expire after 60 minutes (expires_in: 3600).
- Refresh tokens are supported. POST {KCC_ID_BASE_URL}/kccid/v1/token with grant_type=refresh_token and the current refresh_token value returns a new access token.
- Refresh tokens expire after 30 days of non-use.
- **Token Versioning:** KCC ID issues tokens with a token_version claim. If a user's password is changed or 2FA is modified, the global token version increments. Tokens with older versions will be rejected with 401 Unauthorized.
- **2FA:** For some clients (e.g. BigK Wallet), KCC ID login endpoints may return 2fa_enrollment_required or 2fa_required. Clients must intercept these responses and initiate TOTP authentication.

Example token response from /kccid/v1/token:

```
{
  "access_token": "eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9...",
  "token_type": "Bearer",
  "expires_in": 3600,
  "refresh_token": "def502004b...",
  "scope": "commerce wallet"
}
```

3.5 Required Scopes

The following scopes are required for commerce API access:

- commerce — required for wishlist, cart, checkout, and order endpoints
- wallet — required for KCC direct order placement and KCC discount application

If a token is missing required scopes, PlenorHub returns 403.

When using the PKCE flow (/kccid/v1/authorize), include scope=commerce wallet in the authorization request.

3.6 Integration Guidance

- Access tokens should be treated as opaque and sent to PlenorHub as issued.
- JWT claims should not be parsed in client code to infer business state.
- Token refresh should be implemented before expiry, for example when fewer than 5 minutes remain.
- The preferred production auth flow should be confirmed with the platform owner for the relevant app type.

3.7 What “Wallet-Scoped Token” Means

Wishlist, cart, delivery address, checkout, and customer order endpoints require a token that resolves to a valid wallet context inside PlenorHub.

If a token is valid but cannot be resolved to a wallet-enabled commerce user, PlenorHub may return 403.

3.8 Channel distribution (where products appear)

3.8.1 Purpose

PlenorHub is the **central catalog**. Merchants manage a product once. Each product can be shown on one or more **channels** (apps/storefronts).

channel_key	Surface	Notes
bigk	BigK Wallet / K-Mall (/app/*)	Always included by default for new products
kincore	Kincore app	Opt-in via merchant portal
shuyi	Shuyi lifestyle store	Opt-in
numforlife	NumForLife mall	Opt-in

Your app authenticates with its channel key and receives only products published for that channel. Do not re-implement marketplace filtering on the client.

3.8.2 Visibility rules

A product appears in a channel catalog when:

1. Product status is active or live
2. Merchant status is active
3. The product is **published** to that channel

BigK default: every new product (create, import, or create without channel_keys) is published to **bigk automatically**. Merchants do not need to select BigK for the wallet catalog to receive the product. They can still add Kincore / Shuyi / NumForLife as extra channels.

3.8.3 Channel API keys (production)

Use the key for **your** app. Do not share keys across apps.

App / channel	Channel API key
BigK (bigk)	ph_ch_OI9vI6zWSx5QFa01CxKEZxqvo9HbS1zUphjgD1sP
Kincore (kincore)	ph_ch_72PtGHb4SQeMhuwyiLjT2rRcgXbFP5X5M9PbDz41
Shuyi (shuyi)	ph_ch_4DaKzSIUezQ14360r1AMAOzrKcYrbrPs1EeORIGi
NumForLife (numforlife)	ph_ch_pBp5qiznC5vRtuwxj2HdxJjfX0u2vZnlgj4S6wPB

GET /api/v1/integration/products

Authorization: Bearer ph_ch_72PtGHb4SQeMhuwyiLjT2rRcgXbFP5X5M9PbDz41

Accept: application/json

Optional alias header: X-Channel-API-Key: <channel_api_key>.

Outcome	HTTP
Valid key, active channel	200
Missing / invalid key	401
User JWT sent instead of channel key	401
Channel inactive	403

Example (Kincore):

```
curl -s -H "Authorization: Bearer  
ph_ch_72PtGHb4SQeMhuwyiLjT2rRcgXbFP5X5M9PbDz41" \  
"https://api.plenorhub.com/api/v1/integration/products?per_page=20"
```

Response `meta.channel` should match your app (e.g. "kincore").

3.8.4 How apps should integrate

1. Use the channel API key for your app from the table above.
2. Call only /integration/* with that key (do **not** pass ?channel= — channel is derived from the key).
3. Cache the product list if needed; re-fetch periodically (recommended ≤ 5 minutes for browse).
4. Treat product IDs as PlenorHub IDs.
5. Confirm `meta.channel` in list responses.

Example list response meta:

```
{  
  "meta": {
```

```
    "total": 42,  
    "page": 1,  
    "per_page": 20,  
    "last_page": 3,  
    "channel": "kincore"  
  }  
}
```

3.8.5 BigK wallet catalog (/app/*)

/app/products and /app/merchants return the BigK catalog. New products are published to BigK by default, so they appear in the wallet without extra merchant configuration.

3.8.6 Notes for integrators

- Empty catalog for a channel is valid if no merchant has published products there yet.
 - Stock/price can change; re-fetch before checkout if your app supports ordering.
 - Channel identity comes from the API key, not from client-controlled query parameters.
-

4) Integration Conventions

4.1 Canonical Request Field Names

The following field names are the preferred canonical form for new integrations:

- quantity
- shipping_address
 - shipping_address.state
 - shipping_address.postal_code
 - recipient_name
 - recipient_phone

4.3 Money and Currency Rules

PlenorHub commerce evaluates fiat prices cross-currency using exchange rates updated hourly from live market data (e.g., European Central Bank).

- fiat_price: The raw, exact fiat value configured by the merchant.
- merchant_currency: The merchant's native settlement/reference currency (derived strictly from merchant.base_currency).

- `price / display_price.display.amount`: The dynamically converted price in the buyer's requested currency (e.g., USD), calculated live using the latest hourly exchange rates.
- KCC discount calculations are pegged to USD-based discount logic internally.

4.4 Currency & Exchange Rate Endpoints

PlenorHub provides public and authenticated currency utility endpoints:

4.4.1 List Supported Currencies

- **GET** /currencies

Returns list of active currencies configured on the platform.

```
{
  "success": true,
  "data": [
    {"code": "USD", "name": "US Dollar", "symbol": "$"},
    {"code": "MYR", "name": "Malaysian Ringgit", "symbol": "RM"},
    {"code": "CNY", "name": "Chinese Yuan", "symbol": "¥"}
  ]
}
```

4.4.2 Get Exchange Rates

- **GET** /exchange-rates

Query parameters: - base optional, default USD

```
{
  "success": true,
  "data": {
    "base": "USD",
    "rates": {
      "MYR": 4.45,
      "CNY": 7.22,
      "EUR": 0.92
    },
    "status": "fresh",
    "last_updated": "2026-07-31T12:00:00Z"
  }
}
```

4.4.3 Convert Amount Between Currencies

- **GET** /exchange-rates/convert

Query parameters: - amount required (numeric, >= 0) - from required (3-letter currency code) - to required (3-letter currency code)

```
{
  "success": true,
  "data": {
```



```

    "original": {
      "amount": 100.0,
      "currency": "MYR",
      "formatted": "MYR 100.00"
    },
    "converted": {
      "amount": 22.47,
      "currency": "USD",
      "formatted": "$22.47"
    },
    "rate": 0.2247
  }
}

```

4.4.4 Calculate Display Price

- **GET** /currencies/price

Query parameters: - amount required (numeric, >= 0) - currency required (original currency code) - display optional (target display currency code, default USD)

```

{
  "success": true,
  "data": {
    "original": {
      "amount": 100.0,
      "currency": "MYR",
      "formatted": "MYR 100.00"
    },
    "display": {
      "amount": 22.47,
      "currency": "USD",
      "formatted": "$22.47",
      "is_converted": true
    }
  }
}

```

4.4.5 Update User Display Currency Preference

- **PUT** /profile/currency

Auth: User JWT (kcc.id).

Request body:

```

{
  "currency": "MYR"
}

```

Response:

```
{
  "success": true,
  "message": "Display currency updated",
  "data": {
    "currency": "MYR"
  }
}
```

4.5 Timestamps

When timestamps are returned, they are ISO-8601 strings.

4.6 Pagination

Most paginated endpoints return:

```
{
  "meta": {
    "current_page": 1,
    "per_page": 20,
    "total": 100,
    "last_page": 5
  }
}
```

Standard query parameters for list endpoints:

Parameter	Type	Default	Notes
page	integer	1	Page number
per_page	integer	20	Items per page
sort	string	created_at	Field to sort by (not supported on all endpoints)
order	string	desc	Sort direction: asc or desc
search	string	—	Full-text search (supported where noted)

The public `/integration/*` catalog family may also include `page` for compatibility.

Category filter note: The category query parameter on `/app/products` currently performs a direct equality match against the product category name string. It is not a `category_id` filter and should not be treated as a slug-based filter unless the backend is updated to support that explicitly.

5) Channel Catalog APIs (/integration/*)

These endpoints are intended for display-only third-party integrations.

Auth: channel API key (see deployment guide).

Scope: only products **published** to the calling channel (plus legacy-default rules for bigk during migration).

5.1 List Products

- **GET** /integration/products

Query parameters:

- per_page optional, default 20 (max 100)
- page optional, default 1

Example response:

```
{
  "data": [
    {
      "id": 123,
      "name": "Product name",
      "description": "...",
      "price": 99.5,
      "currency": "KCC",
      "image_url": "https://...",
      "images": ["/storage/products/a.jpg"],
      "category": "Category",
      "category_id": 5,
      "stock": 10,
      "in_stock": true,
      "merchant": {
        "id": 77,
        "name": "Merchant name",
        "slug": "merchant-slug",
        "cashback_rate": 5
      }
    }
  ],
  "meta": {
    "total": 100,
    "page": 1,
    "per_page": 20,
    "last_page": 5
  }
}
```

5.2 Get Product Details

- **GET** /integration/products/{productId}

Possible errors:

- 404 if the product does not exist or is not available in the public catalog

5.3 List Merchants

- **GET** /integration/merchants

Query parameters:

- per_page optional, default 20

Example response:

```
{
  "data": [
    {
      "id": 77,
      "name": "Merchant Name",
      "slug": "merchant-slug",
      "description": "Short description",
      "logo_url": "https://...",
      "banner_url": "https://...",
      "category": "Electronics",
      "cashback_rate": "3.00",
      "product_count": 5
    }
  ],
  "meta": {
    "total": 10,
    "page": 1,
    "per_page": 20
  }
}
```

Note: This endpoint returns banner_url, category, and product_count. It does not include an is_active field (only active merchants are returned). The meta shape uses page (not current_page) and omits last_page.

5.4 Get Merchant Details

- **GET** /integration/merchants/{merchantId}

Returns merchant details plus up to 50 active products.

Example response:

```
{
  "data": {
    "id": 77,
    "name": "Merchant Name",
    "slug": "merchant-slug",
    "description": "Short description",
```

```

    "logo_url": "https://...",
    "banner_url": "https://...",
    "category": "Electronics",
    "cashback_rate": "3.00",
    "products": [
      {
        "id": 123,
        "name": "Product Name",
        "price": "99.50",
        "image_url": "https://...",
        "stock": 10
      }
    ]
  }
}

```

Note: Product objects in this response include price and stock (not in_stock or currency). Only active products are returned.

5.5 List Categories

- **GET** /integration/categories

Example response:

```

{
  "data": [
    {
      "id": 5,
      "name": "Electronics",
      "slug": "electronics"
    }
  ]
}

```

6) Wallet-Authenticated Catalog APIs

These endpoints support authenticated K-Mall browsing.

6.1 List Merchants

- **GET** /app/merchants

Query parameters:

- search optional

6.2 Merchant Details

- **GET** /app/merchants/{merchantId}

6.3 List Categories

- **GET** /app/categories

6.4 List Products

- **GET** /app/products

Query parameters:

- merchant_id optional
- category optional
- search optional
- page optional

6.5 Get Product Details

- **GET** /app/products/{productId}

Product responses in this family are richer than the public /integration/* family. Example response:

```
{
  "data": {
    "id": 123,
    "external_id": "gid://shopify/Product/...",
    "name": "Product Name",
    "description": "Full product description",
    "price": 150.0,
    "token_price": null,
    "fiat_price": 150.0,
    "fiat_currency": "USD",
    "price_currency": "USD",
    "display_price": {
      "original": {
        "amount": 150.0,
        "currency": "USD",
        "formatted": "$150.00"
      },
      "display": {
        "amount": 150.0,
        "currency": "USD",
        "formatted": "$150.00",
        "is_converted": false
      }
    },
    "merchant_price": 150.0,
    "merchant_currency": "USD",
    "category": "Electronics",
    "product_type": "standard",
    "inventory": 50,
    "sku": null,
  },
}
```

```

"status": "live",
"image_url": "https://...",
"images": [
  {"url": "https://...", "type": "image"}
],
"variants": [
  {
    "id": 10,
    "name": "Large / Red",
    "sku": "LRG-RED",
    "price_adjustment": 0.0,
    "stock": 5,
    "attributes": {"size": "Large", "color": "Red"},
    "is_active": true
  }
],
"merchant": {
  "id": 77,
  "name": "Merchant Name",
  "logo_url": "https://...",
  "type": "type_1",
  "base_currency": "USD"
}
}
}

```

Key schema notes: - price and display_price.display.amount represent the dynamically converted value (e.g., USD) using hourly-updated exchange rates against the merchant_currency. - display_price is a nested object with original and display sub-objects — not a scalar. - inventory is the stock count field (not stock). - There is no top-level in_stock boolean or has_variants flag — derive these from inventory > 0 and variants.length > 0. - Variant objects use price_adjustment (the delta from base price) and attributes (key/value object) — not price, fiat_price, in_stock, or options. - images is an array of {url, type} objects — not plain URL strings.

Variant rules: Stock is tracked per variant when a product has active variants. Derive variant availability from variants[].is_active === true and variants[].stock > 0. When a product has active variants, a valid variant_id is required for cart, pricing, checkout, and order operations.

6.6 Pricing Preview

- **POST** /app/pricing/preview

Preferred request body:

```

{
  "items": [
    {
      "product_id": 123,

```

```

    "quantity": 2,
    "variant_id": 10,
    "options": {"color": "red"}
  }
]
}

```

Important behavior:

- all items should belong to the same merchant
- if a product has variants, a valid `variant_id` is required
- stock is validated during preview

Response example:

```

{
  "data": {
    "items": [
      {
        "product_id": 123,
        "name": "Product name",
        "unit_price": 150,
        "quantity": 1,
        "line_total": 150,
        "variant_id": null,
        "variant_name": null,
        "options": null
      }
    ],
    "subtotal": 150,
    "discounts": [],
    "total_discount": 0,
    "final_total": 150,
    "currency": "KCC"
  }
}

```

Note: Each item contains only quantity — the legacy `qty` alias is no longer emitted in the response.

7) Wishlist APIs

7.1 List Wishlist

- **GET** /app/wishlist

Query parameters:

- `per_page` optional, default 20

7.2 Add Item to Wishlist

- **POST** /app/wishlist
`{ "product_id": 123 }`

Responses:

- 201 created
- 409 already in wishlist

7.3 Toggle Wishlist Item

- **POST** /app/wishlist/toggle
`{ "product_id": 123 }`

7.4 Remove Wishlist Item

- **DELETE** /app/wishlist/{id}

7.5 Check Wishlist State

- **GET** /app/wishlist/check/{productId}
-

8) Cart APIs

8.1 Get Cart

- **GET** /app/cart

Example response:

```
{
  "data": {
    "id": 2,
    "item_count": 1,
    "total": 150,
    "items": [
      {
        "id": 55,
        "product_id": 123,
        "product": {
          "id": 123,
          "name": "Product Name",
          "price": 150.0,
          "image_url": "https://..."
        },
        "variant_id": null,
        "variant": null,
        "quantity": 1,
        "subtotal": 150.0,
        "options": null
      }
    ]
  }
}
```

```
}  
}
```

Schema notes: - The cart object includes a top-level `id` and `item_count` (total quantity across all cart items). - Each item has a nested `product` object with basic fields; `currency`, `merchant_id`, and `in_stock` are not included at the item level. - `subtotal` on each item is the line total (unit price × quantity).

8.2 Get Cart Count

- **GET** /app/cart/count

Example response:

```
{ "count": 3 }
```

8.3 Add Item

- **POST** /app/cart/items

Preferred request body:

```
{  
  "product_id": 123,  
  "quantity": 2,  
  "variant_id": 10,  
  "options": {"color": "red"}  
}
```

8.4 Update Quantity

- **PUT** /app/cart/items/{itemId}
- ```
{ "quantity": 1 }
```

If quantity is set to 0, the item is removed.

## 8.5 Remove Item

- **DELETE** /app/cart/items/{itemId}

## 8.6 Clear Cart

- **DELETE** /app/cart

## 8.7 Cart Merchant Constraint

Partners should treat cart and checkout as single-merchant flows.

Do not assume a multi-merchant cart can be checked out in a single session.

---

# 9) Delivery Address Management APIs

These endpoints allow signed-in wallet users to save and manage shipping addresses.

**Auth:** User JWT (kcc.id).

### 9.1 List Delivery Addresses

- **GET** /app/address/delivery

Response:

```
{
 "success": true,
 "data": [
 {
 "id": 12,
 "wallet_id": 45,
 "label": "Home",
 "recipient_name": "Jane Doe",
 "phone": "+60123456789",
 "country_code": "MY",
 "state": "WP Kuala Lumpur",
 "city": "Kuala Lumpur",
 "street_line1": "123 Main Street",
 "street_line2": "Apt 4B",
 "postal_code": "50000",
 "is_default": true,
 "created_at": "2026-03-25T10:00:00Z"
 }
]
}
```

### 9.2 Save Delivery Address (Create or Update)

- **POST** /app/address/delivery

Request body:

```
{
 "id": 12,
 "label": "Home",
 "recipient_name": "Jane Doe",
 "phone": "+60123456789",
 "country_code": "MY",
 "state": "WP Kuala Lumpur",
 "city": "Kuala Lumpur",
 "street_line1": "123 Main Street",
 "street_line2": "Apt 4B",
 "postal_code": "50000",
 "is_default": true
}
```

| Field | Type    | Required | Notes                                    |
|-------|---------|----------|------------------------------------------|
| id    | integer | optional | Omit to create a new address; include to |

| Field          | Type    | Required | Notes                                                                     |
|----------------|---------|----------|---------------------------------------------------------------------------|
|                |         |          | update existing address                                                   |
| label          | string  | optional | Max 50 chars (e.g. "Home", "Work")                                        |
| recipient_name | string  | yes      | Max 255 chars                                                             |
| phone          | string  | yes      | Max 50 chars                                                              |
| country_code   | string  | yes      | 2-letter ISO country code (e.g. MY, US, CN)                               |
| state          | string  | yes      | State or province (max 100 chars)                                         |
| city           | string  | yes      | City name (max 100 chars)                                                 |
| street_line1   | string  | yes      | Street address line 1 (max 255 chars)                                     |
| street_line2   | string  | optional | Street address line 2 (max 255 chars)                                     |
| postal_code    | string  | yes      | Postal or ZIP code (max 20 chars)                                         |
| is_default     | boolean | optional | Default false. Setting true automatically unsets other default addresses. |

Response:

```
{
 "success": true,
 "message": "Address saved",
 "data": { "id": 12, "is_default": true }
}
```

### 9.3 Delete Delivery Address

- **DELETE** /app/address/delivery/{id}

Response:

```
{
 "success": true,
 "message": "Address deleted"
}
```

## 10) Checkout APIs (Stripe )

These endpoints support card/fiat checkout through Stripe.

### 10.1 Shipping Rates

- **POST** /checkout/shipping-rates

Actual request body accepted today:

```
{
 "merchant_id": 77,
 "items": [
 {"product_id": 123, "quantity": 2}
],
 "shipping_address": {
 "recipient_name": "Jane Doe",
 "recipient_phone": "+60123456789",
 "address": "123 Street",
 "city": "Kuala Lumpur",
 "state": "WP Kuala Lumpur",
 "postal_code": "50000",
 "country": "MY"
 }
}
```

Client-side normalization may continue to use recipient\_name / recipient\_phone / postal\_code. This route currently validates name and zip.

Shipping response values are returned in the buyer display/payment currency when conversion is needed.

### 10.2 Preview Order Totals

- **POST** /checkout/preview

Supports either:

- items[] cart-style mode
- single-item compatibility mode using product\_id and quantity

Preferred request body:

```
{
 "items": [
 {"product_id": 123, "quantity": 2, "variant_id": 10}
],
 "shipping_option_id": 5,
 "apply_kcc_discount": true,
 "kcc_amount": 100
}
```

The response includes:

- buyer/payment-side totals
- merchant-side totals
- FX metadata
- KCC discount eligibility details

**Important:** This endpoint requires the authenticated user to have a linked BigK wallet. If PlenorHub cannot resolve that wallet, the server returns 404 wallet not found. The token is expected to be issued for the `bigk_wallet` client, and the user account must already have an active wallet on the BigK side.

Example response:

```
{
 "data": {
 "subtotal": 150.0,
 "shipping_fee": 5.0,
 "discount_usd_amount": 0,
 "discount_kcc_amount": 0,
 "total": 155.0,
 "currency": "USD",
 "merchant_subtotal": 150.0,
 "merchant_shipping": 5.0,
 "merchant_total": 155.0,
 "merchant_currency": "USD",
 "fx_rate": null,
 "fx_source": null,
 "can_apply_discount": false,
 "discount_details": {}
 }
}
```

### 10.3 Create Checkout Session

- **POST** /checkout/create-session

Required:

- `items[]` or `product_id` plus quantity
- `shipping_address`
- `shipping_rate`
- `success_url`
- `cancel_url`

Example:

```
{
 "items": [
 {"product_id": 123, "quantity": 2, "variant_id": 10}
],
 "shipping_address": {
 "recipient_name": "Jane Doe",
```

```

 "recipient_phone": "+60123456789",
 "address": "123 Street",
 "city": "Kuala Lumpur",
 "state": "WP Kuala Lumpur",
 "postal_code": "50000",
 "country": "MY"
 },
 "shipping_rate": {
 "id": "rate_abc",
 "amount": 10.0,
 "shipping_option_id": 5,
 "is_live_rate": false
 },
 "apply_kcc_discount": true,
 "kcc_amount": 100,
 "success_url": "https://app.example.com/checkout/success",
 "cancel_url": "https://app.example.com/checkout/cancel"
}

```

Response:

```

{
 "session_id": "cs_test_...",
 "checkout_url": "https://checkout.stripe.com/..."
}

```

#### 10.4 Verify Payment

- **GET** /checkout/verify/{sessionId}

Example response:

```

{
 "status": "paid",
 "order_number": "PH-123456",
 "state": "confirmed"
}

```

#### 10.5 Retry Guidance

The current backend does not advertise a server-enforced Idempotency-Key contract for checkout creation or KCC direct orders.

Recommended behavior:

- prevent duplicate taps/submissions client-side
- do not blindly retry POST /checkout/create-session after a network timeout
- strong deduplication requirements should be handled by backend orchestration with request correlation rules.

## 10.6 Shipping Semantics

shipping\_rate may include:

- id required — a PlenorHub-generated shipping rate identifier returned by /checkout/shipping-rates
- amount required
- shipping\_option\_id optional — present for merchant-configured fixed shipping options
- is\_live\_rate optional — true when the rate was verified against an external carrier at quote time

**Quote validity:** Treat shipping quotes as advisory and valid for the current session only. Fetch rates again right before calling /checkout/create-session. Do not cache or reuse a rate across separate checkout attempts.

**Rate source:** id values are generated by PlenorHub, not by an external carrier. Pass the full shipping\_rate object from the rates response into session creation unchanged.

## 10.7 Currency Semantics for Checkout

Stripe checkout uses buyer/payment currency for charge display and session creation.

PlenorHub also stores merchant-side totals for settlement/reference.

## 10.8 KCC Discount Semantics

KCC discount eligibility is controlled by platform settings and product-level discount support.

Today, that means:

- KCC discount logic is pegged using kcc\_per\_usd
  - the platform enforces a minimum Stripe charge
  - the maximum usable discount is limited by:
    - wallet balance
    - max discount percent
    - minimum Stripe charge floor
  - products may disallow KCC discount entirely
- 

## 11) Orders APIs (KCC direct)

### 11.1 Place Order from KCC Balance

- **POST** /app/orders



Actual request body accepted today:

```
{
 "items": [
 {
 "product_id": 123,
 "quantity": 2,
 "variant_id": 10,
 "options": {"color": "red"}
 }
],
 "recipient_name": "Jane Doe",
 "recipient_phone": "+60123456789",
 "shipping_address": "123 Street",
 "city": "Kuala Lumpur",
 "province": "WP Kuala Lumpur",
 "postal_code": "50000"
}
```

Field validation requirements: - items: required array of items - recipient\_name: required string (max 255) - recipient\_phone: required string (max 50) - shipping\_address: required string - city: required string - province: required string - postal\_code: optional string (nullable|string)

Things to keep in mind:

- all items must be from the same merchant
- stock is checked at order placement
- if the product has active variants, a valid variant\_id is required
- payment is taken from the wallet balance immediately

## 11.2 List My Orders

- **GET** /app/orders

Query parameters:

- page optional
- per\_page optional, default 20

Example response:

```
{
 "data": [
 {
 "id": 88,
 "order_number": "PH-000088",
 "state": "confirmed",
 "total": 199.0,
 "currency": "KCC",
 "created_at": "2026-03-25T10:00:00Z"
 }
]
}
```

```

 }
],
 "meta": {
 "current_page": 1,
 "per_page": 20,
 "total": 3,
 "last_page": 1
 }
}

```

### 11.3 Get One Order

- **GET** /app/orders/{orderId}

Example response:

```

{
 "data": {
 "id": 88,
 "order_number": "KCC260314F30D",
 "state": "confirmed",
 "total": 72.79,
 "currency": "USD",
 "channel": "type_1_app",
 "placed_at": "2026-03-14T04:04:16+00:00",
 "merchant_amount": 500.0,
 "merchant_currency": "CNY",
 "display_amount": 72.79,
 "display_currency": "USD",
 "fx_rate": 0.145582,
 "fx_source": null,
 "can_apply_discount": false,
 "discount_details": {}
 }
}

```

**Schema notes:** - The `placed_at` timestamp replaces `created_at`. - A `channel` field indicates the order source (e.g. `type_1_app`). - A top-level merchant object (`id`, `name`) is included. - A customer object (`name`, `handle`, `email`, `phone`) is included.

Legacy aliases such as top-level `status` are no longer emitted in canonical order or shipment payloads. Clients should read lifecycle state from `state`.

### 11.4 Order State Guidance

For client display, treat these as the main lifecycle concepts:

- `pending`
- `confirmed`
- `processing`

- dispatched
- delivered
- cancelled
- refunded

---

## 12) Dispute & Refund APIs

These endpoints support the dispute and return lifecycle for orders.

### 12.1 List My Disputes (Buyer)

- **GET** /app/disputes

Returns paginated list of disputes opened by the authenticated wallet user.

Response includes dispute ID, external\_id, status (pending\_merchant, escalated, resolved\_buyer, resolved\_seller, cancelled), order details, requested amount, and timeline.

### 12.2 Open Dispute (Buyer)

- **POST** /app/disputes
- **Preconditions:**
  - Order must belong to the caller's wallet.
  - Order state must be dispatched or delivered.
  - Dispute must be opened within **30 days** of order placement.
  - Requested refund amount cannot exceed order total.

- **Request Body:**

```
{
 "order_id": 88,
 "reason": "damaged_item",
 "explanation": "Item arrived broken.",
 "requested_amount": 72.79,
 "refund_type": "full",
 "evidence_urls": ["https://..."]
}
```

- **Response:**

```
{
 "message": "Dispute opened successfully.",
 "data": {
 "id": 12,
 "external_id": "uuid-string",
 "status": "pending_merchant"
 }
}
```

```
}
}
```

### 12.3 Get Dispute Detail

- **GET** /app/disputes/{disputeId} (Buyer)
- **GET** /kmall/merchant/{merchantId}/disputes/{disputeId} (Seller)
- **GET** /disputes/{disputeId} (Platform Admin)
- **Response:** Includes order details, merchant details, current status, message timeline, and evidence attachments.

### 12.4 Send Message on Dispute

- **POST** /app/disputes/{disputeId}/messages (Buyer)
- **POST** /kmall/merchant/{merchantId}/disputes/{disputeId}/messages (Seller)
- **Request Body:**

```
{
 "message": "Here is additional context...",
 "attachments": ["https://..."]
}
```

### 12.5 Escalate Dispute

- **POST** /app/disputes/{disputeId}/escalate (Buyer)
- **Purpose:** Escalates the dispute to a Platform Admin for final arbitration. Updates status to escalated.
- **Note:** Disputes that remain in pending\_merchant status for more than 48 hours are automatically escalated by the platform.

### 12.6 Cancel Dispute

- **POST** /app/disputes/{disputeId}/cancel (Buyer)
- **Purpose:** Buyer closes the dispute. Updates status to cancelled.

### 12.7 Upload Dispute Evidence

- **POST** /app/disputes/upload (Buyer)
- **Request:** Multi-part file upload with image.
- **Response:** Returns the hosted image URL.

### 12.8 Merchant Dispute Response

- **POST** /kmall/merchant/{merchantId}/disputes/{disputeId}/respond (Seller)
- **Request Body:**

```
{
 "response": "accept_refund", // or "decline"
 "notes": "Agreeing to refund request."
}
```

- **Financial Rule:** When a merchant accepts a refund (or a platform admin rules in favor of the buyer), if the order was already delivered and credited, the refunded

amount is proportionally deducted from the merchant's available balance and total earnings.

## 12.9 Refund Financial Policy (Split Return)

If a purchase was made using a combination of credit card/fiat (via Stripe) and KCC Coins, refunds are split proportionally. The credit card portion is returned to Stripe, and the KCC portion is returned directly to the user's wallet.

---

## 13) Merchant Access & Public Application Check

### 13.1 Check Merchant Access

- **GET** /kmail/merchant/access

Returns whether the authenticated user has merchant access and which merchant links exist.

Related wallet-app merchant application routes:

- **GET** /app/merchant-applications/me
- **POST** /app/merchant-applications

### 13.2 Public Merchant Application & Status Check

Public application routes (accessible without auth):

- **POST** /merchant-applications — Submit new merchant application.
- **GET** /merchant-applications/status — Check application status.

Query parameters for status check: - email string - reference\_number optional string

---

## 14) App Configuration & Legal APIs

### 14.1 App Configuration

- **GET** /app/config

Returns platform operational rules, version limits, and maintenance state.

```
{
 "data": {
 "min_app_version": "1.0.0",
 "latest_version": "1.2.0",
 "maintenance_mode": false
 }
}
```

## 14.2 Legal Content

- **GET** /legal

Returns current Terms of Service and Privacy Policy contents.

```
{
 "data": {
 "terms": "...",
 "privacy": "...",
 "last_updated": "2026-07-31"
 }
}
```

---

## 15) Standard Schemas

### 15.1 Address Object

Preferred client-side shape:

```
{
 "recipient_name": "Jane Doe",
 "recipient_phone": "+60123456789",
 "address": "123 Street",
 "city": "Kuala Lumpur",
 "state": "WP Kuala Lumpur",
 "postal_code": "50000",
 "country": "MY"
}
```

### 15.2 Error Object

Suggested client handling target:

```
{
 "message": "Validation failed",
 "code": "VALIDATION_ERROR",
 "errors": {
 "shipping_address.state": ["The shipping_address.state field is required."]
 }
}
```

For KCC direct purchase, call **POST** /app/orders For card/fiat purchase, use /checkout/shipping-rates, /checkout/preview, /checkout/create-session, and /checkout/verify/{sessionId}

---

## 16) Platform Admin Moderation & Payout APIs

These endpoints are used by Platform Admins (plenorhub\_admin or super\_admin role) under /admin/.\*.

### 16.1 Merchant Applications (Pending Sellers)

- **GET** /admin/merchant-applications — List applications. Use query parameter status=pending to filter pending sellers.
- **GET** /admin/merchant-applications/stats — Retrieve count statistics of merchant applications by status.
- **POST** /admin/merchant-applications/{id}/approve — Approve an application. This creates the merchant, sets up temporary credentials, and registers their identity on KCC ID.
- **POST** /admin/merchant-applications/{id}/reject — Reject an application. Requires reason and optional admin\_notes in the request body.

### 16.2 Merchant Payouts & Stats

- **GET** /admin/payouts — List merchant payout requests.
- **GET** /admin/payouts/stats — Retrieve platform payout stats.
  - **Sample JSON Response:** ``json { "data": { "pending\_count": 5, "completed\_count": 12, "rejected\_count": 2, "processing\_count": 1, "total\_requested\_usd": 1450.50 } }
  - **POST** /admin/payouts/{id}/approve — Approve a payout.
  - **POST** /admin/payouts/{id}/reject — Reject a payout. Requires reason in the request body.

### 16.3 Dispute Arbitration (Platform Admin)

- **GET** /admin/disputes — List all escalated disputes across all merchants.
- **GET** /admin/disputes/{id} — View dispute details and timeline.
- **POST** /admin/disputes/{id}/arbitrate — Execute final platform arbitration decision.
  - **Request Body:**

```
{
 "action": "refund_buyer", // or "reject_dispute"
 "notes": "Seller failed to provide valid proof of delivery.",
 "refund_amount": 72.79 // optional override; defaults to full
 requested dispute amount
}
```

### 16.4 Merchant Invitations

- **POST** /admin/merchants/invite — Send email invitation for merchant registration.

- Request body: {"email": "merchant@example.com", "merchant\_name": "Acme Store"}
  - **GET** /admin/invitations — List active invitations.
  - **DELETE** /admin/invitations/{id} — Cancel a pending invitation.
- 

## 17) Partner implementation notes

- Use decimal-safe handling for money values
  - Do not assume one endpoint family uses the same response shape as another
  - Do not assume /app/\* means anonymous access
  - Treat preview totals as provisional until checkout completion is confirmed
  - Prefer server-side checkout/session orchestration for partner applications where possible
- 

**Document owner:** Munene