

# Training Neural Network

## Deep Learning (DSE316/616)

Vinod K Kurmi  
*Assistant Professor, DSE*

Indian Institute of Science Education and Research Bhopal

Aug 08, 2022




# Disclaimer

- Much of the material and slides for this lecture were borrowed from
  - Bernhard Schölkopf's MLSS 2017 lecture,
  - Tommi Jaakkola's 6.867 class,
  - CMP784: Deep Learning Fall 2021 Erkut Erdem Hacettepe University
  - Fei-Fei Li, Andrej Karpathy and Justin Johnson's CS231n class
  - Hongsheng Li's ELEG5491 class


## Previous Class: Recap

- Machine learning is '*Function Estimation*' .
- Assumptions:  $y = f(x)$ .
- Given:  $D = \{(x_1^{train}, y_1), (x_2^{train}, y_2), \dots (x_n^{train}, y_n)\}$ .




## Previous Class: Recap

- Machine learning is '*Function Estimation*' .
- Assumptions:  $y = f(x)$ .
- Given:  $D = \{(x_1^{train}, y_1), (x_2^{train}, y_2), \dots (x_n^{train}, y_n)\}$ .




Not a function



A function


## Previous Class: Recap

- Machine learning is '*Function Estimation*' .
- Assumptions:  $y = f(x)$ .
- Given:  $D = \{(x_1^{train}, y_1), (x_2^{train}, y_2), \dots (x_n^{train}, y_n)\}$ .



# Previous Class: Recap

- Example of Image classification problem and challenges i.e : viewpoint variation, illumination, occlusion etc.



## Previous Class: Recap

Suppose: 3 training examples, 3 classes. With some  $W$  the scores are:



cat	<b>3.2</b>	1.3	2.2
car	5.1	<b>4.9</b>	2.5
frog	-1.7	2.0	<b>-3.1</b>
Losses:	2.9	0	10.9

### Multiclass SVM loss:

- Given an example  $\{(x_i, y_i)\}$  where  $x_i$  is the image and where  $y_i$  is the (integer) label, and using the shorthand for the scores vector:  $s_i = f(x_i, W)$

the SVM loss has the form:

$$\mathcal{L}_i = \sum_{i \neq j} \max(0, s_j - s_{y_i} + 1)$$

$$\mathcal{L} = \frac{1}{N} \sum_{i=1}^N \mathcal{L}_i$$

$$\mathbf{L} = (2.9 + 0 + 10.9)/3$$

# Previous Class: Recap of Perceptron

- Neuron preactivations (or input activation)

$$a(x) = b + \sum_i w_i x_i = w^T X$$

- Neuron output activation:


$$h(x) = g(a(x)) = g(b + \sum_i w_i x_i)$$

where

$w$  are the weights (parameters)

$b$  is ht bias term

$g(\cdot)$  is the activation function





## Previous Class: Recap of Perceptron

- Neuron preactivations (or input activation)

$$a(x) = b + \sum_i w_i x_i = w^T X$$

- Neuron output activation:


$$h(x) = g(a(x)) = g(b + \sum_i w_i x_i)$$

where

$w$  are the weights (parameters)

$b$  is ht bias term

$g(\cdot)$  is the activation function



## Previous Class: Recap of activation functions

- Linear Activation Function
- Sigmoid
- Hyperbolic Tangent ( $\tanh$ ) Activation Function
- ReLu

### Multi-Output Perceptron

- Softmax activation function at the output

## Previous Class: Recap of activation functions

- Linear Activation Function
- Sigmoid
- Hyperbolic Tangent ( $\tanh$ ) Activation Function
- ReLu

### Multi-Output Perceptron

- Softmax activation function at the output

## Previous Class: Recap of activation functions

- Linear Activation Function
- Sigmoid
- Hyperbolic Tangent ( $\tanh$ ) Activation Function
- ReLu

### Multi-Output Perceptron

- Softmax activation function at the output

## Previous Class: Recap of activation functions

- Linear Activation Function
- Sigmoid
- Hyperbolic Tangent ( $\tanh$ ) Activation Function
- ReLu

### Multi-Output Perceptron

- Softmax activation function at the output

## Previous Class: Recap of activation functions

- Linear Activation Function
- Sigmoid
- Hyperbolic Tangent ( $\tanh$ ) Activation Function
- ReLu

### Multi-Output Perceptron

- Softmax activation function at the output

# Previous Class: Multi-Layer Perceptron (MLP)

- Consider a network with  $L$  hidden layers

- layer pre-activation for  $k > 1$


$$a^{(k)}(x) = b^{(k)} + W^{(k)} h^{(k-1)}(x)$$

- hidden layer activation from 1 to  $L$

$$h^{(k)}(x) = g(a^{(k)}(x))$$

- output layer activation  
( $k=L+1$ )

$$h^{(L+1)}(x) = o(a^{(L+1)}(x)) = f(x)$$



# Example Problem: Will my flight be delayed?

- Temperature: -20 F
- Wind Speed: 45 mph






# Example Problem: Will my flight be delayed?


- Temperature: -20 F
- Wind Speed: 45 mph




# Example Problem: Will my flight be delayed?




# Example Problem: Will my flight be delayed?




# Example Problem: Will my flight be delayed?



# Example Problem: Will my flight be delayed?




# Quantifying Loss




$$\ell(\underbrace{f(\mathbf{x}^{(i)}; \theta)}_{\text{Predicted}}, \underbrace{y^{(i)}}_{\text{Actual}})$$

# Quantifying Loss



$$\ell(\underbrace{f(\mathbf{x}^{(i)}; \theta)}_{\text{Predicted}}, \underbrace{y^{(i)}}_{\text{Actual}})$$

# Quantifying Loss




$$\ell(\underbrace{f(\mathbf{x}^{(i)}; \theta)}_{\text{Predicted}}, \underbrace{y^{(i)}}_{\text{Actual}})$$



# Total Loss

Input

[  
[-20, 45],  
[80, 0],  
[4, 15],  
[45, 60],  
]



Predicted

[  
**0.05**  
**0.02**  
**0.96**  
**0.35**  
]

Actual


[  
**1**  
**0**  
**1**  
**1**  
]

$$J(\theta) = \frac{1}{N} \sum_i \ell(\underbrace{f(\mathbf{x}^{(i)}; \theta)}_{\text{Predicted}}, \underbrace{y^{(i)}}_{\text{Actual}})$$

# Total Loss

Input

[  
[-20, 45],  
[80, 0],  
[4, 15],  
[45, 60],  
]



Predicted      Actual


[	[
<b>0.05</b>	<b>1</b>
0.02	0
0.96	1
<b>0.35</b>	<b>1</b>
]	]

$$J(\theta) = \frac{1}{N} \sum_i \ell(\underbrace{f(\mathbf{x}^{(i)}; \theta)}_{\text{Predicted}}, \underbrace{y^{(i)}}_{\text{Actual}})$$

# Binary Cross Entropy Loss

Input

[  
[-20, 45],  
[80, 0],  
[4, 15],  
[45, 60],  
]



Predicted

Actual

<u>Predicted</u>	<u>Actual</u>
[	[
0.05	1
0.02	0
0.96	1
0.35	1
]	]


$$\mathcal{J}_{cross-entropy}(\theta) = \frac{1}{N} \sum_i y^{(i)} \log(f(\mathbf{x}^{(i)}; \theta)) + (1 - y^{(i)}) \log(1 - f(\mathbf{x}^{(i)}; \theta))$$

- For classification problems with a softmax output layer.
- Maximize log-probability of the correct class given an input

# Mean Square Error Loss

Input

[  
[-20, 45],  
[80, 0],  
[4, 15],  
[45, 60],  
]



Predicted

Actual

[	[
0.05	1
0.02	0
0.96	1
0.35	1
]	]


$$\mathcal{J}_{MSE}(\theta) = \frac{1}{N} \sum_i (f(\mathbf{x}^{(i)}; \theta) - y^{(i)})^2$$

# Training

$$\mathcal{J}(\theta) = \frac{1}{N} \sum_i l(\underbrace{f(\mathbf{x}^{(i)}; \theta)}_{\text{Predicted}}, \underbrace{y^{(i)}}_{\text{Actual}})$$
$$\theta = W1, W2, W3...$$


- Learning is cast as optimization.
  - For classification problems, we would like to minimize classification error
  - Loss function can sometimes be viewed as a surrogate for what we want to optimize (e.g. upper bound)

# Loss is a function of the model's parameters




# How to minimize loss?

Start at random point




# How to minimize loss?






# How to minimize loss?

Move in direction opposite of gradient to new point




# How to minimize loss?




# Stochastic Gradient Descent (SGD)

- Initialize  $\theta$  randomly
- For N Epochs
  - For each training example  $(x, y)$ :
    - Compute Loss Gradient:  $\frac{\partial \mathcal{J}(\theta)}{\partial \theta}$
    - Update  $\theta$  with update rule:
$$\theta = \theta - \eta \frac{\partial \mathcal{J}(\theta)}{\partial \theta}$$



# Gradient Descent (SGD)

- Initialize  $\theta$  randomly
- For N Epochs
  - For each training example  $(\mathbf{x}, y)$ :
    - Compute Loss Gradient:  $\frac{\partial \mathcal{J}(\theta)}{\partial \theta}$
    - Update  $\theta$  with update rule:  
$$\theta = \theta - \eta \frac{\partial \mathcal{J}(\theta)}{\partial \theta}$$



# Stochastic Gradient Descent?

- Initialize  $\theta$  randomly
- For N Epochs
  - For each training batch  $\{(x_0, y_0), (x_1, y_1), \dots (x_B, y_B)\}$ :

Compute Loss

Gradient

$\theta_{t+1} = \theta_t - \eta \nabla_{\theta} L(\theta_t)$

Update  $\theta$  with negative

rate  $\eta \rightarrow \theta_t - \eta \nabla_{\theta} L(\theta_t)$

## Advantages

- More accurate estimation of gradient
  - Smoother convergence
  - Allows for larger learning rates
- Minibatches lead to fast training!
  - Can parallelize computation

# Stochastic Gradient Descent?

- Initialize  $\theta$  randomly
- For N Epochs
  - For each training batch  $\{(x_0, y_0), (x_1, y_1), \dots (x_B, y_B)\}$ :
    - Compute Loss
    - Gradient:  

$$\frac{\partial \mathcal{J}(\theta)}{\partial \theta} = \frac{1}{B} \sum_i \frac{\partial \mathcal{J}_i(\theta)}{\partial \theta}$$
    - Update  $\theta$  with update rule:  $\theta = \theta - \eta \frac{\partial \mathcal{J}(\theta)}{\partial \theta}$

## Advantages

- More accurate estimation of gradient
  - Smoother convergence
  - Allows for larger learning rates
- Minibatches lead to fast training!
  - Can parallelize computation

# Stochastic Gradient Descent?

- Initialize  $\theta$  randomly
- For N Epochs
  - For each training batch  $\{(x_0, y_0), (x_1, y_1), \dots (x_B, y_B)\}$ :
    - Compute Loss
    - Gradient:  

$$\frac{\partial \mathcal{J}(\theta)}{\partial \theta} = \frac{1}{B} \sum_i \frac{\partial \mathcal{J}_i(\theta)}{\partial \theta}$$
    - Update  $\theta$  with update rule:  $\theta = \theta - \eta \frac{\partial \mathcal{J}(\theta)}{\partial \theta}$

## Advantages

- More accurate estimation of gradient
  - Smoother convergence
  - Allows for larger learning rates
- Minibatches lead to fast training!
  - Can parallelize computation

# Stochastic Gradient Descent?

- Initialize  $\theta$  randomly
- For N Epochs
  - For each training batch  $\{(x_0, y_0), (x_1, y_1), \dots (x_B, y_B)\}$ :
    - Compute Loss
    - Gradient:  

$$\frac{\partial \mathcal{J}(\theta)}{\partial \theta} = \frac{1}{B} \sum_i \frac{\partial \mathcal{J}_i(\theta)}{\partial \theta}$$
    - Update  $\theta$  with update rule:  $\theta = \theta - \eta \frac{\partial \mathcal{J}(\theta)}{\partial \theta}$

## Advantages

- More accurate estimation of gradient
  - Smoother convergence
  - Allows for larger learning rates
- Minibatches lead to fast training!
  - Can parallelize computation



# Stochastic Gradient Descent?

- Initialize  $\theta$  randomly
- For N Epochs
  - For each training batch  $\{(x_0, y_0), (x_1, y_1), \dots (x_B, y_B)\}$ :
    - Compute Loss
    - Gradient:  

$$\frac{\partial \mathcal{J}(\theta)}{\partial \theta} = \frac{1}{B} \sum_i \frac{\partial \mathcal{J}_i(\theta)}{\partial \theta}$$
    - Update  $\theta$  with update rule:  $\theta = \theta - \eta \frac{\partial \mathcal{J}(\theta)}{\partial \theta}$

## Advantages

- More accurate estimation of gradient
  - Smoother convergence
  - Allows for larger learning rates
- Minibatches lead to fast training!
  - Can parallelize computation

# Stochastic Gradient Descent (SGD)

- Algorithm that performs updates after each example
  - initialize  $\theta = \{W^{(1)}, b^{(1)} \dots W^{(L+1)}, b^{(L+1)}\}$
  - for  $N$  iterations
    - for each training example  $(x^{(i)}, y^{(i)})$  or batch
      - $\Delta = \nabla_{\theta} \ell(f(x^{(i)}; \theta), y^{(i)})$
- To apply this algorithm to neural network training, we need
  - the loss function  $\ell(f(x^{(i)}; \theta), y^{(i)})$
  - a procedure to compute the parameter gradients  $\nabla_{\theta} \ell(f(x^{(i)}; \theta), y^{(i)})$

# Stochastic Gradient Descent (SGD)

- Algorithm that performs updates after each example
  - initialize  $\theta = \{W^{(1)}, b^{(1)} \dots W^{(L+1)}, b^{(L+1)}\}$
  - for  $N$  iterations
    - for each training example  $(x^{(i)}, y^{(i)})$  or batch
      - $\Delta = \nabla_{\theta} \ell(f(x^{(i)}; \theta), y^{(i)})$
- To apply this algorithm to neural network training, we need
  - the loss function  $\ell(f(x^{(i)}; \theta), y^{(i)})$
  - a procedure to compute the parameter gradients  $\nabla_{\theta} \ell(f(x^{(i)}; \theta), y^{(i)})$

# Stochastic Gradient Descent (SGD)

- Algorithm that performs updates after each example
  - initialize  $\theta = \{W^{(1)}, b^{(1)} \dots W^{(L+1)}, b^{(L+1)}\}$
  - for  $N$  iterations
    - for each training example  $(x^{(i)}, y^{(i)})$  or batch  
 $\Delta = \nabla_{\theta} \ell(f(x^{(i)}; \theta), y^{(i)})$
- To apply this algorithm to neural network training, we need
  - the loss function  $\ell(f(x^{(i)}; \theta), y^{(i)})$
  - a procedure to compute the parameter gradients  $\nabla_{\theta} \ell(f(x^{(i)}; \theta), y^{(i)})$

# Stochastic Gradient Descent (SGD)

- Algorithm that performs updates after each example
  - initialize  $\theta = \{W^{(1)}, b^{(1)} \dots W^{(L+1)}, b^{(L+1)}\}$
  - for  $N$  iterations
    - for each training example  $(x^{(i)}, y^{(i)})$  or batch  
 $\Delta = \nabla_{\theta} \ell(f(x^{(i)}; \theta), y^{(i)})$
- To apply this algorithm to neural network training, we need
  - the loss function  $\ell(f(x^{(i)}; \theta), y^{(i)})$
  - a procedure to compute the parameter gradients  $\nabla_{\theta} \ell(f(x^{(i)}; \theta), y^{(i)})$

# Stochastic Gradient Descent (SGD)

- Algorithm that performs updates after each example
  - initialize  $\theta = \{W^{(1)}, b^{(1)} \dots W^{(L+1)}, b^{(L+1)}\}$
  - for  $N$  iterations
    - for each training example  $(x^{(i)}, y^{(i)})$  or batch  
 $\Delta = \nabla_{\theta} \ell(f(x^{(i)}; \theta), y^{(i)})$
- To apply this algorithm to neural network training, we need
  - the loss function  $\ell(f(x^{(i)}; \theta), y^{(i)})$
  - a procedure to compute the parameter gradients  $\nabla_{\theta} \ell(f(x^{(i)}; \theta), y^{(i)})$

# Stochastic Gradient Descent (SGD)

- Algorithm that performs updates after each example
  - initialize  $\theta = \{W^{(1)}, b^{(1)} \dots W^{(L+1)}, b^{(L+1)}\}$
  - for  $N$  iterations
    - for each training example  $(x^{(i)}, y^{(i)})$  or batch  
 $\Delta = \nabla_{\theta} \ell(f(x^{(i)}; \theta), y^{(i)})$
- To apply this algorithm to neural network training, we need
  - the loss function  $\ell(f(x^{(i)}; \theta), y^{(i)})$
  - a procedure to compute the parameter gradients  $\nabla_{\theta} \ell(f(x^{(i)}; \theta), y^{(i)})$

# Stochastic Gradient Descent (SGD)

- Algorithm that performs updates after each example
  - initialize  $\theta = \{W^{(1)}, b^{(1)} \dots W^{(L+1)}, b^{(L+1)}\}$
  - for  $N$  iterations
    - for each training example  $(x^{(i)}, y^{(i)})$  or batch  
 $\Delta = \nabla_{\theta} \ell(f(x^{(i)}; \theta), y^{(i)})$
- To apply this algorithm to neural network training, we need
  - the loss function  $\ell(f(x^{(i)}; \theta), y^{(i)})$
  - a procedure to compute the parameter gradients  $\nabla_{\theta} \ell(f(x^{(i)}; \theta), y^{(i)})$



# What is a neural network again?

- A family of parametric, non-linear and hierarchical representation learning functions
- $a_L(x; \theta_1, \dots, \theta_L) = h_L(h_{L-1}(\dots h_1(x; \theta_1), \theta_{L-1}); \theta_L)$ 
  - $x$ : input
  - $\theta_l$ : parameter of layer  $l$
  - $a_l = h_l(x; \theta_l)$ : (non)-linear function
- Given training corpus  $X, Y$  find optimal parameters

$$\theta^* = \underset{\theta}{\operatorname{argmin}} \sum_{(x,y) \in (X,Y)} \ell(y, a_L(x; \theta_1, \dots, \theta_L))$$

# What is a neural network again?

- A family of parametric, non-linear and hierarchical representation learning functions
- $a_L(x; \theta_1, \dots, \theta_L) = h_L(h_{L-1}(\dots h_1(x; \theta_1), \theta_{L-1}); \theta_L)$ 
  - $x$ : input
  - $\theta_l$ : parameter of layer  $l$
  - $a_l = h_l(x; \theta_l)$ : (non)-linear function
- Given training corpus  $X, Y$  find optimal parameters

$$\theta^* = \underset{\theta}{\operatorname{argmin}} \sum_{(x,y) \in (X,Y)} \ell(y, a_L(x; \theta_1, \dots, \theta_L))$$

# What is a neural network again?

- A family of parametric, non-linear and hierarchical representation learning functions
- $a_L(x; \theta_1, \dots, \theta_L) = h_L(h_{L-1}(\dots h_1(x; \theta_1), \theta_{L-1}); \theta_L)$ 
  - $x$ : input
  - $\theta_l$ : parameter of layer  $l$
  - $a_l = h_l(x; \theta_l)$ : (non)-linear function
- Given training corpus  $X, Y$  find optimal parameters

$$\theta^* = \underset{\theta}{\operatorname{argmin}} \sum_{(x,y) \in (X,Y)} \ell(y, a_L(x; \theta_1, \dots, \theta_L))$$

# What is a neural network again?

- A family of parametric, non-linear and hierarchical representation learning functions
- $a_L(x; \theta_1, \dots, \theta_L) = h_L(h_{L-1}(\dots h_1(x; \theta_1), \theta_{L-1}); \theta_L)$ 
  - $x$ : input
  - $\theta_l$ : parameter of layer  $l$
  - $a_l = h_l(x; \theta_l)$ : (non)-linear function
- Given training corpus  $X, Y$  find optimal parameters

$$\theta^* = \underset{\theta}{\operatorname{argmin}} \sum_{(x,y) \in (X,Y)} \ell(y, a_L(x; \theta_1, \dots, \theta_L))$$

# What is a neural network again?

- A family of parametric, non-linear and hierarchical representation learning functions
- $a_L(x; \theta_1, \dots, \theta_L) = h_L(h_{L-1}(\dots h_1(x; \theta_1), \theta_{L-1}); \theta_L)$ 
  - $x$ : input
  - $\theta_l$ : parameter of layer  $l$
  - $a_l = h_l(x; \theta_l)$ : (non)-linear function
- Given training corpus  $X, Y$  find optimal parameters

$$\theta^* = \underset{\theta}{\operatorname{argmin}} \sum_{(x,y) \in (X,Y)} \ell(y, a_L(x; \theta_1, \dots, \theta_L))$$


# What is a neural network again?

- A family of parametric, non-linear and hierarchical representation learning functions
- $a_L(x; \theta_1, \dots, \theta_L) = h_L(h_{L-1}(\dots h_1(x; \theta_1), \theta_{L-1}); \theta_L)$ 
  - $x$ : input
  - $\theta_l$ : parameter of layer  $l$
  - $a_l = h_l(x; \theta_l)$ : (non)-linear function
- Given training corpus  $X, Y$  find optimal parameters

$$\theta^* = \underset{\theta}{\operatorname{argmin}} \sum_{(x,y) \in (X,Y)} \ell(y, a_L(x; \theta_1, \dots, \theta_L))$$


# Neural network models

- A neural network model is a series of hierarchically connected functions
- The hierarchy can be very, very complex



# Neural network models


- A neural network model is a series of hierarchically connected functions
- The hierarchy can be very, very complex






# Neural network models

- A neural network model is a series of hierarchically connected functions
- The hierarchy can be very, very complex




# Neural network models

- A neural network model is a series of hierarchically connected functions
- The hierarchy can be very, very complex




# What is a module

- A module is a building block for our network
- Each module is an object/function  $a = h(x; \theta)$  that
  - Contains trainable parameters  $\theta$
  - Receives as an argument an input  $x$
  - And returns an output  $a$  based on the activation function  $h(\dots)$
- The activation function should be (at least) first order differentiable (almost) everywhere
- For easier/more efficient backpropagation
  - store module input
  - easy to get module output fast
  - easy to compute derivatives




# What is a module

- A module is a building block for our network
- Each module is an object/function  $a = h(x; \theta)$  that
  - Contains trainable parameters  $\theta$
  - Receives as an argument an input  $x$
  - And returns an output  $a$  based on the activation function  $h(\dots)$
- The activation function should be (at least) first order differentiable (almost) everywhere
- For easier/more efficient backpropagation
  - store module input
  - easy to get module output fast
  - easy to compute derivatives




# What is a module

- A module is a building block for our network
- Each module is an object/function  $a = h(x; \theta)$  that
  - Contains trainable parameters  $\theta$
  - Receives as an argument an input  $x$
  - And returns an output  $a$  based on the activation function  $h(\dots)$
- The activation function should be (at least) first order differentiable (almost) everywhere
- For easier/more efficient backpropagation
  - store module input
  - easy to get module output fast
  - easy to compute derivatives




# What is a module

- A module is a building block for our network
- Each module is an object/function  $a = h(x; \theta)$  that
  - Contains trainable parameters  $\theta$
  - Receives as an argument an input  $x$
  - And returns an output  $a$  based on the activation function  $h(\dots)$
- The activation function should be (at least) first order differentiable (almost) everywhere
- For easier/more efficient backpropagation
  - store module input
  - easy to get module output fast
  - easy to compute derivatives




# What is a module

- A module is a building block for our network
- Each module is an object/function  $a = h(x; \theta)$  that
  - Contains trainable parameters  $\theta$
  - Receives as an argument an input  $x$
  - And returns an output  $a$  based on the activation function  $h(\dots)$
- The activation function should be (at least) first order differentiable (almost) everywhere
- For easier/more efficient backpropagation
  - store module input
  - easy to get module output fast
  - easy to compute derivatives



# What is a module


- A module is a building block for our network
- Each module is an object/function  $a = h(x; \theta)$  that
  - Contains trainable parameters  $\theta$
  - Receives as an argument an input  $x$
  - And returns an output  $a$  based on the activation function  $h(\dots)$
- The activation function should be (at least) first order differentiable (almost) everywhere
- For easier/more efficient backpropagation
  - store module input
  - easy to get module output fast
  - easy to compute derivatives






# What is a module

- A module is a building block for our network
- Each module is an object/function  $a = h(x; \theta)$  that
  - Contains trainable parameters  $\theta$
  - Receives as an argument an input  $x$
  - And returns an output  $a$  based on the activation function  $h(\dots)$
- The activation function should be (at least) first order differentiable (almost) everywhere
- For easier/more efficient backpropagation
  - store module input
  - easy to get module output fast
  - easy to compute derivatives




# What is a module

- A module is a building block for our network
- Each module is an object/function  $a = h(x; \theta)$  that
  - Contains trainable parameters  $\theta$
  - Receives as an argument an input  $x$
  - And returns an output  $a$  based on the activation function  $h(\dots)$
- The activation function should be (at least) first order differentiable (almost) everywhere
- For easier/more efficient backpropagation
  - store module input
  - easy to get module output fast
  - easy to compute derivatives




# What is a module

- A module is a building block for our network
- Each module is an object/function  $a = h(x; \theta)$  that
  - Contains trainable parameters  $\theta$
  - Receives as an argument an input  $x$
  - And returns an output  $a$  based on the activation function  $h(\dots)$
- The activation function should be (at least) first order differentiable (almost) everywhere
- For easier/more efficient backpropagation
  - store module input
  - easy to get module output fast
  - easy to compute derivatives



# What is a module

- A module is a building block for our network
- Each module is an object/function  $a = h(x; \theta)$  that
  - Contains trainable parameters  $\theta$
  - Receives as an argument an input  $x$
  - And returns an output  $a$  based on the activation function  $h(\dots)$
- The activation function should be (at least) first order differentiable (almost) everywhere
- For easier/more efficient backpropagation
  - store module input
  - easy to get module output fast
  - easy to compute derivatives



# Anything goes or do special constraints exist?

- A neural network is a composition of modules (building blocks)
- Any architecture works
- If the architecture is a **feedforward** cascade, no special care
- If acyclic, there is right order of computing the forward computations
- If there are loops, these form **recurrent** connections (revisited later)

# Anything goes or do special constraints exist?

- A neural network is a composition of modules (building blocks)
- Any architecture works
  - If the architecture is a **feedforward** cascade, no special care
  - If acyclic, there is right order of computing the forward computations
  - If there are loops, these form **recurrent** connections (revisited later)

# Anything goes or do special constraints exist?

- A neural network is a composition of modules (building blocks)
- Any architecture works
- If the architecture is a **feedforward** cascade, no special care
- If acyclic, there is right order of computing the forward computations
- If there are loops, these form **recurrent** connections (revisited later)

# Anything goes or do special constraints exist?

- A neural network is a composition of modules (building blocks)
- Any architecture works
- If the architecture is a **feedforward** cascade, no special care
- If acyclic, there is right order of computing the forward computations
- If there are loops, these form **recurrent** connections (revisited later)




# Anything goes or do special constraints exist?

- A neural network is a composition of modules (building blocks)
- Any architecture works
- If the architecture is a **feedforward** cascade, no special care
- If acyclic, there is right order of computing the forward computations
- If there are loops, these form **recurrent** connections (revisited later)


# What is a module

- Simply compute the activation of each module in the network  $a_l = h_l(x_l; \theta_l)$  where  $x_l = a_{l-1}$ 
  - We need to know the precise function behind each module  $h_l(\dots)$
  - Recursive operations
    - One module's output is another's input
- Steps
  - Visit modules one by one starting from the data input
  - Some modules might have several inputs from multiple modules
- Compute modules activations with the **right order**
  - Make sure all the inputs computed at the right time




# What is a module

- Simply compute the activation of each module in the network  $a_l = h_l(x_l; \theta_l)$  where  $x_l = a_{l-1}$ 
  - We need to know the precise function behind each module  $h_l(\dots)$
  - Recursive operations
    - One module's output is another's input
- Steps
  - Visit modules one by one starting from the data input
  - Some modules might have several inputs from multiple modules
- Compute modules activations with the **right order**
  - Make sure all the inputs computed at the right time




# What is a module

- Simply compute the activation of each module in the network  $a_l = h_l(x_l; \theta_l)$  where  $x_l = a_{l-1}$ 
  - We need to know the precise function behind each module  $h_l(\dots)$
  - Recursive operations
    - One module's output is another's input
- Steps
  - Visit modules one by one starting from the data input
  - Some modules might have several inputs from multiple modules
- Compute modules activations with the **right order**
  - Make sure all the inputs computed at the right time




# What is a module

- Simply compute the activation of each module in the network  $a_l = h_l(x_l; \theta_l)$  where  $x_l = a_{l-1}$ 
  - We need to know the precise function behind each module  $h_l(\dots)$
  - Recursive operations
    - One module's output is another's input
- Steps
  - Visit modules one by one starting from the data input
  - Some modules might have several inputs from multiple modules
- Compute modules activations with the **right order**
  - Make sure all the inputs computed at the right time




# What is a module

- Simply compute the activation of each module in the network  $a_l = h_l(x_l; \theta_l)$  where  $x_l = a_{l-1}$ 
  - We need to know the precise function behind each module  $h_l(\dots)$
  - Recursive operations
    - One module's output is another's input
- Steps
  - Visit modules one by one starting from the data input
  - Some modules might have several inputs from multiple modules
- Compute modules activations with the **right order**
  - Make sure all the inputs computed at the right time




# What is a module

- Simply compute the activation of each module in the network  $a_l = h_l(x_l; \theta_l)$  where  $x_l = a_{l-1}$ 
  - We need to know the precise function behind each module  $h_l(\dots)$
  - Recursive operations
    - One module's output is another's input
- Steps
  - Visit modules one by one starting from the data input
    - Some modules might have several inputs from multiple modules
  - Compute modules activations with the **right order**
    - Make sure all the inputs computed at the right time



# What is a module


- Simply compute the activation of each module in the network  $a_l = h_l(x_l; \theta_l)$  where  $x_l = a_{l-1}$ 
  - We need to know the precise function behind each module  $h_l(\dots)$
  - Recursive operations
    - One module's output is another's input
- Steps
  - Visit modules one by one starting from the data input
  - Some modules might have several inputs from multiple modules
- Compute modules activations with the **right order**
  - Make sure all the inputs computed at the right time






# What is a module

- Simply compute the activation of each module in the network  $a_l = h_l(x_l; \theta_l)$  where  $x_l = a_{l-1}$ 
  - We need to know the precise function behind each module  $h_l(\dots)$
  - Recursive operations
    - One module's output is another's input
- Steps
  - Visit modules one by one starting from the data input
  - Some modules might have several inputs from multiple modules
- Compute modules activations with the **right order**
  - Make sure all the inputs computed at the right time




# What is a module

- Simply compute the activation of each module in the network  $a_l = h_l(x_l; \theta_l)$  where  $x_l = a_{l-1}$ 
  - We need to know the precise function behind each module  $h_l(\dots)$
  - Recursive operations
    - One module's output is another's input
- Steps
  - Visit modules one by one starting from the data input
  - Some modules might have several inputs from multiple modules
- Compute modules activations with the **right order**
  - Make sure all the inputs computed at the right time




# What is a module

- Simply compute the gradients of each module for our data
  - We need to know the gradient formulation of each module  $\partial h_l(x_i; \theta_l)$  w.r.t. their inputs  $x_l$  and parameters  $\theta_l$
- We need the forward computations first
  - Their result is the sum of losses for our input data
- Then take the reverse network (reverse connections) and traverse it backwards
- Instead of using the activation functions, we use their gradients
- The whole process can be described very neatly and concisely with the backpropagation algorithm




# What is a module

- Simply compute the gradients of each module for our data
  - We need to know the gradient formulation of each module  $\partial h_l(x_i; \theta_l)$  w.r.t. their inputs  $x_l$  and parameters  $\theta_l$
- We need the forward computations first
  - Their result is the sum of losses for our input data
- Then take the reverse network (reverse connections) and traverse it backwards
- Instead of using the activation functions, we use their gradients
- The whole process can be described very neatly and concisely with the backpropagation algorithm




# What is a module

- Simply compute the gradients of each module for our data
  - We need to know the gradient formulation of each module  $\partial h_l(x_i; \theta_l)$  w.r.t. their inputs  $x_l$  and parameters  $\theta_l$
- We need the forward computations first
  - Their result is the sum of losses for our input data
- Then take the reverse network (reverse connections) and traverse it backwards
- Instead of using the activation functions, we use their gradients
- The whole process can be described very neatly and concisely with the backpropagation algorithm




# What is a module

- Simply compute the gradients of each module for our data
  - We need to know the gradient formulation of each module  $\partial h_l(x_i; \theta_l)$  w.r.t. their inputs  $x_l$  and parameters  $\theta_l$
- We need the forward computations first
  - Their result is the sum of losses for our input data
- Then take the reverse network (reverse connections) and traverse it backwards
- Instead of using the activation functions, we use their gradients
- The whole process can be described very neatly and concisely with the backpropagation algorithm




# What is a module

- Simply compute the gradients of each module for our data
  - We need to know the gradient formulation of each module  $\partial h_l(x_i; \theta_l)$  w.r.t. their inputs  $x_l$  and parameters  $\theta_l$
- We need the forward computations first
  - Their result is the sum of losses for our input data
- Then take the reverse network (reverse connections) and traverse it backwards
- Instead of using the activation functions, we use their gradients
- The whole process can be described very neatly and concisely with the backpropagation algorithm



# What is a module


- Simply compute the gradients of each module for our data
  - We need to know the gradient formulation of each module  $\partial h_l(x_i; \theta_l)$  w.r.t. their inputs  $x_l$  and parameters  $\theta_l$
- We need the forward computations first
  - Their result is the sum of losses for our input data
- Then take the reverse network (reverse connections) and traverse it backwards
- Instead of using the activation functions, we use their gradients
- The whole process can be described very neatly and concisely with the backpropagation algorithm





# What is a module

- Simply compute the gradients of each module for our data
  - We need to know the gradient formulation of each module  $\partial h_l(x_i; \theta_l)$  w.r.t. their inputs  $x_l$  and parameters  $\theta_l$
- We need the forward computations first
  - Their result is the sum of losses for our input data
- Then take the reverse network (reverse connections) and traverse it backwards
- Instead of using the activation functions, we use their gradients
- The whole process can be described very neatly and concisely with the backpropagation algorithm



# Again, what is a neural network again?

- $a_L(x; \theta_1, \dots, \theta_L) = h_L(h_{L-1}(\dots h_1(x; \theta_1), \theta_{L-1}); \theta_L)$ 
  - $x$ : input
  - $\theta_l$ : parameter of layer  $l$
  - $a_l = h_l(x; \theta_l)$ : (non)-linear function
- Given training corpus  $X, Y$  find optimal parameters

$$\theta^* = \underset{\theta}{\operatorname{argmin}} \sum_{(x,y) \in (X,Y)} \ell(y, a_L(x; \theta_1, \dots, \theta_L))$$

- To use any gradient descent based optimization

$$\theta^{(t+1)} = \theta^t - \eta_t \frac{\partial \mathcal{L}}{\partial \theta_t}$$

- we need the gradients  $\frac{\partial \mathcal{L}}{\partial \theta_l}$ ;  $l = 1, 2, \dots, L$
- How to compute the gradients for such a complicated function enclosing other functions, like  $a_l(\dots)$

# Again, what is a neural network again?

- $a_L(x; \theta_1, \dots, \theta_L) = h_L(h_{L-1}(\dots h_1(x; \theta_1), \theta_{L-1}); \theta_L)$ 
  - $x$ : input
  - $\theta_l$ : parameter of layer  $l$
  - $a_l = h_l(x; \theta_l)$ : (non)-linear function
- Given training corpus  $X, Y$  find optimal parameters

$$\theta^* = \underset{\theta}{\operatorname{argmin}} \sum_{(x,y) \in (X,Y)} \ell(y, a_L(x; \theta_1, \dots, \theta_L))$$

- To use any gradient descent based optimization

$$\theta^{(t+1)} = \theta^t - \eta_t \frac{\partial \mathcal{L}}{\partial \theta_t}$$

- we need the gradients  $\frac{\partial \mathcal{L}}{\partial \theta_l}$ ;  $l = 1, 2, \dots, L$
- How to compute the gradients for such a complicated function enclosing other functions, like  $a_l(\dots)$

# Again, what is a neural network again?

- $a_L(x; \theta_1, \dots, \theta_L) = h_L(h_{L-1}(\dots h_1(x; \theta_1), \theta_{L-1}); \theta_L)$ 
  - $x$ : input
  - $\theta_l$ : parameter of layer  $l$
  - $a_l = h_l(x; \theta_l)$ : (non)-linear function
- Given training corpus  $X, Y$  find optimal parameters

$$\theta^* = \underset{\theta}{\operatorname{argmin}} \sum_{(x,y) \in (X,Y)} \ell(y, a_L(x; \theta_1, \dots, \theta_L))$$

- To use any gradient descent based optimization

$$\theta^{(t+1)} = \theta^t - \eta_t \frac{\partial \mathcal{L}}{\partial \theta_t}$$

- we need the gradients  $\frac{\partial \mathcal{L}}{\partial \theta_l}$ ;  $l = 1, 2, \dots, L$
- How to compute the gradients for such a complicated function enclosing other functions, like  $a_l(\dots)$

# Again, what is a neural network again?

- $a_L(x; \theta_1, \dots, \theta_L) = h_L(h_{L-1}(\dots h_1(x; \theta_1), \theta_{L-1}); \theta_L)$ 
  - $x$ : input
  - $\theta_l$ : parameter of layer  $l$
  - $a_l = h_l(x; \theta_l)$ : (non)-linear function
- Given training corpus  $X, Y$  find optimal parameters

$$\theta^* = \underset{\theta}{\operatorname{argmin}} \sum_{(x,y) \in (X,Y)} \ell(y, a_L(x; \theta_1, \dots, \theta_L))$$

- To use any gradient descent based optimization

$$\theta^{(t+1)} = \theta^t - \eta_t \frac{\partial \mathcal{L}}{\partial \theta_t}$$

- we need the gradients  $\frac{\partial \mathcal{L}}{\partial \theta_l}$ ;  $l = 1, 2, \dots, L$
- How to compute the gradients for such a complicated function enclosing other functions, like  $a_l(\dots)$

# Again, what is a neural network again?

- $a_L(x; \theta_1, \dots, \theta_L) = h_L(h_{L-1}(\dots h_1(x; \theta_1), \theta_{L-1}); \theta_L)$ 
  - $x$ : input
  - $\theta_l$ : parameter of layer  $l$
  - $a_l = h_l(x; \theta_l)$ : (non)-linear function
- Given training corpus  $X, Y$  find optimal parameters

$$\theta^* = \underset{\theta}{\operatorname{argmin}} \sum_{(x,y) \in (X,Y)} \ell(y, a_L(x; \theta_1, \dots, \theta_L))$$

- To use any gradient descent based optimization

$$\theta^{(t+1)} = \theta^t - \eta_t \frac{\partial \mathcal{L}}{\partial \theta_t}$$

- we need the gradients  $\frac{\partial \mathcal{L}}{\partial \theta_l}$ ;  $l = 1, 2, \dots, L$
- How to compute the gradients for such a complicated function enclosing other functions, like  $a_l(\dots)$

# Again, what is a neural network again?

- $a_L(x; \theta_1, \dots, \theta_L) = h_L(h_{L-1}(\dots h_1(x; \theta_1), \theta_{L-1}); \theta_L)$ 
  - $x$ : input
  - $\theta_l$ : parameter of layer  $l$
  - $a_l = h_l(x; \theta_l)$ : (non)-linear function
- Given training corpus  $X, Y$  find optimal parameters

$$\theta^* = \underset{\theta}{\operatorname{argmin}} \sum_{(x,y) \in (X,Y)} \ell(y, a_L(x; \theta_1, \dots, \theta_L))$$

- To use any gradient descent based optimization

$$\theta^{(t+1)} = \theta^t - \eta_t \frac{\partial \mathcal{L}}{\partial \theta_t}$$

- we need the gradients  $\frac{\partial \mathcal{L}}{\partial \theta_l}$ ;  $l = 1, 2, \dots, L$
- How to compute the gradients for such a complicated function enclosing other functions, like  $a_l(\dots)$

# Again, what is a neural network again?

- $a_L(x; \theta_1, \dots, \theta_L) = h_L(h_{L-1}(\dots h_1(x; \theta_1), \theta_{L-1}); \theta_L)$ 
  - $x$ : input
  - $\theta_l$ : parameter of layer  $l$
  - $a_l = h_l(x; \theta_l)$ : (non)-linear function
- Given training corpus  $X, Y$  find optimal parameters

$$\theta^* = \underset{\theta}{\operatorname{argmin}} \sum_{(x,y) \in (X,Y)} \ell(y, a_L(x; \theta_1, \dots, \theta_L))$$

- To use any gradient descent based optimization

$$\theta^{(t+1)} = \theta^t - \eta_t \frac{\partial \mathcal{L}}{\partial \theta_t}$$

- we need the gradients  $\frac{\partial \mathcal{L}}{\partial \theta_l}$ ;  $l = 1, 2, \dots, L$
- How to compute the gradients for such a complicated function enclosing other functions, like  $a_l(\dots)$



# Again, what is a neural network again?

- $a_L(x; \theta_1, \dots, \theta_L) = h_L(h_{L-1}(\dots h_1(x; \theta_1), \theta_{L-1}); \theta_L)$ 
  - $x$ : input
  - $\theta_l$ : parameter of layer  $l$
  - $a_l = h_l(x; \theta_l)$ : (non)-linear function
- Given training corpus  $X, Y$  find optimal parameters

$$\theta^* = \underset{\theta}{\operatorname{argmin}} \sum_{(x,y) \in (X,Y)} \ell(y, a_L(x; \theta_1, \dots, \theta_L))$$

- To use any gradient descent based optimization

$$\theta^{(t+1)} = \theta^t - \eta_t \frac{\partial \mathcal{L}}{\partial \theta_t}$$

- we need the gradients  $\frac{\partial \mathcal{L}}{\partial \theta_l}$ ;  $l = 1, 2, \dots, L$
- How to compute the gradients for such a complicated function enclosing other functions, like  $a_l(\dots)$

# backpropagation examples and optimizers

Next Class..