Mini Task Tracker

Goal

Build a menu-based Python Task Tracker that stores tasks in a JSON file and reloads the saved tasks when run again.

Features

- **Add** — ask for a task title and store it as Pending.
- **View** — show a numbered task list with Pending or Done.
- **Complete** — select a task number and mark its `done` field `True`.
- **Delete** — select a task number and remove that task.
- **Save and Load** — save the list to `tasks.json` with `json.dump()`, load it with `json.load()` at startup.
- **Menu** — keep showing choices until the user selects Exit.
- **Error handling** — empty titles, invalid menu choices, invalid task numbers, and a missing JSON file are all handled with a friendly message.

Each task is stored as `{"title": "...", "done": false}`.

Files

- `mini_task_tracker.py` — the complete Python program.
- `README.md` — this file: goal, features, and how to run the program.
- `tasks.json` — created automatically when the program first saves a task. It is not needed to start the program; a missing file just means an empty task list.

How to run

In Google Colab

1. Upload `mini_task_tracker.py` to Colab, or paste its contents into a code cell.
2. Run the program and use the menu.
3. To test that tasks reload, run the program again **in the same Colab runtime** and choose View (2). The saved tasks will still be there.

> Colab files are temporary. For permanent storage, download `tasks.json` or save it to Google Drive.

On your computer

Python 3 and its standard library only — nothing to install.

```
python mini_task_tracker.py
```

Sample run

```
--- TASK TRACKER ---
1. Add  2. View  3. Complete  4. Delete  5. Exit
Choice: 1
Task title: Read notes
Task added.
Choice: 2
1. Read notes [Pending]
Choice: 3
Task number: 1
Task completed.
Choice: 2
1. Read notes [Done]
Choice: 5
Goodbye!
```

How to submit through GitHub

1. Create a new GitHub repository, for example `mini-task-tracker`.
2. **Commit 1:** upload `mini_task_tracker.py` and commit it.
3. **Commit 2:** upload `README.md` and commit it.
4. Submit the repository link. The repository should show at least two meaningful commits.