Lab 1 Exercises

Use Oracle SQL Developer to review some tables in your Oracle account

1. Start the Oracle SQL Developer.
2. Expand your Oracle connection.
3. View the column definition of the table customers_ex. Take a screen shot, showing the entire interface of your oracle SQL developer that includes the result.
4. View the data in the table customers_ex. Take a screen shot, showing the entire interface of your oracle SQL developer that includes the result.

Use Oracle SQL Developer to enter and run some SQL statements

Continue from the previous step.

5. Open a SQL worksheet window.
6. Enter and run the following SQL statement in one line.

   ```
   SELECT vendor_name FROM vendors
   ```

   Take a screen shot, showing the entire interface of your oracle SQL developer that includes both the query and the query result.
7. Add additional column names and ORDER BY such that the query becomes exactly as below in multiples lines.

   ```
   SELECT vendor_name, vendor_address1, vendor_city, vendor_state, vendor_zip_code
   FROM vendors
   ORDER BY vendor_name
   ```
8. Run the new statement in Step 7.
   Take a screen shot, showing the entire interface of your oracle SQL developer that includes both the new query and the query result.
9. Revise the statement in Step 7 by comment out the ORDER By line using two dashes in front of it, exactly as below.

   ```
   SELECT vendor_name, vendor_address1, vendor_city, vendor_state, vendor_zip_code
   FROM vendors
   --ORDER BY vendor_name
   ```
10. Run the new statement and compare the new results to the previous ordered result.
    Take a screen shot, showing the entire interface of your oracle SQL developer that includes both the new query and the query result.
11. Modify the statement by deleting the “e” at the end vendor_zip_code and run the statement again. This should display a syntax error.
    Take a screen shot, showing the entire interface of your oracle SQL developer that includes both the new query and the query result.
12. Read the syntax error closely and note that it explains that the column isn’t a valid identifier.

13. Click the Save button to save this statement. Then click the Cancel button in the Save dialogbox to cancel the operation.

Use Oracle SQL Developer to open and run scripts

Continue from the previous step.

NOTE - The scripts in this section contain some advanced SQL statements. You don't need to understand the meanings of these statements. They will be covered later.

14. Open the script: select_vendor_city_state.sql in the folder Lab1_exercises, which contains just one SQL statement.
15. Run the statement. If you didn't specify a connection for this statement, the Oracle SQL Developer should ask you to select one before it runs the statement.
    Take a screen shot, showing the entire interface of your oracle SQL developer that includes both the new query and the query result.
16. Open the script select_vendor_total_due.sql in the same folder. Note that this opens another tab.
17. Select your connection to the CIS oracle database server. Run this script.
    Take a screen shot, showing the entire interface of your oracle SQL developer that includes both the new query and the query result.
18. Open the script select_vendor_information.sql in the same folder. Notice that this script contains two SQL statements that end with semicolons.
19. Move the cursor to the first statement and press Ctrl+Enter to run that statement.
    Take a screen shot, showing the entire interface of your oracle SQL developer that includes both the new query and the query result.
20. Move the cursor to the second statement and press Ctrl+Enter to run that statement.
    Take a screen shot, showing the entire interface of your oracle SQL developer that includes both the new query and the query result.
21. Press F5 to run both statements that are stored in this script. If you scroll through the Script Output window, this should show the query results for both statements. You don't need to take screen shots for this step.

Close and restart the Oracle SQL Developer

Continue from the previous step.

You don't need to take screen shots for this section.

22. Continue to experiment on your own.
23. Make sure to leave at least one saved script open. Then, exit the Oracle SQL Developer.
24. Restart the Oracle SQL Developer. When it starts, note that any saved scripts that ou left open are automatically opened.

25. Run one of the open scripts. Note that you have to select a connection before the Oracle SQL Developer can run the script.
26. Exit the Oracle SQL Developer.