deeplearning.ai

Basics of Neural Network Programming

Gradient Descent

Gradient Descent

Recap: $\hat{y} = \sigma(w^T x + b)$, $\sigma(z) = \frac{1}{1+e^{-z}}$

$$J(w,b) = \frac{1}{m}\sum_{i=1}^{m} \mathcal{L}(\boxed{\hat{y}^{(i)}}, \boxed{y^{(i)}}) = -\frac{1}{m}\sum_{i=1}^{m} y^{(i)} \log \hat{y}^{(i)} + (1 - y^{(i)}) \log(1 - \hat{y}^{(i)})$$

Want to find w, b that minimize $J(w,b)$





Andrew Ng

Gradient Descent



learning rate

Repeat {

$$w := w - \alpha \boxed{\frac{dJ(w)}{dw}}$$

}

"dw"

$$w := w - \alpha \, dw$$

$$\frac{dJ(w)}{dw} = ?$$

$$J(w,b)$$

$$w := w - \alpha \boxed{\frac{dJ(w,b)}{dw}} \qquad \boxed{\frac{\partial J(w,b)}{\partial w}} \rightarrow dw$$

$$b := b - \alpha \boxed{\frac{dJ(w,b)}{db}} \qquad \boxed{\frac{\partial J(w,b)}{\partial b}} \rightarrow db$$

∂ "partial derivative"

d

J

Andrew Ng