



# C++ Stream Statements

## Error Identification & Best Practices Guide

(a)

```
cout << (void*) amount;
```

⚠️ **CONDITIONALLY VALID**

✓ **Valid only if 'amount' is a pointer**  
The (void\*) cast forces printing the memory address

✗ If amount is not a pointer → logic issue

(b)

```
cout << put("john");
```

✗ **ERROR**

✗ **put() accepts only a single char**

✓ **Correct:**  
cout.put('J') OR cout << "john"

(c)

```
cout << width();
```

✗ ERROR

✗ **width() is not a free function**

✓ **Correct:** `cout.width()`

(d)

```
int p = cout.width(10);
```

✗ ERROR

✗ **width() returns streamsize, not int**

✓ **Correct:**  
`std::streamsize p = cout.width(10);`

(e)

```
cout.width(10).precision(3);
```

✗ ERROR

✗ **width() returns a number, cannot chain methods**

✓ **Correct:**  
`cout.width(10); cout.precision(3);`

(f)

```
cout.setf(ios::scintific, ios::left);
```

**✗ MULTIPLE ERRORS**

✗ **Typo:** 'scintific' should be 'scientific'

✗ **Flag mismatch:** scientific (floatfield) cannot pair with left (adjustfield)

(g)

```
ch = cin.get();
```

**✓ VALID**

✓ cin.get() returns int; char assignment allowed

(h)

```
cin.get().get();
```

**✗ ERROR**

✗ cin.get() returns int, cannot call .get() on int

(i)

```
cin.get(c).get();
```

 **VALID**

✓ cin.get(c) returns cin, so chaining is allowed

(j)

```
cout << setw(5) << setprecision(2);
```

 **VALID BUT INCOMPLETE**

 **Valid syntax but prints nothing**

✓ Requires #include <iomanip>

(k)

```
cout << resetiosflags(ios::left | ios::showpos);
```

 **VALID**

✓ Valid with #include <iomanip>  
Removes specified flags

**Quick Reference for C++ Streams**

Remember: Always include proper headers (`<iostream>`, `<iomanip>`) and check return types!