





#### Cabinet

- Constructed from marine grade aluminium, incorporating channel section corner pillars, mounted on a heavy gauge base frame for structural stability.
- Numerous components are powder coated for extra corrosion protection.
- Available in down, side and top discharge.



### Fan wheel

- The fan wheel is double inlet, multi-blade, forward curve, centrifugal type.
- Constructed from galvanised steel, the wheel is statically balanced.
- The blower shaft on the RPB1200 to 1800 models is mounted in plummer blocks with self-aligning, single row ball bearings.
- RPB600-1000 models have a stainless steel shaft. Mounted in metal housing with selfaligning single row ball bearings.



### Water reservoir

- Rotational moulded in polyethylene to provide corrosion free long life and durability.
- Enhanced water distribution ensures an even water distribution and improved efficiency.



### Fan motors

- Tropic proof two speed motors fitted as standard
- All coolers are three phase and have manual re-set overload for added safety.



### Water connection

 Industry standard connections (1/2 inch BSP) make installation quick and easy.



### **Optional extras**

Automatic water dumping feature

# Why Breezair evaporative air conditioning for commercial and industrial use?



More than 40 years history in the commercial and industrial sector



Australia's number one choice for heavy industrial and commercial cooling



Suits any application, proven performer from small workshops to world's largest plants



Preferred choice of Mechanical Services Contractors, Engineers, Architects and Specifiers



Known for unmatched reliability, outstanding performance and cost effectiveness



Low maintenance and running costs year after year

### Breakthrough technology

### Mini-Cell<sup>^</sup> Chillcel<sup>®</sup> Pad Technology!

Dramatic improvement in cooling efficiency

Revolutionary new Mini-Cell structure provides a new development in cooling technology.

New enhanced small cell design, means that the Breezair range boasts a new cutting edge level of cooling capacity!

New pad formulation has resulted in having 25% more surface area dramatically improving cooling efficiency.

The only evaporative cooling pads fully manufactured in Australia to suit the harshest climates, and now, the absolute over-performer!

^Patent pending



## RPB Series

| Specifications                                |                  | RPB<br>600         | RPB<br>700 | RPB<br>900 | RPB<br>1000      | RPB<br>1200              | RPB<br>1300 | RPB<br>1400 | RPB<br>1500      | RPB<br>1800<br>(Top &<br>down dis.) | RPB<br>1800<br>(Side dis.) |
|---|------------------|--------------------|------------|------------|------------------|--------------------------|-------------|-------------|------------------|-------------------------------------|----------------------------|
| Airflow<br>(@ zero static)                    | High (m³/h)      | 21,096             | 25,920     | 31,716     | 35,604           | 41,292                   | 45,900      | 50,688      | 54,180           | 64,440                              | 58,680                     |
|   | High (cfm)       | 12,417             | 15,256     | 18,667     | 20,956           | 24,303                   | 27,016      | 29,834      | 31,889           | 37,928                              | 34,538                     |
|   | Low (m³/h)       | 14,040             | 16,632     | 21,600     | 23,850           | 27,720                   | 30,762      | 33,966      | 36,018           | 43,387                              | 42,804                     |
|   | Low (cfm)        | 8,263              | 9,789      | 12,713     | 14,037           | 16,315                   | 18,106      | 19,991      | 21,199           | 25,537                              | 25,193                     |
| Cooling capacity<br>(@ 80 Pa / 80% sat. eff.) | High speed (kW)  | 20.7               | 23.7       | 30.4       | 34.2             | 39.0                     | 44.3        | 49.8        | 53.1             | 63.3                                | 56.9                       |
| Blower Wheel                                  | Dia x width (mm) | 760x635            |            |            |                  | 820x800                  |             |             |                  |                                     |                            |
|   | Outlet (mm)      |                    | 780        | x760       |                  | 890x890                  |             |             |                  |                                     |                            |
| Motor   | Туре             | 2 speed<br>3 phase |            |            |                  |                          |             |             |                  |                                     |                            |
|   | Speed (RPM)      | 1450/955           |            |            |                  |                          |             |             |                  |                                     |                            |
|   | Rating (kW)      | 2.5:1.1            | 2.5:1.1    | 4.5:1.5    | 6.0:2.7          | 4.5:1.5                  | 6.0:2.0     | 8.0:2.5     | 10.0:4.4         | 15.0:6.7                            | 15.0:6.7                   |
|   | Current (amp)    | 5.0:4.0            | 5.0:4.0    | 8.5:5.3    | 15.5:7.5         | 8.5:5.3                  | 11.7:6.6    | 16.2:7.0    | 8.5:10.8         | 6.0:14.4                            | 6.0:14.4                   |
|   | Supply           |                    |            |            |                  | 415 V / 50 Hz<br>3 phase |             |             |                  |                                     |                            |
| Pump  | Туре             | Cent x 1           | Cent x 1   | Cent x 1   | Cent x 2         | Cent x 3                 | Cent x 3    | Cent x 3    | Cent x 3         | Cent x 4                            | Cent x 3                   |
|   | Rating (W)       | 50                 |            |            |                  |                          |             |             |                  |                                     |                            |
|   | Flow Rate (I/m)  | 24                 |            |            |                  |                          |             |             |                  |                                     |                            |
| Chillcel Cooling Pads                         | Size top (mm)    | 595 x 580 (6)      |            |            | 595 x<br>580 (8) | 795 x 580 (6)            |             |             |                  | 795 x<br>580 (8)                    | 795 x<br>580 (6)           |
|   | Size bottom (mm) | 595 x 580 (6)      |            |            | 595 x<br>580 (8) | 795 x 890 (6)            |             |             | 795 x<br>890 (8) | 795 x<br>890 (6)                    |                            |
|   | Area (m²)        | 4.14               |            |            | 5.52             |                          | 7.0         |             |                  | 9.4                                 | 7.0                        |
| Water reservoir tank                          | Capacity (L)     | 55                 |            |            |                  | 100                      |             |             |                  |                                     |                            |
|   | Height (mm)      |                    | 1,6        | 530        |                  | 2,050                    |             |             |                  |                                     |                            |
| Shipping                                      | Length (mm)      |                    | 1,5        | 660        |                  | 2,100                    |             |             |                  |                                     |                            |
|   | Width (mm)       |                    | 1,5        | 660        |                  | 2,100                    |             |             |                  |                                     |                            |
|   | Mass (kg)        | 295 331            |            |            | 376              | 415                      | 447         | 457         | 468              | 513                                 |                            |
|   | Operating (kg)   | 330                |            | 366        | 411              | 475                      | 517         | 527         | 538              | 57                                  | 73                         |











### **BREEZAIR**

Direct Evaporative Air Conditioning

#### **CLIMATE WIZARD**

Indirect Evaporative Air Conditioning

### **COOLAIR**

Direct Evaporative Air Conditioning

### **COOLERADO**

Indirect Evaporative Air Conditioning



### **Distributors for INDIA**

### CHADHA INDUSTRIES PVT. LTD.

An ISO 9001 : 2015 Co.

- 38, DLF Industrial Area, Kirti Nagar, New Delhi - 110 015 INDIA
- **\( +91 11 48483700 | 41426023 | 41425532 \)**