

UNIVERSITY OF DELHI



Ramanujan College

Computer Network

Semester-04

Submitted By:

KSHITIJ KHANAL

ROLL NO:
24020570048

Submitted To:

Ms. Sheetal Singh

(Assistant Professor)

**Department of Computer
Science**

Acknowledgement

I would like to take this opportunity to acknowledge everyone who has helped us in every stage of this project.

I am deeply indebted to my computer science Professor, Ms. Sheetal Singh for his guidance and suggestions in completing this practical. The completion of this practical was possible under his guidance and support.

I am also very thankful to my parents and my friends who have boosted me up morally with their continuous support.

At last but not least, I am very thankful to God almighty for showering his blessings upon me.

Index

S.No	Topic	Remarks
1.	To Study Basic Network Command And Network Configuration Commands	
2.	To Study And Perform PC To PC Communication Using Ethernet	
3.	To Create Star Topology Using Hub And Switch	
4.	To Create Bus, Ring, Tree, Hybrid, Mesh Topologies	
5.	Perform An Initial Switch Configuration	
6.	Perform An Initial Router Configuration	
7.	To Implement Client Server Network	
8.	To Implement Connection Between Devices Using Router	
9.	To Perform Remote Desktop Sharing Within LAN Connection	

Practical 1 : To Study Basic Network Command And Network Configuration Commands

1.netstat

```
C:\Users\user>netstat
Active Connections

```

Proto	Local Address	Foreign Address	State
TCP	127.0.0.1:49680	kubernetes:49681	ESTABLISHED
TCP	127.0.0.1:49681	kubernetes:49680	ESTABLISHED
TCP	127.0.0.1:49682	kubernetes:49683	ESTABLISHED
TCP	127.0.0.1:49683	kubernetes:49682	ESTABLISHED
TCP	127.0.0.1:49749	kubernetes:49752	ESTABLISHED
TCP	127.0.0.1:49750	kubernetes:54982	ESTABLISHED
TCP	127.0.0.1:49752	kubernetes:49749	ESTABLISHED
TCP	127.0.0.1:49754	kubernetes:49756	ESTABLISHED
TCP	127.0.0.1:49756	kubernetes:49754	ESTABLISHED
TCP	127.0.0.1:54942	kubernetes:49750	TIME_WAIT
TCP	127.0.0.1:54955	kubernetes:49750	TIME_WAIT
TCP	127.0.0.1:54966	kubernetes:49750	TIME_WAIT
TCP	127.0.0.1:54967	kubernetes:49750	TIME_WAIT
TCP	127.0.0.1:54982	kubernetes:49750	ESTABLISHED
TCP	:::1:49763	RATNESH-KUMAR:50051	ESTABLISHED

```
^C
C:\Users\user>netstat -h
Displays protocol statistics and current TCP/IP network connections.
NETSTAT [-a] [-b] [-e] [-f] [-n] [-o] [-p proto] [-r] [-s] [-t] [-x] [-y] [interval]
-a          Displays all connections and listening ports.
-b          Displays the executable involved in creating each connection or
           listening port. In some cases well-known executables host
           multiple independent components, and in these cases the
           sequence of components involved in creating the connection
           or listening port is displayed. In this case the executable
           name is in [] at the bottom, on top is the component it called,
           and so forth until TCP/IP was reached. Note that this option
           can be time-consuming and will fail unless you have sufficient
           permissions.
-e          Displays Ethernet statistics. This may be combined with the -s
           option.
-f          Displays Fully Qualified Domain Names (FQDN) for foreign
           addresses.
-n          Displays addresses and port numbers in numerical form.
```

2.nslookup

```
C:\Users\user>nslookup google.com
Server:      UnKnown
Address:     192.168.66.177

Non-authoritative answer:
Name:       google.com
Addresses:  2404:6800:4002:826::200e
           142.250.195.14
```

3.ping

```
C:\Users\user>ping www.google.com

Pinging www.google.com [2404:6800:4002:81c::2004] with 32 bytes of data:
Reply from 2404:6800:4002:81c::2004: time=25ms
Reply from 2404:6800:4002:81c::2004: time=46ms
Reply from 2404:6800:4002:81c::2004: time=54ms
Reply from 2404:6800:4002:81c::2004: time=56ms

Ping statistics for 2404:6800:4002:81c::2004:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
    Minimum = 25ms, Maximum = 56ms, Average = 45ms
```

4.route

```
C:\Users\user>route print
=====
Interface List
19...e4 b3 18 b6 49 f1 .....Microsoft Wi-Fi Direct Virtual Adapter #3
9...e6 b3 18 b6 49 f0 .....Microsoft Wi-Fi Direct Virtual Adapter #4
5...a0 8c fd a2 fd 89 .....Intel(R) Ethernet Connection I219-V
11...e4 b3 18 b6 49 f0 .....Intel(R) Dual Band Wireless-AC 8260
1.....Software Loopback Interface 1
=====

IPv4 Route Table
=====
Active Routes:
Network Destination        Netmask          Gateway             Interface           Metric
0.0.0.0                    0.0.0.0          192.168.66.177      192.168.66.158      55
127.0.0.0                  255.0.0.0        On-link             127.0.0.1           331
127.0.0.1                  255.255.255.255  On-link             127.0.0.1           331
127.255.255.255            255.255.255.255  On-link             127.0.0.1           331
169.254.0.0                 255.255.0.0      On-link             169.254.22.148      291
169.254.22.148             255.255.255.255  On-link             169.254.22.148      291
169.254.255.255            255.255.255.255  On-link             169.254.22.148      291
192.168.66.0               255.255.255.0    On-link             192.168.66.158      311
192.168.66.158             255.255.255.255  On-link             192.168.66.158      311
192.168.66.255             255.255.255.255  On-link             192.168.66.158      311
224.0.0.0                  240.0.0.0        On-link             127.0.0.1           331
224.0.0.0                  240.0.0.0        On-link             169.254.22.148      291
224.0.0.0                  240.0.0.0        On-link             192.168.66.158      311
255.255.255.255            255.255.255.255  On-link             127.0.0.1           331
255.255.255.255            255.255.255.255  On-link             169.254.22.148      291
255.255.255.255            255.255.255.255  On-link             192.168.66.158      311
=====
Persistent Routes:
None
```

5.arp

```
C:\Users\user>arp -a

Interface: 169.254.22.148 --- 0x5
    Internet Address      Physical Address         Type
    169.254.255.255       ff-ff-ff-ff-ff-ff      static
    224.0.0.22            01-00-5e-00-00-16      static
    224.0.0.251           01-00-5e-00-00-fb      static
    224.0.0.252           01-00-5e-00-00-fc      static
    255.255.255.255       ff-ff-ff-ff-ff-ff      static

Interface: 192.168.66.158 --- 0xb
    Internet Address      Physical Address         Type
    192.168.66.177       22-04-02-25-aa-fc      dynamic
    192.168.66.255       ff-ff-ff-ff-ff-ff      static
    224.0.0.22            01-00-5e-00-00-16      static
    224.0.0.251           01-00-5e-00-00-fb      static
    224.0.0.252           01-00-5e-00-00-fc      static
    255.255.255.255       ff-ff-ff-ff-ff-ff      static
```

6.tracert

```
C:\Users\user>tracert google.com

Tracing route to google.com [2404:6800:4002:82d::200e]
over a maximum of 30 hops:

  0  1 ms  3 ms  1 ms  2409:40d0:12d2:b44a::ff
  1  43 ms 36 ms 32 ms 2405:200:5202:28:3924:110:3:207
  2  54 ms 58 ms 102 ms 2405:200:5202:28:3925::ff02
  3  * * * Request timed out.
```

7.hostname

```
C:\Users\user>hostname
RATNESH-KUMAR
```


8.ipconfig

```
C:\Users\user>ipconfig

Windows IP Configuration

Wireless LAN adapter Local Area Connection* 1:

    Media State . . . . . : Media disconnected
    Connection-specific DNS Suffix  . :

Wireless LAN adapter Local Area Connection* 2:

    Media State . . . . . : Media disconnected
    Connection-specific DNS Suffix  . :

Ethernet adapter Ethernet:

    Connection-specific DNS Suffix  . :
    Link-local IPv6 Address . . . . . : fe80::85b9:5fb3:f9c8:773d%5
    Autoconfiguration IPv4 Address. . : 169.254.22.148
    Subnet Mask . . . . . : 255.255.0.0
    Default Gateway . . . . . :

Wireless LAN adapter Wi-Fi:

    Connection-specific DNS Suffix  . :
    IPv6 Address. . . . . : 2409:40d0:12d2:b44a:a9fb:460b:74a1:4585
    Temporary IPv6 Address. . . . . : 2409:40d0:12d2:b44a:90df:76eb:e0bf:42a6
    Link-local IPv6 Address . . . . . : fe80::a6c7:f18c:5de4:912f%11
    IPv4 Address. . . . . : 192.168.66.158
    Subnet Mask . . . . . : 255.255.255.0
    Default Gateway . . . . . : fe80::2004:2ff:fe25:aafc%11
                                192.168.66.177
```

9.systeminfo

```
C:\Users\user>systeminfo

Host Name:                 RATNESH-KUMAR
OS Name:                   Microsoft Windows 10 Pro
OS Version:                10.0.19045 N/A Build 19045
OS Manufacturer:         Microsoft Corporation
OS Configuration:        Standalone Workstation
OS Build Type:             Multiprocessor Free
Registered Owner:         user
Registered Organization:
Product ID:                00331-10000-00001-AA293
Original Install Date:     09-03-2024, 08:57:15 PM
System Boot Time:          03-05-2025, 09:57:51 AM
System Manufacturer:      HP
System Model:              HP EliteBook 850 G3
System Type:               x64-based PC
Processor(s):              1 Processor(s) Installed.
                           [01]: Intel64 Family 6 Model 78 Stepping 3 GenuineIntel ~2300 Mhz
BIOS Version:              HP N75 Ver. 01.18, 17-10-2017
Windows Directory:        C:\WINDOWS
System Directory:          C:\WINDOWS\system32
Boot Device:               \Device\HarddiskVolume2
System Locale:              en-us;English (United States)
Input Locale:              00004009
Time Zone:                 (UTC+05:30) Chennai, Kolkata, Mumbai, New Delhi
Total Physical Memory:     8,073 MB
Available Physical Memory: 2,992 MB
Virtual Memory: Max Size: 12,937 MB
Virtual Memory: Available: 5,185 MB
Virtual Memory: In Use:    7,752 MB
Page File Location(s):     C:\pagefile.sys
Domain:                    WORKGROUP
Logon Server:              \\RATNESH-KUMAR
Hotfix(s):                 19 Hotfix(s) Installed.
```

10.telnet

```
Cisco Packet Tracer PC Command Line 1.0
C:\>telnet 192.168.1.3
Trying 192.168.1.3 ...Open

User Access Verification

Username: |
```

Practical 2 : To Study And Perform PC To PC Communication Using Ethernet.

Objective:

- To connect two PCs and ensure they can communicate using IP addresses.

Requirements:

- Two PCs

Procedure:


Step 1 : Drag two PCs onto the workspace.

Step 2 : Use a **Copper Cross-Over Cable** to connect them.

Step 3 : Click on each PC:

- Desktop > IP Configuration.
- Assign IPs like 192.168.1.1 and 192.168.1.2 with subnet mask 255.255.255.0.

Step 4 : Open **Command Prompt** and ping the other PC to check communication.



Practical 3 : To Create Star Topology Using Hub And Switch.

Objective:

- To create Star topology using Hub and Switch

Requirements:

- PCs (3 or more)
- Hub/Switch

Procedure:

Step 1 : Drag the required number of PCs onto the workspace.


Step 2 : Add a Hub and/or Switch to the center of the topology.

Step 3 : Use Copper Straight-Through Cables to connect each PC to the Hub/Switch.

Step 4 : Assign IP addresses to each PC (e.g., 192.168.1.x) using:


- Desktop > IP Configuration.

Step 5 : Ping between PCs to verify connectivity.



**Star Topology
Using Hub**

**Star Topology
Using Switch**



Practical 4 : To Create Bus, Ring, Tree, Hybrid, Mesh Topologies.

Objective:

- To create Bus, Ring, Tree, Hybrid, and Mesh topologies

Requirements:

- Multiple PCs
- Appropriate networking devices (Hubs, Switches, Routers)
- Copper Cables
- Cisco Packet Tracer

Procedure:


Step 1: Drag the required devices (PCs, Switches, Routers) onto the workspace.

Step 2: Connect the devices using appropriate cables (Copper Straight-Through or Copper Cross-Over).


Step 3: Arrange the devices to create different topologies:

- **Bus:** Connect all devices to a single backbone cable.
- **Ring:** Connect devices in a circular loop.
- **Tree:** Connect multiple switches in a hierarchical fashion.
- **Hybrid:** Combine two or more topologies to form a hybrid structure.
- **Mesh:** Connect every device to every other device.

Step 4: Configure IP addresses on each device in the network and verify communication.





**Bus
Topology**



**Hybrid
Topology**

**Bus
Topology**



**Ring
Topology**

Practical 5 : Perform An Initial Switch Configuration.

Objective:

- To perform basic initial configuration of a Cisco switch.

Requirements:

- Switch
- Multiple PCs
- Copper Cables
- Cisco Packet Tracer

Procedure:

1. **Drag a Switch** onto the workspace.
2. **Connect PCs** to the Switch using Copper Straight-Through cables.
3. **Access the Switch CLI** and configure the basic settings:


```
Switch> enable
Switch# configure terminal
Switch(config)# hostname S1
S1(config)# enable secret class123
S1(config)# line console 0
S1(config-line)# password cisco
S1(config-line)# login
S1(config-line)# exit
S1(config)# line vty 0 15
S1(config-line)# password cisco
S1(config-line)# login
S1(config-line)# exit
S1(config)# banner motd #Unauthorized Access Prohibited#
S1(config)# interface vlan 1
S1(config-if)# ip address 192.168.1.2 255.255.255.0
S1(config-if)# no shutdown
S1(config-if)# exit
S1(config)# exit
```

4. **Save the configuration:**

```
S1# copy running-config startup-config
```

5. **Test connectivity** by pinging from a PC to the Switch's IP address.

```
Switch> enable
Switch# configure terminal
Switch(config)# hostname S1
S1(config)# enable secret class123
S1(config)# line console 0
S1(config-line)# password cisco
S1(config-line)# login
S1(config-line)# exit
S1(config)# line vty 0 15
S1(config-line)# password cisco
S1(config-line)# login
S1(config-line)# exit
S1(config)# banner motd #Unauthorized Access Prohibited#
S1(config)# interface vlan 1
S1(config-if)# ip address 192.168.1.2 255.255.255.0
S1(config-if)# no shutdown
S1(config-if)# exit
S1(config)# exit
S1# copy running-config startup-config
```



Practical 6 : Perform An Initial Router Configuration.

Objective:

- To configure a basic Cisco router with an interface IP address and enable the interface.

Requirements:

- Router
- Switch
- PC
- Copper Cables
- Cisco Packet Tracer

Procedure:

1. **Drag a Router** onto the workspace.
2. **Connect the Router** to a Switch and PC using Copper Straight-Through cables.
3. **Access the Router CLI** and perform the configuration:


```
Router> enable
Router# configure terminal
Router(config)# hostname R1
R1(config)# enable secret class123
R1(config)# line console 0
R1(config-line)# password cisco
R1(config-line)# login
R1(config-line)# exit
R1(config)# line vty 0 15
R1(config-line)# password cisco
R1(config-line)# login
R1(config-line)# exit
R1(config)# banner motd #Authorized Access Only#
R1(config)# interface gigabitEthernet 0/0
R1(config-if)# ip address 192.168.1.1 255.255.255.0
R1(config-if)# no shutdown
R1(config-if)# exit
R1(config)# exit
```

4. **Save the configuration:**

```
S1# copy running-config startup-config
```

5. **Test connectivity** by pinging from a PC to the Router's IP address.

```
Router> enable
Router# configure terminal
Router(config)# hostname R1
R1(config)# enable secret class123
R1(config)# line console 0
R1(config-line)# password cisco
R1(config-line)# login
R1(config-line)# exit
R1(config)# line vty 0 4
R1(config-line)# password cisco
R1(config-line)# login
R1(config-line)# exit
R1(config)# banner motd #Authorized Access Only#
R1(config)# interface gigabitEthernet 0/0
R1(config-if)# ip address 192.168.1.1 255.255.255.0
R1(config-if)# no shutdown
R1(config-if)# exit
R1(config)# exit
R1# copy running-config startup-config
```



Practical 7 : To Implement Client Server Network.

Objective:

- To set up a client-server network and ensure communication between a client PC and a server.

Requirements:

- Multiple PCs
- Server
- Switch
- Copper Cables
- Cisco Packet Tracer

Procedure:

1. **Drag two PCs and a Server** onto the workspace.
2. **Connect devices** using Copper Straight-Through cables to a Switch.
3. **Configure static IP addresses** on the Client and Server:

- For the Client:

1. PC1: IP = 192.168.1.11, Mask = 255.255.255.0

2. PC2: IP = 192.168.1.12, Mask = 255.255.255.0

3. PC3: IP = 192.168.1.13, Mask = 255.255.255.0


- For the Server:

IP Address: 192.168.1.10

Subnet Mask: 255.255.255.0

4. **Test communication** by pinging the Server from the Client:

```
ping 192.168.1.10
```



Practical 8 : To Implement Connection Between Devices Using Router.

Objective:

- To configure a router to enable communication between devices on different networks.

Requirements:



- Routers
- Switch
- Multiple PCs
- Serial cables
- Copper Cables
- Cisco Packet Tracer

Procedure:

1. **Drag two Routers** onto the workspace and connect them using Serial cables.
2. **Connect PCs** to the Routers using Copper Straight-Through cables.
3. **Configure Router interfaces** with IP addresses and enable them:
 - o For Router1 (gigabitEthernet 0/0):

```
Router(config)# interface g0/0
Router(config-if)# ip address 192.168.1.1 255.255.255.0
Router(config-if)# no shutdown
Router(config-if)# exit
```
 - o For Router2 (gigabitEthernet 0/1):

```
Router(config)# interface g0/1
Router(config-if)# ip address 192.168.2.1 255.255.255.0
Router(config-if)# no shutdown
Router(config-if)# exit
```
4. **Set up IP Address** between PCs:
 - o Configure Network 1 PCs:
 1. PC0: 192.168.1.10, Gateway: 192.168.1.1
 2. PC1: 192.168.1.11, Gateway: 192.168.1.1
 - o Configure Network 2 PCs:
 1. PC2: 192.168.2.10, Gateway: 192.168.2.1
 2. PC3: 192.168.2.11, Gateway: 192.168.2.1
5. **Test communication** by pinging a PC in Router1's network from Router2's network.



Practical 9 : To Perform Remote Desktop Sharing Within LAN Connection.

Objective:

- To set up and test Remote Desktop access between two PCs within the same LAN.

Requirements:

- Multiple PCs
- Switch
- Copper Cables
- Cisco Packet Tracer

Procedure:

1. **Drag two PCs** onto the workspace and connect them using Copper Straight-Through cables to a Switch.
2. **Configure static IP addresses** on both PCs:
 - For PC1:
IP Address: 192.168.1.10
Subnet Mask: 255.255.255.0
 - For PC2:
IP Address: 192.168.1.20
Subnet Mask: 255.255.255.0
3. **Test the connection** by logging into PC1 from PC2 via the Remote Desktop application.

