

Author:Saurabh Khandagale

Roll No:46

Date :27-August-2020

### EXPERIMENT:-03

AIM:-

TO ESTABLISH A MULTI-RELATION DATABASE AND EXECUTE SQL QUERIES INVOLVING INSERTIONS,DELETIONS AND UPDATE ON IT.

### PROBLEM STATEMENT:

Establish the Academic Database schema, for demonstrating creation, updating and usage of Oracle objects - views, synonyms, indexes, sequences and savepoints. Execute queries based on the logical schemata given below...

STUDENT (ROLL, LNAME, FNAME, EMAIL, ENROLL, ADVISOR, PHONE, REG\_DT)  
STAFF (SID, NAME, BRANCH, DESG, JOIN\_DT) DEPT (DNAME, BRANCH, INTAKE, YR\_EST, HOD)

Relation: STUDENT

Attribute Name ROLL LNAME FNAME EMAIL ENROLL ADVISOR PHONE REG\_DT  
Data Description NUMBER (3) VARCHAR (15) VARCHAR (15) VARCHAR (25) CHAR (13) NUMBER (3) NUMBER (10) DATE

Remarks El-column, [1, 300] Required Required Unique Unique RI-Column, Required, Ref STAFF (SID)

Required

Relation: STAFF

Attribute Name SID NAME

BRANCH DESG JOIN\_DT

Data Description NUMBER (3) VARCHAR (25) VARCHAR (4) VARCHAR (9) DATE

Remarks El-column, Starts 101 Required RI-Column, Required Required, [Professor, Associate, Assistant] Required

Relation: DEPT

Attribute Name DNAME BRANCH INTAKE YR\_EST HOD

Data Description VARCHAR (25) VARCHAR (4) NUMBER (2) NUMBER (4) NUMBER (3)

Remarks Required El-column, [CSE, DAT, AIMS, CSEC] Required, [20, 30, 40] Required, YR\_EST > 2004 RI-column, Ref STAFF(SID), default 101

The SQL script including Academic Database configuration, constraints enforcement and populating the tables will be shared on Google Classroom. [academic.sql]

```
=====Query-02=====
Write SQL code to roll number, print first name, last name, advisor
name for your roll number.
=====
```

```
SELECT STUDENT.ROLL ,STUDENT.FNAME,STUDENT.LNAME,STAFF.NAME
FROM STUDENT INNER JOIN STAFF
ON STAFF.SID=STUDENT. ADVISOR WHERE ROLL=46;
```

ROLL	FNAME	LNAME	NAME
46	Saurabh	Khandagale	Adishesh Vidyarthi

```
=====Query-03=====
Create a sequence STAFF_SQ with appropriate starting value and maximum range
such that you can use it to populate STAFF table the tuples listed below. [Use
STAFF_SQ. NEXTVAL, STAFF_SQ.CURRVAL to access sequence values].
106, DAT, Deo Narayan Mishra, Assistant, 13-Oct-2013
107, CSEC, Sanjeev Bamireddy, Associate, 12-May-2018
108, CSE, Jasmine Arora, Assistant, 11-Aug-2017
109, CSE, Vallabh Pai, Assistant, 17-Sep-2018
110, AIML, Harmeet Khullar, Assistant, 17-Mar-2019
=====
```

```
SQL> CREATE SEQUENCE STAFF_SQ START WITH 106
      INCREMENT BY 1
      MAXVALUE 110
      NOCYCLE CACHE 20;
```

Sequence created.

```
SQL> insert into staff
values(staff_sq.nextval,'&name','&bran','&desg','&join_dt');
Enter value for name: Deo Narayan Mishra
Enter value for bran: DAT
Enter value for desg: Assistant
Enter value for join_dt: 13-Oct-2013
old 1: insert into staff
values(staff_sq.nextval,'&name','&bran','&desg','&join_dt')
new 1: INSERT INTO STAFF VALUES
(staff_sq.nextval,'Deo Narayan Mishra','DAT','Assistant','13-Oct-2013')
```

1 row created.

```
SQL> INSERT INTO STAFF VALUES (staff_sq.nextval,'Sanjeev
Bamireddy','CSEC','Associate','12-MAY-19');
```

1 row created.

```
SQL> INSERT INTO STAFF VALUES (staff_sq.nextval,'Jasmine
Arora','CSE','Assistant','11-Aug-17');
```

```
SQL> INSERT INTO STAFF VALUES
(staff_sq.nextval,'Vallabh Pai','CSE','Assistant','17-SEP-18');

SQL> INSERT INTO STAFF VALUES
(staff_sq.nextval,'Harmeet Khullar','AIML','Assistant','17-Mar-19');
```

```
SELECT * FROM STAFF;
```

SID	NAME	BRAN	DESG	JOIN_DT
101	Kamalkant Marathe	CSE	Professor	12-JUN-05
102	Adishesh Vidyarthi	AIML	Associate	22-JUL-06
103	Manishi Singh	DAT	Professor	10-NOV-07
104	Aasawari Deodhar	CSE	Associate	13-OCT-08
105	Geetika Goenka	CSEC	Professor	15-NOV-09
106	Deo Narayan Mishra	DAT	Assistant	13-OCT-13
107	Sanjeev Bamireddy	CSEC	Associate	12-MAY-19
108	Jasmine Arora	CSE	Assistant	11-AUG-17
109	Vallabh Pai	CSE	Assistant	17-SEP-18
110	Harmeet Khullar	AIML	Assistant	17-MAR-19

10 rows selected.

```
SQL> SELECT * FROM USER_SEQUENCES;
```

SEQUENCE_NAME	MIN_VALUE	MAX_VALUE	INCREMENT	C	O	CACHE_SIZ	LAST_NUMBER
STAFF_SQ	1	110	1	N	N	20	111

```
SQL> DROP SEQUENCE STAFF_SQ;
```

Sequence dropped.

=====Query4=====

While Academic Database was configured few constraints were not enforced as mentioned in the logical schema. Identify (by listing them table-by-table) these constraints (PK & FK) and enforce them.

=====

[BEFORE]

```
SQL> SELECT TABLE_NAME,CONSTRAINT_NAME,CONSTRAINT_TYPE
FROM user_constraints
WHERE (CONSTRAINT_TYPE='R' OR CONSTRAINT_TYPE='P')
AND
(TABLE_NAME='STUDENT' OR TABLE_NAME='STAFF' OR TABLE_NAME='DEPT');
```

TABLE_NAME	CONSTRAINT_NAME	C
DEPT	DEPT_PK_BRANCH	P
DEPT	SYS_C007491	R
STAFF	STAFF_PK_SID	P
STAFF	STAFF_FK_DEPT	R
STUDENT	STUDENT_PK_ROLL	P

5 rows selected.

[AFTER]

```
SQL> ALTER TABLE ADD
CONSTRAINTS STUDENT_FK_STAFF
FOREIGN KEY(ADVISOR) REFERENCES STAFF(SID);
```

```
SQL> SELECT TABLE_NAME,CONSTRAINT_NAME,CONSTRAINT_TYPE
FROM user_constraints
WHERE (CONSTRAINT_TYPE='R' OR CONSTRAINT_TYPE='P')
AND
(TABLE_NAME='STUDENT' OR TABLE_NAME='STAFF' OR TABLE_NAME='DEPT');
```

TABLE_NAME	CONSTRAINT_NAME	C
DEPT	DEPT_PK_BRANCH	P
DEPT	SYS_C007491	R
STAFF	STAFF_PK_SID	P
STAFF	STAFF_FK_DEPT	R
STUDENT	STUDENT_PK_ROLL	P
STUDENT	STUDENT_FK_STAFF	R

6 rows selected.

=====Query05=====

Write SQL code that will create a temporary table (view) named STUDENT\_VW on STUDENT table projecting the attributes ENROLL, LNAME, FNAME, ROLL, ADVISOR. List the contents of STUDENT\_VW.

```
SQL> CREATE VIEW STUDENT_VW
AS
(SELECT ENROLL,LNAME,FNAME,ROLL,ADVISOR,REG_DT FROM STUDENT);
```

View created.

```
SQL> SELECT * FROM STUDENT_VW;
```

ENROLL	LNAME	FNAME	ROLL	ADVISOR	REG_DT
18CSU2001CSU2	Sayed	Afra	1	101	20-JUL-18
18CSU2002CSU2	Wasalu	Akansha	2	104	20-JUL-18
18CSU2003CSU2	Rajendran	Anjali	3	108	19-JUL-18
19CSU2206CSU2	Khandagale	Saurabh	46	102	10-AUG-19
18CSU2036CSU2	Dandekar	Paritosh	57	102	14-JUL-18
17CSU2047CSU2	Pandey	Shapath	86	107	27-JUL-17
17CSU2091CSU2	Singh	Ayush	66	107	27-JUL-17

=====Query06=====

6) Two students Naveen Namjoshi (88) and Tushar Tipnis (89) were admitted on August 14, 2019 and were assigned to staff members 109 and 110 respectively. Write SQL code to insert these student records into STUDENT\_VW and observe the effect on STUDENT table.

=====

EXPLAIN:-[FOR SIMPLE VIEW]

VIEW MAINTAINS LOGICAL VIEW OF DATA AS WELL AS DYNAMIC DATA AND  
INSERT,UPDATE,DELETE IS AN PHYSICAL QUERY ,SO CHANGES MADE IN LOGICAL DATA  
WILL REFLECT ON TABLE AS WELL AS CHANGES MADE IN TABLE WILL REFLECT ON VIEW.

```
SQL> INSERT INTO STUDENT_VW (LNAME,FNAME,ROLL,ADVISOR,REG_DT)
      VALUES
      ('NAMJOSHI','NAVEEN',88,109,'14-AUG-2019');
```

1 row created.

```
SQL> INSERT INTO STUDENT_VW (LNAME,FNAME,ROLL,ADVISOR,REG_DT)
      VALUES
      ('TUSHAR','TIPNIS',89,110,'14-AUG-2019');
```

1 row created.

```
SQL> COMMIT;
```

```
SQL> SELECT LNAME,FNAME,ROLL,ADVISOR,REG_DT FROM STUDENT WHERE ROLL=88 OR
ROLL=89;
```

LNAME	FNAME	ROLL	ADVISOR	REG_DT
NAMJOSHI	NAVEEN	88	109	14-AUG-19
TUSHAR	TIPNIS	89	110	14-AUG-19

=====Query07=====

Write SQL code to create a view STUDENT\_VW\_RO on STUDENT table with READ ONLY option with same attribute set as in STUDENT\_VW. List the contents of STUDENT\_VW\_RO. Now insert a record - 91, Cinderella Goldsmith, 101, 18-Aug-2019 - into STUDENT\_VW\_RO. Observe the effect.

=====

```
SQL> SELECT LNAME,FNAME,ROLL,ADVISOR,REG_DT FROM STUDENT_VW_RO ;
```

LNAME	FNAME	ROLL	ADVISOR	REG_DT
Sayed	Afra	1	101	20-JUL-18
Wasalu	Akansha	2	104	20-JUL-18
Rajendran	Anjali	3	108	19-JUL-18
NAMJOSHI	NAVEEN	88	109	14-AUG-19
TUSHAR	TIPNIS	89	110	14-AUG-19

[NO CHANGES]

```
SQL>INSERT INTO STUDENT_VW_RO
(LNAME,FNAME,ROLL,ADVISOR,REG_DT)VALUES('CINDERELLA','GOLDSMITH',91,101,'18-
AUG-2019')
```

ERROR at line 1:

ORA-42399: cannot perform a DML operation on a read-only view

EXPLAIN:-WHEN WE APPLY DML ON SIMPLE VIEW THE CHANGES IS REFLECTED , BUT THERE ARE SOME CASE WHERE DATABASE USER HAVE TO RESTRICT THE UPDATATION SO FOR THAT ORACLE PROVIDE ADDITIONAL CONSTRAINTS ON VIEW AS READ ONLY ,WHICH DOES NOT ALLOW UNAUTHORIZED USER TO MANIPULATE DATA.

=====Query08=====

Write SQL code to create a view STUDENT\_VW\_CK on STUDENT table with CHECK OPTION and CONSTRAINT with same attribute set as in STUDENT\_VW but will include those tuples having advisors among 101, 103, 105, 108 and 109. Name the constraint as STUDENT\_ADV\_CK. List the contents of STUDENT\_VW\_CK. Now, insert a record - 92, Sebastian Ford, 104, 18-Aug-2019 - into STUDENT\_VW\_CK. Observe the effect.

```
SQL> CREATE OR REPLACE VIEW STUDENT_VW_CK AS SELECT
ENROLL,LNAME,FNAME,ROLL,ADVISOR,REG_DT FROM STUDENT WHERE ADVISOR=101 OR
ADVISOR=103 OR ADVISOR=105 OR ADVISOR=108 OR ADVISOR=109 WITH CHECK
OPTION CONSTRAINT STUDENT_ADV_CK ;
```

View created.

```
SQL> COMMIT;
```

```

INSERT INTO STUDENT_VW_CK
(ROLL,LNAME,FNAME,ADVISOR,REG_DT)VALUES
(92,'SEBASTIAN','FORD',104,'18-AUG-2019')
*
```

ERROR at line 1:

ORA-01402: view WITH CHECK OPTION where-clause violation

EXPLAIN:-ORACLE PROVIDE A CONSTRAINT ON VIEW THAT IS **CHECK CONSTRAINT**  
 IN WHICH USER WILL ONLY ADD SPECIFIED DATA ONLY,IF WE TRY TO ADD  
 INVALID DATA THEN ORACLE GIVE AS ERROR(where-clause violation).

=====Query09=====

List all the views for the current schema tables (use USER\_VIEWS table]. List  
 the constraints (include constraint type) on the views in Academic Schema.

```
SQL> SELECT VIEW_NAME FROM USER_VIEWS;
```

VIEW\_NAME

-----

STUDENT\_VW  
 STUDENT\_VW1  
 STUDENT\_VW\_CK  
 STUDENT\_VW\_RO  
 VW\_PRODUCT

```
SQL> SELECT VIEW_NAME,VIEW_TYPE,READ_ONLY,EDITIONING_VIEW FROM USER_VIEWS;
```

VIEW_NAME	VIEW_TYPE	R	E
STUDENT_VW		N	N
STUDENT_VW_RO		Y	N
STUDENT_VW_CK		N	N
VW_PRODUCT		N	N
STUDENT_VW1		N	N

=====Query10=====

Write a SQL code to create a private synonym FACULTY\_SN for STAFF. Use this synonym to show contents of STAFF. A faculty named Dhawal Giri has been appointed as Assistant in AIML. Insert this record using FACULTY\_SN. Observe contents of STAFF table.

=====

```
SQL> CREATE SYNONYM FACULTY_SN FOR STAFF;
```

```
SQL> SELECT * FROM FACULTY_SN;
```

SID	NAME	BRAN	DESG	JOIN_DT
101	Kamalkant Marathe	CSE	Professor	12-JUN-05
102	Adishesh Vidyarthi	AIML	Associate	22-JUL-06
103	Manishi Singh	DAT	Professor	10-NOV-07
104	Aasawari Deodhar	CSE	Associate	13-OCT-08
105	Geetika Goenka	CSEC	Professor	15-NOV-09
106	Deo Narayan Mishra	DAT	Assistant	13-OCT-13
107	Sanjeev Bamireddy	CSEC	Associate	12-MAY-19
108	Jasmine Arora	CSE	Assistant	11-AUG-17
109	Vallabh Pai	CSE	Assistant	17-SEP-18
110	Harmeet Khullar	AIML	Assistant	17-MAR-19

10 rows selected.

```
SQL> INSERT INTO FACULTY_SN
```

```
VALUES
```

```
(111,'Dhawal Giri','AIML','Assistant','25-AUG-20');
```

1 row created.

```
SQL> SELECT * FROM STAFF;
```

SID	NAME	BRAN	DESG	JOIN_DT
101	Kamalkant Marathe	CSE	Professor	12-JUN-05
102	Adishesh Vidyarthi	AIML	Associate	22-JUL-06
103	Manishi Singh	DAT	Professor	10-NOV-07
104	Aasawari Deodhar	CSE	Associate	13-OCT-08
105	Geetika Goenka	CSEC	Professor	15-NOV-09
106	Deo Narayan Mishra	DAT	Assistant	13-OCT-13
107	Sanjeev Bamireddy	CSEC	Associate	12-MAY-19
108	Jasmine Arora	CSE	Assistant	11-AUG-17
109	Vallabh Pai	CSE	Assistant	17-SEP-18
110	Harmeet Khullar	AIML	Assistant	17-MAR-19
111	Dhawal Giri	AIML	Assistant	25-AUG-20

11 rows selected.



```
=====Query11=====
Write SQL code to create a unique B-Tree index on FNAME attribute of
STUDENT table. Observe the output and report the problem(s). If it fails,
create B-Tree index and test it to locate a certain student by first name.
Now, create a concatenated B-tree index on (LNAME, FNAME) attributes of
STUDENT table and test the index. Also list all indexes for CS5XX for the
current database schema [use USER_INDEXES table].
=====
```

```
SQL> CREATE UNIQUE INDEX UN_IDX1 ON STUDENT(FNAME);
CREATE UNIQUE INDEX UN_IDX1 ON STUDENT(FNAME)
      *
```

```
ERROR at line 1:
ORA-01452: cannot CREATE UNIQUE INDEX; duplicate keys found
```

**EXPLAIN:-**WE CAN CREATE UNIQUE INDEX ONLY ON ATTRIBUTE HAVING UNIQUE VALUES, IN OUR SCHEMA FNAME CONTAINS DUPLICATE VALUES SO BECAUSE OF THAT WE CANNOT CREATE **UNIQUE** INDEX ON FNAME ATTRIBUTE.

```
SQL> CREATE INDEX FNAME_IDX1 ON STUDENT(FNAME);
```

Index created.

```
SQL> SELECT FNAME FROM STUDENT WHERE FNAME='Saurabh';
```

```
FNAME
-----
Saurabh
Saurabh
```

Execution Plan

```
-----
Plan hash value: 3472840140
```

```
-----
-
| Id  | Operation          | Name          | Rows  | Bytes | Cost (%CPU)| Time |
|-----|-----|-----|-----|-----|-----|-----|
-
|  0  | SELECT STATEMENT   |               |      1 |      8 |      1 (0)| 00:00:01 |
|-----|-----|-----|-----|-----|-----|
|*  1  | INDEX RANGE SCAN   | FNAME_IDX1    |      1 |      8 |      1 (0)| 00:00:01 |
|-----|-----|-----|-----|-----|-----|
-
-

```

Predicate Information (identified by operation id):

```
-----
1 - access("FNAME"='Saurabh')
```

```
SQL> CREATE UNIQUE INDEX COMPOSITE_IDX1 ON STUDENT(LNAME,FNAME);
```

Index created.

```
SQL> SELECT INDEX_NAME , INDEX_TYPE, TABLE_TYPE , TABLE_NAME, TABLE_OWNER
       FROM USER_INDEXES
       WHERE (TABLE_OWNER='CSB46')
       AND
       (TABLE_NAME='STUDENT' OR TABLE_NAME='STAFF' OR TABLE_NAME='DEPT');
```

INDEX_NAME	INDEX_TYPE	TABLE_TYPE	TABLE_NAME	TABLE_OWNER
DEPT_PK_BRANCH	NORMAL	TABLE	DEPT	CSB46
STAFF_PK_SID	NORMAL	TABLE	STAFF	CSB46
COMPOSITE_IDX1	NORMAL	TABLE	STUDENT	CSB46
FNAME_IDX1	NORMAL	TABLE	STUDENT	CSB46
SYS_C007490	NORMAL	TABLE	STUDENT	CSB46
SYS_C007489	NORMAL	TABLE	STUDENT	CSB46
STUDENT_PK_ROLL	NORMAL	TABLE	STUDENT	CSB46

NOTE:-ORACLE ENGINE IMPLICITLY CREATE A INDEX ON PRIMARY KEY,OUTPUT WILL BE IN SORTED ORDER BECAUSE(SEARCH & STORE);

\*\*\*\*\*QUES12\*\*\*\*\*

Write SQL code to create a function-based index on LNAME attribute of students such that case-sensitivity is superseded by converting to uppercase/lowercase and test the index. Now create a concatenated function-based index on (LNAME, FNAME) attributes of STUDENT and test the index. Before testing the function-based index, the DBA must set the initialization parameter QUERY\_REWRITE\_ENABLED to true. CONNECT system/system  
ALTER SYSTEM SET QUERY\_REWRITE\_ENABLED=TRUE;

\*\*\*\*\*

```
SQL> CREATE INDEX IDX_LNAME ON STUDENT(UPPER(LNAME));
```

Index created.

```
SQL> SELECT LNAME FROM STUDENT WHERE upper(LNAME)='KHANDAGALE';
```

```
LNAME
-----
Khandagale
```

```
SQL> CREATE INDEX IDX_FUNC ON STUDENT(UPPER(LNAME),UPPER(FNAME));
```

Index created.

```
SQL> SELECT LNAME,FNAME FROM STUDENT WHERE UPPER(LNAME)='KHANDAGALE' AND
UPPER(FNAME)='SAURABH';
```

```
LNAME      FNAME
-----
Khandagale Saurabh
```

```
SQL> SELECT INDEX_NAME , INDEX_TYPE, TABLE_TYPE , TABLE_NAME, TABLE_OWNER
FROM USER_INDEXES
WHERE TABLE_NAME='STUDENT'
OR TABLE_NAME='STAFF'
OR TABLE_NAME='DEPT';
```

INDEX_NAME	INDEX_TYPE	TABLE_TYPE	TABLE_NAME	TABLE_OWNE
DEPT_PK_BRANCH	NORMAL	TABLE	DEPT	CSB46
STAFF_PK_SID	NORMAL	TABLE	STAFF	CSB46
IDX_FUNC	FUNCTION-BASED NORMAL	TABLE	STUDENT	CSB46
IDX_LNAME	FUNCTION-BASED NORMAL	TABLE	STUDENT	CSB46
COMPOSITE_IDX1	NORMAL	TABLE	STUDENT	CSB46
FNAME_IDX1	NORMAL	TABLE	STUDENT	CSB46
SYS_C007490	NORMAL	TABLE	STUDENT	CSB46
SYS_C007489	NORMAL	TABLE	STUDENT	CSB46
STUDENT_PK_ROLL	NORMAL	TABLE	STUDENT	CSB46

\*\*\*\*\*QUES13\*\*\*\*\*

Write SQL script that will

a) Add a student records

91, Cinderella Goldsmith, 101, 18-Aug-2019

92, Sebastian Ford, 104, 18-Aug-2019

b) Naveen Namjoshi has a new advisor, 108.

c) Tushar Tipnis has a new advisor, 111.

Before executing 13(a) create a savepoint SP\_NONE. On adding records for roll numbers 91 and 92, create a savepoint SP\_FORD. Create savepoints SP\_NAV and SP\_TUS after updating in 13(b) and 13(c) respectively.

\*\*\*\*\*

```
SAVEPOINT SP_NONE;
```

Savepoint created.

```
INSERT INTO STUDENT(ROLL,LNAME,FNAME,ADVISOR,REG_DT)
VALUES(91,'Goldsmith','Cinderella',101,'18-AUG-2019');
```

1 row created.

```
INSERT INTO STUDENT(ROLL,LNAME,FNAME,ADVISOR,REG_DT)
VALUES(92,'Ford','Sebstain',104,'18-AUG-2019');
SAVEPOINT SP_FORD;
Savepoint created.
```

```
SQL> UPDATE STUDENT SET ADVISOR=108 WHERE ROLL=88;
1 row updated.
```

```
SQL> SAVEPOINT SP_NAV;
Savepoint created.
```

```
SQL> UPDATE STUDENT SET ADVISOR=111 WHERE ROLL=89;
1 row updated.
```

```
SQL> SAVEPOINT SP_TUS;
Savepoint created.
```

\*\*\*\*\*QUES14\*\*\*\*\*

Write SQL code to recover the database state as it was after executing13(a). Now, regain the database state to the one before executing Query-13.

\*\*\*\*\*

```
SQL> SELECT ROLL, FNAME, LNAME, ADVISOR, REG_DT FROM STUDENT;
```

ROLL	FNAME	LNAME	ADVISOR	REG_DT
1	Afra	Sayed	101	20-JUL-18
2	Akansha	Wasalu	104	20-JUL-18
3	Anjali	Rajendran	108	19-JUL-18
86	Shapath	Pandey	107	27-JUL-17
66	Ayush	Singh	107	27-JUL-17
92	Sebstain	Ford	104	18-AUG-19
88	NAVEEN	NAMJOSHI	108	14-AUG-19
89	TIPNIS	TUSHAR	111	14-AUG-19
91	Cinderella	Goldsmith	101	18-AUG-19
92	Ford	Sebstain	104	18-AUG-19

```
SQL> ROLLBACK TO SP_FORD;
```

Rollback complete.

```
SQL> SELECT ROLL, FNAME, LNAME, ADVISOR, REG_DT FROM STUDENT;
```

ROLL	FNAME	LNAME	ADVISOR	REG_DT
1	Afra	Sayed	101	20-JUL-18
2	Akansha	Wasalu	104	20-JUL-18
3	Anjali	Rajendran	108	19-JUL-18
85	Yogesh	Siral	105	21-JUL-18
86	Shapath	Pandey	107	27-JUL-17
66	Ayush	Singh	107	27-JUL-17
88	NAVEEN	NAMJOSHI	109	14-AUG-19
89	TIPNIS	TUSHAR	110	14-AUG-19
91	Cinderella	Goldsmith	101	18-AUG-19
92	Sebstain	Ford	104	18-AUG-19

```
ROLLBACK TO SP_NONE;
```

```
Rollback complete.
```

```
SQL> SELECT ROLL, FNAME, LNAME, ADVISOR, REG_DT FROM STUDENT;
```

ROLL	FNAME	LNAME	ADVISOR	REG_DT
1	Afra	Sayed	101	20-JUL-18
2	Akansha	Wasalu	104	20-JUL-18
3	Anjali	Rajendran	108	19-JUL-18
85	Yogesh	Siral	105	21-JUL-18
86	Shapath	Pandey	107	27-JUL-17
66	Ayush	Singh	107	27-JUL-17
88	NAVEEN	NAMJOSHI	109	14-AUG-19
89	TIPNIS	TUSHAR	110	14-AUG-19

Viva Voice

=====

\*\*\*\*\*Question-1\*\*\*\*\*

1. How does a simple view differ from a complex view

Ans:-

**SIMPLE VIEW**

- Contains only one single base table or is created from only one table.
- We cannot use group functions like MAX(), COUNT(), etc.
- Does not contain groups of data
- INSERT, DELETE and UPDATE are directly possible on a simple view.

**COMPLEX VIEW**

- Contains more than one base tables or is created from more than one tables
- We can use group functions.
- It can contain groups of data
- DML operations could not always be performed through a complex view

\*\*\*\*\*Question-2\*\*\*\*\*

2. What effect does altering parent table(s) have on a view(s) created on them?.

ANS:-Yes the data will be reflected because view constains the dynamic data.

\*\*\*\*\*Question-3\*\*\*\*\*

3. Can a sequence be reused? What will happen if it were enforced on the El-columns?

Ans:

Case 1:- if we use cycle

If we use cycle while creating the sequence then it can be re used

Case 2:- if we not use cycle

If we do not use cycle then sequence will not be reuse if it reaches to max value

Now if we were enforcing sequence on the El-columns then it will work fine in Case 2 but it will not work for case 1 because we need only unique values in EL-column.

\*\*\*\*\*Question-4\*\*\*\*\*

4. How does a synonym differ from an alias?

**Synonym:-**

- Synonyms are a database object type
- Synonyms can be created for tables, views, functions, procedures, packages,
- sequences, materialized views, java class object types and triggers.
- Since synonyms are a database object, they are valid inside the schema (private synonym) or inside the database (public synonym)

**Alias**

- aliases are just a name to refer a table, view or a column inside a query.
- Not a database object.
- aliases are used only for views, tables and their columns.
- aliases valid inside the query where they are being used.

\*\*\*\*\*Question-4\*\*\*\*\*

5. Do you need to remove savepoints explicitly?

NO,IT AUTOMATICALLY GETS REMOVE BY ORACLE .

\*\*\*\*\*

Inference:-

=====

1. View stores the dynamic data.
- 2.Index are created by default by oracle for primary key.
3. By default the index are private.
- 4.View is gives logical representation of data.
- 5.ORACLE ENGINE IMPLICITLY CREATE A INDEX ON PRIMARY KEY.