

Walid@PC-WALID MINGW64 ~/Desktop/learn_git (master)

\$ git log

commit 954735bb4f070e27b433d4141c14c6d5c72f28c9 (HEAD -> master)

Author: Khelfa <khelfawalid@gmail.com>

Date: Wed Oct 26 11:18:29 2022 +0200

removing third.txt

commit d465cbf6cfb17cd4a7ebb41f304c9de515b080c0

Author: Khelfa <khelfawalid@gmail.com>

Date: Wed Oct 26 11:12:57 2022 +0200

adding fourth.txt

commit 51dc5f4ed40c43a9fe61f40c6bca2489a5ffdb10

Author: Khelfa <khelfawalid@gmail.com>

Date: Wed Oct 26 10:34:55 2022 +0200

adding third.txt

Walid@PC-WALID MINGW64 ~/Desktop/learn_git (master)

\$ git config --global core.pager=cat

error: invalid key: core.pager=cat

Walid@PC-WALID MINGW64 ~/Desktop/learn_git (master)

\$ git config --global

usage: git config [<options>]

Config file location

| | |
|-------------------|------------------------------------|
| --global | use global config file |
| --system | use system config file |
| --local | use repository config file |
| --worktree | use per-worktree config file |
| -f, --file <file> | use given config file |
| --blob <blob-id> | read config from given blob object |

Action

| | |
|------------------|--|
| --get | get value: name [value-pattern] |
| --get-all | get all values: key [value-pattern] |
| --get-regexp | get values for regexp: name-regexp [value-pattern] |
| --get-urlmatch | get value specific for the URL: section[.var] URL |
| --replace-all | replace all matching variables: name value [value-pattern] |
| --add | add a new variable: name value |
| --unset | remove a variable: name [value-pattern] |
| --unset-all | remove all matches: name [value-pattern] |
| --rename-section | rename section: old-name new-name |
| --remove-section | remove a section: name |
| -l, --list | list all |
| --fixed-value | use string equality when comparing values to 'value-pattern' |

