

Module sui::display

Defines a Display struct which defines the way an Object should be displayed. The intention is to keep data as independent from its display as possible, protecting the development process and keeping it separate from the ecosystem agreements.

Each of the fields of the Display object should allow for pattern substitution and filling-in the pieces using the data from the object T.

More entry functions might be added in the future depending on the use cases.

The Display object. Defines the way a T instance should be displayed. Display object can only be created and modified with a PublisherCap, making sure that the rules are set by the owner of the type.

Each of the display properties should support patterns outside of the system, making it simpler to customize Display based on the property values of an Object.

Uses only String type due to external-facing nature of the object, the property names have a priority over their types.

Event: emitted when a new Display object has been created for type T. Type signature of the event corresponds to the type while id serves for the discovery.

Since Sui RPC supports querying events by type, finding a Display for the T would be as simple as looking for the first event with [Display](#).

Version of Display got updated -

For when T does not belong to the package Publisher.

For when vectors passed into one of the multiple insert functions don't match in their lengths.

Create an empty Display object. It can either be shared empty or filled with data right away via cheaper set_owned method.

Create a new Display object with a set of fields.

Create a new empty Display object and keep it.

Manually bump the version and emit an event with the updated version's contents.

Sets a custom name field with the value.

Sets multiple [fields](#) with values.

Change the value of the field. TODO (long run): version changes;

Remove the key from the Display.

Authorization check; can be performed externally to implement protection rules for Display.

Read the [version](#) field.

Read the [fields](#) field.

Internal function to create a new [Display](#).

Private method for inserting fields without security checks.

Struct

The Display object. Defines the way a T instance should be displayed. Display object can only be created and modified with a PublisherCap, making sure that the rules are set by the owner of the type.

Each of the display properties should support patterns outside of the system, making it simpler to customize Display based on the property values of an Object.

Uses only String type due to external-facing nature of the object, the property names have a priority over their types.

```
```bash
```

```
```
```

Event: emitted when a new Display object has been created for type T. Type signature of the event corresponds to the type while id serves for the discovery.

Since Sui RPC supports querying events by type, finding a Display for the T would be as simple as looking for the first event with [Display](#).

```
```bash
```

```
```
```

Version of Display got updated -

```
```bash
```

```
```
```

For when T does not belong to the package Publisher.

```
```bash
```

```
```
```

For when vectors passed into one of the multiple insert functions don't match in their lengths.

```
```bash
```

```
```
```

Create an empty Display object. It can either be shared empty or filled with data right away via cheaper set_owned method.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Create a new Display object with a set of fields.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Create a new empty Display object and keep it.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Manually bump the version and emit an event with the updated version's contents.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Sets a custom name field with the value.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Sets multiple [fields](#) with values.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Change the value of the field. TODO (long run): version changes;

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Remove the key from the Display.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Authorization check; can be performed externally to implement protection rules for Display.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Read the [version](#) field.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Read the [fields](#) field.

```
```bash
```

```
'''
```

```
'''bash
```

```
'''
```

Internal function to create a new [Display](#) .

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Private method for inserting fields without security checks.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

## Struct

Event: emitted when a new Display object has been created for type T. Type signature of the event corresponds to the type while id serves for the discovery.

Since Sui RPC supports querying events by type, finding a Display for the T would be as simple as looking for the first event with [Display](#) .

```
'''bash
```

```
'''
```

Version of Display got updated -

```
'''bash
```

```
'''
```

For when T does not belong to the package Publisher.

```
'''bash
```

```
'''
```

For when vectors passed into one of the multiple insert functions don't match in their lengths.

```
'''bash
```

```
'''
```

Create an empty Display object. It can either be shared empty or filled with data right away via cheaper set\_owned method.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Create a new Display object with a set of fields.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Create a new empty Display object and keep it.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Manually bump the version and emit an event with the updated version's contents.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Sets a custom name field with the value.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Sets multiple [fields](#) with values.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Change the value of the field. TODO (long run): version changes;

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Remove the key from the Display.

```
```bash
```

```
```
```

```
```bash
```

```
'''
```

Authorization check; can be performed externally to implement protection rules for Display.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Read the [version](#) field.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Read the [fields](#) field.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Internal function to create a new [Display](#) .

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Private method for inserting fields without security checks.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Struct

Version of Display got updated -

```
'''bash
```

```
'''
```

For when T does not belong to the package Publisher.

```
'''bash
```

```
'''
```

For when vectors passed into one of the multiple insert functions don't match in their lengths.

```
'''bash
```

```
'''
```

Create an empty Display object. It can either be shared empty or filled with data right away via cheaper `set_owned` method.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Create a new Display object with a set of fields.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Create a new empty Display object and keep it.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Manually bump the version and emit an event with the updated version's contents.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Sets a custom name field with the value.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Sets multiple [fields](#) with values.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Change the value of the field. TODO (long run): version changes;

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Remove the key from the Display.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Authorization check; can be performed externally to implement protection rules for Display.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Read the [version](#) field.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Read the [fields](#) field.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Internal function to create a new [Display](#) .

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Private method for inserting fields without security checks.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Constants

For when T does not belong to the package Publisher.

```
```bash
```

```
```
```

For when vectors passed into one of the multiple insert functions don't match in their lengths.

```
```bash
```

```
```
```

Create an empty Display object. It can either be shared empty or filled with data right away via cheaper set_owned method.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Create a new Display object with a set of fields.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Create a new empty Display object and keep it.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Manually bump the version and emit an event with the updated version's contents.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Sets a custom name field with the value.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Sets multiple [fields](#) with values.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Change the value of the field. TODO (long run): version changes;

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Remove the key from the Display.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Authorization check; can be performed externally to implement protection rules for Display.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Read the [version](#) field.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Read the [fields](#) field.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Internal function to create a new [Display](#) .

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Private method for inserting fields without security checks.

```
```bash
```

```
'''
```

```
'''bash
```

```
'''
```

## Function

Create an empty Display object. It can either be shared empty or filled with data right away via cheaper `set_owned` method.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Create a new Display object with a set of fields.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Create a new empty Display object and keep it.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Manually bump the version and emit an event with the updated version's contents.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Sets a custom name field with the value.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Sets multiple [fields](#) with values.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Change the value of the field. TODO (long run): version changes;

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Remove the key from the Display.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Authorization check; can be performed externally to implement protection rules for Display.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Read the [version](#) field.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Read the [fields](#) field.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Internal function to create a new [Display](#) .

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Private method for inserting fields without security checks.

```
```bash
```

```
```
```

```
```bash
```

```
'''
```

Function

Create a new Display object with a set of fields.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Create a new empty Display object and keep it.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Manually bump the version and emit an event with the updated version's contents.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Sets a custom name field with the value.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Sets multiple [fields](#) with values.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Change the value of the field. TODO (long run): version changes;

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Remove the key from the Display.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Authorization check; can be performed externally to implement protection rules for Display.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Read the [version](#) field.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Read the [fields](#) field.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Internal function to create a new [Display](#) .

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Private method for inserting fields without security checks.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Function

Create a new empty Display object and keep it.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Manually bump the version and emit an event with the updated version's contents.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Sets a custom name field with the value.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Sets multiple [fields](#) with values.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Change the value of the field. TODO (long run): version changes;

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Remove the key from the Display.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Authorization check; can be performed externally to implement protection rules for Display.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Read the [version](#) field.

```
```bash
```

```
```
```

```
```bash
```

```
'''
```

Read the [fields](#) field.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Internal function to create a new [Display](#) .

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Private method for inserting fields without security checks.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

## Function

Manually bump the version and emit an event with the updated version's contents.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Sets a custom name field with the value.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Sets multiple [fields](#) with values.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Change the value of the field. TODO (long run): version changes;

```
'''bash
```



```
'''
```

```
'''bash
```

```
'''
```

Remove the key from the Display.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Authorization check; can be performed externally to implement protection rules for Display.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Read the [version](#) field.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Read the [fields](#) field.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Internal function to create a new [Display](#) .

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Private method for inserting fields without security checks.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

## Function

Sets a custom name field with the value.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Sets multiple [fields](#) with values.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Change the value of the field. TODO (long run): version changes;

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Remove the key from the Display.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Authorization check; can be performed externally to implement protection rules for Display.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Read the [version](#) field.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Read the [fields](#) field.

```
```bash
```

```
```
```

```
```bash
```

```
'''
```

Internal function to create a new [Display](#) .

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Private method for inserting fields without security checks.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Function

Sets multiple [fields](#) with values.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Change the value of the field. TODO (long run): version changes;

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Remove the key from the Display.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Authorization check; can be performed externally to implement protection rules for Display.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Read the [version](#) field.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Read the [fields](#) field.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Internal function to create a new [Display](#) .

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Private method for inserting fields without security checks.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Function

Change the value of the field. TODO (long run): version changes;

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Remove the key from the Display.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Authorization check; can be performed externally to implement protection rules for Display.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Read the [version](#) field.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Read the [fields](#) field.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Internal function to create a new [Display](#) .

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Private method for inserting fields without security checks.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Function

Remove the key from the Display.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Authorization check; can be performed externally to implement protection rules for Display.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Read the [version](#) field.

```
```bash
```

```
```
```

```
'''bash
```

```
'''
```

Read the [fields](#) field.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Internal function to create a new [Display](#) .

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Private method for inserting fields without security checks.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Function

Authorization check; can be performed externally to implement protection rules for Display.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Read the [version](#) field.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Read the [fields](#) field.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Internal function to create a new [Display](#) .

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Private method for inserting fields without security checks.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Function

Read the [version](#) field.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Read the [fields](#) field.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Internal function to create a new [Display](#).

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Private method for inserting fields without security checks.

```
```bash
```

```
```
```

```
```bash
```

```
```
```

Function

Read the [fields](#) field.

```
```bash
```

```
'''
```

```
'''bash
```

```
'''
```

Internal function to create a new [Display](#) .

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Private method for inserting fields without security checks.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

## Function

Internal function to create a new [Display](#) .

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

Private method for inserting fields without security checks.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```

## Function

Private method for inserting fields without security checks.

```
'''bash
```

```
'''
```

```
'''bash
```

```
'''
```