

# The Move Book

Testing is a crucial aspect of software development, especially in blockchain applications where security and correctness are paramount. In this section, we will cover the fundamentals of testing in Move, including how to write and organize tests effectively.

Tests in Move are functions marked with the `#[test]` attribute. This attribute tells the compiler that the function is a test function and should be run when tests are executed. Test functions are regular functions, but they must take no arguments and have no return value. They are excluded from the bytecode and are never published.

To run tests, you can use the `sui move test` command. This command will first build the package in test mode and then run all tests found in the package. In test mode, modules from both `sources/` and `tests/` directories are processed and their tests executed.

Tests for fail cases can be marked with `#[expected_failure]`. This attribute, when added to a `#[test]` function, tells the compiler that the test is expected to fail. This is useful when you want to test that a function fails when a certain condition is met.

Note: This attribute can only be added to a `#[test]` function.

The attribute can take an argument specifying the expected abort code that should be returned if the test fails. If the test returns an abort code different from the one specified in the argument, it will fail. Likewise, if execution does not result in an abort, the test will also fail.

The `abort_code` argument can use constants defined in the `tests` module as well as imported from other modules. This is the only case where constants can be used and "accessed" in other modules.

In some cases, it is helpful to give the test environment access to some internal functions or features. This simplifies the testing process and allows for more thorough testing. However, it is important to remember that these functions should not be included in the final package. This is where the `#[test_only]` attribute comes in handy.

Functions marked with the `#[test_only]` will be available to the test environment, and to the other modules if their visibility is set to `public`.

## The

Tests in Move are functions marked with the `#[test]` attribute. This attribute tells the compiler that the function is a test function and should be run when tests are executed. Test functions are regular functions, but they must take no arguments and have no return value. They are excluded from the bytecode and are never published.

```
```bash module book::testing;
```

```
// The test attribute is placed before the fun keyword (can be both above or // right before the fun keyword, as in #[test] fun
my_test() { ... })// The name of the test in this case would be book::testing::simple_test.
```

## [test]

```
fun simple_test() { let sum = 2 + 2; assert!(sum == 4); }
```

```
// The name of this test would be book::testing::more_advanced_test.
```

## [test] fun more\_advanced\_test() {

```
let sum = 2 + 2 + 2;
assert!(sum == 4);

} ```
```

To run tests, you can use the `sui move test` command. This command will first build the package in test mode and then run all tests found in the package. In test mode, modules from both `sources/` and `tests/` directories are processed and their tests executed.

```
```bash $ sui move test
```

```
INCLUDING DEPENDENCY DeepBook INCLUDING DEPENDENCY SuiSystem INCLUDING  
DEPENDENCY Sui INCLUDING DEPENDENCY MoveStdlib BUILDING book Running Move unit tests ... ``
```

Tests for fail cases can be marked with `#[expected_failure]`. This attribute, when added to a `#[test]` function, tells the compiler that the test is expected to fail. This is useful when you want to test that a function fails when a certain condition is met.

Note: This attribute can only be added to a `#[test]` function.

The attribute can take an argument specifying the expected abort code that should be returned if the test fails. If the test returns an abort code different from the one specified in the argument, it will fail. Likewise, if execution does not result in an abort, the test will also fail.

```
``bash module book::testing_failure;  
const EInvalidArgument: u64 = 1;
```

## [test]

### [expected\_failure(abort\_code = 0)]

```
fun test_fail() { abort 0 // aborts with 0 }  
  
// attributes can be grouped together
```

### [test, expected\_failure(abort\_code = EInvalidArgument)]

```
fun test_fail_1() { abort 1 // aborts with 1 } ``
```

The `abort_code` argument can use constants defined in the tests module as well as imported from other modules. This is the only case where constants can be used and "accessed" in other modules.

In some cases, it is helpful to give the test environment access to some internal functions or features. This simplifies the testing process and allows for more thorough testing. However, it is important to remember that these functions should not be included in the final package. This is where the `#[test_only]` attribute comes in handy.

```
``bash module book::testing;  
  
// Public function which uses the secret function. public fun multiply_by_secret(x: u64): u64 { x * secret() }  
  
/// Private function which is not available to the public. fun secret(): u64 { 100 }
```

## [test\_only]

```
/// This function is only available for testing purposes in tests and other /// test-only functions. Mind the visibility - for #[test_only]  
it is /// common to use public visibility. public fun secret_for_testing(): u64 { secret() }
```

## [test]

```
// In the test environment we have access to the secret_for_testing function. fun test_multiply_by_secret() { let expected =  
secret_for_testing() * 2; assert!(multiply_by_secret(2) == expected); } ``
```

Functions marked with the `#[test_only]` will be available to the test environment, and to the other modules if their visibility is set to `public`.

## Running Tests

To run tests, you can use the `sui move test` command. This command will first build the package in test mode and then run all tests found in the package. In test mode, modules from both `sources/` and `tests/` directories are processed and their tests executed.

```
```bash $ sui move test
```

```
    UPDATING GIT DEPENDENCY https://github.com/MystenLabs/sui.git INCLUDING DEPENDENCY Bridge
    INCLUDING DEPENDENCY DeepBook INCLUDING DEPENDENCY SuiSystem INCLUDING
    DEPENDENCY Sui INCLUDING DEPENDENCY MoveStdlib BUILDING book Running Move unit tests ... ```
```

Tests for fail cases can be marked with `#[expected_failure]`. This attribute, when added to a `#[test]` function, tells the compiler that the test is expected to fail. This is useful when you want to test that a function fails when a certain condition is met.

Note: This attribute can only be added to a `#[test]` function.

The attribute can take an argument specifying the expected abort code that should be returned if the test fails. If the test returns an abort code different from the one specified in the argument, it will fail. Likewise, if execution does not result in an abort, the test will also fail.

```
```bash module book::testing_failure;
```

```
const EInvalidArgument: u64 = 1;
```

## [test]

### [expected\_failure(abort\_code = 0)]

```
fun test_fail() { abort 0 // aborts with 0 }
```

```
// attributes can be grouped together
```

### [test, expected\_failure(abort\_code = EInvalidArgument)]

```
fun test_fail_1() { abort 1 // aborts with 1 } ```
```

The `abort_code` argument can use constants defined in the tests module as well as imported from other modules. This is the only case where constants can be used and "accessed" in other modules.

In some cases, it is helpful to give the test environment access to some internal functions or features. This simplifies the testing process and allows for more thorough testing. However, it is important to remember that these functions should not be included in the final package. This is where the `#[test_only]` attribute comes in handy.

```
```bash module book::testing;
```

```
// Public function which uses the secret function. public fun multiply_by_secret(x: u64): u64 { x * secret() }
```

```
/// Private function which is not available to the public. fun secret(): u64 { 100 }
```

## [test\_only]

```
/// This function is only available for testing purposes in tests and other /// test-only functions. Mind the visibility - for #[test_only]
it is /// common to use public visibility. public fun secret_for_testing(): u64 { secret() }
```

## [test]

```
// In the test environment we have access to the secret_for_testing function. fun test_multiply_by_secret() { let expected =
secret_for_testing() * 2; assert!(multiply_by_secret(2) == expected); } ```
```

Functions marked with the `#[test_only]` will be available to the test environment, and to the other modules if their visibility is set to public.

## Test Fail Cases with

Tests for fail cases can be marked with `#[expected_failure]` . This attribute, when added to a `#[test]` function, tells the compiler that the test is expected to fail. This is useful when you want to test that a function fails when a certain condition is met.

Note: This attribute can only be added to a `#[test]` function.

The attribute can take an argument specifying the expected abort code that should be returned if the test fails. If the test returns an abort code different from the one specified in the argument, it will fail. Likewise, if execution does not result in an abort, the test will also fail.

```
```bash module book::testing_failure;

const EInvalidArgument: u64 = 1;
```

## [test]

### [expected\_failure(abort\_code = 0)]

```
fun test_fail() { abort 0 // aborts with 0 }

// attributes can be grouped together
```

### [test, expected\_failure(abort\_code = EInvalidArgument)]

```
fun test_fail_1() { abort 1 // aborts with 1 } ```
```

The `abort_code` argument can use constants defined in the tests module as well as imported from other modules. This is the only case where constants can be used and "accessed" in other modules.

In some cases, it is helpful to give the test environment access to some internal functions or features. This simplifies the testing process and allows for more thorough testing. However, it is important to remember that these functions should not be included in the final package. This is where the `#[test_only]` attribute comes in handy.

```
```bash module book::testing;

// Public function which uses the secret function. public fun multiply_by_secret(x: u64): u64 { x * secret() }

/// Private function which is not available to the public. fun secret(): u64 { 100 }
```

## [test\_only]

```
/// This function is only available for testing purposes in tests and other /// test-only functions. Mind the visibility - for #[test_only] it is /// common to use public visibility. public fun secret_for_testing(): u64 { secret() }
```

## [test]

```
// In the test environment we have access to the secret_for_testing function. fun test_multiply_by_secret() { let expected = secret_for_testing() * 2; assert!(multiply_by_secret(2) == expected); } ```
```

Functions marked with the `#[test_only]` will be available to the test environment, and to the other modules if their visibility is set to `public` .

## Utilities with

In some cases, it is helpful to give the test environment access to some internal functions or features. This simplifies the testing process and allows for more thorough testing. However, it is important to remember that these functions should not be included in the final package. This is where the `#[test_only]` attribute comes in handy.

```
```bash module book::testing;
```

```
// Public function which uses the secret function. public fun multiply_by_secret(x: u64): u64 { x * secret() }
```

```
/// Private function which is not available to the public. fun secret(): u64 { 100 }
```

## [test\_only]

```
/// This function is only available for testing purposes in tests and other /// test-only functions. Mind the visibility - for #[test_only] it is /// common to use public visibility. public fun secret_for_testing(): u64 { secret() }
```

## [test]

```
// In the test environment we have access to the secret_for_testing function. fun test_multiply_by_secret() { let expected = secret_for_testing() * 2; assert!(multiply_by_secret(2) == expected); } ``
```

Functions marked with the `#[test_only]` will be available to the test environment, and to the other modules if their visibility is set to `public` .

## Further Reading