Which Research Gaps Close? Forecasting Gap Closure in the 6G and IoT Literature

Anonymous Authors

Anonymous Institution

Abstract. Concept co-occurrence can identify missing combinations in the 6G and Internet of Things (IoT) literature, but many such combinations appear within a few years. We introduce GapCast-6G, a temporal benchmark of 194,221 OpenAlex papers (2010 to 2025) tagged with 90 concepts aligned with INISCOM topics. A structural gap at cutoff year T is an established concept pair with no detected joint title or abstract mention, and closure requires at least three joint mentions in papers published within the next three years. Between 14% and 25% of gaps close within three years. A logistic forecaster reaches mean AUC 0.809 across four publication-year-separated test cutoffs, compared with 0.659 for Adamic–Adar; concept-bootstrap intervals for this difference exclude zero at three cutoffs. Popularity and growth alone reach 0.776, accounting for most of the gain over single-feature scores. Across 20 subsets of 60 concepts, median mean AUC is 0.797 (range 0.737–0.845). Finally, we trace three closed 2022 gaps to specific corpus papers and rank the open gaps at the end of 2025 for the 2026–2028 window as relative priorities for literature inspection.

Keywords: Research gap · Link prediction · Science of science · 6G · Internet of Things · Big data analytics.

1 Introduction

Finding open problems is a routine step of research planning. Survey papers on 6G and IoT list open challenges [17,4,11], and literature-based discovery tools seek missing connections between concepts [19,9,8]. An absent combination is a candidate for investigation, but absence can be short-lived. For someone inspecting potential topics, it is useful to distinguish combinations likely to appear in the literature within a near-term window from those likely to remain absent. We investigate whether simple count-based signals can make that distinction in a wireless and IoT corpus.

To study this question, we freeze counts at a publication-year cutoff, list concept pairs with no detected joint mentions, and check which pairs meet a co-occurrence threshold within a three-year window. This formulates gap persistence as an application of temporal link prediction [14,8] using lexical co-occurrence proxies.

We use two terms in a deliberately narrow sense. A *structural gap* is an established concept pair with no detected joint mention in the selected corpus,

and its *closure* is a threshold number of subsequent papers mentioning both concepts. Such mentions indicate co-occurrence activity that can motivate closer inspection, though they do not by themselves prove deep technical integration or problem resolution. Our contributions are as follows.

- **A temporal benchmark for 6G and IoT.** GapCast-6G contains 194,221 papers from 15 OpenAlex topics [15], tagged with 90 concepts derived from the INISCOM 2027 topic list, with yearly concept and pair counts from 2010 to 2025.
- **A measurement of how fast gaps close.** Between 14% and 25% of the gaps open at a cutoff are filled within three years, and the gaps that classic rankings place first (the largest expected co-occurrence) are filled more often than the rest.
- **A publication-year-separated evaluation of simple forecasters.** A logistic model trained on completed outcome windows reaches mean AUC 0.809 against 0.659 for the strongest single score. Multi-feature baselines, concept bootstrap, ablation and fixed-seed vocabulary subsets assess how much the result depends on popularity, growth and the concept list.
- **Traceable examples and a forward-window ranking.** We connect three 2022 gaps to individual later corpus papers, and rank the 356 gaps open at the end of 2025 for the 2026–2028 window to support expert inspection.

2 Related Work

Literature-based discovery. Swanson's work on undiscovered public knowledge [19] started a line of methods that connect concepts through shared intermediate terms. Later systems use word embeddings [20] or semantic networks [9] to propose links that the literature has not yet made. Sourati and Evans [18] showed that adding the distribution of researchers improves such predictions. Our study examines the formation and persistence of missing concept combinations in a wireless and IoT corpus.

Link prediction in growing networks. Classic methods score node pairs with neighbourhood measures such as common neighbours and the Adamic–Adar index [1,14]. Science4Cast [8] predicts future links between previously unconnected concepts in artificial intelligence, varying link-count thresholds and prediction horizons across engineered features and learned models.

Distinction from Science4Cast and implications for planning. With a fixed horizon and closure threshold, gap persistence is the complement of future-link formation. Rather than proposing a new link-prediction algorithm, GapCast-6G contributes a focused, interpretable 6G/IoT vocabulary, measurements of persistence across INISCOM topic areas, dependence-aware comparisons of simple baselines, vocabulary sensitivity checks and paper-level evidence traces. For research planning, a high closure score can prioritise an emerging combination for literature monitoring, whereas a low score can prompt an expert to check whether a persistent omission is technically meaningful.

Novelty and recombination. Studies of scientific novelty measure how atypical a combination of references or concepts is [21,6]. A combination that is rare relative to the popularity of its parts is usually read as novel. Our results show that, for forecasting, the same quantity has a second reading: a large expected but absent combination is also one that the field is likely to fill soon.

Research gap verification. The ESV-Gap system [10] checks individual gap candidates against external evidence before reporting them. The present work estimates whether a lexical gap will cross a co-occurrence threshold within a fixed horizon. Claim verification would be a separate step.

6G and IoT roadmaps. Vision papers on 6G [17,4,11] list enabling technologies such as reconfigurable intelligent surfaces, terahertz links, integrated sensing and communication, and edge intelligence. Our concept list covers these technologies and the INISCOM topic areas, so the forecast can be read against these roadmaps.

3 The GapCast-6G Benchmark

Corpus. We used the OpenAlex API [15] to download article-type works from 2010 to 2025 with an abstract and a primary topic among 15 wireless and IoT topics, including advanced wireless communication technologies, MIMO systems, millimetre-wave propagation, optical wireless communication, satellite communication, UAV networks, IoT and edge/fog computing, wireless sensor networks, vehicular networks, cognitive radio and age of information. Each work enters once, through its primary topic. Cursor pagination applied filters for primary topic, publication years 2010–2025, article type and abstract availability, at a cost of about 0.1 USD of API credit. All queries were run on 30 October 2026. Because OpenAlex records and classifications can change, the planned artifact includes the frozen work-ID list, yearly count tensors, cached semantic similarities, lexicon, analysis code and seeds. These support reproduction from the fixed snapshot; repeating the API query need not recover that snapshot. The final corpus has 194,221 works (Table 1).

Concepts. We use a fixed lexicon of 90 concepts following the six INISCOM 2027 areas (wireless systems, industrial networks and intelligent systems, security and privacy, hardware and software design, signal processing and data analysis, quantum computing), expanded with enabling techniques such as RIS, NOMA, OTFS, ISAC, cell-free MIMO and semantic communication. Each concept has case-insensitive patterns; for example, *RIS* matches "reconfigurable intelligent surface", "intelligent reflecting surface", "RIS" and "IRS". A work mentions a concept if a pattern matches its title or abstract. Whole-word acronym matching can still mislabel ambiguous terms such as *IDS* or *OCC* (Section 6).

The lexicon is held fixed across cutoffs, and a concept enters a cutoff only after reaching m mentions. Section 5.6 examines a 2013-established vocabulary and random concept subsets to assess vocabulary sensitivity. Overall, 90.3% of works mention at least one concept, with a mean of 2.38 concepts per work. Table 2 lists the concepts by area; the most frequent are wireless sensor network

Table 1. OpenAlex primary topics of the corpus and the number of works per topic (2010 to 2025, articles with an abstract).

ID	OpenAlex topic	Works
T10080	Energy Efficient Wireless Sensor Networks	31,957
T10273	IoT and Edge/Fog Computing	21,664
T10125	Advanced Wireless Communication Techniques	20,422
T10851	Optical Wireless Communication Technologies	15,288
T10761	Vehicular Ad Hoc Networks (VANETs)	15,087
T10579	Cognitive Radio Networks and Spectrum Sensing	15,042
T10148	Advanced MIMO Systems Optimization	14,405
T11458	Advanced Wireless Communication Technologies	11,106
T10936	Millimeter-Wave Propagation and Modeling	9,677
T11133	UAV Applications and Optimization	9,125
T12042	Satellite Communication Systems	8,613
T11409	Advanced Wireless Network Optimization	7,590
T13535	Wireless Sensor Networks and IoT	6,542
T12079	IoT Networks and Protocols	6,276
T13553	Age of Information Optimization	1,427
	Total	194,221

(31,493), resource allocation (26,589), IoT (25,754), energy efficiency (21,634), MIMO (19,952).

Counts. For every year y we store the work count N_y, the count $n_y(a)$ mentioning concept a, and the count $n_y(a, b)$ mentioning both a and b. A stricter count $s_y(a, b)$ requires both concepts in the title or in the same sentence of the abstract. It filters separated mentions, but still admits lists and survey sentences. Cumulative counts are $N_{\leq T}$, $n_{\leq T}(a)$ and $n_{\leq T}(a, b)$.

4 Problem Definition and Methods

Gaps and closure. Fix a cutoff year T, a minimum support m, a gap tolerance g, a horizon H and a closure threshold k. A pair of concepts (a, b) is a *gap at* T if both concepts are established, $n_{\leq T}(a) \geq m$ and $n_{\leq T}(b) \geq m$, and the pair has been studied together at most g times, $n_{\leq T}(a, b) \leq g$. The gap is *filled* if

$$\sum_{y=T+1}^{T+H} n_y(a, b) \;\geq\; k. \tag{1}$$

Our main setting uses $m = 50$, $g = 0$, $H = 3$ and $k = 3$. Requiring three papers reduces sensitivity to one isolated mention; repeated incidental mentions can still satisfy the label. Section 5.6 varies each parameter.

Scores. Every score is computed from counts up to T only.

– *Expected co-occurrence*: we use the log expected joint count under independence, $\log\left(n_{\leq T}(a)\, n_{\leq T}(b)/N_{\leq T}\right)$. A larger value indicates a more expected absent combination. This is a frequency-product analogue of preferential attachment; support counts papers, rather than graph neighbours.

Table 2. The 90 concepts of GapCast-6G, grouped by INISCOM 2027 area (counts in brackets). Pattern definitions are provided in the accompanying lexicon source.

Area	Concepts
Wireless systems (39)	5G, 6G, age of information, backscatter, beamforming, body area network, cell-free, channel estimation, cognitive radio, digital twin, eMBB, energy efficiency, free-space optical, full-duplex, healthcare, ISAC, localization, massive MIMO, MIMO, mMTC, mmWave, NOMA, OFDM, optical camera communication, OTFS, physical layer security, quantum communication, relay, RIS, satellite communication, semantic communication, smart city, terahertz, UAV, underwater communication, URLLC, vehicular network, visible light communication, wireless power transfer
Industrial and intelligent (25)	autonomous network, cloud computing, deep learning, edge computing, edge intelligence, embedded system, energy management, federated learning, graph neural network, industrial IoT, intrusion detection, IoT, large language model, LoRa, metaverse, network slicing, optimization, reinforcement learning, resource allocation, routing, smart agriculture, smart grid, smart home, supply chain, wireless sensor network
Security and privacy (7)	authentication, blockchain, encryption, hardware security, jamming, post-quantum cryptography, privacy
HW/SW design (5)	antenna design, NFV, O-RAN, SDN, wearable
Signal processing and data (13)	big data, channel coding, channel modeling, compressive sensing, DOA estimation, fault diagnosis, image processing, information fusion, modulation, radar, signal detection, spectrum efficiency, speech processing
Quantum (1)	quantum computing

- *Concept growth*: for each concept, log of the ratio of its mentions in the last three years to the three years before, +1 smoothed. We use the smaller and the larger of the two values.
- *PPMI profile cosine*: each concept is represented by its positive pointwise mutual information [2] with every other concept, and two concepts are compared by the cosine of these profiles. This is a weighted form of the common-neighbour idea [1]: concepts that keep the same company are likely to meet. *Recent PPMI cosine* uses only the last three years.
- *Adamic–Adar index* [1]: the sum of $1/\log d(z)$ over the concepts z that have co-occurred with both a and b up to T, where $d(z)$ is the number of concepts z has co-occurred with.
- *Semantic similarity*: the cosine between sentence embeddings of each concept's name and patterns, computed with the `all-MiniLM-L6-v2` checkpoint [16].
- *Learned forecaster*: an ℓ_2-regularised logistic model (C=1, at most 2,000 solver iterations) with standardisation fitted on training rows only. Its seven inputs are expected co-occurrence, minimum log support, the two growth values, the two PPMI cosines and semantic similarity (plus the prior pair count $n_{\leq T}(a, b)$ when g>0).

We also evaluate two multi-feature baselines under the same protocol: logistic regression restricted to the four popularity and growth features, and gradient boosting (scikit-learn `HistGradientBoostingClassifier`, maximum depth 3, 200 iterations, learning rate 0.05) on the full feature set with fixed default hyperparameters.




Fig. 1. The GapCast-6G pipeline. Features use counts up to the cutoff only; labels use the following H years and are seen in training only for cutoffs whose window has ended.

Temporal protocol. Test cutoffs are $T \in \{2019, 2020, 2021, 2022\}$, with the final outcome window covering 2023–2025. At cutoff T, training uses gaps from cutoffs $2013, \ldots, T-H$, whose outcome windows end no later than T. A pair can contribute training rows at multiple cutoffs, and all splits are strictly by publication year rather than random pair partitioning. Count features and training labels use no publication years after T. We report ROC AUC, average precision (AP), the filled share among the 20 highest-scoring gaps (P@20), and the open share among the 20 lowest-scoring gaps (Open@20).

Uncertainty. We report pointwise 95% percentile intervals for paired AUC differences against expected co-occurrence, Adamic–Adar and the popularity-and-growth logistic model (1,000 bootstrap draws with fixed random seeds, conditional on the fitted models at each test cutoff). Pair bootstrap resamples gap pairs independently, whereas concept bootstrap resamples the 90 concepts with replacement and weights each pair (a, b) by the product of its endpoint multiplicities to account for shared-node dependence (discarding draws with fewer than ten retained pairs or a single outcome class).

Pipeline. Fig. 1 summarises the steps. The whole pipeline runs on a laptop CPU: tagging the corpus takes about 25 minutes and all experiments take a few minutes.

5 Results

5.1 How Fast Do Gaps Close?

Fig. 2 (left) follows the 264 gaps that were open in 2013. Within three years 20% of them were filled, and by 2025 the share had reached 86%. At the four test cutoffs, between 462 and 560 pairs are gaps and 14% to 25% of them close within three years (Table 3, last row). A list of absent combinations is therefore a mix of long-lasting gaps and openings that the field is already moving into.

Fig. 2 (right) splits the gaps by expected co-occurrence. Gaps in the top quintile, which a classic ranking reports as the most striking omissions, were filled in 30% of cases, against 10% in the bottom quintile. Expected co-occurrence does carry signal, but in the opposite direction from how it is often used: a large




Fig. 2. Left: cumulative share of the 264 gaps open in 2013 that were filled ($\geq$ 3 joint papers) by each later year. Right: three-year fill rate by quintile of expected co-occurrence; quintile 5 holds the "largest" gaps by the classic ranking.

Table 3. Forecasting which gaps are filled within three years (m=50, g=0, k=3, H=3). Higher is better for every column. P@20: share filled among the 20 top-ranked gaps; Open@20: share still open among the 20 lowest-ranked gaps.

	AUC at cutoff T				Mean over cutoffs			
Score	2019	2020	2021	2022	AUC	AP	P@20	Open@20
Random	0.484	0.556	0.565	0.514	0.530	0.217	0.200	0.850
Expected co-occurrence	0.651	0.593	0.658	0.636	0.635	0.297	0.350	0.975
Concept growth (min)	0.623	0.575	0.558	0.569	0.581	0.282	0.388	0.800
PPMI profile cosine	0.554	0.596	0.621	0.632	0.601	0.267	0.263	0.838
Recent PPMI cosine	0.531	0.572	0.601	0.619	0.581	0.255	0.250	0.788
Adamic–Adar index	0.571	0.643	0.734	0.687	0.659	0.342	0.475	0.963
Semantic similarity (MiniLM)	0.483	0.519	0.554	0.545	0.525	0.232	0.225	0.837
Logistic, popularity + growth	0.727	0.733	0.836	0.808	0.776	0.476	0.637	1.000
Gradient boosting	0.709	0.728	0.820	0.835	0.773	0.482	0.688	0.975
Learned forecaster	0.734	0.768	0.863	0.870	**0.809**	**0.524**	**0.688**	0.975
Gaps / filled rate	540/0.25	503/0.18	462/0.14	560/0.23				

expected-but-absent pair is more likely to be a short-lived gap than a durable one.

5.2 Forecasting Gap Closure

Table 3 compares the scores. The learned forecaster reaches mean AUC 0.809 and AP 0.524. The strongest single score by mean AUC is the Adamic–Adar index (0.659), followed by expected co-occurrence (0.635). Popularity and growth alone reach 0.776, accounting for most of the improvement over single scores, while the default gradient boosting baseline reaches 0.773. Semantic similarity alone is close to chance (0.525). Among the 20 highest-scoring gaps, the mean filled share is 0.69; among the 20 lowest-scoring gaps, the mean open share is 0.97. Expected co-occurrence achieves the same Open@20, indicating that

Table 4. Pointwise 95% bootstrap intervals for learned AUC minus comparator AUC at each cutoff. Concept resampling assigns pair weights from shared endpoint multiplicities.

T	Expected co-occ. pair bootstrap	Expected co-occ. concept bootstrap	Adamic–Adar concept bootstrap	Logistic P+G concept bootstrap
2019	[0.024, 0.140]	[-0.043, 0.209]	[0.003, 0.290]	[-0.049, 0.062]
2020	[0.110, 0.252]	[0.055, 0.320]	[0.013, 0.247]	[-0.024, 0.094]
2021	[0.131, 0.280]	[0.066, 0.334]	[-0.017, 0.280]	[-0.024, 0.096]
2022	[0.174, 0.293]	[0.121, 0.334]	[0.065, 0.314]	[0.015, 0.121]

Table 5. Left: drop-one and keep-only ablation of the learned forecaster (mean over the four test cutoffs). Right: standardised weights of the model trained for T=2022.

Feature set	AUC	AP
All features	0.809	0.524
without popularity	0.703	0.375
without growth	0.729	0.387
without PPMI profile cosine	0.802	0.514
without recent PPMI cosine	0.810	0.525
without semantic similarity	0.811	0.526
growth only	0.702	0.364
popularity only	0.637	0.297

Feature (standardised)	Weight
Expected co-occ.	+0.94
Min. support	-0.09
Growth (min)	+0.22
Growth (max)	+0.61
PPMI profile cos.	+0.55
Recent PPMI cos.	+0.04
Semantic sim.	+0.03

the forecaster's main advantage lies in ranking near-term closures rather than isolating the most persistent tail.

Table 4 gives paired AUC-difference intervals. Pair resampling excludes zero against expected co-occurrence at every cutoff, and concept resampling does so at three cutoffs. Against the strongest single score, Adamic–Adar, the mean point-estimate gain is 0.150, with concept intervals excluding zero at three cutoffs (the 2021 interval crosses zero and the 2019 lower bound is close to zero). By contrast, the full model's gain over popularity-and-growth logistic regression excludes zero at only one cutoff. Thus, while the full model outperforms every single score in mean AUC, its additional network and semantic features offer only a modest incremental gain over popularity and growth.

5.3 What Drives the Forecast?

Table 5 shows the ablation and model weights. Removing growth lowers mean AUC to 0.729; removing popularity lowers it to 0.703. Growth alone reaches 0.702 and popularity alone 0.637. Removing semantic similarity gives 0.811, with no loss in performance. The largest positive weights belong to expected co-occurrence (+0.94), the faster concept's growth (+0.61) and PPMI profile cosine (+0.55), indicating that combinations of popular or rapidly expanding concepts are the primary predictors of near-term closure.

Table 6 lists concrete cases at T=2022. Of the ten top-ranked gaps, 8 were filled in the next three years; of the ten lowest-ranked, 0 were.

Table 6. The ten highest- and lowest-ranked gaps at T=2022 and later papers with detected joint mentions in 2023–2025 (closure needs ≥ 3).

Top-ranked at T=2022		Bottom-ranked at T=2022	
Concept pair	Co-occ.	Concept pair	Co-occ.
RIS × semantic communication	26	DOA estimation × supply chain	0
RIS × autonomous network	7	DOA estimation × body area network	1
RIS × smart home	8	NFV × hardware security	0
RIS × smart agriculture	5	quantum communication × supply chain	0
intrusion detection × semantic communication	0	DOA estimation × NFV	0
ISAC × wireless power transfer	16	body area network × quantum communication	0
physical layer security × semantic communication	9	O-RAN × hardware security	0
RIS × wearable	0	O-RAN × supply chain	0
age of information × digital twin	28	fault diagnosis × hardware security	0
cognitive radio × semantic communication	7	body area network × hardware security	0

Table 7. Three-year fill rate of gaps by the INISCOM areas of the two concepts, pooled over the four test cutoffs (number of gaps in brackets; cells with fewer than 20 gaps are greyed). The quantum area has a single concept, so it has no gaps within itself.

	Wireless	Industrial/intell.	Security	HW/SW	Signal/data	Quantum
Wireless	0.30 (317)	0.23 (534)	0.17 (121)	0.17 (172)	0.14 (311)	(10)
Industrial/intell.		0.39 (75)	0.23 (40)	0.18 (90)	0.14 (170)	(9)
Security			(0)	0.35 (20)	0.22 (45)	(0)
HW/SW				(8)	0.04 (93)	(4)
Signal/data					0.11 (37)	(9)
Quantum						(0)

5.4 Gaps Across the INISCOM Areas

Table 7 groups 2,065 pair–cutoff observations across the four test cutoffs. Within-area gaps close in 30% of observations (437), compared with 18% for cross-area gaps (1,628). Gaps within the industrial and intelligent systems area close most frequently, whereas those between hardware/software and signal processing rarely close.

5.5 Calibration

A forecast is easier to use if its probabilities can be read at face value. On the pooled test gaps the forecaster has a Brier score of 0.137, against 0.162 for a constant forecast at the pooled fill rate of 20% (a rate that is only known in hindsight). Table 8 shows, however, that the probabilities are too high in every quintile: gaps in the top quintile have a mean forecast of 0.61 and an observed fill rate of 0.51, and gaps in the bottom quintile 0.07 against 0.03. The training cutoffs had higher fill rates than the test cutoffs, and the model carries that base rate forward.

Table 8. Calibration of the learned forecaster on the 2,065 pooled test gaps, by quintile of the predicted probability.

	Raw logistic output		Temporal Platt scaling	
Quintile	Mean $\hat{p}$	Observed	Mean $\hat{p}$	Observed
1	0.068	0.029	0.078	0.031
2	0.137	0.070	0.146	0.061
3	0.214	0.138	0.217	0.143
4	0.338	0.274	0.334	0.281
5	0.608	0.506	0.587	0.501
Brier	0.137		0.138	

Table 9. Mean AUC over the four test cutoffs under alternative definitions of gap and closure.

Setting	Gaps (mean)	Filled	Best single score	Learned
main (m=50, g=0, k=3, H=3)	516	0.20	0.659	0.809
g=2 (sparse, not only absent)	996	0.31	0.672	0.816
k=1	516	0.53	0.661	0.750
k=5	516	0.11	0.642	0.814
H=2	516	0.11	0.640	0.810
m=20	710	0.21	0.649	0.798
m=100	307	0.24	0.649	0.806
same-sentence closure label	516	0.08	0.620	0.793
concepts established by 2013 only	35	0.12	0.827	0.924

We tried temporal Platt scaling: the forecaster is trained on cutoffs up to $T-H-1$, a logistic score-to-outcome map is fitted on cutoff $T-H$, and that map is applied at T. It did not improve the pooled Brier score (0.138; top quintile 0.59 predicted against 0.50 observed), consistent with continuing base-rate drift. The backtest supports ranking discrimination, but absolute outputs, including Table 11, should be read as relative closure scores.

5.6 Robustness

Table 9 varies one choice at a time: gaps that allow up to two earlier joint papers (g=2), a looser or stricter closure threshold (k=1, k=5), a two-year horizon, a lower or higher support threshold for established concepts, a stricter closure label and a vocabulary restricted to 2013.

Same-sentence label. This label filters mentions separated across sentences while retaining the document-level gap definition and count features. Over the corpus, 54% of document-level pair occurrences survive. The mean closure rate becomes 8%, and mean AUC is 0.793 against 0.620 for the strongest single score (0.783 for popularity-and-growth logistic regression). Co-mention within a sentence remains a lexical proxy, including when a sentence lists technologies.

Vocabulary of 2013. Restricting the vocabulary to concepts with at least m mentions by 2013 removes concepts that became established later. Only 25–52 gaps remain per cutoff, with very few closures at some cutoffs. The AUC of 0.92

Table 10. Vocabulary sensitivity over 20 fixed-seed subsets of 60/90 concepts. Each run first averages AUC over the four cutoffs; entries summarise those run means. The single-score comparator is chosen retrospectively within each subset. Ranges are descriptive, not confidence intervals.

Method	Median	Minimum	Maximum
Learned forecaster	0.797	0.737	0.845
Logistic, popularity + growth	0.766	0.714	0.828
Strongest single score in subset	0.651	0.616	0.692

(strongest single score 0.83) is therefore too unstable to establish an improvement or resolve retrospective vocabulary bias.

Across the eight settings other than the 2013 vocabulary, the learned forecaster stays between 0.75 and 0.82 mean AUC and is ahead of the best single score in every setting.

Random concept subsets. To test sensitivity to concept selection, we draw 20 subsets of 60 concepts without replacement (NumPy seed 2027) and recompute graph profiles, eligible pairs and both logistic models on each induced vocabulary. The average number of gaps across cutoffs ranges from 178.5 to 298.8. Table 10 shows a median mean AUC of 0.797 (range 0.737–0.845) for the full model, which exceeds the strongest single score in all 20/20 subsets and achieves a median paired gain of 0.024 over popularity-and-growth logistic regression.

5.7 What the Backtest Means for 6G Research Planning

We trace three top-ranked 2022 pairs from Table 6 to their underlying corpus records. Each pair had zero detected joint mentions through 2022. In 2023–2025, RIS with semantic communication accumulated 26 joint-mention papers (23 same-sentence); age of information (AoI) with digital twins had 28 (15); and ISAC with wireless power transfer had 16 (12). While these totals include surveys and passing mentions, we highlight two representative papers per pair below (with DOIs and OpenAlex IDs) to illustrate how the concepts were combined in practice.

RIS and semantic communication. Du et al. [5] (`W4382119085`) design RIS-aided encoding of wireless sensing spectra with self-supervised decoding. Huang et al. [7] (`W4401113937`) align a semantic classification objective with active transmitter and passive RIS beamforming. Both studies directly couple propagation hardware with task-oriented representations rather than merely listing the two terms.

AoI and digital twins. Li et al. [12] (`W4387831770`) optimise digital-twin placement in mobile edge computing using an AoI-based service-satisfaction metric (indexed under its 2023 online publication date in OpenAlex and published in a 2024 issue). A second study [13] (`W4396667043`) jointly optimises the freshness of twin-enabled query results and query-service delay under edge capacity

Table 11. Gaps open at the end of 2025 with the highest and lowest closure scores $\hat{p}$ for 2026–2028 (trained on cutoffs through 2022, using publications up to 2025; scores are uncalibrated, see Section 5.5).

Most likely to be filled by 2028		Most likely to stay open	
Concept pair	$\hat{p}$	Concept pair	$\hat{p}$
energy management × large language model	0.83	NFV × optical camera communication	0.019
large language model × post-quantum cryptography	0.75	DOA estimation × NFV	0.023
large language model × quantum communication	0.73	NFV × OTFS	0.025
intrusion detection × semantic communication	0.72	OTFS × supply chain	0.025
metaverse × wireless sensor network	0.68	OTFS × body area network	0.025
graph neural network × image processing	0.68	OTFS × hardware security	0.026
NFV × large language model	0.64	body area network × hardware security	0.027
ISAC × encryption	0.64	optical camera communication × supply chain	0.032
fault diagnosis × metaverse	0.64	NFV × hardware security	0.033
compressive sensing × large language model	0.62	DOA estimation × supply chain	0.033

constraints, making information freshness an explicit part of digital-twin state management.

ISAC and wireless power transfer. Cui et al. [3] (`W4393955155`) analyse a vehicular NOMA–ISAC system with IRS-assisted simultaneous wireless information and power transfer (SWIPT), using time switching to supply energy to a sensing vehicle. Yaswanth et al. [22] (`W4407690662`) optimise sensing and communication in an active/STAR-RIS-assisted MIMO system under energy-harvesting constraints, jointly addressing sensing, data transmission and power delivery.

At the opposite end of the ranking, low-scoring pairs such as direction-of-arrival estimation with supply chains remain absent. In practice, a high closure score can help researchers prioritise emerging intersections for literature monitoring, whereas a low score flags persistent omissions that require domain judgment to separate unpromising pairings from overlooked problems.

5.8 Forward-Window Ranking for 2026 to 2028

Finally, we trained the forecaster on cutoffs 2013–2022 and scored the 356 gaps remaining open at the end of 2025 for the 2026–2028 window (Table 11, constructed from pre-2026 records). The highest-scoring candidates are dominated by large language models paired with established areas such as energy management, post-quantum cryptography and network function virtualisation, whereas low-scoring pairs largely pair specialised physical-layer techniques with distant application domains.

6 Discussion and Limitations

Label validity and research utility. Joint mentions can reflect a shared technical design, background discussion, a survey or an incidental list, and the same-sentence filter cannot fully separate these cases. Our paper traces in Section 5.7 illustrate substantive integration in three closed gaps, but a blinded human annotation study and an expert decision evaluation remain necessary to measure label precision and downstream planning utility. Claim-level verification systems such as ESV-Gap [10] address a complementary evidential question.

Lexical and retrospective resources. Pattern matching misses paraphrases and can confuse ambiguous acronyms, and such errors may correlate with concept popularity or community-specific terminology. In addition, the 90-concept lexicon and pretrained sentence encoder are retrospective resources; the 2013 vocabulary check and random concept subsets assess sensitivity within this corpus, but do not reconstruct historical vocabularies or test generalisation to external corpora.

Model scope. The logistic forecaster relies on standard engineered features and fixed hyperparameters. Its strong performance relative to a default gradient-boosting baseline does not rule out gains from tuned nonlinear ensembles or temporal graph neural networks, and we do not claim algorithmic novelty over general link-prediction frameworks.

Corpus coverage and historical availability. Our snapshot includes only article-type works with abstracts in the 15 selected OpenAlex primary topics, omitting preprints, records without abstracts and papers assigned to other primary topics. Because OpenAlex backfills metadata and topic classifications over time, publication-year separation prevents future-count leakage in features and labels but does not replicate real-time historical indexing; delayed indexing may also depress the observed closure rate in the final window.

Small and dependent test sets. Each cutoff contains a few hundred gaps, and pairs share concepts and recur across cutoffs with overlapping outcome windows. Concept bootstrap accounts for shared-endpoint dependence within each cutoff conditional on the fitted models, without adjusting for training variance or cross-year correlation.

7 Conclusion

In this 6G and IoT corpus, between 14% and 25% of established concept pairs with no prior joint mentions cross a three-paper co-occurrence threshold within three years. Combining concept popularity and recent growth provides substantially stronger closure discrimination than single-score heuristics: the full logistic forecaster reaches mean AUC 0.809 compared with 0.659 for Adamic–Adar (with concept-bootstrap intervals excluding zero at three of four test cutoffs), while most of this gain is already captured by popularity and growth (0.776). Across 20 fixed-seed concept subsets, the model maintains a median mean AUC of 0.797. Together, GapCast-6G and our backtest offer a domain-specific benchmark and

empirical baseline for tracking how quickly missing technical combinations close in the wireless and IoT literature. Future work will focus on human-annotated label validation and expert evaluation of closure forecasts in research planning. The analysis code, lexicon, frozen work-ID list, count tensors, cached semantic similarities and paper-level evidence traces will be released upon publication.

Acknowledgments. AI-based writing and coding assistants were used for language editing, code development and assistance with literature search. Responsibility for the study and the final manuscript rests with the authors.

Disclosure of Interests. The authors have no competing interests to declare that are relevant to the content of this article.

References

1. Adamic, L.A., Adar, E.: Friends and neighbors on the web. Social Networks **25**(3), 211–230 (2003). https://doi.org/10.1016/S0378-8733(03)00009-1
2. Church, K.W., Hanks, P.: Word association norms, mutual information, and lexicography. Computational Linguistics **16**(1), 22–29 (1990)
3. Cui, D., Li, Y., Zhang, K., Wang, X.: Communication and sensing performance study of NOMA-ISAC system with IRS-assisted SWIPT. Journal of Electronics and Information Science **9**(1), 85–94 (2024). https://doi.org/10.23977/jeis.2024.090113
4. Dang, S., Amin, O., Shihada, B., Alouini, M.S.: What should 6G be? Nature Electronics **3**, 20–29 (2020). https://doi.org/10.1038/s41928-019-0355-6
5. Du, H., Wang, J., Niyato, D., Kang, J., Xiong, Z., Zhang, J., Shen, X.: Semantic communications for wireless sensing: RIS-aided encoding and self-supervised decoding. IEEE Journal on Selected Areas in Communications **41**(8), 2547–2562 (2023). https://doi.org/10.1109/JSAC.2023.3288231
6. Foster, J.G., Rzhetsky, A., Evans, J.A.: Tradition and innovation in scientists' research strategies. American Sociological Review **80**(5), 875–908 (2015). https://doi.org/10.1177/0003122415601618
7. Huang, Y., Cai, C., Yuan, X., Zhang, Y.J.A.: Joint active and passive beamforming for RIS-aided semantic communication. IEEE Transactions on Vehicular Technology **73**(12), 19815–19820 (2024). https://doi.org/10.1109/TVT.2024.3435754
8. Krenn, M., Buffoni, L., Coutinho, B., Eppel, S., Foster, J.G., Gritsevskiy, A., Lee, H., Lu, Y., Moutinho, J.P., Sanjabi, N., et al.: Forecasting the future of artificial intelligence with machine learning-based link prediction in an exponentially growing knowledge network. Nature Machine Intelligence **5**, 1326–1335 (2023). https://doi.org/10.1038/s42256-023-00735-0
9. Krenn, M., Zeilinger, A.: Predicting research trends with semantic and neural networks with an application in quantum physics. Proceedings of the National Academy of Sciences **117**(4), 1910–1916 (2020). https://doi.org/10.1073/pnas.1914370116
10. Le, A.H., Nguyen, D.T., Phan, L.V.K., Truong, L., Nguyen, D.H., Ho, D.A.: ESV-Gap: An auditable autonomous reasoning architecture for evidence-grounded scientific hypothesis triage. In: Autonomous Machine Intelligence (AMI 2027). Communications in Computer and Information Science, Springer (2027), to appear

11. Letaief, K.B., Chen, W., Shi, Y., Zhang, J., Zhang, Y.J.A.: The roadmap to 6G: AI empowered wireless networks. IEEE Communications Magazine **57**(8), 84–90 (2019). https://doi.org/10.1109/MCOM.2019.1900271
12. Li, J., Guo, S., Liang, W., Wang, J., Chen, Q., Xu, Z., Xu, W.: AoI-aware user service satisfaction enhancement in digital twin-empowered edge computing. IEEE/ACM Transactions on Networking **32**(2), 1677–1690 (2024). https://doi.org/10.1109/TNET.2023.3324704, published online 20 October 2023
13. Li, J., Guo, S., Liang, W., Wu, J., Chen, Q., Xu, Z., Xu, W., Wang, J.: AoI-aware, digital twin-empowered IoT query services in mobile edge computing. IEEE/ACM Transactions on Networking **32**(4), 3636–3650 (2024). https://doi.org/10.1109/TNET.2024.3395709
14. Liben-Nowell, D., Kleinberg, J.: The link-prediction problem for social networks. Journal of the American Society for Information Science and Technology **58**(7), 1019–1031 (2007). https://doi.org/10.1002/asi.20591
15. Priem, J., Piwowar, H., Orr, R.: OpenAlex: A fully-open index of scholarly works, authors, venues, institutions, and concepts. arXiv preprint arXiv:2205.01833 (2022)
16. Reimers, N., Gurevych, I.: Sentence-BERT: Sentence embeddings using Siamese BERT-networks. In: Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP). pp. 3982–3992 (2019). https://doi.org/10.18653/v1/D19-1410
17. Saad, W., Bennis, M., Chen, M.: A vision of 6G wireless systems: Applications, trends, technologies, and open research problems. IEEE Network **34**(3), 134–142 (2020). https://doi.org/10.1109/MNET.001.1900287
18. Sourati, J., Evans, J.A.: Accelerating science with human-aware artificial intelligence. Nature Human Behaviour **7**, 1682–1696 (2023). https://doi.org/10.1038/s41562-023-01648-z
19. Swanson, D.R.: Fish oil, Raynaud's syndrome, and undiscovered public knowledge. Perspectives in Biology and Medicine **30**(1), 7–18 (1986). https://doi.org/10.1353/pbm.1986.0087
20. Tshitoyan, V., Dagdelen, J., Weston, L., Dunn, A., Rong, Z., Kononova, O., Persson, K.A., Ceder, G., Jain, A.: Unsupervised word embeddings capture latent knowledge from materials science literature. Nature **571**, 95–98 (2019). https://doi.org/10.1038/s41586-019-1335-8
21. Uzzi, B., Mukherjee, S., Stringer, M., Jones, B.: Atypical combinations and scientific impact. Science **342**(6157), 468–472 (2013). https://doi.org/10.1126/science.1240474
22. Yaswanth, J., Saikia, P., Singh, K., Kim, Y.H., Duong, T.Q.: Active and STAR-RIS-assisted MIMO ISAC systems with SWIPT. IEEE Transactions on Cognitive Communications and Networking **11**(6), 3842–3858 (2025). https://doi.org/10.1109/TCCN.2025.3543405