

検査成績表

品名 零相電圧検出装置	形式 VOC-1MS2-3M	製造番号 370590																															
定格電圧 6600VAC	定格周波数 50/60Hz																																
1. 外観・構造 良 2. 特性 <table border="1"> <tr> <th rowspan="2">入力</th> <th>検査項目</th> <th colspan="2">出力電圧特性</th> <th>位相特性</th> <th rowspan="2">判定</th> </tr> <tr> <th>入力条件</th> <th>5%(190V)</th> <th>15%(571V)</th> <th>286V(50Hz)</th> </tr> <tr> <td rowspan="2">G</td> <td>規格</td> <td>0.342~0.418V</td> <td>1.026~1.254V</td> <td>168~180度</td> <td rowspan="2">良</td> </tr> <tr> <td>50Hz</td> <td>0.387 V</td> <td>1.07 V</td> <td rowspan="2">170 度</td> </tr> <tr> <td>60Hz</td> <td>0.394 V</td> <td>1.11 V</td> <td></td> </tr> </table> ※負担抵抗：100KΩ 3. 絶縁抵抗・耐電圧 良 <table border="1"> <tr> <th>印加箇所</th> <th>絶縁抵抗</th> <th>耐電圧</th> </tr> <tr> <td>K3P-M 端子一括と外箱間</td> <td>DC500V 効 - 10MΩ 以上</td> <td>AC2000V 1 分間</td> </tr> </table>				入力	検査項目	出力電圧特性		位相特性	判定	入力条件	5%(190V)	15%(571V)	286V(50Hz)	G	規格	0.342~0.418V	1.026~1.254V	168~180度	良	50Hz	0.387 V	1.07 V	170 度	60Hz	0.394 V	1.11 V		印加箇所	絶縁抵抗	耐電圧	K3P-M 端子一括と外箱間	DC500V 効 - 10MΩ 以上	AC2000V 1 分間
入力	検査項目	出力電圧特性			位相特性	判定																											
	入力条件	5%(190V)	15%(571V)	286V(50Hz)																													
G	規格	0.342~0.418V	1.026~1.254V	168~180度	良																												
	50Hz	0.387 V	1.07 V	170 度																													
60Hz	0.394 V	1.11 V																															
印加箇所	絶縁抵抗	耐電圧																															
K3P-M 端子一括と外箱間	DC500V 効 - 10MΩ 以上	AC2000V 1 分間																															
備考	検査日 23 年 7 月 21 日 温度 24 °C 湿度 65 %	検査 																															