

Artificial Intelligence

Perceptron Learning


Algorithm

A watermark logo is centered behind the title. It features a stylized orange cube with the letters 'HCMUT' and 'CNCP' on its faces. Above the cube, the text 'BACHKHOACNCP.COM' is written in an arc. Below the cube, the text 'TÀI LIỆU SƯU TẬP' is written in an arc, and 'BỞI HCMUT-CNCP' is written in a straight line.

Pham Viet Cuong
Dept. Control Engineering & Automation, FEEE
Ho Chi Minh City University of Technology


Perceptron Learning Algorithm

✓ Proposed by Minsky and Papert in 1969



Perceptron Learning Algorithm

- ✓ A single perceptron can only be used to implement linearly separable functions



TÀI LIỆU SƯU TẬP
BỞI HCMUT-CNCP

$$y = 1 \quad \text{if} \quad \sum_{i=0}^n w_i * x_i \geq 0$$

$$= 0 \quad \text{if} \quad \sum_{i=0}^n w_i * x_i < 0$$

where, $x_0 = 1$ and $w_0 = -\theta$

Perceptron Learning Algorithm

✓ OR function using a Perceptron

x_1	x_2	OR	
0	0	0	$w_0 + \sum_{i=1}^2 w_i x_i < 0$
1	0	1	$w_0 + \sum_{i=1}^2 w_i x_i \geq 0$
0	1	1	$w_0 + \sum_{i=1}^2 w_i x_i \geq 0$
1	1	1	$w_0 + \sum_{i=1}^2 w_i x_i \geq 0$

$$w_0 + w_1 \cdot 0 + w_2 \cdot 0 < 0 \implies w_0 < 0$$


$$w_0 + w_1 \cdot 0 + w_2 \cdot 1 \geq 0 \implies w_2 > -w_0$$

$$w_0 + w_1 \cdot 1 + w_2 \cdot 0 \geq 0 \implies w_1 > -w_0$$

$$w_0 + w_1 \cdot 1 + w_2 \cdot 1 \geq 0 \implies w_1 + w_2 > -w_0$$


One possible solution is

$$w_0 = -1, w_1 = 1.1, w_2 = 1.1$$



Perceptron Learning Algorithm

✓ Dot product of 2 vectors



$$y = 1 \quad \text{if} \quad \sum_{i=0}^n w_i * x_i \geq 0$$

$$= 0 \quad \text{if} \quad \sum_{i=0}^n w_i * x_i < 0$$

where, $x_0 = 1$ and $w_0 = -\theta$

TÀI LIỆU SƯU TẬP
BỞI HCMUT-CNCP

$$\mathbf{W} = [w_0, w_1, w_2, \dots, w_n]$$

$$\mathbf{X} = [1, x_1, x_2, \dots, x_n]$$

$$\mathbf{W} \cdot \mathbf{X} = \mathbf{W}^T \mathbf{X} = \sum_{i=0}^n w_i * x_i$$

Perceptron Learning Algorithm

✓ Algorithm

- ❖ Goal: Find vector w that can perfectly classify positive inputs and negative inputs

$$y = 1 \quad \text{if} \quad \sum_{i=0}^n w_i * x_i \geq 0$$

$$= 0 \quad \text{if} \quad \sum_{i=0}^n w_i * x_i < 0$$

where, $x_0 = 1$ and $w_0 = -\theta$

Algorithm: Perceptron Learning Algorithm

```

P ← inputs with label 1;
N ← inputs with label 0;
Initialize w randomly;
while !convergence do
    Pick random x ∈ P ∪ N ;
    if x ∈ P and w.x < 0 then
        w = w + x ;
    end
    if x ∈ N and w.x ≥ 0 then
        w = w - x ;
    end
end

```

//the algorithm converges when all the inputs are classified correctly


Perceptron Learning Algorithm

- ✓ Angle between 2 vectors

$$\mathbf{w}^T \mathbf{x} = \|\mathbf{w}\| \|\mathbf{x}\| \cos \alpha$$

$$\cos \alpha = \frac{\mathbf{w}^T \mathbf{x}}{\|\mathbf{w}\| \|\mathbf{x}\|}$$

BACHKHOACNCP.COM
TÀI LIỆU SƯU TẬP
BỞI HCMUT-CNCP




Perceptron Learning Algorithm

- ✓ When x belongs to P
 - ❖ We want $\mathbf{w} \cdot \mathbf{x} \geq 0$
 - ❖ $\alpha \leq 90^\circ$
- ✓ When x belongs to N
 - ❖ We want $\mathbf{w} \cdot \mathbf{x} < 0$
 - ❖ $\alpha > 90^\circ$

$$y = 1 \quad \text{if} \quad \sum_{i=0}^n w_i * x_i \geq 0$$
$$= 0 \quad \text{if} \quad \sum_{i=0}^n w_i * x_i < 0$$

where, $x_0 = 1$ and $w_0 = -\theta$



Perceptron Learning Algorithm

Algorithm: Perceptron Learning Algorithm

$P \leftarrow$ inputs with label 1;

$N \leftarrow$ inputs with label 0;

Initialize \mathbf{w} randomly;

while !convergence **do**

 Pick random $\mathbf{x} \in P \cup N$;

if $\mathbf{x} \in P$ and $\mathbf{w} \cdot \mathbf{x} < 0$ **then**

$\mathbf{w} = \mathbf{w} + \mathbf{x}$;

end


if $\mathbf{x} \in N$ and $\mathbf{w} \cdot \mathbf{x} \geq 0$ **then**

$\mathbf{w} = \mathbf{w} - \mathbf{x}$;

end

end

//the algorithm converges when all the
inputs are classified correctly



✓ Animation



Perceptron Learning Algorithm

✓ References

- ❖ <https://towardsdatascience.com/perceptron-learning-algorithm-d5db0deab975>

