



Hochiminh City University of Technology
Computer Science and Engineering
[CO1027] - Fundamentals of C++ Programming

Array, Pointer, Structure

Lecturer: Duc Dung Nguyen
Credits: 3



Outcomes

- ❖ Using array, and structure data types
- ❖ Using pointer
- ❖ Allocating and releasing dynamic memory



Today's outline

- ❖ Structured data types
 - ❖ Array
 - ❖ Structure
- ❖ Pointer
- ❖ Dynamic memory



Structured data types


A watermark logo is centered behind the title. It consists of a circular emblem with the text "BACH KHOA CNCP.COM" around the top edge. Inside the circle is a stylized graphic of two overlapping cubes or blocks, with the letters "CM" and "CP" visible on their faces. Below the emblem, the text "TÀI LIỆU SƯU TẬP" is written in a bold, sans-serif font, and "BỞI HCMUT-CNCP" is written in a smaller font below that.

Structured data types

- ❖ Can we implement a program with only basic data types?
- ❖ What do we need beside basic data types?
 - ❖ A sequence of memory slots that contains a specific data type
 - ❖ A mixture of different data types




Array



Declaring Arrays

❖ `<type> arrayName [arraySize];`

❖ E.g: `int c[5];`



Initializing Arrays

- ❖ One by one

- ❖ E.g: `c[4] = 10;`

- ❖ Using a loop

- ❖ E.g: `for (int i = 0; i < 5; i++) c[i] = 0;`

- ❖ Declaring with an initializer list

- ❖ E.g: `int c[5] = { 10, 20, 30, 40, 50 };`



Accessing the values of an array

- ❖ The values of any of the elements in an array can be accessed just like the value of a regular variable of the same type. The syntax is:

- ❖ `name[index]`

- ❖ Example:

```
int a = 2;  
c[0] = a;  
c[a] = 75;  
b = c[a + 2];  
c[c[a]] = c[2] + 5;
```




Example

```
#include<iostream>
#include<iomanip>
using namespace std;

int main() {
    int c[10];
    for (int i = 0; i < 10; i++) c[i] = 0;

    cout << "Element" << setw(13) << "Value" << endl;
    for (int i = 0; i < 10; i++)
        cout << setw(7) << i << setw(13) << c[i] << endl;

    return 0;
}
```



Example

```
#include<iostream>
#include<iomanip>
using namespace std;

int main() {
    int c[10] = { 10, 20, 30, 40, 50, 60, 70, 80, 90, 100 };

    cout << "Element" << setw(13) << "Value" << endl;
    for (int i = 0; i < 10; i++)
        cout << setw(7) << i << setw(13) << c[i] << endl;

    return 0;
}
```





Structure

- ❖ Structure is user defined data type which allows you to combine data items of different kinds.
- ❖ Structures are used to represent a record.

Books

- ☐ Title
- ☐ Author
- ☐ Subject
- ☐ Book ID

Defining a Structure

```
struct [structure tag] {  
    member definition;  
    member definition;  
    ...  
    member definition;  
}[structure variable(s)];
```



Example

```
struct Books {  
    char    title[50];  
    char    author[50];  
    char    subject[100];  
    int     book_id;  
};
```

```
struct Books book1;
```



The typedef Keyword

- ❖ “Aliasing” types defined by user using keyword typedef

```
typedef struct {  
    char title[50];  
    char author[50];  
    char subject[100];  
    int book_id;  
} Books;
```

```
Books book1;
```




Accessing Structure Members

- ❖ Using the member access operator (.)

```
struct Books Book1;           // Declare Book1 of type Book

// book 1 specification
strcpy_s(Book1.title, "Learn C++ Programming");
strcpy_s(Book1.author, "Chand Miyan");
strcpy_s(Book1.subject, "C++ Programming");
Book1.book_id = 6495407;
```



https://www.tutorialspoint.com/cplusplus/cpp_data_structures.htm



Pointer

- ❖ Pointer variables contain memory addresses as their values

count



count directly references a variable that contains the value 7

countPtr



count



Pointer countPtr indirectly references a variable that contains the value 7

Declaring Pointers

- ❖ Direct way:
 - ❖ `<type> * <identifier>;`
 - ❖ E.g.: `int * a;`
- ❖ Using `typedef` keyword:
 - ❖ `typedef <type>* <alias_type>;`
 - ❖ E.g.:

`typedef int * IntPtr;`

`IntPtr a;`



Using Pointers

- ❖ Defining a pointer variable

```
int var = 20;    // actual variable declaration.
```

```
int *ip;         // pointer variable
```

- ❖ Assigning the address of a variable to a pointer

```
ip = &var;       // using address operator &
```

- ❖ Accessing the value at the address available in the pointer variable

```
cout << *ip << endl; // using dereferencing operator *
```

```
*ip = 5;
```

NULL Pointers

- ❖ Assigning the pointer NULL to a pointer variable in case you do not have exact address to be assigned.

```
int *ptr = NULL;
```

- ❖ To check for a null pointer you can use an if statement as follows

```
if(ptr == NULL)
```

Or

```
if(!ptr)
```



Using const with Pointers

- ❖ ***Nonconstant Pointer to Nonconstant Data***
- ❖ ***Nonconstant Pointer to Constant Data***
- ❖ ***Constant Pointer to Nonconstant Data***
- ❖ ***Constant Pointer to Constant Data***



Using const with Pointers

❖ *Nonconstant Pointer to Nonconstant Data*

- ❖ the data can be modified through the dereferenced pointer
- ❖ the pointer can be modified to point to other data

```
int a = 5;  
int b = 9;  
int *ptr = &a;  
*ptr = 6; // OK  
ptr = &b; // OK
```



Using const with Pointers

❖ *Nonconstant Pointer to Constant Data*

- ❖ the data can NOT be modified through the dereferenced pointer
- ❖ the pointer can be modified to point to other data

```
const int a = 5;  
int b = 9;  
const int *ptr = &a;  
*ptr = 6; // Error  
ptr = &b; // OK
```

TÀI LIỆU SƯU TẬP
BỞI HCMUT-CNCP

Using const with Pointers

❖ *Constant Pointer to Nonconstant Data*

- ❖ the data can be modified through the dereferenced pointer
- ❖ the pointer can NOT be modified to point to other data

```
int a = 5;  
int b = 9;  
int* const ptr = &a;  
*ptr = 6; // OK  
ptr = &b; // Error
```

Using const with Pointers

❖ *Constant Pointer to Constant Data*

- ❖ the data can NOT be modified through the dereferenced pointer
- ❖ the pointer can NOT be modified to point to other data

```
const int a = 5;  
const int b = 9;  
int* const ptr = &a;  
*ptr = 6; // Error  
ptr = &b; // Error
```

TÀI LIỆU SƯU TẬP
BỞI HCMUT-CNCP

Pointer Arithmetic

- ❖ Four arithmetic operators that can be used on pointers: ++, --, +, and -

// point to the next location

```
ptr++;
```

```
ptr = ptr + 1;
```

// point to the previous location

```
ptr--;
```

```
ptr = ptr - 1;
```



Pointer

❖ Order of operators

❖ `*p++` `//` `*(p++)`

❖ `*++p` `//` `*(++p)`

❖ `++*p` `//` `++(*p)`

❖ `(*p)++` `//` increase value at location pointed by p
 `//` (only valid with integer pointers)



When in doubt, use safe statement.

Pointers vs Arrays

- ❖ Arrays and pointers are intimately related in C++ and may be used *almost* interchangeably.

```
int var[MAX] = { 10, 100, 200 };  
int *ptr;
```

```
// let us have array address in pointer.  
ptr = var;
```

- ❖ However, an array name can be thought of as a constant pointer.

```
var++; // This is incorrect syntax.
```



Example

```
#include <iostream>
using namespace std;
const int MAX = 3;

int main() {
    int var[MAX] = { 10, 100, 200 };
    int *ptr;

    // let us have array address in pointer.
    ptr = var;

    for (int i = 0; i < MAX; i++) {
        cout << "Address of var[" << i << "] = " << ptr << endl;
        cout << "Value of var[" << i << "] = " << *ptr << endl;

        // point to the next location
        ptr++;
    }
    return 0;
}
```

https://www.tutorialspoint.com/cplusplus/cpp_pointer_arithmetic.htm



Array of Pointers

```
#include <iostream>

using namespace std;
const int MAX = 4;

int main() {
    const char *names[MAX] = { "An Nguyen", "Binh Tran", "Cong Pham", "Dat Le" };

    for (int i = 0; i < MAX; i++) {
        cout << "Value of names[" << i << "] = " << *(names + i) << endl;
    }

    return 0;
}
```

https://www.tutorialspoint.com/cplusplus/cpp_array_of_pointers.htm



Pointer to Pointer



```
int var = 300;  
int *ptr = &var; // take the address of var  
int **pptr = &ptr; // take the address of ptr
```

Example

```
#include <iostream>

using namespace std;

int main() {
    int var = 300;
    int *ptr = &var; // take the address of var
    int **pptr = &ptr; // take the address of ptr

    // take the value using pptr
    cout << "Value of var :" << var << endl;
    cout << "Value available at *ptr :" << *ptr << endl;
    cout << "Value available at **pptr :" << **pptr << endl;

    return 0;
}
```

https://www.tutorialspoint.com/cplusplus/cpp_pointer_to_pointer.htm



References

- ❖ A reference variable is an alias, that is, another name for an already existing variable.

```
int a = 10;  
int& b = a;
```



- ❖ References are usually used for function argument lists and function return values.

https://www.tutorialspoint.com/cplusplus/cpp_references.htm

Example

```
#include<iostream>
using namespace std;

int main() {
    int a = 10;
    int& b = a;
    cout << "Value of a :" << a << endl;
    cout << "Value of a reference :" << b << endl;
    a = 6;
    cout << "Value of a :" << a << endl;
    cout << "Value of a reference :" << b << endl;
}
```



Pointers vs References

- ❖ Three major differences between references and pointers:
 - ❑ You cannot have NULL references. You must always be able to assume that a reference is connected to a legitimate piece of storage.
 - ❑ Once a reference is initialized to an object, it cannot be changed to refer to another object.
 - ❑ A reference must be initialized when it is created. Pointers can be initialized at any time. Pointers can be pointed to another object at any time.

Dynamic Merory

BACH KHOA CNCP.COM

TÀI LIỆU SƯU TẬP

BỞI HCMUT-CNCP


Allocating Dynamic Memory

❖ Dynamic memory is allocated using operator **new**. Here is the syntax:

- ❑ `<pointer> = new <type>`
- ❑ `<pointer> = new <type> [<number_of_elements>]`

❖ Examples:

- ❑ `int * a = new int[5];`



Releasing Dynamic Memory

❖ Dynamic memory is released using operator **delete**. Here is the syntax:

- ❑ **delete** <pointer>

- ❑ **delete []** <pointer>

❖ Examples:

- ❑ **delete []**a;



Summarise

- ❖ Structured data types
 - ❖ Array
 - ❖ Structure
- ❖ Pointer
- ❖ Dynamic memory

