



Hochiminh City University of Technology
Computer Science and Engineering
[CO1027] - Fundamentals of C++ Programming

Class



Lecturer: Duc Dung Nguyen
Credits: 3

Outcomes

- ❖ Understand the concept of Class.
- ❖ Understand advantages of Object Oriented Programming (OOP).
- ❖ Be able to program using OOP technique.



Outline

- ❖ Class:
 - ❖ Concept and definition
 - ❖ Encapsulation
- ❖ Constructor/Destructor



Structure versus Object-Oriented Programming

- ❖ **Structure programming** focuses on the process / actions that occur in a program. The program starts at the beginning, does something, and ends.
- ❖ **Object-Oriented programming** is based on the data and the functions that operate on it. Objects are instances of abstract data types that represent the data and its functions

Limitations of Structure Programming

- ❖ If the data structures change, many functions must also be changed
- ❖ Programs that are based on complex function hierarchies are:
 - ❖ difficult to understand and maintain
 - ❖ difficult to modify and extend
 - ❖ easy to break



Class

- ❖ Class: a user defined datatype which groups together related pieces of information
 - ❖ Data
 - ❖ Functions (Methods)
- ❖ **Classes** are similar to **Structure** but contain functions, as well.



Terminologies


- ❖ **Object** is an instant of a particular **class**
- ❖ **Data** are known as **fields, members, attributes, or properties**
- ❖ **Functions** are known as **methods**



Classes and Objects

- ❖ A Class is like a blueprint and objects are like houses built from the blueprint

Blueprint that describes a house.



Instances of the house described by the blueprint.



Features

- ❖ **Encapsulation (hiding data)**: allows the programmer to group data and the subroutines that operate on them together in one place, and to hide irrelevant details from the user.
- ❖ **Inheritance**: allows code to be reused between related types.
- ❖ **Polymorphism**: allows a value to be one of several types, and determining at runtime which functions to call on based on its type.



Encapsulation

- ❖ Packaging related stuff together
- ❖ User need to know only **public methods** / **data** of the object: **interface**
- ❖ Interfaces abstract away the details of how all the operations are performed
 - ❖ “Data hiding”, “black box”.



Class Declaration

```
class <Class_Name>
{
    <access_specifier>:
        member declaration;
        ...
    <access_specifier>:
        member declaration;
        ...
};
```



Class Example

```
class Rectangle
{
private:
    double width;
    double height;
public:
    void setWidth(double);
    void setHeight(double);
    double getWidth();
    double getHeight();
    double getArea();
};
```



Class Access specifier

- ❖ Used to control access to members of the class:
 - ❖ **private** (**default**) : the members declared as private are only accessible from within the class. No outside Access is allowed.
 - ❖ **public**: the members declared as public are accessible from outside the Class through an object of the class.
- ❖ Can be listed in any order in a class
- ❖ Can appear multiple times in a class

Member Function Definition

- ❖ When defining a member function:
 - ❖ Put prototype in class declaration
 - ❖ Define function using class name and scope resolution operator (::)



```
void Rectangle::setWidth(double w)
{
    width = w;
}
```

Declaration vs Definition

- ❖ Separate the declaration (specification) part from the definition (implementation) part.
- ❖ Place class declaration in a header file. E.g. Rectangle.h
- ❖ Place member function definitions in *.cpp file. E.g. Rectangle.cpp. This file must #include the class specification file.
- ❖ Programs that use the class must #include the class specification file.

Set and Get

- ❖ Set (mutator): a member function that stores a value in a private member variable, or changes its value in some way.

```
void setWidth(double);  
void setHeight(double);
```



- ❖ Get (accessor): a member function that retrieves a value from a private member variable.

```
double getWidth();  
double getHeight();
```

Using `const` With Member Functions

- ❖ `const` appearing after the parentheses in a member function declaration specifies that the function will not change any data in the calling object.
- ❖ Example

```
double getWidth() const;
```

```
double getHeight() const;
```

```
double getArea() const;
```



Scope operator

- ❖ Scope operator ::
 - ❖ Is used in the definition of member function outside the class
 - ❖ Inline function vs. normal function
 - ❖ Member functions defined in the class definition is considered as inline function.

Static Class Members

- ❖ **Static data members:** are considered as “class” variables since they are common variables for all objects of the same class.
 - ❖ Need to be initialized somewhere outside the class
 - ❖ Can be accessed through object or class
 - ❖ Example: object counter
- ❖ **Static function members:** can only access static members of the class.

Constructor vs Destructor

BACHKHOACNCP.COM
TÀI LIỆU SƯU TẬP
BỞI HCMUT-CNCP

Constructor

- ❖ **Constructors**: a special function that is automatically called whenever a new object is created .
- ❖ allow the class to initialize member variables or allocate storage.
- ❖ do not return a value, including void.
- ❖ can not be called explicitly as member functions.

Default Constructor

- ❖ A default constructor is a constructor that takes no arguments.
- ❖ If you write a class with no constructor at all, C++ will write a default constructor for you, one that does nothing.
- ❖ A simple instantiation of a class (with no arguments) calls the default constructor:

```
Rectangle r;
```

Constructor Syntax

```
class <Class_Name>
{
    ...
public:
    <Class_Name>();
    ...
};
```



Constructors with Parameters

- ❖ To create a constructor that takes arguments:

- ❖ Indicate parameters in prototype:

```
Rectangle(double , double );
```

- ❖ Use parameters in the definition:

```
Rectangle::Rectangle(double w, double h)
{
    width = w;
    height = h;
}
```

- ❖ You can pass arguments to the constructor when you create an object:

```
Rectangle r2(6, 4);
```



More About Default Constructors

- ❖ If all of a constructor's parameters have default arguments, then it is a default constructor. For example:

```
Rectangle(double = 0, double = 0);
```



- ❖ Creating an object and passing no arguments will cause this constructor to execute:

```
Rectangle r;
```

Overloading Constructors

- ❖ A class can have more than one constructor. They can be **overloaded**.
- ❖ The compiler automatically call the one whose parameters match the arguments.

```
Rectangle();
```

```
Rectangle(double);
```

```
Rectangle(double, double);
```



Destructor

- ❖ **Destructor**: responsible for the necessary cleanup of a class when lifetime of an object ends.
- ❖ Destructors cannot:
 - ❖ return a value
 - ❖ accept parameters
- ❖ Destructors must have the same name as the class.
- ❖ Only one destructor per class, i.e., it cannot be overloaded
- ❖ If constructor allocates dynamic memory, destructor should release it



Destructor Syntax

```
class <Class_Name>
{
    ...
public:
    ~<Class_Name>();
    ...
};
```



Using Private Member Functions

- ❖ A `private` member function can only be called by another member function
- ❖ It is used for internal processing by the class, not for use outside of the class
- ❖ If you wrote a class that had a public sort function and needed a function to swap two elements, you'd make that private

Arrays of Objects

- ❖ Objects can be the elements of an array:

`Rectangle rooms[8];`

- ❖ Default constructor for object is used when array is defined



Arrays of Objects

- ❖ Must use initializer list to invoke constructor that takes arguments:

```
Rectangle rectArray[3]={Rectangle(2.1,3.2),  
                        Rectangle(4.1, 9.9),  
                        Rectangle(11.2, 31.4)};
```

Accessing Objects in an Array

- ❖ Objects in an array are referenced using subscripts
- ❖ Member functions are referenced using dot notation:

```
rectArray[1].setWidth(11.3);  
cout << rectrArray[1].getArea();
```

Pointer to Class

- ❖ Objects can also be pointed by pointers. Class is a valid type.
- ❖ Class pointers is similar to struct pointers.
- ❖ E.g.:

```
Rectangle r2(6, 4);  
Rectangle* r3 = &r2;  
cout << r3->getArea() << endl;  
cout << (*r3).getArea() << endl;
```



Using the this Pointer

- ❖ Every object has access to its own address through a pointer called **this** (a C++ keyword)

```
void Rectangle::setWidth(double width)
{
    this->width = width;
}
```



Summarise

- ❖ Understand Class: concept and definition, encapsulation
- ❖ Member functions, static and const members
- ❖ Constructor/Destructor and overloaded operators

