



Functional Dependencies & Normalization for Relational DBs

Chapter 7

Contents

- 1 Introduction
 - 2 Functional dependencies
 - 3 Normalization
-

TÀI LIỆU SƯU TẬP
BỞI HCMUT-CNCP

Contents


1 Introduction

2 Functional dependencies

3 Normalization

TÀI LIỆU SƯU TẬP
BỞI HCMUT-CNCP

Overview of Database Design Process



Introduction

- ▶ Each relation schema consists of a number of attributes and the relational database schema consists of a number of relation schemas
- ▶ Attributes are grouped to form a relation schema
- ▶ Need some formal measure of why one grouping of attributes into a relation schema may be better than another

TÀI LIỆU SƯU TẬP
BỞI HCMUT-CNCP


Introduction

- ▶ “Goodness” measures:
 - ▶ Redundant information in tuples
 - ▶ Update anomalies: modification, deletion, insertion
 - ▶ Reducing the NULL values in tuples
 - ▶ Disallowing the possibility of generating spurious tuples

TÀI LIỆU SƯU TẬP
BỞI HCMUT-CNCP

Introduction

- ▶ **Redundant information** in tuples: the attribute values pertaining to a particular department (DNUMBER, DNAME, DMGRSSN) are repeated for every employee who works for that department.



EMP_DEPT

Ename	<u>Ssn</u>	Bdate	Address	Dnumber	Dname	Dmgr_ssn
Smith, John B.	123456789	1965-01-09	731 Fondren, Houston, TX	5	Research	333445555
Wong, Franklin T.	333445555	1955-12-08	638 Voss, Houston, TX	5	Research	333445555
Zelaya, Alicia J.	999887777	1968-07-19	3321 Castle, Spring, TX	4	Administration	987654321
Wallace, Jennifer S.	987654321	1941-06-20	291 Berry, Bellaire, TX	4	Administration	987654321
Narayan, Ramesh K.	666884444	1962-09-15	975 FireOak, Humble, TX	5	Research	333445555
English, Joyce A.	453453453	1972-07-31	5631 Rice, Houston, TX	5	Research	333445555
Jabbar, Ahmad V.	987987987	1969-03-29	980 Dallas, Houston, TX	4	Administration	987654321
Borg, James E.	888665555	1937-11-10	450 Stone, Houston, TX	1	Headquarters	888665555

Introduction

- ▶ **Update anomalies**: modification, deletion, insertion
 - ▶ Modification
 - ▶ As the manager of a dept. changes we have to update many values according to employees working for that dept.
 - ▶ Easy to make the DB **inconsistent**

EMP_DEPT

Ename	<u>Ssn</u>	Bdate	Address	Dnumber	Dname	Dmgr_ssn
Smith, John B.	123456789	1965-01-09	731 Fondren, Houston, TX	5	Research	333445555
Wong, Franklin T.	333445555	1955-12-08	638 Voss, Houston, TX	5	Research	333445555
Zelaya, Alicia J.	999887777	1968-07-19	3321 Castle, Spring, TX	4	Administration	987654321
Wallace, Jennifer S.	987654321	1941-06-20	291 Berry, Bellaire, TX	4	Administration	987654321
Narayan, Ramesh K.	666884444	1962-09-15	975 FireOak, Humble, TX	5	Research	333445555
English, Joyce A.	453453453	1972-07-31	5631 Rice, Houston, TX	5	Research	333445555
Jabbar, Ahmad V.	987987987	1969-03-29	980 Dallas, Houston, TX	4	Administration	987654321
Borg, James E.	888665555	1937-11-10	450 Stone, Houston, TX	1	Headquarters	888665555

Introduction

- ▶ Deletion: if Borg James E. leaves, we delete his tuple and lose the existing of dept. 1, the name of dept. 1, and who is the manager of dept. 1



EMP_DEPT

Ename	<u>Ssn</u>	Bdate	Address	Dnumber	Dname	Dmgr_ssn
Smith, John B.	123456789	1965-01-09	731 Fondren, Houston, TX	5	Research	333445555
Wong, Franklin T.	333445555	1955-12-08	638 Voss, Houston, TX	5	Research	333445555
Zelaya, Alicia J.	999887777	1968-07-19	3321 Castle, Spring, TX	4	Administration	987654321
Wallace, Jennifer S.	987654321	1941-06-20	291 Berry, Bellaire, TX	4	Administration	987654321
Narayan, Ramesh K.	666884444	1962-09-15	975 FireOak, Humble, TX	5	Research	333445555
English, Joyce A.	453453453	1972-07-31	5631 Rice, Houston, TX	5	Research	333445555
Jabbar, Ahmad V.	987987987	1969-03-29	980 Dallas, Houston, TX	4	Administration	987654321
Borg, James E.	888665555	1937-11-10	450 Stone, Houston, TX	1	Headquarters	888665555

Introduction

- ▶ Insertion:
 - ▶ How can we create a department before any employees are assigned to it ??



EMP_DEPT

Ename	<u>Ssn</u>	Bdate	Address	Dnumber	Dname	Dmgr_ssn
Smith, John B.	123456789	1965-01-09	731 Fondren, Houston, TX	5	Research	333445555
Wong, Franklin T.	333445555	1955-12-08	638 Voss, Houston, TX	5	Research	333445555
Zelaya, Alicia J.	999887777	1968-07-19	3321 Castle, Spring, TX	4	Administration	987654321
Wallace, Jennifer S.	987654321	1941-06-20	291 Berry, Bellaire, TX	4	Administration	987654321
Narayan, Ramesh K.	666884444	1962-09-15	975 FireOak, Humble, TX	5	Research	333445555
English, Joyce A.	453453453	1972-07-31	5631 Rice, Houston, TX	5	Research	333445555
Jabbar, Ahmad V.	987987987	1969-03-29	980 Dallas, Houston, TX	4	Administration	987654321
Borg, James E.	888665555	1937-11-10	450 Stone, Houston, TX	1	Headquarters	888665555

Introduction

- ▶ Reducing the NULL values in tuples
 - ▶ Employees not assigned to any dept.: waste the storage space
 - ▶ Other difficulties: aggregation operations (e.g., COUNT, SUM) and joins



Introduction

- ▶ Disallowing the possibility of generating spurious tuples

EMP_PROJ (SSN, PNumber, Hours, EName, PName, PLocation)

EMP_LOCS (EName, PLocation)

EMP_PROJ1 (SSN, PNumber, Hours, PName, PLocation)

- ▶ Generation of invalid and spurious data during JOINS:
PLocation is the attribute that relates EMP_LOCS and EMP_PROJ1, and PLocation is neither a primary key nor a foreign key in either EMP_LOCS or EMP_PROJ1

Introduction

- ▶ Disallowing the possibility of generating spurious tuples

EMP_LOCS

Ename	Plocation
Smith, John B.	Bellaire
Smith, John B.	Sugarland
Narayan, Ramesh K.	Houston
English, Joyce A.	Bellaire
English, Joyce A.	Sugarland
Wong, Franklin T.	Sugarland
Wong, Franklin T.	Houston
Wong, Franklin T.	Stafford
Zelaya, Alicia J.	Stafford
Jabbar, Ahmad V.	Stafford
Wallace, Jennifer S.	Stafford
Wallace, Jennifer S.	Houston
Borg, James E.	Houston

EMP_PROJ1

Ssn	Pnumber	Hours	Pname	Plocation
123456789	1	32.5	ProductX	Bellaire
123456789	2	7.5	ProductY	Sugarland
666884444	3	40.0	ProductZ	Houston
453453453	1	20.0	ProductX	Bellaire
453453453	2	20.0	ProductY	Sugarland
333445555	2	10.0	ProductY	Sugarland
333445555	3	10.0	ProductZ	Houston
333445555	10	10.0	Computerization	Stafford
333445555	20	10.0	Reorganization	Houston
999887777	30	30.0	Newbenefits	Stafford
999887777	10	10.0	Computerization	Stafford
987987987	10	35.0	Computerization	Stafford
987987987	30	5.0	Newbenefits	Stafford
987654321	30	20.0	Newbenefits	Stafford
987654321	20	15.0	Reorganization	Houston
888665555	20	NULL	Reorganization	Houston

Introduction

- ▶ Disallowing the possibility of generating spurious tuples

Ssn	Pnumber	Hours	Pname	Plocation	Ename
123456789	1	32.5	ProductX	Bellaire	Smith, John B.
* 123456789	1	32.5	ProductX	Bellaire	English, Joyce A.
123456789	2	7.5	ProductY	Sugarland	Smith, John B.
* 123456789	2	7.5	ProductY	Sugarland	English, Joyce A.
* 123456789	2	7.5	ProductY	Sugarland	Wong, Franklin T.
666884444	3	40.0	ProductZ	Houston	Narayan, Ramesh K.
* 666884444	3	40.0	ProductZ	Houston	Wong, Franklin T.
* 453453453	1	20.0	ProductX	Bellaire	Smith, John B.
453453453	1	20.0	ProductX	Bellaire	English, Joyce A.
* 453453453	2	20.0	ProductY	Sugarland	Smith, John B.
453453453	2	20.0	ProductY	Sugarland	English, Joyce A.
* 453453453	2	20.0	ProductY	Sugarland	Wong, Franklin T.
* 333445555	2	10.0	ProductY	Sugarland	Smith, John B.
* 333445555	2	10.0	ProductY	Sugarland	English, Joyce A.
333445555	2	10.0	ProductY	Sugarland	Wong, Franklin T.
* 333445555	3	10.0	ProductZ	Houston	Narayan, Ramesh K.
333445555	3	10.0	ProductZ	Houston	Wong, Franklin T.
333445555	10	10.0	Computerization	Stafford	Wong, Franklin T.
* 333445555	20	10.0	Reorganization	Houston	Narayan, Ramesh K.
333445555	20	10.0	Reorganization	Houston	Wong, Franklin T.

Introduction

- ▶ “Goodness” measures:
 - ▶ Redundant information in tuples
 - ▶ Update anomalies: modification, deletion, insertion
 - ▶ Reducing the NULL values in tuples
 - ▶ Disallowing the possibility of generating spurious tuples

👉 Normalization

TÀI LIỆU SƯU TẬP
BỞI HCMUT-CNCP

Introduction

- ▶ Normalization helps DB designers determine the best relation schemas
 - ▶ A formal framework for analyzing relation schemas based on their keys and on the functional dependencies among their attributes
 - ▶ A series of normal form tests that can be carried out on individual relation schemas so that the relational database can be normalized to any desired degree
- ▶ It is based on the concept of normal form **1NF, 2NF, 3NF, BCNF, 4NF, 5NF**
- ▶ It is a process which ensures that the data is structured in such a way that attributes are grouped with the PK. Attributes that do not directly depend on PK may be extracted to form a new relation

Introduction

- ▶ There are two important properties of decompositions:
 - 1) non-additive or losslessness of the corresponding join
 - 2) preservation of the functional dependencies
- ▶ Note that property (1) is extremely important and cannot be sacrificed. Property (2) is less stringent and may be sacrificed

Contents

1 Introduction

2 Functional dependencies

3 Normalization

TÀI LIỆU SƯU TẬP
BỞI HCMUT-CNCP

Functional Dependencies (FDs)

- ▶ **Definition of FDs**
- ▶ Direct, indirect, partial dependencies
- ▶ Inference Rules for FDs
- ▶ Equivalence of Sets of FDs
- ▶ Minimal Sets of FDs

TÀI LIỆU SƯU TẬP
BỞI HCMUT-CNCP

Functional Dependencies (FDs)

- ▶ Functional dependencies (FDs) are used to specify formal measures of the "goodness" of relational designs
- ▶ FDs and keys are used to define normal forms for relations
- ▶ FDs are constraints that are derived from the meaning and interrelationships of the data attributes
- ▶ A set of attributes X **functionally determines** a set of attributes Y if the value of X determines a unique value for Y

$X \rightarrow Y$

Functional Dependencies (FDs)

- ▶ $X \rightarrow Y$ holds if whenever two tuples have the same value for X , they must have the same value for Y
- ▶ For any two tuples t_1 and t_2 in any relation instance $r(R)$:
If $t_1[X] = t_2[X]$, then $t_1[Y] = t_2[Y]$
- ▶ $X \rightarrow Y$ in R specifies a constraint on all relation instances $r(R)$
- ▶ Examples:
 - ▶ social security number determines employee name:
 $SSN \rightarrow EName$
 - ▶ project number determines project name and location:
 $PNumber \rightarrow \{PName, PLocation\}$
 - ▶ employee ssn and project number determines the hours per week that the employee works on the project:
 $\{SSN, PNumber\} \rightarrow Hours$

Functional Dependencies (FDs)

- ▶ If K is a key of R , then K functionally determines all attributes in R (since we never have two distinct tuples with $t_1[K]=t_2[K]$)



Functional Dependencies (FDs)

- ▶ Definition of FDs
- ▶ **Direct, indirect, partial dependencies**
- ▶ Inference Rules for FDs
- ▶ Equivalence of Sets of FDs
- ▶ Minimal Sets of FDs


TÀI LIỆU SƯU TẬP
BỞI HCMUT-CNCP

Functional Dependencies (FDs)

- ▶ **Direct dependency** (fully functional dependency): All attributes in a R must be fully functionally dependent on the primary key (or the PK is a determinant of all attributes in R)

$SSN \rightarrow \{Name, BDate, Address, DNO\}$

EMPLOYEE




Functional Dependencies (FDs)

- **Indirect dependency** (transitive dependency): Value of an attribute is not determined directly by the primary key

$DNO \rightarrow DName$

EMP_DEPT




Functional Dependencies (FDs)

▶ Partial dependency

- ▶ Composite determinant - more than one value is required to determine the value of another attribute, the combination of values is called a composite determinant
 $\{SSN, PNumber\}$ in EMP_PROJ
- ▶ Partial dependency - if the value of an attribute does not depend on an entire composite determinant, but only part of it, the relationship is known as the partial dependency

$SSN \rightarrow EName$, $Pnumber \rightarrow \{PName, PLocation\}$



Functional Dependencies (FDs)

- ▶ Definition of FD
- ▶ Direct, indirect, partial dependencies
- ▶ **Inference Rules for FDs**
- ▶ Equivalence of Sets of FDs
- ▶ Minimal Sets of FDs

TÀI LIỆU SƯU TẬP
BỞI HCMUT-CNCP

Functional Dependencies (FDs)

- ▶ Given a set of FDs F , we can infer additional FDs that hold whenever the FDs in F hold
- ▶ **Armstrong's inference rules:**
 - ▶ **IR1. (Reflexive)** If $Y \subseteq X$, then $X \rightarrow Y$
 - ▶ **IR2. (Augmentation)** If $X \rightarrow Y$, then $XZ \rightarrow YZ$
(Notation: XZ stands for $X \cup Z$)
 - ▶ **IR3. (Transitive)** If $X \rightarrow Y$ and $Y \rightarrow Z$, then $X \rightarrow Z$

BỞI HCMUT-CNCP

Functional Dependencies (FDs)

- ▶ Some additional inference rules that are useful:
 - ▶ **Decomposition:** If $X \rightarrow YZ$, then $X \rightarrow Y$ and $X \rightarrow Z$
 - ▶ **Union:** If $X \rightarrow Y$ and $X \rightarrow Z$, then $X \rightarrow YZ$
 - ▶ **Pseudotransitivity:** If $X \rightarrow Y$ and $WY \rightarrow Z$, then $WX \rightarrow Z$
- ▶ The last three inference rules, as well as any other inference rules, can be deduced from IR1, IR2, and IR3 (completeness property)

Functional Dependencies (FDs)

- ▶ Closure of a set F of FDs is the set F^+ of all FDs that can be inferred from F
- ▶ Closure of a set of attributes X with respect to F is the set X^+ of all attributes that are functionally determined by X
- ▶ X^+ can be calculated by repeatedly applying IR1, IR2, IR3 using the FDs in F

Inference Rules for FDs

Algorithm 16.1. Determining X^+ , the Closure of X under F

Input: A set F of FDs on a relation schema R , and a set of attributes X , which is a subset of R .

$X^+ := X$;

repeat

$\text{old}X^+ := X^+$;

 for each functional dependency $Y \rightarrow Z$ in F do

 if $X^+ \supseteq Y$ then $X^+ := X^+ \cup Z$;

until $(X^+ = \text{old}X^+)$;

Exercise

- ▶ Consider a relation $R(A, B, C, D, E)$ with the following dependencies F :
 - (1) $AB \rightarrow C$,
 - (2) $CD \rightarrow E$,
 - (3) $DE \rightarrow B$
- ▶ Find $\{A, B\}^+$, $\{A, B, D\}^+$
- ▶ Find F^+



Functional Dependencies (FDs)

- ▶ Definition of FD
- ▶ Direct, indirect, partial dependencies
- ▶ Inference Rules for FDs
- ▶ **Equivalence of Sets of FDs**
- ▶ Minimal Sets of FDs

TÀI LIỆU SƯU TẬP
BỞI HCMUT-CNCP

Functional Dependencies (FDs)

- ▶ Two sets of FDs F and G are **equivalent** if $F^+ = G^+$
- ▶ Definition:
 - ▶ F **covers** G if $G^+ \subseteq F^+$
 - ▶ F and G are **equivalent** if F covers G and G covers F
- ▶ There is an algorithm for checking equivalence of sets of FDs

TÀI LIỆU SƯU TẬP
BỞI HCMUT-CNCP

Equivalence of Sets of FDs

- ▶ Two sets of FDs F and G are **equivalent** if $F^+ = G^+$.
- ▶ Definition: F **covers** G if $G^+ \subseteq F^+$ and G are equivalent if F covers G and G covers F .
- ▶ There is an algorithm for checking equivalence of sets of FDs.

TÀI LIỆU SƯU TẬP
BỞI HCMUT-CNCP

Equivalence of Sets of FDs

- ▶ Nếu tất cả FD trong G đều được suy ra từ F và tất cả FD trong F đều được suy ra từ G.
- ▶ Xác định F cover G? tính X^+ đối với F cho mỗi FD $X \rightarrow Y$ trong G và kiểm tra xem X^+ có chứa thuộc tính Y.
- ▶ 2 tập phụ thuộc hàm sau tương đương:
 - ▶ $F = \{A \rightarrow C, AC \rightarrow D, E \rightarrow AD, E \rightarrow H\}$
 - ▶ $G = \{A \rightarrow CD, E \rightarrow AH\}$
- ▶ $A^+_F = \{A, C, D\}, E^+_F = \{E, A, D, H\} \rightarrow F \text{ cover } G$
- ▶ $A^+_G = \{A, C, D\} \quad AC^+_G = \{A, C, D\} \quad E^+_G = \{E, A, H, C, D\} \rightarrow G \text{ cover } F$

Functional Dependencies (FDs)

- ▶ A set of FDs is minimal if it satisfies the following conditions:
 - ▶ Every dependency in F has a single attribute for its RHS.
 - ▶ We cannot remove any dependency from F and have a set of dependencies that is equivalent to F .
 - ▶ We cannot replace any dependency $X \rightarrow A$ in F with a dependency $Y \rightarrow A$, where Y proper-subset-of X (Y subset-of X) and still have a set of dependencies that is equivalent to F

Functional Dependencies (FDs)

- ▶ Every set of FDs has an equivalent minimal set
- ▶ There can be several equivalent minimal sets
- ▶ There is no simple algorithm for computing a minimal set of FDs that is equivalent to a set F of FDs
- ▶ To synthesize a set of relations, we assume that we start with a set of dependencies that is a **minimal set**

TÀI LIỆU SƯU TẬP
BỞI HCMUT-CNCP

Contents

1 Introduction

2 Functional dependencies

3 Normalization

TÀI LIỆU SƯU TẬP
BỞI HCMUT-CNCP

Normalization

- ▶ **Normalization:** The process of **decomposing** unsatisfactory "bad" relations by breaking up their attributes into smaller relations
- ▶ Normal form: Using keys and FDs of a relation to certify whether a relation schema is in a particular normal form
- ▶ Normalization is carried out in practice so that the resulting designs are of high quality and meet the desirable properties
- ▶ The database designers **need not** normalize to the highest possible normal form (3NF, BCNF or 4NF)


Normalization

- ▶ Two new concepts:
 - ▶ A **Prime attribute** must be a member of some candidate key
 - ▶ A **Nonprime attribute** is not a prime attribute: it is not a member of any candidate key

TÀI LIỆU SƯU TẬP
BỞI HCMUT-CNCP

Normalization

- ▶ 1NF and dependency problems
- ▶ 2NF – solves partial dependency
- ▶ 3NF – solves indirect dependency
- ▶ BCNF – well-normalized relations



Normalization

- ▶ **First normal form (1NF):** there is only one value at the intersection of each row and column of a relation - no set valued attributes in 1NF
 - Disallows composite attributes, multivalued attributes, and **nested relations**
- ▶ To be part of the formal definition of a relation in the basic (flat) relational model

BỞI HCMUT-CNCP

1NF

(a)

DEPARTMENT

DNAME	<u>DNUMBER</u>	DMGRSSN	DLOCATIONS
-------	----------------	---------	------------

Diagram showing functional dependencies with arrows: DNAME → DNUMBER, DNUMBER → DMGRSSN, and DNUMBER → DLOCATIONS. A dashed line connects the arrows from DNUMBER to DMGRSSN and DLOCATIONS.

(b)

DEPARTMENT

DNAME	<u>DNUMBER</u>	DMGRSSN	DLOCATIONS
-------	----------------	---------	------------

Research	5	333445555	{Bellaire, Sugarland, Houston}
Administration	4	987654321	{Stafford}
Headquarters	1	888665555	{Houston}

(c)

DEPARTMENT

DNAME	<u>DNUMBER</u>	DMGRSSN	<u>DLOCATION</u>
-------	----------------	---------	------------------

Research	5	333445555	Bellaire
Research	5	333445555	Sugarland
Research	5	333445555	Houston
Administration	4	987654321	Stafford
Headquarters	1	888665555	Houston

1NF

EMP_PROJ

SSN	ENAME	PROJS	
		PNUMBER	HOURS

EMP_PROJ

Ssn	Ename	Pnumber	Hours
123456789	Smith, John B.	1	32.5
		2	7.5
666884444	Narayan, Ramesh K.	3	40.0
453453453	English, Joyce A.	1	20.0
		2	20.0

1NF

EMP_PROJ

<u>SSN</u>	<u>PNUMBER</u>	HOURS	ENAME	PNAME	PLOCATION
123456789	1	32.5	Smith, John B.	ProductX	Bellaire
123456789	2	7.5	Smith, John B.	ProductY	Sugarland
666884444	3	40.0	Narayan, Ramesh K.	ProductZ	Houston
453453453	1	20.0	English, Joyce A.	ProductX	Bellaire
453453453	2	20.0	English, Joyce A.	ProductY	Sugarland
333445555	2	10.0	Wong, Franklin T.	ProductY	Sugarland
333445555	3	10.0	Wong, Franklin T.	ProductZ	Houston
333445555	10	10.0	Wong, Franklin T.	Computerization	Stafford
333445555	20	10.0	Wong, Franklin T.	Reorganization	Houston
999887777	30	30.0	Zelaya, Alicia J.	Newbenefits	Stafford
999887777	10	10.0	Zelaya, Alicia J.	Computerization	Stafford
987987987	10	35.0	Jabbar, Ahmad V.	Computerization	Stafford
987987987	30	5.0	Jabbar, Ahmad V.	Newbenefits	Stafford

1NF

EMP_PROJ (SSN, PNumber, Hours, EName, PName, PLocation)

1. SSN, PNumber \rightarrow Hours
2. SSN \rightarrow EName
3. PNumber \rightarrow PName, PLocation

TÀI LIỆU SƯU TẬP
BỞI HCMUT-CNCP

1NF

EMP_PROJ (SSN, PNumber, Hours)


EMP (SSN, EName)

PROJ (PNumber, PName, PLocation)

1. SSN, PNUMBER \rightarrow HOURS
2. SSN \rightarrow ENAME
3. PNUMBER \rightarrow PNAME, PLOCATION

Normalization

- ▶ 1NF and dependency problems
- ▶ **2NF – solves partial dependency**
- ▶ 3NF – solves indirect dependency
- ▶ BCNF – well-normalized relations




Normalization

- ▶ Second normal form (2NF) - all attributes must be fully functionally dependent on the primary key
- ▶ 2NF solves partial dependency problem in 1NF
- ▶ Method: identify primary keys and group attributes that relate to the key together to form separate new relations

TÀI LIỆU SƯU TẬP
BỞI HCMUT-CNCP

2NF

EMP_DEPT



EMP_DEPT


➤ Problem with 2NF

Ename	<u>Ssn</u>	Bdate	Address	Dnumber	Dname	Dmgr_ssn
Smith, John B.	123456789	1965-01-09	731 Fondren, Houston, TX	5	Research	333445555
Wong, Franklin T.	333445555	1955-12-08	638 Voss, Houston, TX	5	Research	333445555
Zelaya, Alicia J.	999887777	1968-07-19	3321 Castle, Spring, TX	4	Administration	987654321
Wallace, Jennifer S.	987654321	1941-06-20	291 Berry, Bellaire, TX	4	Administration	987654321
Narayan, Ramesh K.	666884444	1962-09-15	975 FireOak, Humble, TX	5	Research	333445555
English, Joyce A.	453453453	1972-07-31	5631 Rice, Houston, TX	5	Research	333445555
Jabbar, Ahmad V.	987987987	1969-03-29	980 Dallas, Houston, TX	4	Administration	987654321
Borg, James E.	888665555	1937-11-10	450 Stone, Houston, TX	1	Headquarters	888665555


2NF

EMP_PROJ

<u>Ssn</u>	<u>Pnumber</u>	Hours	Ename	Pname	Plocation
------------	----------------	-------	-------	-------	-----------




2NF Normalization



Normalization

- ▶ 1NF and dependency problems
- ▶ 2NF – solves partial dependency
- ▶ **3NF – solves indirect dependency**
- ▶ BCNF – well-normalized relations



Normalization

- ▶ A relation schema R is in **third normal form (3NF)** if it is in 2NF *and* no non-prime attribute A in R is transitively dependent on the primary key

NOTE:

In $X \rightarrow Y$ and $Y \rightarrow Z$, with X as the primary key, we consider this a problem only if Y is not a candidate key. When Y is a candidate key, there is no problem with the transitive dependency .

E.g., Consider EMP (SSN, Emp#, Salary).

Here, $SSN \rightarrow Emp\# \rightarrow Salary$ and Emp# is a candidate key

Normalization

- ▶ 3NF solves indirect (transitive) dependencies problem in 1NF and 2NF
- ▶ Method: identify all transitive dependencies and each transitive dependency will form a new relation, with non-prime attributes participating in the transitive dependency and the attribute which determines others as the attributes for the new relation

TÀI LIỆU SƯU TẬP
BỞI HCMUT-CNCP

3NF

EMP_DEPT

Ename	<u>Ssn</u>	Bdate	Address	Dnumber	Dname	Dmgr_ssn
-------	------------	-------	---------	---------	-------	----------

3NF Normalization

ED1

Ename	<u>Ssn</u>	Bdate	Address	Dnumber
-------	------------	-------	---------	---------

ED2

<u>Dnumber</u>	Dname	Dmgr_ssn
----------------	-------	----------

Exercise

Consider the universal relation $R = \{A, B, C, D, E, F, G, H, I, J\}$ and the set of functional dependencies:

1. $A, B \rightarrow C$
2. $A \rightarrow D, E$
3. $B \rightarrow F$
4. $F \rightarrow G, H$
5. $D \rightarrow I, J$

What is the key for R ? Decompose R into 2NF, then 3NF relations.



Normalization

- ▶ **1NF and dependency problems**
- ▶ **2NF – solves partial dependency**
- ▶ **3NF – solves indirect dependency**
- ▶ **BCNF – well-normalized relations**

TÀI LIỆU SƯU TẬP
BỞI HCMUT-CNCP

SUMMARY OF NORMAL FORMS based on Primary Keys

Summary of Normal Forms Based on Primary Keys and Corresponding Normalization

Normal Form	Test	Remedy (Normalization)
First (1NF)	Relation should have no multivalued attributes or nested relations.	Form new relations for each multi-valued attribute or nested relation.
Second (2NF)	For relations where primary key contains multiple attributes, no nonkey attribute should be functionally dependent on a part of the primary key.	Decompose and set up a new relation for each partial key with its dependent attribute(s). Make sure to keep a relation with the original primary key and any attributes that are fully functionally dependent on it.
Third (3NF)	Relation should not have a nonkey attribute functionally determined by another nonkey attribute (or by a set of nonkey attributes). That is, there should be no transitive dependency of a nonkey attribute on the primary key.	Decompose and set up a relation that includes the nonkey attribute(s) that functionally determine(s) other nonkey attribute(s).

BCNF


- ▶ A relational schema R is in Boyce–Codd normal form if and only if for every one of its dependencies $X \rightarrow Y$, at least one of the following conditions hold:
- ▶ $X \rightarrow Y$ is a trivial functional dependency ($Y \subseteq X$),
- ▶ X is a superkey for schema R .

TÀI LIỆU SƯU TẬP
BỞI HCMUT-CNCP

BCNF


(a)

LOTS1A



BCNF Normalization


LOTS1AX



LOTS1AY



(b)



Boyce-Codd normal form. (a) BCNF normalization of LOTS1A with the functional dependency FD2 being lost in the decomposition. (b) A schematic relation with FDs; it is in 3NF, but not in BCNF.

BCNF

----- R (A, B, C, D, F) -----

A \rightarrow BCDF
BF \rightarrow ACD
D \rightarrow F

----- R1 (A, B, C, D) -----

A \rightarrow BCD

R2 (D, F)

D \rightarrow F

A and **BF** are **candidate keys**
A, B, F are the **prime** attributes
C and **D** are **non-prime** attributes.

R is in 3NF but $D \rightarrow F$ violates BCNF

R1 & R2 are in BCNF

BCNF

- ▶ TEACH (Student, Course, Instructor)
- ▶ **{student, course} is a candidate key for this relation**

FD1: {Student, Course} → Instructor
FD2:¹² Instructor → Course

TEACH

Student	Course	Instructor
Narayan	Database	Mark
Smith	Database	Navathe
Smith	Operating Systems	Ammar
Smith	Theory	Schulman
Wallace	Database	Mark
Wallace	Operating Systems	Ahamad
Wong	Database	Omiecinski
Zelaya	Database	Navathe
Narayan	Operating Systems	Ammar

BCNF

- ▶ – Find the FD $X \rightarrow Y$ in Q that violates BCNF
- ▶ – Replace Q by two relations with schemas $(Q-Y)$ and (X,Y) .
- ▶ TEACH relation is decomposed into:
 $T1(\underline{\text{instructor}}, \text{course})$
 $T2(\underline{\text{instructor}}, \underline{\text{student}})$

Another Example

- ▶ R (A, B, C, D) with keys A and BC
 - ▶ $A \rightarrow BCD$
 - ▶ $BC \rightarrow AD$
 - ▶ $D \rightarrow B$
- ▶ $D \rightarrow B \rightarrow$ violate BCNF because D is not a super key

How to do?

$R \rightarrow R_1$ and R_2 with

$R_1 (\underline{D}, B)$

$R_2 (\underline{A}, D, C)$

Contents

- 1 Introduction
- 2 Functional dependencies
- 3 Normalization

TÀI LIỆU SƯU TẬP
BỞI HCMUT-CNCP



TÀI LIỆU SƯU TẬP
BỞI HCMUT-CNCP



Exercise

Consider the universal relation $R = \{A, B, C, D, E, F, G, H, I, J\}$ and the set of functional dependencies:

- 1) $A, B \rightarrow C$
- 2) $B, D \rightarrow E, F$
- 3) $A, D \rightarrow G, H$
- 4) $A \rightarrow I$
- 5) $H \rightarrow J$

Decompose R into 2NF, then 3NF relations.



Exercise

- ▶ Consider the relation:

BOOK (Book_Name, Author, Edition, Year)

- ▶ Based on a common-sense understanding of the data, what are the possible candidate keys of this relation?

Book_Name	Author	Edition	Copyright_Year
DB_fundamentals	Navathe	4	2004
DB_fundamentals	Elmasri	4	2004
DB_fundamentals	Elmasri	5	2007
DB_fundamentals	Navathe	5	2007

Exercise

Trường ĐH Bách Khoa TP HCM
PHIẾU ĐIỂM - Học kỳ 1 năm 2008

- ▶ *MSSV:* 505000000
- ▶ *Tên sinh viên:* Nguyễn Văn A
- ▶ *Địa chỉ:* KTX Bách Khoa
- ▶ *Khoa:* Khoa học & kỹ thuật máy tính

Mã môn học	Tên môn học	Nhóm	Số TC	Điểm KT	Điểm thi	Điểm tổng kết
501040	CTDL>	TN	3	7	8	7.8
501045	CSDL	2C	3	6.5	8.5	8.1

- ▶ *Ghi chú:* Tùy từng môn học sẽ có hệ số của điểm kiểm tra và điểm thi khác nhau. Điểm tổng kết được tính dựa trên điểm KT, điểm thi và các hệ số này.



Key finding algorithms

Extended part

Key and super key

- ▶ **Superkey** of R: A set of attributes **SK** of **R** such that no two tuples in any valid relation instance $r(R)$ will have the same value for SK. That is, for any distinct tuples t_1 and t_2 in $r(R)$, $t_1[SK] \neq t_2[SK]$
- ▶ **Key** of R: A "**minimal**" **superkey**; that is, a superkey **K** such that removal of any attribute from **K** results in a set of attributes that is not a superkey
- ▶ If **K** is a **key** of R, then **K functionally determines all attributes** in R

Key-finding algorithm (1)

By Elmasri and Navathe

Input: *A relation R and a set of functional dependencies F on the attributes of R .*

Output: *a key K of R*

1. Set K to contain all attributes in R
2. For each attribute A in K {
compute $(K - A)^+$ with respect to F ;
if $(K - A)^+$ contains all attributes in R , then
set $K := K - \{A\}$
};

Key-finding algorithm (1)

By Elmasri and Navathe

- ▶ In algorithm (1), we start by setting K to all the attributes of R ; we then remove one attribute at a time and check whether the remaining attributes still form a superkey.
- ▶ The algorithm (1) determines only **one key** out of the possible candidate keys for R ; the key returned depends on the order in which attributes are removed from R in step 2.

TÀI LIỆU SƯU TẬP
BỞI HCMUT-CNCP

Key-finding algorithm (2)

By Hossein Saiedian & Thomas Spencer

Input: A relation R and a set of functional dependencies F on the attributes of R .

Output: all candidate keys of R

Let:

- ▶ U contain **all** attributes of R
- ▶ U_l contain attributes of R that occur **only** on the **left-hand side** of FDs in F
- ▶ U_r contain attributes of R that occur **only** on the **right-hand side** of FDs in F
- ▶ U_b contain attributes of R that occur on **both sides** of FDs in F

Note:

- ▶ $U_l \cap U_r = \emptyset$, $U_l \cap U_b = \emptyset$ and $U_r \cap U_b = \emptyset$
- ▶ $U_l \cup U_r \cup U_b = U$
- ▶ For every attribute $A \in U$, if $A \in U_l$, then A **must be** part of every candidate key of R .
- ▶ For every attribute $A \in U$, if $A \in U_r$, then A will **not** be part of any candidate key of R .

Key-finding algorithm (2)

By Hossein Saiedian & Thomas Spencer

Input: A relation R and a set of functional dependencies F on the attributes of R .

Output: all candidate keys of R

1. Determine U_l , U_r and U_b
2. If $U_{l\Box}^+ = U$ under F , then U_l forms the only key of R and the algorithm stops here.
Else: move to step 3 // $U_{l\Box}^+ \neq U$ under F
3. Consider every subsets U_{bi} of U_b : $U_{bi} \subset U_b$
For each U_{bi} , if $(U_l \cup U_{bi})^+ = U$ under F , then $K_i = (U_l \cup U_{bi})$ is a candidate key of R (*)

(*) If $K_i = (U_l \cup U_{bi})$ is a candidate key of R , then we need not to check $U_{bj} \subset U_b$ where $U_{bi} \subset U_{bj}$

Key-finding algorithm (2)

By Hossein Saiedian & Thomas Spencer

- ▶ A simple categorization of attributes into the sets U_l , U_r and U_b allows to distinguish between those attributes that will participate in the candidate keys of a relational database schema and those that do not.
- ▶ The algorithm (2) finds all candidate keys.

TÀI LIỆU SƯU TẬP
BỞI HCMUT-CNCP

Exercise 1

Consider the universal relation $R = \{A, B, C, D, E, F\}$ and the set of functional dependencies:

- 1) $A \rightarrow B$
- 2) $C, D \rightarrow A$
- 3) $B, C \rightarrow D$
- 4) $A, E \rightarrow F$
- 5) $C, E \rightarrow D$

What is the key for R ?



Exercise 2

Consider the universal relation $R = \{A, B, C, D, E, F\}$ and the set of functional dependencies:

- 1) $A, D \rightarrow B$
- 2) $A, B \rightarrow E$
- 3) $C \rightarrow D$
- 4) $B \rightarrow C$
- 5) $A, C \rightarrow F$



What is the key for R ? Decompose R into 2NF, then 3NF relations.

Exercise 3

Consider the universal relation $R = \{A, B, C, D, E, F\}$ and the set of functional dependencies:

- 1) $A \rightarrow B$
- 2) $C \rightarrow A, D$
- 3) $A, F \rightarrow C, E$

What is the key for R ? Decompose R into 2NF, 3NF, and BCNF relations.