Calculating Metrics from Raw Data

0:29/9:12

Introduction

A raw data export from a test management tool is just a wall of numbers until you apply the right formulas. This reading walks you through how to use filters and simple calculations in Microsoft Excel to turn that raw data into two key metrics: Pass Rate and Defect Density. You will work through a sample dataset with two features—Feature A and Feature B—and finish with a clear, side-by-side comparison that tells the real story of quality.


What Your Raw Data Looks Like

We open the .csv file in Microsoft Excel. The file contains approximately 150 rows and four columns:

Column	What It Contains
Test Case ID	A unique identifier for each test
Feature Area	The feature the test belongs to, Feature A or Feature B

Status	The result of the test: Pass, Fail, or Blocked
Defect ID	A linked bug identifier, present only when a test failed

Right now, all 150 rows are visible at once. Before you can calculate anything, you need to isolate the data for one feature at a time. Filters are the fastest way to do this.



	A	B	C	D	E	F	G	H
1	**Test ID**	**Feature**	**Status**	**Defect ID**				
2	TC-001	Checkout	Pass					
3	TC-002	Checkout	Pass					
4	TC-003	Checkout	Pass					
5	TC-004	Checkout	Pass					
6	TC-005	Checkout	Pass					
7	TC-006	Checkout	Pass					
8	TC-007	Checkout	Pass					
9	TC-008	Checkout	Pass					
10	TC-009	Checkout	Pass					
11	TC-010	Checkout	Pass					
12	TC-011	Checkout	Pass					
13	TC-012	Checkout	Pass					
14	TC-013	Checkout	Pass					
15	TC-014	Checkout	Pass					


Sample_Test_Data

The image shows a dark-themed spreadsheet grid containing fourteen visible rows of test data. The table is structured into four main columns: Test ID, Feature, Status, and Defect ID.

Setting Up Your Filters

Step 1: Turn on column filters.


Select the header row (Row 1). Go to the Data tab in the Excel ribbon and select Filter. Dropdown arrows will appear next to each column header.



Long Alt Text: The image shows a dark-themed spreadsheet table containing fourteen visible rows of test data across four columns: Test ID, Feature, Status, and Defect ID. A filter dropdown menu is expanded directly over the Feature column header. Inside the menu, a list of feature names with checkboxes is visible, including options like "Task Creation", "Reporting Dashboard", and "Checkout", with "(Select All)" enabled at the top.

Step 2: Isolate Feature A (Checkout).

Select the dropdown arrow on the Feature Area column. Uncheck Select All, then check only Checkout. Select OK. The sheet now displays only the rows for Checkout.



The image displays a dark-themed spreadsheet table filtering test case data. The table consists of four main columns: Test ID, Feature, Status, and Defect ID. A filter dropdown menu is open over the Feature column header, showing that only the


Checkout option is selected from the list of features (with options like "(Select All)", "Task Creation", and "Reporting Dashboard" present).

Calculating Feature A's Pass Rate

Step 3: Count the executed tests.

Highlight all the visible Feature A rows by selecting the first row number and dragging to the last. Look at the Status Bar at the bottom of the Excel window. It displays a Count value, which is your total number of executed tests for Feature A.

Note this number in an empty cell. For example, in cell G2, type Executed Tests, and in H2, enter the count you read from the Status Bar.



	A	B	C	D
1	Test ID	Feature	Status	Defect ID
2	TC-001	Checkout	Pass	
3	TC-002	Checkout	Pass	
4	TC-003	Checkout	Pass	
5	TC-004	Checkout	Pass	
6	TC-005	Checkout	Pass	
7	TC-006	Checkout	Pass	
8	TC-007	Checkout	Pass	
9	TC-008	Checkout	Pass	
10	TC-009	Checkout	Pass	
11	TC-010	Checkout	Pass	
12	TC-011	Checkout	Pass	
13	TC-012	Checkout	Pass	
14	TC-013	Checkout	Pass	
15	TC-014	Checkout	Pass	

The image displays a spreadsheet interface showing a dataset of test cases organized within a grid layout. The table contains four active columns labeled A (Test ID), B (Feature), C (Status), and D (Defect ID), followed by unpopulated grid columns extending from E through H.

Step 4: Count the passed tests.

With the Feature Area filter still set to Feature A, open the Status column dropdown. Uncheck Select All, then check only Pass. Select OK.


Highlight the visible rows again and read the new Count from the Status Bar. Note this number in an empty cell—for example, G3 labeled Passed Tests and H3 for the value.

Step 5: Enter the Pass Rate formula: Passed_Tests / Total_Executed_Tests

Clear the Status filter (leave the Feature Area filter on Feature A). In an empty cell—for example, H4—enter the following formula, referencing your two noted cells:

Select cell H4, go to the Home tab, and apply the Percentage format. Your Pass Rate for Feature A will display as a percentage.

Label cell G4 as Pass Rate.



The image shows a spreadsheet interface containing test case data along with a summary area for pass rate calculation. The main table on the left lists fourteen sequential test cases (TC-001 through TC-014) in the Test ID column, with "Checkout" under Feature, "Pass" under Status, and empty entries under Defect ID. To the right of the main dataset, three summary cells are populated: cell H2 contains the total test count of 100, cell H3 displays the passed test count of 75, and cell H4 displays the calculated pass rate as 75%.

Calculating Feature A's Defect Density

Step 6: Count the defects.

Clear the Status filter so all Feature A rows are visible again. Open the Defect ID column dropdown. Uncheck (Blanks) and select OK. This keeps only the rows where a Defect ID has been logged—in other words, the tests that were linked to a confirmed bug.


Highlight the visible rows and read the Count from the Status Bar. Note this number in an empty cell—for example, G5 labeled Total Defects and H5 for the value.

Clear the Defect ID filter when you are done.

Step 7: Enter the Defect Density formula: Total_Defects / Total_Executed_Tests

In an empty cell—for example, H6—enter the Defect Density formula, referencing your defect count and executed tests count:

Leave the result as a decimal; do not format it as a percentage. Defect Density is a ratio, not a percentage. Label cell G6 Defect Density.



	A	B	C	D	G	H	I
1	**Test ID**	**Feature**	**Status**	**Defect ID**			
2	TC-001	Checkout	Pass		Executed Tests	100	
3	TC-002	Checkout	Pass		Passed Tests	75	
4	TC-003	Checkout	Pass		Pass Rate	**75%**	
5	TC-004	Checkout	Pass		Total Defects	20	
6	TC-005	Checkout	Pass		Defect Density	0.2	
7	TC-006	Checkout	Pass				
8	TC-007	Checkout	Pass		Summary		
9	TC-008	Checkout	Pass		Feature	Pass Rate	Defect Density
10	TC-009	Checkout	Pass		Checkout	0.75	0.2
11	TC-010	Checkout	Pass				
12	TC-011	Checkout	Pass				
13	TC-012	Checkout	Pass				
14	TC-013	Checkout	Pass				
15	TC-014	Checkout	Pass				
16	TC-015	Checkout	Pass				
17	TC-016	Checkout	Pass				
18	TC-017	Checkout	Pass				
19	TC-018	Checkout	Pass				

The image shows a dark-themed spreadsheet displaying test execution metrics and summary tables. On the left side, a data table lists individual test cases with columns for Test ID (TC-001 through TC-014), Feature ("Checkout"), Status ("Pass"), and Defect ID. To the right, a set of summary tables details metrics: Test Metrics Section: Lists Executed Tests (100), Passed Tests (75), Pass Rate (75%), Total Defects (20), and Defect Density (0.2). Summary Table Below: Contains column headers for Feature, Pass Rate, and Defect Density, with a populated row for Checkout showing a Pass Rate of 75% and a Defect Density of 0.2.


Repeating the Process for Feature B

Clear all filters. Open the Feature Area dropdown and filter to Feature B only. Repeat Steps 3 through 7 for Feature B, noting all values in a new set of cells.

Once you have both sets of results, build a small summary table in a few empty cells:

Feature	Pass Rate	Defect Density
Feature A		
Feature B		

Fill in your calculated values for both features.



	A	B	C	D	G	H	I
1	**Test ID**	**Feature**	**Status**	**Defect ID**			
2	TC-001	Checkout	Pass		Executed Tests	100	
3	TC-002	Checkout	Pass		Passed Tests	75	
4	TC-003	Checkout	Pass		Pass Rate	**75%**	
5	TC-004	Checkout	Pass		Total Defects	20	
6	TC-005	Checkout	Pass		Defect Density	0.2	
7	TC-006	Checkout	Pass				
8	TC-007	Checkout	Pass		**Summary**		
9	TC-008	Checkout	Pass		**Feature**	**Pass Rate**	**Defect Density**
10	TC-009	Checkout	Pass		Checkout	0.75	0.2
11	TC-010	Checkout	Pass		Profile	96%	0.04
12	TC-011	Checkout	Pass				
13	TC-012	Checkout	Pass				
14	TC-013	Checkout	Pass				
15	TC-014	Checkout	Pass				
16	TC-015	Checkout	Pass				
17	TC-016	Checkout	Pass				
18	TC-017	Checkout	Pass				
19	TC-018	Checkout	Pass				

The image shows a light-themed spreadsheet interface containing test case data alongside summary metrics tables. On the left, a main table displays sequential test case rows (TC-001 through TC-014) with columns for Test ID, Feature ("Checkout"), Status ("Pass"), and Defect ID.

Reading the Story in the Numbers

With both features calculated, the comparison table tells you far more than a raw spreadsheet ever could.

The Pass Rate gives you a quick read on overall stability how many tests passed relative to how many ran. But the Defect Density is where the real signal lives. A feature with a high defect density is fragile relative to its size, regardless of what the pass rate says.

Brace yourself, because this is the insight that often surprises people: A feature can have a seemingly acceptable pass rate and still carry a dangerously high defect density. That combination means the feature is full of concentrated bugs, and it is a stronger argument for delaying a release than a low pass rate alone.

When a Product Owner is pushing to ship a feature because its pass rate looks acceptable, showing them the defect density gives you the data-backed evidence to make the case for another round of bug fixing. This is how you use metrics to protect the product and the people who use it.

Key Considerations

The Status Bar must reflect only filtered rows. Always highlight the rows after applying your filter. If you highlight before filtering, the Status Bar may include hidden rows in its count, giving you an incorrect total.

Defect Density is a ratio, not a percentage. If your result is 0.20, do not format it as a percentage. Formatting it as 20% changes its meaning and will confuse stakeholders who are familiar with the metric.

Use the same denominator for both formulas. Both Pass Rate and Defect Density use the total number of executed tests as the denominator. Keep this value consistent across both calculations for the same feature.

Summary

By applying filters and two straightforward formulas in Microsoft Excel, you can transform a raw test export into a clear, side-by-side comparison of feature stability. Pass Rate tells you how well a feature performed. Defect Density tells you how concentrated the bugs are relative to the feature's size. Together, these two numbers give you the quantitative evidence you need to move from a gut feeling to a data-backed quality assessment.