

Find the Errors in the below code if exists? Correct the errors and display the output.

```
#include<iostream>
using namespace std;
int main()
{
    float var1 = 2.6;
    const float* const p = &var1;
    *p = 5.9;
    cout << "var1: " << var1 << endl;
    cout << "p: " << *p << endl;

    int numbers[] = { 70, 20, 60, 40, 50 };
    cout << "The array is : ";
    cout << numbers << endl;
    cout << &numbers << endl;
    cout << numbers(1) << endl;
    cout << (*(numbers+1)*2) << endl;
    system("pause");
    return 0;
}
```

What is * called in pointers? Why we use it and what's the benefit of using * in pointers?

Find the Errors in the below code if exists? Correct the errors and display the output.

```
#include<iostream>
using namespace std;
short main()
{
    double var1 = 2.6;
    double * const p = &var1;
    *p = 5.9;
    cout << "var1: " << var1 << endl;
    cout << "p: " << *p << endl;

    int numbers[] = { 70, 20, 60, 40, 50 };
    cout << "The array is : ";
    cout << numbers << endl;
    cout << &numbers[0] << endl;
    cout << (*(numbers+1)+*(numbers+2))<<endl;
    system("pause");
    return 0;
}
```

Why Dynamic variables are used in Object oriented programming? How to create or destroy these variables?