

INTRODUCTION TO CSS

ABSTRACT

This module introduces CSS, its types (inline, internal, external), and selectors with specificity. It covers key properties for backgrounds, text, fonts, borders, and the box model. Learners also explore layout techniques using display, flexbox, grid, and positioning for effective web page design.


Introduction to CSS

Significance of CSS (Cascading Style Sheet)

- **CSS** is a style sheet language used to control the **presentation** (look and layout) of web pages written in HTML.
- It defines how elements should be **displayed**, including colors, fonts, spacing, and overall layout.
- Without CSS, web pages use the **browser's default styles**, resulting in a plain and basic appearance.

- **CSS allows developers to:**
  - ✓ Create visually appealing, consistent web pages.
  - ✓ Maintain **separation of content (HTML)** and **presentation (CSS)** for better organization.
  - ✓ Reuse the same stylesheet across multiple web pages, saving time and effort.
  - ✓ Enhance accessibility and improve user experience across devices and screen sizes.

How CSS works with HTML?



How CSS Works

1. **Load HTML** – The browser first loads the web page's structure, which contains all the text, headings, and images.
2. **Parse HTML** – It then reads and understands the HTML elements on the page (like titles, paragraphs, etc.).
3. **Create DOM Tree** – The browser builds a map (a tree-like structure) showing how all the elements are connected.
4. **Load and Parse CSS** – Next, the browser loads the CSS file and reads the styles , such as colors, fonts, and layouts.
5. **Attach Styles to HTML Elements** – The browser matches each style rule to the right HTML elements in the DOM.
6. **Display the Page** – Finally, the browser combines the structure (HTML) and the style (CSS) and shows the beautifully designed page on your screen.

Imagine opening a recipe website:

- HTML gives you the **content** — the title, ingredients, and steps.
- CSS makes it **look nice** — colorful headings, clean layout, and easy-to-read text.
- The browser mixes both together and displays a clear, well-styled recipe page for you.

Structure, syntax and types of CSS

- ✓ The syntax of CSS is slightly different from that of an HTML.
- ✓ CSS uses **(curly braces { }), (colons :)** and **(semicolon ;)**.

Syntax:

```
selector
{
        property : value;
        property : value;
        |                    |
        property : value;
}
```

- **selector:** Specifies which HTML element(s) to style (e.g., tag(element), id, class, etc.).
- **property:** The aspect of the element you want to change (e.g., color, font-size).
- **value:** The specific setting for that property.

Example:

```
p {
color: blue;
text-align: center;
}
```

- ✓ **p is a selector(element).** It styles all the <**p**> element of the document with color blue and aligned the content in the center of the screen.
- ✓ **color and text-align** are **properties**, and **blue and center** are the respective property **values**.

Types of CSS

Type of CSS	Description	Where It Is Written	Syntax (Example)
1. Inline CSS	Used to style a **single HTML element** directly. It has the **highest priority**.	Inside the HTML tag using the style attribute.	Heading
2. Internal (Embedded) CSS	Used to style elements **within the same HTML page**.	Inside the <style> tag in the <head> section of the HTML document.	<head><style> p { color: red; font-size: 18px; } </style></head>
3. External CSS	Used to apply styles to **multiple web pages** using a separate .css file.	In an external stylesheet linked using the <link> tag in the <head> section.	<head><link rel="stylesheet" href="style.css"></head>*(style.css file contains CSS rules)*

Inline CSS

- An inline CSS is used to apply a unique style to a single HTML element.
- An inline CSS uses the style attribute of an HTML element.
- The following example sets the text color of the <h1> element to blue, and the text color of the <p> element to red:

Syntax
<element **style= "property-name:value; property-name:value……..**"></element>

Example:

```
<html>
<body>
    <h1 style="color:green;">A Green Heading</h1>
    <p style="color:red;">A red paragraph.</p>
</body>
</html>
```

Output:

A Green Heading

A red paragraph.

Internal Style

- An internal CSS is used to define a style for a single HTML page.
- An internal CSS is defined in the <head> section of an HTML page, within a <style> element.
- The following example sets the text color of ALL the <h1> elements (on that page) to blue, and the text color of ALL the <p> elements to purple. In addition, the page will be displayed with a "pink" background color:


Syntax

```
<head>
        <style>
                Selector{
                  property-name 1 : value;
                  property-name 2 : value;
                  |
                  |
                  property-name n : value;
                }
        </style>
 </head>
```

Example:

```
<html>
<head>
<style>
    body {background-color: pink;}
    h1{color: blue;}
    p{color: purple;}
</style>
</head>
    <body>
    <h1>This is a heading</h1>
    <p>This is a paragraph.</p>
    </body>
</html>
```

Output:



External CSS

- Styles are written in a **separate** .css **file**.
- The CSS file is linked to the HTML page using the <link> tag inside the <head> section.
- It helps keep HTML clean and allows styles to be reused across multiple pages.

<link> tag:

The <link> tag defines the relationship between the current document and an external resource.

```
Syntax: <link rel="stylesheet" href="style.css" type=”text/css”>
```

Attributes of <link> tag:

- **The “rel” Attribute :** rel is the relationship between the external file and the current file. For CSS, you use stylesheet. For example, rel="stylesheet".

- **The type Attribute :** type is the type of the document you are linking to the HTML. For CSS, it is text/css. For example, type="text/css".

- **The href Attribute :** href stands for “hypertext reference”. You use it to specify the location of the CSS file and the file name. For example, href="styles.css" if the CSS file is located in the same folder as the HTML file. Or href="folder/styles.css" if the CSS file is located on another folder.

  Note- <link> tag has rel & href is compulsory attributes

Example


style.css

```
body {background-color: pink;}
h1 {color: blue;}
p {color: purple;}
```

demo.html

```
<head>
        <link rel="stylesheet" href="style.css" type=”text/css”>
</head>
<body>
        <h1>This is a heading</h1>
        <p>This is a paragraph.</p>
</body>
```

Output:



Cascading Order

All the styles in a page will "cascade" into a new "virtual" style sheet by the following rules, where number one has the highest priority:
1. Inline style (inside an HTML element)
2. External and internal style sheets (in the head section)
3. Browser default

So, an inline style has the highest priority, and will override external and internal styles and browser defaults.

Example 1

```
<html>
<head>
<link rel="stylesheet" type="text/css" href="mystyle.css">
<style>
body {background-color: red;}
</style>
</head>
<body style="background-color: yellow">
<h1>Multiple Styles Will Cascade into One</h1>
<p>Here, the background color of the page is set with inline CSS, and also with an internal CSS, and also with
an external CSS.</p>
<p>Try experimenting by removing styles to see how the cascading stylesheets work (try removing the inline
CSS first, then the internal, then the external).</p>
</body>
</html>
```

Output:



Note: **Remove Inline CSS from <body> and observe the impact.**

Note: 1) If Internal and External CSS applied in same file then **last one** will take more priority.
2) The **!important** rule in CSS is used to add more importance to a property/value than normal. In fact, if you use the !important rule, it will override ALL previous styling rules for that specific property on that element!

Various CSS Selectors

A **CSS selector** is used to **target HTML elements** so you can **apply styles** to them.

- Select elements to style.
- Apply styles efficiently to many elements at once.
- Control which styles take priority (specificity).
- Enable dynamic effects with pseudo-classes/elements.

Selector Type	Description	Syntax	Example
Element Selector	Selects all elements of a specific type/tag. Lowest specificity (except universal).	**element**	p { color: black; }
ID Selector	Selects a single element with a specific id attribute. Very high specificity.	**#id**	#header { color: red; }
Class Selector	Selects elements with a specific class. Medium specificity.	**.class**	.menu { font-size: 16px; }
Attribute Selector	Selects elements based on an attribute or attribute value.	**[attr], [attr=value]**	[type="text"] { border: 1px solid #ccc; }
Universal Selector	Selects all elements. Lowest specificity.	*****	* { margin: 0; padding: 0; }
Descendant Selector	Selects elements that are descendants (any level) of a specified ancestor.	**ancestor descendant**	div p { color: blue; }
Child Selector	Selects elements that are direct children of a specified parent.	**parent > child**	ul > li { list-style: none; }
Grouping Selector	Groups multiple selectors and applies the same styles.	**selector1, selector2**	h1, h2, h3 { font-family: Arial; }

1) CSS Element Selector

- The element selector selects HTML elements based on the element name.

Syntax: element-name{CSS property: value; CSS property: value……}

Note: Element name can be any HTML tag name

Example:

- Here, all <p> elements on the page will be center-aligned, with a red text color:

```
<html>
<head>
<style>
p {
text-align: center;
color: blue;
}
</style>
</head>
<body>
<p>This is element selector and we have selected paragraph to provide style<p>
<p>Both paragraph will be in blue color</p>
</body>
</html>
```

Output:

This is element selector and we have selected paragraph to provide style

Both paragraph will be in blue color

2) Id Selector

- The id selector uses the id attribute of an HTML element to select a specific element.
- The id of an element is unique within a page, so the id selector is used to select one unique element!(*create problem from javascript “getElementById()”)
- To select an element with a specific id, write a **hash (#)** character, followed by the id of the element.

Syntax:

#element-id{CSS property1: value-1;CSS property2: value-2;}

Note: **An id name Must start with letter and is case sensitive.**

Example:

```
<head>
<style>
#para1 {
text-align: center;
color: green;
}
</style>
</head>
<body>
        <p id="para1">Paragraph with ID</p>
        <p>Paragraph without ID</p>
</body>
```

Output:

Paragraph with ID

Paragraph without ID

3) Class Selector

- The class selector selects HTML elements with a specific class attribute.
- To select elements with a specific class, **write a period (.) character**, followed by the class name.

Syntax:
.element-classname{ css property: value;}

Note: *A class name shouldn't start with a number!*

Example 1:

```
<head>
<style>
.center{text-align: center; color: red;}
</style>
</head>
<body>
<h1 class="center">H1 tag using class selector</h1>
<p class="center">P tag using class selector</p>
</body>
```

Output:

H1 tag using class selector


P tag using class selector

Example 2 (Combination of Element along with class)

- You can also specify that only specific HTML elements should be affected by a class.
- In this example only <p> elements with class="center" will be red and center-aligned:

```
<head>
<style>
p.center {
text-align: center;
color: red;
}
</style>
</head>
<body>
        <h1 class="center">No effect of center class</h1>
        <p class="center">Red and Center aligned</p>
        <p class="center"> Red and Center aligned</p>
</body>
```

Output:



Example 3 (Multiple class can combine with one element)

- HTML elements can also refer to more than one class.
- In this example the <p> element will be styled according to class="center" and to class="large":

```
<head>
<style>
p.center {
text-align: center;
color: red;
}
p.large {
font-size: 200%;
}
</style>
</head>
<body>
  <h1 class="center">No effect of center class</h1>
  <p class="center">Red and Center aligned</p>
  <p class="large">Large font size</p>
  <p class="center large">Effect of both center and large class</p>
</body>
```

Output:

No effect of center class

Red and Center aligned

Large font size

Effect of both center and large class

4) Universal Selector

The universal selector (*) selects all HTML elements on the page.

Syntax:

*{ css property: value;…..}

Example 1: The CSS rule below will affect every HTML element on the page:

```
<html>
<head>
<style>
* {
text-align: center;
color: brown;
}
</style>
 </head>
<body>
<h1>Universal Selector</h1>
<p>Using this</p>
<pre>Every element on the page will be affected by the style.</pre>
</body>
</html>
```

Output:

Universal Selector


Using this

Every element on the page will be affected by the style.

Example2:
By adding a css to particular element as shown below. It will override the color of p element(s).

```
<style>
* { text-align: center; color: blue; }
p{  color: red;}
</style>

<body>
<h1>Universal Selector</h1>
<p>Using this</p>
<pre>Every element on the page will be affected by the style.</pre>
</body>
```



5) Attribute selector

- It is possible to style HTML elements that have specific attributes or attribute values.
- The [attribute] selector is used to select elements with a specified attribute.
- The attribute selectors can be useful for styling forms without class or ID:

Syntax:
element-name[attribute-name= “value”]{css property: value;}

Note: Any supported attribute name along with it’s value for specific tag should be used. For Example: input[type= “text”] , a[target= “_blank”] , etc..

Example:


```
<head>
<style>
input[type=text] { width: 300px; margin-bottom: 10px; background-color: lightpink;
color:rgb(125, 73, 247);padding:10px;margin: 10px;}

input[type=button] { margin:30px;background-color: yellow;padding:20px 30px;
font-size:20px;}

a[target=_blank] {color: blueviolet;font-size: x-large;text-decoration: none;
text-transform: uppercase;}
</style>
```

```
</head>
<body>
<form name="input" action="" method="get">
Firstname:<input type="text" name="Name"> <br>
Email:<input type="email" name="Name"><br>
<input type="button" value="Submit">
</form>
<a href="#" target="_blank">Link 1</a>
<a href="#">Link 2</a>
</body>
```

Output:



CSS Combinators

✓ A combinator is something that explains the relationship between the selectors.
✓ A CSS selector can contain more than one simple selector. Between the simple selectors, we can include a combinator.

6) Descendant selector

- If some tag is nested in the other tag then nested tag is called as descendant of parent tag.
- The Descendant Selectors can be any selector having the white-space in between the elements without using any combinators. Descendant is a manner to nested anywhere within the DOM tree. This selector is used to select all the child elements of the specified tag.

Syntax:

```
element1 element2
{
css property: value;
}
```

Example:

```
<html>
 <head>
 <style>
 ul b
        {
            font-size:20px;
            color:blue;
        }
 </style>
 </head>

 <body>
 <h3>Unordered list</h3>
 <ul>
        <li><b>abc</b></li>
         <li>xyz</li>
        <b><li>pqr</li></b>
        <li><b><i>def</i></b></li>
 </ul>
 </body>
</html>
```

Output:

Unordered list

- **abc**
- xyz
- **pqr**
- ***def***

7) Child Selector (>)

- The child selector selects all elements that are the children of a specified element.
- To apply CSS, nested tag must be a direct child of previous tag.
- The operand on the left side of > is the parent and the operand on the right is the children element.

Syntax:

```
element1>element2
{
css property:value;
}
```

Example 1:

```
<html>
<head>
        <style>
                div > p {
                        color:white;
                        background: green;}
        </style>
</head>
<body>
        <div>
                <p>Child selector</p>
        </div>
      <p>This paragraph will not be styled.   </p>
      <p>
        <div>
        This paragraph will not be styled.
        </div>
      </p>
</body>
</html>
```

Output:

Child selector

This paragraph will not be styled.

This paragraph will not be styled.

8) Grouping Selector

The **Grouping Selector** allows you to **apply the same style to multiple elements at once**, saving time and reducing repetition in your CSS.

Syntax:

```
selector1, selector2, selector3 {
   property: value;
}
```

Example:

```
h1, h2, h3 {
   font-family: Arial, sans-serif;
   color: darkblue;
}
```

- This rule applies the same **font** and **color** to all <h1>, <h2>, and <h3> elements.

CSS Specificity (Priority Order)

When multiple CSS rules target the same element, the browser decides which one to apply based on **specificity** (priority):

Priority Level	Selector Type	Example
1 (Highest)	Inline Styles	Heading
2	IDs	#title { color: red; }
3	Classes, pseudo-classes, attribute selectors	.title { color: green; }, :hover, [type='text']
4 (Lowest)	Elements and pseudo-elements	h1 { color: blue; }, ::before

```
<head>
  <style>
    h1 { color: blue; }          /* Element selector */
    .main { color: green; }      /* Class selector */
    #title { color: red; }       /* ID selector */
  </style>
</head>
<h1 id="title" class="main" style="color:pink;">Welcome!</h1>
```

Rule Type	Color	Priority Level	Who Wins?
h1 { color: blue; }	Blue	Lowest (Element)	✗ Overridden
.main { color: green; }	Green	Medium (Class)	✗ Overridden
#title { color: red; }	Red	High (ID)	✗ Overridden
style="color:pink;"	Pink	Highest (Inline)	✓ **Applied**

Text Properties

These properties are used to **style, format, and control the appearance** of text on a webpage, including alignment, spacing, transformation, decoration, font type, and size.

Text Properties

Property	Description	Syntax	Possible Values
color	Sets the color of the text	color: color;	Named colors (e.g., red), HEX (#ff0000), RGB (rgb(255,0,0)), RGBA, HSL, HSLA
text-align	Aligns text inside an element	text-align: value;	left, right, center, justify, start, end
text-indent	Adds indentation to the first line	text-indent: length;	Any length (px, em, %)
text-transform	Controls text capitalization	text-transform: value;	none, capitalize, uppercase, lowercase
text-decoration	Adds decoration like underline or line-through	text-decoration: value;	none, underline, overline, line-through, underline overline
letter-spacing	Controls space between letters	letter-spacing: length;	Normal (normal), or custom spacing (px, em)
word-spacing	Controls space between words	word-spacing: length;	Normal (normal), or custom spacing (px, em)
line-height	Sets space between lines	line-height: value;	normal, number (e.g., 1.5), length (px, em), %
text-shadow	Adds shadow to text	text-shadow: h-shadow v-shadow blur color;	none or values like 2px 2px 5px gray (can add multiple shadows separated by commas)

CSS colors

- Colors are specified using predefined color names, or RGB, HSL, RGBA, HSLA values.
- Colors are specified using HEX code #rr gg bb, Simple #rgb.
- Colors are specified using RGB function: rgb(RRR, GGG, BBB)
- In CSS, a color can be specified by using a predefined color name: Orange, Red, White, Gray etc.

RGB Format: The RGB (Red, Green, Blue) format is used to define the color of an HTML element by specifying the R, G, B values range between 0 to 255. For example: RGB value of Red color is (255, 0, 0)

RGBA Format: The RGBA format is similar to the RGB, but the difference is RGBA contains A (Alpha) which specifies the transparency of elements. The value of alpha lies between 0.0 to 1.0 where 0.0. represents fully transparent and 1.0 represents not transparent.

HSL: HSL stands for Hue, Saturation, and Lightness respectively. This format uses the cylindrical coordinate system.

- Hue: Hue is the degree of the color wheel. Its value lies between 0 to 360 where 0 represents red, 120 represents green and 240 represents blue color.
- Saturation: It takes a percentage value, where 100% represents completely saturated, while 0% represents completely unsaturated (gray).
- Lightness: It takes percentage value, where 100% represents white, while 0% represents black.

Example:

```
<html>
<body>
<h2 style="color:orange;">Hello World!</h2>
<h3 style="color: hsla(120, 100%, 30%, 0.5);">Be kind</h3>
<h4 style="color:rgb(25,140,230);">Keep Smiling</h4>
<h5 style="color: #df0fdd;">Be Happy</h5>
</body>
</html>
```

Output:

Hello World!

Be kind

Keep Smiling

Be Happy

Understanding Of color selection

Format	Example	Full Form / Meaning	Value Range	Key Points
HEX (6 digits)	#ffffff	Hexadecimal RGB value	00 → ff	Each pair = Red, Green, Blue; common format for web colors
HEX (3 digits)	#fff	Short form of HEX	0 → f	Shorthand for 6-digit HEX (#fff = #ffffff)
RGB	rgb(255, 255, 255)	Red, Green, Blue	0 → 255	Easy to visualize and edit color intensities
RGBA	rgba(255, 0, 0, 0.5)	Red, Green, Blue, Alpha	0 → 255 (RGB), 0 → 1 (Alpha)	"A" controls transparency (1 = opaque, 0 = fully transparent)

Combine Example of all text properties

Using mentioned classes along with group of properties

- **.underline** → blue, left-aligned, capitalized, indented, spaced letters/words, with shadow.
- **.overline** → green, centered, uppercase, spaced letters/words, with shadow.
- **.line-through** → red, right-aligned, lowercase, spaced letters/words, with shadow.
- **.combined** → purple, justified, capitalized, combined underline + overline, letter & word spacing, shadow.

```
<head>
  <title>CSS Text Properties Example</title>
  <style>
    body {line-height: 1.6}


    /* Underline text */
    .underline {
      text-decoration: underline; color: blue; text-align: left;
      text-transform: capitalize; text-indent: 30px;
      letter-spacing: 2px; word-spacing: 5px;
      text-shadow: 2px 2px 3px gray;
    }
    /* Overline text */
    .overline {
      text-decoration: overline; color: green; text-align: center;
      text-transform: uppercase; text-indent: 0px;
      letter-spacing: 1px;word-spacing: 3px;
      text-shadow: 1px 1px 2px black;
    }
```

```
      /* Line-through text */
      .line-through {
         text-decoration: line-through; color: red; text-align: right;
         text-transform: lowercase; text-indent: 0px;
         letter-spacing: 1px;  word-spacing: 2px;
         text-shadow: 1px 1px 3px gray;
      }

      /* Combined text-decoration */
      .combined {
         text-decoration: underline overline;
         color: purple; text-align: justify;
         text-transform: capitalize; text-indent: 40px;
         letter-spacing: 3px; word-spacing: 6px;
         text-shadow: 3px 3px 5px gray;
      }
   </style>
</head>
<body>

<h2>CSS Text Properties Demo</h2>
<p class="underline">
This text demonstrates <b>underline</b> with all other text properties applied.
</p>

<p class="overline">
This text demonstrates <b>overline</b> with all other text properties applied.
</p>
<p class="line-through">
This text demonstrates <b>line-through</b> with all other text properties applied.
</p>
<p class="combined">
This text demonstrates <b>combined underline + overline</b> with all other text properties
applied.
</p>
</body>
```



Note:
Use left / right if your site is **single-language** and fixed layout.
Use start / end for **multilingual, adaptive layouts** — it ensures your design **works for LTR and RTL automatically**.

Font Properties

Property	Description	Syntax	Example	Possible Values
font-family	Specifies the font type	font-family: "FontName", fallback;	font-family: "Arial", sans-serif;	Any font name: "Arial", "Times New Roman", "Courier New", generic families: serif, sans-serif, monospace, cursive, fantasy
font-size	Sets the font size	font-size: size;	font-size: 20px;	Length units: px, em, rem, %; Keywords: xx-small, x-small, small, medium, large, x-large, xx-large, smaller, larger
font-style	Defines style of text	font-style: value;	font-style: italic;	normal, italic
font-weight	Sets font thickness	font-weight: value;	font-weight: bold;	normal, bold, bolder, lighter, 100, 200, 300, 400, 500, 600, 700, 800, 900
font-variant	Displays text in small-caps	font-variant: value;	font-variant: small-caps;	normal, small-caps

Font families:

In CSS, we use the font-family property to specify the font of a text.
Note: If the font name is more than one word, it must be in quotation marks, like: "Times New Roman".

1. **Serif fonts** have a small stroke at the edges of each letter. They create a sense of formality and elegance. Serif fonts include small lines at the end of characters.
Example of serif: Times new roman, Georgia etc.

2. **Sans-serif fonts** have clean lines (no small strokes attached). They create a modern and minimalistic look. A sans-serif font doesn't include the small lines at the end of characters.
Example of Sans-serif: Arial, Verdana etc.

3. **Monospace fonts** - here all the letters have the same fixed width. They create a mechanical look.

4. **Cursive fonts** imitate human handwriting.

5. **Fantasy fonts** are decorative/playful fonts.



Generic Font Family	Examples of Font Names
Serif	Times New Roman
	Georgia
	Garamond
Sans-serif	Arial
	Verdana
	Helvetica
Monospace	Courier New
	Lucida Console
	Monaco
Cursive	Brush Script MT
	Lucida Handwriting
Fantasy	Copperplate
	Papyrus

Example on Font- Property

```
<head>
   <title>CSS Font Properties Demo</title>
   <style>
      /* Individual font properties */
      .font1 {
         font-family: "Times New Roman", serif;
         font-style: italic;        /* normal, italic*/
         font-size: 25px;           /* Size in pixels */
         font-weight: bold;         /* normal, bold, 100-900 */
         font-variant: small-caps;  /* normal, small-caps */
      }
   </style>
</head>
<body>

<p class="font1">
This paragraph demonstrates <b>individual font properties:</b> Times New Roman, italic,
bold, small-caps, 25px size.
</p>

</body>
```

THIS PARAGRAPH DEMONSTRATES INDIVIDUAL FONT PROPERTIES: TIMES NEW ROMAN, ITALIC, BOLD, SMALL-CAPS, 25PX SIZE.

Google Fonts

Why Use Google Fonts?

1. **Variety of Fonts** – Access hundreds of high-quality, free fonts beyond standard system fonts.
2. **Cross-Browser & Cross-Device** – Fonts are hosted online, so they render consistently across browsers and devices.
3. **Performance Optimized** – Google Fonts servers are fast and optimized for web use.
4. **Easy to Use** – Simple embed methods (<link> or @import).
5. **Customizable Weights & Styles** – Choose different weights (400, 600, 700) and styles (italic, normal).


How to Embed Google Fonts

Method 1: Using <link> tag (Recommended)

1. Go to Google Fonts.
2. Search and select your desired font (e.g., **Pacifico**).
3. Choose the styles/weights you need (e.g., 400).



4. Copy the <link> tag under **Embed** section:




<link href="https://fonts.googleapis.com/css2?family=Pacifico&display=swap" rel="stylesheet">

5. Paste it inside the <head> of your HTML file.
6. Apply the font in CSS: or copy full CSS from there.
   body {font-family: "Pacifico";}

Method 2: Using @import in CSS

1. Go to Google Fonts and select your font.



2. Copy the @import code:

   @import url('https://fonts.googleapis.com/css2?family=Pacifico&display=swap');

3. Paste it **at the top of your CSS file**, **before other CSS rules**.
4. Use the font in CSS:

```
body { font-family: "Pacifico"; }
```

Example:
font_example.html

```
<head>
<link href="https://fonts.googleapis.com/css2?family=Pacifico&display=swap"
rel="stylesheet">
<link rel="stylesheet" href="style.css">
<style>
   h1{      font-family: "Pacifico";      font-weight: 400;      font-style: normal;    }
</style>
</head>
<body>
   <h1>google font Using link</h1>
   <h3>Google font using import</h3>
</body>
```

style.css

```
@import url('https://fonts.googleapis.com/css2?family=Pacifico&display=swap');
h3{
   font-family: "Pacifico";
   color: blue;
   font-size:30px;
}
```



CSS Borders

A **border** is a line that wraps around an HTML element's **content and padding**. It visually separates elements or highlights them on a web page.

Property	Description	Why to Use	Possible Values / Syntax
border-style	Defines the style of the border	To give different visual effects like solid, dashed, dotted, etc.	none, solid, dashed, dotted, double
border-idth	Sets the thickness of the border	To adjust border size	length (px, em, rem)
border-color	Sets the color of the border	To visually match design or highlight elements	Named colors (red), hex (#FF0000), RGB (rgb(255,0,0))
border horthand)	Combines style, width, color in one line	To quickly define a complete border	border: 2px solid red;
border-top	Sets border properties for the top side	To style only the top edge	border-top: 3px dashed blue;
border-right	Sets border properties for the right side	To style only the right edge	border-right: 2px solid green;
border-ottom	Sets border properties for the bottom side	To style only the bottom edge	border-bottom: 4px dotted orange;
border-left	Sets border properties for the left side	To style only the left edge	border-left: 5px double purple;
border-adius	Rounds the corners of an element's border box.	To make elements look smoother or create circular shapes.	border-radius: 10px;

Note:


- ✓ The "border-color" property does not work if it is used alone. Use the "border-style" property to set the borders first.
- ✓ If border-color is not set, it inherits the color of the element.

Border Example

```
<!DOCTYPE html>
<html>
<head>
<style>
p.one {
  border-style: solid;
  border-color: red;
  border-width:5px;
}
```

```
p.two {
  border-style: solid double;
  border-color: green red;
  border-width:10px;
}
p.three {
  border-style: dotted solid dashed double;
  border-color: blue red green orange;
  border-width:7px;
}
p.four {
  border:9px double purple;
}
p.five {
  border-top:5px dashed rgb(0, 128, 21);
}
p.six {
  border-left:6px solid red;
}
</style>
</head>
<body>
<p class="one">Solid red border with 5px width!</p>
<p class="two">Top and Bottom borders (Solid Style green color) and Left and right borders (Double style green color)</p>
<p class="three">Top - dotted blue, right - solid red, bottom - dashed green, left- double orange of 7 px width</p>
<p class="four">Border Shorthand </p>
<p class="five">Border top only </p>
<p class="six">Border left only </p>
<p><b>Note:</b> The "border-color" property does not work if it is used alone. Use the "border-style" property to set the borders first.</p>
</body>
</html>
```

Output:



Border Shorthand

- To shorten the code, it is also possible to specify all the individual border properties in one property.
- The border property is a shorthand property for the following individual border properties: border-width, border-style(required), border-color.

Syntax : border: 1px solid red

- It can be also specify all the individual border properties for just one side as shown below:

```
border-left: 6px solid red;
border-bottom: 6px solid red;
border-top: 6px solid red;
border-right: 6px solid red;
```

Note: The "border-color" property does not work if it is used alone. Use the "borderstyle" Property to set the borders first. If border-color is not set, it inherits the color of the element.

Note: border-color: red green blue yellow;
/* **red top**, **green right**, **blue bottom** and **yellow left** */

Box Properties

- All HTML elements can be considered as boxes.
- In CSS, the term "box model" is used when talking about design and layout.
- The box model allows us to add a border around elements, and to define space between elements.
- The CSS box model is essentially a box that wraps around every HTML element. It consists of: margins, borders, padding, and the actual content.

Explanation of the different parts:


Content - The content of the box, where text and images appear

Padding - Clears an area around the content. The padding is transparent

Border - A border that goes around the padding and content, & also allows setting the style, color, and width of the border.

Margin - Clears an area outside the border. The margin is transparent

The box model allows us to add a border around elements, and to define space between elements.




Property	Description	Why to Use	Possible Values / Syntax / Examples
margin	Creates **space outside** the element (outside border).	To **separate elements** on the page.	**Values:** • auto → browser calculates margin (useful for centering) • length → px, em, %, negative values allowed **Shorthand examples:** • 4 values → margin: 25px 50px 75px 100px; → top=25px, right=50px, bottom=75px, left=100px • 3 values → margin: 25px 50px 75px; → top=25px, right/left=50px, bottom=75px • 2 values → margin: 25px 50px; → top/bottom=25px, right/left=50px • 1 value → margin: 25px; → all sides=25px
padding	Creates **space inside** the element (between content & border).	To **add inner spacing** inside the element.	**Values:** • length → px, em, % **Shorthand examples:** • 4 values → padding: 25px 50px 75px 100px; → top=25px, right=50px, bottom=75px, left=100px • 3 values → padding: 25px 50px 75px; → top=25px, right/left=50px, bottom=75px • 2 values → padding: 25px 50px; → top/bottom=25px, right/left=50px • 1 value → padding: 25px; → all sides=25px
width	Specifies the **width** of an element's content area.	To **control horizontal size** of the element.	**Values:** auto, length (px, em, %),
height	Specifies the **height** of an element's content area.	To **control vertical size** of the element.	**Values:** auto, length (px, em, %),
box-sizing	Defines **how width and height are calculated** — whether padding and borders are included.	To **control layout behavior** when adding padding/borders.	**Values:** • content-box (default): width/height exclude padding & border. • border-box: width/height include padding & border.
box-shadow	Adds **shadow effects** around an element's frame.	To **add depth**, **hover effects**, or **visual highlights**.	**Syntax:** box-shadow: h-offset v-offset blur spread color; **Example:** box-shadow: 2px 2px 5px gray;

Example:


```
<html>
<body>
<p style="margin:auto; padding:50px; border:4px solid blue">
        THIS IS P1
</p>
<p style="margin:10px; padding:50px 50px; border:5px dashed red">
        THIS IS P2
</p>
<p style="margin:100px 100px; border:15px dotted green">
        THIS IS P3
</p>
<p style="margin:15px 20px 25px 30px;border:4px double purple">
        THIS IS P4
</p>
</body>
</html>
```

Output:



Example

```
<head>
<style>
.box1 {
   width: 300px;              /* width of box */
   height: 150px;             /* height of box */
   margin: 30px auto;           /* outer spacing & centered horizontally */
   padding: 20px;             /* inner spacing */
   border: 4px solid teal;      /* border around the box */
   box-sizing: content-box;      /* width/height includes content only */
   box-shadow: 5px 5px 15px gray; /* shadow around the box */
   background-color: lightyellow;
   text-align: center;
}
.box2 {
   width: 300px;
   height: 150px;
   margin: 30px auto;
   padding: 20px;
   border: 4px solid purple;
   box-sizing: border-box;       /* width/height includes content + padding + border */
   box-shadow: 5px 5px 15px gray;
   background-color: lightpink;
   text-align: center;
}
</style>
</head>
<body>
<h2>Box Properties Demonstration</h2>
<div class="box1">
   Box 1 - box-sizing: content-box<br>
   width and height include only content
</div>
<div class="box2">
   Box 2 - box-sizing: border-box<br>
   width and height include content + padding + border
</div>
</body>
```



Box-Sizing Comparison

Box 1 – content-box

- Declared size: 300×150 px
- Padding: 20 px, Border: 4 px
- Total width: 300 + 20 + 20 + 4 + 4 = 348 px
- Total height: 150 + 20 + 20 + 4 + 4 = 198 px

→ *Padding and border are added outside the content.*

Box 2 – border-box

- Declared size: 300×150 px
- Padding: 20 px, Border: 4 px
- Content width: 300 − (20 + 20 + 4 + 4) = 252 px
- Content height: 150 − (20 + 20 + 4 + 4) = 102 px

→ *Padding and border are included within the declared size.*

Box	box-sizing	Declared Size	Rendered Size	Notes
Box 1	content-box	300×150 px	348×198 px	Adds padding + border
Box 2	border-box	300×150 px	300×150 px	Includes padding + border

CSS background properties

CSS background properties are a set of properties that allow you to **control the appearance of the background** of HTML elements. This includes **color, images, repetition, position, size, attachment, and clipping**.

Why use them?

- To **enhance the visual design** of a webpage.
- To **highlight elements** with colors or images.
- To **control the layout and behavior** of background images (repeat, size, position, scroll behavior).
- To **create visually appealing effects** using shorthand or combined properties.

Property	Description	Syntax	Key Values / Notes
background-color	Sets the background color of an element	background-color: color;	Any valid color (red, #ffc0cb, rgb(255,0,0))
background-image	Sets an image as the background	background-image: url("image.jpg");	Use image URL;
background-repeat	Controls how background image repeats	background-repeat: repeat;	repeat, repeat-x, repeat-y, no-repeat default repeats if not specified
background-position	Sets the starting position of a background image	background-position: top;	top, bottom, left, right, center, x% y%
background-size	Specifies the size of the background image	background-size: auto;	auto, cover, contain, width height
background-attachment	Sets whether background scrolls with content	background-attachment: scroll;	scroll, fixed, local
background-clip	Determines how far the background extends	background-clip: border-box;	border-box, padding-box, content-box
background (shorthand)	Combines color, image, repeat, position, size, attachment	background: [color] [image] [repeat] [position]/ [size] [attachment];	Example: background: pink url("scenary.jfif") no-repeat top right cover fixed;

CSS background properties

The CSS background properties allow you to control various background effects on HTML elements. Here's a breakdown of commonly used background properties and how they work:

background-color

The background-color property specifies the background color of an element.

Example

```
<html>
<head>
<style>
h1 {background-color: rgb(25, 128, 134);}
div {background-color: #FFC0CB;}
p {background-color: #bcd;}
pre {background-color: aqua;}
</style>
</head>
<body>
<h1>CSS background-color</h1>
<div>
        This is a text inside a div element.
        <p>This paragraph has its own background color.</p>
        We are still in the div element.
        <pre>Preformatted text
        with its own
        background color
        </pre>
</div>
</body>
</html>
```

Output:

CSS background-color

This is a text inside a div element.

This paragraph has its own background color.

We are still in the div element.

Preformatted text
with its own
background color

background-image


- Sets the background image for an element
- The background-image property specifies an image to use as the background of an element.
- By default, the image is repeated so it covers the entire element.
- The background image can also be set for specific elements, like the <p> element.

Note: When using a background image, use an image that does not disturb the text.

Example:

```
<html>
<head>
<style>
body { background-image: url("scenary.jfif");}
</style>
</head>
<body>
        <h1>BACKGROUND IMAGE</h1>
        <p>By default, the image is repeated so it covers the entire element.</p>
</body>
</html>
```

Output:



Note: **background-size:100%** will fill viewport by stretching single image

background-repeat

- By default, the background-image property repeats an image both horizontally and vertically.
- Some images should be repeated only horizontally or vertically, or they will look strange.
- To repeat an image vertically, set background-repeat: repeat-y;
- To repeat an image horizontally, set background-repeat: repeat-x;
- To repeat an image only once, set background-repeat: no-repeat;

Example (repeat-x):

```
<head>
   <style>
   body {
         background-image: url("nature.jfif");
         background-repeat: repeat-X;
         }
   </style>
   </head>
   <body>
         <h1>BACKGROUND IMAGE(REPEAT-X)</h1>
          <p>THE IMAGE IS REPEATED HORIZONATLLY</p>
   </body>
   </html>
```

Output:



Example (repeat-y):

```
<head>
<style>
body {
          background-image: url("scenary.jfif");
          background-repeat: repeat-y;
         }
</style>
</head>
<body>
         <h1>BACKGROUND IMAGE(REPEAT-Y)</h1>
         <p>THE IMAGE IS REPEATED VERTICALLY</p>
</body>
```

Output:



Example (no-repeat)

```
<head><style>
body { background-image: url("scenary.jfif");
        background-repeat: no-repeat;}
</style></head>
<body>
        <h1>BACKGROUND IMAGE(no-repeat)</h1>
        <p>THE IMAGE IS REPEATED ONLY ONCE</p>
</body>
```

Output:



Shorthand

CSS also allows you to combine multiple background properties into a single shorthand declaration. This shorthand format is useful for specifying background color, image, repeat, position, and more in one line.

- **Effect:** Apply multiple properties at once for **compact code**.
- **Shorthand Properties Used Together:** background-color, background-image, background-repeat, background-position, background-size, background-attachment

Syntax:

```
background: [color] [image] [repeat] [position] / [size] [attachment];
```

Example:

```
background: lightpink url("scenary.jfif") no-repeat top right / cover fixed;
```

Note:
/ **is mandatory only** when you specify both position **and** size. If you specify just one of them, no / is needed.

background-clip

background-clip defines **how far the background (color or image)** extends **within an element's box** whether it goes under the border, stops at padding, or only fills the content area.

Value	Description	Background Covers	Visual Effect
border-box (default)	Background extends **under the border**	Border + Padding + Content	Background color/image is visible **behind the border**
padding-box	Background is painted **only inside the padding area**	Padding + Content	Background **stops before the border**
content-box	Background is painted **only behind the content**	Content only	Background **ignores border and padding** (appears smaller)

Example:

```
box1 {
        width: 400px;
        height: 200px;
        padding: 50px;
        background-size:cover;
        background-image: url("nature.jpg");
        border: 20px dotted;
        background-color: rgb(85, 75, 77); /* background color */
        background-clip:border-box;
        text-align: center;
        font-size: 18px;
    }
<div class="box1">
  This box demonstrates <br>
   background-color + background-clip + border + padding
</div>
```



If value is "content-box" then below will be the possible output.

Background **ignores border and padding** (appears smaller)



If value is "padding-box" then below will be the possible output.

Background **stops before the border**



Background-size

- background-size defines **how a background image fits or scales** inside an element.
- It controls **whether the image repeats, stretches, or maintains proportions** — very useful for responsive design and banners.

Value	Description	When to Use	Example
auto	Default — image keeps its original size	When you don't want to resize the image	background-size: auto;
cover	Scales image to **completely cover** the area (cropping if needed)	For full-screen backgrounds or banners	background-size: cover;
contain	Scales image to **fit inside** the box without cropping	When you want the full image visible	background-size: contain;
100% 100%	Stretches image to fill width and height	When exact fit is needed	background-size: 100% 100%;
width height	Manually set image size	When you want precise control	background-size: 200px 100px;

Example

```
<head>
   <title>CSS Background Properties Demo</title>
   <style>
      .box1 {
         width: 600px;
         height: 400px;
         background-size:auto;
         background-image: url("nature.jpg");
         background-color: black; /* background color */
      }
   </style>
</head>
<body>
   <div class="box1">
      This box demonstrates <br> background-size property
   </div></body>
```

background-attachment

It defines whether the background image scrolls with the page **or** stays fixed **in place.**
This helps create visual effects like *parallax scrolling* or *fixed banners*.

Value	Description	Effect / Behavior	Common Use
scroll *(default)*	Background image **moves with the page** when you scroll	Image scrolls normally along with the content	Default for most elements
fixed	Background image **stays fixed** in the same place while the content scrolls	Creates a "parallax" or fixed-banner effect	Used in headers, full-screen backgrounds

background-position

The background-position property defines **where the background image starts** inside an element.
By default, a background image starts at the **top-left corner** (0% 0%).
But you can **move or align it** anywhere center, bottom, right etc.

- **Control image placement** (not always top-left)
- **Align the image with text or layout**
- **Show a specific part** of a large image (like a logo or cropped photo)
- **Create design balance** (especially in banners or cards)
- **Combine with background-size** for perfect image alignment

Value	Description	Effect
left top	Default	Image starts at top-left corner
Center	Centers both horizontally and vertically	Image stays in the middle
top / bottom / left / right / center	Keywords for alignment	Combine as top center, bottom right, etc.

Example

```
<head>
   <title>Background Position & Attachment Example</title>
   <style>
      body {
         height: 1000px; /* just to make scrolling visible */
         background-color: lightblue; /* fallback color */
         background-image: url("nature.jpg");
         background-repeat: no-repeat;
         /*  controlling where the image appears */
         background-position: bottom right ; /* places image at bottom-right corner */
         /* controlling how it behaves during scroll */
         background-attachment: fixed; /* image stays fixed while content scrolls */

         /* scaling the image */
         background-size: cover;
      }
   </style>
</head>
<body>
   <div>
      <h1>CSS background-position + background-attachment</h1>
      <p>
         Scroll this page and notice how the background image stays in the same position
         on the screen because <b>background-attachment: fixed;</b> keeps it fixed, while
         <b>background-position: bottom right;</b> keeps the image anchored to the bottom-
right corner.
      </p>
      <p>
         Change <code>background-attachment</code> to <code>scroll</code> and reload —
         you'll see the image moves with the page instead.
      </p>
   </div>
</body>
```

Note: Change the values and observe output.

Pseudo Class And Pseudo Element

What are they and their purpose?

- **Pseudo-class:** Used to style elements based on **their state or position**. Example: hover, focus, visited link.
- **Pseudo-element:** Used to style **specific parts of an element** or insert content. Example: first letter, first line, before/after content.
- **Purpose:** Both allow you to apply **special styles** without adding extra HTML, making your CSS more powerful and dynamic.

Pseudo Elements

Pseudo-element	Description	Syntax	Example	Result / Effect
::first-line	Styles the **first line** of a block-level element.	p::first-line { property: value; }	p::first-line { color: red; font-weight: bold; }	First line of the paragraph appears red and bold.
::first-letter	Styles the **first letter** of a block-level element.	p::first-letter { property: value; }	p::first-letter { font-size: 50px; color: red; }	First letter of the paragraph becomes large and red.
::before	Inserts content **before** an element's actual content.	selector::before { content: "..."; }	p::before { content: "Note: "; color: red; }	Adds "Note:" before each paragraph.
::after	Inserts content **after** an element's actual content.	selector::after { content: "..."; }	p::after { content: "✔"; color: green; }	Adds a green checkmark after the paragraph.
::marker	Styles the **marker (bullet or number)** of list items.	li::marker { property: value; }	li::marker { color: red; font-size: 20px; }	List bullets or numbers appear red and large.
::selection	Styles the **highlighted text** selected by the user.	::selection { property: value; }	::selection { background: blueviolet; color: white; }	Selected text appears white on a blue-violet background.

A CSS pseudo-element is used to style specified parts of an element. It can be used to:

- ✓ A pseudo-element can be used to style the first letter or the first line of an element.
- ✓ The pseudo-elements can also be used to insert the content after or before an element.

Syntax

```
selector::pseudo-element {    property: value;  }
```

We have used the **double colon notation (::pseudo-element)** in the syntax.

In CSS3, the double colon replaced the single colon notation for pseudo-elements. It was an attempt from W3C to differentiate between the pseudo-elements and pseudo-classes. So, it is recommended to use **double colon notation (::pseudo-element)** instead of using single-colon notation **(:)**.

Example:

```
<head>
<style>
/* ===== FIRST LINE & FIRST LETTER ===== */
p::first-line {  color: red;  font-weight: bold;}

p::first-letter {  font-size: 50px;  color: blue;  text-decoration: underline;}

/* ===== BEFORE & AFTER ===== */
p::before {  content: " Note: ";  color: green;}

p::after {  content: "😊"; }

/* ===== MARKER ===== */
ul li::marker {  color: purple;  font-size: 40px;}

/* ===== SELECTION ===== */
::selection {  background-color: yellow;  color: red;}
</style>
</head>
<body>
<h2>CSS Pseudo-elements Example</h2>
<p>
  This is a paragraph demonstrating CSS pseudo-elements. The first letter and first line are styled differently, and extra content is added before and after the text.
</p>

<ul>
  <li>HTML</li>
  <li>CSS</li>
  <li>JavaScript</li>
</ul>

</body>
</html>
```

CSS Pseudo-elements Example

Note: This is a paragraph demonstrating CSS pseudo-elements. The first letter and first line are styled differently, and extra content is added before and after the text. 😊

- HTML
- CSS
- JavaScript