OFF-HIGHWAY & AGRICULTURE · SUPER UNIVERSAL TRACTOR OILS

AGRISTAR STOU 10W-30.

A Super Tractor Oil Universal - one oil for the engine, the transmission, the hydraulics and the wet brakes.

APPLICATION

- The lightest STOU grade - easier cold starting and lower drag
- Mixed farm fleets consolidating onto one oil
- Winter and shoulder-season work
- Tractors specified for a 10W-30 multifunctional

NOT RECOMMENDED

- × **Hydraulic systems requiring a fire-resistant or biodegradable fluid**
- × **Engines with after-treatment where a low-SAPS engine oil is specified**

BENEFITS

- Formulated for high-contamination working environments - dust, water and soil ingress
- Reduces the number of products held on site by covering multiple applications
- Maintains hydraulic response across wide seasonal temperature swings
- Protects wet brakes and final drives against chatter and glazing
- Carries 14 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

API	CG-4/SF, GL-4
ACEA	E3
Massey Ferguson	M1139, M1144, M1145
John Deere	J20C, J20D, J27
FORD NEW HOLLAND	M2C-134D, M2C-159B/C
CASE Int.	MS-1204/6/7/9
CASE New Holland	MAT 3535, 3526
New Holland	NH 410B
Caterpillar	TO-2
Allison	C-4
FORD New Holland	82009201/2/3
ZF	TE-ML 06A, 06B, 06C, 06D, 07B
Mercedes-Benz	227.1, 228.1

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Specific Gravity @ 15.6°C		**0.877**
Kinematic Viscosity @ 100°C	cSt	**10.9**

Typical values, not a specification.

PACK SIZES

20 L, 205 L, 1000 L IBC, Bulk | Other pack sizes and bulk deliveries up to 25,000 litres are available on request.

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963