OFF-HIGHWAY & AGRICULTURE · SUPER UNIVERSAL TRACTOR OILS

AGRISTAR STOU 15W-40.

A Super Tractor Oil Universal - one oil for the engine, the transmission, the hydraulics and the wet brakes.

APPLICATION

- The standard STOU fill for UK conditions
- Older, higher-hour tractors
- Summer and general-season work
- Machines specified for a 15W-40 multifunctional

NOT RECOMMENDED

- × **Hydraulic systems requiring a fire-resistant or biodegradable fluid**
- × **Engines with after-treatment where a low-SAPS engine oil is specified**

BENEFITS

- Formulated for high-contamination working environments - dust, water and soil ingress
- Reduces the number of products held on site by covering multiple applications
- Maintains hydraulic response across wide seasonal temperature swings
- Protects wet brakes and final drives against chatter and glazing
- Carries 14 industry and OEM approvals, simplifying product consolidation

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Specific Gravity @ 15.6°C		**0.894**
Kinematic Viscosity @ 100°C	cSt	**16.1**

Typical values, not a specification.

PACK SIZES

20 L, 205 L, 1000 L IBC, Bulk

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

API	CG-4/SF, GL-4
ACEA	E3
Massey Ferguson	M1139, M1144, M1145
John Deere	J20C, J27A
FORD	M2C-86B/C, M2C-134D, M2C-159B/C
CASE Int.	MS-1204/6/7/9
CASE New Holland	MAT 3535
Caterpillar	T0-2
Allison	C-4
FORD New Holland	82009201/2/3
ZF	TE-ML 06A, 06B, 06C, 06D, 07B
Mercedes-Benz	227.1
Sperry	Vickers/Eaton M2950S, I-280-S

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963