OFF-HIGHWAY & AGRICULTURE · HEAVY DUTY DIESEL ENGINE OILS

AGRISTAR UHPD 15W40.

A semi-synthetic, low-SAPS heavy-duty diesel engine oil for the latest emission-controlled agricultural and off-highway engines, giving strong soot handling and oxidation control alongside broad OEM approval coverage.

13.5 cSt	0.864	>220 °C
Viscosity @ 100°C	Specific Gravity @ 15	Flash point

APPLICATION

- Euro 5 and Euro 6 emission-controlled diesel engines
- Case New Holland, Hitachi, Isuzu, JCB, John Deere, Kobelco, Komatsu and Liebherr plant

NOT RECOMMENDED

- × **Hydraulic systems requiring a fire-resistant or biodegradable fluid**
- × **Engines with after-treatment where a low-SAPS engine oil is specified**

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Specific Gravity @ 15°C		**0.864**
Kinematic Viscosity @ 100°C	cSt	**13.5**
TBN ASTM D2896		**10.5**
Flash Point ASTM D92	°C	**>220**
Sulphated Ash ASTM D874	%	**<1.0**

Typical values, not a specification.

PACK SIZES

20 L, 205 L, 1000 L IBC, Bulk

BENEFITS

- Formulated for high-contamination working environments - dust, water and soil ingress
- Reduces the number of products held on site by covering multiple applications
- Maintains hydraulic response across wide seasonal temperature swings
- Protects wet brakes and final drives against chatter and glazing
- Carries 14 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

API	CK-4
ACEA	E11, E7, E9
JASO	DH-2
Volvo	VDS 4.5
Renault RVI	RLD-3
Mack	EO-S 4.5
Mercedes-Benz	228.31
Cummins	CES 20086
MAN	M3575
MTU	Type 2.1
Caterpillar	ECF-3
Deutz	DQC-III-10 LA

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963