OFF-HIGHWAY & AGRICULTURE · HEAVY DUTY DIESEL ENGINE OILS

# AGRISTAR ULTRA UHPD 10W40.

A full-synthetic, low-SAPS heavy-duty diesel engine oil for the latest emission-controlled off-highway engines, formulated for extended drain intervals and strong protection against bore polishing and cam wear.

| 83.1 cSt | 13.1 cSt | 0.859 | 189 °C |
|---|---|---|---|
| Viscosity @ 40°C | Viscosity @ 100°C | Specific Gravity @ 15 | Flash point |

## APPLICATION

- Euro 4, Euro 5 and Euro 6 diesel engines with DPF or SCR after-treatment
- Modern off-highway plant and equipment under severe operating conditions

### NOT RECOMMENDED

- × **Hydraulic systems requiring a fire-resistant or biodegradable fluid**
- × **Engines with after-treatment where a low-SAPS engine oil is specified**

## PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

| | |
|---|---|
| **ACEA** | E7, E8, E11, E6, E9 |
| **API** | CK-4 |
| **Mercedes-Benz** | 228.51 |
| **Volvo** | VDS 4.5 |
| **Renault RVI** | RLD-3 |
| **MACK** | EO-S 4.5 |
| **MAN** | M3477, M3271-1 |
| **CAT** | ECF-3 |
| **Cummins** | CES 20076, 20077 |
| **Deutz** | DQC III-10 LA |
| **DAF** | extended drain requirement |

## BENEFITS

- Formulated for high-contamination working environments - dust, water and soil ingress
- Reduces the number of products held on site by covering multiple applications
- Maintains hydraulic response across wide seasonal temperature swings
- Protects wet brakes and final drives against chatter and glazing
- Carries 11 industry and OEM approvals, simplifying product consolidation

## TYPICAL PROPERTIES

| PROPERTY | UNIT | TYPICAL |
|---|---|---|
| Specific Gravity @ 15°C | | **0.859** |
| Kinematic Viscosity @ 40°C | cSt | **83.1** |
| Kinematic Viscosity @ 100°C | cSt | **13.1** |
| Viscosity Index<br>ASTM D2270 | | **159** |
| Pour Point<br>ASTM D97 | °C | **-40** |
| Flash Point (closed) | °C | **189** |
| Sulphated Ash<br>ASTM D874 | % | **<1.0** |
| TBN<br>ASTM D2896 | | **10.5** |

Typical values, not a specification.

### PACK SIZES

20 L, 205 L, 1000 L IBC, Bulk

## HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

**Note:** Read and understand all precautions on container labels before using this product.

**SAR Lubricants** (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963