OFF-HIGHWAY & AGRICULTURE · UNIVERSAL TRACTOR TRANSMISSION OILS

AGRISTAR UTTO.

A Universal Tractor Transmission Oil: transmission, final drives, wet brakes, hydraulics and PTO from one tank - everything except the engine.

APPLICATION

- Tractor transmissions, final drives and wet brakes
- Hydraulic and PTO circuits sharing the transmission oil
- Telehandlers and materials handlers
- Mixed fleets needing one transmission fluid

NOT RECOMMENDED

- × **Hydraulic systems requiring a fire-resistant or biodegradable fluid**
- × **Engines with after-treatment where a low-SAPS engine oil is specified**

BENEFITS

- Formulated for high-contamination working environments - dust, water and soil ingress
- Reduces the number of products held on site by covering multiple applications
- Maintains hydraulic response across wide seasonal temperature swings
- Protects wet brakes and final drives against chatter and glazing
- Carries 14 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

API	GL-4
John Deere	JHD J20C, J20D, J21A
Ford	M2C-86B/C, M2C-134D
CASE	MS-1204, 1206, 1207, 1209
CASE New Holland	MAT 3525, 3526
New Holland	NWH 410B
Kubota	UDT
Sperry/Vickers	Eaton I-286-S, M-2950-S
Caterpillar	TO-2
Allison	C-4
Massey Ferguson	M1135, M1141 (Permatran III), M1143, M1145
Volvo	WB101 (97303)
JCMAS	HK P-041 & P-042
ZF	TE-ML 03E, 05F, 06K, 17E, 21F

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Specific Gravity @ 15.6°C		**0.883**
Kinematic Viscosity @ 100°C	cSt	**10.1**

Typical values, not a specification.

PACK SIZES

20 L, 205 L, 1000 L IBC, Bulk | Other pack sizes and bulk deliveries up to 25,000 litres are available on request.

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963