AUTOMATIC TRANSMISSION FLUIDS · MULTI-VEHICLE ATF

ATF DEXRON II.

The conventional Dexron II automatic transmission and power steering fluid - the red oil that a very large proportion of older automatics, power steering racks and hydraulic systems were designed around.

7.8 cSt	0.860	210 °C	Red
Viscosity @ 100°C	Specific Gravity @ 15.6	Flash point	Colour

APPLICATION

- Older automatic transmissions
- Power steering systems
- Plant and industrial hydraulics calling for ATF
- Allison C3/C4 and Caterpillar TO-2 applications

NOT RECOMMENDED

- × **Transmissions specifying a fluid type not listed in the approvals above**
- × **Use as a hydraulic or gear oil unless the OEM explicitly permits it**
- × **CVT or DCT transmissions**

BENEFITS

- Suitable for many types of automatic transmissions, especially older designs. Please check manufacturers' specified requirement for suitability.
- Dyed red for easy identification.
- Can be used as a power steering fluid where appropriate.
- Enhanced low temperature properties.
- Suitable for hydraulic systems where temperatures vary.

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

General Motors	Dexron II, Dexron IID, Type A, Suffix A (TASA), 1940700
Ford	Mercon, M2C-138CJ, M2C-166H
Allison	C3, C4
CAT	TO-2
Mazda	ATF-DII
Renault	Matic D2
Toyota	ATF D-II
Volvo	97325, 97340
ZF	TE-ML 05L, TE-ML 09, TE-ML 21L

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Colour ASTM D1500		**Red**
Specific Gravity @ 15.6°C		**0.860**
Kinematic Viscosity @ 100°C	cSt	**7.8**
Flash Point	°C	**210**
Copper Corrosion ASTM D130		**Nil**

Typical values, not a specification.

PACK SIZES

1 L, 5 L, 20 L, 205 L. Other pack sizes and bulk deliveries up to 25,000 litres are available on request.

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963